

US009756546B2

(12) **United States Patent**
Patini

(10) **Patent No.:** **US 9,756,546 B2**
(45) **Date of Patent:** **Sep. 5, 2017**

(54) **TARGETING COMMUNICATIONS IN A FEMTOCELL NETWORK**

(71) Applicant: **AT&T Mobility II LLC**, Atlanta, GA (US)

(72) Inventor: **Joseph Patini**, Atlanta, GA (US)

(73) Assignee: **AT&T MOBILITY II LLC**, Atlanta, GA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/190,322**

(22) Filed: **Jun. 23, 2016**

(65) **Prior Publication Data**

US 2016/0302133 A1 Oct. 13, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/719,959, filed on May 22, 2015, now Pat. No. 9,402,221, which is a continuation of application No. 14/446,593, filed on Jul. 30, 2014, now Pat. No. 9,072,028, which is a (Continued)

(51) **Int. Cl.**
H04W 40/02 (2009.01)
H04W 48/02 (2009.01)
H04W 40/24 (2009.01)
H04W 4/12 (2009.01)

(Continued)

(52) **U.S. Cl.**
CPC *H04W 40/02* (2013.01); *H04W 40/248* (2013.01); *H04W 48/02* (2013.01); *H04W 4/12* (2013.01); *H04W 8/26* (2013.01); *H04W 84/045* (2013.01)

(58) **Field of Classification Search**
CPC ... H04W 40/02; H04W 40/248; H04W 48/02; H04W 4/12; H04W 8/26; H04W 84/045
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,089,400 B1 1/2012 Fang et al.
9,072,028 B2 6/2015 Patini
2003/0011684 A1 1/2003 Narayanaswami et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 101206789 6/2008
EP 1215864 6/2002

(Continued)

OTHER PUBLICATIONS

Office Action dated Oct. 16, 2014 for U.S. Appl. No. 14/446,593, 17 pages.

(Continued)

Primary Examiner — Mohammad Anwar


(74) *Attorney, Agent, or Firm* — Amin, Turocy & Watson, LLP

(57) **ABSTRACT**

The disclosed subject matter relates to an architecture that can leverage Universal Mobile Telecommunication System (UMTS) Terrestrial Radio Access Network (UTRAN) features to facilitate more efficient or more robust communication with a femtocell network. In particular, features such as a UMTS localized common pilot channel along with various UTRAN features can enable communications to be directed to specific targets such as to a specific home nodeB (HNB) or to a specific mobile device served by the HNB, while also reducing macro network load.

20 Claims, 11 Drawing Sheets

↖ 320



Related U.S. Application Data

continuation of application No. 12/560,670, filed on Sep. 16, 2009, now Pat. No. 8,824,364.

- (51) **Int. Cl.**
H04W 8/26 (2009.01)
H04W 84/04 (2009.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2003/0034900	A1	2/2003	Han	
2005/0132115	A1	6/2005	Leach	
2006/0036967	A1	2/2006	Crichlow	
2006/0195506	A1	8/2006	Deng	
2006/0293956	A1*	12/2006	Walker G06Q 30/0212 705/14.14
2007/0013547	A1	1/2007	Boaz	
2007/0057814	A1	3/2007	Goldberg et al.	
2007/0130408	A1	6/2007	Leach	
2008/0106425	A1	5/2008	Deaver et al.	
2008/0207170	A1	8/2008	Khetawat et al.	
2009/0100492	A1	4/2009	Hicks, III et al.	
2009/0156213	A1	6/2009	Spinelli et al.	
2009/0262682	A1	10/2009	Khetawat et al.	
2009/0269063	A1	10/2009	Bernard et al.	
2009/0273462	A1	11/2009	Addy	
2009/0305671	A1	12/2009	Luft et al.	
2009/0310766	A1*	12/2009	Ye H04M 3/42017 379/142.17
2010/0013666	A1	1/2010	Panades et al.	
2010/0035647	A1	2/2010	Gholmieh et al.	
2010/0130209	A1	5/2010	Florkey et al.	
2010/0144362	A1	6/2010	Bernard et al.	
2010/0179877	A1	7/2010	Lam	
2010/0278141	A1	11/2010	Choi-Grogan et al.	
2010/0330985	A1	12/2010	Addy	
2011/0110359	A1	5/2011	Cooke et al.	
2011/0158649	A1	6/2011	Hari	
2012/0044973	A1	2/2012	Johnson et al.	

FOREIGN PATENT DOCUMENTS

JP	2003092776	3/2003
JP	2005521303	7/2005
JP	2009182620	8/2009
JP	2010520702	6/2010
WO	2007142443	12/2007
WO	2008045781	4/2008
WO	2008096418	8/2008
WO	2008108717	9/2008
WO	2008108716	12/2008
WO	2009048555	4/2009
WO	2009054058	4/2009

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Dec. 20, 2010 for PCT Application Serial No. PCT/US2010/050449, 12 pages.
 Office Action dated Nov. 16, 2011 for U.S. Appl. No. 12/560,670, 25 pages.
 Final Office Action dated May 15, 2012 for U.S. Appl. No. 12/560,670, 14 pages.
 Office Action dated Feb. 5, 2014 for U.S. Appl. No. 12/560,670, 32 pages.
 European Office Action dated Apr. 23, 2013 for European Application Serial No. 10762822.4, 5 pages.
 Office Action dated Mar. 4, 2013 for U.S. Appl. No. 12/577,856, 29 pages.
 Final Office Action dated Aug. 22, 2013 for U.S. Appl. No. 12/577,856, 27 pages.
 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Home (e)NodeB; Network aspects (Release

8) 3GPP Draft; R3.020_V090_CLEAN, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre; 650, Route Des Lucioles; F-06921 Sophia-Antipolis Cedex; France, vol. RAN WG3, No. Jeju Island; Aug. 18, 2008, Sep. 3, 2008 (Sep. 3, 2008), XP050423676 p. 21-23 p. 64.
 "3rd Generation Partnership Project; Technical Specification Group RAN; UTRAN lu-BC Interface: Service Area Broadcast Protocol (SABP) (Release 7) 3GPP Standard; 3 GPP TS 25.419, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre; 650, Route Des Lucioles; F-06921 Sophia-Antipolis Cedex; France, No. V8.0.0, Dec. 1, 2008 (Dec. 1, 2008), pp. 1-77, XP050368415 *chapter 9.2.6* *chapter 9.2.11*."
 Office Action dated Dec. 11, 2013 for U.S. Appl. No. 12/577,856, 18 pages.
 International Search Report and Written Opinion dated Jan. 25, 2011 for PCT Application Serial No. PCT/US2010/047190, 18 pgs.
 Japanese Office Action dated Feb. 27, 2014 for Japanese Application Serial No. 2012-529784, 13 pages.
 NEC, NIT DOCOMO, "discussion of and Network Interfaces and SABP in HNB-GW." R3(09)01116, RAN Working Group 3 meeting #64, San Francisco, USA, May 4-8, 2009, 4 pages.
 Ip.access Ltd., "Issues affecting SABP use for PWS with H(e)NB." 3GPP TSG RAN WG3, R3-092032, Shenzhen, P.R. China, Aug. 24-28, 2009, 3 pages.
 Global System for Mobile Communications, "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Earthquake and Tsunami Warning System Requirements and Solutions (ETWS); Solution Placeholder (Release 8)" 3GPP TR 23.828 VO.2.0 (May 2008), Valbonne—France, 2006, 24 pages.
 Japanese Office Action mailed Feb. 13, 2014 for Japanese Patent Application No. 2012-534211, 12 pages.
 Chinese Office Action dated Apr. 1, 2014 for Chinese Patent Application No. 2008-2161CN, 9 Pages.
 Final Office Action dated Apr. 15, 2014 for U.S. Appl. No. 12/577,856, 23 pages.
 Office Action dated Nov. 14, 2014 for U.S. Appl. No. 12/577,856, 37 pages.
 Japanese Office action dated Sep. 22, 2014 for Japanese Patent Application No. 2012-529784. 6 pages.
 Chinese Office Action dated Dec. 10, 2014 for Chinese Patent Application No. 2008-2161CN. 5 Pages.
 Office Action dated Jul. 29, 2015 for U.S. Appl. No. 14/719,959, 22 pages.
 Final Office Action dated Feb. 23, 2015 for U.S. Appl. No. 12/577,856, 26 pages.
 Japanese Office Action mailed Mar. 3, 2015 for Japanese Patent Application No. 2012-534211, 11 pages.
 Japanese Office action dated Apr. 14, 2015 for Japanese Patent Application No. 2012-529784, 16 pages.
 Chinese Office Action dated Jun. 25, 2015 for Chinese Patent Application No. 201080046120.5, 8 Pages.
 Office Action dated Jun. 30, 2015 for U.S. Appl. No. 12/577,856, 28 pages.
 Notice of Allowance dated Oct. 28, 2015 for U.S. Appl. No. 12/577,856, 30 pages.
 Final Office Action dated Nov. 19, 2015 for U.S. Appl. No. 14/719,959, 21 pages.
 Korean Office Action for Application No. 10-2012-7008944, dated Mar. 22, 2016, 5 pgs.
 Japanese Office Action dated Aug. 8, 2015 for Japanese Application No. 2014-173032, 4 pgs.
 European Office Action dated Mar. 7, 2016 for European Application Serial No. 10762822.4, 4 pages.
 Chinese Office Action dated Jun. 1, 2016 for Chinese Application Serial No. 201080046120.5, 11 pages.
 Japanese Office Action dated May 31, 2016 for Japanese Application Serial No. 2012-529784, 4 pgs. (with English translation).
 Non-Final Office Action for U.S. Appl. No. 15/007,535, dated Mar. 23, 2016, 25 pgs.
 Final Office Action for U.S. Appl. No. 15/007,535, dated Jul. 25, 2016, 26 pgs.

(56)

References Cited

OTHER PUBLICATIONS

Office Action for U.S. Appl. No. 15/007,535, dated Dec. 5, 2016, 21
pgs.

Office Action for U.S. Appl. No. 15/007,535, dated May 8, 2017, 22
pgs.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5




FIG. 6

700




FIG. 7

800




FIG. 8

900




FIG. 9




FIG. 10




FIG. 11

1

TARGETING COMMUNICATIONS IN A FEMTOCELL NETWORK

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 14/719,959, filed May 22, 2015, and entitled “TARGETING COMMUNICATIONS IN A FEMTOCELL NETWORK”, which is a continuation of U.S. patent application Ser. No. 14/446,593, filed Jul. 30, 2014, now issued as U.S. Pat. No. 9,072,028, and entitled “TARGETING COMMUNICATIONS IN A FEMTOCELL NETWORK”, which is a continuation of U.S. patent application Ser. No. 12/560,670, filed Sep. 16, 2009, now issued as U.S. Pat. No. 8,824,364, and entitled “TARGETING COMMUNICATIONS IN A FEMTOCELL NETWORK”, and the entireties of the aforementioned applications are hereby incorporated by reference herein.

TECHNICAL FIELD

The present application relates generally to a Universal Mobile Telecommunications System (UMTS) Terrestrial Radio Access Network (UTRAN), and more specifically to directing communications to specific recipients within a UTRAN network while reducing macro network resource utilization.

BACKGROUND

Conventional macro network platforms that provide service to mobile devices (e.g., user equipment (UE)) must contend with the mobility of the UE when providing communication services. Traditionally, messages intended for a particular UE must be broadcast to a wide area, whereby surrounding nodes of the macro network all broadcast duplicate information to ensure the intended recipient, wherever the UE is located at a given time, receives the communication. In terms of resource utilization, such flood broadcasting is very inefficient, yet often a consequence when the recipient UE potentially expects to maintain a high degree of mobility over a wide area.

In contrast to macro networks, femtocell network platforms rely upon various nodes or femtocells (e.g., home nodeBs (HNBs)). HNBs are building-based wireless access points interfaced with a wired broadband network. HNBs are generally deployed to improve indoor wireless coverage and to offload a mobility radio access network (RAN) operated by a wireless network and service provider. Thus, coverage of a HNB device is generally intended to be approximately confined within the bounds of an indoor compound such as a residential or commercial building.

Unfortunately, communication systems today—those that offer to subscribers both macro network services for coverage over a wide area and femtocell network for indoor home or office use—generally treat the femtocell network as a sub-network of the macro network and thus handle communications in a substantially identical manner. Such treatment is unfortunate because HNBs, unlike mobile phones or other UE, typically do not change location, but rather remain at a particular, known location.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a system that can leverage Universal Mobile Telecommunication System (UMTS) Ter-

2

restrial Radio Network (UTRAN) features to facilitate more efficient or robust communication with a femtocell network.

FIG. 2 illustrates a block diagram of a system that illustrates additional features, aspects, or detail in connection with communication with a femtocell network.

FIG. 3A depicts a block diagram of a system that can allocate an SAI or an URA ID as a target ID.

FIG. 3B is a block diagram that illustrates example criteria for assignment of target IDs.

FIG. 4 illustrates a block diagram of a system that can employ acknowledgement requests for further mitigating registration oscillations and/or reducing inter-system messaging.

FIG. 5 is a block diagram of a system that includes a HNB device that can facilitate more efficient or robust communication.

FIG. 6 illustrates a block diagram of a system that provides for additional features or aspects in connection with an HNB device that can facilitate more efficient or robust communication.

FIG. 7 is an exemplary flow chart of procedures that define a method for leveraging Universal Mobile Telecommunication System (UMTS) Terrestrial Radio Access Network (UTRAN) features for facilitating more efficient or robust communication with a femtocell network.

FIG. 8 is an exemplary flow chart of procedures that define a method for employing a SAI or an URA ID in connection with the target ID as well as targeting specific UE.

FIG. 9 depicts an exemplary flow chart of procedures defining a method for allocating target IDs to HNB modules and/or employing acknowledgements to further reduce system load.

FIG. 10 illustrates an example wireless communication environment with associated components that can enable operation of a femtocell enterprise network in accordance with aspects described herein.

FIG. 11 illustrates a schematic deployment of a macro cell and a femto cell for wireless coverage in accordance with aspects of the subject specification.

DETAILED DESCRIPTION

The disclosed subject matter is now described with reference to the drawings, wherein like reference numerals are used to refer to like elements throughout. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the disclosed subject matter. It may be evident, however, that the disclosed subject matter may be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form in order to facilitate describing the disclosed subject matter.

As used in this application, the terms “system,” “platform,” “component,” “service,” “framework,” “interface,” “driver,” “tier,” “layer,” “node” and the like are intended to refer to a computer-related entity or an entity related to an operational machine with one or more specific functionalities. The entities disclosed herein can be either hardware, a combination of hardware and software, software, or software in execution. For example, a component may be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, a program, and/or a computer. By way of illustration, both an application running on a server and the server can be a component. One or more components may reside within a process and/or thread of execution and a component may be

localized on one computer and/or distributed between two or more computers. These components also can execute from various computer readable media having various data structures stored thereon. The components may communicate via local and/or remote processes such as in accordance with a signal having one or more data packets (e.g., data from one component interacting with another component in a local system, distributed system, and/or across a network such as the Internet with other systems via the signal). As another example, a component can be an apparatus with specific functionality provided by mechanical parts operated by electric or electronic circuitry that is operated by software or firmware application(s) executed by a processor, wherein the processor can be internal or external to the apparatus and executes at least a part of the software or firmware application. As yet another example, a component can be an apparatus that provides specific functionality through electronic components without mechanical parts, the electronic components can include a processor therein to execute software or firmware that confers at least in part the functionality of the electronic components. An interface can include input/output (I/O) components as well as associated processor, application, and/or API components.

Furthermore, the disclosed subject matter may be implemented as a method, apparatus, or article of manufacture using standard programming and/or engineering techniques to produce software, firmware, hardware, or any combination thereof to control a computer to implement the disclosed subject matter. The term "article of manufacture" as used herein is intended to encompass a computer program accessible from any computer-readable device, carrier, or media. For example, computer readable media can include but are not limited to magnetic storage devices (e.g., hard disk, floppy disk, magnetic strips . . .), optical disks (e.g., compact disk (CD), digital versatile disk (DVD) . . .), smart cards, and flash memory devices (e.g., card, stick, key drive . . .). Additionally it should be appreciated that a carrier wave can be employed to carry computer-readable electronic data such as those used in transmitting and receiving electronic mail or in accessing a network such as the Internet or a local area network (LAN). Of course, those skilled in the art will recognize many modifications may be made to this configuration without departing from the scope or spirit of the disclosed subject matter.

Moreover, the word "exemplary" is used herein to mean serving as an example, instance, or illustration. Any aspect or design described herein as "exemplary" is not necessarily to be construed as preferred or advantageous over other aspects or designs. Rather, use of the word exemplary is intended to present concepts in a concrete fashion. As used in this application, the term "or" is intended to mean an inclusive "or" rather than an exclusive "or". That is, unless specified otherwise, or clear from context, "X employs A or B" is intended to mean any of the natural inclusive permutations. That is, if X employs A; X employs B; or X employs both A and B, then "X employs A or B" is satisfied under any of the foregoing instances. In addition, the articles "a" and "an" as used in this application and the appended claims should generally be construed to mean "one or more" unless specified otherwise or clear from context to be directed to a singular form.

Further, terms like "user equipment," "mobile station," "mobile," subscriber station," "access terminal," "terminal," "handset," and similar terminology, refer to a wireless device utilized by a subscriber or user of a wireless communication service to receive or convey data, control, voice, video, sound, gaming, or substantially any data-stream or

signaling-stream. The foregoing terms are utilized interchangeably in the subject specification and related drawings. Likewise, the terms "access point," "base station," "femto-cell," "home Node B (HNB)," and the like, are utilized interchangeably in the subject application, and refer to a wireless network component or appliance that serves and receives data, control, voice, video, sound, gaming, or substantially any data-stream or signaling-stream from a set of subscriber stations. Data and signaling streams can be packetized or frame-based flows. It is noted that in the subject specification and drawings, context or explicit distinction provides differentiation with respect to access points or base stations that serve and receive data from a mobile device in an outdoor environment, and access points or base stations that operate in a confined, primarily indoor environment overlaid in an outdoor coverage area. Data and signaling streams can be packetized or frame-based flows.

Furthermore, the terms "user," "subscriber," "customer," "consumer," and the like are employed interchangeably throughout the subject specification, unless context warrants particular distinction(s) among the terms. It should be appreciated that such terms can refer to human entities or automated components supported through artificial intelligence (e.g., a capacity to make inference based on complex mathematical formalisms) which can provide simulated vision, sound recognition and so forth.

In addition, the terms "wireless network" and "network" are used interchangeably in the subject application, when context wherein the term is utilized warrants distinction for clarity purposes such distinction is made explicit.

The subject matter disclosed herein, in one aspect thereof, comprises an architecture that can leverage Universal Mobile Telecommunication System (UMTS) Terrestrial Radio Access Network (UTRAN) features in order to facilitate more efficient or more robust communication for a femtocell network. In particular, the architecture can leverage the fact that home nodeB (HNB) devices within a femtocell network remain relatively stationary and that today's HNB devices often provide availability of a UMTS localized common pilot channel, which can operate as a dedicated channel for communications. Various other UTRAN features can also be leveraged to provide a number of benefits over conventional femtocell communications.

In accordance therewith and to other related ends, the architecture can be configured to interface to a set of HNB devices that employ an UMTS localized common pilot channel. This set of HNB device can represent all or a portion of a UTRAN network. The architecture can also be configured to receive a message originating from, or forwarded by, a messaging center or another suitable element of the host communication network. The message can include a target ID that identifies a subset of HNB devices included in the set of HNB devices. Essentially, this subset of HNB devices can constitute one or more of the HNB devices included in the set and, moreover, are specifically identified as intended recipient(s) of the message, as indicated by the target ID.

Accordingly, the architecture can thus facilitate transmission of all or a portion of the message to only the subset of HNB devices identified by the target ID. In other words, messages need not be duplicated and transmitted by surrounding nodeBs, either at the macro network level or the femtocell network level. Rather, messages can be specifically targeted only to and delivered only to a single HNB device or a collection of HNB devices based upon a logical assignment that accounts for substantially any criteria desired. Such targeted messaging can be employed in con-

nection with home/office utility management or substantially any other suitable purpose.

Referring now to the drawing, with reference initially to FIG. 1, system **100** that can leverage Universal Mobile Telecommunication System (UMTS) Terrestrial Radio Network (UTRAN) features to facilitate more efficient or robust communication employing a femtocell network is depicted. Generally, system **100** can be implemented in or coupled to a femtocell network and/or an operating support system (OSS) for a femtocell network. Regardless, system **100** can include interface component **102**. Interface component **102** can be configured to interface to set **104** of home nodeB (HNB) devices that employ UMTS localized common pilot channel **106**. In one or more aspects, set **104** can include all or a portion of HNB devices operating within a UTRAN network.

Appreciably, UMTS localized common pilot channel **106** can operate as a dedicated signal for an associated HNB that can facilitate numerous advantages in wireless communication systems. For example, HNB devices (e.g., femtocells) can provide or enhance indoor network coverage, and thus, typically, remain at a static location such as at a network subscriber's home or office. Thus, even though user equipment (UE) such as mobile phones or handsets might otherwise constantly change location, while such UE is being served by a particular HNB, the location of that UE is established and the dedicated signal provided by pilot channel **106** can be leveraged to facilitate more efficient communication, which is further detailed herein.

In accordance therewith, system **100** can also include reception component **108** that can receive message **110**. Message **110** can originate from or be forwarded by a messaging center (not shown) associated with the wireless network. Regardless, message **110** can include target ID **112**, wherein target ID **112** can identify subset **114** of HNB devices included in set **104** of HNB devices. In other words, from among all HNB devices included in set **104**, a certain subset (e.g., subset **114**) of one or more HNB devices can be identified by target ID **112**. In addition, system **100** can further include filter component **116** that can facilitate transmission of message **110** to only subset **114** of HNB devices identified by target ID **112**. For example, once HNB devices that are not identified by target ID **112** have been filtered from a target list, filter component **116** can, for example, employ interface component **102** to transmit message **110** (or suitable contents or portions) to and only to the HNB devices included in subset **114**.

Thus, specific groups or even individual network subscribers can be expressly targeted by network traffic, which can be more efficient since flood broadcasting is not necessary to reach any particular subscriber. In particular, communications (e.g., message **110**) can be delivered to specified HNB devices (e.g., subset **114**) without any extra or undue load upon other network resources such as that customarily required by conventional systems. For example, flood broadcasting can be avoided for an associated UTRAN network. Similarly, RAN resources of an associated macro network (e.g., macro network **118**) such as nodeB's or Radio Network Controllers (RNCs) need not be unnecessarily utilized. The above applies regardless of whether message **110** originates inter-system such as an associated messaging center (e.g., short message service (SMS)) or originates from a disparate source such as third party network **120** and is then forwarded to the host network for delivery to the intended recipient(s).

Accordingly, a greater degree of granularity can be attained than has previously been available on macrocell

UMTS networks or associated femtocell networks. Moreover, in addition to savings in terms of resource utilization and providing more robust granularity, the above-mentioned techniques can also be inherently more secure. For instance, since delivery of message **110** (or other communications) will generally be limited to intended or authorized recipients, there is typically little or no exposure of message **110** of any type to unintended recipients.

A further benefit of the features described herein is that inter-system registration oscillations can be avoided. For example, one problem in conventional femtocell networks is that a mobile UE served by a particular HNB device, say at the subscriber's home or office, will often attempt to reselect to the macro network that provides wide area coverage even while substantially within the coverage area of the HNB. These attempted reselections can "ping-pong" back and forth between the femtocell network and the macro network. Moreover, during such registration oscillations while the UE is attempting to register with one or the other network, the UE is generally unable to receive communications for which it is an intended recipient. However, by utilizing a designated resource at a known location, there is no need to attempt to select out of the femtocell network and/or look to the macro network. Thus, registration oscillation can be substantially mitigated.

In addition, it should be appreciated that many or all of the benefits described herein can be achieved without the necessity of additional hardware or other costly means. Rather, the features and/or solutions detailed herein can be implemented on existing communication platforms without significant modifications.

Turning now to FIG. 2, system **200** illustrates additional features, aspects, or detail in connection with communication employing a femtocell network. System **200** can include interface component **102** that can be configured to interface to set **104** of HNB devices as substantially described supra. Depicted here, however, are HNB devices **114₁-114_N**, which are intended to be only those HNB devices included in subset **114** rather than the entire set **104**. In other words, only the HNB devices referred to by target ID **112**. Thus, while four distinct HNB devices are illustrated in the diagram, it should be appreciated that N can be substantially any positive integer. Hence, subset **114** can be comprised of a single HNB device or multiple HNB devices.

As with system **100** of FIG. 1, system **200** can also include reception component **108** that can receive message **110** that includes target ID **112**, wherein target ID identifies the specific (one or more) HNB device(s) to which message **110** is intended to be directed. Message **110** can originate from third party network **120** such as, e.g., a utility company or service provider; or from inter-system network **206** such as a message center for the host communication platform providing or maintaining the femtocell network and/or macro cell network **118**.

In addition, system **200** can further include filter component **116** as substantially described above. In particular, filter component **116** can identify the intended recipient(s) of message **110** based upon target ID **112**, and employ interface component **102** to propagate message **110** only to those intended recipient(s).

In one or more aspects of the disclosed subject matter, target ID **112** can be a UTRAN Service Area Identifier (SAI, which is illustrated as "Case 1" and denoted by reference numeral **202**). SAI is defined in the 3GPP technical specifications, which provides unified telecommunications standards. The June 2009 3GPP technical specification can be found at <http://www.3gpp.org>

slash specifications, and is included herein by reference. Briefly, a SAI represents a value or a localized cell ID for an individual HNB or site. Thus, in connection with the disclosed subject matter, the SAI can represent an identifier associated with a single HNB device. In that case, filter component **116** can facilitate transmission (e.g., via interface component **102**) of message **110** only to the single HNB device. Naturally, in this case, subset **114** of HNB devices identified by target ID **112** is a single HNB device.

Appreciably, assignment of a SAI can be handled within a UTRAN system, which is further detailed in connection with FIGS. **3A** and **3B**. Thus, it should be understood that each and every HNB device included in set **104** can be assigned one or more unique identifier(s). Hence, each HNB device included in subset **114** (e.g., a subset of set **104**) will be assigned one or more unique identifier that identifies the associated single HNB device, which is illustrated as single identifier 1 (SID1), single identifier 2 (SID2), and so on for HNB devices **114₁-114_N**, wherein each of the HNB devices **114₁-114₃** have multiple SIDs (in this case SID1 and SID2 yet more can exist), while HNB device **114_N** has only one SID (in this case SID1).

Therefore, for example, if target ID **112** represents an SAI equal to “1234” or “9876”, then filter component **116** can ensure that interface component **102** transmits message **110** only to HNB device **114₁**. Likewise, if target ID **112** represents an SAI equal to the values “1235” or “9877”, message **110** can be delivered only to HNB device **114₂**, and so on. It should be appreciated that four digit base-ten numbers such as “1234” are selected for illustrative purposes only and that actual SAI values can be implemented in substantially any format desired and/or in conformity with the 3GPP standards.

Moreover, given that the UTRAN system can handle assignment of SAIs, such identifiers can be logically assigned according to any scheme desired. Thus, a SAI can be designated as a group identifier even though the 3GPP specification does not necessarily envision such use. Accordingly, one or more unique group identifiers are illustrated by HNB devices **114₁-114_N** as GID1, GID2 (and additional GIDs can also exist) according to substantially any logical grouping assignment desired. For instance, a single SAI, say, GID “1111” can identify a block or range of other single SAIs, say those SIDs from “1234” to “1237”. As another example, the SAI that represents a GID can denote all or a portion of HNB devices within a particular zip code. As still another example, the SAI that represents a GID can represent subscribers to third party products or services, such as street addresses with a particular garbage collection service, utilities provider, lawn care service, club member for a local business or vendor, a public or private community, a particular zoning area, or the like as well as for substantially any localized weather, news, or advertisements. In addition, the disclosed features can be readily integrated with or supplement future developments such as regulation or controls relating to, as well as actual deployment of, “Smart Grid.”

Put in another perspective, a SAI that represents a unique group identifier (e.g., GID=1111) can be assigned to all residences that share a particular garbage collection service, while a second SAI (e.g., GID=2222) can be assigned to subscribers to a particular gas utility company, and yet a third SAI (e.g., GID=2244) represents community members of a neighborhood watch program. Thus, billing notifications or other information from the garbage collection service can be included in message **110** along with target ID **112** of “1111” such that only the targeted parties will receive

message **110**, in this case at least HNB devices **114₁**, **114₂**, **114₃**, and **114_N**. Similarly, notifications or information from the gas utility company included in message **110** with a target ID **112** of “2222” can be delivered only to HNB devices **114₁** and **114₃**, and so on for other target ID(s) **112**.

In one or more aspects of the disclosed subject matter, target ID **112** can be a UTRAN Routing Area (URA) ID, which is illustrated as “Case 2” and denoted by reference numeral **204**. A URA ID is typically associated with multiple HNB devices included in a specified logical routing area. Thus, in contrast to SAIs, which are typically associated with a single HNB device, URA IDs customarily inherently define a collection of HNB devices such as those within a logical routing area. Hence, in this case, a URA ID can be similar to SAIs that represent group identifiers (e.g., GIDs), and can therefore be implemented with all or some of the features described supra in connection with GIDs.

Furthermore, in one or more aspects, target ID **112** can be a URA ID associated with a single HNB device in which a URA paging channel is enabled. Thus, while typical URA IDs relate to collections or groups of HNB devices, when the URA paging channel is enabled, an individualized URA ID can be assigned to a single HNB device. Therefore, all or some of the features detailed above with respect to SAIs can be implemented in this case as well. Employing URA IDs can be especially convenient when message **110** originates at (or is forwarded by) an inter-system source such as an SMS messaging center, in which case message **110** can be an SMS message. Moreover, whether utilizing SAIs or URA IDs or both, such identifiers can be stored to data store **208** for later access or recall and/or comparison with target ID **112** included in message **110**. Data store **208** can also include other unique identifiers associated with HNB device hardware such as a serial number, a Media Access Control (MAC) address, or the like, any of which can be associated with one or more SAI or URA ID in data store **208**.

Referring now to FIG. **3A**, system **300** that can allocate a SAI or an URA ID is illustrated. In more detail, system **300** can include interface component **102** and filter component **116** as substantially described supra, as well as other components described herein. In addition, system **300** can also include management component **302** that can assign (e.g., allocate or update) one or more target ID (e.g., a SAI or an URA ID) to each HNB device included in set **104**, and depicted here as HNB devices **104₁-104_M**, wherein M is a positive integer, generally greater than N as described in connection with FIG. **2**.

Thus, regardless of whether target ID **112** represents a SAI or an URA ID, message **110** can be specifically targeted and delivered to only the intended recipient(s). Moreover, by allowing single or individual HNB devices to be targeted as well as any number of groups or collections of HNB devices, a rich and efficient means for delivering message **110** only to specified parties can be achieved. For example, individual households (or even individual mobile devices, discussed infra) can be targeted as well as various communities that pivot on essentially any desired characteristic or association. For example, management component **302** can provide assignment **304** to data store **208** that allocates one or more SAI or URA ID (e.g., target ID **112**) to any given HNB device included in set **104** and can do so based upon any trait a network operator desires, which is further discussed with reference to FIG. **3B**.

While still referring to FIG. **3A**, but turning also to FIG. **3B**, illustration **320** provides example criteria for assignment of target IDs is depicted. In particular, illustration **320** provides example criteria that can be useful or convenient

for management component **302** when assigning target IDs to specific HNB devices. Such criteria can be based upon, e.g., a customer, commercial, public, private, or another type of relationship (denoted relationship **322**) or a subscription or good or service provision (denoted by reference numeral **324**). Typically, relationship **322** and subscription/provision **324** will generally relate to examples provided previously such as waste removal services or utilities provision, but can also be based upon warranty features of goods or services, familial relationships, friends, acquaintances, or colleague relationships, club or membership relationships, location-based relationships and so forth.

In addition, management component **302** can produce assignment **304** based upon request or query **326**. For example, consider an ad hoc community based upon a television audience who employ an UE to respond to a poll or voting request advertised by the televised program. Management component **302** can allocate a target ID **112** for such an ad hoc community and associate that target ID **112** to the appropriate subset **114** of HNB devices. Thus, results of the poll or vote or other data can be later delivered only to those HNB devices from which a vote or poll response originated or for which that particular target ID **112** is otherwise applicable (e.g., the subset **114** of HNB devices from which votes were sent).

Furthermore, management component **302** can also allocate assignment **304** based upon a demographic or interest **328** for the residence or business hosting one or more HNB devices. Demographic/interest **328** can be, e.g., based upon age, gender, income, political views, likes, dislikes and so forth, and can be particularly relevant for advertisements included in message **110**. Thus, management component **302** can design a particular community based upon a certain demographic/interest **328** and provision a SAI or URA ID for that community. Hence, any message **110** deemed suitable can be targeted expressly to that community based upon the particular demographic/interest **328**. It should be appreciated that regardless of the particular criteria employed, whether one of the provided examples indicated by illustration **320** or other criteria, all suitable information can be stored to data store **208**. For example, management component **302** can build profiles for each HNB device that can relate to relationships **322**, subscriptions/provisions **324**, requests/queries **326**, and/or demographic/interests **328** of a user of that particular HNB device.

It should be further appreciated that, while many HNB devices might well each serve a single UE (e.g., a preferred mobile device utilized by a single individual) as illustrated by HNB **104₁** and HNB **104₂** respectively serving UE **306₁** and UE **306₂**, it is also conceivable that a single HNB device can serve many UE terminals. For example, as depicted here in the case of HNB device **104_M** serving multiple UE, specifically UE **306₃**-**306₅**, any or all of which can be utilized by a different individual, such as multiple individuals in the same household or multiple employees at the same place of business.

In the latter case, where an HNB device serves multiple UE terminals, it should be appreciated that target ID **112** typically only identifies a particular HNB device and therefore generally cannot distinguish between individual recipients in this latter case. However, an additional feature exists in which individual subscribers served by an HNB device can be specifically targeted. For example, HNB devices often maintain an access control list or a “whitelist” that identifies the UE devices authorized to access the HNB device. Typically, access control lists are populated by way of customer input (e.g., inputting authorized phone numbers

or other identification), however any suitable discovery mechanism can be employed to automatically populate an access control list.

Regardless, once such information is obtained, it can be propagated by the HNB up the femtocell network to management component **302** (e.g., to the OSS or to another network component where management component **302** resides). As with other data described herein, the access control list can be stored to data store **208**. Moreover, once such information is obtained, communications can have the granularity to target individual subscribers above and beyond targeting individual HNB devices. More specifically, message **110** can further include a UE ID (e.g., recorded in an access control list) that identifies a specific wireless communication device served by a particular HNB device included in subset **114** of HNB devices. Thus, filter component **116** can determine a specific individual to whom message **110** is directed and employ interface component **102** to deliver message **110** only to a specific UE utilized by or otherwise associated with that specific individual.

With reference now to FIG. 4, system **400** that can employ acknowledgement requests for further mitigating registration oscillations and/or reducing inter-system messaging is provided. As introduced above, when a UE is registered to an associated HNB device, a dedicated resource such as a URA or a SAI range can eliminate or reduce unnecessary resource loading/communications to the macro network since a connection is already known and established with the femtocell network. As long as that connection exists, there is no need to broadcast communications on the macro network, since the location of (and therefore the path to) the designated target is already known. Thus, registration oscillation can be mitigated by targeting communications to the femtocell network while the UE is utilizing the femtocell network (e.g., an associated HNB device).

Moreover, registration oscillation can be further mitigated by facilitating acknowledgements in connection with certain communications. For example, in conventional networks and/or at the macro network level, messages delivered by way of flood broadcasting are not typically acknowledged. Thus, most systems employ a retry mechanism to transmit the broadcasts a certain number of times (e.g., three retries) before timing out. With respect to the features described herein much of this activity can be viewed as an unnecessary utilization of resources.

For example, once a message (e.g., message **110**) has been transmitted to the intended recipient(s) (e.g., subset **114**), management component **302** can facilitate transmission of acknowledgement request **402** to subset **114** of HNB devices to acknowledge that message **110** has been received. If or when acknowledgement **404** is received by management component **302**, it can be determined that retries are unnecessary and further that a dedicated resource is established for further communications directly to the associated HNB device. Moreover, in one or more aspects of the disclosed subject matter, acknowledgement request **402** can relate to a cyclic acknowledgement that mitigates inter-system reselection between a femtocell network and an associated macro network.

Appreciably, by employing cyclic acknowledgements, e.g., propagated from a UE to the associated HNB device and then up to management component **302**, the location of the UE can be re-verified over time. Thus, in addition to extending the period in which registration oscillation can be mitigated, implementing a cyclic acknowledgement on a dedicated HNB—UE basis as described can also contribute to reducing inter-system messaging such as that for paging

traffic. For instance, as long as acknowledgement requests **402** are met with acknowledgement **404**, there is no need to listen for a particular UE on the macro network since a dedicated stream to the associated HNB device is already operating. Hence, conventional signaling between the two networks, namely the femtocell network and the macro network, can be reduced or eliminated entirely. Furthermore, it should be understood that although management component **302** is conceptually depicted transmitting acknowledgement request **402** to and receiving acknowledgement **404** from subset **114** of HNB devices, interface component **102** can be employed to perform the actual transmitting and receiving on behalf of management component **302**.

Now turning to FIG. 5, system **500**, which represents a HNB device that can facilitate more efficient or robust communication, is illustrated. In general, HNB device **500** can include registration component **502** that can maintain access control list **504**, sometimes referred to as a "whitelist." Access control list **504** can include multiple UE IDs, wherein each of the multiple UE IDs can represent one or more specific wireless communication device(s) authorized to be served by HNB device **500**. As one example, HNB device **500** can operate in a household with three distinct subscribers to the host communications network. Examples of wireless communication devices or terminals **506** can include cellular phones, smart phones, mobile terminals, or the like.

HNB device **500** include an interface to a remote network (e.g., first interface component **508**) as well as an interface (e.g., second interface component **514**) to the hosted UE devices or terminals **506** registered to HNB device **500**, in this case 3 terminals **506** are depicted, but it should be appreciated that substantially any number of terminals **506** can be served. First interface component **508** can receive message **510** that can include UE ID **512**. Message **512** can be substantially similar to or a portion of message **110** discussed supra, which can include target ID **112**. While target ID **112** can identify intended recipients defined as subset **114**, of which HNB device **500** is a member, UE ID **512** can identify a specific wireless communication device from among multiple registered wireless communication devices or terminals **506** served by HNB device **500**.

In addition, second interface component **514** that is included in HNB device **500** can transmit message **510** only to the specific wireless communication device(s) identified by UE ID **512** included in message **510**. Thus, even though 3 terminals **506** are served by HNB device **500**, message **510** can be selectively transmitted to any one or more of these 3 terminals based upon the UE ID **512**.

Referring now to FIG. 6, system **600** that provides for additional features or aspects in connection with an HNB device that can facilitate more efficient or robust communication is illustrated. System **600** can include registration component **502** that can maintain access control list **504** and second interface component **514** that can transmit message **510** to only specified terminals **506** identified by UE ID as substantially detailed supra, as well as other components detailed in connection with HNB device **500** of FIG. 5.

Additionally, system **600** can further include memory **602** that can store message **510** when the specific wireless communication device or terminal **506** identified by UE ID **512** is not present (or camped on its home femtocell). Furthermore, system **600** can also include polling component **606** that can detect the presence of the specific wireless communications device (e.g., any or all terminals identified by access control list **504**). In accordance with the above, when one or more wireless communication terminals iden-

tified by UE ID **512** is not present (in this case, the middle terminal **506** with an "X" to denote a lack of current presence on HNB device **500**), second interface component **514** can store message **510** intended for the absent terminal **506** to memory **602**.

It should be appreciated that polling component **606** can actively or persistently maintain a presence or absence list, which can be readily compared to UE ID(s) **512** when message **510** is received in order to ascertain whether message **510** can be forwarded directly to the specific wireless communication terminal(s) **506** or stored to memory **602**. Moreover, if message **510** is received when a terminal **506** identified by UE ID **512** is absent, polling component **606** can facilitate transmission (e.g., by way of second interface component **514**) of message **510** previously stored to memory **602** once it is detected that the specific terminal is no longer absent.

Furthermore, system **600** can also receive an acknowledgement request **608**, which can be received by first interface component **508** and can be substantially similar to acknowledgement request **402** discussed in connection with FIG. 4. Upon receipt, polling component **606** can forward the acknowledgement request **608** to the one or more recipient(s) among terminals **506** of message **510**. In response, terminals **506** who received acknowledgement request **608** can reply with acknowledgement **610**, which can be received by second interface component **514** and forward along the uplink by first interface component **508** of HNB device **500**. Acknowledgement **610** can verify that message **510** was received by a specific terminal **506** identified by UE ID **512**, and thus mitigate registration oscillation and reduce inter-system messaging by establishing a dedicated path between a particular UE and other communication sources. Moreover, as introduced previously, both acknowledgement request **608** and acknowledgement **610** can be of a periodic or cyclic nature, thus potentially refining the duration of this dedicated path more suitably.

FIGS. 7, 8, and 9 illustrate various methodologies in accordance with the disclosed subject matter. While, for purposes of simplicity of explanation, the methodologies are shown and described as a series of acts, it is to be understood and appreciated that the disclosed subject matter is not limited by the order of acts, as some acts may occur in different orders and/or concurrently with other acts from that shown and described herein. For example, those skilled in the art will understand and appreciate that a methodology could alternatively be represented as a series of interrelated states or events, such as in a state diagram. Moreover, not all illustrated acts may be required to implement a methodology in accordance with the disclosed subject matter. Additionally, it should be further appreciated that the methodologies disclosed hereinafter and throughout this specification are capable of being stored on an article of manufacture to facilitate transporting and transferring such methodologies to computers. The term article of manufacture, as used herein, is intended to encompass a computer program accessible from any computer-readable device, carrier, or media.

Turning now to FIG. 7, an exemplary method **700** for leveraging Universal Mobile Telecommunication System (UMTS) Terrestrial Radio Access Network (UTRAN) features for facilitating more efficient or robust communication with a femtocell network is illustrated. Generally, at reference numeral **702**, a set of home nodeB (HNB) modules that employ a UMTS localized common pilot channel can be interfaced to. The set of HNB modules can include a portion of or all HNB modules operating in a UTRAN network, any

or all of which can be controlled remotely by way of an OSS or other suitable network elements.

At reference numeral **704**, a message that includes a target ID can be received. The target ID can identify a subset of HNB modules included in the set of HNB modules. In other words, from among all the HNB modules interfaced to at reference numeral **702**, a particular subset (e.g., one or more) can be identified by target ID. Accordingly, at reference numeral **706**, the message received at reference numeral **704**, in its entirety or in part, can be propagated to only the subset of HNB modules identified by the target ID, rather than to all or additional HNB modules included in the set.

Appreciably, by selectively targeting particular HNB modules, the path to which can be identified in advance by a dedicated channel, a number of advantages can be provided. For example, communications can be more efficient since flood broadcasting is no longer needed and, in fact, duplicate messages delivered to non-targeted recipients are not necessary. Moreover, selective propagation of the message can be inherently more secure as non-targeted individuals will not generally be recipients of the message at all. Furthermore, inter-system messaging and registration oscillations can also be mitigated or reduced as substantially detailed supra. Furthermore, the disclosed subject matter can be readily integrated with or supplement future technologies or regulation such as the proposals relating to Smart Grid.

With reference now FIG. **8**, exemplary method **800** for employing a SAI or an URA ID in connection with the target ID as well as targeting a specific UE is provided. At reference numeral **802**, the message received at reference numeral **704** of FIG. **7** can further include (e.g., in addition to the target ID) a UE ID, the UE ID identifying one or more specific wireless communication device(s) based upon an access control list provided by the serving HNB module. Hence, while the target ID can be sufficient to select a specific HNB module or femtocell, the UE ID can provide additional granularity to select a specific mobile device associated with a specific individual.

With regard to the target ID included in the message, at reference numeral **804**, the message can be propagated to a single HNB module that is associated with a SAI matching the target ID. Likewise, at reference numeral **806**, the message can be propagated to multiple HNB modules, each of which is associated with a group SAI matching the target ID. Thus, an SAI can be employed to define a single HNB module as detailed at reference numeral **804** as well as a collection or group of HNB modules as discussed in connection with reference numeral **806**.

Additionally or alternatively, at reference numeral **808**, the message can be propagated to a single HNB module with a URA paging channel enabled, wherein the single HNB module is associated with a URA ID matching the target ID. However, in the case of more than one intended recipient, at reference numeral **810**, the message can be propagated to multiple HNB modules, each of which is associated with a URA ID matching the target ID. Accordingly, as with the case in which the target ID reflects a SAI, when the target ID reflects a URA ID, both individual and group HNB modules can be targeted.

Turning briefly to FIG. **9**, an exemplary method **900** for allocating target IDs to HNB modules and/or employing acknowledgements to further reduce system load is depicted. At reference numeral **902**, one or more target ID can be assigned to each HNB module included in the set of HNB modules. Typically, every HNB module included in the set will have at least an individual or single target ID

(SID) assigned thereto, whether the single ID is based upon a SAI or an URA ID. However, some HNB modules (potentially all) can have more than one SID, e.g., one based upon a SAI and another based upon a URA ID, or for any other suitable reason. The first or primary SID can be assigned, e.g., incrementally according to a location zip code of the HNB. In addition, each HNB module can potentially have a great many group IDs (GIDs), for example, one assigned based upon a customer subscription to a local gas company, another assigned based upon a relationship with a local condominium community, and another based upon an ad hoc or temporary relationship.

Any or all of these target IDs, but particularly the GIDs can be assigned based upon a variety of useful criteria. For example, at reference numeral **904**, the one or more target ID can be assigned based upon a customer relationship, a commercial relationship, a social network relationship, or another type of relationship. The one or more target ID can also be assigned based upon a subscription or a good or service provision. Other examples can include a request or query, a demographic or interest, and so on.

At reference numeral **906**, an acknowledgement request can be transmitted to the subset of HNB modules for acknowledging that the message has been received. Similarly, at reference numeral **908**, an acknowledgement request can be transmitted for instructing the subset of HNB devices to provide a cyclic acknowledgement in response to the acknowledgement request. The cyclic acknowledgement can be employed for mitigating inter-system reselection between a femtocell network and an associated macro network as well as for reducing inter-system message traffic between the femtocell network and the macro network.

To provide further context for various aspects of the subject specification, FIG. **10** illustrates an example wireless communication environment **1000**, with associated components that can enable operation of a femtocell enterprise network in accordance with aspects described herein. Wireless communication environment **1000** includes two wireless network platforms: (i) A macro network platform **1010** that serves, or facilitates communication) with user equipment **1075** via a macro radio access network (RAN) **1070**. It should be appreciated that in cellular wireless technologies (e.g., 4G, 3GPP UMTS, HSPA, 3GPP LTE, 3GPP UMB), macro network platform **1010** is embodied in a Core Network. (ii) A femto network platform **1080**, which can provide communication with UE **1075** through a femto RAN **1090**, linked to the femto network platform **1080** through a routing platform **102** via backhaul pipe(s) **1085**, wherein backhaul pipe(s) are substantially the same a backhaul link **3853** below. It should be appreciated that femto network platform **1080** typically offloads UE **1075** from macro network, once UE **1075** attaches (e.g., through macro-to-femto handover, or via a scan of channel resources in idle mode) to femto RAN.

It is noted that RAN includes base station(s), or access point(s), and its associated electronic circuitry and deployment site(s), in addition to a wireless radio link operated in accordance with the base station(s). Accordingly, macro RAN **1070** can comprise various coverage cells like cell **1205**, while femto RAN **1090** can comprise multiple femto access points. As mentioned above, it is to be appreciated that deployment density in femto RAN **1090** is substantially higher than in macro RAN **1070**.

Generally, both macro and femto network platforms **1010** and **1080** include components, e.g., nodes, gateways, interfaces, servers, or platforms, that facilitate both packet-switched (PS) (e.g., internet protocol (IP), frame relay,

asynchronous transfer mode (ATM)) and circuit-switched (CS) traffic (e.g., voice and data) and control generation for networked wireless communication. In an aspect of the subject innovation, macro network platform **1010** includes CS gateway node(s) **1012** which can interface CS traffic received from legacy networks like telephony network(s) **1040** (e.g., public switched telephone network (PSTN), or public land mobile network (PLMN)) or a SS7 network **1060**. Circuit switched gateway **1012** can authorize and authenticate traffic (e.g., voice) arising from such networks. Additionally, CS gateway **1012** can access mobility, or roaming, data generated through SS7 network **1060**; for instance, mobility data stored in a VLR, which can reside in memory **1030**. Moreover, CS gateway node(s) **1012** interfaces CS-based traffic and signaling and gateway node(s) **1018**. As an example, in a 3GPP UMTS network, gateway node(s) **1018** can be embodied in gateway GPRS support node(s) (GGSN).

In addition to receiving and processing CS-switched traffic and signaling, gateway node(s) **1018** can authorize and authenticate PS-based data sessions with served (e.g., through macro RAN) wireless devices. Data sessions can include traffic exchange with networks external to the macro network platform **1010**, like wide area network(s) (WANs) **1050**; it should be appreciated that local area network(s) (LANs) can also be interfaced with macro network platform **1010** through gateway node(s) **1018**. Gateway node(s) **1018** generates packet data contexts when a data session is established. To that end, in an aspect, gateway node(s) **1018** can include a tunnel interface (e.g., tunnel termination gateway (TTG) in 3GPP UMTS network(s); not shown) which can facilitate packetized communication with disparate wireless network(s), such as Wi-Fi networks. It should be further appreciated that the packetized communication can include multiple flows that can be generated through server(s) **1014**. It is to be noted that in 3GPP UMTS network(s), gateway node(s) **1018** (e.g., GGSN) and tunnel interface (e.g., TTG) comprise a packet data gateway (PDG).

Macro network platform **1010** also includes serving node(s) **1016** that convey the various packetized flows of information or data streams, received through gateway node(s) **1018**. As an example, in a 3GPP UMTS network, serving node(s) can be embodied in serving GPRS support node(s) (SGSN).

As indicated above, server(s) **1014** in macro network platform **1010** can execute numerous applications (e.g., location services, online gaming, wireless banking, wireless device management . . .) that generate multiple disparate packetized data streams or flows, and manage (e.g., schedule, queue, format . . .) such flows. Such application(s), for example can include add-on features to standard services provided by macro network platform **1010**. Data streams can be conveyed to gateway node(s) **1018** for authorization/authentication and initiation of a data session, and to serving node(s) **1016** for communication thereafter. Server(s) **1014** can also effect security (e.g., implement one or more firewalls) of macro network platform **1010** to ensure network's operation and data integrity in addition to authorization and authentication procedures that CS gateway node(s) **1012** and gateway node(s) **1018** can enact. Moreover, server(s) **1014** can provision services from external network(s), e.g., WAN **1050**, or Global Positioning System (GPS) network(s) (not shown). It is to be noted that server(s) **1014** can include one or more processor configured to confer at least in part the functionality of macro network platform **1010**. To that end,

the one or more processor can execute code instructions stored in memory **1030**, for example.

In example wireless environment **1000**, memory **1030** stores information related to operation of macro network platform **1010**. Information can include business data associated with subscribers; market plans and strategies, e.g., promotional campaigns, business partnerships; operational data for mobile devices served through macro network platform; service and privacy policies; end-user service logs for law enforcement; and so forth. Memory **1030** can also store information from at least one of telephony network(s) **1040**, WAN(s) **1050**, or SS7 network **1060**, enterprise NW(s) **1065**, or service NW(s) **1067**.

Femto gateway node(s) **1084** have substantially the same functionality as PS gateway node(s) **1018**. Additionally, femto gateway node(s) **1084** can also include substantially all functionality of serving node(s) **1016**. In an aspect, femto gateway node(s) **1084** facilitates handover resolution, e.g., assessment and execution. Further, control node(s) **1020** can receive handover requests and relay them to a handover component (not shown) via gateway node(s) **1084**. According to an aspect, control node(s) **1020** can support RNC capabilities and can be substantially similar to the control component **320** (FIG. 3) and can include functionality thereof.

Server(s) **1082** have substantially the same functionality as described in connection with server(s) **1014**. In an aspect, server(s) **1082** can execute multiple application(s) that provide service (e.g., voice and data) to wireless devices served through femto RAN **1090**. Server(s) **1082** can also provide security features to femto network platform. In addition, server(s) **1082** can manage (e.g., schedule, queue, format . . .) substantially all packetized flows (e.g., IP-based, frame relay-based, ATM-based) it generates in addition to data received from macro network platform **1010**. It is to be noted that server(s) **1082** can include one or more processor configured to confer at least in part the functionality of macro network platform **1010**. To that end, the one or more processor can execute code instructions stored in memory **1086**, for example.

Memory **1086** can include information relevant to operation of the various components of femto network platform **1080**. For example operational information that can be stored in memory **1086** can comprise, but is not limited to, subscriber information; contracted services; maintenance and service records; femto cell configuration (e.g., devices served through femto RAN **1090**; access control lists, or white lists); service policies and specifications; privacy policies; add-on features; and so forth.

It is noted that femto network platform **1080** and macro network platform **1010** can be functionally connected through one or more reference link(s) or reference interface(s). In addition, femto network platform **1080** can be functionally coupled directly (not illustrated) to one or more of external network(s) **1040**, **1050**, **1060**, **1065** or **1067**. Reference link(s) or interface(s) can functionally link at least one of gateway node(s) **1084** or server(s) **1086** to the one or more external networks **1040**, **1050**, **1060**, **1065** or **1067**.

FIG. 11 illustrates a wireless environment that includes macro cells and femtocells for wireless coverage in accordance with aspects described herein. In wireless environment **1150**, two areas **1105** represent "macro" cell coverage, each macro cell is served by a base station **1110**. It can be appreciated that macro cell coverage area **1105** and base station **1110** can include functionality, as more fully described herein, for example, with regard to system **1100**.

Macro coverage is generally intended to serve mobile wireless devices, like UE **1120_A**, **1120_B**, in outdoors locations. An over-the-air wireless link **115** provides such coverage, the wireless link **1215** comprises a downlink (DL) and an uplink (UL), and utilizes a predetermined band, licensed or unlicensed, of the radio frequency (RF) spectrum. As an example, UE **1120_A**, **1120_B** can be a 3GPP Universal Mobile Telecommunication System (UMTS) mobile phone. It is noted that a set of base stations, its associated electronics, circuitry or components, base stations control component(s), and wireless links operated in accordance to respective base stations in the set of base stations form a radio access network (RAN). In addition, base station **1110** communicates via backhaul link(s) **1151** with a macro network platform **1160**, which in cellular wireless technologies (e.g., 3rd Generation Partnership Project (3GPP) Universal Mobile Telecommunication System (UMTS), Global System for Mobile Communication (GSM)) represents a core network.

In an aspect, macro network platform **1160** controls a set of base stations **1110** that serve either respective cells or a number of sectors within such cells. Base station **1110** comprises radio equipment **1114** for operation in one or more radio technologies, and a set of antennas **1112** (e.g., smart antennas, microwave antennas, satellite dish(es) . . .) that can serve one or more sectors within a macro cell **1105**. It is noted that a set of radio network control node(s), which can be a part of macro network platform; a set of base stations (e.g., Node B **1110**) that serve a set of macro cells **1105**; electronics, circuitry or components associated with the base stations in the set of base stations; a set of respective OTA wireless links (e.g., links **1115** or **1116**) operated in accordance to a radio technology through the base stations; and backhaul link(s) **1155** and **1151** form a macro radio access network (RAN). Macro network platform **1160** also communicates with other base stations (not shown) that serve other cells (not shown). Backhaul link(s) **1151** or **1153** can include a wired backbone link (e.g., optical fiber backbone, twisted-pair line, T1/E1 phone line, a digital subscriber line (DSL) either synchronous or asynchronous, an asymmetric ADSL, or a coaxial cable . . .) or a wireless (e.g., line-of-sight (LOS) or non-LOS) backbone link. Backhaul pipe(s) **1155** link disparate base stations **1110**. According to an aspect, backhaul link **1153** can connect multiple femto access points **1130** and/or controller components (CC) **1101** to the femto network platform **1102**. In one example, multiple femto APs can be connected to a routing platform (RP) **1087**, which in turn can be connect to a controller component (CC) **1101**. Typically, the information from UEs **1120_A** can be routed by the RP **102**, for example, internally, to another UE **1120_A** connected to a disparate femto AP connected to the RP **1087**, or, externally, to the femto network platform **1102** via the CC **1101**, as discussed in detail supra.

In wireless environment **1150**, within one or more macro cell(s) **1105**, a set of femtocells **1145** served by respective femto access points (APs) **1130** can be deployed. It can be appreciated that, aspects of the subject innovation are geared to femtocell deployments with substantive femto AP density, e.g., 10^4 - 10^7 femto APs **1130** per base station **1110**. According to an aspect, a set of femto access points **1130₁-3730_N**, with N a natural number, can be functionally connected to a routing platform **1087**, which can be functionally coupled to a controller component **1101**. The controller component **1101** can be operationally linked to the femto network platform **330** by employing backhaul link(s) **1153**. Accordingly, UEs UE **3720_A** connected to femto APs **1130₁-3830_N** can communicate internally within the femto enterprise via

the routing platform (RP) **1087** and/or can also communicate with the femto network platform **1102** via the RP **1087**, controller component **1101** and the backhaul link(s) **1153**. It can be appreciated that although only one femto enterprise is depicted in FIG. **11**, multiple femto enterprise networks can be deployed within a macro cell **1105**.

It is noted that while various aspects, features, or advantages described herein have been illustrated through femto access point(s) and associated femto coverage, such aspects and features also can be exploited for home access point(s) (HAPs) that provide wireless coverage through substantially any, or any, disparate telecommunication technologies, such as for example Wi-Fi (wireless fidelity) or picocell telecommunication. Additionally, aspects, features, or advantages of the subject innovation can be exploited in substantially any wireless telecommunication, or radio, technology; for example, Wi-Fi, Worldwide Interoperability for Microwave Access (WiMAX), Enhanced General Packet Radio Service (Enhanced GPRS), 3GPP LTE, 3GPP2 UMB, 3GPP UMTS, HSPA, HSDPA, HSUPA, or LTE Advanced. Moreover, substantially all aspects of the subject innovation can include legacy telecommunication technologies.

Various aspects or features described herein can be implemented as a method, apparatus, or article of manufacture using standard programming and/or engineering techniques. In addition, various aspects disclosed in the subject specification can also be implemented through program modules stored in a memory and executed by a processor, or other combination of hardware and software, or hardware and firmware. The term "article of manufacture" as used herein is intended to encompass a computer program accessible from any computer-readable device, carrier, or media. For example, computer readable media can include but are not limited to magnetic storage devices (e.g., hard disk, floppy disk, magnetic strips . . .), optical disks (e.g., compact disc (CD), digital versatile disc (DVD), blu-ray disc (BD) . . .), smart cards, and flash memory devices (e.g., card, stick, key drive . . .). Additionally it should be appreciated that a carrier wave can be employed to carry computer-readable electronic data such as those used in transmitting and receiving electronic mail or in accessing a network such as the internet or a local area network (LAN). Of course, those skilled in the art will recognize many modifications may be made to this configuration without departing from the scope or spirit of the disclosed subject matter.

As it employed in the subject specification, the term "processor" can refer to substantially any computing processing unit or device comprising, but not limited to comprising, single-core processors; single-processors with software multithread execution capability; multi-core processors; multi-core processors with software multithread execution capability; multi-core processors with hardware multithread technology; parallel platforms; and parallel platforms with distributed shared memory. Additionally, a processor can refer to an integrated circuit, an application specific integrated circuit (ASIC), a digital signal processor (DSP), a field programmable gate array (FPGA), a programmable logic controller (PLC), a complex programmable logic device (CPLD), a discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. Processors can exploit nano-scale architectures such as, but not limited to, molecular and quantum-dot based transistors, switches and gates, in order to optimize space usage or enhance performance of user equipment. A processor also can be implemented as a combination of computing processing units.

In the subject specification, terms such as “store,” “data store,” “data storage,” “database,” “repository,” and substantially any other information storage component relevant to operation and functionality of a component, refer to “memory components,” or entities embodied in a “memory” or components comprising the memory. It will be appreciated that the memory components described herein can be either volatile memory or nonvolatile memory, or can include both volatile and nonvolatile memory. In addition, memory components or memory elements can be removable or stationary. Moreover, memory can be internal or external to a device or component, or removable or stationary. Memory can include various types of media that are readable by a computer, such as hard-disc drives, zip drives, magnetic cassettes, flash memory cards or other types of memory cards, cartridges, or the like.

By way of illustration, and not limitation, nonvolatile memory can include read only memory (ROM), programmable ROM (PROM), electrically programmable ROM (EPROM), electrically erasable ROM (EEPROM), or flash memory. Volatile memory can include random access memory (RAM), which acts as external cache memory. By way of illustration and not limitation, RAM is available in many forms such as synchronous RAM (SRAM), dynamic RAM (DRAM), synchronous DRAM (SDRAM), double data rate SDRAM (DDR SDRAM), enhanced SDRAM (ESDRAM), Synchlink DRAM (SLDRAM), and direct Rambus RAM (DRRAM). Additionally, the disclosed memory components of systems or methods herein are intended to comprise, without being limited to comprising, these and any other suitable types of memory.

What has been described above includes examples of the various embodiments. It is, of course, not possible to describe every conceivable combination of components or methodologies for purposes of describing the embodiments, but one of ordinary skill in the art may recognize that many further combinations and permutations are possible. Accordingly, the detailed description is intended to embrace all such alterations, modifications, and variations that fall within the spirit and scope of the appended claims.

In particular and in regard to the various functions performed by the above described components, devices, circuits, systems and the like, the terms (including a reference to a “means”) used to describe such components are intended to correspond, unless otherwise indicated, to any component which performs the specified function of the described component (e.g., a functional equivalent), even though not structurally equivalent to the disclosed structure, which performs the function in the herein illustrated exemplary aspects of the embodiments. In this regard, it will also be recognized that the embodiments includes a system as well as a computer-readable medium having computer-executable instructions for performing the acts and/or events of the various methods.

In addition, while a particular feature may have been disclosed with respect to only one of several implementations, such feature may be combined with one or more other features of the other implementations as may be desired and advantageous for any given or particular application. Furthermore, to the extent that the terms “includes,” and “including” and variants thereof are used in either the detailed description or the claims, these terms are intended to be inclusive in a manner similar to the term “comprising.”

What is claimed is:

1. A system, comprising:
 - a processor; and
 - a memory that stores executable instructions that, when executed by the processor, facilitate performance of operations, comprising:
 - assigning, by the system, target identifiers to femtocell access point devices based on demographics and interests of subscriber identities associated with the femtocell access point devices, wherein a femtocell access point device of the femtocell access point devices is assigned a target identifier based on the femtocell access point device being associated with a subscriber identity determined to satisfy a criterion based on the demographics and the interests;
 - receiving, by the system, a first transmission comprising a message comprising the target identifier;
 - identifying, by the system, the femtocell access point device as a targeted recipient of the message based on the target identifier; and
 - transmitting, by the system, a second transmission comprising the message to the femtocell access point device.
2. The system of claim 1, wherein the demographics and the interests of subscriber identities are received from the femtocell access point devices.
3. The system of claim 1, wherein the criterion is based on whether a defined familial relationship is present between identities of the subscriber identities.
4. The system of claim 1, wherein the criterion is based on whether an identity of the subscriber identities has a defined gender.
5. The system of claim 1, wherein the criterion is based on whether some of the femtocell access point devices have been determined to be located within a common weather coverage area.
6. The system of claim 1, wherein the criterion is based on whether a demographic of the demographics satisfies a defined income criterion.
7. The system of claim 1, wherein the criterion is based on whether a demographic of the demographics satisfies a defined age criterion.
8. A method, comprising:
 - assigning, by a system comprising a processor, target identifiers to home nodeB access point devices based on demographics and interests of subscriber identities associated with the home nodeB access point devices, wherein a home nodeB access point device of the home nodeB access point devices is assigned a target identifier based on the home nodeB access point device being associated with a subscriber identity determined to satisfy a specified criterion based on the demographics and the interests;
 - receiving, by the system, a first transmission comprising a message comprising the target identifier;
 - identifying, by the system, the home nodeB access point device as an intended recipient of the message based on the target identifier; and
 - sending, by the system to the home nodeB access point device, a second transmission comprising the message to the home nodeB access point device.
9. The method of claim 8, wherein the specified criterion is with respect to a defined political view of the subscriber identity of the subscriber identities.

21

10. The method of claim 8, wherein the demographics and the interests of the subscriber identities are derived from information received from the home nodeB access point devices.

11. The method of claim 8, wherein the specified criterion is with respect to a membership of the subscriber identity of the subscriber identities to a common private club.

12. The method of claim 8, wherein the specified criterion is with respect to whether the home nodeB access point devices are determined to be located within a common weather coverage area.

13. The method of claim 8, wherein the specified criterion is with respect to whether a demographic of the subscriber identity of the subscriber identities satisfies a defined income criterion.

14. The method of claim 8, wherein the specified criterion is with respect to whether a demographic of an identity of the subscriber identities satisfies a defined age criterion.

15. A non-transitory machine-readable storage medium, comprising executable instructions that, when executed by a processor, facilitate performance of operations, comprising:
 assigning target identifiers for access point devices based on demographics and interests of subscribers associated with the access point devices, wherein an access point device of the access point devices is assigned a target identifier based on the access point device being

22

determined to be associated with a subscriber meeting a defined criterion based on the demographics and the interests;

receiving a first transmission of a message comprising the target identifier;

identifying the access point device as a recipient of the message based on the target identifier; and

sending a second transmission comprising the message to the access point device.

16. The machine-readable storage medium of claim 15, wherein the demographics and the interests of the subscribers are generated by an operator of a network comprising the access point devices.

17. The machine-readable storage medium of claim 15, wherein the criterion relates to a familial relationship between identities of the subscribers.

18. The machine-readable storage medium of claim 15, wherein the criterion relates to a gender.

19. The machine-readable storage medium of claim 15, wherein the criterion relates to some of the access point devices being determined to be located within a common weather coverage area.

20. The machine-readable storage medium of claim 15, wherein the criterion relates to a demographic of an identity of the subscriber satisfying a defined age criterion.

* * * * *