



US009774787B2

(12) **United States Patent**  
**Miller et al.**

(10) **Patent No.:** **US 9,774,787 B2**  
(45) **Date of Patent:** **Sep. 26, 2017**

(54) **MOBILE ZOOM USING MULTIPLE  
OPTICAL IMAGE STABILIZATION  
CAMERAS**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Scott W. Miller**, Los Gatos, CA (US);  
**Aurelien R. Hubert**, Saratoga, CA  
(US); **Shashank Sharma**, San  
Francisco, CA (US); **Simon S. Lee**, San  
Jose, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/871,716**

(22) Filed: **Sep. 30, 2015**

(65) **Prior Publication Data**

US 2017/0094181 A1 Mar. 30, 2017

(51) **Int. Cl.**  
**H04N 5/232** (2006.01)  
**H04N 5/225** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **H04N 5/23296** (2013.01); **H04N 5/2257**  
(2013.01); **H04N 5/2258** (2013.01); **H04N**  
**5/23287** (2013.01)

(58) **Field of Classification Search**  
CPC ..... G02B 27/64; G02B 27/646; G03B  
2205/0007; G03B 2205/00; G03B  
2205/015; G03B 2205/0038; G03B  
2205/0053; G03B 2205/0061; G03B  
2205/0084; H04N 5/2328; H04N  
5/23287;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,294,780 B2 10/2012 Chang  
8,731,390 B2 5/2014 Goldenberg et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 104054020 9/2014  
EP 2802937 11/2014

(Continued)

OTHER PUBLICATIONS

International Search Report & Written Opinion from PCT/US2016/  
048475, dated Nov. 2, 2016, Apple Inc., pp. 1-12.


*Primary Examiner* — Rochelle-Ann J Blackman

(74) *Attorney, Agent, or Firm* — Robert C. Kowert;  
Meyertons, Hood, Kivlin, Kowert & Goetzel, P.C.

(57) **ABSTRACT**

A first camera unit includes a first actuator for moving a first optical package configured for a first focal length. In some embodiments, a camera system of a multifunction device includes a second camera unit of the multifunction device for simultaneously capturing a second image of a second visual field. In some embodiments, the second camera unit includes a second actuator for moving a second optical package configured for a second focal length. In some embodiments, the second actuator includes a second actuator lateral magnet. In some embodiments, the first optical package and the second optical package are situated between the first actuator lateral magnet and the second actuator lateral magnet along an axis between the first actuator lateral magnet and the second actuator lateral magnet. In some embodiments, no actuator lateral magnets are situated between the first optical package and the second optical package along the axis.

**20 Claims, 29 Drawing Sheets**



(58)

Field of Classification Search

CPC . H04N 5/23245; H04N 5/225; H04N 5/23296

USPC .... 396/55, 75, 77, 79–82; 348/208.4, 208.5, 348/208.7, 208.11, 360; 359/554, 557, 359/819–826

See application file for complete search history.

2013/0242057 A1

2015/0029601 A1

2015/0085174 A1

2015/0177479 A1 \*

2015/0244942 A1

2015/0316744 A1

2016/0316150 A1

9/2013

1/2015

3/2015

6/2015

8/2015

11/2015

10/2016

Hong et al.

Dror et al.

Shabtay et al.

Lee ..... G02B 7/09 359/824

Shabtay et al.

Chen

Eromaki

(56)

References Cited

U.S. PATENT DOCUMENTS

8,792,782 B1

7/2014

Cheng et al.

9,083,873 B1

7/2015

Lewkow

9,185,291 B1

11/2015

Shabtay et al.

2010/0097443 A1

4/2010

Lablans

2011/0169920 A1

7/2011

Ryu et al.

2013/0028581 A1 \*

1/2013

Yeung ..... G03B 17/14 396/75

2013/0141541 A1

6/2013

Jung et al.

2013/0194466 A1

8/2013

Cheng et al.

FOREIGN PATENT DOCUMENTS

TW

I498658

9/2013

TW

201518838

5/2015

TW

201518854

5/2015

WO

2015001519

1/2015

WO

2015015383

2/2015

WO

2015068056

5/2015

WO

2015068061

5/2015

WO

2015124966

8/2015

\* cited by examiner






FIG. 1




FIG. 2




FIG. 3A




FIG. 3B






FIG. 3C




FIG. 4A




FIG. 4C




FIG. 4B




FIG. 4D






FIG. 4E




FIG. 4G




FIG. 4F







FIG. 4H



	Carrier + Lens (Moves in X,Y,Z)
	AF Coil (Moves in X,Y,Z)
	Magnetic (Moves in X,Y)
	SP Coil (Stationary)

FIG. 4L




FIG. 5




FIG. 6A






FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E






FIG. 7A





FIG. 7B




FIG. 7C






FIG. 8A




FIG. 8E




FIG. 8B




FIG. 8C




FIG. 8D






FIG. 9A




FIG. 9B





FIG. 9C

**FIG. 9D**






FIG. 10A




FIG. 10B





FIG. 10C

*FIG. 10D*




FIG. 11A




FIG. 11B




FIG. 11C






FIG. 12A

*Inventive concept 7-1 – no center magnet. First orientation plan*




FIG. 12B






FIG. 12C




FIG. 12E

FIG. 12F




FIG. 12D




FIG. 12G




FIG. 13A

*Inventive concept 7-3 – no center magnet, but wait, the polarity configuration has changed from 12 C.*




FIG. 13B






FIG. 14A




FIG. 14B




FIG. 15



# MOBILE ZOOM USING MULTIPLE OPTICAL IMAGE STABILIZATION CAMERAS

## BACKGROUND

### Technical Field

This disclosure relates generally to camera module components and more specifically to the use of multiple cameras for zoom functions in mobile devices.

### Description of the Related Art

The advent of small, mobile multipurpose devices such as smartphones and tablet or pad devices has resulted in a need for high-resolution, small form factor cameras, capable of generating high levels of image quality, for integration in the devices.

Increasingly, as users rely on these multifunction devices as their primary cameras for day-to-day use, users demand features, such as zoom photography, that they have become accustomed to using in dedicated-purpose camera bodies. The zoom function is useful for capturing the details of a scene or alternatively capturing the context in which those details exist. The ability to change focal length to achieve zoom effects is sufficiently compelling to users of dedicated purpose cameras that it compels them to carry bags with an array of removable lenses, each of which weighs more and takes up more space than many common examples of a multifunction device, such as a phone.

Providing the zoom feature in a camera unit of a multifunction device has traditionally required moving mechanical parts that increase complexity and cost of the device. Such moving parts also reduce reliability of the device and take up valuable space inside the device, which puts the desire for zoom functions in direct conflict with the desire for smaller camera units that take up less space in the multifunction device.

## SUMMARY OF EMBODIMENTS

In some embodiments, a camera system of a multifunction device includes a first camera unit of a multifunction device for capturing a first image of a first visual field. In some embodiments, the first camera unit includes a first actuator for moving a first optical package configured for a first focal length. In some embodiments, a camera system of a multifunction device includes a second camera unit of the multifunction device for simultaneously capturing a second image of a second visual field. In some embodiments, the second camera unit includes a second actuator for moving a second optical package configured for a second focal length. In some embodiments, the second actuator includes a second actuator lateral magnet. In some embodiments, the first optical package and the second optical package are situated between the first actuator lateral magnet and the second actuator lateral magnet along an axis between the first actuator lateral magnet and the second actuator lateral magnet. In some embodiments, no actuator lateral magnets are situated between the first optical package and the second optical package along the axis.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a block diagram of a portable multifunction device with a multiple camera system for portable zoom in accordance with some embodiments.

FIG. 2 depicts a portable multifunction device having a multiple camera system for portable zoom in accordance with some embodiments.

FIG. 3A illustrates a view of an example embodiment of camera module components arranged for multiple visual fields usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIG. 3B illustrates a user interface for a multiple camera system for portable zoom, according to at least some embodiments.

FIG. 3C depicts a side view of an example embodiment of camera module components usable for a multiple camera system for portable zoom with optical image stabilization, according to at least some embodiments.

FIGS. 4A-D illustrate an example embodiment of camera module components including paired side magnet arrays usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIGS. 4 E-H depict an example embodiment of camera module components including paired side magnet arrays usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIGS. 4I-L illustrate an example embodiment of camera module components including paired side magnet arrays usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIG. 5 depicts an example embodiment of camera modules including corner magnets in a shared magnet holder usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIGS. 6A-E illustrate an example embodiment of camera module components including shared magnets usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIGS. 7A-C illustrate an example embodiment of camera module components including shared magnets usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIGS. 8A-E illustrate an example embodiment of camera module components including stationary magnets usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIGS. 9A-D depict an example embodiment of camera module components including stationary magnets usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIGS. 10A-D illustrate an example embodiment of camera module components including stationary magnets usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIGS. 11A-C depict an example embodiment of camera module components including shielded magnets usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIGS. 12A-G depict example embodiments of camera module components including arrays of magnets omitting a center magnet between modules and usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIGS. 13A-B depict example embodiments of camera module components including arrays of magnets omitting a center magnet between modules and usable for a multiple camera system for portable zoom, according to at least some embodiments.

FIG. 14A is a flow chart of a method usable in a multiple camera system for portable zoom, according to at least some embodiments.



FIG. 14B is a flow chart of a method usable in a multiple camera system for portable zoom, according to at least some embodiments.

FIG. 15 illustrates an example computer system configured to implement aspects of the system and method for camera control, according to some embodiments.

This specification includes references to “one embodiment” or “an embodiment.” The appearances of the phrases “in one embodiment” or “in an embodiment” do not necessarily refer to the same embodiment. Particular features, structures, or characteristics may be combined in any suitable manner consistent with this disclosure.

“Comprising.” This term is open-ended. As used in the appended claims, this term does not foreclose additional structure or steps. Consider a claim that recites: “An apparatus comprising one or more processor units . . . .” Such a claim does not foreclose the apparatus from including additional components (e.g., a network interface unit, graphics circuitry, etc.).

“Configured To.” Various units, circuits, or other components may be described or claimed as “configured to” perform a task or tasks. In such contexts, “configured to” is used to connote structure by indicating that the units/circuits/components include structure (e.g., circuitry) that performs those task or tasks during operation. As such, the unit/circuit/component can be said to be configured to perform the task even when the specified unit/circuit/component is not currently operational (e.g., is not on). The units/circuits/components used with the “configured to” language include hardware—for example, circuits, memory storing program instructions executable to implement the operation, etc. Reciting that a unit/circuit/component is “configured to” perform one or more tasks is expressly intended not to invoke 35 U.S.C. §112, sixth paragraph, for that unit/circuit/component. Additionally, “configured to” can include generic structure (e.g., generic circuitry) that is manipulated by software and/or firmware (e.g., an FPGA or a general-purpose processor executing software) to operate in manner that is capable of performing the task(s) at issue. “Configure to” may also include adapting a manufacturing process (e.g., a semiconductor fabrication facility) to fabricate devices (e.g., integrated circuits) that are adapted to implement or perform one or more tasks.

“First,” “Second,” etc. As used herein, these terms are used as labels for nouns that they precede, and do not imply any type of ordering (e.g., spatial, temporal, logical, etc.). For example, a buffer circuit may be described herein as performing write operations for “first” and “second” values. The terms “first” and “second” do not necessarily imply that the first value must be written before the second value.

“Based On.” As used herein, this term is used to describe one or more factors that affect a determination. This term does not foreclose additional factors that may affect a determination. That is, a determination may be solely based on those factors or based, at least in part, on those factors. Consider the phrase “determine A based on B.” While in this case, B is a factor that affects the determination of A, such a phrase does not foreclose the determination of A from also being based on C. In other instances, A may be determined based solely on B.

#### DETAILED DESCRIPTION

##### Introduction to Multiple Cameras for Optical Zoom

Some embodiments include methods and/or systems for using multiple cameras to provide optical zoom to a user. Some embodiments include a first camera unit of a multi-

function device capturing a first image of a first visual field. A second camera unit of the multifunction device simultaneously captures a second image of a second visual field. In some embodiments, the first camera unit includes a first optical package with a first focal length. In some embodiments, the second camera unit includes a second optical package with a second focal length. In some embodiments, the first focal length is different from the second focal length, and the first visual field is a subset of the second visual field.

In some embodiments, a camera system of a multifunction device, includes a first camera unit of the multifunction device for capturing a first image of a first visual field. In some embodiments, the first camera unit includes a first optical image stabilization actuator for moving a first optical package configured for a first focal length. The camera system further includes second camera unit of the multifunction device for simultaneously capturing a second image of a second visual field. In some embodiments, the second camera unit includes a second optical image stabilization actuator for moving a second optical package configured for a second focal length. In some embodiments, the first focal length is different from the second focal length. In some embodiments, the first focal length being different from the second focal length includes both the first focal length and the second focal length being adjustable ranges, which may or may not overlap.

In some embodiments, the camera system includes a shared magnet positioned between the first camera unit and the second camera unit to generate magnetic fields usable in creating motion in both the first camera actuator and the second camera actuator. In some embodiments, the camera system includes a shared magnet positioned between the first camera unit and the second camera unit to generate magnetic fields usable in creating motion in both the first camera actuator and the second camera actuator.

In some embodiments, the camera system further includes a first actuator lateral magnet positioned opposite the shared magnet with respect to an optical axis of the first camera unit. In some embodiments, the camera system further includes a pair of first actuator transverse magnets situated opposite one another with respect to an axis between the shared magnet and the first actuator lateral magnet. In some embodiments, the camera system further includes a second actuator lateral magnet positioned opposite the shared magnet with respect to an optical axis of the second camera unit. In some embodiments, the camera system further includes a pair of second actuator transverse magnets situated opposite one another with respect to an axis between the shared magnet and the second actuator lateral magnet.

In some embodiments, the camera system includes a shared magnet holder to which are attached one or more magnets of the first camera unit and one or more magnets of the second camera unit used to generate magnetic fields usable in creating motion in one or more of the first camera actuator and the second camera actuator. In some embodiments, the camera system includes one or more stationary magnets secured at fixed positions relative to image sensors of the first camera unit and the second camera unit to generate magnetic fields usable in creating motion in one or more of the first camera actuator and the second camera actuator.

In some embodiments, the second camera unit includes a second central magnet array situated along the axis between the first optics package of the first camera unit and the second optics package of the second camera unit. In some embodiments, the second central magnet array includes an



## 5

second central upper magnet having a first polarity and a second central lower magnet having a polarity antiparallel to the first polarity. In some embodiments, the second camera unit includes a second distal magnet array situated opposite the second central magnet array with respect to the second optics package of the second camera unit. In some embodiments, the second distal magnet array includes a second distal lower magnet having the first polarity and a second distal upper magnet.

In some embodiments, the first camera unit includes a first central magnet array situated along an axis between a first optics package of the first camera unit and a second optics package of the second camera unit. In some embodiments, the first central magnet array includes a first central upper magnet having a first polarity and a first central lower magnet having a polarity antiparallel to the first polarity. In some embodiments, the first camera unit includes a first distal magnet array situated opposite the first central magnet array with respect to the first optics package of the first camera unit. In some embodiments, the first distal magnet array includes a first distal lower magnet having the first polarity and a first distal upper magnet having the polarity antiparallel to the first polarity.

In some embodiments, a magnetic shield is included between the first optical image stabilization actuator and the second optical image stabilization actuator.

In some embodiments, a metallic shield is included between the first optical image stabilization actuator and the second optical image stabilization actuator. In some embodiments, the metallic shield includes steel including at least a quantity of iron, a quantity of manganese, a quantity of Sulphur, a quantity of phosphorus, and a quantity of carbon. In some embodiments, shielding is articulated to individual magnets of the first optical image stabilization actuator and the second optical image stabilization actuator.

In some embodiments, metallic shields are articulated to respective ones of the magnets of the first optical image stabilization actuator and respective ones of the magnets of the second optical image stabilization actuator to reduce magnetic interference between the first optical image stabilization actuator and the second optical image stabilization actuator.

In some embodiments, a method for capturing images with multiple cameras of a multifunction device includes providing optical image stabilization to the multiple cameras. In some embodiments, the method includes a first camera unit of a multifunction device capturing a first image of a first visual field. In some embodiments, the method includes a second camera unit of the multifunction device simultaneously capturing a second image of a second visual field. In some embodiments, the first camera unit includes a first optical package with a first focal length. In some embodiments, the second camera unit includes a second optical package with a second focal length. In some embodiments, the first focal length is different from the second focal length, and the first visual field is a subset of the second visual field. In some embodiments, the method includes providing optical image stabilization to the first camera unit, and providing optical image stabilization to the second camera unit.

In some embodiments, the providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include moving the first camera unit and the second camera unit independently of one another.

In some embodiments, the providing optical image stabilization to the first camera unit and the providing optical

## 6

image stabilization to the second camera unit further include moving the first camera unit and the second camera unit in unison.

In some embodiments, the providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include generating a first magnetic field in the first camera unit and a second magnetic field in the second camera unit based on a magnet shared between the first camera unit and the second camera unit.

In some embodiments, the providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include moving the first camera unit and the second camera unit in unison through operation of a first camera unit actuator and a second camera unit actuator that share a central magnet.

In some embodiments, the providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include moving the first camera unit and the second camera unit in unison through operation of a first camera unit actuator and a second camera unit actuator that share a magnet holder.

Some embodiments include a non-transitory computer-readable storage medium, storing program instructions computer-executable to implement capturing a first image of a first visual field with a first camera unit of a multifunction device, simultaneously capturing a second image of a second visual field with a second camera unit of the multifunction device, providing optical image stabilization to the first camera unit, and providing optical image stabilization to the second camera unit.

In some embodiments, the first camera unit includes a first optical package with a first focal length, the second camera unit includes a second optical package with a second focal length, the first focal length is different from the second focal length, and the first visual field is a subset of the second visual field.

In some embodiments, the program instructions computer-executable to implement providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include program instructions computer-executable to implement moving the first camera unit and the second camera unit independently of one another.

In some embodiments, the program instructions computer-executable to implement providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include program instructions computer-executable to implement moving the first camera unit and the second camera unit in unison.

In some embodiments, the program instructions computer-executable to implement providing optical image stabilization to the first camera unit and the program instructions computer-executable to implement providing optical image stabilization to the second camera unit further include program instructions computer-executable to implement generating a first magnetic field in the first camera unit and a second magnetic field in the second camera unit based on a magnet shared between the first camera unit and the second camera unit.

In some embodiments, the program instructions computer-executable to implement providing optical image stabilization to the first camera unit and the program instructions computer-executable to implement providing optical image stabilization to the second camera unit further include program instructions computer-executable to implement



moving the first camera unit and the second camera unit in unison through operation of a first camera unit actuator and a second camera unit actuator that share a magnet holder.

In some embodiments, a camera system of a multifunction device includes a first camera unit of a multifunction device for capturing a first image of a first visual field. In some embodiments, the first camera unit includes a first actuator for moving a first optical package configured for a first focal length. In some embodiments, a camera system of a multifunction device includes a second camera unit of the multifunction device for simultaneously capturing a second image of a second visual field. In some embodiments, the second camera unit includes a second actuator for moving a second optical package configured for a second focal length. In some embodiments, the second actuator includes a second actuator lateral magnet. In some embodiments, the first optical package and the second optical package are situated between the first actuator lateral magnet and the second actuator lateral magnet along an axis between the first actuator lateral magnet and the second actuator lateral magnet. In some embodiments, no actuator lateral magnets are situated between the first optical package and the second optical package along the axis.

In some embodiments, the first actuator lateral magnet and the second actuator lateral magnet have polarities aligned antiparallel to one another. In some embodiments, the first camera unit and the second camera unit each include a respective first pair of first actuator transverse magnets situated opposite one another with respect to the axis between the first actuator lateral magnet and the second actuator lateral magnet, and the first camera unit and the second camera unit each include a respective second pair of first actuator transverse magnets situated opposite one another with respect to the axis between the first actuator lateral magnet and the second actuator lateral magnet.

In some embodiments, the magnets of the respective first pair of first actuator transverse magnets have polarity alignments parallel to the respective alignments of corresponding respective magnets of the first pair of second actuator transverse magnets.

In some embodiments, the magnets of the respective first pair of first actuator transverse magnets have polarity alignments antiparallel to the respective alignments of corresponding respective magnets of the first pair of second actuator transverse magnets.

In some embodiments, the first actuator lateral magnet and the second actuator lateral magnet have polarities aligned at right angles to polarities of the respective first pair of first actuator transverse magnets.

Some embodiments further include coils aligned with current circulating in a plane parallel to a plane in which the first actuator lateral magnet and the second actuator lateral magnet have polarities aligned.

In some embodiments, a camera unit of a multifunction device, includes an optical package and an actuator for moving the optical package to a first focal length. In some embodiments, the actuator includes a lateral magnet to one side of the optical package, and a first pair of first actuator transverse magnets situated on sides opposite one another with respect to an axis between the optical package and the lateral magnet. In some embodiments, the lateral magnet is situated one on one side of the optical package at which no transverse magnets are present. In some embodiments, no actuator lateral magnet is situated on a remaining side of the optical package at which neither the lateral magnet nor the transverse magnets are situated.

In some embodiments, In some embodiments, coils are aligned with current circulating in a plane parallel to a plane in which the lateral magnet and the transverse magnets have polarities aligned.

In some embodiments, coils are aligned with current circulating in a plane perpendicular to a plane in which the lateral magnet and the transverse magnets have polarities aligned.

In some embodiments, a second pair of first actuator transverse magnets is situated opposite one another with respect to the axis between the lateral magnet and the optical package. In some embodiments, the magnets of the first pair of transverse magnets have polarity alignments antiparallel to one another.

In some embodiments, the magnets of the second pair of transverse magnets have polarity alignments antiparallel to one another. In some embodiments, the magnets of the first pair of transverse magnets have polarity alignments antiparallel to magnets of the second pair of transverse magnets situated on a same side of the axis between the lateral magnet and the optical package.

Some embodiments include an actuator having a lateral magnet for moving an optical package, wherein the lateral magnet is situated to one side of the optical package, and a first pair of first actuator transverse magnets situated on sides opposite one another with respect to an axis between the optical package and the lateral magnet. In some embodiments, the lateral magnet is situated one on one side of the optical package at which no transverse magnets are present, and no actuator lateral magnet is situated on a remaining side of the optical package at which neither the lateral magnet nor the transverse magnets are situated.

In some embodiments, coils are aligned with current circulating in a plane parallel to a plane in which the lateral magnet and the transverse magnets have polarities aligned. In some embodiments, coils are aligned with current circulating in a plane perpendicular to a plane in which the lateral magnet and the transverse magnets have polarities aligned.

In some embodiments, a second pair of first actuator transverse magnets situated opposite one another with respect to the axis between the lateral magnet and the optical package. In some embodiments, the magnets of the first pair of transverse magnets have polarity alignments antiparallel to one another. In some embodiments, the magnets of the second pair of transverse magnets have polarity alignments antiparallel to one another.

In some embodiments, the first image and the second image are preserved to a storage medium as separate data structures. In some embodiments, the first image and second image are of different media types. For example, in some embodiments, the first image is a moving image data structure captured at a first frame rate. In some embodiments, the second image is a moving image data structure captured at a second frame rate. In some embodiments, the second frame rate is faster than the first frame rate. In some embodiments, the first image is a still image taken at time  $t(0)$ , and the second image is a moving image data structure captured over a time interval including  $t(0)$ .

Some embodiments assign metadata to the first image and the second image a time indexing feature for establishing that the first image and the second image correspond as having been simultaneously captured or captured at overlapping time intervals. Some embodiments display the first image in a screen interface with a control for switching to display of the second image, and, responsive to an actuation of the control, display the second image in place of the first image. Some embodiments generate a synthetic intermediate



image at least in part from data of the first image and data of the second image. In some embodiments, the synthetic intermediate image has a third focal length different from each of the first focal length and the second focal length, and the synthetic intermediate image has a third visual field different from each of the first visual field and the second visual field. Some embodiments preserve storage of the first image and data of the second image after creation of the synthetic intermediate image.

Some embodiments generate a synthetic result image at least in part from data of the first image and data of the second image. In some embodiments, the synthetic intermediate image has is generated by enhancing the first image using data from the second image. Some embodiments display the first image and the second image in a shared screen interface.

Some embodiments include a camera system of a multifunction device. In some embodiments, the camera system includes a first camera unit of a multifunction device for capturing a first image of a first visual field and a second camera unit of the multifunction device for simultaneously capturing a second image of a second visual field. In some embodiments, the first camera unit includes a first optical package configured for a first focal length. In some embodiments, the second camera unit includes a second optical package configured for a second focal length. In some embodiments, the first focal length is different from the second focal length.

In some embodiments, the camera system includes a processing unit configured to assign to the first image and the second image a time indexing feature for establishing that the first image and the second image were simultaneously captured. In some embodiments, the first camera unit includes a lens having a folded lens configuration with a longer focal length than a lens of the second camera unit, and the second visual field is centered on a second visual axis aligned with a first visual axis on which the first visual field is centered.

In some embodiments, the first camera unit includes a lens having a longer focal length than a lens of the second camera unit, and the second visual field is centered on a second visual axis aligned with a first visual axis on which the first visual field is centered. In some embodiments, the first camera unit includes a first moveable lens and a first image sensor attached a chassis of the camera unit, the second camera unit includes a lens and a second image sensor moveably attached a chassis of the camera unit.

In some embodiments, the first camera unit includes a first moveable lens and a first image sensor attached a chassis of the camera unit, and the second camera unit includes a lens and a second image sensor moveably attached a chassis of the camera unit. In some embodiments, the first camera unit and the second camera unit include a first image processing pipeline and a second image processing pipeline, respectively.

Some embodiments include a non-transitory computer-readable storage medium, storing program instructions, computer-executable to implement a first camera unit of a multifunction device capturing a first image of a first visual field, and a second camera unit of the multifunction device simultaneously capturing a second image of a second visual field. In some embodiments, the first camera unit includes a first optical package with a first focal length, the second camera unit includes a second optical package with a second focal length, the first focal length is different from the second focal length, and the first visual field is a subset of the second visual field.

In some embodiments, the program instructions are further computer-executable to implement assigning metadata to the first image and the second image a time indexing feature for establishing that the first image and the second image correspond as having been simultaneously captured. In some embodiments, the program instructions are further computer-executable to implement displaying the first image in a screen interface with a control for switching to display of the second image, and responsive to an actuation of the control, displaying the second image in place of the first image.

In some embodiments, the program instructions are further computer-executable to implement generating a synthetic intermediate image from data of the first image and data of the second image. In some embodiments, the synthetic intermediate image has a third focal length different from each of the first focal length and the second focal length, and the synthetic intermediate image has a third visual field different from each of the first visual field and the second visual field. In some embodiments, the program instructions are further computer-executable to implement preserving storage of the first image and data of the second image after creation of the synthetic intermediate image. In some embodiments, the synthetic intermediate image has is generated by enhancing the first image using data from the second image. In some embodiments, the program instructions are further computer-executable to implement displaying the first image and the second image in a shared screen interface.

In some embodiments, the first image is a moving image data structure captured at a first frame rate. In some embodiments, the second image is a moving image data structure captured at a second frame rate. In some embodiments, the second frame rate is faster than the first frame rate. In some embodiments, the first image is a still image taken at time  $t(0)$ , and the second image is a moving image data structure captured over a time interval including  $t(0)$ .

#### Multifunction Device Examples

Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the present disclosure. However, it will be apparent to one of ordinary skill in the art that some embodiments may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

It will also be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first contact could be termed a second contact, and, similarly, a second contact could be termed a first contact, without departing from the intended scope. The first contact and the second contact are both contacts, but they are not the same contact.

The terminology used in the description herein is for the purpose of describing particular embodiments only and is not intended to be limiting. As used in the description and the appended claims, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further



## 11

understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

As used herein, the term “if” may be construed to mean “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” may be construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context.

Embodiments of electronic devices, user interfaces for such devices, and associated processes for using such devices are described. In some embodiments, the device is a portable communications device, such as a mobile telephone, that also contains other functions, such as PDA and/or music player functions. Other portable electronic devices, such as laptops, cameras, cell phones, or tablet computers, may also be used. It should also be understood that, in some embodiments, the device is not a portable communications device, but is a desktop computer with a camera. In some embodiments, the device is a gaming computer with orientation sensors (e.g., orientation sensors in a gaming controller). In other embodiments, the device is not a portable communications device, but is a camera.

In the discussion that follows, an electronic device that includes a display and a touch-sensitive surface is described. It should be understood, however, that the electronic device may include one or more other physical user-interface devices, such as a physical keyboard, a mouse and/or a joystick.

The device typically supports a variety of applications, such as one or more of the following: a drawing application, a presentation application, a word processing application, a website creation application, a disk authoring application, a spreadsheet application, a gaming application, a telephone application, a video conferencing application, an e-mail application, an instant messaging application, a workout support application, a photo management application, a digital camera application, a digital video camera application, a web browsing application, a digital music player application, and/or a digital video player application.

The various applications that may be executed on the device may use at least one common physical user-interface device, such as the touch-sensitive surface. One or more functions of the touch-sensitive surface as well as corresponding information displayed on the device may be adjusted and/or varied from one application to the next and/or within a respective application. In this way, a common physical architecture (such as the touch-sensitive surface) of the device may support the variety of applications with user interfaces that are intuitive and transparent to the user.

Attention is now directed toward embodiments of portable devices with cameras. FIG. 1 is a block diagram illustrating portable multifunction device 100 with cameras 164a-b in accordance with some embodiments. Cameras 164a-b are sometimes called “optical sensors” for convenience, and may also be known as or called an optical sensor system. Device 100 may include memory 102 (which may include one or more computer readable storage mediums), memory controller 122, one or more processing units (CPU’s) 120, peripherals interface 118, RF circuitry 108,

## 12

audio circuitry 110, speaker 111, touch-sensitive display system 112, microphone 113, input/output (I/O) subsystem 106, other input or control devices 116, and external port 124. Device 100 may include optical sensors 164a-b. These components may communicate over one or more communication buses or signal lines 103.

It should be appreciated that device 100 is only one example of a portable multifunction device, and that device 100 may have more or fewer components than shown, may combine two or more components, or may have a different configuration or arrangement of the components. The various components shown in various of the figures may be implemented in hardware, software, or a combination of hardware and software, including one or more signal processing and/or application specific integrated circuits.

Memory 102 may include high-speed random access memory and may also include non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Access to memory 102 by other components of device 100, such as CPU 120 and the peripherals interface 118, may be controlled by memory controller 122.

Peripherals interface 118 can be used to couple input and output peripherals of the device to CPU 120 and memory 102. The one or more processors 120 run or execute various software programs and/or sets of instructions stored in memory 102 to perform various functions for device 100 and to process data.

In some embodiments, peripherals interface 118, CPU 120, and memory controller 122 may be implemented on a single chip, such as chip 104. In some other embodiments, they may be implemented on separate chips.

RF (radio frequency) circuitry 108 receives and sends RF signals, also called electromagnetic signals. RF circuitry 108 converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry 108 may include well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry 108 may communicate with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The wireless communication may use any of a variety of communications standards, protocols and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSUPA), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g and/or IEEE 802.11n), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for e-mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), or any other



## 13

suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

Audio circuitry 110, speaker 111, and microphone 113 provide an audio interface between a user and device 100. Audio circuitry 110 receives audio data from peripherals interface 118, converts the audio data to an electrical signal, and transmits the electrical signal to speaker 111. Speaker 111 converts the electrical signal to human-audible sound waves. Audio circuitry 110 also receives electrical signals converted by microphone 113 from sound waves. Audio circuitry 110 converts the electrical signal to audio data and transmits the audio data to peripherals interface 118 for processing. Audio data may be retrieved from and/or transmitted to memory 102 and/or RF circuitry 108 by peripherals interface 118. In some embodiments, audio circuitry 110 also includes a headset jack (e.g., 212, FIG. 2). The headset jack provides an interface between audio circuitry 110 and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

I/O subsystem 106 couples input/output peripherals on device 100, such as touch screen 112 and other input control devices 116, to peripherals interface 118. I/O subsystem 106 may include display controller 156 and one or more input controllers 160 for other input or control devices. The one or more input controllers 160 receive/send electrical signals from/to other input or control devices 116. The other input control devices 116 may include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) 160 may be coupled to any (or none) of the following: a keyboard, infrared port, USB port, and a pointer device such as a mouse. The one or more buttons (e.g., 208, FIG. 2) may include an up/down button for volume control of speaker 111 and/or microphone 113. The one or more buttons may include a push button (e.g., 206, FIG. 2).

Touch-sensitive display 112 provides an input interface and an output interface between the device and a user. Display controller 156 receives and/or sends electrical signals from/to touch screen 112. Touch screen 112 displays visual output to the user. The visual output may include graphics, text, icons, video, and any combination thereof (collectively termed “graphics”). In some embodiments, some or all of the visual output may correspond to user-interface objects.

Touch screen 112 has a touch-sensitive surface, sensor or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch screen 112 and display controller 156 (along with any associated modules and/or sets of instructions in memory 102) detect contact (and any movement or breaking of the contact) on touch screen 112 and converts the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages or images) that are displayed on touch screen 112. In an example embodiment, a point of contact between touch screen 112 and the user corresponds to a finger of the user.

Touch screen 112 may use LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies may be used in other embodiments. Touch screen 112 and display controller 156 may detect contact and any movement or breaking thereof using any of a variety of touch sensing technologies now known or later developed, including but not limited to capacitive,

## 14

resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch screen 112. In an example embodiment, projected mutual capacitance sensing technology is used, such as that found in the iPhone®, iPod Touch®, and iPad® from Apple Inc. of Cupertino, Calif.

Touch screen 112 may have a video resolution in excess of 100 dpi. In some embodiments, the touch screen has a video resolution of approximately 160 dpi. The user may make contact with touch screen 112 using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work primarily with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions calculated by the user.

In some embodiments, in addition to the touch screen, device 100 may include a touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad may be a touch-sensitive surface that is separate from touch screen 112 or an extension of the touch-sensitive surface formed by the touch screen.

Device 100 also includes power system 162 for powering the various components. Power system 162 may include a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

Device 100 may also include optical sensors or cameras 164a-b. Optical sensors 164a-b may include charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. Optical sensors 164a-b receive light from the environment, projected through one or more lens, and converts the light to data representing an image. In conjunction with imaging module 143 (also called a camera module), optical sensors 164a-b may capture still images or video. In some embodiments, an optical sensor is located on the back of device 100, opposite touch screen display 112 on the front of the device, so that the touch screen display may be used as a viewfinder for still and/or video image acquisition. In some embodiments, another optical sensor is located on the front of the device so that the user's image may be obtained for videoconferencing while the user views the other video conference participants on the touch screen display. In embodiments in which multiple cameras or optical sensors 164a-b are supported, each of the multiple cameras or optical sensors 164a-b may include its own photo sensor(s), or the multiple cameras or optical sensors 164a-b may be supported by a shared photo sensor. Likewise, in embodiments in which multiple cameras or optical sensors 164a-b are supported, each of the multiple cameras or optical sensors 164a-b may include its own image processing pipeline of processors and storage units, or the multiple cameras or optical sensors 164a-b may be supported by a image processing pipeline of processors and storage units.

Device 100 may also include one or more proximity sensors 166. FIG. 28 shows proximity sensor 166 coupled to peripherals interface 118. Alternately, proximity sensor 166



## 15

may be coupled to input controller **160** in I/O subsystem **106**. In some embodiments, the proximity sensor turns off and disables touch screen **112** when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call).

Device **100** includes one or more orientation sensors **168**. In some embodiments, the one or more orientation sensors include one or more accelerometers (e.g., one or more linear accelerometers and/or one or more rotational accelerometers). In some embodiments, the one or more orientation sensors include one or more gyroscopes. In some embodiments, the one or more orientation sensors include one or more magnetometers. In some embodiments, the one or more orientation sensors include one or more of global positioning system (GPS), Global Navigation Satellite System (GLONASS), and/or other global navigation system receivers. The GPS, GLONASS, and/or other global navigation system receivers may be used for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device **100**. In some embodiments, the one or more orientation sensors include any combination of orientation/rotation sensors. FIG. **1** shows the one or more orientation sensors **168** coupled to peripherals interface **118**. Alternately, the one or more orientation sensors **168** may be coupled to an input controller **160** in I/O subsystem **106**. In some embodiments, information is displayed on the touch screen display in a portrait view or a landscape view based on an analysis of data received from the one or more orientation sensors.

In some embodiments, the software components stored in memory **102** include operating system **126**, communication module (or set of instructions) **128**, contact/motion module (or set of instructions) **130**, graphics module (or set of instructions) **132**, text input module (or set of instructions) **134**, Global Positioning System (GPS) module (or set of instructions) **135**, arbiter module **157** and applications (or sets of instructions) **136**. Furthermore, in some embodiments memory **102** stores device/global internal state **157**, as shown in FIGS. **1A** and **3**. Device/global internal state **157** includes one or more of: active application state, indicating which applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch screen display **112**; sensor state, including information obtained from the device's various sensors and input control devices **116**; and location information concerning the device's location and/or attitude.

Operating system **126** (e.g., Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

Communication module **128** facilitates communication with other devices over one or more external ports **124** and also includes various software components for handling data received by RF circuitry **108** and/or external port **124**. External port **124** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with the 30-pin connector used on iPod (trademark of Apple Inc.) devices.

Contact/motion module **130** may detect contact with touch screen **112** (in conjunction with display controller **156**) and other touch sensitive devices (e.g., a touchpad or

## 16

physical click wheel). Contact/motion module **130** includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred (e.g., detecting a finger-down event), determining if there is movement of the contact and tracking the movement across the touch-sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module **130** receives contact data from the touch-sensitive surface. Determining movement of the point of contact, which is represented by a series of contact data, may include determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations may be applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., "multitouch"/multiple finger contacts). In some embodiments, contact/motion module **130** and display controller **156** detect contact on a touchpad.

Contact/motion module **130** may detect a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns. Thus, a gesture may be detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (lift off) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by detecting a finger-up (lift off) event.

Graphics module **132** includes various known software components for rendering and displaying graphics on touch screen **112** or other display, including components for changing the intensity of graphics that are displayed. As used herein, the term "graphics" includes any object that can be displayed to a user, including without limitation text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations and the like.

In some embodiments, graphics module **132** stores data representing graphics to be used. Each graphic may be assigned a corresponding code. Graphics module **132** receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller **156**.

Text input module **134**, which may be a component of graphics module **132**, provides soft keyboards for entering text in various applications (e.g., contacts **137**, e-mail **140**, IM **141**, browser **147**, and any other application that needs text input).

GPS module **135** determines the location of the device and provides this information for use in various applications (e.g., to telephone **138** for use in location-based dialing, to camera **143** as picture/video metadata, and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

Applications **136** may include the following modules (or sets of instructions), or a subset or superset thereof:

- contacts module **137** (sometimes called an address book or contact list);
- telephone module **138**;
- video conferencing module **139**;



## 17

e-mail client module **140**;  
 instant messaging (IM) module **141**;  
 workout support module **142**;  
 dual camera module **143** for still and/or video images;  
 image management module **144**;  
 browser module **147**;  
 calendar module **148**;  
 widget modules **149**, which may include one or more of:  
   weather widget **149-1**, stocks widget **149-2**, calculator  
   widget **149-3**, alarm clock widget **149-4**, dictionary  
   widget **149-5**, and other widgets obtained by the user,  
   as well as user-created widgets **149-6**;  
 widget creator module **150** for making user-created wid-  
 gets **149-6**;  
 search module **151**;  
 video and music player module **152**, which may be made  
   up of a video player  
   module and a music player module;  
 notes module **153**;  
 map module **154**; and/or  
 online video module **155**.

Examples of other applications **136** that may be stored in  
 memory **102** include other word processing applications,  
 other image editing applications, drawing applications, pre-  
 sentation applications, JAVA-enabled applications, encryp-  
 tion, digital rights management, voice recognition, and voice  
 replication.

In conjunction with touch screen **112**, display controller  
**156**, contact module **130**, graphics module **132**, and text  
 input module **134**, contacts module **137** may be used to  
 manage an address book or contact list (e.g., stored in  
 application internal state **192** of contacts module **137** in  
 memory **102** or memory **370**), including: adding name(s) to  
 the address book; deleting name(s) from the address book;  
 associating telephone number(s), e-mail address(es), physi-  
 cal address(es) or other information with a name; associating  
 an image with a name; categorizing and sorting names;  
 providing telephone numbers or e-mail addresses to initiate  
 and/or facilitate communications by telephone **138**, video  
 conference **139**, e-mail **140**, or IM **141**; and so forth.

In conjunction with RF circuitry **108**, audio circuitry **110**,  
 speaker **111**, microphone **113**, touch screen **112**, display  
 controller **156**, contact module **130**, graphics module **132**,  
 and text input module **134**, telephone module **138** may be  
 used to enter a sequence of characters corresponding to a  
 telephone number, access one or more telephone numbers in  
 address book **137**, modify a telephone number that has been  
 entered, dial a respective telephone number, conduct a  
 conversation and disconnect or hang up when the conver-  
 sation is completed. As noted above, the wireless commu-  
 nication may use any of a variety of communications  
 standards, protocols and technologies.

In conjunction with RF circuitry **108**, audio circuitry **110**,  
 speaker **111**, microphone **113**, touch screen **112**, display  
 controller **156**, optical sensors **164a-b**, optical sensor con-  
 troller **158**, contact module **130**, graphics module **132**, text  
 input module **134**, contact list **137**, and telephone module  
**138**, videoconferencing module **139** includes executable  
 instructions to initiate, conduct, and terminate a video con-  
 ference between a user and one or more other participants in  
 accordance with user instructions.

In conjunction with RF circuitry **108**, touch screen **112**,  
 display controller **156**, contact module **130**, graphics module  
**132**, and text input module **134**, e-mail client module **140**  
 includes executable instructions to create, send, receive, and  
 manage e-mail in response to user instructions. In conjunc-  
 tion with image management module **144**, e-mail client

## 18

module **140** makes it very easy to create and send e-mails  
 with still or video images taken with dual camera module  
**143**.

In conjunction with RF circuitry **108**, touch screen **112**,  
 display controller **156**, contact module **130**, graphics module  
**132**, and text input module **134**, the instant messaging  
 module **141** includes executable instructions to enter a  
 sequence of characters corresponding to an instant message,  
 to modify previously entered characters, to transmit a  
 respective instant message (for example, using a Short  
 Message Service (SMS) or Multimedia Message Service  
 (MMS) protocol for telephony-based instant messages or  
 using XMPP, SIMPLE, or IMPS for Internet-based instant  
 messages), to receive instant messages and to view received  
 instant messages. In some embodiments, transmitted and/or  
 received instant messages may include graphics, photos,  
 audio files, video files and/or other attachments as are  
 supported in a MMS and/or an Enhanced Messaging Service  
 (EMS). As used herein, "instant messaging" refers to both  
 telephony-based messages (e.g., messages sent using SMS  
 or MMS) and Internet-based messages (e.g., messages sent  
 using XMPP, SIMPLE, or IMPS).

In conjunction with RF circuitry **108**, touch screen **112**,  
 display controller **156**, contact module **130**, graphics module  
**132**, text input module **134**, GPS module **135**, map module  
**154**, and music player module **146**, workout support module  
**142** includes executable instructions to create workouts  
 (e.g., with time, distance, and/or calorie burning goals);  
 communicate with workout sensors (sports devices); receive  
 workout sensor data; calibrate sensors used to monitor a  
 workout; select and play music for a workout; and display,  
 store and transmit workout data.

In conjunction with touch screen **112**, display controller  
**156**, optical sensor(s) **164**, optical sensor controller **158**,  
 contact module **130**, graphics module **132**, and image man-  
 agement module **144**, dual camera module **143** includes  
 executable instructions to capture still images or video  
 (including a video stream) and store them into memory **102**,  
 modify characteristics of a still image or video, or delete a  
 still image or video from memory **102**.

In conjunction with touch screen **112**, display controller  
**156**, contact module **130**, graphics module **132**, text input  
 module **134**, and dual camera module **143**, image manage-  
 ment module **144** includes executable instructions to  
 arrange, modify (e.g., edit), or otherwise manipulate, label,  
 delete, present (e.g., in a digital slide show or album), and  
 store still and/or video images.

In conjunction with RF circuitry **108**, touch screen **112**,  
 display system controller **156**, contact module **130**, graphics  
 module **132**, and text input module **134**, browser module  
**147** includes executable instructions to browse the Internet  
 in accordance with user instructions, including searching,  
 linking to, receiving, and displaying web pages or portions  
 thereof, as well as attachments and other files linked to web  
 pages.

In conjunction with RF circuitry **108**, touch screen **112**,  
 display system controller **156**, contact module **130**, graphics  
 module **132**, text input module **134**, e-mail client module  
**140**, and browser module **147**, calendar module **148** includes  
 executable instructions to create, display, modify, and store  
 calendars and data associated with calendars (e.g., calendar  
 entries, to do lists, etc.) in accordance with user instructions.

In conjunction with RF circuitry **108**, touch screen **112**,  
 display system controller **156**, contact module **130**, graphics  
 module **132**, text input module **134**, and browser module  
**147**, widget modules **149** are mini-applications that may be  
 downloaded and used by a user (e.g., weather widget **149-1**,



stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, and dictionary widget **149-5**) or created by the user (e.g., user-created widget **149-6**). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript file (e.g., Yahoo! Widgets).

In conjunction with RF circuitry **108**, touch screen **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, and browser module **147**, the widget creator module **150** may be used by a user to create widgets (e.g., turning a user-specified portion of a web page into a widget).

In conjunction with touch screen **112**, display system controller **156**, contact module **130**, graphics module **132**, and text input module **134**, search module **151** includes executable instructions to search for text, music, sound, image, video, and/or other files in memory **102** that match one or more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

In conjunction with touch screen **112**, display system controller **156**, contact module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, and browser module **147**, video and music player module **152** includes executable instructions that allow the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or AAC files, and executable instructions to display, present or otherwise play back videos (e.g., on touch screen **112** or on an external, connected display via external port **124**). In some embodiments, device **100** may include the functionality of an MP3 player, such as an iPod (trademark of Apple Inc.).

In conjunction with touch screen **112**, display controller **156**, contact module **130**, graphics module **132**, and text input module **134**, notes module **153** includes executable instructions to create and manage notes, to do lists, and the like in accordance with user instructions.

In conjunction with RF circuitry **108**, touch screen **112**, display system controller **156**, contact module **130**, graphics module **132**, text input module **134**, GPS module **135**, and browser module **147**, map module **154** may be used to receive, display, modify, and store maps and data associated with maps (e.g., driving directions; data on stores and other points of interest at or near a particular location; and other location-based data) in accordance with user instructions.

In conjunction with touch screen **112**, display system controller **156**, contact module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, text input module **134**, e-mail client module **140**, and browser module **147**, online video module **155** includes instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen or on an external, connected display via external port **124**), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats, such as H.264. In some embodiments, instant messaging module **141**, rather than e-mail client module **140**, is used to send a link to a particular online video.

Each of the above identified modules and applications correspond to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (i.e., sets of instructions) need not be implemented as separate software programs, procedures or modules, and thus various subsets of these

modules may be combined or otherwise rearranged in various embodiments. In some embodiments, memory **102** may store a subset of the modules and data structures identified above. Furthermore, memory **102** may store additional modules and data structures not described above.

In some embodiments, device **100** is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device **100**, the number of physical input control devices (such as push buttons, dials, and the like) on device **100** may be reduced.

The predefined set of functions that may be performed exclusively through a touch screen and/or a touchpad include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device **100** to a main, home, or root menu from any user interface that may be displayed on device **100**. In such embodiments, the touchpad may be referred to as a “menu button.” In some other embodiments, the menu button may be a physical push button or other physical input control device instead of a touchpad.

FIG. 2 illustrates a portable multifunction device **100** having a touch screen **112** in accordance with some embodiments. The touch screen may display one or more graphics within user interface (UI) **200**. In this embodiment, as well as others described below, a user may select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers **202** (not drawn to scale in the figure) or one or more styluses **203** (not drawn to scale in the figure).

Device **100** may also include one or more physical buttons, such as “home” or menu button **204**. As described previously, menu button **204** may be used to navigate to any application **136** in a set of applications that may be executed on device **100**. Alternatively, in some embodiments, the menu button is implemented as a soft key in a GUI displayed on touch screen **112**.

In one embodiment, device **100** includes touch screen **112**, menu button **204**, push button **206** for powering the device on/off and locking the device, volume adjustment button(s) **208**, Subscriber Identity Module (SIM) card slot **210**, head set jack **212**, and docking/charging external port **124**. Push button **206** may be used to turn the power on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In an alternative embodiment, device **100** also may accept verbal input for activation or deactivation of some functions through microphone **113**.

It should be noted that, although many of the examples herein are given with reference to optical sensors/cameras **164a-b** (on the front of a device), a rear-facing camera or optical sensor that is pointed opposite from the display may be used instead of or in addition to an optical sensors/cameras **164a-b** on the front of a device.

FIG. 3A illustrates a view of an example embodiment of camera module components arranged for multiple visual fields usable for a multiple camera system for portable zoom, according to at least some embodiments. A portable multifunction device **3080** includes a first optical sensor/camera unit **3082** with a first focal length **3090** for capturing a first visual field **3086** and a second optical sensor/camera unit **3084** with a first focal length **3092** for capturing a second visual field **3088**.



## 21

Some embodiments include a first camera unit **3082** (such as one of the cameras described below with respect to FIG. **3B** and FIG. **3C**) of a multifunction device capturing a first image of a first visual field **3086**. A second camera unit **3084** (such as one of the cameras described below with respect to FIG. **3B** and FIG. **3C**) of the multifunction device **3080** simultaneously captures a second image of a second visual field **3088**. In some embodiments, the first camera unit **3082** includes a first optical package with a first focal length **3090**. In some embodiments, the second camera unit **3084** includes a second optical package (described below with respect to FIG. **3B**, below) with a second focal length **3092**. In some embodiments, the first focal length **3090** is different from the second focal length **3092**, and the first visual field **3086** is a subset of the second visual field **3088**. In some embodiments, the first image and the second image are preserved to a storage medium as separate data structures.

In some embodiments, a camera system of a multifunction device **3080**, includes a first camera unit **3082** of the multifunction device for capturing a first image of a first visual field **3086**. In some embodiments, the first camera unit **3082** includes a first optical image stabilization actuator for moving a first optical package configured for a first focal length **3090**. The camera system further includes second camera **3084** unit of the multifunction device **3080** for simultaneously capturing a

second image of a second visual field **3088**. In some embodiments, the second camera unit **3084** includes a second optical image stabilization actuator for moving a second optical package configured for a second focal length **3092**. In some embodiments, the first focal length **3090** is different from the second focal length **3092**. In some embodiments, the first focal length being different from the second focal length includes both the first focal length and the second focal length being adjustable ranges, which may or may not overlap.

Some embodiments assign metadata to the first image of the first visual field **3086** and the second image of the second visual field **3088** a time indexing feature for establishing that the first image of the first visual field **3086** and the second image of the second visual field **3088** correspond as having been simultaneously captured. Some embodiments display the first image of the first visual field **3086** in a screen interface with a control for switching to display of the second image of the second visual field **3088**, and, responsive to an actuation of the control, display the second image of the second visual field **3088** in place of the first image. Some embodiments generate a synthetic intermediate image at least in part from data of the first image of the first visual field **3086** and data of the second image of the second visual field **3088**. In some embodiments, the synthetic intermediate image has a third focal length different from each of the first focal length **3090** and the second focal length **3092**, and the synthetic intermediate image has a third visual field different from each of the first visual field **3086** and the second visual field **3088**. Some embodiments preserve storage of the first image of the first visual field **3086** and data of the second image of the second visual field **3088** after creation of the synthetic intermediate image.

Some embodiments generate a synthetic result image at least in part from data of the first image of the first visual field **3086** and data of the second image of the second visual field **3088**. In some embodiments, the synthetic intermediate image has is generated by enhancing the first image of the first visual field **3086** using data from the second image of the second visual field **3088**. Some embodiments display the

## 22

first image of the first visual field **3086** and the second image of the second visual field **3088** in a shared screen interface.

Some embodiments include a camera system of a multifunction device. In some embodiments, the camera system includes a first camera unit **3082** of a multifunction device **3080** for capturing a first image of a first visual field **3086** and a second camera unit of the multifunction device for simultaneously capturing a second image of a second visual field **3088**. In some embodiments, the first camera unit **3082** includes a first optical package configured for a first focal length **3090**. In some embodiments, the second camera unit **3084** includes a second optical package configured for a second focal length **3092**. In some embodiments, the first focal length **3090** is different from the second focal length **3092**.

In some embodiments, the camera system includes a processing unit configured to assign to the first image of a first visual field **3086** and the second image a time indexing feature for establishing that the first image and the second image of a second visual field **3088** were simultaneously captured. In some embodiments, the first camera unit **3082** includes a lens having a folded lens configuration (not shown) with a longer focal length **3090** than a focal length **3092** of a lens of the second camera unit **3084**, and the second visual field **3088** is centered on a second visual axis aligned with a first visual axis on which the first visual field **3086** is centered. In some embodiments, the first camera unit **3082** includes a first moveable lens (shown below with respect to FIG. **3B**) and a first image sensor attached a chassis of the camera unit, the second camera unit includes a lens and a second image sensor moveably attached a chassis of the second camera unit **3084**.

In some embodiments, the first camera unit **3082** includes a first moveable lens and a first image sensor attached a chassis of the first **3082** camera unit, and the second camera unit **3084** includes a lens (shown below with respect to FIG. **3B**) and a second image sensor moveably attached a chassis of the second camera unit. In some embodiments, the first camera unit **3082** and the second camera unit **3084** include a first image processing pipeline and a second image processing pipeline, respectively.

In some embodiments, the first image and second image are of different media types. For example, in some embodiments, the first image is a moving image data structure captured at a first frame rate. In some embodiments, the second image is a moving image data structure captured at a second frame rate. In some embodiments, the second frame rate is faster than the first frame rate. In some embodiments, the first image is a still image taken at time  $t(0)$ , and the second image is a moving image data structure captured over a time interval including  $t(0)$ .

In some embodiments, the first image has a first resolution and the second image has a second resolution. An example of the use of a first image that is a moving image data structure at a first frame rate and a second image that is a moving image data structure at a second frame rate arises in that some embodiments include second camera module **3084** recording 720p (also known as 720 pixels of vertical resolution progressive scan) slow motion video at 240 frames per second while first camera module **3082** is capturing 4K (horizontal resolution on the order of 4,000 pixels) video at 30 frames per second. In some embodiments, the analog-to-digital converter bandwidth required for each separate module to achieve the recording is 220-270 Mpixels/s. Achieving the same functionality with conventional single camera module technology requires up to 32 times higher analog-to-digital converter bandwidth for a single camera



module if it is compared to embodiments in which there is a 2× difference in focal length from wide to tele module, providing benefits in terms of power, thermal dissipation, storage bandwidth, storage capacity, and actual achievable frame rates combined with zoom capability.

A use case for some embodiments is well-illustrated with respect to sports photography. In one example use case, it is possible to imagine a user of portable multifunction device **3080** filming a batter in a baseball game. Recording video of the game with portable multifunction device **3080** from bleachers, not shown, a user may decide to zoom in to capture a batter swinging and hitting the ball in slow motion using second camera module **3084** recording 720p slow motion video at 240 frames per second, but may subsequently want to switch to the simultaneously captured 4K video from first camera module **3082** at 30 frames per second of resulting home run in high quality video of the full baseball field, to capture the moments where the opposing team scrambles to catch the ball and the batter is running from base to base. Some embodiments enable this mixed-video capture by simultaneously recording using second camera module **3084** as a telephoto camera module in a 240 frames per second slow motion mode while at the same time using first camera module **3082** as a wide camera module in a 4K at 30 frames per second. After capturing a data structure including both video streams the awesome moment, some embodiments provide for a mixed-video data structure and an interface for the video streams from the two separate camera modules to be manually or automatically edited and combined to create a more engaging media which may contain normal 1080p video, 4K high resolution video, 720p motion video, and still images. In the example described above, this mixed-video media both captures the close up expressions of players, the peak action in slow motion, and frames it all in the context of a great play in a baseball game.

Another example of a use case for some embodiments arises in the context of capturing a child extinguishing candles on a birthday cake. In such an example, one can imagine a child about to blow out the candles on the birthday cake while all her friends are singing a birthday song. In some embodiments, second camera module **3084** can be used as a telephoto camera module to zoom in on the face of the child as she is about to blow out the candles and first camera module **3082** can capture a burst of high resolution still images of her smiling face. In some embodiments, first camera module **3082** is simultaneously capturing standard 1080p 30 frames per second video of the entire group of kids gathered and singing around the cake. Some embodiments provide an editing interface for combining the video stream from the wide camera module, either manually or automatically, with the close up portraits to create a much more engaging media experience which can be shared. As the two camera modules are synchronized in time, the still images can easily be automatically inserted at the right time in a final video stream.

FIG. 3B illustrates a user interface for a multiple camera system for portable zoom, according to at least some embodiments. A portable multifunction device **400** displays a first image of a first visual field **404** captured by a first camera unit and a second image of a second visual field **402** simultaneously captured by a second camera unit of the multifunction device **400**. A zoom control **406** is displayed within first image of a first visual field **404**. In the embodiment shown, zoom control **406** is an area of first image of first visual field **404**, that, in response to control actuation through the touch screen of portable multifunction device

**400**, is used as a control for toggling the display mode for displaying first image of a first visual field **404** captured by a first camera unit and second image of a second visual field **402** simultaneously captured by a second camera unit of the multifunction device **400**.

Some embodiments assign metadata to the first image **404** and the second image **402** for a time indexing feature for establishing that the first image **404** and the second image **402** correspond as having been simultaneously captured. Some embodiments display the first image **404** in a screen interface with a control (e.g., similar to control **406**) for switching to display of the second image **402**, and, responsive to an actuation of the control **406**, display the second image **402** in place of the first image **404**. Some embodiments generate a synthetic intermediate image at least in part from data of the first image **404** and data of the second image **402**.

FIG. 3C depicts a side view of an example embodiment of camera module, according to at least some embodiments. Camera module **3000**, which is an embodiment of cameras **164a-b**, discussed below includes camera components such as an optics module (e.g., a lens barrel) **3002** attached to an optics holder **3003** and a magnet holder **3006**. An image sensor **3070**, which may or may not be mounted on a substrate that is not shown separately in FIG. 3, is attached to a camera module base **3008**. The camera components may further include, in addition to components such as power and remote control connections not shown, a cover **3012** and suspension wires **3020**.

Optics module **3002** may be suspended on the base assembly **3008** by suspension of the upper springs **3030** and the suspension wires **3020**. Camera components may include one or more of, but are not limited to, optics **3002**, optics holder **3003**, magnet holder(s) **3006**, upper spring(s) **3030**, and lower spring(s) **3032**. The upper and lower spring(s) may be collectively referred to herein as optics springs. An optics module (e.g., a lens or lens assembly or lens barrel) **3002** may be screwed, mounted or otherwise held in or by an optics holder **3003**. In at least some embodiments, the optics **3002**/optics holder **3003** assembly may be suspended from or attached to the magnet holder **3006** by upper spring(s) **3030**, and lower spring(s) **3032**. Note that upper spring(s) **3030** and lower spring(s) **3032** are flexible to allow the optics assembly **3000** a range of motion along the Z (optical) axis for optical focusing, wires **3020** are flexible to allow a range of motion on the XY plane orthogonal to the optical axis for optical image stabilization.

Note that, in some embodiments, a camera may not include magnets and magnet holder(s) **3006**, but may include a yoke or other structure **3006** that may be used to help support the optics assembly on suspension wires **3020** via upper springs **3030**. In general, other embodiments of an optics assembly **3000** may include fewer or more components than the example optics assembly **3000** shown in FIG. 3. Also note that, while embodiments show the optics assembly **3000** suspended on wires **3020**, other mechanisms may be used to suspend an optics assembly **3000** in other embodiments.

The autofocus yoke (e.g., magnet holder(s) **3006**) acts as the support chassis structure for the autofocus mechanism of actuator **3000**. The lens carrier (optics holder **3003**) is suspended on the autofocus yoke by an upper autofocus (AF) spring **3030** and a lower optics spring **3032**. In this way when an electric current is applied to the autofocus coil, Lorentz forces are developed due to the presence of the four magnets, and a force substantially parallel to the optical axis is generated to move the lens carrier, and hence lens, along



25

the optical axis, relative to the support structure of the autofocus mechanism of the actuator, so as to focus the lens. In addition to suspending the lens carrier and substantially eliminating parasitic motions, the upper spring 3030 and lower spring 3032 also resist the Lorentz forces, and hence convert the forces to a displacement of the lens. This basic architecture shown in FIG. 3 is typical of some embodiments, in which optical image stabilization function includes moving the entire autofocus mechanism of the actuator (supported by the autofocus yoke) in linear directions orthogonal to the optical axis, in response to user handshake, as detected by some means, such a two or three axis gyroscope, which senses angular velocity. The handshake of interest is the changing angular tilt of the camera in 'pitch and yaw directions', which can be compensated by said linear movements of the lens relative to the image sensor.

In at least some embodiments, the suspension of the autofocus mechanism on the actuator 3000 support structure may be achieved by the use of four corner wires 3020, for example wires with a circular cross-section. Each wire 3020 acts as a flexure beams capable of bending with relatively low stiffness, thus allowing motion in both optical image stabilization degrees-of-freedom. However, wire 3020 is in some embodiments relatively stiff in directions parallel to the optical axis, as this would require the wire to stretch or buckle, thus substantially preventing parasitic motions in these directions. In addition, the presence of four such wires, appropriately separated allows them to be stiff in the parasitic tilt directions of pitch and yaw, thus substantially preventing relative dynamic tilt between the lens and image sensor. This may be seen by appreciating that each wire 3020 is stiff in directions that require it to change in length, and hence the fixed points at the ends of each wire (eight points in total) will substantially form the vertices of a parallelepiped for all operational positions of the optical image stabilization mechanism.

FIGS. 4A-D illustrate an example embodiment of camera module components including paired side magnet arrays usable for a multiple camera system for portable zoom, according to at least some embodiments.

Each of FIGS. 4A-4C includes a different view of a camera unit 400a-c, which is one embodiment of a first camera unit or a second camera unit of a multifunction device for capturing a first image of a first or second visual field. Each of camera units 400a-c includes one of optics packages 402a-c and one of optical image stabilization actuators 404a-c for moving the optical package 402a-c configured for focal length or an adjustable range of focal lengths. FIG. 4D is a legend indicating the motion capability of various components illustrated in each of FIGS. 4A-C.

Optical stabilization actuators 404a-c include magnet arrays 406a-c and 418a-c, which include central magnet arrays 406a-c and distal magnet arrays 418a-c. In some embodiments, central magnet arrays 406a-c and distal magnet arrays 418a-c are arranged in opposing and mutually-cancelling pairs of magnets. Additionally, in some embodiments, lower magnet arrays 420b-c and upper magnet array 422b are arranged in analogous opposing and mutually-cancelling pairs. In some embodiments, the designation of central magnet arrays 406a-c and distal magnet arrays 418a-c is arbitrary, with the difference between them being the opposite and mutually cancelling arrangement of magnets in the respective arrays. In some embodiments, the designation of central magnet arrays 406a-c and distal magnet arrays 418a-c is defined with respect to a center line between a pair of camera units in a camera system, as described elsewhere herein.

26

As portrayed in FIGS. 4A-4D, camera units 400a-c include central magnet arrays 406a-c, which can be situated along the axis between the optics package of a first camera unit and an optics package of a second camera unit. Central magnet array 406a includes a central upper magnet 410a having a first polarity and a central lower magnet 412a having a polarity antiparallel to the first polarity. Camera units 400a-c also include distal magnet arrays 418a-c situated opposite the central magnet arrays 406a-c with respect to the optics packages 402a-c of the camera units 400a-c. Distal magnet array 418a includes a distal lower magnet 416a having the first polarity and a distal upper magnet 414a having the polarity antiparallel to the first polarity.

In some embodiments, camera units 400a-c include distal magnet arrays 418a-c that are situated opposite the central magnet arrays 406a-c with respect to the optics packages 402a-c of the camera units 400a-c and the distal magnet arrays 418a-c include a distal lower magnet 416a having the first polarity and a distal upper magnet 414a having the polarity antiparallel to the first polarity.

In some embodiments, camera units 400a-c include upper autofocus coils 408a-b and lower autofocus coils 428a attached to optics packages 402a-c for moving optics packages 402a-c in any of an X, Y, or Z axis, where, in some embodiments, the Z axis is the optical axis of optics packages 402a-c (thus, with at three degrees of freedom). In some embodiments, central magnet arrays 406a-c and distal magnet arrays 418a-c interact with upper latitudinal SP coils 426a-c and lower SP latitudinal coils 424a and 424c. As one of ordinary skill in the art will readily comprehend, while specific orientations of magnets

FIGS. 4E-G depict an example embodiment of camera module components including paired side magnet arrays usable for a multiple camera system for portable zoom, according to at least some embodiments. Each of FIGS. 4E-4G includes a different view of a camera unit 400e-g, which is one embodiment of a first camera unit or a second camera unit of a multifunction device for capturing a first image of a first or second visual field. Each of camera units 400e-g includes one of optics packages 402e-g and one of optical image stabilization actuators 404e (not labeled in FIG. 4F or shown in FIG. 4G) for moving the optical package 402e-g configured for focal length or an adjustable range of focal lengths. FIG. 4H is a legend indicating the motion capability of various components illustrated in each of FIGS. 4E-G. As one of skill in the art will readily comprehend in light of having viewed the present disclosure, while particular orientations of magnets and directions of current are shown for the embodiments depicted herein, other embodiments exist, in which the direction of current and orientations of magnetic poles are reversed, and such embodiments are within the scope and intent of the present disclosure.

Optical stabilization actuator 404e includes magnet arrays 406e-f and 418e-f, which include central magnet arrays 406e-f and distal magnet arrays 418e-f. In some embodiments, central magnet arrays 406e-f and distal magnet arrays 418e-f are arranged in opposing and mutually-cancelling pairs of magnets. Additionally, in some embodiments, lower magnet arrays 420f and upper magnet array 422f are arranged in analogous opposing and mutually-cancelling pairs. In some embodiments, the designation of central magnet arrays 406e-f and distal magnet arrays 418e-f is arbitrary, with the difference between them being the opposite and mutually cancelling arrangement of magnets in the respective arrays. In some embodiments, the designation of central magnet arrays 406e-f and distal magnet arrays 418e-f



is defined with respect to a center line between a pair of camera units in a camera system, as described elsewhere herein. In some embodiments, an optical package or optics module is a set of components (e.g., a lens barrel) housing one or more lens elements and other components for connecting a lens to an actuator for moving the lens relative to an image sensor.

As portrayed in FIGS. 4E-4G, camera units **400e-g** include central magnet arrays **406e-f**, which can be situated along the axis between the optics package of a first camera unit and an optics package of a second camera unit. Central magnet array **406e** includes a central upper magnet **410e** having a first polarity and a central lower magnet **412e** having a polarity antiparallel to the first polarity. Camera units **400e-f** also include distal magnet arrays **418e-f** situated opposite the central magnet arrays **406e-f** with respect to the optics packages **402e-g** of the camera units **400e-g**. Distal magnet array **418e** includes a distal lower magnet **416e** having the first polarity and a distal upper magnet **414e** having the polarity antiparallel to the first polarity.

In some embodiments, camera units **400e-g** include distal magnet arrays **418a-c** that are situated opposite the central magnet arrays **406a-c** with respect to the optics packages **402a-c** of the camera units **400e-f** and the distal magnet arrays **418e-f** include a distal lower magnet **416e** having the first polarity and a distal upper magnet **414e** having the polarity antiparallel to the first polarity.

In some embodiments, camera units **400e-g** include upper autofocus coils **408e-f** and lower autofocus coils **428e** attached to optics packages **402e-f** for moving optics packages **402e-f** in any of an X, Y, or Z axis, where, in some embodiments, the Z axis is the optical axis of optics packages **402e-f** (thus, with at three degrees of freedom). In some embodiments, central magnet arrays **406e-f** and distal magnet arrays **418e-f** interact with central coils **426e** and **426g** and radial SP coils **424e-g**.

FIGS. 4I-L illustrate an example embodiment of camera module components including paired side magnet arrays usable for a multiple camera system for portable zoom, according to at least some embodiments. Each of FIGS. 4I-4K includes a different view of a camera unit **400i-k**, which is one embodiment of a first camera unit or a second camera unit of a multifunction device for capturing a first image of a first or second visual field. Each of camera units **400i-k** includes one of optics packages **402i-k** and one of optical image stabilization actuators **404i** (not labeled in FIG. 4J or shown in FIG. 4K) for moving the optical package **402i-j** configured for focal length or an adjustable range of focal lengths. FIG. 4L is a legend indicating the motion capability of various components illustrated in each of FIGS. 4I-J.

Optical stabilization actuator **404i** includes magnet arrays **406i-j** and **418i-j**, which include central magnet arrays **406i-j** and distal magnet arrays **418i-j**. In some embodiments, central magnet arrays **406i-j** and distal magnet arrays **418i-j** are arranged in opposing and mutually-cancelling pairs of magnets. Additionally, in some embodiments, lower magnet array **420j** and upper magnet array **422j** are arranged in analogous opposing and mutually-cancelling pairs. In some embodiments, the designation of central magnet arrays **406i-j** and distal magnet arrays **418i-j** is arbitrary, with the difference between them being the opposite and mutually cancelling arrangement of magnets in the respective arrays. In some embodiments, the designation of central magnet arrays **406i-j** and distal magnet arrays **418i-j** is defined with respect to a center line between a pair of camera units in a camera system, as described elsewhere herein.

As portrayed in FIGS. 4i-4k, camera units **400i-k** include central magnet arrays **406i-j**, which can be situated along the axis between the optics package of a first camera unit and an optics package of a second camera unit. Central magnet array **406i** includes a central upper magnet **410i** having a first polarity and a central lower magnet **412i** having a polarity antiparallel to the first polarity. Camera units **400i-j** also include distal magnet arrays **418i-j** situated opposite the central magnet arrays **406i-j** with respect to the optics packages **402i-j** of the camera units **400i-j**. Distal magnet array **418i** includes a distal lower magnet **416i** having the first polarity and a distal upper magnet **414i** having the polarity antiparallel to the first polarity.

In some embodiments, camera units **400i-j** include distal magnet arrays **418i-j** that are situated opposite the central magnet arrays **406i-i** with respect to the optics packages **402i-j** of the camera units **400i-j** and the distal magnet arrays **418i-j** include a distal lower magnet **416i** having the first polarity and a distal upper magnet **414i** having the polarity antiparallel to the first polarity.

In some embodiments, camera units **400i-j** include upper autofocus coils **408i-j** and lower autofocus coils **428j** attached to optics packages **402i-j** for moving optics packages **402i-j** in any of an X, Y, or Z axis, where, in some embodiments, the Z axis is the optical axis of optics packages **402e-f** (thus, with at three degrees of freedom). In some embodiments, central magnet arrays **406i-j** and distal magnet arrays **418i-j** interact with top SP coils **426i-j** and lower SP coils **424i** and **424k**.

FIG. 5 depicts an example embodiment of camera modules including corner magnets in a shared magnet holder usable for a multiple camera system for portable zoom, according to at least some embodiments.

In some embodiments, the VCM applies the same OIS correction to both modules together at any given time. In some embodiments, OIS correction is a function of focal length and is different for the two modules. Thus, at any given moment the VCM can stabilize only one module.

In some embodiments, video capture involves shooting with only one lens at a time and the VCM can successfully command OIS correction as user switches between the 1× and 4× lenses.

In some embodiments, image fusion combines the wide field of view from a 1× lens and the narrow focus from a 4× lens to produce a wide angle image with extra detail and sharpness around the subject (image center). It can also be used to generate depth data (stereo vision). In some embodiments, dual OIS solution allows commanding different corrections on the two OIS modules simultaneously. In some embodiments, in fast exposure and shots with low subject motion, the two OIS corrections can be applied in succession producing the same effect.

A dual camera unit **500** includes one embodiment of a first camera unit **502a** and a second camera unit **502b** of a multifunction device for capturing a first image of a first or second visual field. Each of camera units **500a-b** includes one of optics packages (circular feature) **504a-b** and one of optical image stabilization actuators **506a-b** using autofocus coils **520a-b** for moving the optical package **506a-b** configured for focal length or an adjustable range of focal lengths.

In some embodiments, the camera system of dual camera unit **500** includes a shared magnet holder **508** to which are attached one or more magnets **510a-516a** of the first camera unit and one or more magnets **510b-516b** of the second camera unit used to generate magnetic fields usable in creating motion in one or more of the first camera actuator **506a** and the second camera actuator **506b**. In some embodi-



ments, the camera system of dual camera unit **500** includes a shared magnet holder **508** to which are attached one or more diagonal-angled corner magnets **510a-516a** of the first camera unit and one or more diagonal-angled corner magnets **510b-516b** of the second camera unit used to generate magnetic fields usable in creating motion in one or more of the first camera actuator **506a** and the second camera actuator **506b**, though other embodiments may employ shared magnet holder **508** with linear magnet pairs or linear magnets as described elsewhere herein.

FIGS. 6A-E illustrate an example embodiment of camera module components including shared magnets usable for a multiple camera system for portable zoom, according to at least some embodiments. In some embodiments, by using side magnets the VCMs can share one magnet between the two modules. In some embodiments, a shared magnet helps reduce the lens center to center distance i.e. parallax reduction (as well as over all size. A square design also permits symmetric dynamics. In some embodiments, the VCM applies the same OIS correction to both modules together at any given time. In some embodiments, OIS correction is a function of focal length and is different for the two modules. Thus, at any given moment the VCM in some embodiments stabilizes only one module.

In some embodiments, capture involves shooting with only one lens at a time and the VCM can successfully command OIS correction as user switches between the 1× and 4× lenses. In some embodiments, image fusion combines the wide field of view from the 1× lens and the narrow focus from the 4× lens to produce a wide angle image with extra detail and sharpness around the subject (image center). In some embodiments, it can also be used to generate depth data (stereo vision).

A dual camera unit **600a-e** includes one embodiment of a first camera unit **602a-e** and a second camera unit **618a-d** of a multifunction device for capturing a first image of a first or second visual field. Each of camera units **602a-e** and **618a-d** includes one of optics packages **604b-e** and **606b-d** and actuator components for moving the optical packages **604b-e** and **606b-d** configured for focal length or an adjustable range of focal lengths. In some embodiments, the camera system of dual camera unit **600a-e** includes a shared magnet holder **608a-e** to which are attached one or more shared magnets **620a** and one or more unshared magnets **610a-612a** of the first camera unit **602a-e** and one or more magnets **613a-615a** of the second camera unit **618a-d** used to generate magnetic fields usable in creating motion in one or more of the first camera unit **602a-e** and the second camera unit **618a-d**. In some embodiments, the camera system of dual camera unit **600a-e** includes coils **630a-638e** of the first camera unit **602a-e** and one or more coils **640a-648e** of the second camera unit used to generate force usable in creating motion in one or more of the first camera unit **602a-e** and the second camera unit **618a-d**. Suspension wires **650c-652e** and a covering can **654b-e** are also shown. In some embodiments, coil **636b-d** and coil **646b-d** are a single shared coil. In some embodiments, shared magnet holder **608a-e** is a pair of separate units articulated together.

FIGS. 7A-C illustrate an example embodiment of camera module components including shared magnets usable for a multiple camera system for portable zoom, according to at least some embodiments. A dual camera unit **700a-c** includes one embodiment of a first camera unit **702a-c** and a second camera unit **718a-b** of a multifunction device for capturing a first image of a first or second visual field. Each of camera units **702a-c** and **718a-b** includes one of optics packages **704a-c** and **706a-b** and actuator components for

moving the optical packages **704a-c** and **706a-b** configured for focal length or an adjustable range of focal lengths. In some embodiments, the camera system of dual camera unit **700a-c** includes a shared magnet holder **708a-b** to which are attached one or more shared magnets **720a** and one or more unshared magnets **710a-712a** of the first camera unit **702a-c** and one or more magnets **713a-715a** of the second camera unit **718a-b** used to generate magnetic fields usable in creating motion in one or more of the first camera unit **702a-c** and the second camera unit **718a-d**. In some embodiments, the indicated magnetic field directions of all of shared magnet **720a** and one or more unshared magnets **710a-712a** of the first camera unit **702a-c** are oriented inward toward optics packages **704a-c** while the indicated magnetic field directions of all of shared magnet **720a** and one or more magnets **713a-715a** of the second camera unit **718a-b** are oriented outward away from optics packages **704a-b**.

In some embodiments, the camera system of dual camera unit **700a-e** includes coils **730a-736c** of the first camera unit **702a-c** and one or more coils **740a-744b** of the second camera unit used to generate force usable in creating motion in one or more of the first camera unit **702a-c** and the second camera unit **718a-b**. Suspension wires **750c** and a covering can **754a-c** are also shown. In some embodiments, coil **746a-b** is a single shared coil. In some embodiments, shared magnet holder **708a-b** is a pair of separate units articulated together.

FIGS. 8A-E illustrate an example embodiment of camera module components including stationary magnets usable for a multiple camera system for portable zoom, according to at least some embodiments. In some embodiments, the VCM architecture of FIGS. 8A-E is based on a stationary magnet design, allowing for two OIS VCMs to be placed side to side with reduced stroke loss due to magnetic interactions between the two. In some embodiments, the VCMs can be used to independently command the required OIS corrections on the two modules.

In some embodiments, the current design allows for inclusion of 3 different independent drive channels (Drive X, Drive Y, Drive Z) and a 4th Auxiliary channel for Zoom or Electrochromic aperture.

Camera units **802a-c** include one embodiment of a first camera unit and/or a second camera unit of a multifunction device for capturing a first image of a first or second visual field. Each of camera units **802a-c** includes one of optics carriers **804a-b** containing an optics package and actuator components for moving the optical packages in optics carriers **804a-b** configured for focal length or an adjustable range of focal lengths.

In some embodiments, the camera systems of camera units **802a-c** include one or more stationary magnets **810a-816a** of the camera units **802a-c** to generate magnetic fields usable in creating motion in one or more of the camera unit **802a-c**.

In some embodiments, the camera system of camera units **802a-c** includes coils **830b-832b** set in a coil base **828a-c** and coil holder **826a-b** of the camera unit **802a-c** used to generate force usable in creating motion in the camera unit **802a-c**. Suspension and control wires **858a-872b** provide for both suspension and transmission of control and data signals. A coil race track **832b-838c** and a base **840b-c** are also shown. Wires **870a-872a** provide AF (+/-) signals. Wires **858a-860a** provide Aux (+/-) signals. Wires **862a-864a** provide SP\_X (+/-) signals. Wires **866a-868a** provide SP\_Y (+/-) signals.



FIG. 8E contains a legend for understanding the various parts of FIGS. 8A-8C. FIG. 8D shows articulation of control wires **862a-864a** to frames **888d-890d**.

FIGS. 9A-D depict an example embodiment of camera module components including stationary magnets usable for a multiple camera system for portable zoom, according to at least some embodiments. Dual camera units **900a-c** include embodiments of a first camera unit **902a-c** and a second camera unit **918a-c** of a multifunction device for capturing a first image of a first or second visual field.

Each of camera units **902a-c** and **918a-c** includes one of optics packages **904a-b** and **909a-b** and actuator components for moving the optical packages **904a-b** and **909a-b** configured for focal length or an adjustable range of focal lengths.

In some embodiments, the camera system of dual camera unit **900a-c** includes independent magnet holders **907a-908b** to which are attached one or more one or more unshared magnets **910a-913c** of the first camera unit **902a-c** and one or more magnets **914a-917c** of the second camera unit **918a-c** used to generate magnetic fields usable in creating motion in one or more of the first camera unit **902a-c** and the second camera unit **918a-c**. In some embodiments, the camera system of dual camera unit **900a-c** includes coils **932b-934b** of the first camera unit **902b** and one or more coils **936b-938b** of the second camera unit used to generate force usable in creating motion in one or more of the first camera unit **902a-c** and the second camera unit **918a-c**. Suspension wires **950a-964b** are also shown. Coil bases **980a-982c**, actuator bases **990b-992c**, and SP coil race tracks **970b-978c**. FIG. 9D is a legend illustrating the components of FIGS. 9A-9C.

FIGS. 10A-D illustrate an example embodiment of camera module components including stationary magnets usable for a multiple camera system for portable zoom, according to at least some embodiments. Dual camera units **1000a-c** include embodiments of a first camera unit **1002a-c** sharing a magnet **1015a-1015c** a second camera unit **1018a-c** of a multifunction device for capturing a first image of a first or second visual field.

Each of camera units **1002a-c** and **1018a-c** includes one of optics packages **1004a-b** and **1009a-b** and actuator components for moving the optical packages **1004a-b** and **1009a-b** configured for focal length or an adjustable range of focal lengths.

In some embodiments, the camera system of dual camera unit **1000a-c** includes independent magnet holders **1007a-1008b** to which are attached one or more one or more unshared magnets **1010a-1013c** of the first camera unit **1002a-c** and one or more magnets **1014a-c**, shared magnets **1015a-c** and **1016a-1017c** of the second camera unit **1018a-c** used to generate magnetic fields usable in creating motion in one or more of the first camera unit **1002a-c** and the second camera unit **1018a-c**. In some embodiments, the camera system of dual camera unit **1000a-c** includes coils **1032b-1034b** of the first camera unit **1002b** and one or more coils **1036b-1038b** of the second camera unit used to generate force usable in creating motion in one or more of the first camera unit **1002a-c** and the second camera unit **1018a-c**. Suspension wires **1050a-1064b** are also shown. Coil bases **1080a-1082c**, actuator bases **1090b-1092c**, and SP coil race tracks **1070b-1078c**. FIG. 10D is a legend illustrating the components of FIGS. 10A-10C.

FIGS. 11A-C depict an example embodiment of camera module components including shielded magnets usable for a multiple camera system for portable zoom, according to at least some embodiments. Some embodiments use high per-

meability metal to shield the magnetic field restricting it to stay within the magnet holder, thereby limiting undesirable interaction forces or disturbances from nearby magnetic materials or stray fields from other electro magnetic devices. An example using high permeability **1010** steel is shown in FIGS. 11A-11C. In some embodiments, shielding material is coated or glued or insert molded into a plastic magnet holder. In some embodiments, shielding material is used to make the entire magnet holder (e.g., in metal injection molding).

Each of camera units **1102a-1104a** includes one of optics carriers **1106a**, **1106b** and **1108a** containing an optics package and actuator components for moving the optical packages in optics carriers **1106a-b** and **1108a** configured for focal length or an adjustable range of focal lengths.

In some embodiments, the camera systems of camera units **1102a-1104a** include one or more magnets **1110a-1116a** and **1110b** of the camera units **1102a-1104a** with metallic shields **1120a-1126a** and **1120b** of thickness  $t$  **1128b** set in magnet holders **1130a-1136a** and **1130b** to generate magnetic fields usable in creating motion in one or more of the camera unit **1102a-1104a**. In some embodiments, camera units **1102a-1104a** operate independently.

In some embodiments, the camera system of camera units **1102a-c** includes coils **1140a-1146a** and **1140b** set in a coil base **1121a-c** and coil holder **1126a-b** of the camera unit **1102a-c** used to generate force usable in creating motion in the camera unit **1102a-c** for movement relative to bases **1152a-1154a**. FIG. 11C is a legend for use with FIGS. 11A-11B.

FIGS. 12A-G depict example embodiments of camera module components including arrays of magnets omitting a center magnet between modules and usable for a multiple camera system for portable zoom, according to at least some embodiments. Some embodiments use a magnet arrangement that enables side by side (dual) Optical Image Stabilization (OIS) camera modules in portable devices, with minimal magnetic interaction between adjacent modules.

While other magnet arrangements described herein have four total magnets: one in each corner of the module or one along each side of the module, the embodiments described below and illustrated in FIGS. 12A-G include a single side magnet on one side and four total magnets on the adjacent sides, each pair with opposite polarity, which totals five magnets per module. The remaining single side (e.g., center between the two actuators) does not have a permanent magnet. In some embodiments, opposing polarity magnets function to contain the fringing flux field, which might otherwise be a a primary source of interaction forces between adjacent camera modules. Such embodiments reduce the interaction forces.

In some embodiments, each of FIGS. 12A-12G includes a view of a set of magnets (or a set of magnets and coils) usable for a dual camera unit, which unit is one embodiment of a first camera unit and a second camera unit of a multifunction device for capturing a first image of a first or second visual field. In some embodiments, magnets **1202a-g** are lateral magnets of a first camera unit. In some embodiments, magnets **1204a-g** are lateral magnets of a second camera unit. In some embodiments, the camera systems **1200a-g** each include a first pair of first actuator transverse magnets **1206a-g** and **1208a-g** situated opposite one another with respect to an axis between lateral magnets **1202a-g** and lateral magnets **1204a-g**. In some embodiments, the camera systems **1200a-g** further each comprise a second pair of first actuator transverse magnets **1210a-g** and **1212a-g** situated



opposite one another with respect to an axis between lateral magnets **1202a-g** and lateral magnets **1204a-g**.

In some embodiments, the camera systems **1200a-g** each further include a first pair of second actuator transverse magnets **1226a-g** and **1228a-g** situated opposite one another with respect to an axis between lateral magnets **1202a-g** and lateral magnets **1204a-g**. In some embodiments, the camera systems **1200a-g** each further include a second pair of second actuator transverse magnets **1230a-g** and **1232a-g** situated opposite one another with respect to an axis between lateral magnets **1202a-g** and lateral magnets **1204a-g**. In some embodiments, magnets **1230a-g**, **1226a-g**, **1208a-g**, and **1210a-g** are oriented with a first polarity antiparallel to a second polarity with which magnets **1228a-g**, **1226a-g**, **1206a-g** and **1212a-g** are oriented.

In some embodiments, magnets **1206a-g** and **1210a-g** are arrayed in a pair with polarities opposite one another, and magnets **1232a-g** and **1226a-g** are arrayed in a pair with polarities opposite one another. In some embodiments, magnets **1206a-g** and **1210a-g** are arrayed in a pair with polarities opposite one another, and magnets **1232a-g** and **1226a-g** are arrayed in a pair with polarities opposite one another. In some embodiments, OIS coils **1240a-g** interact with magnetic fields generated by respective ones of magnets **1202a-g-1232a-g**. Some embodiments of orientations **1252b-c-1258b-c** are provided in FIGS. **12B-C**. In some embodiments, autofocus coils **1282e-1288g** interact with magnetic fields generated by respective ones of magnets **1202a-g-1232a-g**. Note that magnetic field orientations within any of FIGS. **12A-G** may differ from magnetic field orientations of any other of FIGS. **12A-G**, such that the use of “first orientation” or “second orientation” is arbitrary as between diagrams and represents many possible embodiments without departing from the scope or intent of the disclosure contained herein.

FIGS. **13A-B** depict example embodiments of camera module components including arrays of magnets omitting a center magnet between modules and usable for a multiple camera system for portable zoom, according to at least some embodiments.

In some embodiments, each of FIGS. **13A-13B** includes a view of a set of magnets usable for a dual camera unit, which unit is one embodiment of a first camera unit and a second camera unit of a multifunction device for capturing a first image of a first or second visual field. In some embodiments, magnets **1302a-b** are lateral magnets of a first camera unit. In some embodiments, magnets **1304a-b** are lateral magnets of a second camera unit. In some embodiments, the camera systems **1300a-b** each include a first pair of first actuator transverse magnets **1306a-b** and **1308a-b** situated opposite one another with respect to an axis between lateral magnets **1302a-b** and lateral magnets **1304a-b**. In some embodiments, the camera systems **1300a-b** further each comprise a second pair of first actuator transverse magnets **1310a** and **1313a** situated opposite one another with respect to an axis between lateral magnets **1302a-b** and lateral magnets **1304a-b**.

In some embodiments, the camera systems **1300a-b** each further include a first pair of second actuator transverse magnets **1326a** and **1328a** situated opposite one another with respect to an axis between lateral magnets **1302a-b** and lateral magnets **1304a-b**. In some embodiments, the camera systems **1300a-b** each further include a second pair of second actuator transverse magnets **1330a-b** and **1332a-b** situated opposite one another with respect to an axis between lateral magnets **1302a-b** and lateral magnets **1304a-b**. In some embodiments, magnets **1330a-b**, **1326a**, **1306a-b**,

and **1313a** are oriented with a first polarity **1352b** antiparallel to a second polarity **1354b** with which magnets **1328a**, **1332a-b**, **1310a** and **1308a-b** are oriented.

In some embodiments, magnets **1306a-b** and **1310a** are arrayed in a pair with polarities opposite one another, and magnets **1332a-b** and **1326a** are arrayed in a pair with polarities opposite one another. In some embodiments, magnets **1306a-b** and **1310a** are arrayed in a pair with polarities opposite one another, and magnets **1332a-b** and **1326a** are arrayed in a pair with polarities opposite one another.

FIG. **14A** is a flow chart of a method usable in a multiple camera system for portable zoom, according to at least some embodiments. A first camera unit of a multifunction device, having a first optical package with a first focal length, captures a first image of a first visual field (block **1400**). A second camera unit of the multifunction device, having a second optical package with a second focal length different from the first focal length simultaneously captures a second image of a second visual field that is a subset of the first visual field (block **1402**). The first image and the second image are preserved to a storage medium as separate data structures (block **1404**). The first image is displayed in a screen interface with a control for switching to display of the second image (block **1406**). Responsive to an actuation of the control, the second image is displayed in place of the first image (block **1408**).

FIG. **14B** is a flow chart of a method usable in a multiple camera system for portable zoom, according to at least some embodiments. A first camera unit of a multifunction device, having a first optical package with a first focal length, captures a first image of a first visual field (block **1410**). A second camera unit of the multifunction device, having a second optical package with a second focal length different from the first focal length simultaneously captures a second image of a second visual field that is a subset of the first visual field (block **1412**). Optical image stabilization is provided to the first camera unit (block **1414**). Optical image stabilization is provided to the second camera unit (block **1414**).

#### Example Computer System

FIG. **15** illustrates an example computer system **1500** that may be configured to execute any or all of the embodiments described above. In different embodiments, computer system **1500** may be any of various types of devices, including, but not limited to, a personal computer system, desktop computer, laptop, notebook, tablet, slate, pad, or netbook computer, mainframe computer system, handheld computer, workstation, network computer, a camera, a set top box, a mobile device, a consumer device, video game console, handheld video game device, application server, storage device, a television, a video recording device, a peripheral device such as a switch, modem, router, or in general any type of computing or electronic device.

Various embodiments of a dual-prime camera system as described herein, including embodiments of single frame camera active optical tilt alignment correction, as described herein may be executed in one or more computer systems **1500**, which may interact with various other devices. Note that any component, action, or functionality described above with respect to FIGS. **1-10** may be implemented on one or more computers configured as computer system **1500** of FIG. **15**, according to various embodiments. In the illustrated embodiment, computer system **1500** includes one or more processors **1510** coupled to a system memory **1520** via an input/output (I/O) interface **1530**. Computer system **1500** further includes a network interface **1540** coupled to I/O interface **1530**, and one or more input/output devices **1550**,



such as cursor control device **1560**, keyboard **1570**, and display(s) **1580**. In some cases, it is contemplated that embodiments may be implemented using a single instance of computer system **1500**, while in other embodiments multiple such systems, or multiple nodes making up computer system **1500**, may be configured to host different portions or instances of embodiments. For example, in one embodiment some elements may be implemented via one or more nodes of computer system **1500** that are distinct from those nodes implementing other elements.

In various embodiments, computer system **1500** may be a uniprocessor system including one processor **1510**, or a multiprocessor system including several processors **1510** (e.g., two, four, eight, or another suitable number). Processors **1510** may be any suitable processor capable of executing instructions. For example, in various embodiments processors **1510** may be general-purpose or embedded processors implementing any of a variety of instruction set architectures (ISAs), such as the x86, PowerPC, SPARC, or MIPS ISAs, or any other suitable ISA. In multiprocessor systems, each of processors **1510** may commonly, but not necessarily, implement the same ISA.

System memory **1520** may be configured to store camera control program instructions **1522** and/or camera control data accessible by processor **1510**. In various embodiments, system memory **1520** may be implemented using any suitable memory technology, such as static random access memory (SRAM), synchronous dynamic RAM (SDRAM), nonvolatile/Flash-type memory, or any other type of memory. In the illustrated embodiment, program instructions **1522** may be configured to implement a lens control application **1524** incorporating any of the functionality described above. Additionally, existing camera control data **1532** of memory **1520** may include any of the information or data structures described above. In some embodiments, program instructions and/or data may be received, sent or stored upon different types of computer-accessible media or on similar media separate from system memory **1520** or computer system **1500**. While computer system **1500** is described as implementing the functionality of functional blocks of previous Figures, any of the functionality described herein may be implemented via such a computer system.

In one embodiment, I/O interface **1530** may be configured to coordinate I/O traffic between processor **1510**, system memory **1520**, and any peripheral devices in the device, including network interface **1540** or other peripheral interfaces, such as input/output devices **1550**. In some embodiments, I/O interface **1530** may perform any necessary protocol, timing or other data transformations to convert data signals from one component (e.g., system memory **1520**) into a format suitable for use by another component (e.g., processor **1510**). In some embodiments, I/O interface **1530** may include support for devices attached through various types of peripheral buses, such as a variant of the Peripheral Component Interconnect (PCI) bus standard or the Universal Serial Bus (USB) standard, for example. In some embodiments, the function of I/O interface **1530** may be split into two or more separate components, such as a north bridge and a south bridge, for example. Also, in some embodiments some or all of the functionality of I/O interface **1530**, such as an interface to system memory **1520**, may be incorporated directly into processor **1510**.

Network interface **1540** may be configured to allow data to be exchanged between computer system **1500** and other devices attached to a network **1585** (e.g., carrier or agent devices) or between nodes of computer system **1500**. Net-

work **1585** may in various embodiments include one or more networks including but not limited to Local Area Networks (LANs) (e.g., an Ethernet or corporate network), Wide Area Networks (WANs) (e.g., the Internet), wireless data networks, some other electronic data network, or some combination thereof. In various embodiments, network interface **1540** may support communication via wired or wireless general data networks, such as any suitable type of Ethernet network, for example; via telecommunications/telephony networks such as analog voice networks or digital fiber communications networks; via storage area networks such as Fibre Channel SANs, or via any other suitable type of network and/or protocol.

Input/output devices **1550** may, in some embodiments, include one or more display terminals, keyboards, keypads, touchpads, scanning devices, voice or optical recognition devices, or any other devices suitable for entering or accessing data by one or more computer systems **1500**. Multiple input/output devices **1550** may be present in computer system **1500** or may be distributed on various nodes of computer system **1500**. In some embodiments, similar input/output devices may be separate from computer system **1500** and may interact with one or more nodes of computer system **1500** through a wired or wireless connection, such as over network interface **1540**.

As shown in FIG. **15**, memory **1520** may include program instructions **1522**, which may be processor-executable to implement any element or action described above. In one embodiment, the program instructions may implement the methods described above. In other embodiments, different elements and data may be included. Note that data may include any data or information described above.

Those skilled in the art will appreciate that computer system **1500** is merely illustrative and is not intended to limit the scope of embodiments. In particular, the computer system and devices may include any combination of hardware or software that can perform the indicated functions, including computers, network devices, Internet appliances, PDAs, wireless phones, pagers, etc. Computer system **1500** may also be connected to other devices that are not illustrated, or instead may operate as a stand-alone system. In addition, the functionality provided by the illustrated components may in some embodiments be combined in fewer components or distributed in additional components. Similarly, in some embodiments, the functionality of some of the illustrated components may not be provided and/or other additional functionality may be available.

Those skilled in the art will also appreciate that, while various items are illustrated as being stored in memory or on storage while being used, these items or portions of them may be transferred between memory and other storage devices for purposes of memory management and data integrity. Alternatively, in other embodiments some or all of the software components may execute in memory on another device and communicate with the illustrated computer system via inter-computer communication. Some or all of the system components or data structures may also be stored (e.g., as instructions or structured data) on a computer-accessible medium or a portable article to be read by an appropriate drive, various examples of which are described above. In some embodiments, instructions stored on a computer-accessible medium separate from computer system **1500** may be transmitted to computer system **1500** via transmission media or signals such as electrical, electromagnetic, or digital signals, conveyed via a communication medium such as a network and/or a wireless link. Various embodiments may further include receiving, sending or



storing instructions and/or data implemented in accordance with the foregoing description upon a computer-accessible medium. Generally speaking, a computer-accessible medium may include a non-transitory, computer-readable storage medium or memory medium such as magnetic or optical media, e.g., disk or DVD/CD-ROM, volatile or non-volatile media such as RAM (e.g. SDRAM, DDR, RDRAM, SRAM, etc.), ROM, etc. In some embodiments, a computer-accessible medium may include transmission media or signals such as electrical, electromagnetic, or digital signals, conveyed via a communication medium such as network and/or a wireless link.

The methods described herein may be implemented in software, hardware, or a combination thereof, in different embodiments. In addition, the order of the blocks of the methods may be changed, and various elements may be added, reordered, combined, omitted, modified, etc. Various modifications and changes may be made as would be obvious to a person skilled in the art having the benefit of this disclosure. The various embodiments described herein are meant to be illustrative and not limiting. Many variations, modifications, additions, and improvements are possible. Accordingly, plural instances may be provided for components described herein as a single instance. Boundaries between various components, operations and data stores are somewhat arbitrary, and particular operations are illustrated in the context of specific illustrative configurations.

Additional descriptions of embodiments:

CLAUSE 1: A camera system of a multifunction device, including:

- a first camera unit of a multifunction device for capturing a first image of a first visual field, wherein the first camera unit includes a first actuator for moving a first optical package configured for a first focal length; and
- a second camera unit of the multifunction device for simultaneously capturing a second image of a second visual field, wherein the second camera unit includes a second actuator for moving a second optical package configured for a second focal length the second actuator includes a second actuator lateral magnet;
- the first optical package and the second optical package are situated between the first actuator lateral magnet and the second actuator lateral magnet along an axis between the first actuator lateral magnet and the second actuator lateral magnet;
- no actuator lateral magnets are situated between the first optical package and the second optical package along the axis.

CLAUSE 2: The camera system of clause 1, wherein the first actuator lateral magnet and the second actuator lateral magnet have polarities aligned antiparallel to one another.

CLAUSE 3: The camera system of any of clauses 1-2, wherein

- the first camera unit and the second camera unit each include a respective first pair of first actuator transverse magnets situated opposite one another with respect to the axis between the first actuator lateral magnet and the second actuator lateral magnet; and
- the first camera unit and the second camera unit each include a respective second pair of first actuator transverse magnets situated opposite one another with respect to the axis between the first actuator lateral magnet and the second actuator lateral magnet.

CLAUSE 4: The camera system of clause 3, wherein the magnets of the respective first pair of first actuator transverse magnets have polarity alignments parallel to the respective alignments of corresponding respective magnets of the first pair of second actuator transverse magnets.

CLAUSE 5: The camera system of clause 3, wherein the magnets of the respective first pair of first actuator transverse magnets have polarity alignments antiparallel to the respective alignments of corresponding respective magnets of the first pair of second actuator transverse magnets.

CLAUSE 6: The camera system of clause 5, wherein the first actuator lateral magnet and the second actuator lateral magnet have polarities aligned at right angles to polarities of the respective first pair of first actuator transverse magnets.

CLAUSE 7: The camera system of any of clauses 1-6, further including

- coils aligned with current circulating in a plane parallel to a plane in which the first actuator lateral magnet and the second actuator lateral magnet have polarities aligned.

CLAUSE 8: A camera unit of a multifunction device, including:

- an optical package;
- an actuator for moving the optical package to a first focal length, wherein the actuator includes a lateral magnet to one side of the optical package, a first pair of first actuator transverse magnets situated on sides opposite one another with respect to an axis between the optical package and the lateral magnet, wherein the lateral magnet is situated one on one side of the optical package at which no transverse magnets are present; and

wherein no actuator lateral magnet is situated on a remaining side of the optical package at which neither the lateral magnet nor the transverse magnets are situated.

CLAUSE 9: The camera unit of clause 8, further including: coils aligned with current circulating in a plane parallel to a plane in which the lateral magnet and the transverse magnets have polarities aligned.

CLAUSE 10: The camera unit of any of clauses 8-9, further including:

- coils aligned with current circulating in a plane perpendicular to a plane in which the lateral magnet and the transverse magnets have polarities aligned.

CLAUSE 11: The camera unit of any of clauses 8-10, further including:

- a second pair of first actuator transverse magnets situated opposite one another with respect to the axis between the lateral magnet and the optical package.

CLAUSE 12: The camera unit of clause 11, further including:

- the magnets of the first pair of transverse magnets have polarity alignments antiparallel to one another.

CLAUSE 13: The camera unit of clause 11, further including:

- the magnets of the second pair of transverse magnets have polarity alignments antiparallel to one another.

CLAUSE 14: The camera unit of clause 11, further including:

- the magnets of the first pair of transverse magnets have polarity alignments antiparallel to magnets of the sec-



39

ond pair of transverse magnets situated on a same side of the axis between the lateral magnet and the optical package.

CLAUSE 15: An actuator, including:

a lateral magnet for moving an optical package, wherein the lateral magnet is situated to one side of the optical package,

a first pair of first actuator transverse magnets situated on sides opposite one another with respect to an axis between the optical package and the lateral magnet, wherein

the lateral magnet is situated one on one side of the optical package at which no transverse magnets are present; and

wherein no actuator lateral magnet is situated on a remaining side of the optical package at which nether the lateral magnet nor the transverse magnets are situated.

CLAUSE 16: The actuator of clause 15, further including: coils aligned with current circulating in a plane parallel to a plane in which the lateral magnet and the transverse magnets have polarities aligned.

CLAUSE 17: The actuator of any of clauses 15-16, further including:

coils aligned with current circulating in a plane perpendicular to a plane in which the lateral magnet and the transverse magnets have polarities aligned.

CLAUSE 18: The actuator of any of clauses 15-17, further including:

a second pair of first actuator transverse magnets situated opposite one another with respect to the axis between the lateral magnet and the optical package.

CLAUSE 19: The actuator of clause 18, wherein:

the magnets of the first pair of transverse magnets have polarity alignments antiparallel to one another.

CLAUSE 20: The actuator of clause 18, wherein:

the magnets of the second pair of transverse magnets have polarity alignments antiparallel to one another.

CLAUSE 21: A camera system of a multifunction device, including:

a first camera unit of a multifunction device for capturing a first image of a first visual field, wherein

the first camera unit includes a first optical image stabilization actuator for moving a first optical package configured for a first focal length; and

a second camera unit of the multifunction device for simultaneously capturing a second image of a second visual field, wherein

the second camera unit includes a second optical image stabilization actuator for moving a second optical package configured for a second focal length, and the first focal length is different from the second focal length.

CLAUSE 22: The camera system of clause 21, wherein:

the camera system includes a shared magnet positioned between the first camera unit and the second camera unit to generate magnetic fields usable in creating motion in both the first camera actuator and the second camera actuator.

CLAUSE 23: The camera system of any of clauses 21-22, wherein:

the camera system includes a shared magnet positioned between the first camera unit and the second camera unit to generate magnetic fields usable in creating motion in both the first camera actuator and the second camera actuator;

40

the camera system further includes a first actuator lateral magnet positioned opposite the shared magnet with respect to an optical axis of the first camera unit;

the camera system further includes a pair of first actuator transverse magnets situated opposite one another with respect to an axis between the shared magnet and the first actuator lateral magnet;

the camera system further includes a second actuator lateral magnet positioned opposite the shared magnet with respect to an optical axis of the second camera unit; and

the camera system further includes a pair of second actuator transverse magnets situated opposite one another with respect to an axis between the shared magnet and the second actuator lateral magnet.

CLAUSE 24: The camera system of any of clauses 21-23, wherein:

the camera system includes a shared magnet holder to which are attached one or more magnets of the first camera unit and one or more magnets of the second camera unit used to generate magnetic fields usable in creating motion in one or more of the first camera actuator and the second camera actuator.

CLAUSE 25: The camera system of any of clauses 21-24, wherein:

the camera system includes one or more stationary magnets secured at fixed positions relative to image sensors of the first camera unit and the second camera unit to generate magnetic fields usable in creating motion in one or more of the first camera actuator and the second camera actuator.

CLAUSE 26: The camera system of any of clauses 21-25, wherein:

the second camera unit includes a second central magnet array situated along the axis between the first optics package of the first camera unit and the second optics package of the second camera unit;

the second central magnet array includes an second central upper magnet having a first polarity and a second central lower magnet having a polarity antiparallel to the first polarity;

the second camera unit includes a second distal magnet array situated opposite the second central magnet array with respect to the second optics package of the second camera unit; and

the second distal magnet array includes a second distal lower magnet having the first polarity and a second distal upper magnet having the polarity antiparallel to the first polarity.

CLAUSE 27: The camera system of clause 26, wherein:

the first camera unit includes a first central magnet array situated along an axis between a first optics package of the first camera unit and a second optics package of the second camera unit;

the first central magnet array includes a first central upper magnet having a first polarity and a first central lower magnet having a polarity antiparallel to the first polarity;

the first camera unit includes a first distal magnet array situated opposite the first central magnet array with respect to the first optics package of the first camera unit; and

the first distal magnet array includes a first distal lower magnet having the first polarity and a first distal upper magnet having the polarity antiparallel to the first polarity.



## 41

CLAUSE 28: The camera system of any of clauses 21-27, further including:

a magnetic shield between the first optical image stabilization actuator and the second optical image stabilization actuator.

CLAUSE 29: The camera system of any of clauses 21-28, further including:

a metallic shield between the first optical image stabilization actuator and the second optical image stabilization actuator, wherein

the metallic shield includes steel including at least a quantity of iron, a quantity of manganese, a quantity of Sulphur, a quantity of phosphorus, and a quantity of carbon.

CLAUSE 30: A method, including:

a first camera unit of a multifunction device capturing a first image of a first visual field;

a second camera unit of the multifunction device simultaneously capturing a second image of a second visual field, wherein

the first camera unit includes a first optical package with a first focal length,

the second camera unit includes a second optical package with a second focal length,

the first focal length is different from the second focal length, and

the first visual field is a subset of the second visual field;

providing optical image stabilization to the first camera unit; and

providing optical image stabilization to the second camera unit.

CLAUSE 31: The method of clause 30, wherein:

the providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include moving the first camera unit and the second camera unit independently of one another.

CLAUSE 32: The method of any of clauses 30-31, wherein:

the providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include moving the first camera unit and the second camera unit in unison.

CLAUSE 33: The method of any of clauses 30-32, wherein:

the providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include generating a first magnetic field in the first camera unit and a second magnetic field in the second camera unit based on a magnet shared between the first camera unit and the second camera unit.

CLAUSE 34: The method of any of clauses 30-33, wherein:

the providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include moving the first camera unit and the second camera unit in unison through operation of a first camera unit actuator and a second camera unit actuator that share a central magnet.

CLAUSE 35: The method of any of clauses 30-34, wherein:

the providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include moving the first camera unit and the second camera unit in unison through operation of a first camera unit actuator and a second camera unit actuator that share a magnet holder.

## 42

CLAUSE 36: A non-transitory computer-readable storage medium, storing program instructions, wherein the program instructions are computer-executable to implement:

capturing a first image of a first visual field with a first camera unit of a multifunction device;

simultaneously capturing a second image of a second visual field with a second camera unit of the multifunction device, wherein

the first camera unit includes a first optical package with a first focal length,

the second camera unit includes a second optical package with a second focal length,

the first focal length is different from the second focal length, and

the first visual field is a subset of the second visual field;

providing optical image stabilization to the first camera unit; and

providing optical image stabilization to the second camera unit.

CLAUSE 37: The non-transitory computer-readable storage medium of clause 36, wherein:

the program instructions computer-executable to implement providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include program instructions computer-executable to implement moving the first camera unit and the second camera unit independently of one another.

CLAUSE 38: The non-transitory computer-readable storage medium of any of clauses 36-37, wherein:

the program instructions computer-executable to implement providing optical image stabilization to the first camera unit and the providing optical image stabilization to the second camera unit further include program instructions computer-executable to implement moving the first camera unit and the second camera unit in unison.

CLAUSE 39: The non-transitory computer-readable storage medium of any of clauses 36-38, wherein

the program instructions computer-executable to implement providing optical image stabilization to the first camera unit and the program instructions computer-executable to implement providing optical image stabilization to the second camera unit further include program instructions computer-executable to implement generating a first magnetic field in the first camera unit and a second magnetic field in the second camera unit based on a magnet shared between the first camera unit and the second camera unit.

CLAUSE 40: The non-transitory computer-readable storage medium of any of clauses 36-39, wherein:

the program instructions computer-executable to implement providing optical image stabilization to the first camera unit and the program instructions computer-executable to implement providing optical image stabilization to the second camera unit further include program instructions computer-executable to implement moving the first camera unit and the second camera unit in unison through operation of a first camera unit actuator and a second camera unit actuator that share a magnet holder.

Other allocations of functionality are envisioned and may fall within the scope of claims that follow. Finally, structures and functionality presented as discrete components in the example configurations may be implemented as a combined structure or component. These and other variations, modi-



43

fications, additions, and improvements may fall within the scope of embodiments as defined in the claims that follow.

What is claimed is:

1. A camera system of a multifunction device, comprising:  
a first camera unit of the multifunction device, the first camera unit for capturing a first image of a first visual field, wherein:  
the first camera unit comprises a first actuator for moving a first optical package configured for a first focal length, and  
the first actuator comprises:  
a first actuator lateral magnet to move the first optical package in one or more directions orthogonal to a first optical axis of the first optical package; and  
a first pair of actuator transverse magnets to move the first optical package along at least the first optical axis, the first pair of actuator transverse magnets situated on opposite sides of one another with respect to the first optical package; and  
a second camera unit of the multifunction device, the second camera unit for capturing a second image of a second visual field, wherein:  
the second camera unit comprises a second actuator for moving a second optical package configured for a second focal length, and  
the second actuator comprises a second actuator lateral magnet to move the second optical package in one or more directions orthogonal to a second optical axis of the second optical package;  
wherein:  
the first optical package and the second optical package are situated between the first actuator lateral magnet and the second actuator lateral magnet along an axis between the first actuator lateral magnet and the second actuator lateral magnet; and  
no actuator lateral magnets are situated between the first optical package and the second optical package along the axis.
2. The camera system of claim 1, wherein the first actuator lateral magnet and the second actuator lateral magnet have polarities aligned antiparallel to one another.
3. The camera system of claim 1, wherein:  
the first actuator and the second actuator each comprise a respective first pair of first actuator transverse magnets situated opposite one another with respect to the axis between the first actuator lateral magnet and the second actuator lateral magnet; and  
the first actuator and the second actuator each comprise a respective second pair of first actuator transverse magnets situated opposite one another with respect to the axis between the first actuator lateral magnet and the second actuator lateral magnet.
4. The camera system of claim 3, wherein:  
the magnets of the respective first pair of first actuator transverse magnets have polarity alignments parallel to the respective alignments of corresponding respective magnets of the first pair of second actuator transverse magnets.
5. The camera system of claim 3, wherein:  
the magnets of the respective first pair of first actuator transverse magnets have polarity alignments antiparallel to the respective alignments of corresponding respective magnets of the first pair of second actuator transverse magnets.

44

6. The camera system of claim 5, wherein:  
the first actuator lateral magnet and the second actuator lateral magnet have polarities aligned at right angles to polarities of the respective first pair of first actuator transverse magnets.
7. The camera system of claim 1, further comprising:  
coils aligned with current circulating in a plane parallel to a plane in which the first actuator lateral magnet and the second actuator lateral magnet have polarities aligned.
8. A camera unit of a multifunction device, comprising:  
an optical package;  
an actuator for moving the optical package to a first focal length, wherein the actuator comprises:  
an actuator lateral magnet to move the optical package in one or more directions orthogonal to an optical axis of the optical package, and  
a first pair of actuator transverse magnets to move the optical package along at least the optical axis, the first pair of actuator transverse magnets situated on sides opposite one another with respect to an axis between the optical package and the actuator lateral magnet;  
wherein:  
the actuator lateral magnet is situated to one side of the optical package at which no actuator transverse magnets are present; and  
the actuator does not include an actuator magnet opposite the actuator lateral magnet with respect to the optical package.
9. The camera unit of claim 8, further comprising:  
coils aligned with current circulating in a plane parallel to a plane in which the actuator lateral magnet and the actuator transverse magnets have polarities aligned.
10. The camera unit of claim 8, further comprising:  
coils aligned with current circulating in a plane perpendicular to a plane in which the actuator lateral magnet and the actuator transverse magnets have polarities aligned.
11. The camera unit of claim 8, further comprising:  
a second pair of actuator transverse magnets situated opposite one another with respect to the axis between the actuator lateral magnet and the optical package.
12. The camera unit of claim 11, wherein:  
the magnets of the first pair of actuator transverse magnets have polarity alignments antiparallel to one another.
13. The camera unit of claim 11, wherein:  
the magnets of the second pair of actuator transverse magnets have polarity alignments antiparallel to one another.
14. The camera unit of claim 11, wherein:  
the magnets of the first pair of actuator transverse magnets have polarity alignments antiparallel to magnets of the second pair of actuator transverse magnets situated on a same side of the axis between the actuator lateral magnet and the optical package.
15. An actuator, comprising:  
an actuator lateral magnet that moves an optical package in at least a first direction that is orthogonal to an optical axis of the optical package, and  
a first pair of actuator transverse magnets that move the optical package in at least a second direction that is orthogonal to the first direction, the first pair of actuator transverse magnets situated on sides opposite one another with respect to an axis between the optical package and the actuator lateral magnet;

wherein:  
the actuator lateral magnet is situated one on one side  
of the optical package at which no transverse mag-  
nets are present; and  
the actuator does not include an actuator magnet oppo- 5  
site the actuator lateral magnet with respect to the  
optical package.  
**16.** The actuator of claim **15**, further comprising:  
coils aligned with current circulating in a plane parallel to  
a plane in which the actuator lateral magnet and the 10  
actuator transverse magnets have polarities aligned.  
**17.** The actuator of claim **15**, further comprising:  
coils aligned with current circulating in a plane perpen-  
dicular to a plane in which the actuator lateral magnet  
and the actuator transverse magnets have polarities 15  
aligned.  
**18.** The actuator of claim **15**, further comprising:  
a second pair of actuator transverse magnets situated  
opposite one another with respect to the axis between  
the actuator lateral magnet and the optical package. 20  
**19.** The actuator of claim **18**, wherein:  
the magnets of the first pair of actuator transverse magnets  
have polarity alignments antiparallel to one another.  
**20.** The actuator of claim **18**, wherein:  
the magnets of the second pair of actuator transverse 25  
magnets have polarity alignments antiparallel to one  
another.

\* \* \* \* \*