

US009792007B2

(12) **United States Patent**
Sirpal et al.

(10) **Patent No.:** **US 9,792,007 B2**
(45) **Date of Patent:** ***Oct. 17, 2017**

(54) **FOCUS CHANGE UPON APPLICATION LAUNCH**

(2013.01); *G06F 3/0346* (2013.01); *G06F 3/044* (2013.01); *G06F 3/048* (2013.01); *G06F 3/0412* (2013.01);

(71) Applicant: **Z124**, George Town (KY)

(Continued)

(72) Inventors: **Sanjiv Sirpal**, Oakville (CA); **Paul Edward Reeves**, Oakville (CA); **Alexander de Paz**, Burlington (CA); **Rodney Wayne Schrock**, San Diego, CA (US)

(58) **Field of Classification Search**

CPC G09G 5/14; G06F 9/4443; G06F 17/241
USPC 715/802
See application file for complete search history.

(73) Assignee: **Z124**, George Town (KY)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 222 days.

5,227,771 A 7/1993 Kerr et al.
5,467,102 A 11/1995 Kuno et al.

(Continued)

This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/523,069**

CN 101087459 12/2007
CN 101788850 7/2010

(Continued)

(22) Filed: **Oct. 24, 2014**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2015/0046851 A1 Feb. 12, 2015

U.S. Appl. No. 14/703,243, filed May 4, 2015, Sirpal et al.
(Continued)

Related U.S. Application Data

Primary Examiner — Joy Weber

(63) Continuation of application No. 13/248,618, filed on Sep. 29, 2011, now Pat. No. 8,875,050.

(74) *Attorney, Agent, or Firm* — Sheridan Ross P.C.

(Continued)

(51) **Int. Cl.**

G06F 3/048 (2013.01)
G06F 3/0484 (2013.01)

(Continued)


(57) **ABSTRACT**

Embodiments are described for handling focus when a gesture is input in a multi-screen device. In embodiments, a first image displayed on a first touch sensitive display of a first screen may be currently in focus. In embodiments, the gesture is a tap on a second touch sensitive display of the device. In response to the gesture, an application is launched, which displays a second image on a second display of a second screen. Focus is then changed from the first image on the first touch sensitive display to the second image on the second touch sensitive display.

(52) **U.S. Cl.**

CPC *G06F 3/0484* (2013.01); *G06F 1/16* (2013.01); *G06F 1/1616* (2013.01); *G06F 1/1641* (2013.01); *G06F 1/1647* (2013.01); *G06F 1/1677* (2013.01); *G06F 3/017*

20 Claims, 20 Drawing Sheets



Related U.S. Application Data

(60) Provisional application No. 61/539,884, filed on Sep. 27, 2011, provisional application No. 61/458,150, filed on Nov. 17, 2010, provisional application No. 61/389,000, filed on Oct. 1, 2010, provisional application No. 61/389,117, filed on Oct. 1, 2010, provisional application No. 61/389,087, filed on Oct. 1, 2010.

(51) **Int. Cl.**

G06F 1/16 (2006.01)
G06F 3/0481 (2013.01)
G06F 3/0483 (2013.01)
G06F 3/0488 (2013.01)
G06F 3/14 (2006.01)
G06F 3/041 (2006.01)
G06F 3/01 (2006.01)
G06T 3/40 (2006.01)
G06F 3/0482 (2013.01)
G06F 3/0486 (2013.01)
G06F 3/044 (2006.01)
G06T 3/00 (2006.01)
G06F 3/0346 (2013.01)
G09G 5/14 (2006.01)

(52) **U.S. Cl.**

CPC **G06F 3/0416** (2013.01); **G06F 3/0481** (2013.01); **G06F 3/0482** (2013.01); **G06F 3/0483** (2013.01); **G06F 3/0486** (2013.01); **G06F 3/0488** (2013.01); **G06F 3/04812** (2013.01); **G06F 3/04817** (2013.01); **G06F 3/04842** (2013.01); **G06F 3/04845** (2013.01); **G06F 3/04847** (2013.01); **G06F 3/04883** (2013.01); **G06F 3/04886** (2013.01); **G06F 3/1423** (2013.01); **G06F 3/1446** (2013.01); **G06T 3/0006** (2013.01); **G06T 3/40** (2013.01); **G09G 5/14** (2013.01); **G06F 2200/1614** (2013.01); **G06F 2203/04803** (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

5,847,698 A	12/1998	Reavey et al.
6,512,497 B1	1/2003	Kondo et al.
7,289,084 B2	10/2007	Lesniak
RE40,821 E	7/2009	Narayanaswamy et al.
8,046,701 B2	10/2011	Chiu et al.
8,421,762 B2 *	4/2013	Rapp G06F 3/0481 345/173
8,866,763 B2	10/2014	Sirpal et al.
8,875,050 B2	10/2014	Sirpal et al.
8,959,445 B2	2/2015	Sirpal et al.
9,026,930 B2	5/2015	Sirpal et al.
9,063,694 B2	6/2015	Sirpal et al.
2003/0020754 A1	1/2003	Berman
2003/0146897 A1	8/2003	Hunter
2003/0229731 A1	12/2003	Keller
2005/0052341 A1	3/2005	Henriksson
2006/0129948 A1	6/2006	Hamzy et al.
2007/0198948 A1	8/2007	Toriyama
2007/0285533 A1	12/2007	Furuya et al.
2007/0288868 A1	12/2007	Rhee et al.
2009/0231233 A1	9/2009	Liberatore
2009/0244016 A1	10/2009	Casparian et al.
2009/0278806 A1	11/2009	Duarte et al.
2009/0293007 A1	11/2009	Duarte et al.
2009/0315807 A1	12/2009	Hsu
2010/0081475 A1	4/2010	Chiang et al.
2010/0085274 A1	4/2010	Kilpatrick, II et al.
2010/0182265 A1	7/2010	Kim et al.

2010/0188352 A1	7/2010	Ikeda
2010/0194705 A1	8/2010	Kim et al.
2010/0201712 A1	8/2010	Grignani et al.
2010/0229089 A1	9/2010	Narita
2010/0245106 A1	9/2010	Miller et al.
2010/0245267 A1	9/2010	Min et al.
2010/0245275 A1	9/2010	Tanaka
2010/0298032 A1	11/2010	Lee et al.
2010/0302179 A1	12/2010	Ahn et al.
2010/0306669 A1	12/2010	Della Pasqua
2011/0006971 A1	1/2011	Ebey et al.
2011/0090155 A1	4/2011	Caskey et al.
2011/0099512 A1	4/2011	Jeong
2011/0107272 A1	5/2011	Aguilar
2011/0187655 A1	8/2011	Min et al.
2011/0191701 A1	8/2011	Kim et al.
2011/0209058 A1	8/2011	Hinckley et al.
2011/0239142 A1	9/2011	Steeves et al.
2011/0296333 A1	12/2011	Bateman et al.
2012/0050177 A1	3/2012	Simmons
2012/0081303 A1	4/2012	Cassar et al.
2012/0081401 A1	4/2012	Sirpal et al.
2012/0084678 A1	4/2012	Sirpal et al.
2012/0084682 A1	4/2012	Sirpal et al.
2012/0084712 A1	4/2012	Gimpl et al.
2012/0092233 A1	4/2012	Kazamaki
2012/0236035 A1	9/2012	Kimura
2013/0021262 A1	1/2013	Chen
2014/0380202 A1	12/2014	Sirpal et al.

FOREIGN PATENT DOCUMENTS

EP	2207076	7/2010
JP	H08-234953	9/1996
JP	2011-070525	4/2011

OTHER PUBLICATIONS

“Lapdock™ for Motorola ATRIX,” at <http://www.motorola.com/Consumers/US-EN/Consumer-Product-and-Services/Mobile> . . . , accessed Apr. 18, 2011, 1 page.

“Motorola ATRIX 4G Laptop Dock Review,” at http://www.phonearena.com/reviews/Motorola-ATRIX-4G-Laptop-Dock-Review_id2667, Mar. 2, 2011, 6 pages.

Burns, C., “Motorola ATRIX 4G Laptop Dock Review,” at <http://androidcommunity.com/motorola-atrrix-4g-laptop-dock-review-20110220/>, Feb. 20, 2011, 5 pages.

Google images, accessed Apr. 18, 2011, 6 pages.

Harman03, “Kyocera Echo Dual-screen Android Phone,” posted 4 weeks from Apr. 18, 2011, 3 pages.

Stein, S., “How does the Motorola Atrix 4G Lapdock compare with a laptop?” Crave—CNET, at http://news.cnet.com/8301-17938_105-20031251-1.html, Feb. 9, 2011, 7 pages.

Catachio, Chad, “This smartphone has two huge screens . . . that rotate,” The Next Web at <http://thenextweb.com/asia/2010/10/07/this-smartphone-has-two-huge-screens-that-rotate/>, Jul. 21, 2011, 2 pages.

Website entitled, “Kyocera Echo,” at <http://www.echobykyocera.com/>, 2011, 6 pages.

Website entitled, “Sony Tablet,” at <http://store.sony.com/webapp/wcs/stores/servlet/CategoryDisplay?catalogId=10551&storeId=10151&langId=-1&categoryId=8198552921644795521>, 2011, 3 pages.

International Search Report and Written Opinion for International (PCT) Patent Application No. PCT/US11/53924, dated Jan. 20, 2012, 11 pages.

International Preliminary Report on Patentability for International (PCT) Patent Application No. PCT/US11/53924, dated Apr. 11, 2013, 10 pages.

Official Action for U.S. Appl. No. 13/248,618, dated Nov. 21, 2013 26 pages.

Notice of Allowance for U.S. Appl. No. 13/248,618, dated Jun. 10, 2014 20 pages.

Official Action for U.S. Appl. No. 13/248,665, dated May 14, 2013, 13 pages.

(56)

References Cited

OTHER PUBLICATIONS

Official Action for U.S. Appl. No. 13/248,665, dated Nov. 7, 2013 14 pages.
 Official Action for U.S. Appl. No. 13/248,665, dated Mar. 24, 2014 14 pages.
 Official Action for U.S. Appl. No. 13/249,056, dated Mar. 10, 2014 14 pages.
 Official Action for U.S. Appl. No. 13/248,665, dated Jun. 5, 2013, 14 pages.
 Official Action for U.S. Appl. No. 13/223,039, dated Nov. 19, 2013 15 pages.
 Official Action for U.S. Appl. No. 13/223,043, dated Oct. 3, 2013 13 pages.
 Official Action for U.S. Appl. No. 13/223,043, dated Jan. 17, 2014 15 pages.
 Official Action for U.S. Appl. No. 13/223,043, dated Mar. 17, 2014 15 pages.
 Official Action for U.S. Appl. No. 13/247,815, dated Jun. 20, 2013, 33 pages.
 Official Action for U.S. Appl. No. 13/247,815, dated Dec. 3, 2013 35 pages.
 Official Action for U.S. Appl. No. 13/247,815, dated Mar. 21, 2014 35 pages.
 Official Action for U.S. Appl. No. 13/248,496, dated Jun. 20, 2013, 33 pages.
 Official Action for U.S. Appl. No. 13/248,496, dated Dec. 3, 2013 37 pages.
 Official Action for U.S. Appl. No. 13/248,496, dated Apr. 3, 2014 40 pages.
 Official Action for U.S. Appl. No. 13/248,427, dated Feb. 24, 2014 16 pages.
 Official Action for U.S. Appl. No. 13/247,824, dated Mar. 19, 2013, 15 pages.
 Final Action for U.S. Appl. No. 13/247,824, dated Jul. 8, 2013, 17 pages.
 Official Action for U.S. Appl. No. 13/247,824, dated Nov. 6, 2013 13 pages.
 Official Action (3rd Party Observations) for European Patent Application No. 11829885.0, dated Jul. 21, 2014, 6 pages.
 Extended European Search Report for European Patent Application No. 11829885.0, dated Feb. 10, 2015, 7 pages.

Notice of Allowance (English translation) for Japanese Patent Application No. 2013-531848, dated Dec. 2, 2014, 2 pages.
 Official Action for U.S. Appl. No. 13/248,665, dated Aug. 29, 2014 15 pages.
 Notice of Allowance for U.S. Appl. No. 13/248,665, dated Jan. 30, 2015 5 pages.
 Official Action for U.S. Appl. No. 13/248,578, dated May 22, 2015 22 pages.
 Notice of Allowance for U.S. Appl. No. 13/249,056, dated Sep. 24, 2014 9 pages.
 Official Action for U.S. Appl. No. 13/223,039, dated Nov. 28, 2014 16 pages.
 Official Action for U.S. Appl. No. 13/223,039, dated May 5, 2015 16 pages.
 Notice of Allowance for U.S. Appl. No. 13/223,043, dated Jun. 6, 2014 9 pages.
 Official Action for U.S. Appl. No. 13/247,815, dated Jul. 24, 2014 35 pages.
 Notice of Allowance for U.S. Appl. No. 13/247,815, dated Apr. 24, 2015 11 pages.
 Official Action for U.S. Appl. No. 13/248,496, dated Jul. 24, 2014 41 pages.
 Notice of Allowance for U.S. Appl. No. 13/248,496, dated Apr. 22, 2015 12 pages.
 Notice of Allowance for U.S. Appl. No. 13/248,427, dated Sep. 26, 2014 9 pages.
 Official Action for U.S. Appl. No. 14/703,243, dated Jun. 23, 2015 14 pages.
 Official Action for U.S. Appl. No. 13/247,824, dated May 12, 2014 13 pages.
 Official Action for U.S. Appl. No. 13/247,824, dated Feb. 23, 2015 20 pages.
 U.S. Appl. No. 14/818,806, filed Aug. 5, 2015, Cassar et al.
 U.S. Appl. No. 14/834,248, filed Aug. 24, 2015, Sirpal et al.
 U.S. Appl. No. 14/954,576, filed Nov. 30, 2015, Sirpal et al.
 Official Action (with English translation) for Chinese Patent Application No. 201180057986.0, dated Jul. 7, 2015, 18 pages.
 Notice of Allowance for U.S. Appl. No. 14/703,243, dated Oct. 29, 2015 6 pages.
 Official Action for U.S. Appl. No. 14/476,249, dated Aug. 11, 2016, 6 pages.
 Notice of Allowance for U.S. Appl. No. 14/476,249, dated Dec. 9, 2016, 8 pages.

* cited by examiner




FIG. 1A





FIG. 1B






FIG. 1H




FIG. 1I




FIG. 1J




FIG. 2










FIG. 3A

	PORTRAIT					LANDSCAPE						
	OPEN	CLOSED	EASEL	MODIFIED EASEL	PHONE	IMAGE / VIDEO	OPEN	CLOSED	EASEL	MODIFIED EASEL	PHONE	IMAGE / VIDEO
P	X	HT	HT	HT	P	I	AT	HAT	HAT	HAT	P	I
O	HT	X	HAT	HAT	P	I	HAT	AT	HAT	HAT	P	I
R	HT	HT	X	X	P	I	HAT	HAT	HAT	HAT	P	I
T	HT	X	HT	HT	X	I	HAT	HAT	HAT	HAT	X	I
R	HT	HT	HT	X	P	X	HAT	HAT	HAT	HAT	X	HAT
I												
A												
T												
L	AT	HAT	HAT	HAT	P	I	X	HT	HAT	HAT	P	I
A	HAT	AT	HAT	HAT	P	I	HT	X	HAT	HAT	P	I
N	HAT	HAT	HAT	HAT	P	I	HT	HT	X	HAT	P	I
D	HAT	HAT	HAT	HAT	P	I	HT	HT	HAT	X	P	I
S												
C	HAT	HAT	HAT	HAT	HAT	AT	HT	HT	HT	HAT	P	X
A												
P												
E												
DOCKED												

Key:
H - Hall Effect Sensor(s)
a - accelerometer(s)
T - Timer
P - communications Trigger
I - Image / Video capture Request

FIG. 3B






FIG. 4G




FIG. 4H




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6E




FIG. 6D




FIG. 6F




FIG. 6H

FIG. 6G





FIG. 6I






FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A




FIG. 8B





FIG. 8C






FIG. 9

FOCUS CHANGE UPON APPLICATION LAUNCH

CROSS REFERENCE TO RELATED APPLICATION

The present application is a continuation of U.S. patent application Ser. No. 13/248,618, filed on Sep. 29, 2011, which claims the benefits of and priority, under 35 U.S.C. §119(e), to U.S. Provisional Application Ser. Nos. 61/389,000, filed Oct. 1, 2010, entitled "DUAL DISPLAY WINDOWING SYSTEM;" 61/389,117, filed Oct. 1, 2010, entitled "MULTI-OPERATING SYSTEM PORTABLE DOCKETING DEVICE;" 61/389,087, filed Oct. 1, 2010, entitled "TABLET COMPUTING USER INTERFACE;" 61/458,150, filed Nov. 17, 2010, entitled "DUAL SCREEN EMAIL CLIENT;" 61/539,884, filed Sep. 27, 2011, entitled "MOBILE DEVICE." Each of the aforementioned documents is incorporated herein by this reference in their entirety for all that they teach and for all purposes.

BACKGROUND

A substantial number of handheld computing devices, such as cellular phones, tablets, and E-Readers, make use of a touch screen display not only to deliver display information to the user but also to receive inputs from user interface commands. While touch screen displays may increase the configurability of the handheld device and provide a wide variety of user interface options, this flexibility typically comes at a price. The dual use of the touch screen to provide content and receive user commands, while flexible for the user, may obfuscate the display and cause visual clutter, thereby leading to user frustration and loss of productivity.

The small form factor of handheld computing devices requires a careful balancing between the displayed graphics and the area provided for receiving inputs. On the one hand, the small display constrains the display space, which may increase the difficulty of interpreting actions or results. On the other hand, a virtual keypad or other user interface scheme is superimposed on or positioned adjacent to an executing application, requiring the application to be squeezed into an even smaller portion of the display.

This balancing act is particularly difficult for single display touch screen devices. Single display touch screen devices are crippled by their limited screen space. When users are entering information into the device, through the single display, the ability to interpret information in the display can be severely hampered, particularly when a complex interaction between display and interface is required.

SUMMARY

There is a need for a dual multi-display handheld computing device that provides for enhanced power and/or versatility compared to conventional single display handheld computing devices. These and other needs are addressed by the various aspects, embodiments, and/or configurations of the present disclosure. Also, while the disclosure is presented in terms of exemplary embodiments, it should be appreciated that individual aspects of the disclosure can be separately claimed.

In one embodiment, a method includes displaying a first image that is in focus in a first display of a first screen. First input is received indicating a request to launch a second application. The second application is launched in response

to the first input. The second application displays a second image on a second display. The focus is then changed from the first image to the second image.

Another embodiment is directed to a non-transitory computer readable medium storing computer executable instructions that when executed by at least one processor perform a method. The method includes receiving, by one of a first touch sensitive display, a second touch sensitive display, or a gesture capture region, input indicating a request to launch an application. In response to receiving the input, the focus is changed from a first image displayed on a first touch sensitive display of a first screen to a second image displayed by the application.

Yet another embodiment is directed to a dual screen communication device. The communication device includes a gesture capture region to receive a gesture, a first touch sensitive display, a second touch sensitive display, and a computer readable medium that stores computer executable instructions that when executed by at least one processor perform a method. The method includes receiving a tap, by the second touch sensitive display of a second screen, indicating a request to launch an application and in response, launching the application. The application displays a second image on the second touch sensitive display of the second screen. The focus is then changed from the first touch sensitive display of a first screen to the second image. Input is allowed from at least one button of the second screen.

The present disclosure can provide a number of advantages depending on the particular aspect, embodiment, and/or configuration. In a device that includes more than one screen, a decision must be made by the device as to what screen, display area, desktop, or displayed image has the focus. This decision must be made so that any input received by a user can be associated with a screen, display area, desktop, or displayed image. In embodiments, a gesture indicates that an application should be launched and the focus should be changed from its current location, such as from an image displayed on a first screen to an image displayed as a result of the application being launched to allow interaction with the launched application. This solves the problem of where the focus is maintained when the device receives a gesture for launching application. These and other advantages will be apparent from the disclosure.

The phrases "at least one", "one or more", and "and/or" are open-ended expressions that are both conjunctive and disjunctive in operation. For example, each of the expressions "at least one of A, B and C", "at least one of A, B, or C", "one or more of A, B, and C", "one or more of A, B, or C" and "A, B, and/or C" means A alone, B alone, C alone, A and B together, A and C together, B and C together, or A, B and C together.

The term "a" or "an" entity refers to one or more of that entity. As such, the terms "a" (or "an"), "one or more" and "at least one" can be used interchangeably herein. It is also to be noted that the terms "comprising", "including", and "having" can be used interchangeably.

The term "automatic" and variations thereof, as used herein, refers to any process or operation done without material human input when the process or operation is performed. However, a process or operation can be automatic, even though performance of the process or operation uses material or immaterial human input, if the input is received before performance of the process or operation. Human input is deemed to be material if such input influences how the process or operation will be performed. Human input that consents to the performance of the process or operation is not deemed to be "material".

The term “computer-readable medium” as used herein refers to any tangible storage and/or transmission medium that participate in providing instructions to a processor for execution. Such a medium may take many forms, including but not limited to, non-volatile media, volatile media, and transmission media. Non-volatile media includes, for example, NVRAM, or magnetic or optical disks. Volatile media includes dynamic memory, such as main memory. Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, or any other magnetic medium, magneto-optical medium, a CD-ROM, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, a RAM, a PROM, and EPROM, a FLASH-EPROM, a solid state medium like a memory card, any other memory chip or cartridge, a carrier wave as described hereinafter, or any other medium from which a computer can read. A digital file attachment to e-mail or other self-contained information archive or set of archives is considered a distribution medium equivalent to a tangible storage medium. When the computer-readable media is configured as a database, it is to be understood that the database may be any type of database, such as relational, hierarchical, object-oriented, and/or the like. Accordingly, the disclosure is considered to include a tangible storage medium or distribution medium and prior art-recognized equivalents and successor media, in which the software implementations of the present disclosure are stored.

The term “desktop” refers to a metaphor used to portray systems. A desktop is generally considered a “surface” that typically includes pictures, called icons, widgets, folders, etc. that can activate show applications, windows, cabinets, files, folders, documents, and other graphical items. The icons are generally selectable to initiate a task through user interface interaction to allow a user to execute applications or conduct other operations.

The term “screen,” “touch screen,” or “touchscreen” refers to a physical structure that includes one or more hardware components that provide the device with the ability to render a user interface and/or receive user input. A screen can encompass any combination of gesture capture region, a touch sensitive display, and/or a configurable area. The device can have one or more physical screens embedded in the hardware. However a screen may also include an external peripheral device that may be attached and detached from the device. In embodiments, multiple external devices may be attached to the device. Thus, in embodiments, the screen can enable the user to interact with the device by touching areas on the screen and provides information to a user through a display. The touch screen may sense user contact in a number of different ways, such as by a change in an electrical parameter (e.g., resistance or capacitance), acoustic wave variations, infrared radiation proximity detection, light variation detection, and the like. In a resistive touch screen, for example, normally separated conductive and resistive metallic layers in the screen pass an electrical current. When a user touches the screen, the two layers make contact in the contacted location, whereby a change in electrical field is noted and the coordinates of the contacted location calculated. In a capacitive touch screen, a capacitive layer stores electrical charge, which is discharged to the user upon contact with the touch screen, causing a decrease in the charge of the capacitive layer. The decrease is measured, and the contacted location coordinates determined. In a surface acoustic wave touch screen, an acoustic wave is transmitted through the screen, and the acoustic wave is disturbed by

user contact. A receiving transducer detects the user contact instance and determines the contacted location coordinates.

The term “display” refers to a portion of one or more screens used to display the output of a computer to a user. A display may be a single-screen display or a multi-screen display, referred to as a composite display. A composite display can encompass the touch sensitive display of one or more screens. A single physical screen can include multiple displays that are managed as separate logical displays. Thus, different content can be displayed on the separate displays although part of the same physical screen.

The term “displayed image” refers to an image produced on the display. A typical displayed image is a window or desktop. The displayed image may occupy all or a portion of the display.

The term “display orientation” refers to the way in which a rectangular display is oriented by a user for viewing. The two most common types of display orientation are portrait and landscape. In landscape mode, the display is oriented such that the width of the display is greater than the height of the display (such as a 4:3 ratio, which is 4 units wide and 3 units tall, or a 16:9 ratio, which is 16 units wide and 9 units tall). Stated differently, the longer dimension of the display is oriented substantially horizontal in landscape mode while the shorter dimension of the display is oriented substantially vertical. In the portrait mode, by contrast, the display is oriented such that the width of the display is less than the height of the display. Stated differently, the shorter dimension of the display is oriented substantially horizontal in the portrait mode while the longer dimension of the display is oriented substantially vertical.

The term “composited display” refers to a logical structure that defines a display that can encompass one or more screens. A multi-screen display can be associated with a composite display that encompasses all the screens. The composite display can have different display characteristics based on the various orientations of the device.

The term “gesture” refers to a user action that expresses an intended idea, action, meaning, result, and/or outcome. The user action can include manipulating a device (e.g., opening or closing a device, changing a device orientation, moving a trackball or wheel, etc.), movement of a body part in relation to the device, movement of an implement or tool in relation to the device, audio inputs, etc. A gesture may be made on a device (such as on the screen) or with the device to interact with the device.

The term “module” as used herein refers to any known or later developed hardware, software, firmware, artificial intelligence, fuzzy logic, or combination of hardware and software that is capable of performing the functionality associated with that element.

The term “gesture capture” refers to a sense or otherwise a detection of an instance and/or type of user gesture. The gesture capture can occur in one or more areas of the screen. A gesture region can be on the display, where it may be referred to as a touch sensitive display or off the display where it may be referred to as a gesture capture area.

A “multi-screen application” refers to an application that is capable of multiple modes. The multi-screen application mode can include, but is not limited to, a single screen mode (where the application is displayed on a single screen) or a composite display mode (where the application is displayed on two or more screens). A multi-screen application can have different layouts optimized for the mode. Thus, the multi-screen application can have different layouts for a single screen or for a composite display that can encompass two or more screens. The different layouts may have differ-

ent screen/display dimensions and/or configurations on which the user interfaces of the multi-screen applications can be rendered. The different layouts allow the application to optimize the application's user interface for the type of display, e.g., single screen or multiple screens. In single screen mode, the multi-screen application may present one window pane of information. In a composite display mode, the multi-screen application may present multiple window panes of information or may provide a larger and a richer presentation because there is more space for the display contents. The multi-screen applications may be designed to adapt dynamically to changes in the device and the mode depending on which display (single or composite) the system assigns to the multi-screen application. In alternative embodiments, the user can use a gesture to request the application transition to a different mode, and, if a display is available for the requested mode, the device can allow the application to move to that display and transition modes.

A "single-screen application" refers to an application that is capable of single screen mode. Thus, the single-screen application can produce only one window and may not be capable of different modes or different display dimensions. A single-screen application is incapable of the several modes discussed with the multi-screen application.

The term "window" refers to a, typically rectangular, displayed image on at least part of a display that contains or provides content different from the rest of the screen. The window may obscure the desktop.

The terms "determine", "calculate" and "compute," and variations thereof, as used herein, are used interchangeably and include any type of methodology, process, mathematical operation or technique.

It shall be understood that the term "means" as used herein shall be given its broadest possible interpretation in accordance with 35 U.S.C., Section 112, Paragraph 6. Accordingly, a claim incorporating the term "means" shall cover all structures, materials, or acts set forth herein, and all of the equivalents thereof. Further, the structures, materials or acts and the equivalents thereof shall include all those described in the summary of the invention, brief description of the drawings, detailed description, abstract, and claims themselves.

The term "focus" refers to being active and/or selected to receive input. A screen, a display, or a component (e.g., displayed image) of a displayed graphical user interface may have "focus." Non-limiting examples of displayed images on a graphical user interface that may have "focus" include an icon of an application, an open window of an application, and/or a desktop/portion of a desktop.

The preceding is a simplified summary of the disclosure to provide an understanding of some aspects of the disclosure. This summary is neither an extensive nor exhaustive overview of the disclosure and its various aspects, embodiments, and/or configurations. It is intended neither to identify key or critical elements of the disclosure nor to delineate the scope of the disclosure but to present selected concepts of the disclosure in a simplified form as an introduction to the more detailed description presented below. As will be appreciated, other aspects, embodiments, and/or configurations of the disclosure are possible utilizing, alone or in combination, one or more of the features set forth above or described in detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A includes a first view of an embodiment of a multi-screen user device;

FIG. 1B includes a second view of an embodiment of a multi-screen user device;

FIG. 1C includes a third view of an embodiment of a multi-screen user device;

FIG. 1D includes a fourth view of an embodiment of a multi-screen user device;

FIG. 1E includes a fifth view of an embodiment of a multi-screen user device;

FIG. 1F includes a sixth view of an embodiment of a multi-screen user device;

FIG. 1G includes a seventh view of an embodiment of a multi-screen user device;

FIG. 1H includes a eighth view of an embodiment of a multi-screen user device;

FIG. 1I includes a ninth view of an embodiment of a multi-screen user device;

FIG. 1J includes a tenth view of an embodiment of a multi-screen user device;

FIG. 2 is a block diagram of an embodiment of the hardware of the device;

FIG. 3A is a block diagram of an embodiment of the state model for the device based on the device's orientation and/or configuration;

FIG. 3B is a table of an embodiment of the state model for the device based on the device's orientation and/or configuration;

FIG. 4A is a first representation of an embodiment of user gesture received at a device;

FIG. 4B is a second representation of an embodiment of user gesture received at a device;

FIG. 4C is a third representation of an embodiment of user gesture received at a device;

FIG. 4D is a fourth representation of an embodiment of user gesture received at a device;

FIG. 4E is a fifth representation of an embodiment of user gesture received at a device;

FIG. 4F is a sixth representation of an embodiment of user gesture received at a device;

FIG. 4G is a seventh representation of an embodiment of user gesture received at a device;

FIG. 4H is a eighth representation of an embodiment of user gesture received at a device;

FIG. 5A is a block diagram of an embodiment of the device software and/or firmware;

FIG. 5B is a second block diagram of an embodiment of the device software and/or firmware;

FIG. 6A is a first representation of an embodiment of a device configuration generated in response to the device state;

FIG. 6B is a second representation of an embodiment of a device configuration generated in response to the device state;

FIG. 6C is a third representation of an embodiment of a device configuration generated in response to the device state;

FIG. 6D is a fourth representation of an embodiment of a device configuration generated in response to the device state;

FIG. 6E is a fifth representation of an embodiment of a device configuration generated in response to the device state;

FIG. 6F is a sixth representation of an embodiment of a device configuration generated in response to the device state;

FIG. 6G is a seventh representation of an embodiment of a device configuration generated in response to the device state;

7

FIG. 6H is a eighth representation of an embodiment of a device configuration generated in response to the device state;

FIG. 6I is a ninth representation of an embodiment of a device configuration generated in response to the device state;

FIG. 6J is a tenth representation of an embodiment of a device configuration generated in response to the device state;

FIGS. 7A-7C are a representation of an embodiment showing a first image in focus and the response when a gesture is made to move the focus from a first screen to a second screen;

FIGS. 8A-8C are a representation of a second embodiment showing a first image in focus and the response when a gesture is made to move the focus from a first screen to a second screen; and

FIG. 9 illustrates a flow chart of an embodiment for handling a gesture.

In the appended figures, similar components and/or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a letter that distinguishes among the similar components. If only the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

DETAILED DESCRIPTION

Presented herein are embodiments of a device. The device can be a communications device, such as a cellular telephone, or other smart device. The device can include two screens that are oriented to provide several unique display configurations. Further, the device can receive user input in unique ways. The overall design and functionality of the device provides for an enhanced user experience making the device more useful and more efficient.

Mechanical Features:

FIGS. 1A-1J illustrate a device 100 in accordance with embodiments of the present disclosure. As described in greater detail below, device 100 can be positioned in a number of different ways each of which provides different functionality to a user. The device 100 is a multi-screen device that includes a primary screen 104 and a secondary screen 108, both of which are touch sensitive. In embodiments, the entire front surface of screens 104 and 108 may be touch sensitive and capable of receiving input by a user touching the front surface of the screens 104 and 108. Primary screen 104 includes touch sensitive display 110, which, in addition to being touch sensitive, also displays information to a user. Secondary screen 108 includes touch sensitive display 114, which also displays information to a user. In other embodiments, screens 104 and 108 may include more than one display area.

Primary screen 104 also includes a configurable area 112 that has been configured for specific inputs when the user touches portions of the configurable area 112. Secondary screen 108 also includes a configurable area 116 that has been configured for specific inputs. Areas 112a and 116a have been configured to receive a “back” input indicating that a user would like to view information previously displayed. Areas 112b and 116b have been configured to receive a “menu” input indicating that the user would like to view options from a menu. Areas 112c and 116c have been configured to receive a “home” input indicating that the user would like to view information associated with a “home”

8

view. In other embodiments, areas 112a-c and 116a-c may be configured, in addition to the configurations described above, for other types of specific inputs including controlling features of device 100, some non-limiting examples including adjusting overall system power, adjusting the volume, adjusting the brightness, adjusting the vibration, selecting of displayed items (on either of screen 104 or 108), operating a camera, operating a microphone, and initiating/terminating of telephone calls. Also, in some embodiments, areas 112a-c and 116a-c may be configured for specific inputs depending upon the application running on device 100 and/or information displayed on touch sensitive displays 110 and/or 114.

In addition to touch sensing, primary screen 104 and secondary screen 108 may also include areas that receive input from a user without requiring the user to touch the display area of the screen. For example, primary screen 104 includes gesture capture area 120, and secondary screen 108 includes gesture capture area 124. These areas are able to receive input by recognizing gestures made by a user without the need for the user to actually touch the surface of the display area. In comparison to touch sensitive displays 110 and 114, the gesture capture areas 120 and 124 are commonly not capable of rendering a displayed image.

The two screens 104 and 108 are connected together with a hinge 128, shown clearly in FIG. 1C (illustrating a back view of device 100). Hinge 128, in the embodiment shown in FIGS. 1A-1J, is a center hinge that connects screens 104 and 108 so that when the hinge is closed, screens 104 and 108 are juxtaposed (i.e., side-by-side) as shown in FIG. 1B (illustrating a front view of device 100). Hinge 128 can be opened to position the two screens 104 and 108 in different relative positions to each other. As described in greater detail below, the device 100 may have different functionalities depending on the relative positions of screens 104 and 108.

FIG. 1D illustrates the right side of device 100. As shown in FIG. 1D, secondary screen 108 also includes a card slot 132 and a port 136 on its side. Card slot 132 in embodiments, accommodates different types of cards including a subscriber identity module (SIM). Port 136 in embodiments is an input/output port (I/O port) that allows device 100 to be connected to other peripheral devices, such as a display, keyboard, or printing device. As can be appreciated, these are merely some examples and in other embodiments device 100 may include other slots and ports such as slots and ports for accommodating additional memory devices and/or for connecting other peripheral devices. Also shown in FIG. 1D is an audio jack 140 that accommodates a tip, ring, sleeve (TRS) connector for example to allow a user to utilize headphones or a headset.

Device 100 also includes a number of buttons 158. For example, FIG. 1E illustrates the left side of device 100. As shown in FIG. 1E, the side of primary screen 104 includes three buttons 144, 148, and 152, which can be configured for specific inputs. For example, buttons 144, 148, and 152 may be configured to, in combination or alone, control a number of aspects of device 100. Some non-limiting examples include overall system power, volume, brightness, vibration, selection of displayed items (on either of screen 104 or 108), a camera, a microphone, and initiation/termination of telephone calls. In some embodiments, instead of separate buttons two buttons may be combined into a rocker button. This arrangement is useful in situations where the buttons are configured to control features such as volume or brightness. In addition to buttons 144, 148, and 152, device 100 also includes a button 156, shown in FIG. 1F, which illustrates the top of device 100. In one embodiment, button 156

is configured as an on/off button used to control overall system power to device 100. In other embodiments, button 156 is configured to, in addition to or in lieu of controlling system power, control other aspects of device 100. In some embodiments, one or more of the buttons 144, 148, 152, and 156 are capable of supporting different user commands. By way of example, a normal press has a duration commonly of less than about 1 second and resembles a quick tap. A medium press has a duration commonly of 1 second or more but less than about 12 seconds. A long press has a duration commonly of about 12 seconds or more. The function of the buttons is normally specific to the application that is currently in focus on the respective display 110 and 114. In a telephone application for instance and depending on the particular button, a normal, medium, or long press can mean end call, increase in call volume, decrease in call volume, and toggle microphone mute. In a camera or video application for instance and depending on the particular button, a normal, medium, or long press can mean increase zoom, decrease zoom, and take photograph or record video.

There are also a number of hardware components within device 100. As illustrated in FIG. 1C, device 100 includes a speaker 160 and a microphone 164. Device 100 also includes a camera 168 (FIG. 1B). Additionally, device 100 includes two position sensors 172A and 172B, which are used to determine the relative positions of screens 104 and 108. In one embodiment, position sensors 172A and 172B are Hall effect sensors. However, in other embodiments other sensors can be used in addition to or in lieu of the Hall effect sensors. An accelerometer 176 may also be included as part of device 100 to determine the orientation of the device 100 and/or the orientation of screens 104 and 108. Additional internal hardware components that may be included in device 100 are described below with respect to FIG. 2.

The overall design of device 100 allows it to provide additional functionality not available in other communication devices. Some of the functionality is based on the various positions and orientations that device 100 can have. As shown in FIGS. 1B-1G, device 100 can be operated in an “open” position where screens 104 and 108 are juxtaposed. This position allows a large display area for displaying information to a user. When position sensors 172A and 172B determine that device 100 is in the open position, they can generate a signal that can be used to trigger different events such as displaying information on both screens 104 and 108. Additional events may be triggered if accelerometer 176 determines that device 100 is in a portrait position (FIG. 1B) as opposed to a landscape position (not shown).

In addition to the open position, device 100 may also have a “closed” position illustrated in FIG. 1H. Again, position sensors 172A and 172B can generate a signal indicating that device 100 is in the “closed” position. This can trigger an event that results in a change of displayed information on screen 104 and/or 108. For example, device 100 may be programmed to stop displaying information on one of the screens, e.g., screen 108, since a user can only view one screen at a time when device 100 is in the “closed” position. In other embodiments, the signal generated by position sensors 172A and 172B, indicating that the device 100 is in the “closed” position, can trigger device 100 to answer an incoming telephone call. The “closed” position can also be a preferred position for utilizing the device 100 as a mobile phone.

Device 100 can also be used in an “easel” position which is illustrated in FIG. 1I. In the “easel” position, screens 104 and 108 are angled with respect to each other and facing

outward with the edges of screens 104 and 108 substantially horizontal. In this position, device 100 can be configured to display information on both screens 104 and 108 to allow two users to simultaneously interact with device 100. When device 100 is in the “easel” position, sensors 172A and 172B generate a signal indicating that the screens 104 and 108 are positioned at an angle to each other, and the accelerometer 176 can generate a signal indicating that device 100 has been placed so that the edge of screens 104 and 108 are substantially horizontal. The signals can then be used in combination to generate events that trigger changes in the display of information on screens 104 and 108.

FIG. 1J illustrates device 100 in a “modified easel” position. In the “modified easel” position, one of screens 104 or 108 is used as a stand and is faced down on the surface of an object such as a table. This position provides a convenient way for information to be displayed to a user in landscape orientation. Similar to the easel position, when device 100 is in the “modified easel” position, position sensors 172A and 172B generate a signal indicating that the screens 104 and 108 are positioned at an angle to each other. The accelerometer 176 would generate a signal indicating that device 100 has been positioned so that one of screens 104 and 108 is faced downwardly and is substantially horizontal. The signals can then be used to generate events that trigger changes in the display of information of screens 104 and 108. For example, information may not be displayed on the screen that is face down since a user cannot see the screen.

Transitional states are also possible. When the position sensors 172A and B and/or accelerometer indicate that the screens are being closed or folded (from open), a closing transitional state is recognized. Conversely when the position sensors 172A and B indicate that the screens are being opened or folded (from closed), an opening transitional state is recognized. The closing and opening transitional states are typically time-based, or have a maximum time duration from a sensed starting point. Normally, no user input is possible when one of the closing and opening states is in effect. In this manner, incidental user contact with a screen during the closing or opening function is not misinterpreted as user input. In embodiments, another transitional state is possible when the device 100 is closed. This additional transitional state allows the display to switch from one screen 104 to the second screen 108 when the device 100 is closed based on some user input, e.g., a double tap on the screen 110,114.

As can be appreciated, the description of device 100 is made for illustrative purposes only, and the embodiments are not limited to the specific mechanical features shown in FIGS. 1A-1J and described above. In other embodiments, device 100 may include additional features, including one or more additional buttons, slots, display areas, hinges, and/or locking mechanisms. Additionally, in embodiments, the features described above may be located in different parts of device 100 and still provide similar functionality. Therefore, FIGS. 1A-1J and the description provided above are non-limiting.

Hardware Features:

FIG. 2 illustrates components of a device 100 in accordance with embodiments of the present disclosure. In general, the device 100 includes a primary screen 104 and a secondary screen 108. While the primary screen 104 and its components are normally enabled in both the opened and closed positions or states, the secondary screen 108 and its components are normally enabled in the opened state but disabled in the closed state. However, even when in the

closed state a user or application triggered interrupt (such as in response to a phone application or camera application operation) can flip the active screen, or disable the primary screen **104** and enable the secondary screen **108**, by a suitable command. Each screen **104**, **108** can be touch sensitive and can include different operative areas. For example, a first operative area, within each touch sensitive screen **104** and **108**, may comprise a touch sensitive display **110**, **114**. In general, the touch sensitive display **110**, **114** may comprise a full color, touch sensitive display. A second area within each touch sensitive screen **104** and **108** may comprise a gesture capture region **120**, **124**. The gesture capture region **120**, **124** may comprise an area or region that is outside of the touch sensitive display **110**, **114** area, and that is capable of receiving input, for example in the form of gestures provided by a user. However, the gesture capture region **120**, **124** does not include pixels that can perform a display function or capability.

A third region of the touch sensitive screens **104** and **108** may comprise a configurable area **112**, **116**. The configurable area **112**, **116** is capable of receiving input and has display or limited display capabilities. In embodiments, the configurable area **112**, **116** may present different input options to the user. For example, the configurable area **112**, **116** may display buttons or other relatable items. Moreover, the identity of displayed buttons, or whether any buttons are displayed at all within the configurable area **112**, **116** of a touch sensitive screen **104** or **108**, may be determined from the context in which the device **100** is used and/or operated. In an exemplary embodiment, the touch sensitive screens **104** and **108** comprise liquid crystal display devices extending across at least those regions of the touch sensitive screens **104** and **108** that are capable of providing visual output to a user, and a capacitive input matrix over those regions of the touch sensitive screens **104** and **108** that are capable of receiving input from the user.

One or more display controllers **216a**, **216b** may be provided for controlling the operation of the touch sensitive screens **104** and **108**, including input (touch sensing) and output (display) functions. In the exemplary embodiment illustrated in FIG. 2, a separate touch screen controller **216a** or **216b** is provided for each touch screen **104** and **108**. In accordance with alternate embodiments, a common or shared touch screen controller may be used to control each of the included touch sensitive screens **104** and **108**. In accordance with still other embodiments, the functions of a touch screen controller may be incorporated into other components, such as a processor **204**.

The processor **204** may comprise a general purpose programmable processor or controller for executing application programming or instructions. In accordance with at least some embodiments, the processor **204** may include multiple processor cores, and/or implement multiple virtual processors. In accordance with still other embodiments, the processor **204** may include multiple physical processors. As a particular example, the processor **204** may comprise a specially configured application specific integrated circuit (ASIC) or other integrated circuit, a digital signal processor, a controller, a hardwired electronic or logic circuit, a programmable logic device or gate array, a special purpose computer, or the like. The processor **204** generally functions to run programming code or instructions implementing various functions of the device **100**.

A communication device **100** may also include memory **208** for use in connection with the execution of application programming or instructions by the processor **204**, and for the temporary or long term storage of program instructions

and/or data. As examples, the memory **208** may comprise RAM, DRAM, SDRAM, or other solid state memory. Alternatively or in addition, data storage **212** may be provided. Like the memory **208**, the data storage **212** may comprise a solid state memory device or devices. Alternatively or in addition, the data storage **212** may comprise a hard disk drive or other random access memory.

In support of communications functions or capabilities, the device **100** can include a cellular telephony module **228**. As examples, the cellular telephony module **228** can comprise a GSM, CDMA, FDMA and/or analog cellular telephony transceiver capable of supporting voice, multimedia and/or data transfers over a cellular network. Alternatively or in addition, the device **100** can include an additional or other wireless communications module **232**. As examples, the other wireless communications module **232** can comprise a Wi-Fi, BLUETOOTH™, WiMax, infrared, or other wireless communications link. The cellular telephony module **228** and the other wireless communications module **232** can each be associated with a shared or a dedicated antenna **224**.

A port interface **252** may be included. The port interface **252** may include proprietary or universal ports to support the interconnection of the device **100** to other devices or components, such as a dock, which may or may not include additional or different capabilities from those integral to the device **100**. In addition to supporting an exchange of communication signals between the device **100** and another device or component, the docking port **136** and/or port interface **252** can support the supply of power to or from the device **100**. The port interface **252** also comprises an intelligent element that comprises a docking module for controlling communications or other interactions between the device **100** and a connected device or component.

An input/output module **248** and associated ports may be included to support communications over wired networks or links, for example with other communication devices, server devices, and/or peripheral devices. Examples of an input/output module **248** include an Ethernet port, a Universal Serial Bus (USB) port, Institute of Electrical and Electronics Engineers (IEEE) 1394, or other interface.

An audio input/output interface/device(s) **244** can be included to provide analog audio to an interconnected speaker or other device, and to receive analog audio input from a connected microphone or other device. As an example, the audio input/output interface/device(s) **244** may comprise an associated amplifier and analog to digital converter. Alternatively or in addition, the device **100** can include an integrated audio input/output device **256** and/or an audio jack for interconnecting an external speaker or microphone. For example, an integrated speaker and an integrated microphone can be provided, to support near talk or speaker phone operations.

Hardware buttons **158** can be included for example for use in connection with certain control operations. Examples include a master power switch, volume control, etc., as described in conjunction with FIGS. 1A through 1J. One or more image capture interfaces/devices **240**, such as a camera, can be included for capturing still and/or video images. Alternatively or in addition, an image capture interface/device **240** can include a scanner or code reader. An image capture interface/device **240** can include or be associated with additional elements, such as a flash or other light source.

The device **100** can also include a global positioning system (GPS) receiver **236**. In accordance with embodiments of the present invention, the GPS receiver **236** may

further comprise a GPS module that is capable of providing absolute location information to other components of the device 100. An accelerometer(s) 176 may also be included. For example, in connection with the display of information to a user and/or other functions, a signal from the accelerometer 176 can be used to determine an orientation and/or format in which to display that information to the user.

Embodiments of the present invention can also include one or more position sensor(s) 172. The position sensor 172 can provide a signal indicating the position of the touch sensitive screens 104 and 108 relative to one another. This information can be provided as an input, for example to a user interface application, to determine an operating mode, characteristics of the touch sensitive displays 110, 114, and/or other device 100 operations. As examples, a screen position sensor 172 can comprise a series of Hall effect sensors, a multiple position switch, an optical switch, a Wheatstone bridge, a potentiometer, or other arrangement capable of providing a signal indicating of multiple relative positions the touch screens are in.

Communications between various components of the device 100 can be carried by one or more buses 220. In addition, power can be supplied to the components of the device 100 from a power source and/or power control module 260. The power control module 260 can, for example, include a battery, an AC to DC converter, power control logic, and/or ports for interconnecting the device 100 to an external source of power.

Device State:

FIGS. 3A and 3B represent illustrative states of device 100. While a number of illustrative states are shown, and transitions from a first state to a second state, it is to be appreciated that the illustrative state diagram may not encompass all possible states and/or all possible transitions from a first state to a second state. As illustrated in FIG. 3, the various arrows between the states (illustrated by the state represented in the circle) represent a physical change that occurs to the device 100, that is detected by one or more of hardware and software, the detection triggering one or more of a hardware and/or software interrupt that is used to control and/or manage one or more functions of device 100.

As illustrated in FIG. 3A, there are twelve exemplary “physical” states: closed 304, transition 308 (or opening transitional state), easel 312, modified easel 316, open 320, inbound/outbound call or communication 324, image/video capture 328, transition 332 (or closing transitional state), landscape 340, docked 336, docked 344 and landscape 348. Next to each illustrative state is a representation of the physical state of the device 100 with the exception of states 324 and 328, where the state is generally symbolized by the international icon for a telephone and the icon for a camera, respectfully.

In state 304, the device is in a closed state with the device 100 generally oriented in the portrait direction with the primary screen 104 and the secondary screen 108 back-to-back in different planes (see FIG. 1H). From the closed state, the device 100 can enter, for example, docked state 336, where the device 100 is coupled with a docking station, docking cable, or in general docked or associated with one or more other devices or peripherals, or the landscape state 340, where the device 100 is generally oriented with the primary screen 104 facing the user, and the primary screen 104 and the secondary screen 108 being back-to-back.

In the closed state, the device can also move to a transitional state where the device remains closed but the display is moved from one screen 104 to another screen 108 based on a user input, e.g., a double tap on the screen 110, 114. Still

another embodiment includes a bilateral state. In the bilateral state, the device remains closed, but a single application displays at least one window on both the first display 110 and the second display 114. The windows shown on the first and second display 110, 114 may be the same or different based on the application and the state of that application. For example, while acquiring an image with a camera, the device may display the view finder on the first display 110 and displays a preview for the photo subjects (full screen and mirrored left-to-right) on the second display 114.

In state 308, a transition state from the closed state 304 to the semi-open state or easel state 312, the device 100 is shown opening with the primary screen 104 and the secondary screen 108 being rotated around a point of axis coincidence with the hinge. Upon entering the easel state 312, the primary screen 104 and the secondary screen 108 are separated from one another such that, for example, the device 100 can sit in an easel-like configuration on a surface.

In state 316, known as the modified easel position, the device 100 has the primary screen 104 and the secondary screen 108 in a similar relative relationship to one another as in the easel state 312, with the difference being one of the primary screen 104 or the secondary screen 108 are placed on a surface as shown.

State 320 is the open state where the primary screen 104 and the secondary screen 108 are generally on the same plane. From the open state, the device 100 can transition to the docked state 344 or the open landscape state 348. In the open state 320, the primary screen 104 and the secondary screen 108 are generally in the portrait-like orientation while in landscaped state 348 the primary screen 104 and the secondary screen 108 are generally in a landscape-like orientation.

State 324 is illustrative of a communication state, such as when an inbound or outbound call is being received or placed, respectively, by the device 100. While not illustrated for clarity, it should be appreciated the device 100 can transition to the inbound/outbound call state 324 from any state illustrated in FIG. 3. In a similar manner, the image/video capture state 328 can be entered into from any other state in FIG. 3, with the image/video capture state 328 allowing the device 100 to take one or more images via a camera and/or videos with a video capture device 240.

Transition state 332 illustratively shows primary screen 104 and the secondary screen 108 being closed upon one another for entry into, for example, the closed state 304.

FIG. 3B illustrates, with reference to the key, the inputs that are received to detect a transition from a first state to a second state. In FIG. 3B, various combinations of states are shown with in general, a portion of the columns being directed toward a portrait state 352, a landscape state 356, and a portion of the rows being directed to portrait state 360 and landscape state 364.

In FIG. 3B, the Key indicates that “H” represents an input from one or more Hall Effect sensors, “A” represents an input from one or more accelerometers, “T” represents an input from a timer, “P” represents a communications trigger input and “I” represents an image and/or video capture request input. Thus, in the center portion 376 of the chart, an input, or combination of inputs, are shown that represent how the device 100 detects a transition from a first physical state to a second physical state.

As discussed, in the center portion of the chart 376, the inputs that are received enable the detection of a transition from, for example, a portrait open state to a landscape easel state—shown in bold—“HAT.” For this exemplary transition from the portrait open to the landscape easel state, a Hall

Effect sensor (“H”), an accelerometer (“A”) and a timer (“T”) input may be needed. The timer input can be derived from, for example, a clock associated with the processor.

In addition to the portrait and landscape states, a docked state **368** is also shown that is triggered based on the receipt of a docking signal **372**. As discussed above and in relation to FIG. 3, the docking signal can be triggered by the association of the device **100** with one or more other device **100s**, accessories, peripherals, smart docks, or the like.

User Interaction:

FIGS. 4A through 4H depict various graphical representations of gesture inputs that may be recognized by the screens **104, 108**. The gestures may be performed not only by a user’s body part, such as a digit, but also by other devices, such as a stylus, that may be sensed by the contact sensing portion(s) of a screen **104, 108**. In general, gestures are interpreted differently, based on where the gestures are performed (either directly on the display **110, 114** or in the gesture capture region **120, 124**). For example, gestures in the display **110,114** may be directed to a desktop or application, and gestures in the gesture capture region **120, 124** may be interpreted as for the system.

With reference to FIGS. 4A-4H, a first type of gesture, a touch gesture **420**, is substantially stationary on the screen **104,108** for a selected length of time. A circle **428** represents a touch or other contact type received at particular location of a contact sensing portion of the screen. The circle **428** may include a border **432**, the thickness of which indicates a length of time that the contact is held substantially stationary at the contact location. For instance, a tap **420** (or short press) has a thinner border **432a** than the border **432b** for a long press **424** (or for a normal press). The long press **424** may involve a contact that remains substantially stationary on the screen for longer time period than that of a tap **420**. As will be appreciated, differently defined gestures may be registered depending upon the length of time that the touch remains stationary prior to contact cessation or movement on the screen.

With reference to FIG. 4C, a drag gesture **400** on the screen **104,108** is an initial contact (represented by circle **428**) with contact movement **436** in a selected direction. The initial contact **428** may remain stationary on the screen **104,108** for a certain amount of time represented by the border **432**. The drag gesture typically requires the user to contact an icon, window, or other displayed image at a first location followed by movement of the contact in a drag direction to a new second location desired for the selected displayed image. The contact movement need not be in a straight line but have any path of movement so long as the contact is substantially continuous from the first to the second locations.

With reference to FIG. 4D, a flick gesture **404** on the screen **104,108** is an initial contact (represented by circle **428**) with truncated contact movement **436** (relative to a drag gesture) in a selected direction. In embodiments, a flick has a higher exit velocity for the last movement in the gesture compared to the drag gesture. The flick gesture can, for instance, be a finger snap following initial contact. Compared to a drag gesture, a flick gesture generally does not require continual contact with the screen **104,108** from the first location of a displayed image to a predetermined second location. The contacted displayed image is moved by the flick gesture in the direction of the flick gesture to the predetermined second location. Although both gestures commonly can move a displayed image from a first location

to a second location, the temporal duration and distance of travel of the contact on the screen is generally less for a flick than for a drag gesture.

With reference to FIG. 4E, a pinch gesture **408** on the screen **104,108** is depicted. The pinch gesture **408** may be initiated by a first contact **428** to the screen **104,108** by, for example, a first digit and a second contact **428b** to the screen **104,108** by, for example, a second digit. The first and second contacts **428a,b** may be detected by a common contact sensing portion of a common screen **104, 108**, by different contact sensing portions of a common screen **104** or **108**, or by different contact sensing portions of different screens. The first contact **428a** is held for a first amount of time, as represented by the border **432a**, and the second contact **428b** is held for a second amount of time, as represented by the border **432b**. The first and second amounts of time are generally substantially the same, and the first and second contacts **428 a, b** generally occur substantially simultaneously. The first and second contacts **428 a, b** generally also include corresponding first and second contact movements **436 a, b**, respectively. The first and second contact movements **436 a, b** are generally in opposing directions. Stated another way, the first contact movement **436a** is towards the second contact **436b**, and the second contact movement **436b** is towards the first contact **436a**. More simply stated, the pinch gesture **408** may be accomplished by a user’s digits touching the screen **104,108** in a pinching motion.

With reference to FIG. 4F, a spread gesture **410** on the screen **104,108** is depicted. The spread gesture **410** may be initiated by a first contact **428a** to the screen **104,108** by, for example, a first digit and a second contact **428b** to the screen **104,108** by, for example, a second digit. The first and second contacts **428a,b** may be detected by a common contact sensing portion of a common screen **104,108**, by different contact sensing portions of a common screen **104,108**, or by different contact sensing portions of different screens. The first contact **428a** is held for a first amount of time, as represented by the border **432a**, and the second contact **428b** is held for a second amount of time, as represented by the border **432b**. The first and second amounts of time are generally substantially the same, and the first and second contacts **428 a, b** generally occur substantially simultaneously. The first and second contacts **428 a, b** generally also include corresponding first and second contact movements **436a, b**, respectively. The first and second contact movements **436 a, b** are generally in a common direction. Stated another way, the first and second contact movements **436 a, b** are away from the first and second contacts **428a, b**. More simply stated, the spread gesture **410** may be accomplished by a user’s digits touching the screen **104,108** in a spreading motion.

The above gestures may be combined in any manner, such as those shown by FIGS. 4G and 4H, to produce a determined functional result. For example, in FIG. 4G a tap gesture **420** is combined with a drag or flick gesture **412** in a direction away from the tap gesture **420**. In FIG. 4H, a tap gesture **420** is combined with a drag or flick gesture **416** in a direction towards the tap gesture **420**.

The functional result of receiving a gesture can vary depending on a number of factors, including a state of the device **100**, display **110, 114**, or screen **104, 108**, a context associated with the gesture, or sensed location of the gesture. The state of the device commonly refers to one or more of a configuration of the device **100**, a display orientation, and user and other inputs received by the device **100**. Context commonly refers to one or more of the particular application(s) selected by the gesture and the portion(s) of

the application currently executing, whether the application is a single- or multi-screen application, and whether the application is a multi-screen application displaying one or more windows in one or more screens or in one or more stacks. Sensed location of the gesture commonly refers to whether the sensed set(s) of gesture location coordinates are on a touch sensitive display **110**, **114** or a gesture capture region **120**, **124**, whether the sensed set(s) of gesture location coordinates are associated with a common or different display or screen **104,108**, and/or what portion of the gesture capture region contains the sensed set(s) of gesture location coordinates.

A tap, when received by an a touch sensitive display **110**, **114**, can be used, for instance, to select an icon to initiate or terminate execution of a corresponding application, to maximize or minimize a window, to reorder windows in a stack, and to provide user input such as by keyboard display or other displayed image. A drag, when received by a touch sensitive display **110**, **114**, can be used, for instance, to relocate an icon or window to a desired location within a display, to reorder a stack on a display, or to span both displays (such that the selected window occupies a portion of each display simultaneously). A flick, when received by a touch sensitive display **110**, **114** or a gesture capture region **120**, **124**, can be used to relocate a window from a first display to a second display or to span both displays (such that the selected window occupies a portion of each display simultaneously). Unlike the drag gesture, however, the flick gesture is generally not used to move the displayed image to a specific user-selected location but to a default location that is not configurable by the user.

The pinch gesture, when received by a touch sensitive display **110**, **114** or a gesture capture region **120**, **124**, can be used to minimize or otherwise increase the displayed area or size of a window (typically when received entirely by a common display), to switch windows displayed at the top of the stack on each display to the top of the stack of the other display (typically when received by different displays or screens), or to display an application manager (a “pop-up window” that displays the windows in the stack). The spread gesture, when received by a touch sensitive display **110**, **114** or a gesture capture region **120**, **124**, can be used to maximize or otherwise decrease the displayed area or size of a window, to switch windows displayed at the top of the stack on each display to the top of the stack of the other display (typically when received by different displays or screens), or to display an application manager (typically when received by an off-screen gesture capture region on the same or different screens).

The combined gestures of FIG. 4G, when received by a common display capture region in a common display or screen **104,108**, can be used to hold a first window stack location in a first stack constant for a display receiving the gesture while reordering a second window stack location in a second window stack to include a window in the display receiving the gesture. The combined gestures of FIG. 4H, when received by different display capture regions in a common display or screen **104,108** or in different displays or screens, can be used to hold a first window stack location in a first window stack constant for a display receiving the tap part of the gesture while reordering a second window stack location in a second window stack to include a window in the display receiving the flick or drag gesture. Although specific gestures and gesture capture regions in the preceding examples have been associated with corresponding sets of functional results, it is to be appreciated that these associations can be redefined in any manner to produce

differing associations between gestures and/or gesture capture regions and/or functional results.

Firmware and Software:

Referring now to FIG. 5A, one embodiment of device software **500** is illustrated. The memory **508** may store and the processor **504** may execute one or more software components. These components can include at least one operating system (OS) **516**, an application manager **562**, a desktop **566**, and/or one or more applications **564a** and/or **564b** from an application store **560**. The OS **516** can include a framework **520**, one or more frame buffers **548**, one or more drivers **512**, previously described in conjunction with FIG. 2, and/or a kernel **518**. The OS **516** can be any software, consisting of programs and data, which manages computer hardware resources and provides common services for the execution of various applications **564**. The OS **516** can be any operating system and, at least in some embodiments, dedicated to mobile devices, including, but not limited to, Linux, ANDROID™, iPhone OS (IOS™), WINDOWS PHONE 7™, etc. The OS **516** is operable to provide functionality to the phone by executing one or more operations, as described herein.

The applications **564** can be any higher level software that executes particular functionality for the user. Applications **564** can include programs such as email clients, web browsers, texting applications, games, media players, office suites, etc. The applications **564** can be stored in an application store **560**, which may represent any memory or data storage, and the management software associated therewith, for storing the applications **564**. Once executed, the applications **564** may be run in a different area of memory **508**.

The framework **520** may be any software or data that allows the multiple tasks running on the device to interact. In embodiments, at least portions of the framework **520** and the discrete components described hereinafter may be considered part of the OS **516** or an application **564**. However, these portions will be described as part of the framework **520**, but those components are not so limited. The framework **520** can include, but is not limited to, a Multi-Display Management (MDM) module **524**, a Surface Cache module **528**, a Window Management module **532**, an Input Management module **536**, a Task Management module **540**, an Application Model Manager **542**, a Display Controller, one or more frame buffers **548**, a task stack **552**, one or more window stacks **550** (which is a logical arrangement of windows and/or desktops in a display area), and/or an event buffer **556**.

The MDM module **524** includes one or more modules that are operable to manage the display of applications or other data on the screens of the device. An embodiment of the MDM module **524** is described in conjunction with FIG. 5B. In embodiments, the MDM module **524** receives inputs from the other OS **516** components, such as, the drivers **512**, and from the applications **564** to determine continually the state of the device **100**. The inputs assist the MDM module **524** in determining how to configure and allocate the displays according to the application’s preferences and requirements, and the user’s actions. Once a determination for display configurations is made, the MDM module **524** can bind the applications **564** to a display. The configuration may then be provided to one or more other components to generate a window with a display.

The Surface Cache module **528** includes any memory or storage and the software associated therewith to store or cache one or more images of windows. A series of active and/or non-active windows (or other display objects, such as, a desktop display) can be associated with each display.

An active window (or other display object) is currently displayed. A non-active windows (or other display objects) were opened and, at some time, displayed but are now not displayed. To enhance the user experience, before a window transitions from an active state to an inactive state, a “screen shot” of a last generated image of the window (or other display object) can be stored. The Surface Cache module **528** may be operable to store a bitmap of the last active image of a window (or other display object) not currently displayed. Thus, the Surface Cache module **528** stores the images of non-active windows (or other display objects) in a data store.

In embodiments, the Window Management module **532** is operable to manage the windows (or other display objects) that are active or not active on each of the displays. The Window Management module **532**, based on information from the MDM module **524**, the OS **516**, or other components, determines when a window (or other display object) is visible or not active. The Window Management module **532** may then put a non-visible window (or other display object) in a “not active state” and, in conjunction with the Task Management module Task Management **540** suspends the application’s operation. Further, the Window Management module **532** may assign, through collaborative interaction with the MDM module **524**, a display identifier to the window (or other display object) or manage one or more other items of data associated with the window (or other display object). The Window Management module **532** may also provide the stored information to the application **564**, the Task Management module **540**, or other components interacting with or associated with the window (or other display object). The Window Management module **532** can also associate an input task with a window based on window focus and display coordinates within the motion space.

The Input Management module **536** is operable to manage events that occur with the device. An event is any input into the window environment, for example, a user interface interactions with a user. The Input Management module **536** receives the events and logically stores the events in an event buffer **556**. Events can include such user interface interactions as a “down event,” which occurs when a screen **104**, **108** receives a touch signal from a user, a “move event,” which occurs when the screen **104**, **108** determines that a user’s finger is moving across a screen(s), an “up event,” which occurs when the screen **104**, **108** determines that the user has stopped touching the screen **104**, **108**, etc. These events are received, stored, and forwarded to other modules by the Input Management module **536**. The Input Management module **536** may also map screen inputs to a motion space which is the culmination of all physical and virtual display available on the device.

The motion space is a virtualized space that includes all touch sensitive displays **110,114** “tiled” together to mimic the physical dimensions of the device **100**. For example, when the device **100** is unfolded, the motion space size may be 960x800, which may be the number of pixels in the combined display area for both touch sensitive displays **110**, **114**. If a user touches on a first touch sensitive display **110** on location (40, 40), a full screen window can receive touch event with location (40, 40). If a user touches on a second touch sensitive display **114**, with location (40, 40), the full screen window can receive touch event with location (520, 40), because the second touch sensitive display **114** is on the right side of the first touch sensitive display **110**, so the device **100** can offset the touch by the first touch sensitive display’s **110** width, which is 480 pixels. When a hardware event occurs with location info from a driver **512**, the

framework **520** can up-scale the physical location to the motion space because the location of the event may be different based on the device orientation and state. The motion space may be as described in U.S. patent application Ser. No. 13/187,026, filed Jul. 20, 2011, entitled “Systems and Methods for Receiving Gesture Inputs Spanning Multiple Input Devices,” which is hereby incorporated by reference in its entirety for all that it teaches and for all purposes.

A task can be an application and a sub-task can be an application component that provides a window with which users can interact to do something, such as dial the phone, take a photo, send an email, or view a map. Each task may be given a window in which to draw a user interface. The window typically fills a display (for example, touch sensitive display **110,114**), but may be smaller than the display **110,114** and float on top of other windows. An application usually consists of multiple sub-tasks that are loosely bound to each other. Typically, one task in an application is specified as the “main” task, which is presented to the user when launching the application for the first time. Each task can then start another task or sub-task to perform different actions.

The Task Management module **540** is operable to manage the operation of one or more applications **564** that may be executed by the device. Thus, the Task Management module **540** can receive signals to launch, suspend, terminate, etc. an application or application sub-tasks stored in the application store **560**. The Task Management module **540** may then instantiate one or more tasks or sub-tasks of the application **564** to begin operation of the application **564**. Further, the Task Management Module **540** may launch, suspend, or terminate a task or sub-task as a result of user input or as a result of a signal from a collaborating framework **520** component. The Task Management Module **540** is responsible for managing the lifecycle of applications (tasks and sub-task) from when the application is launched to when the application is terminated.

The processing of the Task Management Module **540** is facilitated by a task stack **552**, which is a logical structure associated with the Task Management Module **540**. The task stack **552** maintains the state of all tasks and sub-tasks on the device **100**. When some component of the operating system **516** requires a task or sub-task to transition in its lifecycle, the OS **516** component can notify the Task Management Module **540**. The Task Management Module **540** may then locate the task or sub-task, using identification information, in the task stack **552**, and send a signal to the task or sub-task indicating what kind of lifecycle transition the task needs to execute. Informing the task or sub-task of the transition allows the task or sub-task to prepare for the lifecycle state transition. The Task Management Module **540** can then execute the state transition for the task or sub-task. In embodiments, the state transition may entail triggering the OS kernel **518** to terminate the task when termination is required.

Further, the Task Management module **540** may suspend the application **564** based on information from the Window Management Module **532**. Suspending the application **564** may maintain application data in memory but may limit or stop the application **564** from rendering a window or user interface. Once the application becomes active again, the Task Management module **540** can again trigger the application to render its user interface. In embodiments, if a task is suspended, the task may save the task’s state in case the

task is terminated. In the suspended state, the application task may not receive input because the application window is not visible to the user.

The frame buffer **548** is a logical structure(s) used to render the user interface. The frame buffer **548** can be created and destroyed by the OS kernel **518**. However, the Display Controller **544** can write the image data, for the visible windows, into the frame buffer **548**. A frame buffer **548** can be associated with one screen or multiple screens. The association of a frame buffer **548** with a screen can be controlled dynamically by interaction with the OS kernel **518**. A composite display may be created by associating multiple screens with a single frame buffer **548**. Graphical data used to render an application's window user interface may then be written to the single frame buffer **548**, for the composite display, which is output to the multiple screens **104,108**. The Display Controller **544** can direct an application's user interface to a portion of the frame buffer **548** that is mapped to a particular display **110,114**, thus, displaying the user interface on only one screen **104** or **108**. The Display Controller **544** can extend the control over user interfaces to multiple applications, controlling the user interfaces for as many displays as are associated with a frame buffer **548** or a portion thereof. This approach compensates for the multiple physical screens **104,108** that are in use by the software component above the Display Controller **544**.

The Application Manager **562** is an application that provides a presentation layer for the window environment. Thus, the Application Manager **562** provides the graphical model for rendering by the Task Management Module **540**. Likewise, the Desktop **566** provides the presentation layer for the Application Store **560**. Thus, the desktop provides a graphical model of a surface having selectable application icons for the Applications **564** in the Application Store **560** that can be provided to the Window Management Module **556** for rendering.

Further, the framework can include an Application Model Manager (AMM) **542**. The Application Manager **562** may interface with the AMM **542**. In embodiments, the AMM **542** receives state change information from the device **100** regarding the state of applications (which are running or suspended). The AMM **542** can associate bit map images from the Surface Cache Module **528** to the tasks that are alive (running or suspended). Further, the AMM **542** can convert the logical window stack maintained in the Task Manager Module **540** to a linear ("film strip" or "deck of cards") organization that the user perceives when the using the off gesture capture area **120** to sort through the windows. Further, the AMM **542** may provide a list of executing applications to the Application Manager **562**.

An embodiment of the MDM module **524** is shown in FIG. **5B**. The MDM module **524** is operable to determine the state of the environment for the device, including, but not limited to, the orientation of the device, whether the device **100** is opened or closed, what applications **564** are executing, how the applications **564** are to be displayed, what actions the user is conducting, the tasks being displayed, etc. To configure the display, the MDM module **524** interprets these environmental factors and determines a display configuration, as described in conjunction with FIGS. **6A-6J**. Then, the MDM module **524** can bind the applications **564** or other device components to the displays. The configuration may then be sent to the Display Controller **544** and/or the other components within the OS **516** to generate the display. The MDM module **524** can include one or more of, but is not limited to, a Display Configuration Module **568**, a Preferences Module **572**, a Device State Module **574**, a

Gesture Module **576**, a Requirements Module **580**, an Event Module **584**, and/or a Binding Module **588**.

The Display Configuration Module **568** determines the layout for the display. In embodiments, the Display Configuration Module **568** can determine the environmental factors. The environmental factors may be received from one or more other MDM modules **524** or from other sources. The Display Configuration Module **568** can then determine from the list of factors the best configuration for the display. Some embodiments of the possible configurations and the factors associated therewith are described in conjunction with FIGS. **6A-6F**.

The Preferences Module **572** is operable to determine display preferences for an application **564** or other component. For example, an application can have a preference for Single or Dual displays. The Preferences Module **572** can determine an application's display preference (e.g., by inspecting the application's preference settings) and may allow the application **564** to change to a mode (e.g., single screen, dual screen, max, etc.) if the device **100** is in a state that can accommodate the preferred mode. However, some user interface policies may disallow a mode even if the mode is available. As the configuration of the device changes, the preferences may be reviewed to determine if a better display configuration can be achieved for an application **564**.

The Device State Module **574** is operable to determine or receive the state of the device. The state of the device can be as described in conjunction with FIGS. **3A** and **3B**. The state of the device can be used by the Display Configuration Module **568** to determine the configuration for the display. As such, the Device State Module **574** may receive inputs and interpret the state of the device. The state information is then provided to the Display Configuration Module **568**.

The Gesture Module **576** is shown as part of the MDM module **524**, but, in embodiments, the Gesture module **576** may be a separate Framework **520** component that is separate from the MDM module **524**. In embodiments, the Gesture Module **576** is operable to determine if the user is conducting any actions on any part of the user interface. In alternative embodiments, the Gesture Module **576** receives user interface actions from the configurable area **112,116** only. The Gesture Module **576** can receive touch events that occur on the configurable area **112,116** (or possibly other user interface areas) by way of the Input Management Module **536** and may interpret the touch events (using direction, speed, distance, duration, and various other parameters) to determine what kind of gesture the user is performing. When a gesture is interpreted, the Gesture Module **576** can initiate the processing of the gesture and, by collaborating with other Framework **520** components, can manage the required window animation. The Gesture Module **576** collaborates with the Application Model Manager **542** to collect state information with respect to which applications are running (active or paused) and the order in which applications must appear when a user gesture is performed. The Gesture Module **576** may also receive references to bitmaps (from the Surface Cache Module **528**) and live windows so that when a gesture occurs it can instruct the Display Controller **544** how to move the window(s) across the display **110,114**. Thus, suspended applications may appear to be running when those windows are moved across the display **110,114**.

Further, the Gesture Module **576** can receive task information either from the Task Manage Module **540** or the Input Management module **536**. The gestures may be as defined in conjunction with FIGS. **4A** through **4H**. For example, moving a window causes the display to render a series of display frames that illustrate the window moving.

The gesture associated with such user interface interaction can be received and interpreted by the Gesture Module 576. The information about the user gesture is then sent to the Task Management Module 540 to modify the display binding of the task.

The Requirements Module 580, similar to the Preferences Module 572, is operable to determine display requirements for an application 564 or other component. An application can have a set display requirement that must be observed. Some applications require a particular display orientation. For example, the application “Angry Birds” can only be displayed in landscape orientation. This type of display requirement can be determined or received, by the Requirements Module 580. As the orientation of the device changes, the Requirements Module 580 can reassert the display requirements for the application 564. The Display Configuration Module 568 can generate a display configuration that is in accordance with the application display requirements, as provided by the Requirements Module 580.

The Event Module 584, similar to the Gesture Module 576, is operable to determine one or more events occurring with an application or other component that can affect the user interface. Thus, the Event Module 584 can receive event information either from the event buffer 556 or the Task Management module 540. These events can change how the tasks are bound to the displays. The Event Module 584 can collect state change information from other Framework 520 components and act upon that state change information. In an example, when the phone is opened or closed or when an orientation change has occurred, a new message may be rendered in a secondary screen. The state change based on the event can be received and interpreted by the Event Module 584. The information about the events then may be sent to the Display Configuration Module 568 to modify the configuration of the display.

The Binding Module 588 is operable to bind the applications 564 or the other components to the configuration determined by the Display Configuration Module 568. A binding associates, in memory, the display configuration for each application with the display and mode of the application. Thus, the Binding Module 588 can associate an application with a display configuration for the application (e.g. landscape, portrait, multi-screen, etc.). Then, the Binding Module 588 may assign a display identifier to the display. The display identifier associated the application with a particular display of the device 100. This binding is then stored and provided to the Display Controller 544, the other components of the OS 516, or other components to properly render the display. The binding is dynamic and can change or be updated based on configuration changes associated with events, gestures, state changes, application preferences or requirements, etc.

User Interface Configurations:

With reference now to FIGS. 6A-J, various types of output configurations made possible by the device 100 will be described hereinafter.

FIGS. 6A and 6B depict two different output configurations of the device 100 being in a first state. Specifically, FIG. 6A depicts the device 100 being in a closed portrait state 304 where the data is displayed on the primary screen 104. In this example, the device 100 displays data via the touch sensitive display 110 in a first portrait configuration 604. As can be appreciated, the first portrait configuration 604 may only display a desktop or operating system home screen. Alternatively, one or more windows may be pre-

sented in a portrait orientation while the device 100 is displaying data in the first portrait configuration 604.

FIG. 6B depicts the device 100 still being in the closed portrait state 304, but instead data is displayed on the secondary screen 108. In this example, the device 100 displays data via the touch sensitive display 114 in a second portrait configuration 608.

It may be possible to display similar or different data in either the first or second portrait configuration 604, 608. It may also be possible to transition between the first portrait configuration 604 and second portrait configuration 608 by providing the device 100 a user gesture (e.g., a double tap gesture), a menu selection, or other means. Other suitable gestures may also be employed to transition between configurations. Furthermore, it may also be possible to transition the device 100 from the first or second portrait configuration 604, 608 to any other configuration described herein depending upon which state the device 100 is moved.

An alternative output configuration may be accommodated by the device 100 being in a second state. Specifically, FIG. 6C depicts a third portrait configuration where data is displayed simultaneously on both the primary screen 104 and the secondary screen 108. The third portrait configuration may be referred to as a Dual-Portrait (PD) output configuration. In the PD output configuration, the touch sensitive display 110 of the primary screen 104 depicts data in the first portrait configuration 604 while the touch sensitive display 114 of the secondary screen 108 depicts data in the second portrait configuration 608. The simultaneous presentation of the first portrait configuration 604 and the second portrait configuration 608 may occur when the device 100 is in an open portrait state 320. In this configuration, the device 100 may display one application window in one display 110 or 114, two application windows (one in each display 110 and 114), one application window and one desktop, or one desktop. Other configurations may be possible. It should be appreciated that it may also be possible to transition the device 100 from the simultaneous display of configurations 604, 608 to any other configuration described herein depending upon which state the device 100 is moved. Furthermore, while in this state, an application’s display preference may place the device into bilateral mode, in which both displays are active to display different windows in the same application. For example, a Camera application may display a viewfinder and controls on one side, while the other side displays a mirrored preview that can be seen by the photo subjects. Games involving simultaneous play by two players may also take advantage of bilateral mode.

FIGS. 6D and 6E depicts two further output configurations of the device 100 being in a third state. Specifically, FIG. 6D depicts the device 100 being in a closed landscape state 340 where the data is displayed on the primary screen 104. In this example, the device 100 displays data via the touch sensitive display 110 in a first landscape configuration 612. Much like the other configurations described herein, the first landscape configuration 612 may display a desktop, a home screen, one or more windows displaying application data, or the like.

FIG. 6E depicts the device 100 still being in the closed landscape state 340, but instead data is displayed on the secondary screen 108. In this example, the device 100 displays data via the touch sensitive display 114 in a second landscape configuration 616. It may be possible to display similar or different data in either the first or second portrait configuration 612, 616. It may also be possible to transition between the first landscape configuration 612 and second landscape configuration 616 by providing the device 100

with one or both of a twist and tap gesture or a flip and slide gesture. Other suitable gestures may also be employed to transition between configurations. Furthermore, it may also be possible to transition the device **100** from the first or second landscape configuration **612**, **616** to any other configuration described herein depending upon which state the device **100** is moved.

FIG. **6F** depicts a third landscape configuration where data is displayed simultaneously on both the primary screen **104** and the secondary screen **108**. The third landscape configuration may be referred to as a Dual-Landscape (LD) output configuration. In the LD output configuration, the touch sensitive display **110** of the primary screen **104** depicts data in the first landscape configuration **612** while the touch sensitive display **114** of the secondary screen **108** depicts data in the second landscape configuration **616**. The simultaneous presentation of the first landscape configuration **612** and the second landscape configuration **616** may occur when the device **100** is in an open landscape state **340**. It should be appreciated that it may also be possible to transition the device **100** from the simultaneous display of configurations **612**, **616** to any other configuration described herein depending upon which state the device **100** is moved.

FIGS. **6G** and **6H** depict two views of a device **100** being in yet another state. Specifically, the device **100** is depicted as being in an easel state **312**. FIG. **6G** shows that a first easel output configuration **618** may be displayed on the touch sensitive display **110**. FIG. **6H** shows that a second easel output configuration **620** may be displayed on the touch sensitive display **114**. The device **100** may be configured to depict either the first easel output configuration **618** or the second easel output configuration **620** individually. Alternatively, both the easel output configurations **618**, **620** may be presented simultaneously. In some embodiments, the easel output configurations **618**, **620** may be similar or identical to the landscape output configurations **612**, **616**. The device **100** may also be configured to display one or both of the easel output configurations **618**, **620** while in a modified easel state **316**. It should be appreciated that simultaneous utilization of the easel output configurations **618**, **620** may facilitate two-person games (e.g., Battleship®, chess, checkers, etc.), multi-user conferences where two or more users share the same device **100**, and other applications. As can be appreciated, it may also be possible to transition the device **100** from the display of one or both configurations **618**, **620** to any other configuration described herein depending upon which state the device **100** is moved.

FIG. **6I** depicts yet another output configuration that may be accommodated while the device **100** is in an open portrait state **320**. Specifically, the device **100** may be configured to present a single continuous image across both touch sensitive displays **110**, **114** in a portrait configuration referred to herein as a Portrait-Max (PMax) configuration **624**. In this configuration, data (e.g., a single image, application, window, icon, video, etc.) may be split and displayed partially on one of the touch sensitive displays while the other portion of the data is displayed on the other touch sensitive display. The Pmax configuration **624** may facilitate a larger display and/or better resolution for displaying a particular image on the device **100**. Similar to other output configurations, it may be possible to transition the device **100** from the Pmax configuration **624** to any other output configuration described herein depending upon which state the device **100** is moved.

FIG. **6J** depicts still another output configuration that may be accommodated while the device **100** is in an open landscape state **348**. Specifically, the device **100** may be

configured to present a single continuous image across both touch sensitive displays **110**, **114** in a landscape configuration referred to herein as a Landscape-Max (LMax) configuration **628**. In this configuration, data (e.g., a single image, application, window, icon, video, etc.) may be split and displayed partially on one of the touch sensitive displays while the other portion of the data is displayed on the other touch sensitive display. The Lmax configuration **628** may facilitate a larger display and/or better resolution for displaying a particular image on the device **100**. Similar to other output configurations, it may be possible to transition the device **100** from the Lmax configuration **628** to any other output configuration described herein depending upon which state the device **100** is moved.

FIGS. **7A-7C** illustrate an embodiment showing device **100** and how device **100** responds when a gesture is made. FIG. **7A** illustrates device **100** (with screens **104** and **108**) when a focus is on screen **104** and display area **110**. As noted above, “focus” means active and selected for receiving input. Accordingly, in FIG. **7A** screen **104** and display area **110** are active and selected for input. Highlight **704** provides an indication to a user that screen **104** and display area **110** have the focus. If a user presses configurable area **112**, device **100** will consider the inputs as inputs for screen **104** and/or for display **110**.

As shown in FIG. **7B**, a user can make a gesture **708**, such as a tap, drag, or flick gesture on display **114** to indicate a request to launch an application. In some embodiments, the gesture may be made in gesture capture region **120** (e.g., gesture **708A**). Device **100** receives the gesture **708** or **708A**. In the embodiment shown in FIG. **7**, the gesture **708** is made on an icon **716** that represents the application. In response to the gesture **708**, an application is launched. As shown in FIG. **7C**, the launching of the application results in an image **720** being displayed on display **114**. The focus is also moved from screen **104** to screen **108**, and display area **114**, so that image **720** is in focus and a user can immediately begin to interact with the launched application through the image **720**. Also, highlighting **704** changes from screen **104** and display area **110** to screen **108** and display area **114**. The highlighting **704** provides an indication to a user of what screen, display, and/or application currently has the focus.

Highlighting **704** as noted above, indicates that screen **104** and display **110** are active. Highlighting **704** can be effected in a number of different ways. In some embodiments, the highlighting **704** is accomplished using light. In these embodiments, a backlight in device **100** may be configured to provide brighter light in some areas, such as around a border as shown in FIGS. **7A-7C**. In other embodiments, the brighter light may be located on just one side/area or may be the entire display **110**, which is made brighter than at least a portion of screen **108** and/or display **114**.

In other embodiments, highlighting **704** may be accomplished using color, or a displayed image such as an icon that indicates that a screen (**104** or **108**) and/or a display (**110** or **114**) have the focus. In other embodiments, the highlighting may be accomplished by some other difference, such as changing text to a different font type, size, or other format change (e.g., italics, underline, bold etc). In some embodiments, the highlighting can be accomplished, or enhanced, by changing a different screen, display, and/or displayed image. For example, in embodiments, the screen, display and/or displayed image that does not have the focus, will be deemphasized by darkening, a color change, or other features that distinguishes it from the highlighted screen, dis-

play, and/or image. As can be appreciated, a combination of one or more of the above highlighting features may be used in some embodiments.

In one embodiment, in addition to highlighting 704, configurable area 112 of screen 104 is highlighted to indicate that screen 104 and display 110 have the focus. Device 100 can be configured so that configurable areas are only highlighted when the corresponding screen has the focus. That is, configurable area 112 is highlighted when screen 104 is in focus, while configurable area 116 is highlighted when focus is on screen 108. As indicated above, the highlighting may be effected by lighting, color, or an image displayed near the configurable area. In the embodiment, shown in FIGS. 7A-7C, when screen 104 is in focus, the configurable area 112 is back lit to show buttons that can be used to receive input from a user.

In some embodiments, when configurable area 112 is highlighted, input can be received by pressing portions of area 112. At the same time, device 100 may be configured so that no input is received from configurable area 116. Thus, even if a user presses on area 116, no input will be received by device 100. Similarly, when configurable area 116 is highlighted device 100 will allow input to be received from area 116, and no input will be received from area 112. In other embodiments, only one configurable area will be highlighted at a time reflecting the particular screen, display, or image that is in focus. That is, when configurable area 112 is highlighted configurable area 116 will not be highlighted, and when configurable area 116 is highlighted configurable area 112 will not be highlighted.

It is noted that although gesture 708 is made on display 114, in other embodiments, the gesture 708 may be made on one or more portions of display 110, display 114, configurable area 112, configurable area 116, or as shown in FIG. 7B (gesture 708A). The gesture 708 may involve touching portions of screens 104 and/or 108 or can involve only movement above the surface of portions of screens 104 and/or 108. In some embodiments, for the gesture to be recognized, contact is required to be made with the display 110 or 114 for a predetermined period of time.

As a result of receiving the gesture 708, an application is launched and focus changes from screen 104 and display 110 to screen 108 and display 114. In some embodiments, device 100 is configured to interpret different gestures as indications of different operations. For example, the device 100 may be configured to move an image when the gesture 708 is a drag gesture or flick gesture, but launch applications if gesture 708 is a flick, tap gesture, or double tap gesture. In embodiments, when an application is launched, any image displayed in response to the launching of the application (e.g., open window) is placed in focus. This allows a user to immediately begin to interact with the open application to the displayed image. In some embodiments, the location of the gesture 708, whether in gesture capture region 120 or some other portion of displays 110 and 114, may determine what operation is performed.

FIGS. 8A-8C illustrates another embodiment of device 100 and its output in response to receiving a gesture. In FIG. 8A the focus is on screen 104, display 110, and image 804. Image 804 is in embodiments a window of an active application which is selected to receive input from a user. In other embodiment, image 804 is an icon on a desktop. In the embodiment shown in FIGS. 8A-8C, a user makes a gesture 708 on display 114. The gesture is a gesture that is associated with launching an application, i.e. a tap on display 114. In response to the gesture 708, device 100 launches an appli-

cation and then changes focus away from screen 104, display 110, and image 804 and to screen 108 and display 114.

In some embodiments, as shown in FIG. 8C, the gesture 708 that results in automatically launching an application and placing the focus on an image, i.e., image 808, displayed when the application is launched, does not have to occur on an icon or other representation of an application. In these embodiments, device 100 may be configured by a user so that when the gesture is received on any portion of display 114 (or in other embodiments 110), an application is launched and the focus will be changed on an image, e.g., a window of an open application, displayed as a result of the launched application. The user may, for example, list applications in order of priority such that an application at the top of the list will be launched first. If a window is open for an application at the top the list, then the list can be traversed in order of priority until an application without an open window is found. If all of the applications on the list have open windows then the gesture will not cause any applications to launch, but instead the focus will change to the open window, on display 114 and screen 108, of the application associated with the application at the top of the priority list. In some embodiments, the focus may be changed to a window of the same application that was previously in focus, e.g., a window associated with the same application as image 804. In other embodiments, the gesture 708 may always launch a default application and place the focus on an image displayed as a result of the launch (e.g., open window).

In some embodiments, device 100 is configured so that depending upon the particular gesture 708, an application may be launched and be placed in focus or not. For example, the device 100 may be configured to, in response to gesture 708, launch an application and place the focus on an image displayed as a result of the launch. However, if gesture 708 is a different gesture, a different application may be launched, no application will be launched, or an application may be launched but focus is not changed to an image displayed as a result of the launched application. In other embodiments, the location of the gesture 708, whether in gesture capture region 120 or some other portion of displays 110 and 114, may determine whether an application is launched or not.

It is noted that although gesture 708 is being made on display 114, in other embodiments, the gesture 708 is made on one or more gesture capture regions (e.g., 120), which are not on display 110 or display 114. The gesture 708 may involve touching some portion of screens 102 or 104 and or can involve only movement above the surface of displays 110 and 114.

As shown in FIG. 8C, when an application is launched and focus is changed to screen 108 and display 114, configurable area 116 is highlighted to indicate that the focus is changed. Device 100 can be configured so that configurable areas are only highlighted when the corresponding screen has the focus. That is, configurable area 112 is highlighted when screen 104 and/or display 110 is in focus, while configurable area 116 is highlighted when focus is on screen 108 and/or display 114. As indicated above, the highlighting may be effected by lighting, color, or an image displayed near the configurable area. In the embodiment, shown in FIGS. 8A-8C, when screen 104 and/or display 110 is in focus, the configurable area 112 is back lit to show buttons that can be used to receive input from a user. Similarly, when

focus changes to screen **108** and/or display **114**, the configurable area **116** is back lit to show buttons that can be used to receive input from a user.

Referring now to FIG. **9**, a flow diagram **900** in accordance with at least some embodiments of the present disclosure is shown and will be described. Flow **900** is in embodiments performed by a device such as device **100**. More specifically, one or more hardware or software components may be involved in performing flow **900**. In one embodiment, modules in middleware **520** (FIG. **5A**) such as multi-display management class **524** (FIG. **5B**) perform one or more of the steps of flow **900**. In other embodiments, in addition to, or in lieu of, middleware **520** performing steps of flow **900**, operating system kernel(s) **516a**, processor **504**, and/or drivers **512a-512b** may also perform steps of flow **900**.

Flow **900** is initiated at **904**. Flow **900** passes from **904** to optional step **908** where input regarding focus behavior is received. In this step, a user may provide configuration information that indicates how a device should handle gestures. In embodiments, the device is device **100** (FIGS. **1-3**), which includes multiple screens. The user may input any information that affects how a device **100** may handle input gestures, including but not limited to, what applications are launched, changes (if any) that occur to displays **104** and **108** when a gesture has been received, what is highlighted when focus is changed, priority list of applications when a gesture is received, whether focus changes are limited to a display, screen, and/or displayed image, whether the type of gesture received results in different operations, and other information. In one embodiment, the input indicates that in response to a gesture, an application should be launched and focus should be placed on an image displayed as a result of the launching of the application.

From step **908**, flow **900** passes to step **910** where a gesture is received. The gesture can be received in some embodiments by pressure sensitive displays **110** and **114** or gesture capture regions such as regions **120** and **124**. In some embodiments, as shown in FIGS. **1** and **2**, the gesture capture region(s) is distinct and located away from the pressure sensitive displays. In other embodiments the gesture capture area may overlap partially or completely with the pressure sensitive displays.

The gesture may be any type of gesture. In embodiments, the gesture is one or more of the gestures illustrated in FIG. **4A-4H**. The device **100** is configured so that the gesture received at **910** indicates a request to launch an application and change focus to an image (e.g., window) displayed as a result of launching the application.

Flow **900** passes from **912** to step **916** where the focus is changed to an image displayed as a result of launching the application. The image may be for example a window that provides a user interface for a user to begin interacting with the application. In some embodiments, this may involve changing the focus from a different window that is displayed on a different display and/or screen. For example, if at the time the gesture is received at step **910** the focus is on a window of a different application, the focus will be changed from the different window to the newly opened window. In other embodiments, there may not be any image that currently has the focus in which case the focus is placed on the newly opened window. As indicated above, if the newly opened window is on a different screen and display than a window that currently is in focus, the focus will change to the different screen and display where the new the opened window is displayed. The newly opened window, in some embodiments, is displayed on a display and screen which

currently displays a window that is in focus. In these instances, the focus will change from a window with the current focus to the newly opened window.

It should be noted that in some embodiments, step **916** may involve a number of sub steps. For example, in some embodiments as part of step **916**, a configurable area may be highlighted, a display may be highlighted, an icon may be generated indicating the focus change, and/or portions of a first screen may be changed to emphasize the highlighting on a second screen. In some embodiments, the substeps may involve not allowing input from a configurable area associated with a first screen and allowing input from a configurable area associated with a second screen. Flow **900** ends at **920**.

The exemplary systems and methods of this disclosure have been described in relation to FIGS. **1-10**. However, to avoid unnecessarily obscuring the present disclosure, the preceding description omits a number of known structures and devices. This omission is not to be construed as a limitation of the scopes of the claims. Specific details are set forth to provide an understanding of the present disclosure. It should however be appreciated that the present disclosure may be practiced in a variety of ways beyond the specific detail set forth herein.

Furthermore, while the exemplary aspects, embodiments, and/or configurations illustrated herein show the various components of the system collocated, certain components of the system can be located remotely, at distant portions of a distributed network, such as a LAN and/or the Internet, or within a dedicated system. Thus, it should be appreciated, that the components of the system can be combined in to one or more devices, such as a phone, computer, PDA, electronic book reader, gaming device, or collocated on a particular node of a distributed network, such as an analog and/or digital telecommunications network, a packet-switch network, or a circuit-switched network. It will be appreciated from the preceding description, and for reasons of computational efficiency, that the components of the system can be arranged at any location within a distributed network of components without affecting the operation of the system. For example, the various components can be located in a switch such as a PBX and media server, gateway, in one or more communications devices, at one or more users' premises, or some combination thereof. Similarly, one or more functional portions of the system could be distributed between a telecommunications device(s) and an associated computing device.

Furthermore, it should be appreciated that the various links connecting the elements can be wired or wireless links, or any combination thereof, or any other known or later developed element(s) that is capable of supplying and/or communicating data to and from the connected elements. These wired or wireless links can also be secure links and may be capable of communicating encrypted information. Transmission media used as links, for example, can be any suitable carrier for electrical signals, including coaxial cables, copper wire and fiber optics, and may take the form of acoustic or light waves, such as those generated during radio-wave and infra-red data communications.

Also, while the flowcharts have been discussed and illustrated in relation to a particular sequence of events, it should be appreciated that changes, additions, and omissions to this sequence can occur without materially affecting the operation of the disclosed embodiments, configuration, and aspects.

A number of variations and modifications of the disclosure can be used. It would be possible to provide for some features of the disclosure without providing others.

For example in one alternative embodiment, all of the focus behavior information and information regarding launching applications may be preprogrammed into the device **100**. In these embodiments, there would be no input received from a user regarding how a device **100** handles gestures indicating the launching of applications or a change in focus.

In other alternative embodiments, device **100** may be in any configuration described above with respect to FIGS. **6A-6J**. In these embodiments, gestures would be received as described above indicating a request for launching an application or changing focus.

In yet another embodiment, the systems and methods of this disclosure can be implemented in conjunction with a special purpose computer, a programmed microprocessor or microcontroller and peripheral integrated circuit element(s), an ASIC or other integrated circuit, a digital signal processor, a hard-wired electronic or logic circuit such as discrete element circuit, a programmable logic device or gate array such as PLD, PLA, FPGA, PAL, special purpose computer, any comparable means, or the like. In general, any device(s) or means capable of implementing the methodology illustrated herein can be used to implement the various aspects of this disclosure. Exemplary hardware that can be used for the disclosed embodiments, configurations and aspects includes computers, handheld devices, telephones (e.g., cellular, Internet enabled, digital, analog, hybrids, and others), and other hardware known in the art. Some of these devices include processors (e.g., a single or multiple microprocessors), memory, nonvolatile storage, input devices, and output devices. Furthermore, alternative software implementations including, but not limited to, distributed processing or component/object distributed processing, parallel processing, or virtual machine processing can also be constructed to implement the methods described herein.

In yet another embodiment, the disclosed methods may be readily implemented in conjunction with software using object or object-oriented software development environments that provide portable source code that can be used on a variety of computer or workstation platforms. Alternatively, the disclosed system may be implemented partially or fully in hardware using standard logic circuits or VLSI design. Whether software or hardware is used to implement the systems in accordance with this disclosure is dependent on the speed and/or efficiency requirements of the system, the particular function, and the particular software or hardware systems or microprocessor or microcomputer systems being utilized.

In yet another embodiment, the disclosed methods may be partially implemented in software that can be stored on a storage medium, executed on programmed general-purpose computer with the cooperation of a controller and memory, a special purpose computer, a microprocessor, or the like. In these instances, the systems and methods of this disclosure can be implemented as program embedded on personal computer such as an applet, JAVA® or CGI script, as a resource residing on a server or computer workstation, as a routine embedded in a dedicated measurement system, system component, or the like. The system can also be implemented by physically incorporating the system and/or method into a software and/or hardware system.

Although the present disclosure describes components and functions implemented in the aspects, embodiments, and/or configurations with reference to particular standards

and protocols, the aspects, embodiments, and/or configurations are not limited to such standards and protocols. Other similar standards and protocols not mentioned herein are in existence and are considered to be included in the present disclosure. Moreover, the standards and protocols mentioned herein and other similar standards and protocols not mentioned herein are periodically superseded by faster or more effective equivalents having essentially the same functions. Such replacement standards and protocols having the same functions are considered equivalents included in the present disclosure.

The present disclosure, in various aspects, embodiments, and/or configurations, includes components, methods, processes, systems and/or apparatus substantially as depicted and described herein, including various aspects, embodiments, configurations, subcombinations, and/or subsets thereof. Those of skill in the art will understand how to make and use the disclosed aspects, embodiments, and/or configurations after understanding the present disclosure. The present disclosure, in various aspects, embodiments, and/or configurations, includes providing devices and processes in the absence of items not depicted and/or described herein or in various aspects, embodiments, and/or configurations hereof, including in the absence of such items as may have been used in previous devices or processes, e.g., for improving performance, achieving ease and/or reducing cost of implementation.

The foregoing discussion has been presented for purposes of illustration and description. The foregoing is not intended to limit the disclosure to the form or forms disclosed herein. In the foregoing Detailed Description for example, various features of the disclosure are grouped together in one or more aspects, embodiments, and/or configurations for the purpose of streamlining the disclosure. The features of the aspects, embodiments, and/or configurations of the disclosure may be combined in alternate aspects, embodiments, and/or configurations other than those discussed above. This method of disclosure is not to be interpreted as reflecting an intention that the claims require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive aspects lie in less than all features of a single foregoing disclosed aspect, embodiment, and/or configuration. Thus, the following claims are hereby incorporated into this Detailed Description, with each claim standing on its own as a separate preferred embodiment of the disclosure.

Moreover, though the description has included description of one or more aspects, embodiments, and/or configurations and certain variations and modifications, other variations, combinations, and modifications are within the scope of the disclosure, e.g., as may be within the skill and knowledge of those in the art, after understanding the present disclosure. It is intended to obtain rights which include alternative aspects, embodiments, and/or configurations to the extent permitted, including alternate, interchangeable and/or equivalent structures, functions, ranges or steps to those claimed, whether or not such alternate, interchangeable and/or equivalent structures, functions, ranges or steps are disclosed herein, and without intending to publicly dedicate any patentable subject matter.

What is claimed is:

1. A method, comprising:

displaying a first image of a first application on a first display, wherein the first image is in focus, wherein input options for the first application are displayed in a first configurable area, wherein input is allowed from the first configurable area and the first display, wherein

33

no input options are displayed in a second configurable area, wherein input is not allowed from the second configurable area, wherein input is allowed from a second display, wherein the first configurable area does not display content from an application, and wherein the second configurable area does not display content from an application;

receiving first input indicating a request to launch a second application;

launching the second application; and

in response to launching the second application:

displaying, by the second application, a second image on the second display; and

changing the focus from the first image to the second image;

stopping display of input options in the first configurable area, wherein input is not allowed from the first configurable area, wherein input is allowed from the first display; and

displaying input options for the second application in the second configurable area, wherein input is allowed from the second configurable area and the second display.

2. The method of claim 1, wherein the first image is displayed in portrait mode on the first display and the second image is displayed in portrait mode on the second display, and wherein the first display, the first configurable area, the second display, and the second configurable area are on a common first screen.

3. The method of claim 1, wherein the first image is displayed in landscape mode on the first display and the second image is displayed in landscape mode on the second display, and wherein the first display and the first configurable area are on a first screen, and wherein the second display and the second configurable area are on a different second screen.

4. The method of claim 1, further comprising: wherein the first image is a first open window of the first application and the second image is a second open window of the second application.

5. The method of claim 1, further comprising: receiving second input indicating that in response to receiving the first input, the second application should be launched and the focus should be placed on the second image displayed by the second application.

6. The method of claim 1, further comprising: highlighting the first configurable area when the focus is on the first image in the first display; and changing the highlighting to the second configurable area when the focus is on the second image in the second display.

7. The method of claim 6, wherein the first configuration area is separate from the first display and the second configurable area is separate from the second display.

8. The method of claim 1, further comprising: in response to receiving the first input, highlighting at least one of the second image or the second display.

9. The method of claim 1, wherein the first input is a tap gesture received by one of the first display, the second display, a first gesture capture region, or a second gesture capture region, wherein the first gesture capture region is separate from the first display and the second gesture capture region is separate from the second display, and wherein the first and second gesture capture regions are not capable of displaying images of applications.

34

10. A non-transitory computer readable medium storing computer executable instructions that when executed by at least one processor perform a method, comprising:

displaying a first image of a first application on a first display, wherein the first image is in focus wherein input is allowed from the first display, and wherein input is allowed from a second display;

receiving first input indicating a request to launch a second application, the input is received by one of the first display and the second display;

in response to receiving the first input, launching the second application;

displaying, by the second application, a second image on the second display; and

changing focus from the first image to the second display, wherein input is allowed from the first display, and wherein input is allowed from the second display;

in response changing focus, stopping display of input options in a first configurable area, wherein input is not allowed from the first configurable area, wherein input is allowed from the first display; and

in response changing focus, displaying input options for the second application in a second configurable area, wherein input is allowed from the second configurable area and the second display, wherein the first configurable area does not display content from an application, and wherein the second configurable area does not display content from an application.

11. The non-transitory computer readable medium of claim 10, wherein the first display, the first configurable area, the second display, and the second configurable area are on a common first screen, wherein the first input is a tap gesture received by one of the first display, the second display, a first gesture capture region, or a second gesture capture region, wherein the tap requires contact with the second display for a predetermined period of time, wherein the first gesture capture region is separate from the first display and the second gesture capture region is separate from the second display, and wherein the first and second gesture capture regions are not capable of displaying images of applications.

12. The non-transitory computer readable medium of claim 11, wherein in response to changing focus to the second display, allowing input from the second gesture capture region, and allowing input from the first gesture capture region.

13. The non-transitory computer readable medium of claim 10, wherein the tap requires contact with the second display for a predetermined period of time, wherein the first display and the first configurable area are on a first screen, and wherein the second display and the second configurable area are on a different second screen.

14. The non-transitory computer readable medium of claim 10, wherein the method further comprises: highlighting a first configurable area on a first screen when the focus is on the first image in the first display, wherein input options for the first application are displayed in the first configurable area when the focus is on the first image, wherein input is allowed from the first configurable area when the focus is on the first image, wherein no input options are displayed in a second configurable area of the first screen and input is not allowed from the second configurable area when the focus is on the first image; and changing the highlighting to the second configurable area when the focus is on the second image in the second display, wherein input options for the second applica-

35

tion are displayed in the second configurable area when the focus is on the second image, wherein input is allowed from the second configurable area when the focus is on the second image, and wherein no input options are displayed in the first configurable area and input is not allowed from the first configurable area when the focus is on the second image.

15. The non-transitory computer readable medium of claim 14, wherein the first configurable area is separate from the first display and the second configurable area is separate from the second display.

16. The non-transitory computer readable medium of claim 10, wherein the method further comprises: receiving second input indicating that in response to the first input, the focus should be changed to the second display.

17. A communication device, comprising:

a first touch sensitive display and a first configurable area;
a second touch sensitive display and a second configurable area; and

a computer readable medium that stores computer executable instructions that, when executed by at least one processor, perform a method comprising:

displaying a first image of a first application on the first touch sensitive display, wherein the first image is in focus, wherein input options for the first application are displayed in the first configurable area, wherein input is allowed from the first configurable area and the first touch sensitive display, wherein no input options are displayed in the second configurable area, wherein input is not allowed from the second configurable area, wherein input is allowed from the second touch sensitive display, wherein the first configurable area does not display content from an application, and wherein the second configurable area does not display content from an application;

receiving first input on the first touch sensitive display or the second touch sensitive display indicating a request to launch a second application;

36

launching the second application;

displaying, by the second application, a second image on the second touch sensitive display; and

changing the focus from the first touch sensitive display to the second touch sensitive display, wherein no input options are displayed in the first configurable area, wherein input is not allowed from the first configurable area, wherein input is allowed from the first touch sensitive display, wherein input options for the second application are displayed in the second configurable area, and wherein input is allowed from the second configurable area and the second touch sensitive display.

18. The device of claim 17, wherein the first display, the first configurable area, the second display, and the second configurable area are on a common first screen and wherein the method further comprises:

providing a visual indication that focus is on the first image in the first touch sensitive display, wherein the indication identifies which display or application has the focus; and

changing the visual indication when the focus is on the second image in the second touch sensitive display.

19. The device of claim 17, wherein the first configurable area is separate from the first touch sensitive display and the second configurable area is separate from the second touch sensitive display, wherein the first display and the first configurable area are on a first screen, and wherein the second display and the second configurable area are on a different second screen.

20. The device of claim 17, wherein the first input is a tap gesture received by one of the first touch sensitive display, the second touch sensitive display, a first gesture capture region, or a second gesture capture region, wherein the first gesture capture region is separate from the first touch sensitive display and the second gesture capture region is separate from the second touch sensitive display, and wherein the first and second gesture capture regions are not capable of displaying images of applications.

* * * * *