

US009796038B2

(12) **United States Patent**
Rappl et al.

(10) **Patent No.:** **US 9,796,038 B2**
(45) **Date of Patent:** ***Oct. 24, 2017**

(54) **WELDING SYSTEM WITH POWER LINE COMMUNICATION**

(71) Applicant: **ILLINOIS TOOL WORKS INC.**,
Glenview, IL (US)

(72) Inventors: **James Francis Rappl**, Neenah, WI (US); **Brian Lee Ott**, Sherwood, WI (US); **Andrew David Nelson**, Grand Chute, WI (US); **Jeremy Daniel Overesch**, Neenah, WI (US); **Anthony Van Bergen Salsich**, Appleton, WI (US); **Quinn William Schartner**, Kaukauna, WI (US); **Kenneth Austin Stanzel**, Appleton, WI (US)

(73) Assignee: **ILLINOIS TOOL WORKS INC.**,
Glenview, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/624,104**

(22) Filed: **Feb. 17, 2015**

(65) **Prior Publication Data**
US 2015/0158104 A1 Jun. 11, 2015

Related U.S. Application Data

(63) Continuation of application No. 12/843,321, filed on Jul. 26, 2010, now Pat. No. 8,957,344.
(Continued)

(51) **Int. Cl.**
B23K 9/18 (2006.01)
B23K 9/10 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B23K 9/1087** (2013.01); **B23K 9/095** (2013.01); **B23K 9/1006** (2013.01); **B23K 9/1068** (2013.01); **B23K 9/124** (2013.01)

(58) **Field of Classification Search**
CPC B23K 9/095; B23K 9/1006; B23K 9/1068; B23K 9/1087; B23K 9/124
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,043,331 A 6/1936 Notvest
2,175,891 A 10/1939 Graham
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101360580 2/2009
DE 19828986 12/1999
(Continued)

OTHER PUBLICATIONS

International Search Report for application No. PCT/US2010/045906 dated Nov. 29, 2010.


Primary Examiner — Duy T Nguyen

(74) *Attorney, Agent, or Firm* — Fletcher Yoder P.C.

(57) **ABSTRACT**

Various welding systems that provide communication over auxiliary or weld power lines are provided. The disclosed embodiments may include a multi-process welding power supply that is communicatively coupled to a pendant via an auxiliary conduit that facilitates the exchange of data and power between components of the welding system. In some embodiments, the pendant may also include auxiliary outlets that allow an operator to power auxiliary devices at the weld location. The disclosed embodiments further include a pendant with a wire spool and wire feeder drive circuitry that is configured to activate spooling during MIG welding. Embodiments are provided that also allow for bidirectional

(Continued)



US 9,796,038 B2

data communication over a power line in networked welding systems.

20 Claims, 12 Drawing Sheets

Related U.S. Application Data

(60) Provisional application No. 61/247,396, filed on Sep. 30, 2009.

(51) **Int. Cl.**
B23K 9/095 (2006.01)
B23K 9/12 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,526,597	A	10/1950	Winslow
2,642,515	A	6/1953	Bagg
4,008,384	A	2/1977	Cecil
4,051,344	A	9/1977	Robbins
4,147,919	A	4/1979	Matasovic
4,216,367	A	8/1980	Risberg
4,216,368	A	8/1980	Delay
4,227,066	A	10/1980	Bulwidas
4,247,752	A	1/1981	Stringer
4,266,114	A	5/1981	Hansen
4,467,174	A	8/1984	Gilliland
4,508,954	A	4/1985	Kroll
4,521,572	A	6/1985	Cuscurida
4,584,685	A	4/1986	Gajjar
4,641,292	A	2/1987	Tunnell
4,716,274	A	12/1987	Gilliland
4,767,908	A	8/1988	Dallavalle
5,039,635	A	8/1991	Stempin
5,039,835	A	8/1991	Schwiete
5,043,557	A	8/1991	Tabata
5,276,305	A	1/1994	Hsien
5,376,894	A	12/1994	Petranovich
5,406,050	A	4/1995	Macomber

5,653,902	A	8/1997	Chang
5,982,253	A	11/1999	Perrin
6,040,555	A	3/2000	Tiller
6,103,994	A	8/2000	DeCoster
6,156,999	A	12/2000	Ignatchenko
6,365,868	B1	4/2002	Borowy
6,423,936	B1	7/2002	Reed
6,458,157	B1	10/2002	Suaning
6,570,132	B1	5/2003	Brunner
6,624,388	B1	9/2003	Blankenship
6,781,095	B2	8/2004	Hayes
6,906,285	B2	6/2005	Zucker
6,909,285	B2	6/2005	Jordan
7,180,029	B2	2/2007	Ott
2001/0043656	A1	11/2001	Koslar
2004/0199846	A1	10/2004	Matsumoto
2004/0232128	A1	11/2004	Niedereder
2005/0016975	A1	1/2005	Reynolds
2005/0199605	A1*	9/2005	Furman B23K 9/095 219/132
2005/0230372	A1	10/2005	Ott
2005/0263513	A1	12/2005	Leisner
2006/0077046	A1	4/2006	Endo
2006/0138113	A1	6/2006	Ott
2006/0213892	A1	9/2006	Ott
2006/0276288	A1	12/2006	Iwanaka
2007/0114216	A1	5/2007	Ott
2009/0039064	A1*	2/2009	Enyedy B23K 9/12 219/132

FOREIGN PATENT DOCUMENTS

EP	0575082	12/1993
EP	1586403	10/2005
JP	4017977	1/1992
JP	4162964	6/1992
JP	2003088957	3/2003
JP	2003154455	5/2003
JP	2003191075	7/2003
JP	2003236663	8/2003
JP	2003236669	8/2003
WO	9958285	11/1999

* cited by examiner




FIG. 1




FIG. 2






FIG. 3






FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11






FIG. 14




FIG. 15




FIG. 16

WELDING SYSTEM WITH POWER LINE COMMUNICATION

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a Continuation Patent Application for U.S. patent application Ser. No. 12/843,321, entitled "Welding System with Power Line Communication", filed Jul. 26, 2010, and issued as U.S. Pat. No. 8,957,344 on Feb. 17, 2015, which is a Non-Provisional Patent Application of U.S. Provisional Patent Application No. 61/247,396, entitled "Welding System with Power Line Communication", filed Sep. 30, 2009, both of which are herein incorporated by reference.

BACKGROUND

The invention relates generally to welding systems, and more particularly to welding systems with power line communication.

Traditional single process welding systems support a variety of processes, such as metal inert gas (MIG) welding, tungsten inert gas (TIG) welding, stick welding, and so forth, which may operate in different modes, such as constant current or constant voltage. Such welding systems typically include a single output connection and, therefore, are configured to support a single process at a time. In contrast to these single process welding systems, multi-process welding systems may connect to and support multiple processes at the same time.

Certain multi-process welding applications, such as coal-fired boiler repair, shipyard work, and so forth, may position a welding location or workpiece large distances from a multi-process welding power source. The power source provides conditioned power for the welding application, and the welder must pull and monitor a long welding power cable extending from the power source to the welding location. In such applications, changing welding processes and settings traditionally requires a manual adjustment to a knob or switch on or proximate to the welding power source, and even connection of entirely different welding cables to the source, particularly when the welder uses stick or MIG processes for some of the work, and a TIG process for other work, typically finer or more intricate tasks. Furthermore, the welder often uses auxiliary devices, such as lights and electric grinders, at the location of the weld. However, the auxiliary outlets that support such devices are located on the power supply. Accordingly, the location of power terminals (e.g., plugs) and controls on or proximate to the welding power source may require the user to stop welding and return to the power source to plug in auxiliary devices, make changes to the welding process, and so forth. In many applications, this may entail walking back considerable distances, through sometimes complex and intricate work environments.

Accordingly, there exists a need for systems and methods for providing more convenient power and control functionalities in multi-process welding systems, particularly in environments where the welding operation is carried out at a considerable distance from the welding power source.

BRIEF DESCRIPTION

The present invention provides solutions for such welding applications. In accordance with certain embodiments, welding systems are provided that offer communication over

auxiliary or weld power lines. The disclosed embodiments may include a multi-process welding power supply that is communicatively coupled to a remotely located pendant via an auxiliary conduit that facilitates the exchange of data and power between components of the welding system. In some embodiments, data may be bidirectionally transferred over an auxiliary power line between the power supply and the pendant. The pendant may also include auxiliary outlets that allow an operator to power auxiliary devices at the weld location. The disclosed embodiments may further include a pendant with a wire spool and wire feeder drive circuitry that is configured to feed wire during MIG welding.

Furthermore, embodiments are provided that allow for bidirectional data communication over a power line in networked welding systems. Control circuitry is also provided that may include memory and processing circuitry and may be located in the power supply, the pendant, or both.

DRAWINGS

These and other features, aspects, and advantages of the present invention will become better understood when the following detailed description is read with reference to the accompanying drawings in which like characters represent like parts throughout the drawings, wherein:

FIG. 1 is a diagram of an exemplary welding system having a multi-process power supply and a pendant that bidirectionally communicate data over a power line in accordance with aspects of the present invention;

FIG. 2 is a diagram of the exemplary welding system of FIG. 1 that includes multiple gas sources in accordance with aspects of the present invention;

FIG. 3 is a diagram of the exemplary welding system of FIG. 1 that includes weld receptacles on the pendant in accordance with aspects of the present invention;

FIG. 4 is a diagram of the exemplary welding system of FIG. 2 wherein the pendant includes a wire feeder in accordance with aspects of the present invention;

FIG. 5 is a diagram of an exemplary networked welding system including data communication over a power line in accordance with aspects of the present invention;

FIG. 6 is a diagram illustrating internal components of an exemplary pendant in accordance with aspects of the present invention;

FIG. 7 is a perspective view of an exemplary operator interface that may be located on a pendant in accordance with aspects of the present invention;

FIG. 8 is a side view of an exemplary pendant illustrating placement of power receptacles in accordance with aspects of the present invention;

FIG. 9 is a diagram of an exemplary welding system including an auxiliary power distribution in accordance with aspects of the present invention;

FIG. 10 is a diagram of the welding system of FIG. 9 wherein the auxiliary power distribution unit is located within a distribution box in accordance with aspects of the present invention;

FIG. 11 is a diagram of an exemplary welding system that includes communication over both an auxiliary power line and a primary power line in accordance with aspects of the present invention;

FIG. 12 is a diagram of an exemplary welding system that includes communication over an auxiliary power line via one or more free standing communication power interface modules in accordance with aspects of the present invention;

FIG. 13 is a perspective view of an exemplary weld system that includes one or more junction boxes associated

with one or more weld power supplies in accordance with aspects of the present invention;

FIG. 14 is a perspective view of an exemplary pendant in accordance with aspects of the present invention;

FIG. 15 is a perspective view of an exemplary operator interface that may be located on the pendant of FIG. 14 in accordance with aspects of the present invention; and

FIG. 16 illustrates an exemplary operator interface that may be located on one or more power supplies associated with the pendant of FIG. 14 in accordance with aspects of the present invention.

DETAILED DESCRIPTION

As discussed in detail below, various embodiments of welding systems that provide communication over auxiliary or weld power lines are provided. Some embodiments include a multi-process welding power supply that is communicatively coupled to a pendant via an auxiliary conduit that facilitates the exchange of data and power between components of the welding system. In some embodiments, as used herein, the term “pendant” refers to an auxiliary power and control device that is designed to be coupled to a welding power supply to provide power to one or more auxiliary devices. That is, in embodiments disclosed herein, data may be bidirectionally transferred over an auxiliary power line between the power supply and the pendant. The pendant may include auxiliary outlets that allow an operator to power auxiliary devices at the weld location as well as an operator interface that allows the operator to program a welding process, welding parameters, and so forth from the location of the weld. The disclosed embodiments further include a pendant with a wire spool and wire feeder drive circuitry that is configured to feed wire during MIG welding. Furthermore, embodiments are provided that allow for bidirectional data communication over a power line in networked welding systems. In such embodiments, a central welding power source may be shared by multiple welding power supplies, which communicate with one or more remote control and monitoring stations over an auxiliary power line.

Control circuitry is provided that may be located in the power supply, the pendant, or both, as also discussed below. The control circuitry may include processing circuitry and memory. The memory may include volatile or non-volatile memory, such as read only memory (ROM), random access memory (RAM), magnetic storage memory, optical storage memory, or a combination thereof. Furthermore, a variety of control parameters may be stored in the memory along with code configured to provide a specific output (e.g., initiate wire feed, enable gas flow, etc.) to the pendant during operation. An operator interface located on the power supply, the pendant, or both, may allow a user to set the process (e.g., set constant current, constant voltage, or regulated metal deposition), set the polarity (e.g., set direct current electrode negative (DCEN) or direct current electrode positive (DCEP)), enable or disable a wire feed, and enable or disable gas flow.

Moreover, as noted above, the present techniques may implement power line communication in at least one, and potentially several ways. For example, in some embodiments, the data is transmitted over an “auxiliary” power line between the pendant and the power supply, with the pendant also allowing for powering of devices such as lights, powered hand tools, and so forth. Secondly, in some applications, data may be transmitted between power supplies, using a power line as a “data backbone” for the exchange of

data that may be used for control and/or monitoring functions by the different power supplies. Such power line communication may be used with or without “auxiliary” power data communication, and vice versa. Moreover, some data may also be transmitted over a welding cable along with weld power (i.e., power signals adapted for creating and sustaining a welding arc between an electrode and a workpiece). Such data communication is described, for example, in U.S. Pat. No. 7,180,029 B2, U.S. application Ser. No. 11/276,288, U.S. patent application Ser. No. 11/609,871, and U.S. patent application Ser. No. 11/625,357, which are hereby incorporated into the present disclosure by reference.

Turning now to the drawings, FIG. 1 is a diagram of an exemplary welding system 10 including a multi-process welding power supply 12 in accordance with aspects of the present invention. The multi-process power supply 12 is configured to supply power to a plurality of welding devices (e.g., MIG torch, TIG torch, stick electrode, etc.) associated with a variety of welding processes (e.g., MIG, TIG, stick, etc.). In certain embodiments, the power supply 12 receives primary power 14 from an alternating current power source (e.g., the AC power grid, an engine/generator set, a battery, or a combination thereof), conditions the input power, and provides an output power to one or more welding devices in accordance with demands of the system 10. The primary power 14 may be supplied from an offsite location (i.e., the primary power 14 may originate from a wall outlet). Accordingly, in some embodiments, the power source 12 may include power conversion circuitry 16 that includes circuit elements such as transformers, rectifiers, switches, and so forth, capable of converting the AC input power to a DCEP or DCEN output as dictated by the demands of the system 10. Such circuits are generally known in the art.

In some embodiments, the power conversion circuitry 16 may be configured to convert the primary power 14 to both weld and auxiliary power outputs. However, in other embodiments, the power conversion circuitry 16 may be adapted to convert primary power only to a weld power output, and a separate auxiliary converter may be provided to convert primary power to auxiliary power. Still further, in some embodiments, the power supply 12 may be adapted to receive a converted auxiliary power output directly from a wall outlet. Indeed, any suitable power conversion system or mechanism may be employed by the power supply 12 to generate and supply both weld and auxiliary power.

The power supply 12 also includes control circuitry 18 that is configured to receive and process a plurality of inputs regarding the performance and demands of the system 10. The control circuitry 18 includes processing circuitry 20, memory 22, and a communication power interface module 24. The memory 22 may include volatile or non-volatile memory, such as ROM, RAM, magnetic storage memory, optical storage memory, or a combination thereof. Furthermore, a variety of control parameters may be stored in the memory 22 along with code configured to provide a specific output (e.g., initiate wire feed, enable gas flow, etc.) during operation. The processing circuitry 20 may also receive an input from a user interface 26 located on the power supply 12, through which the user may choose a process, and input desired parameters (e.g., voltages, currents, particular pulsed or non-pulsed welding regimes, and so forth).

The power supply 12 may also include a gas cylinder 28. The gas cylinder 28 may supply shielding gases, such as argon, helium, carbon dioxide, and so forth, via hose 30. In the embodiment illustrated in FIG. 1, the gas enters gas valving 32 located in the power supply 12. During use, the gas valving 32 modulates the amount of gas supplied to a

welding operation via gas conduit **34**. The gas conduit **34** and a power conduit **36** supply a welding device **38** (e.g., TIG torch) with gas and power, respectively. The power conduit **36** transfers the power output by the power conversion circuitry **16** to the welding device **38** to power the welding process during operation.

A plurality of conduits **40** couple the power supply **12** to the welding device **38**. In the illustrated embodiment, the plurality of conduits **40** is shown as a group of individual connections to the welding device **38**. However, it should be noted that in alternate embodiments, the plurality of conduits **40** may be bundled into a single supply cable that connects the power supply **12** to the welding device **38**. A lead cable **42** terminating in a clamp **44** couples the power conversion circuitry **16** to a workpiece **46**.

In the illustrated embodiment, the power supply **12** is coupled to a pendant **48**. As used herein, the pendant **48** is a welding control device designed to allow an operator to choose welding processes and settings from a remote location with respect to the power supply **12**. The pendant **48** is further designed to provide power to one or more auxiliary devices (e.g., lights, hand grinders, etc.) at the location of the weld. That is, the pendant **48** provides a user with both remote control of the welding settings as well as a remote source of auxiliary power. Accordingly, the pendant **48** is coupled to the power source **12** via an auxiliary conduit **50**. The auxiliary conduit **50** provides auxiliary power to the pendant **48** and facilitates bidirectional data exchange between the pendant **48** and the power supply **12**. That is, embodiments of the present invention allow for data communication over an auxiliary power cable.

In the illustrated embodiment, an auxiliary power line **52** exits the power conversion circuitry **16** and meets a data stream, as represented by reference numeral **54** that exits the control circuitry **18** at node **56** within the power supply **12**. Data, therefore, may be transferred from the pendant **48** via auxiliary conduit **50** to the communication power interface module **24** in the power supply **12**. Data may also be transferred from the communication power interface module **24** to the pendant **48** via the same path. Concurrently, auxiliary power may be transferred from the power conversion circuitry **16** in the power supply **12** to the pendant **48** via power line **52** and auxiliary conduit **50**. In other words, presently contemplated embodiments allow for communication over an existing power line.

The power line communication circuitry and protocols used for this communication may follow any of several available standards, such as ISO/IEC14908.1, available from ECHELON under the commercial designation LONWORKS 2.0. In general, certain such systems will include circuitry at the power supply configured to modulate data signals and superimpose the data or otherwise combine the signals with power signals (e.g., AC waveforms) transmitted to the remote location of the pendant **48** via the power line **52**. The pendant will include complimentary circuitry that demodulates the data signals and provides them to processing circuitry configured to display, act on, or otherwise use the data signals. Conversely, the pendant circuitry may originate data signals, such as for changing settings of the power supply, and send these data signals over the same pendant auxiliary power line to be received and acted upon by the control circuitry of the power supply. In a typical application, the auxiliary power line may transmit 115 V AC power at 60 Hz, although other voltages and frequencies may be employed.

In certain embodiments, the pendant **48** may be located in close proximity to the welding operation but distant from the

power supply **12**. For instance, coal-fired boiler welding applications, shipyard applications, construction sites, and so forth, often requires a welding operator to be located distant from the power supply **12**. Since the pendant **48** may be located close to the weld, the current system **10** may have the effect of reducing the amount of time and effort that the welding operator traditionally spends returning from the site of the weld to the power supply to plug in cords associated with auxiliary devices (e.g., lights, grinders, powered hand tools, etc.).

In the illustrated embodiment, the pendant **48** includes a user interface, through which a user may choose a process (e.g., MIG, TIG, stick, etc.), control the voltage, control the current, power auxiliary devices, and so forth, while remotely located with respect to the power supply unit **12**. For example, in the embodiment shown, the user may plug in auxiliary devices, such as a light **58** or a hand grinder **60**, into the pendant **48**. Accordingly, the auxiliary power supplied to the pendant via auxiliary conduit **50** may be used to power such devices in a location proximate to the welding operation. The foregoing feature may have the effect of reducing the length of extension cables **62** and **64** as compared to traditional systems, since the light **58** and the grinder **60** derive auxiliary power from the pendant **48**, which is close to the location of the weld, and not from the power supply **12**, which may be distant from the weld. In addition to the user interface, in some embodiments, the pendant **48** may also include processing circuitry that receives inputs from the power supply **12** and the user interface, processes the inputs, and generates output data that may be communicated back to the power supply **12** over the auxiliary conduit **50**.

In the embodiment illustrated in FIG. 1, the single gas source **28** and the single gas conduit **34** provide the means for the gas to be transferred from the power supply **12** to the welding device **38** if gas is suitable for the given welding process. In the embodiments illustrated in FIGS. 2, 3, and 4, however, a second gas supply **66** supplies a second gas to the gas valving **32** via a second gas conduit **68**. In these embodiments, gas conduit **34** is routed from the power supply **12** to a remote box **72**, which supplies the gas suitable for the welding operation being performed to the welding device. The gas valving **32** located in the power supply **12** modulates the release of the proper gas for a given operation. That is, the gas valving **32** may include directional control valving that selects gas source **28** or gas source **66** depending upon the active or selected process. Additionally, the gas line **34** may be purged when the system switches between the first gas supply **28** and the second gas supply **66**. It should be noted that in other embodiments, an additional gas line may be routed from the gas valving **32** to the remote box **72** such that each gas source **28** or **66** is transported to the box **72** via a separate gas line.

In the embodiment illustrated in FIG. 2, the weld power cable **36** and the gas cable **34** are routed to the remote box **72**. Multiple welding devices, such as the first welding device **38** (e.g., a TIG torch) and a second welding device (e.g., a stick stinger) **75** may be plugged into the remote box **72** to access power and gas as necessary for the welding operation. In some embodiments, multiple welding devices may be plugged into the remote box **72** simultaneously. However, the only active device is the one necessary for the welding operation selected by the operator on the interface located on the pendant **48**. For example, in the illustrated embodiment, both TIG torch **38** and stick stinger **75** may be plugged into the remote box **72** at the same time. However, only TIG torch **38** is active for use with the workpiece **46** if

a user selects the TIG process from the interface on the pendant **48**. It should be noted that in the illustrated embodiments, gas conduit **34** and power conduit **36** are shown as separate connections to the remote box **72**. In further embodiments, the plurality of conduits **34** and **36**, may be bundled together in a single supply cable, as indicated by reference numeral **76**. In alternate embodiments, the gas conduit **34** may include a plurality of gas conduits (e.g., one gas conduit dedicated to each type of gas supplied) bundled together in a single supply cable, and the weld power conduit **36** may be separate. FIG. **3** illustrates an alternate embodiment of the system **10** shown in FIGS. **1** and **2**. In this embodiment, both the auxiliary conduit **50** and the weld power conduit **36** are routed into pendant **48**. Accordingly, the welding device **38** (e.g., TIG torch) may be connected to cable **70** and plugged into the pendant **48**. Certain embodiments may support multiple welding devices (e.g., MIG torches, stick stingers, etc.) that operate at different polarities (e.g., DCEN or DCEP). For example, in one embodiment, multiple welding devices may be plugged into the pendant **48**, but only one device may be active at a given time. That is, only the device designed for use with the process selected by the operator may be in use. In the illustrated embodiment, data may be communicated over power line **50**, power conduit **36**, or both. That is, the illustrated embodiment provides for communication over an auxiliary power line, a weld power line, or both.

In the embodiments illustrated in FIGS. **1**, **2** and **3**, a wire feeder (not shown) for use with MIG welding operations may be a stand-alone unit located in close proximity to the pendant **48**. In alternate embodiments, the wire feeder may be located in or on the pendant **48**, or, as illustrated in FIG. **4**, the pendant itself may be incorporated within a wire feeder **78**. In such an embodiment, a wire spool **80** feeds wire **82** into a wire feeder driver **84**, which contains circuitry that initiates a wire feed to the MIG torch **74** during MIG welding operations. In this embodiment, the auxiliary devices **58** and **60** as well as the welding devices **38** and **74** may be plugged into the wire feeder **78**. As before, the auxiliary conduit **50** provides auxiliary power for the auxiliary devices **58** and **60** and facilitates bidirectional communication over the power line between the power supply **12** and the wire feeder **78** while power conduit **36** provides weld power for welding devices **38** and **74**. It should be noted that the weld power supplied over the power conduit **36** may be DCEP or DCEN as dictated by the demands of the system.

The embodiments of FIGS. **1-4** illustrate bidirectional data communication between a single power supply and a single pendant over an auxiliary power line. FIG. **5** illustrates a further embodiment of the present invention that includes such communication over a power line but in a networked welding system **86**. For illustrative purposes, the shown embodiment includes a first welding power supply **88** and a second welding power supply **90**. However, it should be noted that in other embodiments, any number of power supplies suitable for the welding application may be used with the present invention. For example, in one embodiment, only one power supply may be included. In such an embodiment, the power supply **88** and the remote control and/or monitoring station **98** may bidirectionally exchange data over the backbone **96**. A common power source, e.g., the AC power grid, an engine/generator set, a battery, or a combination thereof, supplies primary power **92** to each of the power supplies (e.g., **88** and **90**) in the network via power conduit **94** that supplies power to backbone **96** (e.g., a power line mains interface). The primary power source may be

located in close proximity to or remote from one or more of the welding power supplies. The primary power **92** may be supplied from an offsite location (i.e., the primary power **92** may originate from a wall outlet in the plant).

One or more remote control and monitoring stations **98** transmits and receives data signals to and from the backbone **96** to facilitate communication both to and from the power supplies **88**, **90**. That is, the backbone **96** provides a means for both communication and power transmission to the networked welding system **86**. In other words, a centralized backbone allows for communication over a power line to the power supplies. In some embodiments, the remote control and monitoring stations **98** may be configured to connect to an external network such that information may be bidirectionally communicated between the stations **98** and one or more external devices. Accordingly, the remote control and monitoring stations **98** may include hubs, switches, routers, repeaters, gateways, or a combination thereof.

In the illustrated embodiment, the welding power supplies **88**, **90** include a communication power interface module **100**, which is configured to send, receive and process instructions transmitted via the backbone **96** from the remote control and monitoring station **98**. Each power supply **88**, **90** also includes conversion circuitry **102**, through which the incoming power is routed. The conversion circuitry **102** may include circuit elements, such as transformers, rectifiers, switches, and so forth, capable of converting the input power to suitable output power. For example, the power conversion circuitry **102** may convert incoming power to a DCEP or DCEN output as dictated by the demands of the system. Such conversion circuitry **102** may supply a weld power output **104** and an auxiliary power output **106**. The weld power output **104** may be supplied to a welding device (e.g., a MIG torch, a TIG torch, a stick stinger) for use in a welding operation. Similarly, the auxiliary power output **106** may be supplied to auxiliary devices, such as lights and hand grinders, for use during the welding operation. A common ground output **108** may also extend from each power supply **88**, **90** to close the welding circuit.

FIG. **6** illustrates internal components that may be included in the pendant **48** of FIGS. **1-4**. It should be noted that FIG. **6** illustrates one exemplary embodiment of the pendant **48**, and that in further embodiments, more or fewer components may be included. In the illustrated embodiment, the pendant **48** includes power receptacles **110**, processing circuitry **112**, memory **114**, a communication power interface module **116**, and an operator interface **118**. The power receptacles **110** provide a means for the operator to plug in auxiliary devices, such as lights and hand grinders, to receive auxiliary power during operation. Three power receptacles **110** are illustrated in FIG. **6**. However, in other embodiments, any number of power receptacles **110** may be provided. The communication power interface module **116** receives both the incoming power from the power line and the incoming data transmitted over the power line. The communication power interface module **116** further routes the power to the power receptacles **110** and the data to the processing circuitry **112**. The processing circuitry **112** receives and processes the incoming data transmitted via the auxiliary conduit **50** extracted by the communication power interface module. The operator interface **118** also generates data that corresponds to instructions received via operator interaction with the interface **118**. This data is also received and processed by the processing circuitry **112**. Accordingly, the processing circuitry **112** bidirectionally communicates with memory **114** to store and retrieve information as dictated by the demands of the system. Power conversion

circuitry **119** may also be provided in the remote device **48** for the conversion of power to a level appropriate for use by the components of the remote device **48**. That is, in one embodiment, the power conversion circuitry **119** may derive power from the incoming line **50** and convert it to an output appropriate for powering the processing circuitry **112**, memory **114**, and operator interface **118** components.

In certain embodiments, when the auxiliary conduit **50** is connected between the power supply **12** and the pendant **48**, the control circuitry **18** may disable controls located on the user interface **26** located on the power supply that are redundant with controls on the operator interface **118** that is located on the pendant **48**. In this way, activation of the pendant **48** and its associated operator interface **118** leads to deactivation of similar controls located on the power supply unit **12** such that all process control selection is relegated to the pendant **48** during operation.

One embodiment of the pendant **48** including an exemplary operator interface **118** and the power receptacles **110** is shown in FIG. 7. The pendant **48** receives power from the welding power supply **12** and transmits data over the auxiliary conduit **50**. The operator interface **118** includes a plurality of buttons **120** that may be programmed to allow the user to change a variety of application specific parameters. For instance, the plurality of buttons **120** may include an output on/off button, a process button, a wire button, a gas button, and so forth. The operator interface **118** also includes a setup button **122** that the operator may use to set parameters associated with the chosen weld process. For example, in one embodiment, the user may press the setup button **122**, and subsequently use adjustment knobs **124** and **126** to set parameters such as wire feed speed, type of gas, voltage, current, and so forth. Buttons **120** and **122** cooperate with display panels **128** and **130** to communicate options and choices with the user. For example, adjustment knob **124** may be used in conjunction with panel **128**, and adjustment knob **126** may be used in conjunction with panel **130**. For further example, the display panel **128** may be used to display the chosen weld polarity and process. In such an embodiment, the panel **128** may read +EP STICK, indicating that the user has chosen a DCEP polarity for a stick welding process. For further example, the display panel **130** may be used to display the type of information associated with a given process. In such an embodiment, the panel **130** may read VOLTS, AMPS, ARC LENGTH, ARC CONTRL, WIRE, GAS, and so forth. For further example, the display panels **128** and **130** may be used to display numerical values of weld parameters (e.g., a number that show the actual arc length).

FIG. 8 illustrates a side panel **132** of the pendant **48** that includes the power receptacles **110**. The power receptacles **110** are configured to supply auxiliary power, such as 60 Hz single phase power, which may be used to power auxiliary devices associated with the welding operation. The side panel may also include a reset button **134**, which may be used to ensure electrical protection of the pendant **48** and/or the auxiliary devices. For example, if a ground fault is detected by circuitry in the pendant **48**, the reset button **134** may pop out, rendering the outlets inactive and alerting the operator. The operator may subsequently press the reset button **134** to reset the receptacles **110** and resume operation.

The embodiments of the pendant **48** illustrated in FIGS. 7 and 8 illustrate a "smart" pendant that includes many of the presently contemplated functionalities. However, it should be noted that in other embodiments the pendant **48** may include fewer functionalities. For instance, in one embodiment, the pendant **48** may not include interface **118**. In such

an embodiment, accessories such as a foot pedal may replace the illustrated interface as the operator interface. For instance, a potentiometer located in the foot pedal may allow the operator to control the amount of amps supplied to the welding process being performed. In fact, in some embodiments, such accessories (e.g., the foot pedal) may be the pendant **48**. That is, 115V auxiliary power may enter the pendant **48** but may not be supplied to auxiliary devices at the location of the weld. However, data regarding operator input may still be exchanged with the power supply via the auxiliary power line. That is, in certain embodiments, the pendant **48** may not deliver auxiliary power but information may still be transmitted down the auxiliary power line.

FIGS. 9 and 10 illustrate further embodiments of the power line communication disclosed herein. FIGS. 9 and 10 illustrate welding systems that include a plurality of welding power supplies, e.g., a first weld power supply **138** and a second weld power supply **140**. It should be noted that although only two weld power supplies are illustrated, in other embodiments, any number of weld power supplies may be included. A common power source, e.g., the AC power grid, an engine/generator set, a battery, or a combination thereof, supplies primary power **142** to each of the power supplies **138** and **140** in the network via power lines **144** and **146**, respectively. The power source may be located in close proximity to or remote from one or more of the welding power supplies. As before, the primary power **142** may be supplied from an offsite location and may be supplied onsite via a wall outlet. In the illustrated embodiment, the welding power supplies **138** and **140** include conversion circuitry **148**, through which the incoming primary power is routed. The conversion circuitry **148** may include circuit elements, such as transformers, rectifiers, switches, and so forth, capable of converting the input power to suitable output weld power. For example, the power conversion circuitry **148** may convert incoming power to a DCEP or DCEN output as dictated by the demands of the system. Such conversion circuitry **148** may supply a weld power output **104**. The weld power output **104** may be supplied to a welding device (e.g., a MIG torch, a TIG torch, a stick stinger) for use in a welding operation. A common ground output **108** may also extend from each power supply **138** and **140** to close the welding circuit.

The primary power **142** is also supplied to an auxiliary power conversion unit **150** located in a receiving and transmitting (RT) unit **152** via power line **154**. In some embodiments, the RT unit **152** may be located in close proximity to a rack of weld power supplies, e.g., **138** and **140**. The auxiliary power conversion unit **150** is configured to receive primary power at a high voltage and output auxiliary power at a lower voltage. Accordingly, the auxiliary power conversion unit **150** may include circuitry, such as transformers, configured to step down the voltage of the incoming power. The RT unit **152** also includes a plurality of communication power interface modules **100**, which are configured to transmit, receive, and process data transmitted to and from an auxiliary power distribution unit **156** via auxiliary power line **158**. That is, presently contemplated embodiments provide for data communication over power line **158**.

In the embodiment illustrated in FIG. 9, as before, one or more remotely located pendants **48**, **48'** are designed to allow an operator to choose welding processes and settings from a remote location with respect to the power supplies **138**, **140**. However, in this embodiment, a plurality of pendants, as represented by two pendants **48** and **48'** but not meant to limit the invention, may be plugged into the central

auxiliary power conversion unit **156**. The pendants **48**, **48'** are still designed to provide power to one or more auxiliary devices **58**, **58'**, **60**, **60'** at the location of one or more welds. That is, the pendants **48**, **48'** provide a user with both remote control of the welding settings as well as a remote source of auxiliary power for one or more welds. For example, pendant **48** may be located in close proximity to a first weld, and pendant **48'** may be located in close proximity to a second weld remote from the first weld.

During operation, a first operator may input desired weld settings to pendant **48**. These weld settings are transmitted via conduit **160** through the auxiliary power distribution unit **156**, across power line **158**, through communication power interface module **100**, along data conduit **162**, and to control circuitry **164** located in power supply **138**. In this way, data may be bidirectionally communicated over power line **160** and power line **158**. Similarly, a second operator may input desired weld settings to pendant **48'**. These weld settings are transmitted via power line **166** through the auxiliary power distribution unit **156**, across power line **158**, through communication power interface module **100**, along data conduit **168**, and to control circuitry **164** located in power supply **140**. In this way, data may be bidirectionally communicated over power line **166** and power line **158**.

The embodiment illustrated in FIG. **10** operates similarly to that of FIG. **9**. However, in this embodiment, the auxiliary power distribution unit **156** is located in a remote distribution box **172**. The remote distribution box **172** also houses the pendants **48** and **48'**. That is, in this embodiment, the operator interfaces for multiple welding processes may be located on one central remote box **172**. Also, the auxiliary devices **58**, **58'**, **60**, **60'** for multiple welding processes may also be plugged into the central distribution box **172**. As before, data is communicated over power line **158** and transmitted back to the power supplies **138** and **140** for processing. Also, in the embodiments illustrated in FIGS. **9** and **10**, two power supplies **138** and **140** are shown. However, it should be noted that in alternate embodiments, more or fewer power supplies may be included in the system. For example, in one embodiment, only one power supply may be included.

FIG. **11** is a diagram of another exemplary welding system including communication over both a primary weld power line and an auxiliary power line. As before, the primary power **142** may be supplied from an offsite location and may be supplied onsite via a wall outlet. Primary power **142** is delivered to the welding power supplies **138** and **140** via primary power line **154**. Accordingly, the power supplies **138** and **140** include conversion circuitry **148**, through which the incoming primary power is routed. Such conversion circuitry **148** may supply a weld power output **104**. The weld power output **104** may be supplied to a welding device (e.g., a MIG torch, a TIG torch, a stick stinger) for use in a welding operation. A common ground output **108** may also extend from each power supply **138** and **140** to close the welding circuit. In the illustrated embodiment, two power supplies **138** and **140** are shown. However, it should be noted that in alternate embodiments, more or fewer power supplies may be included in the system. For example, in one embodiment, only one power supply may be included.

The primary power **142** is also supplied to the auxiliary power conversion unit **150** located in the RT unit **152** via primary power line **154**. That is, primary power **142** is supplied to both the auxiliary power conversion unit **150** and the power supplies **138** and **140** via power line **154**. As before, the auxiliary power conversion unit **150** is configured to receive primary power at a high voltage and output

auxiliary power at a lower voltage. The RT unit **152** also includes a first plurality of communication power interface modules **100** and **100'**, which are configured to transmit, receive, and process data transmitted to and from the auxiliary power distribution unit **156** via auxiliary power line **158**. That is, presently contemplated embodiments provide for data communication over auxiliary power line **158**. Additionally, the RT unit **152** includes a second plurality of communication power interface modules **174** and **174'** configured to receive the data from the first plurality of communication power interface modules **100** and **100'** and convert the data to a form suitable for communication over primary power line **154** for transmission to power supplies **138** and **140**. Accordingly, power supply **138** includes a communication power interface module **176** configured to transmit, receive, and process data to and from power line **154**. Likewise, power supply **140** includes a communication power interface module **178** that transmits, receives, and processes data to and from the primary power line **154**.

During operation, a first operator may input desired weld settings to pendant **48**. These weld settings are transmitted via conduit **160** through the auxiliary power distribution unit **156**, across power line **158**, through communication power interface module **100**, through communication power interface module **174**, along primary power line **154**, and to the communication power interface module **176** located in power supply **138**. In this way, data may be communicated both over auxiliary power lines **158** and **160** as well as over primary power line **154**. Similarly, a second operator may input desired weld settings to pendant **48'**. These weld settings are transmitted via power line **166** through the auxiliary power distribution unit **156**, across power line **158**, through communication power interface module **100'**, through communication power interface module **174'**, along primary power line **154**, and to the communication power interface module **178** located in power supply **140**. That is, the embodiment illustrated in FIG. **11** facilitates the bidirectional exchange of data over both an auxiliary power line as well as a primary weld power line. The foregoing features may have the effect of enabling the extraction of data regarding weld parameters at a location proximate to the weld power supplies **138** and **140**. That is, presently contemplated embodiments allow a remotely located user to monitor the welding process without additional wires, cables, circuitry, and the like located proximate to the welding operation.

FIG. **12** illustrates a welding system **180** that includes a plurality of welding power supplies, e.g., the first weld power supply **138** and the second weld power supply **140**. In other embodiments, any suitable number of weld power supplies may be included. A common power source, such as the AC power grid, an engine/generator set, or a battery, supplies primary power **142** to each of the power supplies **138** and **140** in the network via power lines **144** and **146**, respectively. As before, the primary power **142** may be supplied from an offsite location and may be supplied onsite via a wall outlet, and the welding power supplies **138** and **140** include conversion circuitry **148**, through which the incoming primary power is routed. Such conversion circuitry **148** may supply the weld power output **104**. The weld power output **104** may be supplied to a welding device (e.g., a MIG torch, a TIG torch, a stick stinger) for use in a welding operation. A common ground output **108** may also extend from each power supply **138** and **140** to close the welding circuit.

The primary power **142** is also supplied to the auxiliary power conversion unit **150** located in the receiving and

13

transmitting (RT) unit **152** via power line **154**. In some embodiments, the RT unit **152** may be located in close proximity to a rack of weld power supplies, e.g., **138** and **140**, and may include additional components not shown in FIG. **12**. As before, the auxiliary power conversion unit **150** is adapted to receive primary power at a high voltage and output auxiliary power at a lower voltage. In this embodiment, however, the RT unit **152** is coupled to communication power interface modules **100** and **100'**, which are configured to transmit, receive, and process data transmitted to and from the power supplies **138** and **140** as well as to and from the remotely located pendants **48**, **48'**. That is, in the illustrated embodiment, the communication power interface modules **100** and **100'** are free standing and, accordingly, are not located in the RT unit **152**.

In this embodiment, the plurality of pendants, as represented by pendants **48** and **48'** but not meant to limit the invention, may be directly plugged into the communication power interface modules **100** and **100'**. For example, in the illustrated embodiment, the communication power interface modules **100** and **100'** are coupled to the pendants **48** and **48'** via auxiliary power lines **182** and **184**, respectively. However, in this embodiment, the communication power interface modules **100** and **100'** are also coupled to the output of the auxiliary power conversion unit **150** via power lines **186** and **188**, respectively. As such, the communication power interface modules **100** and **100'** are adapted to bidirectionally communicate data over auxiliary power lines **182** and **184** to the pendants **48** and **48'**. The pendants **48**, **48'** are still designed to provide power to one or more auxiliary devices **58**, **58'**, **60**, **60'** at the location of one or more welds. That is, the pendants **48**, **48'** provide a user with both remote control of the welding settings as well as a remote source of auxiliary power for one or more welds.

FIG. **13** is a perspective view illustrating an exemplary weld system **190** in accordance with aspects of the present invention. The weld system **190** includes a plurality of power supplies **138**, **140**, **192**, **194**, **196**, and **198** disposed on a rack **200** adapted to support the power supplies. The weld system **190** further includes junction boxes **202**, **204**, **206**, **208**, **210**, and **212** each associated with corresponding power supplies **138**, **140**, **192**, **194**, **196**, and **198**, respectively. For example, junction box **202** is associated with corresponding power supply **138**, junction box **204** is associated with corresponding power supply **140**, and so forth. In the illustrated embodiment, the junction boxes are coupled to the rack **200**. However, in other embodiments, the junction boxes may be coupled to the power supplies, disposed on a separate rack, or positioned in any other suitable location. The weld system **190** further includes the auxiliary power conversion unit **150** and the pendant **48**. In the illustrated embodiment, the auxiliary power conversion unit **150** includes auxiliary power receptacles **214** disposed thereon.

As shown, the auxiliary power conversion unit **150** is coupled to the first junction box **202** via cable **216**. The junction box **202** is coupled to power supply **138** via cable **218** and to the pendant **48** via cable **220**. Although not shown, the additional auxiliary outlets **214** may be coupled to the remaining junction boxes via additional cables, and the junction boxes may also be coupled to their corresponding power supplies and to the pendant via additional cables in further embodiments. During operation, the auxiliary power conversion unit **150** receives power from a primary power source and converts the primary power to an auxiliary power output (e.g., 115 volts). The auxiliary power is routed via auxiliary outlet **214** to the junction box **202** through

14

cable **216**. As such, the junction box **202** is adapted to receive the auxiliary power from the cable **216**.

In the embodiments illustrated and described herein, the primary power is converted to auxiliary power in the auxiliary power conversion unit. However, it should be noted that in other embodiments, the auxiliary power may be generated in and received from a variety of other sources. For example, in one embodiment, the auxiliary power may be received from an outlet disposed in the wall. In such an embodiment, the cable **216** may couple the junction box directly to a wall outlet configured to deliver an auxiliary output power (e.g., 115 volts).

The junction box **202** is also adapted to transmit and receive control signals to and from the power supply **138** via control cable **218**. The junction box **202** is further configured to couple the received control signals to the received auxiliary power and to transmit the auxiliary power and data to the pendant **48** via cable **220**. It should also be noted that control signals may also be received by the junction box **202** from the pendant **48** via cable **220**. As such, the junction box **202** may include any number of suitable components, such as a communication power interface module, electrical circuitry, and so forth.

FIGS. **14** and **15** illustrate an exemplary embodiment of the pendant **48** that may be employed in the weld system **190** of FIG. **13**. As shown, the pendant **48** includes an operator interface **222**, through which a user may control the welding process. For example, the illustrated operator interface **22** includes an ON/OFF button **224**, which the user may press to enable or disable the welding output. The user interface **222** also includes a process selection button **226**, which the user may press to change the welding process, e.g., between TIG welding and MIG welding. The user interface further includes a setup button **228**, through which the operator may control a variety of parameters of the welding process, such as control of the arc, weld characteristics, and so forth. As such, a knob **230** may be used in conjunction with button **228** to change one or more weld characteristics and/or to change the magnitude of one or more weld parameters.

The user interface **222** also includes a display panel **232**, through which one or more parameters or values of the welding process may be communicated to the user. For example, the display panel **232** includes a first indicator **234** and a second indicator **236**. In one embodiment, the first indicator **234** may be a light emitting diode (LED) adapted to illuminate when a DCEP weld process is occurring, and the second indicator **236** may be an LED adapted to illuminate when a DCEN weld process is occurring. Still further, the display panel **232** may be configured to communicate one or more numerical values via display **238** to the user. For example, as the user turns the knob **230** to change a parameter of the welding process, the display **238** may display the value of the weld parameter (e.g., the voltage or amperage level).

FIG. **16** illustrates an exemplary user interface **240** that may be disposed on the one or more power supplies in accordance with aspects of the present invention. The user interface **240** in the illustrated embodiment includes LEDs **242** positioned by process symbols that are configured to illuminate when a process is selected. In a presently contemplated embodiment, the user selects a welding process via a knob **244**. As the user turns the knob **244**, the LEDs are illuminated, indicating the chosen process. A selection panel **246** includes multiple sub-panels that allow the user to choose the welding process. For instance, in the illustrated embodiment, the selection panel **246** includes a flux core (FCAW) no gas panel **248**, a lift-arc TIG panel **250**, a scratch

15

start TIG panel **252**, a stick panel **254**, and a MIG/FCAW with gas panel **256**. When the user turns the knob **244**, LED associated with the panel associated with the suitable process is illuminated and the process is initiated. For instance, if the user turns knob **244** to the stick panel **254**, the stick LED is illuminated, and the power supply receives and processes the stick user selection. Additionally, as the user turns the knob **244**, the polarity of the chosen process is communicated to the user via the DCEN icon **258** and the DCEP icon **260**.

The user interface **240** also includes a power button **262**, through which the user may enable or disable the welding output. The user interface **240** also includes a voltage display **264** and an amperage display **266**, which display the voltage and amperage of the weld process, respectively. For example, the user may utilize the adjustment panel **268** by rotating knob **270** to set the desired voltage or amperage of the weld process, which is displayed on panels **264** and **266**. Still further, the operator interface includes an arc control panel **272**, through which the user may adjust an arc parameter via rotation of knob **274**.

While only certain features of the invention have been illustrated and described herein, many modifications and changes will occur to those skilled in the art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the invention.

The invention claimed is:

1. A welding system comprising:
 - a power supply unit that in operation outputs welding power at welding terminals and outputs a combined signal comprising an auxiliary power signal combined with a modulated data signal to an auxiliary power conductor; and
 - a pendant located remotely with respect to the power supply unit, wherein the pendant receives the combined signal via the auxiliary power conductor and provides auxiliary power to one or more auxiliary devices plugged into the pendant based on the auxiliary power signal received via the auxiliary power conductor, wherein the pendant is configured to communicate data with the power supply unit via the modulated data signal of the combined signal from the auxiliary power conductor.
2. The welding system of claim 1, wherein the pendant includes one or more power receptacles configured to output the auxiliary power to the one or more auxiliary devices.
3. The welding system of claim 1, wherein the pendant comprises a wire feeder enabled when a metal inert gas (MIG) process or a MIG/flux core process is selected.
4. The welding system of claim 1, wherein the communication of data is bidirectional between the power supply unit and the pendant.
5. The welding system of claim 1, wherein the pendant is configured to allow a user to select a welding process and to communicate the selection to the power supply unit via the auxiliary power conductor.
6. The welding system of claim 1, comprising a first set of controls located on the power supply unit and a second set of controls located on the pendant, and wherein at least one of the first set of controls is disabled automatically when the pendant is coupled to the power supply unit via the auxiliary power conductor.
7. The welding system of claim 1, comprising one or more gas sources and one or more gas conduits connected to the one or more gas sources.

16

8. The welding system of claim 7, wherein the one or more gas conduits supply one or more gases to a welding torch.

9. A welding system comprising:

- a power supply that outputs welding power for a welding application and outputs a combined signal comprising an auxiliary power signal and a data signal, wherein the auxiliary power signal provides power to one or more auxiliary devices via an auxiliary power conductor; and
- a remote pendant coupled to the power supply via the auxiliary power conductor and configured to receive the auxiliary power signal from the power supply via the auxiliary power conductor, to provide the auxiliary power signal to the one or more auxiliary devices plugged into the remote pendant, and to exchange data with the power supply via the same auxiliary power conductor.

10. The welding system of claim 9, wherein the remote pendant is configured to permit user selection of at least one welding parameter and to communicate the user selection to the power supply via the auxiliary power conductor.

11. The welding system of claim 9, wherein the remote pendant comprises at least one auxiliary electrical receptacle into which a power cord for at least one of the auxiliary devices may be plugged, and the at least one auxiliary electrical receptacle is configured to output at least a portion of the auxiliary power signal to the at least one of the auxiliary devices.

12. The welding system of claim 9, comprising a first set of controls located on the power supply and a second set of controls located on the remote pendant, and wherein at least one of the first set of controls are disabled automatically when the remote pendant is communicatively coupled to the power supply via the auxiliary power conductor.

13. The welding system of claim 9, wherein the remote pendant comprises a wire feeder enabled when a metal inert gas (MIG) process or a MIG/flux core process is selected.

14. The welding system of claim 9, comprising one or more gas sources and one or more gas conduits connected to the one or more gas sources.

15. The welding system of claim 14, wherein the one or more gas conduits supply one or more gases to a welding torch via gas valving located in the power supply.

16. A welding system comprising:

- a power supply that outputs welding power for a welding application and a combined signal comprising an auxiliary power signal for powering one or more auxiliary devices and a modulated data signal; and
- an auxiliary power distribution unit located external to the power supply and configured to receive the auxiliary power signal from the power supply, to output the auxiliary power signal to a plurality of remote pendants via an auxiliary power conductor, and to exchange data via the modulated data signal through the auxiliary power conductor, wherein the power supply is configured to exchange the data with the auxiliary power distribution unit via the same auxiliary power conductor, a control cable, a primary power conduit, or a combination thereof.

17. The welding system of claim 16, wherein the plurality of remote pendants each include one or more power receptacles configured to output power to the one or more auxiliary devices.

18. The welding system of claim 17, wherein the one or more auxiliary devices comprise lights, grinders, or hand tools.

19. The welding system of claim 16, wherein the exchange of data via the auxiliary power conductor is bidirectional.

20. The welding system of claim 16, wherein the plurality of remote pendants are each configured to select a welding process and to communicate the selection to the power supply via the auxiliary power conductor. 5

* * * * *