

US009798148B2

(12) **United States Patent**
Border et al.

(10) **Patent No.:** **US 9,798,148 B2**
(45) **Date of Patent:** **Oct. 24, 2017**

(54) **OPTICAL CONFIGURATIONS FOR HEAD-WORN SEE-THROUGH DISPLAYS**

(71) Applicant: **Osterhout Group, Inc.**, San Francisco, CA (US)

(72) Inventors: **John N. Border**, Eaton, NH (US); **Joseph Bietry**, Chili, NY (US); **John D. Haddick**, Mill Valley, CA (US)

(73) Assignee: **Osterhout Group, Inc.**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/155,139**

(22) Filed: **May 16, 2016**

(65) **Prior Publication Data**

US 2017/0023790 A1 Jan. 26, 2017

Related U.S. Application Data

(62) Division of application No. 14/325,991, filed on Jul. 8, 2014, now Pat. No. 9,366,867.

(51) **Int. Cl.**

G02B 27/14 (2006.01)
G09G 5/00 (2006.01)
G02B 27/01 (2006.01)
G02B 27/28 (2006.01)
G02B 5/30 (2006.01)

(52) **U.S. Cl.**

CPC **G02B 27/0172** (2013.01); **G02B 5/30** (2013.01); **G02B 27/0176** (2013.01); **G02B 27/28** (2013.01); **G02B 27/283** (2013.01); **G02B 2027/0118** (2013.01); **G02B 2027/0152** (2013.01); **G02B 2027/0178** (2013.01)

(58) **Field of Classification Search**

CPC G02B 27/017; G02B 27/0172; G02B 27/0101; G02B 2027/0178; G02B 27/01
USPC 359/630; 345/7-9
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,897,833 A 2/1933 Benway
3,305,294 A 2/1967 Alvarez
5,257,094 A 10/1993 Larussa et al.
5,596,451 A 1/1997 Handschy et al.
5,699,194 A 12/1997 Takahashi
5,717,422 A 2/1998 Ferguson et al.
5,808,589 A 9/1998 Ferguson
5,808,800 A 9/1998 Handschy et al.
5,914,818 A 6/1999 Tejada et al.
5,949,583 A 9/1999 Rallison et al.
6,147,805 A 11/2000 Ferguson
6,195,136 B1 2/2001 Handschy et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 368898 A1 5/1990
EP 777867 A1 6/1997

(Continued)

OTHER PUBLICATIONS

US 8,743,465, 06/2014, Totani et al. (withdrawn)

(Continued)


Primary Examiner — William Choi

(74) *Attorney, Agent, or Firm* — GTC Law Group PC & Affiliates

(57) **ABSTRACT**

Aspects of the present invention relate to methods and systems for providing high quality display images in see-through head-worn optics.

1 Claim, 82 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

			2002/0109903	A1	8/2002	Kaeriyama et al.
			2002/0181115	A1	12/2002	Massof et al.
			2002/0191297	A1*	12/2002	Gleckman G02B 27/0172 359/629
6,204,974	B1	3/2001	Spitzer	2003/0030597	A1	2/2003 Geist
6,359,723	B1	3/2002	Handschy et al.	2003/0030912	A1	2/2003 Gleckman et al.
6,369,952	B1	4/2002	Rallison et al.	2003/0151834	A1	8/2003 Penn et al.
6,379,009	B1	4/2002	Ferguson	2004/0066547	A1	4/2004 Parker et al.
6,384,982	B1	5/2002	Spitzer	2004/0194880	A1	10/2004 Jiang et al.
6,433,760	B1	8/2002	Vaissie et al.	2004/0227994	A1	11/2004 Ma et al.
6,456,438	B1	9/2002	Lee et al.	2005/0041289	A1	2/2005 Berman et al.
6,461,000	B1	10/2002	Magarill	2005/0157949	A1	7/2005 Aiso et al.
6,478,429	B1	11/2002	Aritake et al.	2005/0212980	A1	9/2005 Miyazaki et al.
6,747,611	B1	6/2004	Budd et al.	2006/0098293	A1	5/2006 Garoutte et al.
6,847,336	B1	1/2005	Lemelson et al.	2006/0215111	A1	9/2006 Mihashi et al.
6,906,836	B2	6/2005	Parker et al.	2006/0250322	A1	11/2006 Hall et al.
6,987,787	B1	1/2006	Mick	2006/0250696	A1	11/2006 McGuire
7,088,234	B2	8/2006	Naito et al.	2007/0024750	A1	2/2007 Chung et al.
7,119,971	B2	10/2006	Kobayashi et al.	2007/0024763	A1	2/2007 Chung et al.
7,199,934	B2	4/2007	Yamasaki	2007/0024764	A1	2/2007 Chung et al.
7,206,134	B2	4/2007	Weissman et al.	2007/0024820	A1	2/2007 Chung et al.
7,417,617	B2	8/2008	Eichenlaub	2007/0024823	A1	2/2007 Chung et al.
7,543,943	B1	6/2009	Hubby et al.	2007/0025273	A1	2/2007 Chung et al.
7,690,799	B2	4/2010	Nestorovic et al.	2007/0030456	A1	2/2007 Duncan et al.
7,733,571	B1	6/2010	Li	2007/0070859	A1	3/2007 Hirayama
7,777,690	B2	8/2010	Winsor et al.	2007/0120806	A1	5/2007 Schmidt et al.
7,777,960	B2	8/2010	Freeman	2007/0263174	A1	11/2007 Shyu et al.
7,830,370	B2	11/2010	Yamazaki et al.	2008/0088793	A1	4/2008 Sverdrup et al.
7,855,743	B2	12/2010	Sako et al.	2008/0169998	A1	7/2008 Jacobsen et al.
7,928,926	B2	4/2011	Yamamoto et al.	2008/0266645	A1	10/2008 Dharmatilleke et al.
8,004,765	B2	8/2011	Amitai	2008/0298639	A1	12/2008 Tsunekawa et al.
8,018,579	B1	9/2011	Krah et al.	2009/0015735	A1	1/2009 Simmonds et al.
8,079,713	B2	12/2011	Ashkenazi et al.	2009/0147331	A1	6/2009 Ashkenazi et al.
8,166,421	B2	4/2012	Magal et al.	2009/0279180	A1	11/2009 Amitai et al.
8,376,548	B2	2/2013	Schultz	2010/0073376	A1	3/2010 Schmale
8,378,924	B2	2/2013	Jacobsen et al.	2010/0079733	A1	4/2010 Lu et al.
8,384,999	B1	2/2013	Crosby et al.	2010/0097580	A1	4/2010 Yamamoto et al.
8,427,396	B1	4/2013	Kim	2010/0103075	A1	4/2010 Kalaboukis et al.
8,467,133	B2	6/2013	Miller et al.	2010/0130140	A1	5/2010 Waku et al.
8,472,120	B2	6/2013	Border et al.	2010/0149073	A1	6/2010 Chaum et al.
8,477,425	B2	7/2013	Border et al.	2010/0149510	A1	6/2010 Zaczek et al.
8,482,859	B2	7/2013	Border et al.	2010/0254017	A1	10/2010 Martins et al.
8,488,246	B2	7/2013	Border et al.	2010/0283774	A1	11/2010 Bovet et al.
8,494,215	B2	7/2013	Kimchi et al.	2010/0290127	A1	11/2010 Kessler et al.
8,520,310	B2	8/2013	Shimizu et al.	2011/0012874	A1	1/2011 Kurozuka et al.
8,564,883	B2	10/2013	Totani et al.	2011/0043644	A1	2/2011 Munger et al.
8,570,656	B1	10/2013	Weissman et al.	2011/0096100	A1	4/2011 Sprague et al.
8,576,276	B2	11/2013	Bar-Zeev et al.	2011/0130958	A1	6/2011 Stahl et al.
8,576,491	B2	11/2013	Takagi et al.	2011/0131495	A1	6/2011 Bull et al.
8,587,869	B2	11/2013	Totani et al.	2011/0164047	A1	7/2011 Pance et al.
8,594,467	B2	11/2013	Lu et al.	2011/0164163	A1	7/2011 Bilbrey et al.
8,662,686	B2	3/2014	Takagi et al.	2011/0164221	A1	7/2011 Tillemann et al.
8,670,183	B2	3/2014	Clavin et al.	2011/0196610	A1	8/2011 Waldman et al.
8,698,157	B2	4/2014	Hanamura	2011/0199171	A1	8/2011 Prest et al.
8,711,487	B2	4/2014	Takeda et al.	2011/0201213	A1	8/2011 Dabov et al.
8,745,058	B1	6/2014	Garcia-Barrio	2011/0202823	A1	8/2011 Berger et al.
8,750,541	B1	6/2014	Dong et al.	2011/0205209	A1	8/2011 Kurokawa et al.
8,752,963	B2	6/2014	McCulloch et al.	2011/0248963	A1	10/2011 Lawrence et al.
8,803,867	B2	8/2014	Oikawa	2012/0050140	A1	3/2012 Border et al.
8,823,071	B2	9/2014	Oyamada	2012/0050493	A1	3/2012 Ernst et al.
8,832,557	B2	9/2014	Tang et al.	2012/0062444	A1	3/2012 Cok et al.
8,837,880	B2	9/2014	Takeda et al.	2012/0062850	A1	3/2012 Travis
8,854,735	B2	10/2014	Totani et al.	2012/0062998	A1	3/2012 Schultz et al.
9,076,368	B2	7/2015	Evans et al.	2012/0069413	A1	3/2012 Schultz et al.
9,298,001	B2	3/2016	Border et al.	2012/0075168	A1	3/2012 Osterhout et al.
9,298,002	B2	3/2016	Border et al.	2012/0081800	A1	4/2012 Cheng et al.
9,310,610	B2	4/2016	Border	2012/0120103	A1	5/2012 Border et al.
9,316,833	B2	4/2016	Border et al.	2012/0120498	A1	5/2012 Harrison et al.
9,329,387	B2	5/2016	Border et al.	2012/0163013	A1	6/2012 Buelow et al.
9,366,867	B2	6/2016	Border et al.	2012/0176682	A1	7/2012 Dejong et al.
9,366,868	B2	6/2016	Border et al.	2012/0188245	A1	7/2012 Hyatt et al.
9,377,625	B2	6/2016	Border et al.	2012/0194553	A1	8/2012 Osterhout et al.
9,436,006	B2	9/2016	Border	2012/0200935	A1	8/2012 Miyao et al.
9,448,409	B2	9/2016	Border et al.	2012/0206817	A1	8/2012 Totani et al.
9,494,800	B2	11/2016	Border et al.	2012/0212484	A1	8/2012 Haddick et al.
9,594,246	B2	3/2017	Border et al.	2012/0212593	A1	8/2012 Na'aman et al.
9,651,783	B2	5/2017	Border et al.	2012/0223885	A1	9/2012 Perez
2001/0019240	A1	9/2001	Takahashi et al.	2012/0235885	A1	9/2012 Miller et al.
2002/0021498	A1	2/2002	Ohtaka et al.	2012/0250152	A1	10/2012 Larson et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0264510	A1	10/2012	Wigdor et al.
2012/0287398	A1	11/2012	Baker et al.
2012/0306850	A1	12/2012	Balan et al.
2012/0327116	A1	12/2012	Liu et al.
2013/0009366	A1	1/2013	Hannegan et al.
2013/0021658	A1	1/2013	Miao et al.
2013/0044042	A1	2/2013	Olsson et al.
2013/0070344	A1	3/2013	Takeda et al.
2013/0083055	A1	4/2013	Piemonte et al.
2013/0088413	A1	4/2013	Raffle et al.
2013/0100259	A1	4/2013	Ramaswamy
2013/0120841	A1	5/2013	Shpunt et al.
2013/0127980	A1	5/2013	Haddick
2013/0135198	A1	5/2013	Hodge et al.
2013/0154913	A1	6/2013	Genc et al.
2013/0169530	A1	7/2013	Bhaskar et al.
2013/0176626	A1	7/2013	Heinrich et al.
2013/0196757	A1	8/2013	Latta et al.
2013/0201080	A1	8/2013	Evans et al.
2013/0201081	A1	8/2013	Evans et al.
2013/0207887	A1	8/2013	Raffle et al.
2013/0207970	A1	8/2013	Shpunt et al.
2013/0222919	A1	8/2013	Komatsu et al.
2013/0230215	A1	9/2013	Gurman et al.
2013/0242405	A1	9/2013	Gupta et al.
2013/0248691	A1	9/2013	Mirov et al.
2013/0250207	A1	9/2013	Bohn et al.
2013/0250430	A1	9/2013	Robbins et al.
2013/0257622	A1	10/2013	Davalos et al.
2013/0265227	A1	10/2013	Julian et al.
2013/0278631	A1	10/2013	Border et al.
2013/0321265	A1	12/2013	Bychkov et al.
2013/0321271	A1	12/2013	Bychkov et al.
2013/0321932	A1	12/2013	Hsu et al.
2013/0342571	A1	12/2013	Kinnebrew et al.
2014/0028704	A1	1/2014	Wu et al.
2014/0043682	A1	2/2014	Hussey et al.
2014/0062854	A1	3/2014	Cho
2014/0063055	A1	3/2014	Osterhout et al.
2014/0125785	A1	5/2014	Na et al.
2014/0129328	A1	5/2014	Mathew
2014/0146394	A1	5/2014	Tout et al.
2014/0147829	A1	5/2014	Jerauld
2014/0152530	A1	6/2014	Venkatesha et al.
2014/0152558	A1	6/2014	Salter et al.
2014/0152676	A1	6/2014	Rohn et al.
2014/0159995	A1	6/2014	Adams et al.
2014/0160055	A1	6/2014	Margolis et al.
2014/0160157	A1	6/2014	Poulos et al.
2014/0160170	A1	6/2014	Lyons
2014/0160576	A1	6/2014	Robbins et al.
2014/0168735	A1	6/2014	Yuan et al.
2014/0176603	A1	6/2014	Kumar et al.
2014/0177023	A1	6/2014	Gao et al.
2014/0232651	A1	8/2014	Kress et al.
2014/0253605	A1	9/2014	Border et al.
2014/0361957	A1	12/2014	Hua et al.
2015/0035744	A1	2/2015	Robbins et al.
2015/0147000	A1	5/2015	Salvador et al.
2015/0205035	A1	7/2015	Border et al.
2015/0205107	A1	7/2015	Border
2015/0205108	A1	7/2015	Border et al.
2015/0205111	A1	7/2015	Border et al.
2015/0205113	A1	7/2015	Border et al.
2015/0205114	A1	7/2015	Border et al.
2015/0205115	A1	7/2015	Border et al.
2015/0205116	A1	7/2015	Border et al.
2015/0205117	A1	7/2015	Border et al.
2015/0205118	A1	7/2015	Border et al.
2015/0205119	A1	7/2015	Osterhout et al.
2015/0205120	A1	7/2015	Border et al.
2015/0205121	A1	7/2015	Border et al.
2015/0205122	A1	7/2015	Border et al.
2015/0205125	A1	7/2015	Border et al.
2015/0205127	A1	7/2015	Border et al.
2015/0205128	A1	7/2015	Border
2015/0205129	A1	7/2015	Border et al.
2015/0205130	A1	7/2015	Border
2015/0205131	A1	7/2015	Border et al.
2015/0205135	A1	7/2015	Border et al.
2015/0213754	A1	7/2015	Amjad
2015/0260887	A1	9/2015	Salisbury et al.
2015/0277120	A1	10/2015	Border
2015/0309313	A1	10/2015	Border et al.
2015/0309314	A1	10/2015	Border et al.
2015/0316769	A1	11/2015	Border et al.
2015/0316770	A1	11/2015	Border et al.
2015/0316771	A1	11/2015	Border et al.
2015/0316772	A1	11/2015	Border et al.
2015/0355466	A1	12/2015	Border
2016/0007849	A1	1/2016	Krueger et al.
2016/0011417	A1	1/2016	Border et al.
2016/0018644	A1	1/2016	Border et al.
2016/0018645	A1	1/2016	Haddick et al.
2016/0018650	A1	1/2016	Haddick et al.
2016/0018651	A1	1/2016	Haddick et al.
2016/0018652	A1	1/2016	Haddick et al.
2016/0018653	A1	1/2016	Haddick et al.
2016/0018654	A1	1/2016	Haddick et al.
2016/0035139	A1	2/2016	Fuchs et al.
2016/0048018	A1	2/2016	De Matos
2016/0048021	A1	2/2016	Border
2016/0055675	A1	2/2016	Kasahara et al.
2016/0062121	A1	3/2016	Border et al.
2016/0062122	A1	3/2016	Border
2016/0085071	A1	3/2016	Border
2016/0085072	A1	3/2016	Haddick et al.
2016/0091718	A1	3/2016	Border et al.
2016/0091719	A1	3/2016	Border
2016/0109711	A1	4/2016	Border
2016/0147070	A1	5/2016	Border et al.
2016/0154242	A1	6/2016	Border
2016/0154244	A1	6/2016	Border et al.
2016/0170207	A1	6/2016	Haddick et al.
2016/0170208	A1	6/2016	Border et al.
2016/0170209	A1	6/2016	Border et al.
2016/0171769	A1	6/2016	Haddick et al.
2016/0216516	A1	7/2016	Border
2016/0216517	A1	7/2016	Border
2016/0231571	A1	8/2016	Border et al.
2016/0252731	A1	9/2016	Border et al.
2016/0259166	A1	9/2016	Border et al.
2016/0274361	A1	9/2016	Border et al.
2016/0274365	A1	9/2016	Bailey et al.
2016/0282626	A1	9/2016	Border et al.
2016/0286177	A1	9/2016	Border et al.
2016/0286203	A1	9/2016	Border et al.
2016/0286210	A1	9/2016	Border et al.
2016/0357019	A1	12/2016	Border et al.
2017/0115486	A1	4/2017	Border et al.

FOREIGN PATENT DOCUMENTS

EP	2486450	A1	8/2012
EP	2502410	A1	9/2012
WO	2011143655	A1	11/2011
WO	2012058175	A1	5/2012
WO	2012064546	A1	5/2012
WO	2012082807	A2	6/2012
WO	2012118573	A1	9/2012
WO	2012118575	A2	9/2012
WO	2013043288	A2	3/2013
WO	2013049248	A2	3/2013
WO	2013050650	A1	4/2013
WO	2013103825	A1	7/2013
WO	2013110846	A1	8/2013
WO	2013170073	A1	11/2013

OTHER PUBLICATIONS

US 8,792,178, 07/2014, Totani et al. (withdrawn)
 US 9,195,056, 11/2015, Border et al. (withdrawn)

(56)

References Cited

OTHER PUBLICATIONS

Allison, et al., ““Tolerance of Temporal Delay in Virtual Environments””, VR '01 Proceedings of the Virtual Reality 2001 Conference (VR'01), Mar. 2001, p. 2-8.

Cheng, et al., “Design of an optical see-through head-mounted display with a low f-number and large field of view using a freeform prism”, Applied Optics, vol. 48, No. 14, May 10, 2009, pp. 2655-2668.

Lang, et al., ““Nonlinear Disparity Mapping for Stereoscopic 3D””, Jul. 2010, pp. 1-10.

Schedwill, “Bidirectional OLED Microdisplay”, Fraunhofer Research Institution for Organics, Materials and Electronic Device Comedd, Apr. 11, 2014, 2 pages.

Vogel, et al., “Data glasses controlled by eye movements”, Information and communication, Fraunhofer-Gesellschaft, Sep. 22, 2013, 2 pages.

* cited by examiner




Figure 1





Figure 2



PRIOR ART

Figure 3a




Figure 3b




Figure 4




Figure 4a

202




Figure 4b




Figure 5




Figure 5a




Figure 5b




Figure 5c




Figure 5d




Figure 5e




Figure 6




Figure 7




Figure 8




Figure 8a




Figure 8b




Figure 8c




Figure 9




Figure 10




Figure 10a




Figure 10b




Figure 11a




Fig. 11b




Figure 11c

1108




Fig. 11d




Figure 12a




Figure 12b




Figure 12c




Figure 13a




Figure 13b




Figure 13c




Figure 14a




Figure 14b




Figure 14c




Figure 15




FIG. 16A




FIG. 16B




FIG. 16C




Fig. 17A




Fig. 17B






Fig. 17C






Fig. 18B






Fig. 18C






FIG. 20




Figure 21




Figure 22




Figure 23




Figure 23a




Figure 24




Figure 25




Figure 26




Figure 27




Figure 28a

2810

2820

2815




Figure 28b

2810

2830

2825




Figure 28c

2810

2840

2835




Figure 29




Figure 30




Figure 31




Figure 32




Figure 32a




Figure 33




Figure 34




Figure 34a




Figure 35




Figure 36a




Figure 36b




Figure 37




Figure 38




Figure 39




Figure 40




Figure 41




Figure 42





Figure 43






Figure 45




Figure 46




Figure 47




Figure 48




Figure 49




Figure 50




Figure 51




Figure 52




Figure 53




Figure 54




Figure 55




Figure 56




Figure 57

OPTICAL CONFIGURATIONS FOR HEAD-WORN SEE-THROUGH DISPLAYS

CROSS REFERENCE OF RELATED APPLICATIONS

This application claims the benefit of priority to and is a divisional of the following U.S. patent application, which is incorporated by reference herein in its entirety:

U.S. non-provisional application Ser. No. 14/325,991, filed Jul. 8, 2014.

BACKGROUND

Field of the Invention

This invention relates to head worn computing. More particularly, this invention relates to optical configurations for head-worn see-through computer displays.

Description of Related Art

Wearable computing systems have been developed and are beginning to be commercialized. Many problems persist in the wearable computing field that need to be resolved to make them meet the demands of the market.

SUMMARY

Aspects of the present invention relate to optical configurations for head-worn see-through computer displays.

In displays it is typically important to provide a high quality image to the user. In head mounted displays it is important to provide a compact display assembly that is low in weight so the display can be comfortably worn on the head of the user. In head mounted displays that provide a see-through view of the environment, it is also important to provide a high contrast displayed image with black blacks so the environment can be easily viewed. Optical systems of the present inventions are small, light-weight and produce high image quality in a head-worn see-through device.

Systems and methods described herein provide upper optics comprised of a reflective display, a field lens, a reflective polarizer and a light source. The optical layout of the illumination optical path and the imaging optical path are overlapped to reduce the overall size of the optics package. In embodiments, a flat reflective polarizer is used both to redirect polarized illumination light toward a reflective image source and to act as the analyzer polarizer on the image light thereby enabling more compact optics and reducing the weight of the display assembly. In embodiments where the reflective polarizer is flat, the illumination light is provided with a central light ray at about 45 degrees, high incident angle surfaces are avoided to reduce scattered light and thereby enable increased contrast in the displayed image. Further, the flat reflective polarizer can be a film or a coating to reduce weight. Space is provided at the surface of the reflective image source so that a compensator film can be provided on the reflective image source to provide a higher contrast image to the user.

In embodiments, the lower optics comprising a beam splitter, a quarter wave film and a rotationally curved partial mirror, are largely comprised of air to provide a compact display assembly that has very low weight. In addition, in embodiments, the optical surfaces in the imaging optics are all either on axis or flat to thereby preserve the wavefront of the image light and thereby provide a high image quality.

These and other systems, methods, objects, features, and advantages of the present invention will be apparent to those skilled in the art from the following detailed description of

the preferred embodiment and the drawings. All documents mentioned herein are hereby incorporated in their entirety by reference.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments are described with reference to the following Figures. The same numbers may be used throughout to reference like features and components that are shown in the Figures:

FIG. 1 illustrates a head worn computing system in accordance with the principles of the present invention.

FIG. 2 illustrates a head worn computing system with optical system in accordance with the principles of the present invention.

FIG. 3a illustrates a large prior art optical arrangement.

FIG. 3b illustrates an upper optical module in accordance with the principles of the present invention.

FIG. 4 illustrates an upper optical module in accordance with the principles of the present invention.

FIG. 4a illustrates an upper optical module in accordance with the principles of the present invention.

FIG. 4b illustrates an upper optical module in accordance with the principles of the present invention.

FIG. 5 illustrates an upper optical module in accordance with the principles of the present invention.

FIG. 5a illustrates an upper optical module in accordance with the principles of the present invention.

FIG. 5b illustrates an upper optical module and dark light trap according to the principles of the present invention.

FIG. 5c illustrates an upper optical module and dark light trap according to the principles of the present invention.

FIG. 5d illustrates an upper optical module and dark light trap according to the principles of the present invention.

FIG. 5e illustrates an upper optical module and dark light trap according to the principles of the present invention.

FIG. 6 illustrates upper and lower optical modules in accordance with the principles of the present invention.

FIG. 7 illustrates angles of combiner elements in accordance with the principles of the present invention.

FIG. 8 illustrates upper and lower optical modules in accordance with the principles of the present invention.

FIG. 8a illustrates upper and lower optical modules in accordance with the principles of the present invention.

FIG. 8b illustrates upper and lower optical modules in accordance with the principles of the present invention.

FIG. 8c illustrates upper and lower optical modules in accordance with the principles of the present invention.

FIG. 9 illustrates an eye imaging system in accordance with the principles of the present invention.

FIG. 10 illustrates a light source in accordance with the principles of the present invention.

FIG. 10a illustrates a back lighting system in accordance with the principles of the present invention.

FIG. 10b illustrates a back lighting system in accordance with the principles of the present invention.

FIGS. 11a to 11d illustrate light source and filters in accordance with the principles of the present invention.

FIGS. 12a to 12c illustrate light source and quantum dot systems in accordance with the principles of the present invention.

FIGS. 13a to 13c illustrate peripheral lighting systems in accordance with the principles of the present invention.

FIGS. 14a to 14c illustrate a light suppression systems in accordance with the principles of the present invention.

FIG. 15 illustrates an external user interface in accordance with the principles of the present invention.

FIGS. 16a to 16c illustrate distance control systems in accordance with the principles of the present invention.

FIGS. 17a to 17c illustrate force interpretation systems in accordance with the principles of the present invention.

FIGS. 18a to 18c illustrate user interface mode selection systems in accordance with the principles of the present invention.

FIG. 19 illustrates interaction systems in accordance with the principles of the present invention.

FIG. 20 illustrates external user interfaces in accordance with the principles of the present invention.

FIG. 21 illustrates mD trace representations presented in accordance with the principles of the present invention.

FIG. 22 illustrates mD trace representations presented in accordance with the principles of the present invention.

FIG. 23 illustrates an mD scanned environment in accordance with the principles of the present invention.

FIG. 23a illustrates mD trace representations presented in accordance with the principles of the present invention.

FIG. 24 illustrates a stray light suppression technology in accordance with the principles of the present invention.

FIG. 25 illustrates a stray light suppression technology in accordance with the principles of the present invention.

FIG. 26 illustrates a stray light suppression technology in accordance with the principles of the present invention.

FIG. 27 illustrates a stray light suppression technology in accordance with the principles of the present invention.

FIGS. 28a to 28c illustrate DLP mirror angles.

FIG. 29, FIG. 30, FIG. 31, FIG. 32, FIG. 32a, and FIG. 33 illustrate eye imaging systems according to the principles of the present invention.

FIGS. 34 and 34a illustrate structured eye lighting systems according to the principles of the present invention.

FIG. 35 illustrates eye glint in the prediction of eye direction analysis in accordance with the principles of the present invention.

FIG. 36a illustrates eye characteristics that may be used in personal identification through analysis of a system according to the principles of the present invention.

FIG. 36b illustrates a digital content presentation reflection off of the wearer's eye that may be analyzed in accordance with the principles of the present invention.

FIG. 37 illustrates eye imaging along various virtual target lines and various focal planes in accordance with the principles of the present invention.

FIG. 38 illustrates content control with respect to eye movement based on eye imaging in accordance with the principles of the present invention.

FIG. 39 illustrates eye imaging and eye convergence in accordance with the principles of the present invention.

FIG. 40 illustrates content position dependent on sensor feedback in accordance with the principles of the present invention.

FIG. 41 illustrates content position dependent on sensor feedback in accordance with the principles of the present invention.

FIG. 42 illustrates content position dependent on sensor feedback in accordance with the principles of the present invention.

FIG. 43 illustrates content position dependent on sensor feedback in accordance with the principles of the present invention.

FIG. 44 illustrates content position dependent on sensor feedback in accordance with the principles of the present invention.

FIG. 45 illustrates various headings over time in an example.

FIG. 46 illustrates content position dependent on sensor feedback in accordance with the principles of the present invention.

FIG. 47 illustrates content position dependent on sensor feedback in accordance with the principles of the present invention.

FIG. 48 illustrates content position dependent on sensor feedback in accordance with the principles of the present invention.

FIG. 49 illustrates content position dependent on sensor feedback in accordance with the principles of the present invention.

FIG. 50 illustrates a scene where a person is walking with a HWC mounted on his head.

FIG. 51 illustrates a system for receiving, developing and using movement heading, sight heading, eye heading and/or persistence information from HWC(s).

FIG. 52 illustrates a scene where a person is collecting other people's eye/sight headings.

FIG. 53 illustrates an optical configuration for a see-through head-worn computer display in accordance with the principles of the present invention.

FIG. 54 illustrates an optical configuration for a see-through head-worn computer display in accordance with the principles of the present invention.

FIG. 55 illustrates an optical configuration for a see-through head-worn computer display in accordance with the principles of the present invention.

FIG. 56 illustrates an optical configuration for a see-through head-worn computer display in accordance with the principles of the present invention.

FIG. 57 illustrates an optical configuration for a see-through head-worn computer display in accordance with the principles of the present invention.

While the invention has been described in connection with certain preferred embodiments, other embodiments would be understood by one of ordinary skill in the art and are encompassed herein.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

Aspects of the present invention relate to head-worn computing ("HWC") systems. HWC involves, in some instances, a system that mimics the appearance of head-worn glasses or sunglasses. The glasses may be a fully developed computing platform, such as including computer displays presented in each of the lenses of the glasses to the eyes of the user. In embodiments, the lenses and displays may be configured to allow a person wearing the glasses to see the environment through the lenses while also seeing, simultaneously, digital imagery, which forms an overlaid image that is perceived by the person as a digitally augmented image of the environment, or augmented reality ("AR").

HWC involves more than just placing a computing system on a person's head. The system may need to be designed as a lightweight, compact and fully functional computer display, such as wherein the computer display includes a high resolution digital display that provides a high level of emersion comprised of the displayed digital content and the see-through view of the environmental surroundings. User interfaces and control systems suited to the HWC device may be required that are unlike those used for a more conventional computer such as a laptop. For the HWC and associated systems to be most effective, the glasses may be equipped with sensors to determine environmental conditions, geographic location, relative positioning to other

points of interest, objects identified by imaging and movement by the user or other users in a connected group, and the like. The HWC may then change the mode of operation to match the conditions, location, positioning, movements, and the like, in a method generally referred to as a contextually aware HWC. The glasses also may need to be connected, wirelessly or otherwise, to other systems either locally or through a network. Controlling the glasses may be achieved through the use of an external device, automatically through contextually gathered information, through user gestures captured by the glasses sensors, and the like. Each technique may be further refined depending on the software application being used in the glasses. The glasses may further be used to control or coordinate with external devices that are associated with the glasses.

Referring to FIG. 1, an overview of the HWC system 100 is presented. As shown, the HWC system 100 comprises a HWC 102, which in this instance is configured as glasses to be worn on the head with sensors such that the HWC 102 is aware of the objects and conditions in the environment 114. In this instance, the HWC 102 also receives and interprets control inputs such as gestures and movements 116. The HWC 102 may communicate with external user interfaces 104. The external user interfaces 104 may provide a physical user interface to take control instructions from a user of the HWC 102 and the external user interfaces 104 and the HWC 102 may communicate bi-directionally to affect the user's command and provide feedback to the external device 108. The HWC 102 may also communicate bi-directionally with externally controlled or coordinated local devices 108. For example, an external user interface 104 may be used in connection with the HWC 102 to control an externally controlled or coordinated local device 108. The externally controlled or coordinated local device 108 may provide feedback to the HWC 102 and a customized GUI may be presented in the HWC 102 based on the type of device or specifically identified device 108. The HWC 102 may also interact with remote devices and information sources 112 through a network connection 110. Again, the external user interface 104 may be used in connection with the HWC 102 to control or otherwise interact with any of the remote devices 108 and information sources 112 in a similar way as when the external user interfaces 104 are used to control or otherwise interact with the externally controlled or coordinated local devices 108. Similarly, HWC 102 may interpret gestures 116 (e.g. captured from forward, downward, upward, rearward facing sensors such as camera(s), range finders, IR sensors, etc.) or environmental conditions sensed in the environment 114 to control either local or remote devices 108 or 112.

We will now describe each of the main elements depicted on FIG. 1 in more detail; however, these descriptions are intended to provide general guidance and should not be construed as limiting. Additional description of each element may also be further described herein.

The HWC 102 is a computing platform intended to be worn on a person's head. The HWC 102 may take many different forms to fit many different functional requirements. In some situations, the HWC 102 will be designed in the form of conventional glasses. The glasses may or may not have active computer graphics displays. In situations where the HWC 102 has integrated computer displays the displays may be configured as see-through displays such that the digital imagery can be overlaid with respect to the user's view of the environment 114. There are a number of see-through optical designs that may be used, including ones that have a reflective display (e.g. LCoS, DLP), emissive

displays (e.g. OLED, LED), hologram, TIR waveguides, and the like. In embodiments, lighting systems used in connection with the display optics may be solid state lighting systems, such as LED, OLED, quantum dot, quantum dot LED, etc. In addition, the optical configuration may be monocular or binocular. It may also include vision corrective optical components. In embodiments, the optics may be packaged as contact lenses. In other embodiments, the HWC 102 may be in the form of a helmet with a see-through shield, sunglasses, safety glasses, goggles, a mask, fire helmet with see-through shield, police helmet with see through shield, military helmet with see-through shield, utility form customized to a certain work task (e.g. inventory control, logistics, repair, maintenance, etc.), and the like.

The HWC 102 may also have a number of integrated computing facilities, such as an integrated processor, integrated power management, communication structures (e.g. cell net, WiFi, Bluetooth, local area connections, mesh connections, remote connections (e.g. client server, etc.)), and the like. The HWC 102 may also have a number of positional awareness sensors, such as GPS, electronic compass, altimeter, tilt sensor, IMU, and the like. It may also have other sensors such as a camera, rangefinder, hyperspectral camera, Geiger counter, microphone, spectral illumination detector, temperature sensor, chemical sensor, biologic sensor, moisture sensor, ultrasonic sensor, and the like.

The HWC 102 may also have integrated control technologies. The integrated control technologies may be contextual based control, passive control, active control, user control, and the like. For example, the HWC 102 may have an integrated sensor (e.g. camera) that captures user hand or body gestures 116 such that the integrated processing system can interpret the gestures and generate control commands for the HWC 102. In another example, the HWC 102 may have sensors that detect movement (e.g. a nod, head shake, and the like) including accelerometers, gyros and other inertial measurements, where the integrated processor may interpret the movement and generate a control command in response. The HWC 102 may also automatically control itself based on measured or perceived environmental conditions. For example, if it is bright in the environment the HWC 102 may increase the brightness or contrast of the displayed image. In embodiments, the integrated control technologies may be mounted on the HWC 102 such that a user can interact with it directly. For example, the HWC 102 may have a button(s), touch capacitive interface, and the like.

As described herein, the HWC 102 may be in communication with external user interfaces 104. The external user interfaces may come in many different forms. For example, a cell phone screen may be adapted to take user input for control of an aspect of the HWC 102. The external user interface may be a dedicated UI, such as a keyboard, touch surface, button(s), joy stick, and the like. In embodiments, the external controller may be integrated into another device such as a ring, watch, bike, car, and the like. In each case, the external user interface 104 may include sensors (e.g. IMU, accelerometers, compass, altimeter, and the like) to provide additional input for controlling the HWC 102.

As described herein, the HWC 102 may control or coordinate with other local devices 108. The external devices 108 may be an audio device, visual device, vehicle, cell phone, computer, and the like. For instance, the local external device 108 may be another HWC 102, where information may then be exchanged between the separate HWCs 108.

Similar to the way the HWC 102 may control or coordinate with local devices 106, the HWC 102 may control or coordinate with remote devices 112, such as the HWC 102 communicating with the remote devices 112 through a network 110. Again, the form of the remote device 112 may have many forms. Included in these forms is another HWC 102. For example, each HWC 102 may communicate its GPS position such that all the HWCs 102 know where all of HWC 102 are located.

FIG. 2 illustrates a HWC 102 with an optical system that includes an upper optical module 202 and a lower optical module 204. While the upper and lower optical modules 202 and 204 will generally be described as separate modules, it should be understood that this is illustrative only and the present invention includes other physical configurations, such as that when the two modules are combined into a single module or where the elements making up the two modules are configured into more than two modules. In embodiments, the upper module 202 includes a computer controlled display (e.g. LCoS, DLP, OLED, etc.) and image light delivery optics. In embodiments, the lower module includes eye delivery optics that are configured to receive the upper module's image light and deliver the image light to the eye of a wearer of the HWC. In FIG. 2, it should be noted that while the upper and lower optical modules 202 and 204 are illustrated in one side of the HWC such that image light can be delivered to one eye of the wearer, that it is envisioned by the present invention that embodiments will contain two image light delivery systems, one for each eye.

FIG. 3b illustrates an upper optical module 202 in accordance with the principles of the present invention. In this embodiment, the upper optical module 202 includes a DLP (also known as DMD or digital micromirror device) computer operated display 304 which includes pixels comprised of rotatable mirrors (such as, for example, the DLP3000 available from Texas Instruments), polarized light source 302, ¼ wave retarder film 308, reflective polarizer 310 and a field lens 312. The polarized light source 302 provides substantially uniform polarized light that is generally directed towards the reflective polarizer 310. The reflective polarizer reflects light of one polarization state (e.g. S polarized light) and transmits light of the other polarization state (e.g. P polarized light). The polarized light source 302 and the reflective polarizer 310 are oriented so that the polarized light from the polarized light source 302 is reflected generally towards the DLP 304. The light then passes through the ¼ wave film 308 once before illuminating the pixels of the DLP 304 and then again after being reflected by the pixels of the DLP 304. In passing through the ¼ wave film 308 twice, the light is converted from one polarization state to the other polarization state (e.g. the light is converted from S to P polarized light). The light then passes through the reflective polarizer 310. In the event that the DLP pixel(s) are in the "on" state (i.e. the mirrors are positioned to reflect light towards the field lens 312, the "on" pixels reflect the light generally along the optical axis and into the field lens 312. This light that is reflected by "on" pixels and which is directed generally along the optical axis of the field lens 312 will be referred to as image light 316. The image light 316 then passes through the field lens to be used by a lower optical module 204.

The light that is provided by the polarized light source 302, which is subsequently reflected by the reflective polarizer 310 before it reflects from the DLP 304, will generally be referred to as illumination light. The light that is reflected by the "off" pixels of the DLP 304 is reflected at a different

angle than the light reflected by the "on" pixels, so that the light from the "off" pixels is generally directed away from the optical axis of the field lens 312 and toward the side of the upper optical module 202 as shown in FIG. 3. The light that is reflected by the "off" pixels of the DLP 304 will be referred to as dark state light 314.

The DLP 304 operates as a computer controlled display and is generally thought of as a MEMs device. The DLP pixels are comprised of small mirrors that can be directed. The mirrors generally flip from one angle to another angle. The two angles are generally referred to as states. When light is used to illuminate the DLP the mirrors will reflect the light in a direction depending on the state. In embodiments herein, we generally refer to the two states as "on" and "off," which is intended to depict the condition of a display pixel. "On" pixels will be seen by a viewer of the display as emitting light because the light is directed along the optical axis and into the field lens and the associated remainder of the display system. "Off" pixels will be seen by a viewer of the display as not emitting light because the light from these pixels is directed to the side of the optical housing and into a light trap or light dump where the light is absorbed. The pattern of "on" and "off" pixels produces image light that is perceived by a viewer of the display as a computer generated image. Full color images can be presented to a user by sequentially providing illumination light with complimentary colors such as red, green and blue. Where the sequence is presented in a recurring cycle that is faster than the user can perceive as separate images and as a result the user perceives a full color image comprised of the sum of the sequential images. Bright pixels in the image are provided by pixels that remain in the "on" state for the entire time of the cycle, while dimmer pixels in the image are provided by pixels that switch between the "on" state and "off" state within the time of the cycle, or frame time when in a video sequence of images.

FIG. 3a shows an illustration of a system for a DLP 304 in which the unpolarized light source 350 is pointed directly at the DLP 304. In this case, the angle required for the illumination light is such that the field lens 352 must be positioned substantially distant from the DLP 304 to avoid the illumination light from being clipped by the field lens 352. The large distance between the field lens 352 and the DLP 304 along with the straight path of the dark state light 354, means that the light trap for the dark state light 354 is also located at a substantial distance from the DLP. For these reasons, this configuration is larger in size compared to the upper optics module 202 of the preferred embodiments.

The configuration illustrated in FIG. 3b can be lightweight and compact such that it fits into a small portion of a HWC. For example, the upper modules 202 illustrated herein can be physically adapted to mount in an upper frame of a HWC such that the image light can be directed into a lower optical module 204 for presentation of digital content to a wearer's eye. The package of components that combine to generate the image light (i.e. the polarized light source 302, DLP 304, reflective polarizer 310 and ¼ wave film 308) is very light and is compact. The height of the system, excluding the field lens, may be less than 8 mm. The width (i.e. from front to back) may be less than 8 mm. The weight may be less than 2 grams. The compactness of this upper optical module 202 allows for a compact mechanical design of the HWC and the light weight nature of these embodiments help make the HWC lightweight to provide for a HWC that is comfortable for a wearer of the HWC.

The configuration illustrated in FIG. 3b can produce sharp contrast, high brightness and deep blacks, especially when

compared to LCD or LCoS displays used in HWC. The “on” and “off” states of the DLP provide for a strong differentiator in the light reflection path representing an “on” pixel and an “off” pixel. As will be discussed in more detail below, the dark state light from the “off” pixel reflections can be managed to reduce stray light in the display system to produce images with high contrast.

FIG. 4 illustrates another embodiment of an upper optical module 202 in accordance with the principles of the present invention. This embodiment includes a light source 404, but in this case, the light source can provide unpolarized illumination light. The illumination light from the light source 404 is directed into a TIR wedge 418 such that the illumination light is incident on an internal surface of the TIR wedge 418 (shown as the angled lower surface of the TRI wedge 418 in FIG. 4) at an angle that is beyond the critical angle as defined by Eqn 1.

$$\text{Critical angle} = \arcsin(1/n)$$

Eqn 1

Where the critical angle is the angle beyond which the illumination light is reflected from the internal surface when the internal surface comprises an interface from a solid with a higher refractive index (n) to air with a refractive index of 1 (e.g. for an interface of acrylic, with a refractive index of n=1.5, to air, the critical angle is 41.8 degrees; for an interface of polycarbonate, with a refractive index of n=1.59, to air the critical angle is 38.9 degrees). Consequently, the TIR wedge 418 is associated with a thin air gap 408 along the internal surface to create an interface between a solid with a higher refractive index and air. By choosing the angle of the light source 404 relative to the DLP 402 in correspondence to the angle of the internal surface of the TIR wedge 418, illumination light is turned toward the DLP 402 at an angle suitable for providing image light 414 as reflected from “on” pixels. Wherein, the illumination light is provided to the DLP 402 at approximately twice the angle of the pixel mirrors in the DLP 402 that are in the “on” state, such that after reflecting from the pixel mirrors, the image light 414 is directed generally along the optical axis of the field lens. Depending on the state of the DLP pixels, the illumination light from “on” pixels may be reflected as image light 414 which is directed towards a field lens and a lower optical module 204, while illumination light reflected from “off” pixels (generally referred to herein as “dark” state light, “off” pixel light or “off” state light) 410 is directed in a separate direction, which may be trapped and not used for the image that is ultimately presented to the wearer’s eye.

The light trap for the dark state light 410 may be located along the optical axis defined by the direction of the dark state light 410 and in the side of the housing, with the function of absorbing the dark state light. To this end, the light trap may be comprised of an area outside of the cone of image light 414 from the “on” pixels. The light trap is typically made up of materials that absorb light including coatings of black paints or other light absorbing materials to prevent light scattering from the dark state light degrading the image perceived by the user. In addition, the light trap may be recessed into the wall of the housing or include masks or guards to block scattered light and prevent the light trap from being viewed adjacent to the displayed image.

The embodiment of FIG. 4 also includes a corrective wedge 420 to correct the effect of refraction of the image light 414 as it exits the TIR wedge 418. By including the corrective wedge 420 and providing a thin air gap 408 (e.g. 25 micron), the image light from the “on” pixels can be maintained generally in a direction along the optical axis of the field lens (i.e. the same direction as that defined by the

image light 414) so it passes into the field lens and the lower optical module 204. As shown in FIG. 4, the image light 414 from the “on” pixels exits the corrective wedge 420 generally perpendicular to the surface of the corrective wedge 420 while the dark state light exits at an oblique angle. As a result, the direction of the image light 414 from the “on” pixels is largely unaffected by refraction as it exits from the surface of the corrective wedge 420. In contrast, the dark state light 410 is substantially changed in direction by refraction when the dark state light 410 exits the corrective wedge 420.

The embodiment illustrated in FIG. 4 has the similar advantages of those discussed in connection with the embodiment of FIG. 3b. The dimensions and weight of the upper module 202 depicted in FIG. 4 may be approximately 8x8 mm with a weight of less than 3 grams. A difference in overall performance between the configuration illustrated in FIG. 3b and the configuration illustrated in FIG. 4 is that the embodiment of FIG. 4 doesn’t require the use of polarized light as supplied by the light source 404. This can be an advantage in some situations as will be discussed in more detail below (e.g. increased see-through transparency of the HWC optics from the user’s perspective). Polarized light may be used in connection with the embodiment depicted in FIG. 4, in embodiments. An additional advantage of the embodiment of FIG. 4 compared to the embodiment shown in FIG. 3b is that the dark state light (shown as DLP off light 410) is directed at a steeper angle away from the optical axis of the image light 414 due to the added refraction encountered when the dark state light 410 exits the corrective wedge 420. This steeper angle of the dark state light 410 allows for the light trap to be positioned closer to the DLP 402 so that the overall size of the upper module 202 can be reduced. The light trap can also be made larger since the light trap doesn’t interfere with the field lens, thereby the efficiency of the light trap can be increased and as a result, stray light can be reduced and the contrast of the image perceived by the user can be increased. FIG. 4a illustrates the embodiment described in connection with FIG. 4 with an example set of corresponding angles at the various surfaces with the reflected angles of a ray of light passing through the upper optical module 202. In this example, the DLP mirrors are provided at 17 degrees to the surface of the DLP device. The angles of the TIR wedge are selected in correspondence to one another to provide TIR reflected illumination light at the correct angle for the DLP mirrors while allowing the image light and dark state light to pass through the thin air gap, various combinations of angles are possible to achieve this.

FIG. 5 illustrates yet another embodiment of an upper optical module 202 in accordance with the principles of the present invention. As with the embodiment shown in FIG. 4, the embodiment shown in FIG. 5 does not require the use of polarized light. Polarized light may be used in connection with this embodiment, but it is not required. The optical module 202 depicted in FIG. 5 is similar to that presented in connection with FIG. 4; however, the embodiment of FIG. 5 includes an off light redirection wedge 502. As can be seen from the illustration, the off light redirection wedge 502 allows the image light 414 to continue generally along the optical axis toward the field lens and into the lower optical module 204 (as illustrated). However, the off light 504 is redirected substantially toward the side of the corrective wedge 420 where it passes into the light trap. This configuration may allow further height compactness in the HWC because the light trap (not illustrated) that is intended to absorb the off light 504 can be positioned laterally adjacent

the upper optical module **202** as opposed to below it. In the embodiment depicted in FIG. **5** there is a thin air gap between the TIR wedge **418** and the corrective wedge **420** (similar to the embodiment of FIG. **4**). There is also a thin air gap between the corrective wedge **420** and the off light redirection wedge **502**. There may be HWC mechanical configurations that warrant the positioning of a light trap for the dark state light elsewhere and the illustration depicted in FIG. **5** should be considered illustrative of the concept that the off light can be redirected to create compactness of the overall HWC. FIG. **5a** illustrates an example of the embodiment described in connection with FIG. **5** with the addition of more details on the relative angles at the various surfaces and a light ray trace for image light and a light ray trace for dark light are shown as it passes through the upper optical module **202**. Again, various combinations of angles are possible.

FIG. **4b** shows an illustration of a further embodiment in which a solid transparent matched set of wedges **456** is provided with a reflective polarizer **450** at the interface between the wedges. Wherein the interface between the wedges in the wedge set **456** is provided at an angle so that illumination light **452** from the polarized light source **458** is reflected at the proper angle (e.g. 34 degrees for a 17 degree DLP mirror) for the DLP mirror “on” state so that the reflected image light **414** is provided along the optical axis of the field lens. The general geometry of the wedges in the wedge set **456** is similar to that shown in FIGS. **4** and **4a**. A quarter wave film **454** is provided on the DLP **402** surface so that the illumination light **452** is one polarization state (e.g. S polarization state) while in passing through the quarter wave film **454**, reflecting from the DLP mirror and passing back through the quarter wave film **454**, the image light **414** is converted to the other polarization state (e.g. P polarization state). The reflective polarizer is oriented such that the illumination light **452** with its polarization state is reflected and the image light **414** with its other polarization state is transmitted. Since the dark state light from the “off” pixels **410** also passes through the quarter wave film **454** twice, it is also the other polarization state (e.g. P polarization state) so that it is transmitted by the reflective polarizer **450**.

The angles of the faces of the wedge set **450** correspond to the needed angles to provide illumination light **452** at the angle needed by the DLP mirrors when in the “on” state so that the reflected image light **414** is reflected from the DLP along the optical axis of the field lens. The wedge set **456** provides an interior interface where a reflective polarizer film can be located to redirect the illumination light **452** toward the mirrors of the DLP **402**. The wedge set also provides a matched wedge on the opposite side of the reflective polarizer **450** so that the image light **414** from the “on” pixels exits the wedge set **450** substantially perpendicular to the exit surface, while the dark state light from the “off” pixels **410** exits at an oblique angle to the exit surface. As a result, the image light **414** is substantially unrefracted upon exiting the wedge set **456**, while the dark state light from the “off” pixels **410** is substantially refracted upon exiting the wedge set **456** as shown in FIG. **4b**.

By providing a solid transparent matched wedge set, the flatness of the interface is reduced, because variations in the flatness have a negligible effect as long as they are within the cone angle of the illuminating light **452**. Which can be $f\#2.2$ with a 26 degree cone angle. In a preferred embodiment, the reflective polarizer is bonded between the matched internal surfaces of the wedge set **456** using an optical adhesive so that Fresnel reflections at the interfaces on either side of the

reflective polarizer **450** are reduced. The optical adhesive can be matched in refractive index to the material of the wedge set **456** and the pieces of the wedge set **456** can be all made from the same material such as BK7 glass or cast acrylic. Wherein the wedge material can be selected to have low birefringence as well to reduce non-uniformities in brightness. The wedge set **456** and the quarter wave film **454** can also be bonded to the DLP **402** to further reduce Fresnel reflections at the DLP interface losses. In addition, since the image light **414** is substantially normal to the exit surface of the wedge set **456**, the flatness of the surface is not critical to maintain the wavefront of the image light **414** so that high image quality can be obtained in the displayed image without requiring very tightly toleranced flatness on the exit surface.

A yet further embodiment of the invention that is not illustrated, combines the embodiments illustrated in FIG. **4b** and FIG. **5**. In this embodiment, the wedge set **456** is comprised of three wedges with the general geometry of the wedges in the wedge set corresponding to that shown in FIGS. **5** and **5a**. A reflective polarizer is bonded between the first and second wedges similar to that shown in FIG. **4b**, however, a third wedge is provided similar to the embodiment of FIG. **5**. Wherein there is an angled thin air gap between the second and third wedges so that the dark state light is reflected by TIR toward the side of the second wedge where it is absorbed in a light trap. This embodiment, like the embodiment shown in FIG. **4b**, uses a polarized light source as has been previously described. The difference in this embodiment is that the image light is transmitted through the reflective polarizer and is transmitted through the angled thin air gap so that it exits normal to the exit surface of the third wedge.

FIG. **5b** illustrates an upper optical module **202** with a dark light trap **514a**. As described in connection with FIGS. **4** and **4a**, image light can be generated from a DLP when using a TIR and corrective lens configuration. The upper module may be mounted in a HWC housing **510** and the housing **510** may include a dark light trap **514a**. The dark light trap **514a** is generally positioned/constructed/formed in a position that is optically aligned with the dark light optical axis **512**. As illustrated, the dark light trap may have depth such that the trap internally reflects dark light in an attempt to further absorb the light and prevent the dark light from combining with the image light that passes through the field lens. The dark light trap may be of a shape and depth such that it absorbs the dark light. In addition, the dark light trap **514b**, in embodiments, may be made of light absorbing materials or coated with light absorbing materials. In embodiments, the recessed light trap **514a** may include baffles to block a view of the dark state light. This may be combined with black surfaces and textured or fibrous surfaces to help absorb the light. The baffles can be part of the light trap, associated with the housing, or field lens, etc.

FIG. **5c** illustrates another embodiment with a light trap **514b**. As can be seen in the illustration, the shape of the trap is configured to enhance internal reflections within the light trap **514b** to increase the absorption of the dark light **512**. FIG. **5d** illustrates another embodiment with a light trap **514c**. As can be seen in the illustration, the shape of the trap **514c** is configured to enhance internal reflections to increase the absorption of the dark light **512**.

FIG. **5e** illustrates another embodiment of an upper optical module **202** with a dark light trap **514d**. This embodiment of upper module **202** includes an off light reflection wedge **502**, as illustrated and described in connection with the embodiment of FIGS. **5** and **5a**. As can be seen in FIG.

5e, the light trap 514d is positioned along the optical path of the dark light 512. The dark light trap 514d may be configured as described in other embodiments herein. The embodiment of the light trap 514d illustrated in figure 5e includes a black area on the side wall of the wedge, wherein the side wall is located substantially away from the optical axis of the image light 414. In addition, baffles 5252 may be added to one or more edges of the field lens 312 to block the view of the light trap 514d adjacent to the displayed image seen by the user.

FIG. 6 illustrates a combination of an upper optical module 202 with a lower optical module 204. In this embodiment, the image light projected from the upper optical module 202 may or may not be polarized. The image light is reflected off a flat combiner element 602 such that it is directed towards the user's eye. Wherein, the combiner element 602 is a partial mirror that reflects image light while transmitting a substantial portion of light from the environment so the user can look through the combiner element and see the environment surrounding the HWC.

The combiner 602 may include a holographic pattern, to form a holographic mirror. If a monochrome image is desired, there may be a single wavelength reflection design for the holographic pattern on the surface of the combiner 602. If the intention is to have multiple colors reflected from the surface of the combiner 602, a multiple wavelength holographic mirror may be included on the combiner surface. For example, in a three-color embodiment, where red, green and blue pixels are generated in the image light, the holographic mirror may be reflective to wavelengths substantially matching the wavelengths of the red, green and blue light provided by the light source. This configuration can be used as a wavelength specific mirror where pre-determined wavelengths of light from the image light are reflected to the user's eye. This configuration may also be made such that substantially all other wavelengths in the visible pass through the combiner element 602 so the user has a substantially clear view of the surroundings when looking through the combiner element 602. The transparency between the user's eye and the surrounding may be approximately 80% when using a combiner that is a holographic mirror. Wherein holographic mirrors can be made using lasers to produce interference patterns in the holographic material of the combiner where the wavelengths of the lasers correspond to the wavelengths of light that are subsequently reflected by the holographic mirror.

In another embodiment, the combiner element 602 may include a notch mirror comprised of a multilayer coated substrate wherein the coating is designed to substantially reflect the wavelengths of light provided by the light source and substantially transmit the remaining wavelengths in the visible spectrum. For example, in the case where red, green and blue light is provided by the light source to enable full color images to be provided to the user, the notch mirror is a tristimulus notch mirror wherein the multilayer coating is designed to reflect narrow bands of red, green and blue light that are matched to the what is provided by the light source and the remaining visible wavelengths are transmitted through the coating to enable a view of the environment through the combiner. In another example where monochrome images are provided to the user, the notch mirror is designed to reflect a single narrow band of light that is matched to the wavelength range of the light provided by the light source while transmitting the remaining visible wavelengths to enable a see-thru view of the environment. The combiner 602 with the notch mirror would operate, from the user's perspective, in a manner similar to the combiner that

includes a holographic pattern on the combiner element 602. The combiner, with the tristimulus notch mirror, would reflect the "on" pixels to the eye because of the match between the reflective wavelengths of the notch mirror and the color of the image light, and the wearer would be able to see with high clarity the surroundings. The transparency between the user's eye and the surrounding may be approximately 80% when using the tristimulus notch mirror. In addition, the image provided by the upper optical module 202 with the notch mirror combiner can provide higher contrast images than the holographic mirror combiner due to less scattering of the imaging light by the combiner.

Light can escape through the combiner 602 and may produce face glow as the light is generally directed downward onto the cheek of the user. When using a holographic mirror combiner or a tristimulus notch mirror combiner, the escaping light can be trapped to avoid face glow. In embodiments, if the image light is polarized before the combiner, a linear polarizer can be laminated, or otherwise associated, to the combiner, with the transmission axis of the polarizer oriented relative to the polarized image light so that any escaping image light is absorbed by the polarizer. In embodiments, the image light would be polarized to provide S polarized light to the combiner for better reflection. As a result, the linear polarizer on the combiner would be oriented to absorb S polarized light and pass P polarized light. This provides the preferred orientation of polarized sunglasses as well.

If the image light is unpolarized, a microlouvered film such as a privacy filter can be used to absorb the escaping image light while providing the user with a see-thru view of the environment. In this case, the absorbance or transmittance of the microlouvered film is dependent on the angle of the light. Where steep angle light is absorbed and light at less of an angle is transmitted. For this reason, in an embodiment, the combiner with the microlouver film is angled at greater than 45 degrees to the optical axis of the image light (e.g. the combiner can be oriented at 50 degrees so the image light from the field lens is incident on the combiner at an oblique angle).

FIG. 7 illustrates an embodiment of a combiner element 602 at various angles when the combiner element 602 includes a holographic mirror. Normally, a mirrored surface reflects light at an angle equal to the angle that the light is incident to the mirrored surface. Typically, this necessitates that the combiner element be at 45 degrees, 602a, if the light is presented vertically to the combiner so the light can be reflected horizontally towards the wearer's eye. In embodiments, the incident light can be presented at angles other than vertical to enable the mirror surface to be oriented at other than 45 degrees, but in all cases wherein a mirrored surface is employed (including the tristimulus notch mirror described previously), the incident angle equals the reflected angle. As a result, increasing the angle of the combiner 602a requires that the incident image light be presented to the combiner 602a at a different angle which positions the upper optical module 202 to the left of the combiner as shown in FIG. 7. In contrast, a holographic mirror combiner, included in embodiments, can be made such that light is reflected at a different angle from the angle that the light is incident onto the holographic mirrored surface. This allows freedom to select the angle of the combiner element 602b independent of the angle of the incident image light and the angle of the light reflected into the wearer's eye. In embodiments, the angle of the combiner element 602b is greater than 45 degrees (shown in FIG. 7) as this allows a more laterally compact HWC design. The increased angle of the combiner

element **602b** decreases the front to back width of the lower optical module **204** and may allow for a thinner HWC display (i.e. the furthest element from the wearer's eye can be closer to the wearer's face).

FIG. **8** illustrates another embodiment of a lower optical module **204**. In this embodiment, polarized image light provided by the upper optical module **202**, is directed into the lower optical module **204**. The image light reflects off a polarized mirror **804** and is directed to a focusing partially reflective mirror **802**, which is adapted to reflect the polarized light. An optical element such as a $\frac{1}{4}$ wave film located between the polarized mirror **804** and the partially reflective mirror **802**, is used to change the polarization state of the image light such that the light reflected by the partially reflective mirror **802** is transmitted by the polarized mirror **804** to present image light to the eye of the wearer. The user can also see through the polarized mirror **804** and the partially reflective mirror **802** to see the surrounding environment. As a result, the user perceives a combined image comprised of the displayed image light overlaid onto the see-thru view of the environment.

While many of the embodiments of the present invention have been referred to as upper and lower modules containing certain optical components, it should be understood that the image light and dark light production and management functions described in connection with the upper module may be arranged to direct light in other directions (e.g. upward, sideward, etc.). In embodiments, it may be preferred to mount the upper module **202** above the wearer's eye, in which case the image light would be directed downward. In other embodiments it may be preferred to produce light from the side of the wearer's eye, or from below the wearer's eye. In addition, the lower optical module is generally configured to deliver the image light to the wearer's eye and allow the wearer to see through the lower optical module, which may be accomplished through a variety of optical components.

FIG. **8a** illustrates an embodiment of the present invention where the upper optical module **202** is arranged to direct image light into a TIR waveguide **810**. In this embodiment, the upper optical module **202** is positioned above the wearer's eye **812** and the light is directed horizontally into the TIR waveguide **810**. The TIR waveguide is designed to internally reflect the image light in a series of downward TIR reflections until it reaches the portion in front of the wearer's eye, where the light passes out of the TIR waveguide **812** into the wearer's eye. In this embodiment, an outer shield **814** is positioned in front of the TIR waveguide **810**.

FIG. **8b** illustrates an embodiment of the present invention where the upper optical module **202** is arranged to direct image light into a TIR waveguide **818**. In this embodiment, the upper optical module **202** is arranged on the side of the TIR waveguide **818**. For example, the upper optical module may be positioned in the arm or near the arm of the HWC when configured as a pair of head worn glasses. The TIR waveguide **818** is designed to internally reflect the image light in a series of TIR reflections until it reaches the portion in front of the wearer's eye, where the light passes out of the TIR waveguide **812** into the wearer's eye.

FIG. **8c** illustrates yet further embodiments of the present invention where an upper optical module **202** is directing polarized image light into an optical guide **828** where the image light passes through a polarized reflector **824**, changes polarization state upon reflection of the optical element **822** which includes a $\frac{1}{4}$ wave film for example and then is reflected by the polarized reflector **824** towards the wearer's eye, due to the change in polarization of the image

light. The upper optical module **202** may be positioned to direct light to a mirror **820**, to position the upper optical module **202** laterally, in other embodiments, the upper optical module **202** may direct the image light directly towards the polarized reflector **824**. It should be understood that the present invention comprises other optical arrangements intended to direct image light into the wearer's eye.

Another aspect of the present invention relates to eye imaging. In embodiments, a camera is used in connection with an upper optical module **202** such that the wearer's eye can be imaged using pixels in the "off" state on the DLP. FIG. **9** illustrates a system where the eye imaging camera **802** is mounted and angled such that the field of view of the eye imaging camera **802** is redirected toward the wearer's eye by the mirror pixels of the DLP **402** that are in the "off" state. In this way, the eye imaging camera **802** can be used to image the wearer's eye along the same optical axis as the displayed image that is presented to the wearer. Wherein, image light that is presented to the wearer's eye illuminates the wearer's eye so that the eye can be imaged by the eye imaging camera **802**. In the process, the light reflected by the eye passes back through the optical train of the lower optical module **204** and a portion of the upper optical module to where the light is reflected by the "off" pixels of the DLP **402** toward the eye imaging camera **802**.

In embodiments, the eye imaging camera may image the wearer's eye at a moment in time where there are enough "off" pixels to achieve the required eye image resolution. In another embodiment, the eye imaging camera collects eye image information from "off" pixels over time and forms a time lapsed image. In another embodiment, a modified image is presented to the user wherein enough "off" state pixels are included that the camera can obtain the desired resolution and brightness for imaging the wearer's eye and the eye image capture is synchronized with the presentation of the modified image.

The eye imaging system may be used for security systems. The HWC may not allow access to the HWC or other system if the eye is not recognized (e.g. through eye characteristics including retina or iris characteristics, etc.). The HWC may be used to provide constant security access in some embodiments. For example, the eye security confirmation may be a continuous, near-continuous, real-time, quasi real-time, periodic, etc. process so the wearer is effectively constantly being verified as known. In embodiments, the HWC may be worn and eye security tracked for access to other computer systems.

The eye imaging system may be used for control of the HWC. For example, a blink, wink, or particular eye movement may be used as a control mechanism for a software application operating on the HWC or associated device.

The eye imaging system may be used in a process that determines how or when the HWC **102** delivers digitally displayed content to the wearer. For example, the eye imaging system may determine that the user is looking in a direction and then HWC may change the resolution in an area of the display or provide some content that is associated with something in the environment that the user may be looking at. Alternatively, the eye imaging system may identify different user's and change the displayed content or enabled features provided to the user. User's may be identified from a database of users eye characteristics either located on the HWC **102** or remotely located on the network **110** or on a server **112**. In addition, the HWC may identify a primary user or a group of primary users from eye characteristics wherein the primary user(s) are provided with an enhanced set of features and all other user's are provided

with a different set of features. Thus in this use case, the HWC 102 uses identified eye characteristics to either enable features or not and eye characteristics need only be analyzed in comparison to a relatively small database of individual eye characteristics.

FIG. 10 illustrates a light source that may be used in association with the upper optics module 202 (e.g. polarized light source if the light from the solid state light source is polarized such as polarized light source 302 and 458), and light source 404. In embodiments, to provide a uniform surface of light 1008 to be directed into the upper optical module 202 and towards the DLP of the upper optical module, either directly or indirectly, the solid state light source 1002 may be projected into a backlighting optical system 1004. The solid state light source 1002 may be one or more LEDs, laser diodes, OLEDs. In embodiments, the backlighting optical system 1004 includes an extended section with a length/distance ratio of greater than 3, wherein the light undergoes multiple reflections from the sidewalls to mix of homogenize the light as supplied by the solid state light source 1002. The backlighting optical system 1004 can also include structures on the surface opposite (on the left side as shown in FIG. 10) to where the uniform light 1008 exits the backlight 1004 to change the direction of the light toward the DLP 302 and the reflective polarizer 310 or the DLP 402 and the TIR wedge 418. The backlighting optical system 1004 may also include structures to collimate the uniform light 1008 to provide light to the DLP with a smaller angular distribution or narrower cone angle. Diffusers or polarizers can be used on the entrance or exit surface of the backlighting optical system. Diffusers can be used to spread or uniformize the exiting light from the backlight to improve the uniformity or increase the angular spread of the uniform light 1008. Elliptical diffusers that diffuse the light more in some directions and less in others can be used to improve the uniformity or spread of the uniform light 1008 in directions orthogonal to the optical axis of the uniform light 1008. Linear polarizers can be used to convert unpolarized light as supplied by the solid state light source 1002 to polarized light so the uniform light 1008 is polarized with a desired polarization state. A reflective polarizer can be used on the exit surface of the backlight 1004 to polarize the uniform light 1008 to the desired polarization state, while reflecting the other polarization state back into the backlight where it is recycled by multiple reflections within the backlight 1004 and at the solid state light source 1002. Therefore by including a reflective polarizer at the exit surface of the backlight 1004, the efficiency of the polarized light source is improved.

FIGS. 10a and 10b show illustrations of structures in backlight optical systems 1004 that can be used to change the direction of the light provided to the entrance face 1045 by the light source and then collimates the light in a direction lateral to the optical axis of the exiting uniform light 1008. Structure 1060 includes an angled sawtooth pattern in a transparent waveguide wherein the left edge of each sawtooth clips the steep angle rays of light thereby limiting the angle of the light being redirected. The steep surface at the right (as shown) of each sawtooth then redirects the light so that it reflects off the left angled surface of each sawtooth and is directed toward the exit surface 1040. The sawtooth surfaces shown on the lower surface in FIGS. 10a and 10b, can be smooth and coated (e.g. with an aluminum coating or a dielectric mirror coating) to provide a high level of reflectivity without scattering. Structure 1050 includes a curved face on the left side (as shown) to focus the rays after they pass through the exit surface 1040, thereby providing a

mechanism for collimating the uniform light 1008. In a further embodiment, a diffuser can be provided between the solid state light source 1002 and the entrance face 1045 to homogenize the light provided by the solid state light source 1002. In yet a further embodiment, a polarizer can be used between the diffuser and the entrance face 1045 of the backlight 1004 to provide a polarized light source. Because the sawtooth pattern provides smooth reflective surfaces, the polarization state of the light can be preserved from the entrance face 1045 to the exit face 1040. In this embodiment, the light entering the backlight from the solid state light source 1002 passes through the polarizer so that it is polarized with the desired polarization state. If the polarizer is an absorptive linear polarizer, the light of the desired polarization state is transmitted while the light of the other polarization state is absorbed. If the polarizer is a reflective polarizer, the light of the desired polarization state is transmitted into the backlight 1004 while the light of the other polarization state is reflected back into the solid state light source 1002 where it can be recycled as previously described, to increase the efficiency of the polarized light source.

FIG. 11a illustrates a light source 1100 that may be used in association with the upper optics module 202. In embodiments, the light source 1100 may provide light to a backlighting optical system 1004 as described above in connection with FIG. 10. In embodiments, the light source 1100 includes a tristimulus notch filter 1102. The tristimulus notch filter 1102 has narrow band pass filters for three wavelengths, as indicated in FIG. 11c in a transmission graph 1108. The graph shown in FIG. 11b, as 1104 illustrates an output of three different colored LEDs. One can see that the bandwidths of emission are narrow, but they have long tails. The tristimulus notch filter 1102 can be used in connection with such LEDs to provide a light source 1100 that emits narrow filtered wavelengths of light as shown in FIG. 11d as the transmission graph 1110. Wherein the clipping effects of the tristimulus notch filter 1102 can be seen to have cut the tails from the LED emission graph 1104 to provide narrower wavelength bands of light to the upper optical module 202. The light source 1100 can be used in connection with a combiner 602 with a holographic mirror or tristimulus notch mirror to provide narrow bands of light that are reflected toward the wearer's eye with less waste light that does not get reflected by the combiner, thereby improving efficiency and reducing escaping light that can cause faceglow.

FIG. 12a illustrates another light source 1200 that may be used in association with the upper optics module 202. In embodiments, the light source 1200 may provide light to a backlighting optical system 1004 as described above in connection with FIG. 10. In embodiments, the light source 1200 includes a quantum dot cover glass 1202. Where the quantum dots absorb light of a shorter wavelength and emit light of a longer wavelength (FIG. 12b shows an example wherein a UV spectrum 1202 applied to a quantum dot results in the quantum dot emitting a narrow band shown as a PL spectrum 1204) that is dependent on the material makeup and size of the quantum dot. As a result, quantum dots in the quantum dot cover glass 1202 can be tailored to provide one or more bands of narrow bandwidth light (e.g. red, green and blue emissions dependent on the different quantum dots included as illustrated in the graph shown in FIG. 12c where three different quantum dots are used. In embodiments, the LED driver light emits UV light, deep blue or blue light. For sequential illumination of different colors, multiple light sources 1200 would be used where each light source 1200 would include a quantum dot cover

glass **1202** with a quantum dot selected to emit at one of the desired colors. The light source **1100** can be used in connection with a combiner **602** with a holographic mirror or tristimulus notch mirror to provide narrow transmission bands of light that are reflected toward the wearer's eye with less waste light that does not get reflected.

Another aspect of the present invention relates to the generation of peripheral image lighting effects for a person wearing a HWC. In embodiments, a solid state lighting system (e.g. LED, OLED, etc), or other lighting system, may be included inside the optical elements of an lower optical module **204**. The solid state lighting system may be arranged such that lighting effects outside of a field of view (FOV) of the presented digital content is presented to create an emersive effect for the person wearing the HWC. To this end, the lighting effects may be presented to any portion of the HWC that is visible to the wearer. The solid state lighting system may be digitally controlled by an integrated processor on the HWC. In embodiments, the integrated processor will control the lighting effects in coordination with digital content that is presented within the FOV of the HWC. For example, a movie, picture, game, or other content, may be displayed or playing within the FOV of the HWC. The content may show a bomb blast on the right side of the FOV and at the same moment, the solid state lighting system inside of the upper module optics may flash quickly in concert with the FOV image effect. The effect may not be fast, it may be more persistent to indicate, for example, a general glow or color on one side of the user. The solid state lighting system may be color controlled, with red, green and blue LEDs, for example, such that color control can be coordinated with the digitally presented content within the field of view.

FIG. **13a** illustrates optical components of a lower optical module **204** together with an outer lens **1302**. FIG. **13a** also shows an embodiment including effects LED's **1308a** and **1308b**. FIG. **13a** illustrates image light **1312**, as described herein elsewhere, directed into the upper optical module where it will reflect off of the combiner element **1304**, as described herein elsewhere. The combiner element **1304** in this embodiment is angled towards the wearer's eye at the top of the module and away from the wearer's eye at the bottom of the module, as also illustrated and described in connection with FIG. **8** (e.g. at a 45 degree angle). The image light **1312** provided by an upper optical module **202** (not shown in FIG. **13a**) reflects off of the combiner element **1304** towards the collimating mirror **1310**, away from the wearer's eye, as described herein elsewhere. The image light **1312** then reflects and focuses off of the collimating mirror **1304**, passes back through the combiner element **1304**, and is directed into the wearer's eye. The wearer can also view the surrounding environment through the transparency of the combiner element **1304**, collimating mirror **1310**, and outer lens **1302** (if it is included). As described herein elsewhere, various surfaces are polarized to create the optical path for the image light and to provide transparency of the elements such that the wearer can view the surrounding environment. The wearer will generally perceive that the image light forms an image in the FOV **1305**. In embodiments, the outer lens **1302** may be included. The outer lens **1302** is an outer lens that may or may not be corrective and it may be designed to conceal the lower optical module components in an effort to make the HWC appear to be in a form similar to standard glasses or sunglasses.

In the embodiment illustrated in FIG. **13a**, the effects LEDs **1308a** and **1308b** are positioned at the sides of the combiner element **1304** and the outer lens **1302** and/or the collimating mirror **1310**. In embodiments, the effects LEDs

1308a are positioned within the confines defined by the combiner element **1304** and the outer lens **1302** and/or the collimating mirror. The effects LEDs **1308a** and **1308b** are also positioned outside of the FOV **1305**. In this arrangement, the effects LEDs **1308a** and **1308b** can provide lighting effects within the lower optical module outside of the FOV **1305**. In embodiments the light emitted from the effects LEDs **1308a** and **1308b** may be polarized such that the light passes through the combiner element **1304** toward the wearer's eye and does not pass through the outer lens **1302** and/or the collimating mirror **1310**. This arrangement provides peripheral lighting effects to the wearer in a more private setting by not transmitting the lighting effects through the front of the HWC into the surrounding environment. However, in other embodiments, the effects LEDs **1308a** and **1308b** may be unpolarized so the lighting effects provided are made to be purposefully viewable by others in the environment for entertainment such as giving the effect of the wearer's eye glowing in correspondence to the image content being viewed by the wearer.

FIG. **13b** illustrates a cross section of the embodiment described in connection with FIG. **13a**. As illustrated, the effects LED **1308a** is located in the upper-front area inside of the optical components of the lower optical module. It should be understood that the effects LED **1308a** position in the described embodiments is only illustrative and alternate placements are encompassed by the present invention. Additionally, in embodiments, there may be one or more effects LEDs **1308a** in each of the two sides of HWC to provide peripheral lighting effects near one or both eyes of the wearer.

FIG. **13c** illustrates an embodiment where the combiner element **1304** is angled away from the eye at the top and towards the eye at the bottom (e.g. in accordance with the holographic or notch filter embodiments described herein). In this embodiment, the effects LED **1308a** is located on the outer lens **1302** side of the combiner element **1304** to provide a concealed appearance of the lighting effects. As with other embodiments, the effects LED **1308a** of FIG. **13c** may include a polarizer such that the emitted light can pass through a polarized element associated with the combiner element **1304** and be blocked by a polarized element associated with the outer lens **1302**.

Another aspect of the present invention relates to the mitigation of light escaping from the space between the wearer's face and the HWC itself. Another aspect of the present invention relates to maintaining a controlled lighting environment in proximity to the wearer's eyes. In embodiments, both the maintenance of the lighting environment and the mitigation of light escape are accomplished by including a removable and replaceable flexible shield for the HWC. Wherein the removable and replaceable shield can be provided for one eye or both eyes in correspondence to the use of the displays for each eye. For example, in a night vision application, the display to only one eye could be used for night vision while the display to the other eye is turned off to provide good see-thru when moving between areas where visible light is available and dark areas where night vision enhancement is needed.

FIG. **14a** illustrates a removable and replaceable flexible eye cover **1402** with an opening **1408** that can be attached and removed quickly from the HWC **102** through the use of magnets. Other attachment methods may be used, but for illustration of the present invention we will focus on a magnet implementation. In embodiments, magnets may be included in the eye cover **1402** and magnets of an opposite polarity may be included (e.g. embedded) in the frame of the

HWC **102**. The magnets of the two elements would attract quite strongly with the opposite polarity configuration. In another embodiment, one of the elements may have a magnet and the other side may have metal for the attraction. In embodiments, the eye cover **1402** is a flexible elastomeric shield. In embodiments, the eye cover **1402** may be an elastomeric bellows design to accommodate flexibility and more closely align with the wearer's face. FIG. **14b** illustrates a removable and replaceable flexible eye cover **1404** that is adapted as a single eye cover. In embodiments, a single eye cover may be used for each side of the HWC to cover both eyes of the wearer. In embodiments, the single eye cover may be used in connection with a HWC that includes only one computer display for one eye. These configurations prevent light that is generated and directed generally towards the wearer's face by covering the space between the wearer's face and the HWC. The opening **1408** allows the wearer to look through the opening **1408** to view the displayed content and the surrounding environment through the front of the HWC. The image light in the lower optical module **204** can be prevented from emitting from the front of the HWC through internal optics polarization schemes, as described herein, for example.

FIG. **14c** illustrates another embodiment of a light suppression system. In this embodiment, the eye cover **1410** may be similar to the eye cover **1402**, but eye cover **1410** includes a front light shield **1412**. The front light shield **1412** may be opaque to prevent light from escaping the front lens of the HWC. In other embodiments, the front light shield **1412** is polarized to prevent light from escaping the front lens. In a polarized arrangement, in embodiments, the internal optical elements of the HWC (e.g. of the lower optical module **204**) may polarize light transmitted towards the front of the HWC and the front light shield **1412** may be polarized to prevent the light from transmitting through the front light shield **1412**.

In embodiments, an opaque front light shield **1412** may be included and the digital content may include images of the surrounding environment such that the wearer can visualize the surrounding environment. One eye may be presented with night vision environmental imagery and this eye's surrounding environment optical path may be covered using an opaque front light shield **1412**. In other embodiments, this arrangement may be associated with both eyes.

Another aspect of the present invention relates to automatically configuring the lighting system(s) used in the HWC **102**. In embodiments, the display lighting and/or effects lighting, as described herein, may be controlled in a manner suitable for when an eye cover **1408** is attached or removed from the HWC **102**. For example, at night, when the light in the environment is low, the lighting system(s) in the HWC may go into a low light mode to further control any amounts of stray light escaping from the HWC and the areas around the HWC. Covert operations at night, while using night vision or standard vision, may require a solution which prevents as much escaping light as possible so a user may clip on the eye cover(s) **1408** and then the HWC may go into a low light mode. The low light mode may, in some embodiments, only go into a low light mode when the eye cover **1408** is attached if the HWC identifies that the environment is in low light conditions (e.g. through environment light level sensor detection). In embodiments, the low light level may be determined to be at an intermediate point between full and low light dependent on environmental conditions.

Another aspect of the present invention relates to automatically controlling the type of content displayed in the

HWC when eye covers **1408** are attached or removed from the HWC. In embodiments, when the eye cover(s) **1408** is attached to the HWC, the displayed content may be restricted in amount or in color amounts. For example, the display(s) may go into a simple content delivery mode to restrict the amount of information displayed. This may be done to reduce the amount of light produced by the display(s). In an embodiment, the display(s) may change from color displays to monochrome displays to reduce the amount of light produced. In an embodiment, the monochrome lighting may be red to limit the impact on the wearer's eyes to maintain an ability to see better in the dark.

Referring to FIG. **15**, we now turn to describe a particular external user interface **104**, referred to generally as a pen **1500**. The pen **1500** is a specially designed external user interface **104** and can operate as a user interface, such as to many different styles of HWC **102**. The pen **1500** generally follows the form of a conventional pen, which is a familiar user handled device and creates an intuitive physical interface for many of the operations to be carried out in the HWC system **100**. The pen **1500** may be one of several user interfaces **104** used in connection with controlling operations within the HWC system **100**. For example, the HWC **102** may watch for and interpret hand gestures **116** as control signals, where the pen **1500** may also be used as a user interface with the same HWC **102**. Similarly, a remote keyboard may be used as an external user interface **104** in concert with the pen **1500**. The combination of user interfaces or the use of just one control system generally depends on the operation(s) being executed in the HWC's system **100**.

While the pen **1500** may follow the general form of a conventional pen, it contains numerous technologies that enable it to function as an external user interface **104**. FIG. **15** illustrates technologies comprised in the pen **1500**. As can be seen, the pen **1500** may include a camera **1508**, which is arranged to view through lens **1502**. The camera may then be focused, such as through lens **1502**, to image a surface upon which a user is writing or making other movements to interact with the HWC **102**. There are situations where the pen **1500** will also have an ink, graphite, or other system such that what is being written can be seen on the writing surface. There are other situations where the pen **1500** does not have such a physical writing system so there is no deposit on the writing surface, where the pen would only be communicating data or commands to the HWC **102**. The lens configuration is described in greater detail herein. The function of the camera is to capture information from an unstructured writing surface such that pen strokes can be interpreted as intended by the user. To assist in the prediction of the intended stroke path, the pen **1500** may include a sensor, such as an IMU **1512**. Of course, the IMU could be included in the pen **1500** in its separate parts (e.g. gyro, accelerometer, etc.) or an IMU could be included as a single unit. In this instance, the IMU **1512** is used to measure and predict the motion of the pen **1500**. In turn, the integrated microprocessor **1510** would take the IMU information and camera information as inputs and process the information to form a prediction of the pen tip movement.

The pen **1500** may also include a pressure monitoring system **1504**, such as to measure the pressure exerted on the lens **1502**. As will be described in greater detail herein, the pressure measurement can be used to predict the user's intention for changing the weight of a line, type of a line, type of brush, click, double click, and the like. In embodiments, the pressure sensor may be constructed using any force or pressure measurement sensor located behind the

lens **1502**, including for example, a resistive sensor, a current sensor, a capacitive sensor, a voltage sensor such as a piezoelectric sensor, and the like.

The pen **1500** may also include a communications module **1518**, such as for bi-directional communication with the HWC **102**. In embodiments, the communications module **1518** may be a short distance communication module (e.g. Bluetooth). The communications module **1518** may be security matched to the HWC **102**. The communications module **1518** may be arranged to communicate data and commands to and from the microprocessor **1510** of the pen **1500**. The microprocessor **1510** may be programmed to interpret data generated from the camera **1508**, IMU **1512**, and pressure sensor **1504**, and the like, and then pass a command onto the HWC **102** through the communications module **1518**, for example. In another embodiment, the data collected from any of the input sources (e.g. camera **1508**, IMU **1512**, pressure sensor **1504**) by the microprocessor may be communicated by the communication module **1518** to the HWC **102**, and the HWC **102** may perform data processing and prediction of the user's intention when using the pen **1500**. In yet another embodiment, the data may be further passed on through a network **110** to a remote device **112**, such as a server, for the data processing and prediction. The commands may then be communicated back to the HWC **102** for execution (e.g. display writing in the glasses display, make a selection within the UI of the glasses display, control a remote external device **112**, control a local external device **108**), and the like. The pen may also include memory **1514** for long or short term uses.

The pen **1500** may also include a number of physical user interfaces, such as quick launch buttons **1522**, a touch sensor **1520**, and the like. The quick launch buttons **1522** may be adapted to provide the user with a fast way of jumping to a software application in the HWC system **100**. For example, the user may be a frequent user of communication software packages (e.g. email, text, Twitter, Instagram, Facebook, Google+, and the like), and the user may program a quick launch button **1522** to command the HWC **102** to launch an application. The pen **1500** may be provided with several quick launch buttons **1522**, which may be user programmable or factory programmable. The quick launch button **1522** may be programmed to perform an operation. For example, one of the buttons may be programmed to clear the digital display of the HWC **102**. This would create a fast way for the user to clear the screens on the HWC **102** for any reason, such as for example to better view the environment. The quick launch button functionality will be discussed in further detail below. The touch sensor **1520** may be used to take gesture style input from the user. For example, the user may be able to take a single finger and run it across the touch sensor **1520** to affect a page scroll.

The pen **1500** may also include a laser pointer **1524**. The laser pointer **1524** may be coordinated with the IMU **1512** to coordinate gestures and laser pointing. For example, a user may use the laser **1524** in a presentation to help with guiding the audience with the interpretation of graphics and the IMU **1512** may, either simultaneously or when the laser **1524** is off, interpret the user's gestures as commands or data input.

FIGS. **16A-C** illustrate several embodiments of lens and camera arrangements **1600** for the pen **1500**. One aspect relates to maintaining a constant distance between the camera and the writing surface to enable the writing surface to be kept in focus for better tracking of movements of the pen **1500** over the writing surface. Another aspect relates to maintaining an angled surface following the circumference

of the writing tip of the pen **1500** such that the pen **1500** can be rolled or partially rolled in the user's hand to create the feel and freedom of a conventional writing instrument.

FIG. **16A** illustrates an embodiment of the writing lens end of the pen **1500**. The configuration includes a ball lens **1604**, a camera or image capture surface **1602**, and a domed cover lens **1608**. In this arrangement, the camera views the writing surface through the ball lens **1604** and dome cover lens **1608**. The ball lens **1604** causes the camera to focus such that the camera views the writing surface when the pen **1500** is held in the hand in a natural writing position, such as with the pen **1500** in contact with a writing surface. In embodiments, the ball lens **1604** should be separated from the writing surface to obtain the highest resolution of the writing surface at the camera **1602**. In embodiments, the ball lens **1604** is separated by approximately 1 to 3 mm. In this configuration, the domed cover lens **1608** provides a surface that can keep the ball lens **1604** separated from the writing surface at a constant distance, such as substantially independent of the angle used to write on the writing surface. For instance, in embodiments the field of view of the camera in this arrangement would be approximately 60 degrees.

The domed cover lens, or other lens **1608** used to physically interact with the writing surface, will be transparent or transmissive within the active bandwidth of the camera **1602**. In embodiments, the domed cover lens **1608** may be spherical or other shape and comprised of glass, plastic, sapphire, diamond, and the like. In other embodiments where low resolution imaging of the surface is acceptable. The pen **1500** can omit the domed cover lens **1608** and the ball lens **1604** can be in direct contact with the surface.

FIG. **16B** illustrates another structure where the construction is somewhat similar to that described in connection with FIG. **16A**; however this embodiment does not use a dome cover lens **1608**, but instead uses a spacer **1610** to maintain a predictable distance between the ball lens **1604** and the writing surface, wherein the spacer may be spherical, cylindrical, tubular or other shape that provides spacing while allowing for an image to be obtained by the camera **1602** through the lens **1604**. In a preferred embodiment, the spacer **1610** is transparent. In addition, while the spacer **1610** is shown as spherical, other shapes such as an oval, doughnut shape, half sphere, cone, cylinder or other form may be used.

FIG. **16C** illustrates yet another embodiment, where the structure includes a post **1614**, such as running through the center of the lensed end of the pen **1500**. The post **1614** may be an ink deposition system (e.g. ink cartridge), graphite deposition system (e.g. graphite holder), or a dummy post whose purpose is mainly only that of alignment. The selection of the post type is dependent on the pen's use. For instance, in the event the user wants to use the pen **1500** as a conventional ink depositing pen as well as a fully functional external user interface **104**, the ink system post would be the best selection. If there is no need for the 'writing' to be visible on the writing surface, the selection would be the dummy post. The embodiment of FIG. **16C** includes camera(s) **1602** and an associated lens **1612**, where the camera **1602** and lens **1612** are positioned to capture the writing surface without substantial interference from the post **1614**. In embodiments, the pen **1500** may include multiple cameras **1602** and lenses **1612** such that more or all of the circumference of the tip **1614** can be used as an input system. In an embodiment, the pen **1500** includes a contoured grip that keeps the pen aligned in the user's hand so that the camera **1602** and lens **1612** remains pointed at the surface.

Another aspect of the pen **1500** relates to sensing the force applied by the user to the writing surface with the pen **1500**. The force measurement may be used in a number of ways. For example, the force measurement may be used as a discrete value, or discontinuous event tracking, and compared against a threshold in a process to determine a user's intent. The user may want the force interpreted as a 'click' in the selection of an object, for instance. The user may intend multiple force exertions interpreted as multiple clicks. There may be times when the user holds the pen **1500** in a certain position or holds a certain portion of the pen **1500** (e.g. a button or touch pad) while clicking to affect a certain operation (e.g. a 'right click'). In embodiments, the force measurement may be used to track force and force trends. The force trends may be tracked and compared to threshold limits, for example. There may be one such threshold limit, multiple limits, groups of related limits, and the like. For example, when the force measurement indicates a fairly constant force that generally falls within a range of related threshold values, the microprocessor **1510** may interpret the force trend as an indication that the user desires to maintain the current writing style, writing tip type, line weight, brush type, and the like. In the event that the force trend appears to have gone outside of a set of threshold values intentionally, the microprocessor may interpret the action as an indication that the user wants to change the current writing style, writing tip type, line weight, brush type, and the like. Once the microprocessor has made a determination of the user's intent, a change in the current writing style, writing tip type, line weight, brush type, and the like may be executed. In embodiments, the change may be noted to the user (e.g. in a display of the HWC **102**), and the user may be presented with an opportunity to accept the change.

FIG. **17A** illustrates an embodiment of a force sensing surface tip **1700** of a pen **1500**. The force sensing surface tip **1700** comprises a surface connection tip **1702** (e.g. a lens as described herein elsewhere) in connection with a force or pressure monitoring system **1504**. As a user uses the pen **1500** to write on a surface or simulate writing on a surface the force monitoring system **1504** measures the force or pressure the user applies to the writing surface and the force monitoring system communicates data to the microprocessor **1510** for processing. In this configuration, the microprocessor **1510** receives force data from the force monitoring system **1504** and processes the data to make predictions of the user's intent in applying the particular force that is currently being applied. In embodiments, the processing may be provided at a location other than on the pen (e.g. at a server in the HWC system **100**, on the HWC **102**). For clarity, when reference is made herein to processing information on the microprocessor **1510**, the processing of information contemplates processing the information at a location other than on the pen. The microprocessor **1510** may be programmed with force threshold(s), force signature(s), force signature library and/or other characteristics intended to guide an inference program in determining the user's intentions based on the measured force or pressure. The microprocessor **1510** may be further programmed to make inferences from the force measurements as to whether the user has attempted to initiate a discrete action (e.g. a user interface selection 'click') or is performing a constant action (e.g. writing within a particular writing style). The inferring process is important as it causes the pen **1500** to act as an intuitive external user interface **104**.

FIG. **17B** illustrates a force **1708** versus time **1710** trend chart with a single threshold **1718**. The threshold **1718** may

be set at a level that indicates a discrete force exertion indicative of a user's desire to cause an action (e.g. select an object in a GUI). Event **1712**, for example, may be interpreted as a click or selection command because the force quickly increased from below the threshold **1718** to above the threshold **1718**. The event **1714** may be interpreted as a double click because the force quickly increased above the threshold **1718**, decreased below the threshold **1718** and then essentially repeated quickly. The user may also cause the force to go above the threshold **1718** and hold for a period indicating that the user is intending to select an object in the GUI (e.g. a GUI presented in the display of the HWC **102**) and 'hold' for a further operation (e.g. moving the object).

While a threshold value may be used to assist in the interpretation of the user's intention, a signature force event trend may also be used. The threshold and signature may be used in combination or either method may be used alone. For example, a single-click signature may be represented by a certain force trend signature or set of signatures. The single-click signature(s) may require that the trend meet a criteria of a rise time between x any y values, a hold time of between a and b values and a fall time of between c and d values, for example. Signatures may be stored for a variety of functions such as click, double click, right click, hold, move, etc. The microprocessor **1510** may compare the real-time force or pressure tracking against the signatures from a signature library to make a decision and issue a command to the software application executing in the GUI.

FIG. **17C** illustrates a force **1708** versus time **1710** trend chart with multiple thresholds **1718**. By way of example, the force trend is plotted on the chart with several pen force or pressure events. As noted, there are both presumably intentional events **1720** and presumably non-intentional events **1722**. The two thresholds **1718** of FIG. **4C** create three zones of force: a lower, middle and higher range. The beginning of the trend indicates that the user is placing a lower zone amount of force. This may mean that the user is writing with a given line weight and does not intend to change the weight, the user is writing. Then the trend shows a significant increase **1720** in force into the middle force range. This force change appears, from the trend to have been sudden and thereafter it is sustained. The microprocessor **1510** may interpret this as an intentional change and as a result change the operation in accordance with preset rules (e.g. change line width, increase line weight, etc.). The trend then continues with a second apparently intentional event **1720** into the higher-force range. During the performance in the higher-force range, the force dips below the upper threshold **1718**. This may indicate an unintentional force change and the microprocessor may detect the change in range however not affect a change in the operations being coordinated by the pen **1500**. As indicated above, the trend analysis may be done with thresholds and/or signatures.

Generally, in the present disclosure, instrument stroke parameter changes may be referred to as a change in line type, line weight, tip type, brush type, brush width, brush pressure, color, and other forms of writing, coloring, painting, and the like.

Another aspect of the pen **1500** relates to selecting an operating mode for the pen **1500** dependent on contextual information and/or selection interface(s). The pen **1500** may have several operating modes. For instance, the pen **1500** may have a writing mode where the user interface(s) of the pen **1500** (e.g. the writing surface end, quick launch buttons **1522**, touch sensor **1520**, motion based gesture, and the like) is optimized or selected for tasks associated with writing. As

another example, the pen **1500** may have a wand mode where the user interface(s) of the pen is optimized or selected for tasks associated with software or device control (e.g. the HWC **102**, external local device, remote device **112**, and the like). The pen **1500**, by way of another example, may have a presentation mode where the user interface(s) is optimized or selected to assist a user with giving a presentation (e.g. pointing with the laser pointer **1524** while using the button(s) **1522** and/or gestures to control the presentation or applications relating to the presentation). The pen may, for example, have a mode that is optimized or selected for a particular device that a user is attempting to control. The pen **1500** may have a number of other modes and an aspect of the present invention relates to selecting such modes.

FIG. **18A** illustrates an automatic user interface(s) mode selection based on contextual information. The microprocessor **1510** may be programmed with IMU thresholds **1814** and **1812**. The thresholds **1814** and **1812** may be used as indications of upper and lower bounds of an angle **1804** and **1802** of the pen **1500** for certain expected positions during certain predicted modes. When the microprocessor **1510** determines that the pen **1500** is being held or otherwise positioned within angles **1802** corresponding to writing thresholds **1814**, for example, the microprocessor **1510** may then institute a writing mode for the pen's user interfaces. Similarly, if the microprocessor **1510** determines (e.g. through the IMU **1512**) that the pen is being held at an angle **1804** that falls between the predetermined wand thresholds **1812**, the microprocessor may institute a wand mode for the pen's user interface. Both of these examples may be referred to as context based user interface mode selection as the mode selection is based on contextual information (e.g. position) collected automatically and then used through an automatic evaluation process to automatically select the pen's user interface(s) mode.

As with other examples presented herein, the microprocessor **1510** may monitor the contextual trend (e.g. the angle of the pen over time) in an effort to decide whether to stay in a mode or change modes. For example, through signatures, thresholds, trend analysis, and the like, the microprocessor may determine that a change is an unintentional change and therefore no user interface mode change is desired.

FIG. **18B** illustrates an automatic user interface(s) mode selection based on contextual information. In this example, the pen **1500** is monitoring (e.g. through its microprocessor) whether or not the camera at the writing surface end **1508** is imaging a writing surface in close proximity to the writing surface end of the pen **1500**. If the pen **1500** determines that a writing surface is within a predetermined relatively short distance, the pen **1500** may decide that a writing surface is present **1820** and the pen may go into a writing mode user interface(s) mode. In the event that the pen **1500** does not detect a relatively close writing surface **1822**, the pen may predict that the pen is not currently being used to as a writing instrument and the pen may go into a non-writing user interface(s) mode.

FIG. **18C** illustrates a manual user interface(s) mode selection. The user interface(s) mode may be selected based on a twist of a section **1824** of the pen **1500** housing, clicking an end button **1828**, pressing a quick launch button **1522**, interacting with touch sensor **1520**, detecting a predetermined action at the pressure monitoring system (e.g. a click), detecting a gesture (e.g. detected by the IMU), etc. The manual mode selection may involve selecting an item in a GUI associated with the pen **1500** (e.g. an image presented in the display of HWC **102**).

In embodiments, a confirmation selection may be presented to the user in the event a mode is going to change. The presentation may be physical (e.g. a vibration in the pen **1500**), through a GUI, through a light indicator, etc.

FIG. **19** illustrates a couple pen use-scenarios **1900** and **1901**. There are many use scenarios and we have presented a couple in connection with FIG. **19** as a way of illustrating use scenarios to further the understanding of the reader. As such, the use-scenarios should be considered illustrative and non-limiting.

Use scenario **1900** is a writing scenario where the pen **1500** is used as a writing instrument. In this example, quick launch button **122A** is pressed to launch a note application **1910** in the GUI **1908** of the HWC **102** display **1904**. Once the quick launch button **122A** is pressed, the HWC **102** launches the note program **1910** and puts the pen into a writing mode. The user uses the pen **1500** to scribe symbols **1902** on a writing surface, the pen records the scribing and transmits the scribing to the HWC **102** where symbols representing the scribing are displayed **1912** within the note application **1910**.

Use scenario **1901** is a gesture scenario where the pen **1500** is used as a gesture capture and command device. In this example, the quick launch button **122B** is activated and the pen **1500** activates a wand mode such that an application launched on the HWC **102** can be controlled. Here, the user sees an application chooser **1918** in the display(s) of the HWC **102** where different software applications can be chosen by the user. The user gestures (e.g. swipes, spins, turns, etc.) with the pen to cause the application chooser **1918** to move from application to application. Once the correct application is identified (e.g. highlighted) in the chooser **1918**, the user may gesture or click or otherwise interact with the pen **1500** such that the identified application is selected and launched. Once an application is launched, the wand mode may be used to scroll, rotate, change applications, select items, initiate processes, and the like, for example.

In an embodiment, the quick launch button **122A** may be activated and the HWC **102** may launch an application chooser presenting to the user a set of applications. For example, the quick launch button may launch a chooser to show all communication programs (e.g. SMS, Twitter, Instagram, Facebook, email, etc.) available for selection such that the user can select the program the user wants and then go into a writing mode. By way of further example, the launcher may bring up selections for various other groups that are related or categorized as generally being selected at a given time (e.g. Microsoft Office products, communication products, productivity products, note products, organizational products, and the like)

FIG. **20** illustrates yet another embodiment of the present invention. FIG. **2000** illustrates a watchband clip on controller **2000**. The watchband clip on controller may be a controller used to control the HWC **102** or devices in the HWC system **100**. The watchband clip on controller **2000** has a fastener **2018** (e.g. rotatable clip) that is mechanically adapted to attach to a watchband, as illustrated at **2004**.

The watchband controller **2000** may have quick launch interfaces **2008** (e.g. to launch applications and choosers as described herein), a touch pad **2014** (e.g. to be used as a touch style mouse for GUI control in a HWC **102** display) and a display **2012**. The clip **2018** may be adapted to fit a wide range of watchbands so it can be used in connection with a watch that is independently selected for its function. The clip, in embodiments, is rotatable such that a user can position it in a desirable manner. In embodiments the clip

may be a flexible strap. In embodiments, the flexible strap may be adapted to be stretched to attach to a hand, wrist, finger, device, weapon, and the like.

In embodiments, the watchband controller may be configured as a removable and replacable watchband. For example, the controller may be incorporated into a band with a certain width, segment spacing's, etc. such that the watchband, with its incorporated controller, can be attached to a watch body. The attachment, in embodiments, may be mechanically adapted to attach with a pin upon which the watchband rotates. In embodiments, the watchband controller may be electrically connected to the watch and/or watch body such that the watch, watch body and/or the watchband controller can communicate data between them.

The watchband controller may have 3-axis motion monitoring (e.g. through an IMU, accelerometers, magnetometers, gyroscopes, etc.) to capture user motion. The user motion may then be interpreted for gesture control.

In embodiments, the watchband controller may comprise fitness sensors and a fitness computer. The sensors may track heart rate, calories burned, strides, distance covered, and the like. The data may then be compared against performance goals and/or standards for user feedback.

Another aspect of the present invention relates to visual display techniques relating to micro Doppler ("mD") target tracking signatures ("mD signatures"). mD is a radar technique that uses a series of angle dependent electromagnetic pulses that are broadcast into an environment and return pulses are captured. Changes between the broadcast pulse and return pulse are indicative of changes in the shape, distance and angular location of objects or targets in the environment. These changes provide signals that can be used to track a target and identify the target through the mD signature. Each target or target type has a unique mD signature. Shifts in the radar pattern can be analyzed in the time domain and frequency domain based on mD techniques to derive information about the types of targets present (e.g. whether people are present), the motion of the targets and the relative angular location of the targets and the distance to the targets. By selecting a frequency used for the mD pulse relative to known objects in the environment, the pulse can penetrate the known objects to enable information about targets to be gathered even when the targets are visually blocked by the known objects. For example, pulse frequencies can be used that will penetrate concrete buildings to enable people to be identified inside the building. Multiple pulse frequencies can be used as well in the mD radar to enable different types of information to be gathered about the objects in the environment. In addition, the mD radar information can be combined with other information such as distance measurements or images captured of the environment that are analyzed jointly to provide improved object identification and improved target identification and tracking. In embodiments, the analysis can be performed on the HWC or the information can be transmitted to a remote network for analysis and results transmitted back to the HWC. Distance measurements can be provided by laser range finding, structured lighting, stereoscopic depth maps or sonar measurements. Images of the environment can be captured using one or more cameras capable of capturing images from visible, ultraviolet or infrared light. The mD radar can be attached to the HWC, located adjacently (e.g. in a vehicle) and associated wirelessly with the HWC or located remotely. Maps or other previously determined information about the environment can also be used in the

analysis of the mD radar information. Embodiments of the present invention relate to visualizing the mD signatures in useful ways.

FIG. 21 illustrates a FOV 2102 of a HWC 102 from a wearer's perspective. The wearer, as described herein elsewhere, has a see-through FOV 2102 wherein the wearer views adjacent surroundings, such as the buildings illustrated in FIG. 21. The wearer, as described herein elsewhere, can also see displayed digital content presented within a portion of the FOV 2102. The embodiment illustrated in FIG. 21 is indicating that the wearer can see the buildings and other surrounding elements in the environment and digital content representing traces, or travel paths, of bullets being fired by different people in the area. The surroundings are viewed through the transparency of the FOV 2102. The traces are presented via the digital computer display, as described herein elsewhere. In embodiments, the trace presented is based on a mD signature that is collected and communicated to the HWC in real time. The mD radar itself may be on or near the wearer of the HWC 102 or it may be located remote from the wearer. In embodiments, the mD radar scans the area, tracks and identifies targets, such as bullets, and communicates traces, based on locations, to the HWC 102.

There are several traces 2108 and 2104 presented to the wearer in the embodiment illustrated in FIG. 21. The traces communicated from the mD radar may be associated with GPS locations and the GPS locations may be associated with objects in the environment, such as people, buildings, vehicles, etc, both in latitude and longitude perspective and an elevation perspective. The locations may be used as markers for the HWC such that the traces, as presented in the FOV, can be associated, or fixed in space relative to the markers. For example, if the friendly fire trace 2108 is determined, by the mD radar, to have originated from the upper right window of the building on the left, as illustrated in FIG. 21, then a virtual marker may be set on or near the window. When the HWC views, through its camera or other sensor, for example, the building's window, the trace may then virtually anchor with the virtual marker on the window. Similarly, a marker may be set near the termination position or other flight position of the friendly fire trace 2108, such as the upper left window of the center building on the right, as illustrated in FIG. 21. This technique fixes in space the trace such that the trace appears fixed to the environmental positions independent of where the wearer is looking. So, for example, as the wearer's head turns, the trace appears fixed to the marked locations.

In embodiments, certain user positions may be known and thus identified in the FOV. For example, the shooter of the friendly fire trace 2108 may be from a known friendly combatant and as such his location may be known. The position may be known based on his GPS location based on a mobile communication system on him, such as another HWC 102. In other embodiments, the friendly combatant may be marked by another friendly. For example, if the friendly position in the environment is known through visual contact or communicated information, a wearer of the HWC 102 may use a gesture or external user interface 104 to mark the location. If a friendly combatant location is known the originating position of the friendly fire trace 2108 may be color coded or otherwise distinguished from unidentified traces on the displayed digital content. Similarly, enemy fire traces 2104 may be color coded or otherwise distinguished on the displayed digital content. In embodiments, there may be an additional distinguished appearance on the displayed digital content for unknown traces.

In addition to situationally associated trace appearance, the trace colors or appearance may be different from the originating position to the terminating position. This path appearance change may be based on the mD signature. The mD signature may indicate that the bullet, for example, is slowing as it propagates and this slowing pattern may be reflected in the FOV **2102** as a color or pattern change. This can create an intuitive understanding of where the shooter is located. For example, the originating color may be red, indicative of high speed, and it may change over the course of the trace to yellow, indicative of a slowing trace. This pattern changing may also be different for a friendly, enemy and unknown combatant. The enemy may go blue to green for a friendly trace, for example.

FIG. **21** illustrates an embodiment where the user sees the environment through the FOV and may also see color coded traces, which are dependent on bullet speed and combatant type, where the traces are fixed in environmental positions independent on the wearer's perspective. Other information, such as distance, range, range rings, time of day, date, engagement type (e.g. hold, stop firing, back away, etc.) may also be displayed in the FOV.

Another aspect of the present invention relates to mD radar techniques that trace and identify targets through other objects, such as walls (referred to generally as through wall mD), and visualization techniques related therewith. FIG. **22** illustrates a through wall mD visualization technique according to the principles of the present invention. As described herein elsewhere, the mD radar scanning the environment may be local or remote from the wearer of a HWC **102**. The mD radar may identify a target (e.g. a person) that is visible **2204** and then track the target as he goes behind a wall **2208**. The tracking may then be presented to the wearer of a HWC **102** such that digital content reflective of the target and the target's movement, even behind the wall, is presented in the FOV **2202** of the HWC **102**. In embodiments, the target, when out of visible sight, may be represented by an avatar in the FOV to provide the wearer with imagery representing the target.

mD target recognition methods can identify the identity of a target based on the vibrations and other small movements of the target. This can provide a personal signature for the target. In the case of humans, this may result in a personal identification of a target that has been previously characterized. The cardio, heart beat, lung expansion and other small movements within the body may be unique to a person and if those attributes are pre-identified they may be matched in real time to provide a personal identification of a person in the FOV **2202**. The person's mD signatures may be determined based on the position of the person. For example, the database of personal mD signature attributes may include mD signatures for a person standing, sitting, laying down, running, walking, jumping, etc. This may improve the accuracy of the personal data match when a target is tracked through mD signature techniques in the field. In the event a person is personally identified, a specific indication of the person's identity may be presented in the FOV **2202**. The indication may be a color, shape, shade, name, indication of the type of person (e.g. enemy, friendly, etc.), etc. to provide the wearer with intuitive real time information about the person being tracked. This may be very useful in a situation where there is more than one person in an area of the person being tracked. If just one person in the area is personally identified, that person or the avatar of that person can be presented differently than other people in the area.

FIG. **23** illustrates an mD scanned environment **2300**. An mD radar may scan an environment in an attempt to identify

objects in the environment. In this embodiment, the mD scanned environment reveals two vehicles **2302a** and **2302b**, an enemy combatant **2309**, two friendly combatants **2308a** and **2308b** and a shot trace **2318**. Each of these objects may be personally identified or type identified. For example, the vehicles **2302a** and **2302b** may be identified through the mD signatures as a tank and heavy truck. The enemy combatant **2309** may be identified as a type (e.g. enemy combatant) or more personally (e.g. by name). The friendly combatants may be identified as a type (e.g. friendly combatant) or more personally (e.g. by name). The shot trace **2318** may be characterized by type of projectile or weapon type for the projectile, for example.

FIG. **23a** illustrates two separate HWC **102** FOV display techniques according to the principles of the present invention. FOV **2312** illustrates a map view **2310** where the mD scanned environment is presented. Here, the wearer has a perspective on the mapped area so he can understand all tracked targets in the area. This allows the wearer to traverse the area with knowledge of the targets. FOV **2312** illustrates a heads-up view to provide the wearer with an augmented reality style view of the environment that is in proximity of the wearer.

An aspect of the present invention relates to suppression of extraneous or stray light. As discussed herein elsewhere, eyeglow and faceglow are two such artifacts that develop from such light. Eyeglow and faceglow can be caused by image light escaping from the optics module. The escaping light is then visible, particularly in dark environments when the user is viewing bright displayed images with the HWC. Light that escapes through the front of the HWC is visible as eyeglow as it that light that is visible in the region of the user's eyes. Eyeglow can appear in the form of a small version of the displayed image that the user is viewing. Light that escapes from the bottom of the HWC shines onto the user's face, cheek or chest so that these portions of the user appear to glow. Eyeglow and faceglow can both increase the visibility of the user and highlight the use of the HWC, which may be viewed negatively by the user. As such, reducing eyeglow and faceglow is advantageous. In combat situations (e.g. the mD trace presentation scenarios described herein) and certain gaming situations, the suppression of extraneous or stray light is very important.

The disclosure relating to FIG. **6** shows an example where a portion of the image light passes through the combiner **602** such that the light shines onto the user's face, thereby illuminating a portion of the user's face in what is generally referred to herein as faceglow. Faceglow be caused by any portion of light from the HWC that illuminates the user's face.

An example of the source for the faceglow light can come from wide cone angle light associated with the image light incident onto the combiner **602**. Where the combiner can include a holographic mirror or a notch mirror in which the narrow bands of high reflectivity are matched to wavelengths of light by the light source. The wide cone angle associated with the image light corresponds with the field of view provided by the HWC. Typically the reflectivity of holographic mirrors and notch mirrors is reduced as the cone angle of the incident light is increased above 8 degrees. As a result, for a field of view of 30 degrees, substantial image light can pass through the combiner and cause faceglow.

FIG. **24** shows an illustration of a light trap **2410** for the faceglow light. In this embodiment, an extension of the outer shield lens of the HWC is coated with a light absorbing material in the region where the converging light responsible for faceglow is absorbed in a light trap **2410**. The light

absorbing material can be black or it can be a filter designed to absorb only the specific wavelengths of light provided by the light source(s) in the HWC. In addition, the surface of the light trap **2410** may be textured or fibrous to further improve the absorption.

FIG. **25** illustrates an optical system for a HWC that includes an outer absorptive polarizer **2520** to block the faceglow light. In this embodiment, the image light is polarized and as a result the light responsible for faceglow is similarly polarized. The absorptive polarizer is oriented with a transmission axis such that the faceglow light is absorbed and not transmitted. In this case, the rest of the imaging system in the HWC may not require polarized image light and the image light may be polarized at any point before the combiner. In embodiments, the transmission axis of the absorptive polarizer **2520** is oriented vertically so that external glare from water (S polarized light) is absorbed and correspondingly, the polarization of the image light is selected to be horizontal (S polarization). Consequently, image light that passes through the combiner **602** and is then incident onto the absorptive polarizer **2520**, is absorbed. In FIG. **25** the absorptive polarizer **2520** is shown outside the shield lens, alternatively the absorptive polarizer **2520** can be located inside the shield lens.

FIG. **26** illustrates an optical system for a HWC that includes a film with an absorptive notch filter **2620**. In this case, the absorptive notch filter absorbs narrow bands of light that are selected to match the light provided by the optical system's light source. As a result, the absorptive notch filter is opaque with respect to the faceglow light and is transparent to the remainder of the wavelengths included in the visible spectrum so that the user has a clear view of the surrounding environment. A triple notch filter suitable for this approach is available from Iridian Spectral Technologies, Ottawa, ON: <http://www.ilphotonics.com/cdv2/Iridian-Interference%20Filters/New%20filters/Triple%20Notch%20Filter.pdf>

In embodiments, the combiner **602** may include a notch mirror coating to reflect the wavelengths of light in the image light and a notch filter **2620** can be selected in correspondence to the wavelengths of light provided by the light source and the narrow bands of high reflectivity provided by the notch mirror. In this way, image light that is not reflected by the notch mirror is absorbed by the notch filter **2620**. In embodiments of the invention the light source can provide one narrow band of light for a monochrome imaging or three narrow bands of light for full color imaging. The notch mirror and associated notch filter would then each provide one narrow band or three narrow bands of high reflectivity and absorption respectively.

FIG. **27** includes a microlouver film **2750** to block the faceglow light. Microlouver film is sold by 3M as ALCF-P, for example and is typically used as a privacy filter for computer. See http://multimedia.3m.com/mws/mediawebserver?mwsid=SSSSSuH8gc7nZxtUoY_xIY_eevUqe17zHvTSevTSeSSSSSS--&fn=ALCF-P_ABR2_Control_Film_DS.pdf The microlouver film transmits light within a somewhat narrow angle (e.g. 30 degrees of normal and absorbs light beyond 30 degrees of normal). In FIG. **27**, the microlouver film **2750** is positioned such that the faceglow light **2758** is incident beyond 30 degrees from normal while the see-through light **2755** is incident within 30 degrees of normal to the microlouver film **2750**. As such, the faceglow light **2758** is absorbed by the microlouver film and the see-through light **2755** is transmitted so that the user has a bright see-thru view of the surrounding environment.

We now turn back to a description of eye imaging technologies. Aspects of the present invention relate to various methods of imaging the eye of a person wearing the HWC **102**. In embodiments, technologies for imaging the eye using an optical path involving the "off" state and "no power" state, which is described in detail below, are described. In embodiments, technologies for imaging the eye with optical configurations that do not involve reflecting the eye image off of DLP mirrors is described. In embodiments, unstructured light, structured light, or controlled lighting conditions, are used to predict the eye's position based on the light reflected off of the front of the wearer's eye. In embodiments, a reflection of a presented digital content image is captured as it reflects off of the wearer's eye and the reflected image may be processed to determine the quality (e.g. sharpness) of the image presented. In embodiments, the image may then be adjusted (e.g. focused differently) to increase the quality of the image presented based on the image reflection.

FIGS. **28a**, **28b** and **28c** show illustrations of the various positions of the DLP mirrors. FIG. **28a** shows the DLP mirrors in the "on" state **2815**. With the mirror in the "on" state **2815**, illumination light **2810** is reflected along an optical axis **2820** that extends into the lower optical module **204**. FIG. **28b** shows the DLP mirrors in the "off" state **2825**. With the mirror in the "off" state **2825**, illumination light **2810** is reflected along an optical axis **2830** that is substantially to the side of optical axis **2820** so that the "off" state light is directed toward a dark light trap as has been described herein elsewhere. FIG. **28c** shows the DLP mirrors in a third position, which occurs when no power is applied to the DLP. This "no power" state differs from the "on" and "off" states in that the mirror edges are not in contact with the substrate and as such are less accurately positioned. FIG. **28c** shows all of the DLP mirrors in the "no power" state **2835**. The "no power" state is achieved by simultaneously setting the voltage to zero for the "on" contact and "off" contact for a DLP mirror, as a result, the mirror returns to a no stress position where the DLP mirror is in the plane of the DLP platform as shown in FIG. **28c**. Although not normally done, it is also possible to apply the "no power" state to individual DLP mirrors. When the DLP mirrors are in the "no power" state they do not contribute image content. Instead, as shown in FIG. **28c**, when the DLP mirrors are in the "no power" state, the illumination light **2810** is reflected along an optical axis **2840** that is between the optical axes **2820** and **2830** that are respectively associated with the "on" and "off" states and as such this light doesn't contribute to the displayed image as a bright or dark pixel. This light can however contribute scattered light into the lower optical module **204** and as a result the displayed image contrast can be reduced or artifacts can be created in the image that detract from the image content. Consequently, it is generally desirable, in embodiments, to limit the time associated with the "no power" state to times when images are not displayed or to reduce the time associated with having DLP mirrors in the "no power" state so that the affect of the scattered light is reduced.

FIG. **29** shows an embodiment of the invention that can be used for displaying digital content images to a wearer of the HWC **102** and capturing images of the wearer's eye. In this embodiment, light from the eye **2971** passes back through the optics in the lower module **204**, the solid corrective wedge **2966**, at least a portion of the light passes through the partially reflective layer **2960**, the solid illumination wedge **2964** and is reflected by a plurality of DLP mirrors on the DLP **2955** that are in the "no power" state.

The reflected light then passes back through the illumination wedge 2964 and at least a portion of the light is reflected by the partially reflective layer 2960 and the light is captured by the camera 2980.

For comparison, illuminating light rays 2973 from the light source 2958 are also shown being reflected by the partially reflective layer 2960. Where the angle of the illuminating light 2973 is such that the DLP mirrors, when in the “on” state, reflect the illuminating light 2973 to form image light 2969 that substantially shares the same optical axis as the light from the wearer’s eye 2971. In this way, images of the wearer’s eye are captured in a field of view that overlaps the field of view for the displayed image content. In contrast, light reflected by DLP mirrors in the “off” state form dark light 2975 which is directed substantially to the side of the image light 2969 and the light from eye 2971. Dark light 2975 is directed toward a light trap 2962 that absorbs the dark light to improve the contrast of the displayed image as has been described above in this specification.

In an embodiment, partially reflective layer 2960 is a reflective polarizer. The light that is reflected from the eye 2971 can then be polarized prior to entering the corrective wedge 2966 (e.g. with an absorptive polarizer between the upper module 202 and the lower module 204), with a polarization orientation relative to the reflective polarizer that enables the light reflected from the eye 2971 to substantially be transmitted by the reflective polarizer. A quarter wave retarder layer 2957 is then included adjacent to the DLP 2955 (as previously disclosed in FIG. 3b) so that the light reflected from the eye 2971 passes through the quarter wave retarder layer 2957 once before being reflected by the plurality of DLP mirrors in the “no power” state and then passes through a second time after being reflected. By passing through the quarter wave retarder layer 2957 twice, the polarization state of the light from the eye 2971 is reversed, such that when it is incident upon the reflective polarizer, the light from the eye 2971 is then substantially reflected toward the camera 2980. By using a partially reflective layer 2960 that is a reflective polarizer and polarizing the light from the eye 2971 prior to entering the corrective wedge 2964, losses attributed to the partially reflective layer 2960 are reduced.

FIG. 28c shows the case wherein the DLP mirrors are simultaneously in the “no power” state, this mode of operation can be particularly useful when the HWC 102 is first put onto the head of the wearer. When the HWC 102 is first put onto the head of the wearer, it is not necessary to display an image yet. As a result, the DLP can be in a “no power” state for all the DLP mirrors and an image of the wearer’s eyes can be captured. The captured image of the wearer’s eye can then be compared to a database, using iris identification techniques, or other eye pattern identification techniques to determine, for example, the identity of the wearer.

In a further embodiment illustrated by FIG. 29 all of the DLP mirrors are put into the “no power” state for a portion of a frame time (e.g. 50% of a frame time for the displayed digital content image) and the capture of the eye image is synchronized to occur at the same time and for the same duration. By reducing the time that the DLP mirrors are in the “no power” state, the time where light is scattered by the DLP mirrors being in the “no power” state is reduced such that the wearer doesn’t perceive a change in the displayed image quality. This is possible because the DLP mirrors have a response time on the order of microseconds while typical frame times for a displayed image are on the order of 0.016 seconds. This method of capturing images of the wearer’s

eye can be used periodically to capture repetitive images of the wearer’s eye. For example, eye images could be captured for 50% of the frame time of every 10th frame displayed to the wearer. In another example, eye images could be captured for 10% of the frame time of every frame displayed to the wearer.

Alternately, the “no power” state can be applied to a subset of the DLP mirrors (e.g. 10% of the DLP mirrors) within while another subset is in busy generating image light for content to be displayed. This enables the capture of an eye image(s) during the display of digital content to the wearer. The DLP mirrors used for eye imaging can, for example, be distributed randomly across the area of the DLP to minimize the impact on the quality of the digital content being displayed to the wearer. To improve the displayed image perceived by the wearer, the individual DLP mirrors put into the “no power” state for capturing each eye image, can be varied over time such as in a random pattern, for example. In yet a further embodiment, the DLP mirrors put into the “no power” state for eye imaging may be coordinated with the digital content in such a way that the “no power” mirrors are taken from a portion of the image that requires less resolution.

In the embodiments of the invention as illustrated in FIGS. 9 and 29, in both cases the reflective surfaces provided by the DLP mirrors do not preserve the wavefront of the light from the wearer’s eye so that the image quality of captured image of the eye is somewhat limited. It may still be useful in certain embodiments, but it is somewhat limited. This is due to the DLP mirrors not being constrained to be on the same plane. In the embodiment illustrated in FIG. 9, the DLP mirrors are tilted so that they form rows of DLP mirrors that share common planes. In the embodiment illustrated in FIG. 29, the individual DLP mirrors are not accurately positioned to be in the same plane since they are not in contact with the substrate. Examples of advantages of the embodiments associated with FIG. 29 are: first, the camera 2980 can be located between the DLP 2955 and the illumination light source 2958 to provide a more compact upper module 202. Second, the polarization state of the light reflected from the eye 2971 can be the same as that of the image light 2969 so that the optical path of the light reflected from the eye and the image light can be the same in the lower module 204.

FIG. 30 shows an illustration of an embodiment for displaying images to the wearer and simultaneously capturing images of the wearer’s eye, wherein light from the eye 2971 is reflected towards a camera 3080 by the partially reflective layer 2960. The partially reflective layer 2960 can be an optically flat layer such that the wavefront of the light from the eye 2971 is preserved and as a result, higher quality images of the wearer’s eye can be captured. In addition, since the DLP 2955 is not included in the optical path for the light from the eye 2971, and the eye imaging process shown in FIG. 30 does not interfere with the displayed image, images of the wearer’s eye can be captured independently (e.g. with independent of timing, impact on resolution, or pixel count used in the image light) from the displayed images.

In the embodiment illustrated in FIG. 30, the partially reflective layer 2960 is a reflective polarizer, the illuminating light 2973 is polarized, the light from the eye 2971 is polarized and the camera 3080 is located behind a polarizer 3085. The polarization axis of the illuminating light 2973 and the polarization axis of the light from the eye are oriented perpendicular to the transmission axis of the reflective polarizer so that they are both substantially reflected by

the reflective polarizer. The illumination light **2973** passes through a quarter wave layer **2957** before being reflected by the DLP mirrors in the DLP **2955**. The reflected light passes back through the quarter wave layer **2957** so that the polarization states of the image light **2969** and dark light **2975** are reversed in comparison to the illumination light **2973**. As such, the image light **2969** and dark light **2975** are substantially transmitted by the reflective polarizer. Where the DLP mirrors in the “on” state provide the image light **2969** along an optical axis that extends into the lower optical module **204** to display an image to the wearer. At the same time, DLP mirrors in the “off” state provide the dark light **2975** along an optical axis that extends to the side of the upper optics module **202**. In the region of the corrective wedge **2966** where the dark light **2975** is incident on the side of the upper optics module **202**, an absorptive polarizer **3085** is positioned with its transmission axis perpendicular to the polarization axis of the dark light and parallel to the polarization axis of the light from the eye so that the dark light **2975** is absorbed and the light from the eye **2971** is transmitted to the camera **3080**.

FIG. **31** shows an illustration of another embodiment of a system for displaying images and simultaneously capturing image of the wearer’s eye that is similar to the one shown in FIG. **30**. The difference in the system shown in FIG. **31** is that the light from the eye **2971** is subjected to multiple reflections before being captured by the camera **3180**. To enable the multiple reflections, a mirror **3187** is provided behind the absorptive polarizer **3185**. Therefore, the light from the eye **2971** is polarized prior to entering the corrective wedge **2966** with a polarization axis that is perpendicular to the transmission axis of the reflective polarizer that comprises the partially reflective layer **2960**. In this way, the light from the eye **2971** is reflected first by the reflective polarizer, reflected second by the mirror **3187** and reflected third by the reflective polarizer before being captured by the camera **3180**. While the light from the eye **2971** passes through the absorptive polarizer **3185** twice, since the polarization axis of the light from the eye **2971** is oriented parallel to the polarization axis of the light from the eye **2971**, it is substantially transmitted by the absorptive polarizer **3185**. As with the system described in connection with FIG. **30**, the system shown in FIG. **31** includes an optically flat partially reflective layer **2960** that preserves the wavefront of the light from the eye **2971** so that higher quality images of the wearer’s eye can be captured. Also, since the DLP **2955** is not included in the optical path for the light reflected from the eye **2971** and the eye imaging process shown in FIG. **31** does not interfere with the displayed image, images of the wearer’s eye can be captured independently from the displayed images.

FIG. **32** shows an illustration of a system for displaying images and simultaneously capturing images of the wearer’s eye that includes a beam splitter plate **3212** comprised of a reflective polarizer, which is held in air between the light source **2958**, the DLP **2955** and the camera **3280**. The illumination light **2973** and the light from the eye **2971** are both polarized with polarization axes that are perpendicular to the transmission axis of the reflective polarizer. As a result, both the illumination light **2973** and the light from the eye **2971** are substantially reflected by the reflective polarizer. The illumination light **2873** is reflected toward the DLP **2955** by the reflective polarizer and split into image light **2969** and dark light **3275** depending on whether the individual DLP mirrors are respectively in the “on” state or the “off” state. By passing through the quarter wave layer **2957** twice, the polarization state of the illumination light **2973** is

reversed in comparison to the polarization state of the image light **2969** and the dark light **3275**. As a result, the image light **2969** and the dark light **3275** are then substantially transmitted by the reflective polarizer. The absorptive polarizer **3285** at the side of the beam splitter plate **3212** has a transmission axis that is perpendicular to the polarization axis of the dark light **3275** and parallel to the polarization axis of the light from the eye **2971** so that the dark light **3275** is absorbed and the light from the eye **2971** is transmitted to the camera **3280**. As in the system shown in FIG. **30**, the system shown in FIG. **31** includes an optically flat beam splitter plate **3212** that preserves the wavefront of the light from the eye **2971** so that higher quality images of the wearer’s eye can be captured. Also, since the DLP **2955** is not included in the optical path for the light from the eye **2971** and the eye imaging process shown in FIG. **31** does not interfere with the displayed image, images of the wearer’s eye can be captured independently from the displayed images.

Eye imaging systems where the polarization state of the light from the eye **2971** needs to be opposite to that of the image light **2969** (as shown in FIGS. **30**, **31** and **32**), need to be used with lower modules **204** that include combiners that will reflect both polarization states. As such, these upper modules **202** are best suited for use with the lower modules **204** that include combiners that are reflective regardless of polarization state, examples of these lower modules are shown in FIGS. **6**, **8a**, **8b**, **8c** and **24-27**.

In a further embodiment shown in FIG. **33**, the partially reflective layer **3360** is comprised of a reflective polarizer on the side facing the illumination light **2973** and a short pass dichroic mirror on the side facing the light from the eye **3371** and the camera **3080**. Where the short pass dichroic mirror is a dielectric mirror coating that transmits visible light and reflects infrared light. The partially reflective layer **3360** can be comprised of a reflective polarizer bonded to the inner surface of the illumination wedge **2964** and a short pass dielectric mirror coating on the opposing inner surface of the corrective wedge **2966**, wherein the illumination wedge **2964** and the corrective wedge **2966** are then optically bonded together. Alternatively, the partially reflective layer **3360** can be comprised of a thin substrate that has a reflective polarizer bonded to one side and a short pass dichroic mirror coating on the other side, where the partially reflective layer **3360** is then bonded between the illumination wedge **2964** and the corrective wedge **2966**. In this embodiment, an infrared light is included to illuminate the eye so that the light from the eye and the images captured of the eye are substantially comprised of infrared light. The wavelength of the infrared light is then matched to the reflecting wavelength of the shortpass dichroic mirror and the wavelength that the camera can capture images, for example an 800 nm wavelength can be used. In this way, the short pass dichroic mirror transmits the image light and reflects the light from the eye. The camera **3080** is then positioned at the side of the corrective wedge **2966** in the area of the absorbing light trap **3382**, which is provided to absorb the dark light **2975**. By positioning the camera **3080** in a depression in the absorbing light trap **3382**, scattering of the dark light **2975** by the camera **3080** can be reduced so that higher contrast images can be displayed to the wearer. An advantage of this embodiment is that the light from the eye need not be polarized, which can simplify the optical system and increase efficiency for the eye imaging system.

In yet another embodiment shown in FIG. **32a** a beam splitter plate **3222** is comprised of a reflective polarizer on the side facing the illumination light **2973** and a short pass

dichroic mirror on the side facing the light from the eye **3271** and the camera **3280**. An absorbing surface **3295** is provided to trap the dark light **3275** and the camera **3280** is positioned in an opening in the absorbing surface **3295**. In this way the system of FIG. **32** can be made to function with unpolarized light from the eye **3271**.

In embodiments directed to capturing images of the wearer's eye, light to illuminate the wearer's eye can be provided by several different sources including: light from the displayed image (i.e. image light); light from the environment that passes through the combiner or other optics; light provided by a dedicated eye light, etc. FIGS. **34** and **34a** show illustrations of dedicated eye illumination lights **3420**. FIG. **34** shows an illustration from a side view in which the dedicated illumination eye light **3420** is positioned at a corner of the combiner **3410** so that it doesn't interfere with the image light **3415**. The dedicated eye illumination light **3420** is pointed so that the eye illumination light **3425** illuminates the eyebox **3427** where the eye **3430** is located when the wearer is viewing displayed images provided by the image light **3415**. FIG. **34a** shows an illustration from the perspective of the eye of the wearer to show how the dedicated eye illumination light **3420** is positioned at the corner of the combiner **3410**. While the dedicated eye illumination light **3420** is shown at the upper left corner of the combiner **3410**, other positions along one of the edges of the combiner **3410**, or other optical or mechanical components, are possible as well. In other embodiments, more than one dedicated eye light **3420** with different positions can be used. In an embodiment, the dedicated eye light **3420** is an infrared light that is not visible by the wearer (e.g. 800 nm) so that the eye illumination light **3425** doesn't interfere with the displayed image perceived by the wearer.

FIG. **35** shows a series of illustrations of captured eye images that show the eye glint (i.e. light that reflects off the front of the eye) produced by a dedicated eye light. In this embodiment of the invention, captured images of the wearer's eye are analyzed to determine the relative positions of the iris **3550**, pupil, or other portion of the eye, and the eye glint **3560**. The eye glint is a reflected image of the dedicated eye light **3420** when the dedicated light is used. FIG. **35** illustrates the relative positions of the iris **3550** and the eye glint **3560** for a variety of eye positions. By providing a dedicated eye light **3420** in a fixed position, combined with the fact that the human eye is essentially spherical, or at least a reliably repeatable shape, the eye glint provides a fixed reference point against which the determined position of the iris can be compared to determine where the wearer is looking, either within the displayed image or within the see-through view of the surrounding environment. By positioning the dedicated eye light **3420** at a corner of the combiner **3410**, the eye glint **3560** is formed away from the iris **3550** in the captured images. As a result, the positions of the iris and the eye glint can be determined more easily and more accurately during the analysis of the captured images, since they do not interfere with one another. In a further embodiment, the combiner includes an associated cut filter that prevents infrared light from the environment from entering the HWC and the camera is an infrared camera, so that the eye glint is only provided by light from the dedicated eye light. For example, the combiner can include a low pass filter that passes visible light while absorbing infrared light and the camera can include a high pass filter that absorbs visible light while passing infrared light.

In an embodiment of the eye imaging system, the lens for the camera is designed to take into account the optics

associated with the upper module **202** and the lower module **204**. This is accomplished by designing the camera to include the optics in the upper module **202** and optics in the lower module **204**, so that a high MTF image is produced, at the image sensor in the camera, of the wearer's eye. In yet a further embodiment, the camera lens is provided with a large depth of field to eliminate the need for focusing the camera to enable sharp image of the eye to be captured. Where a large depth of field is typically provided by a high $f/\#$ lens (e.g. $f/\# > 5$). In this case, the reduced light gathering associated with high $f/\#$ lenses is compensated by the inclusion of a dedicated eye light to enable a bright image of the eye to be captured. Further, the brightness of the dedicated eye light can be modulated and synchronized with the capture of eye images so that the dedicated eye light has a reduced duty cycle and the brightness of infrared light on the wearer's eye is reduced.

In a further embodiment, FIG. **36a** shows an illustration of an eye image that is used to identify the wearer of the HWC. In this case, an image of the wearer's eye **3611** is captured and analyzed for patterns of identifiable features **3612**. The patterns are then compared to a database of eye images to determine the identity of the wearer. After the identity of the wearer has been verified, the operating mode of the HWC and the types of images, applications, and information to be displayed, can be adjusted and controlled in correspondence to the determined identity of the wearer. Examples of adjustments to the operating mode depending on who the wearer is determined to be or not be include: making different operating modes or feature sets available, shutting down or sending a message to an external network, allowing guest features and applications to run, etc.

FIG. **36b** is an illustration of another embodiment using eye imaging, in which the sharpness of the displayed image is determined based on the eye glint produced by the reflection of the displayed image from the wearer's eye surface. By capturing images of the wearer's eye **3611**, an eye glint **3622**, which is a small version of the displayed image can be captured and analyzed for sharpness. If the displayed image is determined to not be sharp, then an automated adjustment to the focus of the HWC optics can be performed to improve the sharpness. This ability to perform a measurement of the sharpness of a displayed image at the surface of the wearer's eye can provide a very accurate measurement of image quality. Having the ability to measure and automatically adjust the focus of displayed images can be very useful in augmented reality imaging where the focus distance of the displayed image can be varied in response to changes in the environment or changes in the method of use by the wearer.

An aspect of the present invention relates to controlling the HWC **102** through interpretations of eye imagery. In embodiments, eye-imaging technologies, such as those described herein, are used to capture an eye image or series of eye images for processing. The image(s) may be processed to determine a user intended action, an HWC predetermined reaction, or other action. For example, the imagery may be interpreted as an affirmative user control action for an application on the HWC **102**. Or, the imagery may cause, for example, the HWC **102** to react in a pre-determined way such that the HWC **102** is operating safely, intuitively, etc.

FIG. **37** illustrates a eye imagery process that involves imaging the HWC **102** wearer's eye(s) and processing the images (e.g. through eye imaging technologies described herein) to determine in what position **3702** the eye is relative to its neutral or forward looking position and/or the FOV **3708**. The process may involve a calibration step where the

user is instructed, through guidance provided in the FOV of the HWC 102, to look in certain directions such that a more accurate prediction of the eye position relative to areas of the FOV can be made. In the event the wearer's eye is determined to be looking towards the right side of the FOV 3708 (as illustrated in FIG. 37, the eye is looking out of the page) a virtual target line may be established to project what in the environment the wearer may be looking towards or at. The virtual target line may be used in connection with an image captured by camera on the HWC 102 that images the surrounding environment in front of the wearer. In embodiments, the field of view of the camera capturing the surrounding environment matches, or can be matched (e.g. digitally), to the FOV 3708 such that making the comparison is made more clear. For example, with the camera capturing the image of the surroundings in an angle that matches the FOV 3708 the virtual line can be processed (e.g. in 2d or 3d, depending on the camera images capabilities and/or the processing of the images) by projecting what surrounding environment objects align with the virtual target line. In the event there are multiple objects along the virtual target line, focal planes may be established corresponding to each of the objects such that digital content may be placed in an area in the FOV 3708 that aligns with the virtual target line and falls at a focal plane of an intersecting object. The user then may see the digital content when he focuses on the object in the environment, which is at the same focal plane. In embodiments, objects in line with the virtual target line may be established by comparison to mapped information of the surroundings.

In embodiments, the digital content that is in line with the virtual target line may not be displayed in the FOV until the eye position is in the right position. This may be a predetermined process. For example, the system may be set up such that a particular piece of digital content (e.g. an advertisement, guidance information, object information, etc.) will appear in the event that the wearer looks at a certain object(s) in the environment. A virtual target line(s) may be developed that virtually connects the wearer's eye with an object(s) in the environment (e.g. a building, portion of a building, mark on a building, gps location, etc.) and the virtual target line may be continually updated depending on the position and viewing direction of the wearer (e.g. as determined through GPS, e-compass, IMU, etc.) and the position of the object. When the virtual target line suggests that the wearer's pupil is substantially aligned with the virtual target line or about to be aligned with the virtual target line, the digital content may be displayed in the FOV 3704.

In embodiments, the time spent looking along the virtual target line and/or a particular portion of the FOV 3708 may indicate that the wearer is interested in an object in the environment and/or digital content being displayed. In the event there is no digital content being displayed at the time a predetermined period of time is spent looking at a direction, digital content may be presented in the area of the FOV 3708. The time spent looking at an object may be interpreted as a command to display information about the object, for example. In other embodiments, the content may not relate to the object and may be presented because of the indication that the person is relatively inactive. In embodiments, the digital content may be positioned in proximity to the virtual target line, but not in-line with it such that the wearer's view of the surroundings are not obstructed but information can augment the wearer's view of the surroundings. In embodiments, the time spent looking along a target line in the direction of displayed digital content may be an indication of

interest in the digital content. This may be used as a conversion event in advertising. For example, an advertiser may pay more for an add placement if the wearer of the HWC 102 looks at a displayed advertisement for a certain period of time. As such, in embodiments, the time spent looking at the advertisement, as assessed by comparing eye position with the content placement, target line or other appropriate position may be used to determine a rate of conversion or other compensation amount due for the presentation.

An aspect of the invention relates to removing content from the FOV of the HWC 102 when the wearer of the HWC 102 apparently wants to view the surrounding environments clearly. FIG. 38 illustrates a situation where eye imagery suggests that the eye has or is moving quickly so the digital content 3804 in the FOV 3808 is removed from the FOV 3808. In this example, the wearer may be looking quickly to the side indicating that there is something on the side in the environment that has grabbed the wearer's attention. This eye movement 3802 may be captured through eye imaging techniques (e.g. as described herein) and if the movement matches a predetermined movement (e.g. speed, rate, pattern, etc.) the content may be removed from view. In embodiments, the eye movement is used as one input and HWC movements indicated by other sensors (e.g. IMU in the HWC) may be used as another indication. These various sensor movements may be used together to project an event that should cause a change in the content being displayed in the FOV.

In embodiments, to remove the entire displayed image from the FOV and thereby provide an unencumbered view of the surrounding environment, power to the light source is turned OFF while power to the electronics in the HWC is left ON. As a result, the entire displayed image disappears instantly but the electronics associated with displaying images continues to run so that when eye movement or other triggering event occurs, a displayed image can be instantly provided without having to wait for the electronics to reboot. By turning the light source OFF and ON, to make the displayed image respectively disappear and then reappear, rapid changes between a display mode and a see-through mode can be provided. In an example, a rapid eye movement to the side as captured by eye imaging can cause the light source to turn OFF thereby providing an unencumbered view of the environment. Later when the eye returns to a central position, the light source may be turned ON so the displayed image returns. In another example, a rapid eye movement or rapid head nod by the wearer can be used in an operating mode to cause the light source to be turned OFF to obtain an unencumbered view of the environment for a predetermined period of time. After the predetermined period of time, the light source is turned ON and the displayed image is returned.

Another aspect of the present invention relates to determining a focal plane based on the wearer's eye convergence. Eyes are generally converged slightly and converge more when the person focuses on something very close. This is generally referred to as convergence. In embodiments, convergence is calibrated for the wearer. That is, the wearer may be guided through certain focal plane exercises to determine how much the wearer's eyes converge at various focal planes and at various viewing angles. The convergence information may then be stored in a database for later reference. In embodiments, a general table may be used in the event there is no calibration step or the person skips the calibration step. The two eyes may then be imaged periodically to determine the convergence in an attempt to under-

stand what focal plane the wearer is focused on. In embodiments, the eyes may be imaged to determine a virtual target line and then the eye's convergence may be determined to establish the wearer's focus, and the digital content may be displayed or altered based thereon.

FIG. 39 illustrates a situation where digital content is moved 3902 within one or both of the FOVs 3908 and 3910 to align with the convergence of the eyes as determined by the pupil movement 3904. By moving the digital content to maintain alignment, in embodiments, the overlapping nature of the content is maintained so the object appears properly to the wearer. This can be important in situations where 3D content is displayed.

An aspect of the present invention relates to controlling the HWC 102 based on events detected through eye imaging. A wearer winking, blinking, moving his eyes in a certain pattern, etc. may, for example, control an application of the HWC 102. Eye imaging (e.g. as described herein) may be used to monitor the eye(s) of the wearer and once a pre-determined pattern is detected an application control command may be initiated.

An aspect of the invention relates to monitoring the health of a person wearing a HWC 102 by monitoring the wearer's eye(s). Calibrations may be made such that the normal performance, under various conditions (e.g. lighting conditions, image light conditions, etc.) of a wearer's eyes may be documented. The wearer's eyes may then be monitored through eye imaging (e.g. as described herein) for changes in their performance. Changes in performance may be indicative of a health concern (e.g. concussion, brain injury, stroke, loss of blood, etc.). If detected the data indicative of the change or event may be communicated from the HWC 102.

Aspects of the present invention relate to security and access of computer assets (e.g. the HWC itself and related computer systems) as determined through eye image verification. As discussed herein elsewhere, eye imagery may be compared to known person eye imagery to confirm a person's identity. Eye imagery may also be used to confirm the identity of people wearing the HWCs 102 before allowing them to link together or share files, streams, information, etc.

An aspect of the present invention relates to securely linking HWC 102 and securely sharing files, streams, etc. (referred to generally as file sharing) with other HWC's 102 and/or other computers. Eye imaging, position, and tracking described herein elsewhere may be used in connection with the secure linking and file sharing. For example, a first HWC 102 may only be permitted to securely link with another HWC 102 if the wearer of the other HWC 102 is verified as a known person of a certain security level. In embodiments, the security level may be a government determined security level, a known person, a known friend, etc. Eye imaging may be used to identify the other HWCs 102 that may be allowed for sharing. For example, GPS or other location technologies may be used to identify other HWC's 102 in the proximity of a first HWC 102 and those proximal HWC's may be sorted into ones verified as secure HWC's, as verified by eye imaging, for example, and ones not verified. The sorted information or portion thereof may be presented in the first HWC 102 such that the wearer of the first HWC 102 can select secure sharing partners. Other sensor information may be used in connection with the secure sharing process. For example, identifying that two HWC's 102 are looking at one another (e.g. through e-compass readings, or HWC 102 forward facing camera image capture processing, etc.) may indicate that the two would like to share files or otherwise link communications and this

information may be used in connection with the eye imaging verification for the secure sharing process. Similarly, facial recognition, biometric information (e.g. heart rate signature, lung signature, etc.), near field communication identification, gestures by and between people wearing the HWC's, external user interfaces, voice commands, voice signatures, light emission signatures/signals, wireless communication signals (e.g. encrypted signals/commands), etc. may be used in combination with eye imaging and each other as a way of identifying potential secure share partners and sharing. In the event secure share partner(s) are identified, linking may be done automatically or through a user interface action, for example. In the event a user action is required, the display in the HWC 102 may display indications of who is a potential secure share partner by presented the indications on a map, through AR, or otherwise. The AR interface may involve presenting the indication in at positions in the field of view of the HWC 102 that are indicative of a GPS location of the potential secure sharing partner (as described herein elsewhere). For further information on secure linking and file sharing see U.S. patent application Ser. No. 14/181,473, entitled Secure Sharing in Head Worn Computing, filed Feb. 14, 2014, which is hereby incorporated by reference herein in its entirety.

Another aspect of the present invention relates to presentation techniques relating to the presentation of a known location or person or object at the known location. In embodiments, a spatially three-dimensional target line may be established between a first HWC 102 and a known geo-spatial location (e.g. as described by a gps location or other triangulation technology). Digital content may then be presented in a position in the field of view of the HWC 102 that corresponds, or is in-line, with the target line. The digital content may further be presented such that it comes into the wearer's view when the wearer focuses on a particular focal plane in the distance. The focal plane could then be aligned with the geo-spatial location such that when the wearer looks at the geo-spatial location, which is in-line with the target line, the digital content will come into view for the wearer and indicate the location with a proper visual perspective. In embodiments, the perceived environmental position indicative of the geo-spatial location may be verified by comparing the distance and angle defined by the virtual target line with a distance and angle measured by a range finder. This may be done to confirm that there are no obstacles in between the wearer of the HWC 102 and the geo-spatial location, for example. In the event that the verification indicates that there is an obstacle and that the geo-spatial location cannot be directly viewed, the digital content indicative of the location may be altered to indicate that the location is obstructed. The digital content may indicate if the location is in close proximity to the obstruction, far from the obstruction, etc. For further information on geo-spatial position visualizations see U.S. patent application Ser. No. 14/205,313 entitled Spatial Location Presentation in Head Worn Computing, filed Mar. 11, 2014, which is hereby incorporated by reference herein in its entirety.

An aspect of the present invention relates to presenting digital content in a field of view of a see-through head worn optical system at a position that is dependent on feedback from a sensor. In embodiments, the sensor provides information relating to a speed of forward motion of a person wearing the see-through head worn optical system. In embodiments, the content may be shifted to a portion of the FOV that provides for greater see-through visibility for the wearer. For example, if the wearer is walking, the content may be shifted towards the edge of the FOV so the person

can focus on the surrounding environment while walking but still be able to view the content at the edges of the FOV. In other embodiments, the person may be moving very fast, driving a car, for example, and the content may be shifted even further towards the edge of the FOV, or even past the FOV such that the person can more intently focus on the environment. In embodiments, when the content is shifted beyond the FOV, the content may be removed from display entirely and it may re-appear when an indication is presented that the wearer wants to view it or that the motion has slowed. For example, the wearer may use an external UL gesture, eye control command, etc. to cause the content to come back into the FOV. In embodiments, the wearer may be able to affirmatively cause the content to be moved to a location in the FOV dependent on his needs and this may modify or over-ride the content position shift based on the person's movement speed. For example, if the wearer is driving a car and the car is moving quickly, the wearer may choose to have the content displayed closer to the middle of the FOV and over-ride the auto-shift content position function.

When a user is moving through an environment while wearing a head worn computer, the method in which information is displayed may differ depending on a variety of factors that describe the way in which the user is moving. Factors such as speed, gaze direction, rate of change of gaze direction, rate of change of movement direction and the type of information being displayed may all affect how the user wants the information to be displayed.

In describing the method of display when moving, the pertinent information includes the heading that the user is looking along (generally referred to herein as "sight heading" or "sight vector"), the heading that the user is moving along (generally referred to herein as "movement heading" or "movement vector") and the heading where the displayed information is visible by the user (generally referred to herein as "display heading" or "display vector"). Where headings are described in term of degrees as measured, for example, with a compass. Sight heading can be determined, for example, with an electronic compass or magnetometer in the HWC. Movement heading can be determined by multiple GPS readings, IMU readings, etc.

A method of presenting content is to provide the displayed information directly in front of the user all the time. In this case, the sight heading is the same as the display heading. This method can be less than ideal when the user is moving because the displayed information interferes with the view of the surrounding environment. With a see-through HWC, there can be times when the user would prefer to be provided with an unencumbered view of the environment. As such, there will be times when the user would prefer to not have displayed information in the see-through field of view. In embodiments, the process adjusts the display heading in response to the sight heading, movement heading and speed of movement. In further embodiments the method of the invention adjusts the display heading based on the type of information being displayed and in response to the sight heading, movement heading and speed of movement. In yet other embodiments, the method adjusts the display heading in response to indications of how the user is moving. In further embodiments, the brightness of the displayed image is reduced in response to the sight heading, movement heading and speed of movement.

Another example of when a user may not want to have displayed information presented in the see-through field of view is when some type of stimulus occurs in the adjacent vicinity such as a loud noise to the side of the user. Typically

people respond to loud noises by turning their head to look toward the loud noise. At that point in time, the user would prefer to have an unencumbered view of the environment and, in embodiments, the content is removed based on the sound received at the HWC.

In another example, the user moves through an environment at various speeds. When a person is stationary, the person can look in any direction so the sight heading can change, but the movement heading doesn't change because there is no movement. If a person is walking, the person can look back and forth while moving, as such the sight heading can vary on either side of the movement heading and the sight heading can vary slowly. As the speed increases, it becomes more difficult for the person to look to the side for long periods of time so the sight heading can change more rapidly as the person glances to the side and in general the sight heading is more likely to match the movement heading. At high speed, such as running, the person needs to look directly ahead most of the time, so the sight heading matches the movement heading most of the time. When in a vehicle traveling at even greater speed, the person can only look briefly to the side when driving and most of the time must look ahead at the road where the sight heading matches the movement heading with only brief departures. Of course when the person is riding in a vehicle but not driving the vehicle, the person can look sideways for extended periods of time, as a result the sight heading can vary substantially from the movement heading.

FIG. 45 shows an example set of data for a person moving through an environment over a path that starts with a movement heading of 0 degrees and ends with a movement heading of 114 degrees during which time the speed of movement varies from 0 m/sec to 20 m/sec. The sight heading can be seen to vary on either side of the movement heading while moving as the person looks from side to side. Large changes in sight heading occur when the movement speed is 0 m/sec when the person is standing still, followed by step changes in movement heading.

Embodiments provide a process for determining the display heading that takes into account the way a user moves through an environment and provides a display heading that makes it easy for the user to find the displayed information while also providing unencumbered see-through views of the environment in response to different movements, speed of movement or different types of information being displayed.

FIG. 46 illustrates a see-through view as may be seen when using a HWC wherein information is overlaid onto a see-through view of the environment. The tree and the building are actually in the environment and the text is displayed in the see-through display such that it appears overlaid on the environment. In addition to text information such as, for example, instructions and weather information, some augmented reality information is shown that relates to nearby objects in the environment.

In an embodiment, the display heading is determined based on speed of movement. At low speeds, the display heading may be substantially the same as the sight heading while at high speed the display heading may be substantially the same as the movement heading. In embodiments, as long as the user remains stationary, the displayed information is presented directly in front of the user and HWC. However, as the movement speed increases (e.g. above a threshold or continually, etc.) the display heading becomes substantially the same as the movement heading regardless of the direction the user is looking, so that when the user looks in the direction of movement, the displayed information is directly

in front of the user and HMD and when the user looks to the side the displayed information is not visible.

Rapid changes in sight heading can be followed by a slower change in the display heading to provide a damped response to head rotation. Alternatively, the display heading can be substantially the time averaged sight heading so that the displayed information is presented at a heading that is in the middle of a series of sight headings over a period of time. In this embodiment, if the user stops moving their head, the display heading gradually becomes the same as the sight heading and the displayed information moves into the display field of view in front of the user and HMD. In embodiments, when there is a high rate of sight heading change, the process delays the effect of the time averaged sight heading on the display heading. In this way, the effect of rapid head movements on display heading is reduced and the positioning of the displayed information within the display field of view is stabilized laterally.

In another embodiment, display heading is determined based on speed of movement where at high-speed, the display heading is substantially the same as the movement heading. At mid-speed the display heading is substantially the same as a time averaged sight heading so that rapid head rotations are damped out and the display heading is in the middle of back and forth head movements.

In yet another embodiment, the type of information being displayed is included in determining how the information should be displayed. Augmented reality information that is connected to objects in the environment is given a display heading that substantially matches the sight heading. In this way, as the user rotates their head, augmented reality information comes into view that is related to objects that are in the see-through view of the environment. At the same time, information that is not connected to objects in the environment is given a display heading that is determined based on the type of movements and speed of movements as previously described in this specification.

In yet a further embodiment, when the speed of movement is determined to be above a threshold, the information displayed is moved downward in the display field of view so that the upper portion of the display field of view has less information or no information displayed to provide the user with an unencumbered see-through view of the environment.

FIGS. 47 and 48 show illustrations of a see-through view including overlaid displayed information. FIG. 47 shows the see-through view immediately after a rapid change in sight heading from the sight heading associated with the see-through view shown in FIG. 46 wherein the change in sight heading comes from a head rotation. In this case, the display heading is delayed. FIG. 48 shows how at a later time, the display heading catches up to the sight heading. The augmented reality information remains in positions within the display field of view where the association with objects in the environment can be readily made by the user.

FIG. 49 shows an illustration of a see-through view example including overlaid displayed information that has been shifted downward in the display field of view to provide an unencumbered see-through view in the upper portion of the see-through view. At the same time, augmented reality labels have been maintained in locations within the display field of view so they can be readily associated with objects in the environment.

In embodiments, the content may be positioned with respect to other types of sensors. For example, a sensor may detect an environmental condition that may be of interest and this may effect the position of the content in the display.

For example, the sensor may be a chemical sensor, fire sensor, mechanical sensor, electrical sensor, audio sensor, biologic sensor, etc. and the sensor may detect the presence of danger or other condition that causes the wearer to want to view the surroundings in a clear view so the content may then shift in or out of the field of view, as described herein. In embodiments, the sensor(s) may be mounted on/in the HWC 102, local to the HWC 102, remote from the HWC 102, or otherwise located. In embodiments, the sensor input may cause content to be presented in the field of view and then the sensor input, from the same or a different sensor or combination of sensors, may cause the content to be re-positioned.

FIG. 40 illustrates an embodiment in which digital content presented in a see-through FOV is positioned based on the speed in which the wearer is moving. When the person is not moving, as measured by sensor(s) in the HWC 102 (e.g. IMU, GPS based tracking, etc.), digital content may be presented at the stationary person content position 4004. The content position 4004 is indicated as being in the middle of the see-through FOV 4002; however, this is meant to illustrate that the digital content is positioned within the see-through FOV at a place that is generally desirable knowing that the wearer is not moving and as such the wearer's surrounding see through view can be somewhat obstructed. So, the stationary person content position, or neutral position, may not be centered in the see-through FOV; it may be positioned somewhere in the see-through FOV deemed desirable and the sensor feedback may shift the digital content from the neutral position. The movement of the digital content for a quickly moving person is also shown in FIG. 40 wherein as the person turns their head to the side, the digital content moves out of the see-through FOV to content position 4008 and then moves back as the person turns their head back. For a slowly moving person, the head movement can be more complex and as such the movement of the digital content in an out of the see-through FOV can follow a path such as that shown by content position 4010.

In embodiments, the sensor that assesses the wearer's movements may be a GPS sensor, IMU, accelerometer, etc. The content position may be shifted from a neutral position to a position towards a side edge of the field of view as the forward motion increases. The content position may be shifted from a neutral position to a position towards a top or bottom edge of the field of view as the forward motion increases. The content position may shift based on a threshold speed of the assessed motion. The content position may shift linearly based on the speed of the forward motion. The content position may shift non-linearly based on the speed of the forward motion. The content position may shift outside of the field of view. In embodiments, the content is no longer displayed if the speed of movement exceeds a predetermined threshold and will be displayed again once the forward motion slows.

In embodiments, the content position may generally be referred to as shifting; it should be understood that the term shifting encompasses a process where the movement from one position to another within the see-through FOV or out of the FOV is visible to the wearer (e.g. the content appears to slowly or quickly move and the user perceives the movement itself) or the movement from one position to another may not be visible to the wearer (e.g. the content appears to jump in a discontinuous fashion or the content disappears and then reappears in the new position).

Another aspect of the present invention relates to removing the content from the field of view or shifting it to a position within the field of view that increases the wearer's

view of the surrounding environment when a sensor causes an alert command to be issued. In embodiments, the alert may be due to a sensor or combination of sensors that sense a condition above a threshold value. For example, if an audio sensor detects a loud sound of a certain pitch, content in the field of view may be removed or shifted to provide a clear view of the surrounding environment for the wearer. In addition to the shifting of the content, in embodiments, an indication of why the content was shifted may be presented in the field of view or provided through audio feedback to the wearer. For instance, if a carbon monoxide sensor detects a high concentration in the area, content in the field of view may be shifted to the side of the field of view or removed from the field of view and an indication may be provided to the wearer that there is a high concentration of carbon monoxide in the area. This new information, when presented in the field of view, may similarly be shifted within or outside of the field of view depending on the movement speed of the wearer.

FIG. 41 illustrates how content may be shifted from a neutral position 4104 to an alert position 4108. In this embodiment, the content is shifted outside of the see-through FOV 4102. In other embodiments, the content may be shifted as described herein.

Another aspect of the present invention relates to identification of various vectors or headings related to the HWC 102, along with sensor inputs, to determine how to position content in the field of view. In embodiments, the speed of movement of the wearer is detected and used as an input for position of the content and, depending on the speed, the content may be positioned with respect to a movement vector or heading (i.e. the direction of the movement), or a sight vector or heading (i.e. the direction of the wearer's sight direction). For example, if the wearer is moving very fast the content may be positioned within the field of view with respect to the movement vector because the wearer is only going to be looking towards the sides of himself periodically and for short periods of time. As another example, if the wearer is moving slowly, the content may be positioned with respect to the sight heading because the user may more freely be shifting his view from side to side.

FIG. 42 illustrates two examples where the movement vector may effect content positioning. Movement vector A 4202 is shorter than movement vector B 4210 indicating that the forward speed and/or acceleration of movement of the person associated with movement vector A 4202 is lower than the person associated with movement vector B 4210. Each person is also indicated as having a sight vector or heading 4208 and 4212. The sight vectors A 4208 and B 4210 are the same from a relative perspective. The white area inside of the black triangle in front of each person is indicative of how much time each person likely spends looking at a direction that is not in line with the movement vector. The time spent looking off angle A 4204 is indicated as being more than that of the time spent looking off angle B 4214. This may be because the movement vector speed A is lower than movement vector speed B. The faster the person moves forward the more the person tends to look in the forward direction, typically. The FOVs A 4218 and B 4222 illustrate how content may be aligned depending on the movement vectors 4202 and 4210 and sight vectors 4208 and 4212. FOV A 4218 is illustrated as presenting content in-line with the sight vector 4220. This may be due to the lower speed of the movement vector A 4202. This may also be due to the prediction of a larger amount of time spent looking off angle A 4204. FOV B 4222 is illustrated as presenting content in line with the movement vector 4224.

This may be due to the higher speed of movement vector B 4210. This may also be due to the prediction of a shorter amount of time spent looking off angle B 4214.

Another aspect of the present invention relates to damping a rate of content position change within the field of view. As illustrated in FIG. 43, the sight vector may undergo a rapid change 4304. This rapid change may be an isolated event or it may be made at or near a time when other sight vector changes are occurring. The wearer's head may be turning back and forth for some reason. In embodiments, the rapid successive changes in sight vector may cause a damped rate of content position change 4308 within the FOV 4302. For example, the content may be positioned with respect to the sight vector, as described herein, and the rapid change in sight vector may normally cause a rapid content position change; however, since the sight vector is successively changing, the rate of position change with respect to the sight vector may be damped, slowed, or stopped. The position rate change may be altered based on the rate of change of the sight vector, average of the sight vector changes, or otherwise altered.

Another aspect of the present invention relates to simultaneously presenting more than one content in the field of view of a see-through optical system of a HWC 102 and positioning one content with the sight heading and one content with the movement heading. FIG. 44 illustrates two FOV's A 4414 and B 4420, which correspond respectively to the two identified sight vectors A 4402 and B 4404. FIG. 44 also illustrates an object in the environment 4408 at a position relative to the sight vectors A 4402 and B 4404. When the person is looking along sight vector A 4402, the environment object 4408 can be seen through the field of view A 4414 at position 4412. As illustrated, sight heading aligned content is presented as TEXT in proximity with the environment object 4412. At the same time, other content 4418 is presented in the field of view A 4414 at a position aligned in correspondence with the movement vector. As the movement speed increases, the content 4418 may shift as described herein. When the sight vector of the person is sight vector B 4404 the environmental object 4408 is not seen in the field of view B 4420. As a result, the sight aligned content 4410 is not presented in field of view B 4420; however, the movement aligned content 4418 is presented and is still dependent on the speed of the motion.

In a further embodiment, in an operating mode such as when the user is moving in an environment, digital content is presented at the side of the user's see-through FOV so that the user can only view the digital content by turning their head. In this case, when the user is looking straight ahead, such as when the movement heading matches the sight heading, the see-through view FOV does not include digital content. The user then accesses the digital content by turning their head to the side whereupon the digital content moves laterally into the user's see-through FOV. In another embodiment, the digital content is ready for presentation and will be presented if an indication for its presentation is received. For example, the information may be ready for presentation and if the sight heading or predetermined position of the HWC 102 is achieved the content may then be presented. The wearer may look to the side and the content may be presented. In another embodiment, the user may cause the content to move into an area in the field of view by looking in a direction for a predetermined period of time, blinking, winking, or displaying some other pattern that can be captured through eye imaging technologies (e.g. as described herein elsewhere).

In yet another embodiment, an operating mode is provided wherein the user can define sight headings wherein the associated see-through FOV includes digital content or does not include digital content. In an example, this operating mode can be used in an office environment where when the user is looking at a wall digital content is provided within the FOV, whereas when the user is looking toward a hallway, the FOV is unencumbered by digital content. In another example, when the user is looking horizontally digital content is provided within the FOV, but when the user looks down (e.g. to look at a desktop or a cellphone) the digital content is removed from the FOV.

Another aspect of the present invention relates to collecting and using eye position and sight heading information. Head worn computing with motion heading, sight heading, and/or eye position prediction (sometimes referred to as “eye heading” herein) may be used to identify what a wearer of the HWC **102** is apparently interested in and the information may be captured and used. In embodiments, the information may be characterized as viewing information because the information apparently relates to what the wearer is looking at. The viewing information may be used to develop a personal profile for the wearer, which may indicate what the wearer tends to look at. The viewing information from several or many HWC’s **102** may be captured such that group or crowd viewing trends may be established. For example, if the movement heading and sight heading are known, a prediction of what the wearer is looking at may be made and used to generate a personal profile or portion of a crowd profile. In another embodiment, if the eye heading and location, sight heading and/or movement heading are known, a prediction of what is being looked at may be predicted. The prediction may involve understanding what is in proximity of the wearer and this may be understood by establishing the position of the wearer (e.g. through GPS or other location technology) and establishing what mapped objects are known in the area. The prediction may involve interpreting images captured by the camera or other sensors associated with the HWC **102**. For example, if the camera captures an image of a sign and the camera is in-line with the sight heading, the prediction may involve assessing the likelihood that the wearer is viewing the sign. The prediction may involve capturing an image or other sensory information and then performing object recognition analysis to determine what is being viewed. For example, the wearer may be walking down a street and the camera that is in the HWC **102** may capture an image and a processor, either on-board or remote from the HWC **102**, may recognize a face, object, marker, image, etc. and it may be determined that the wearer may have been looking at it or towards it.

FIG. **50** illustrates a scene where a person is walking with a HWC **102** mounted on his head. In this scene, the person’s geo-spatial location **5004** is known through a GPS sensor, which could be another location system, and his movement heading, sight heading **5014** and eye heading **5002** are known and can be recorded (e.g. through systems described herein). There are objects and a person in the scene. Person **5012** may be recognized by the wearer’s HWC **102** system, the person may be mapped (e.g. the person’s GPS location may be known or recognized), or otherwise known. The person may be wearing a garment or device that is recognizable. For example, the garment may be of a certain style and the HWC may recognize the style and record it’s viewing. The scene also includes a mapped object **5018** and a recognized object **5020**. As the wearer moves through the scene, the sight and/or eye headings may be recorded and

communicated from the HWC **102**. In embodiments, the time that the sight and/or eye heading maintains a particular position may be recorded. For example, if a person appears to look at an object or person for a predetermined period of time (e.g. 2 seconds or longer), the information may be communicated as gaze persistence information as an indication that the person may have been interested in the object.

In embodiments, sight headings may be used in conjunction with eye headings or eye and/or sight headings may be used alone. Sight headings can do a good job of predicting what direction a wearer is looking because many times the eyes are looking forward, in the same general direction as the sight heading. In other situations, eye headings may be a more desirable metric because the eye and sight headings are not always aligned. In embodiments herein examples may be provided with the term “eye/sight” heading, which indicates that either or both eye heading and sight heading may be used in the example.

FIG. **51** illustrates a system for receiving, developing and using movement heading, sight heading, eye heading and/or persistence information from HWC(s) **102**. The server **5104** may receive heading or gaze persistence information, which is noted as persistence information **5102**, for processing and/or use. The heading and/or gaze persistence information may be used to generate a personal profile **5108** and/or a group profile **5110**. The personal profile **5108** may reflect the wearer’s general viewing tendencies and interests. The group profile **5110** may be an assemblage of different wearer’s heading and persistence information to create impressions of general group viewing tendencies and interests. The group profile **5110** may be broken into different groups based on other information such as gender, likes, dislikes, biographical information, etc. such that certain groups can be distinguished from other groups. This may be useful in advertising because an advertiser may be interested in what a male adult sports go’er is generally looking at as oppose to a younger female. The profiles **5108** and **5110** and raw heading and persistence information may be used by retailers **5114**, advertisers **5118**, trainers, etc. For example, an advertiser may have an advertisement posted in an environment and may be interested in knowing how many people look at the advertisement, how long they look at it and where they go after looking at it. This information may be used as conversion information to assess the value of the advertisement and thus the payment to be received for the advertisement.

In embodiments, the process involves collecting eye and/or sight heading information from a plurality of head-worn computers that come into proximity with an object in an environment. For example, a number of people may be walking through an area and each of the people may be wearing a head worn computer with the ability to track the position of the wearer’s eye(s) as well as possibly the wearer’s sight and movement headings. The various HWC wearing individuals may then walk, ride, or otherwise come into proximity with some object in the environment (e.g. a store, sign, person, vehicle, box, bag, etc.). When each person passes by or otherwise comes near the object, the eye imaging system may determine if the person is looking towards the object. All of the eye/sight heading information may be collected and used to form impressions of how the crowd reacted to the object. A store may be running a sale and so the store may put out a sign indicating such. The storeowners and managers may be very interested to know if anyone is looking at their sign. The sign may be set as the object of interest in the area and as people navigate near the sign, possibly determined by their GPS locations, the eye/

sight heading determination system may record information relative to the environment and the sign. Once, or as, the eye/sight heading information is collected and associations between the eye headings and the sign are determined, feedback may be sent back to the storeowner, managers, advertiser, etc. as an indication of how well their sign is attracting people. In embodiments, the sign's effectiveness at attracting people's attention, as indicated through the eye/sight headings, may be considered a conversion metric and impact the economic value of the sign and/or the signs placement.

In embodiments, a map of the environment with the object may be generated by mapping the locations and movement paths of the people in the crowd as they navigate by the object (e.g. the sign). Layered on this map may be an indication of the various eye/sight headings. This may be useful in indicating wear people were in relation to the object when then viewed they object. The map may also have an indication of how long people looked at the object from the various positions in the environment and where they went after seeing the object.

In embodiments, the process involves collecting a plurality of eye/sight headings from a head-worn computer, wherein each of the plurality of eye/sight headings is associated with a different pre-determined object in an environment. This technology may be used to determine which of the different objects attracts more of the person's attention. For example, if there are three objects placed in an environment and a person enters the environment navigating his way through it, he may look at one or more of the objects and his eye/sight heading may persist on one or more objects longer than others. This may be used in making or refining the person's personal attention profile and/or it may be used in connection with other such people's data on the same or similar objects to determine an impression of how the population or crowd reacts to the objects. Testing advertisements in this way may provide good feedback of its effectiveness.

In embodiments, the process may involve capturing eye/sight headings once there is substantial alignment between the eye/sight heading and an object of interest. For example, the person with the HWC may be navigating through an environment and once the HWC detects substantial alignment or the projected occurrence of an upcoming substantial alignment between the eye/sight heading and the object of interest, the occurrence and/or persistence may be recorded for use.

In embodiments, the process may involve collecting eye/sight heading information from a head-worn computer and collecting a captured image from the head-worn computer that was taken at substantially the same time as the eye/sight heading information was captured. These two pieces of information may be used in conjunction to gain an understanding of what the wearer was looking at and possibly interested in. The process may further involve associating the eye/sight heading information with an object, person, or other thing found in the captured image. This may involve processing the captured image looking for objects or patterns. In embodiments, gaze time or persistence may be measured and used in conjunction with the image processing. The process may still involve object and/or pattern recognition, but it may also involve attempting to identify what the person gazed at for the period of time by more particularly identifying a portion of the image in conjunction with image processing.

In embodiments, the process may involve setting a pre-determined eye/sight heading from a pre-determined geo-

spatial location and using them as triggers. In the event that a head worn computer enters the geospatial location and an eye/sight heading associated with the head worn computer aligns with the pre-determined eye/sight heading, the system may collect the fact that there was an apparent alignment and/or the system may record information identifying how long the eye/sight heading remains substantially aligned with the pre-determined eye/sight heading to form a persistence statistic. This may eliminate or reduce the need for image processing as the triggers can be used without having to image the area. In other embodiments, image capture and processing is performed in conjunction with the triggers. In embodiments, the triggers may be a series a geospatial locations with corresponding eye/sight headings such that many spots can be used as triggers that indicate when a person entered an area in proximity to an object of interest and/or when that person actually appeared to look at the object.

In embodiments, eye imaging may be used to capture images of both eyes of the wearer in order to determine the amount of convergence of the eyes (e.g. through technologies described herein elsewhere) to get an understanding of what focal plane is being concentrated on by the wearer. For example, if the convergence measurement suggests that the focal plane is within 15 feet of the wearer, than, even though the eye/sight headings may align with an object that is more than 15 feet away it may be determined that the wearer was not looking at the object. If the object were within the 15 foot suggested focal plane, the determination may be that the wearer was looking at the object.

Another aspect of the present invention relates to collecting other peoples' eye/sight heading and predicting what they appear to be looking at. In embodiments, the process involves capturing image(s) of others through the use of a head-worn computer, understanding the geospatial location of the head-worn computer, processing the captured image(s) of the others to determine a sight heading for each of the others, estimating a geospatial position for each of the others, and then predicting, based on the other persons geospatial location and eye/sight direction, what the other person may be looking at. In embodiments, the image capture process may involve taking a series of images or video such that a persistence factor can be determined. As with other techniques described herein elsewhere, a prediction of the other person's eye/sight heading may be taken after it is recognized that the other person persisted in looking in a direction for a period of time (e.g. 1 or 2 seconds). In embodiments, the person collecting other people's interests (sometimes referred to as a "collector" herein) may locate himself at a particular geospatial location and the capture process may involve capturing images when another person is perceived as looking in a particular direction, as determined by their eye/sight heading, and they persist to look in the direction for a period of time. In embodiments, the series of images or video may be used to observe how the other person's eye/sight heading changes with their movement. For example, if their eye/sight heading continually changes, as if it is connected to something in the environment, while they move, the continual change may be understood as a persistence of gazing at an object in the environment. In embodiments, such a continual eye/sight change may be noted with respect to a person that is not moving, or moving slowly, and understood as a persistence of gaze with respect to a moving object in the environment. In embodiments, eye/sight headings may have a component of vertical aspect as well as horizontal to determine at what altitude the other person appears to be observing.

FIG. 52 illustrates a person acting as a collector **5202** of others' eye/sight headings and predicting the others' geospatial locations for a prediction of object sight lines. The other people, in this embodiment, are generally referred to as observers. The collector **5202** is wearing a HWC **102** with an internal camera that has a field of view **5214**. The collector's HWC **102** also has a GPS sensor so his geospatial location **5218** is known to the HWC **102** and related systems. The collector **5202** captures images of the observers A-D, **5204**, **5208**, **5210**, and **5212**. The images can then be processed to determine the apparent eye/sight heading of each of the observers. The eye/sight headings may be associated with a heading that appears to be in-line with an object in the environment (e.g. object A **5220** or object B **5222**). Once an association is noted between the eye/sight heading and the object, prediction analytics can be used to establish how long the person appeared to look at the object, if it was truly the object that the person was looking at, if the person was interested in the object, etc.

Observer A **5204** is in close proximity to the collector **5202**. In this embodiment, the predicted GPS location of observer A **5204** appears to be within the predicted GPS location of the collector **5202**, or at least near or within the measurement error of the GPS location. In this situation, the collector **5202** may establish observer A's **5204** eye/sight headings and then project an object line from the collector's GPS location, which can be used as an estimate of observer A's **5204** location, to understand if the object line intersects with an object of interest in the environment. Here, as indicated in the illustration, observer A **5204** has a eye/sight heading that appears in line with object B **5222**. This may be an indication that observer A **5204** was looking at object B **5222** in the environment.

Observers B, C, and D, **5208**, **5210**, and **5212** are not as close to the collector **5202** as observer A **5204**. This may cause a prediction of geospatial locations to be made. In embodiments, the collector captures an image of observer B **5208** and processes the image, or the image is processed remotely, to determine the observer's eye/sight heading and a prediction of the observer's geospatial location is also made. The geospatial location prediction may be made through the image processing (e.g. comparing the size of a known object with the size of the observer or portions of the observer, reviewing camera focal distance, etc.) or the location prediction may be based on other sensory input (e.g. a range finder, stereo camera parallax, structured light 3D solutions, etc.). With a prediction of geospatial location and eye/sight headings, an object sight line can be determined and the observer's interest in an intersecting object can be predicted.

In embodiments, eye and sight headings may be determined through image processing. For example, similar in nature to technologies described herein elsewhere with respect to determining a wearer's eye position, if the observer's eyes are visible in images captured by the camera in the collector's HWC, the observer's eye position may be predicted based on pupil's position, sclera viewed, symmetry of imagery of the two eyes, etc. If the observer's eyes are not visible in images captured by the camera in the collector's HWC, an approximation of the observer's sight heading may be still be determined by analyzing images captured of the observer by determining the direction of the shoulders and head, the angle of the head to the body, glasses to the body, other head or head-worn items to body parts, etc. For example, from the captured image, one may understand that the shoulders of the observer are at an angle as compared to the collector's camera. Where, the collector's camera angle

may be known through an e-compass, or other position sensor, in the HWC **102** of the collector. A determination of the absolute value of the observer's shoulder position may be estimated from image analysis of the collector's body based on a comparison to the collector's e-compass heading. The observer's head position may then be determined by comparing various parts of the observer's head with the position of the observer's shoulders, to establish the observer's sight heading. The sight heading may be determined as a compass angle based on the references in the calculation. If eye position is of interest in addition to the sight heading, the eye position may be referenced by the sight heading to determine the eye heading.

In a further embodiment, sight headings for a group of observers can be collected by the collector moving through the group. The collected sight heading data can be presented in aggregate or by location within an area. Additional analysis of the images of the observers can be used to simultaneously determine general characteristics of the observers such as: height, volume (or weight), gender, age or race. This general characteristic data can be combined with the determined sight heading data to determine additional information about the type of people that are looking at specific objects in the environment.

Another aspect of the present invention relates to an optical configuration that provides digitally displayed content to an eye of a person wearing a head-worn display (e.g. as used in a HWC **102**) and allows the person to see through the display such that the digital content is perceived by the person as augmenting the see through view of the surrounding environment. The optical configuration may have a variable transmission optical element that is in-line with the person's see-through view such that the transmission of the see-through view can be increased and decreased. This may be helpful in situations where a person wants or would be better served with a high transmission see-through view and when, in the same HWC **102**, the person wants or would be better served with less see-through transmission. The lower see-through transmission may be used in bright conditions and/or in conditions where higher contrast for the digitally presented content is desirable. The optical system may also have a camera that images the surrounding environment by receiving reflected light from the surrounding environment off of an optical element that is in-line with the person's see-through view of the surrounding. In embodiments, the camera may further be aligned in a dark light trap such that light reflected and/or transmitted in the direction of the camera that is not captured by the camera is trapped to reduce stray light.

In embodiments, a HWC **102** is provided that includes a camera that is coaxially aligned with the direction that the user is looking. FIG. 53 shows an illustration of an optical system **5315** that includes an absorptive polarizer **5337** and a camera **5339**. The image source **5310** can include light sources, displays and reflective surfaces as well as one or more lenses **5320**. Image light **5350** is provided by the image source **5310** wherein, a portion of the image light **5350** is reflected toward the user's eye **5330** by a partially reflective combiner **5335**. At the same time, a portion of the image light **5350** may be transmitted by the combiner **5335** such that it is incident onto the absorptive polarizer **5337**. In this embodiment, the image light **5350** is polarized light with the polarization state of the image light **5350** oriented relative to the transmission axis of the absorptive polarizer **5337** such that the incident image light **5350** is absorbed by the absorptive polarizer **5337**. In this way, faceglow produced by escaping image light **5350** is reduced. In embodiments,

the absorptive polarizer **5337** includes an antireflection coating to reduce reflections from the surface of the absorptive polarizer **5337**.

FIG. **53** further shows a camera **5339** for capturing images of the environment in the direction that the user is looking. The camera **5339** is positioned behind the absorptive polarizer **5337** and below the combiner **5335** so that a portion of light from the environment **5370** is reflected by the combiner **5335** toward the camera **5339**. Light from the environment **5370** can be unpolarized so that a portion of the light from the environment **5370** that is reflected by the combiner **5335** passes through the absorptive polarizer **5337** and it is this light that is captured by the camera **5339**. As a result, the light captured by the camera will have a polarization state that is opposite that of the image light **5350**. In addition, the camera **5339** is aligned relative to the combiner **5335** such that the field of view associated with the camera **5339** is coaxial to the display field of view provided by image light **5350**. At the same time, a portion of scene light **5360** from the environment is transmitted by the combiner **5335** to provide a see-through view of the environment to the user's eye **5330**. Where the display field of view associated with the image light **5350** is typically coincident to the see-through field of view associated with the scene light **5360** and thereby the see through field of view and the field of view of the camera **5339** are at least partially coaxial. By attaching the camera **5339** to the lower portion of the optical system **5315**, the field of view of the camera **5339** as shown by the light from the environment **5370** moves as the user moves their head so that images captured by the camera **5339** correspond to the area of the environment that the user is looking at. By coaxially aligning the camera field of view with the displayed image and the user's view of the scene, augmented reality images with improved alignment to objects in the scene can be provided. This is because the captured images from the camera **5339** provide an accurate representation of the user's perspective view of the scene. As an example, when the user sees an object in the scene as being located in the middle of the see-through view of the HWC, the object will be located in the middle of the image captured by the camera and any augmented reality imagery that is to be associated with the object can be located in the middle of the displayed image. As the user moves their head, the relative position of the object as seen in the see-through view of the scene will change and the position of the augmented reality imagery can be changed within the displayed image in a corresponding manner. When a camera **5339** is provided for each of the user's eyes, an accurate representation of the 3D view of the scene can be provided as well. This is an important advantage provided by the invention because images captured by a camera located in the frame of the HWC (e.g. between the eyes or at the corners) capture images that are laterally offset from the user's perspective of the scene and as a result it is difficult to align augmented reality images with objects in the scene as seen from the user's perspective.

In the optical system **5315** shown in FIG. **53**, the absorptive polarizer **5337** simultaneously functions as a light trap for escaping image light **5350**, a light blocker of the image light **5350** for the camera **5339** and a window for light from the environment **5370** to the camera **5339**. This is possible because the polarization state of the image light **5350** is perpendicular to the transmission axis of the absorptive polarizer **5337** while the light from the environment **5370** is unpolarized so that a portion of the light from the environment **5370** that is the opposite polarization state to the image light is transmitted by the absorptive polarizer **5337**. The

combiner **5335** can be any partially reflective surface including a simple partial mirror, a notch mirror and a holographic mirror. The reflectivity of the combiner **5335** can be selected to be greater than 50% (e.g. 55% reflectivity and 45% transmission over the visible wavelength spectral band) whereby a majority of the image light **5350** will be reflected toward the user's eye **5330** and a majority of light from the environment **5370** will be reflected toward the camera **5339**, this system will provide a brighter displayed image, a brighter captured image with a dimmer see-through view of the environment. Alternatively, the reflectivity of the combiner **5335** can be selected to be less than 50% (e.g. 20% reflectivity and 80% transmission over the visible wavelength spectral band) whereby the majority of the image light **5350** will be transmitted by the combiner **5335** and a majority of light from the environment **5370** will be transmitted to the user's eye **5330**, this system will provide a brighter see-through view of the environment, while providing a dimmer displayed image and a dimmer captured image. As such, the system can be designed to favor the anticipated use by the user.

In embodiments, the combiner **5335** is planar with an optical flatness that is sufficient to enable a sharp displayed image and a sharp captured image, such as a flatness of less than 20 waves of light within the visible wavelengths. However, in embodiments, the combiner **5335** may be curved in which case the displayed image and the captured image will both be distorted and this distortion will have to be digitally corrected by the associated image processing system. In the case of the displayed image, the image is digitally distorted by the image processing system in a direction that is opposite to the distortion that is caused by the curved combiner so the two distortions cancel one another and as a result the user sees an undistorted displayed image. In the case of the captured image, the captured image is digitally distorted after capture to cancel out the distortion caused by the curved combiner so that the image appears to be undistorted after image processing.

In embodiments, the combiner **5335** is an adjustable partial mirror in which the reflectivity can be changed by the user or automatically to better function within different environmental conditions or different use cases. The adjustable partial mirror can be an electrically controllable mirror such as for example, the e-Transflector that can be obtained from Kent Optronics (<http://www.kentoptronics.com/mirror.html>) where the reflectivity can be adjusted based on an applied voltage. The adjustable partial mirror can also be a fast switchable mirror (e.g. a switching time of less than 0.03 seconds) wherein the perceived transparency is derived from the duty cycle of the mirror rapidly switching between a reflecting state and a transmitting state. In embodiments, the images captured by the camera **5339** can be synchronized to occur when the fast switchable mirror is in the reflecting state to provide an increased amount of light to the camera **5339** during image capture. As such, an adjustable partial mirror allows for the transmissivity of the partial mirror to be changed corresponding to the environmental conditions, e.g. the transmissivity can be low when the environment is bright and the transmissivity can be high when the environment is dim.

In a further embodiment, the combiner **5335** includes a hot mirror coating on the side facing the camera **5339** wherein visible wavelength light is substantially transmitted while a spectral wavelength band of infrared light is substantially reflected and the camera **5339** captures images that include at least a portion of the infrared wavelength light. In these embodiments, the image light **5350** includes visible

wavelength light and a portion of the visible wavelength light is transmitted by the combiner **5335**, where it is then absorbed by the absorptive polarizer **5337**. A portion of the scene light **5360** is comprised of visible wavelength light and this is also transmitted by the combiner **5335**, to provide the user with a see-through view of the environment. The light from the environment **5370** is comprised of visible wavelength light and infrared wavelength light. A portion of the visible wavelength light along with substantially all of the infrared wavelength light within the spectral wavelength band associated with the hot mirror, is reflected by the combiner **5335** toward the camera **5339** thereby passing through the absorptive polarizer **5337**. In embodiments, the camera **5339** is selected to include an image sensor that is sensitive to infrared wavelengths of light and the absorptive polarizer **5337** is selected to substantially transmit infrared wavelengths of light of both polarization states (e.g. ITOS XP44 polarizer which transmits both polarization states of light with wavelengths above 750 nm: see <http://www.ito-s.de/english/polarisatoren/linear/linear.php>) so that an increased % of infrared light is captured by the camera **5339**. In these embodiments, the absorptive polarizer **5337** functions as a light trap for the escaping image light **5350** and thereby blocking the image light **5350** that is in the visible wavelengths from the camera **5339** while simultaneously acting as a window for infrared wavelength light from the environment **5370** for the camera **5339**.

By coaxially aligning the camera field of view with the displayed image and the user's view of the scene, augmented reality images with improved alignment to objects in the scene can be provided. This is because the captured images from the camera provide an accurate representation of the user's perspective view of the scene. In embodiments, the camera that is coaxially aligned with the user's view captures an image of the scene, the processor then identifies an object in the captured image and identifies a field of view position for the object, which can be compared to the displayed field of view correlated position so digital content is then displayed relative to the position of the object.

Another aspect of the present invention relates to an optical assembly that uses a reflective display where the reflective display is illuminated with a front light arranged to direct the illumination at angles around 90 degrees from the active reflective surface of the reflective display. In embodiments, the optical configuration is light weight, small and produces a high quality image in a head-worn see-through display.

FIG. **54** provides a cross sectional illustration of the compact optical display assembly for a HWC **102** according to principles of the present invention along with illustrative light rays to show how the light passes through the assembly. The display assembly is comprised of upper optics and lower optics. The upper optics include a reflective image source **5410**, a quarter wave film **5415**, a field lens **5420**, a reflective polarizer **5430** and a polarized light source **5450**. The upper optics convert illumination light **5437** into image light **5435**. The lower optics comprise a beam splitter plate **5470** and a rotationally curved partial mirror **5460**. The lower optics deliver the image light to a user who is wearing the HWC **102**. The compact optical display assembly provides the user with image light **5435** that conveys a displayed image along with scene light **5465** that provides a see-through view of the environment so that user sees the displayed image overlaid onto the view of the environment.

In the upper optics, linearly polarized light is provided by the polarized light source **5450**. Where the polarized light source **5450** can include one or more lights such as LEDs,

QLEDs, laser diodes, fluorescent lights, etc. The polarized light source **5450** can also include a backlight assembly with light scattering surfaces or diffusers to spread the light uniformly across the output area of the polarized light source. Light control films or light control structures can be included as well to control the distribution of the light (also known as the cone angle) that is provided by the polarized light source **5450**. The light control films can include, for example, diffusers, elliptical diffusers, prism films and lenticular lens arrays. The light control structures can include prism arrays, lenticular lenses, cylindrical lenses, Fresnel lenses, refractive lenses, diffractive lenses or other structures that control the angular distribution of the illumination light **5437**. The output surface of the polarized light source **5450** is a polarizer film to ensure that the illumination light **5437** provided to the upper optics is linearly polarized.

The illumination light **5437** provided by the polarized light source **5450** is reflected by a reflective polarizer **5430**. Where the polarizer on the output surface of the polarized light source **5450** and the reflective polarizer **5430** are oriented so that their respective transmission axes are perpendicular to one another. As a result, the majority of the illumination light **5437** provided by the polarized light source **5450** is reflected by the reflective polarizer **5430**. In addition, the reflective polarizer **5430** is angled so that the illumination light **5437** is reflected toward the reflective image source **5410** thereby illuminating the reflective image source **5410** as shown in FIG. **54**.

The illumination light **5437** passes through a field lens **5420** and is then incident onto the reflective image source **5410**. The illumination light **5437** is then reflected by the reflective image source (otherwise referred to as a reflective display herein elsewhere) **5410**. Wherein the reflective image source **5410** can comprise a liquid crystal on silicon (LCOS) display, a ferroelectric liquid crystal on silicon (FLCSO) display, a reflective liquid crystal display, a cholesteric liquid crystal display, a bistable nematic liquid crystal display, or other such reflective display. The display can be a monochrome reflective display that is used with sequential red/green/blue illumination light **5437** or a full color display that is used with white illumination light **5437**. The reflective image source **5410** locally changes the polarization state of the illumination light **5437** in correspondence to the pixel by pixel image content that is displayed by the reflective image source **5410** thereby forming image light **5435**. Wherein if the reflective image source **5410** is a normally white display, the areas of the image light **5435** that correspond to bright areas of the image content end up with a polarization state that is opposite to the polarization state of the illumination light and dark areas of the image light **5435** end up with a polarization state that is the same as the illumination light **5437** (it should be noted that the invention can be used with normally black displays which provide an opposite effect on polarization in the image light). As such, the image light **5435** as initially reflected by the reflective image source **5410** has a mixed polarization state pixel by pixel. The image light **5435** then passes through the field lens **5420** which modifies the distribution of the image light **5435** while preserving the wavefront to match the requirements (such as for example, magnification and focus) of the lower optics. As the image light **5435** passes through the reflective polarizer **5430**, the bright areas of the image light **5435** that have a polarization state that is opposite to the illumination light **5437** are transmitted through the reflective polarizer **5430** and the dark areas of the image light **5435** that have the same polarization state as the illumination light **5437** are reflected back toward the

61

polarized light source **5450**, as a result, the image light **5435** after passing through the reflective polarizer **5430** is linearly polarized with a single polarization state in all the pixels of the image but now with different intensities pixel by pixel. Thus the reflective polarizer **5430** acts first as a reflector for the illumination light **5437** and then second as an analyzer polarizer for the image light **5435**.

As such, the optical axis of the illumination light **5437** is coincident with the optical axis of the image light **5435** between the reflective polarizer **5430** and the reflective image source **5410**. The illumination light **5437** and the image light **5435**.

5435 both pass through the field lens **5420**, but in opposite directions. Wherein the field lens acts to expand the illumination light **5437** so it illuminates the entire active area of the reflective image source **5410** and also to expand the image light **5435** so it fills the eyebox **5482** after passing through the rest of the compact optical display system. By overlapping the portion of the compact optical display assembly associated with the illumination light **5437** with the portion of the compact optical display assembly associated with the image light **5435**, the overall size of the compact optical display assembly is reduced. Given that the focal length associated with the field lens **5420** requires some space in the compact optical display assembly, the reflective polarizer **5430** and the polarized light source **5450** are located in space that would otherwise be unused so the overall size of the display assembly is more compact.

The reflective polarizer **5430** can be a relatively thin film (e.g. 80 microns) or thin plate (e.g. 0.2 mm) as shown in FIG. **54**. The reflective polarizer **5430** can be a wiregrid polarizer such as is available from Asahi Kasei under the name WGF, or a multilayer dielectric film polarizer such as is available from 3M under the name DBEF. As previously described, the reflective polarizer **5430** has two functions. First, the reflective polarizer **5430** reflects the illumination light **5437** provided by the polarized light source **5450** and redirects the illumination light **5437** toward the reflective image source **5410**. Second, the reflective polarizer **5430** acts as an analyzer polarizer to the image light **5435** thereby converting the mixed polarization state of the image light **5435** above the reflective polarizer **5430** to linearly polarized light with a single polarization state below the reflective polarizer **5430**. While the illumination light **5437** incident on the reflective polarizer **5430** is incident on a relatively small portion of the reflective polarizer **5430**, the image light **5435** is incident on the majority of the area of the reflective polarizer **5430**. Consequently, the reflective polarizer **5430** extends at least across the entire area of the field lens **5420** and may extend across the entire area between the field lens **5420** and the beam splitter **5470** as shown in FIG. **54**. In addition, the reflective polarizer **5430** is angled at least in the portion where the illumination light **5437** is incident to redirect the illumination light **5437** toward the reflective image source **5410**. However, since reflective polarizers (such as a wiregrid polarizer) can be relatively insensitive to the incident angle, in a preferred embodiment, the reflective polarizer **5430** is a flat surface angled to redirect the illumination light **5437** toward the reflective image source **5410** wherein the flat surface extends substantially across the entire area between the field lens **5420** and the beam splitter **5470** in one continuously flat surface to make manufacturing easier. The thin film or thin plate of the reflective polarizer **5470** can be retained at the edges to position it at the desired angle and to make the surface flat.

The systems and methods described herein with respect to FIGS. **54** through **57** have a number of advantages. By

62

avoiding grazing angles of the illumination light **5437** and the image light **5435** at all the surfaces in the compact optical display assembly, scattering of light in the assembly is reduced and as a result the contrast of the image presented to the user's eye **5480** is higher with blacker blacks. In addition, the reflective image source **5410** can include a compensating retarder film **5415** as is known to those skilled in the art, to enable the reflective image source **5410** to provide a higher contrast image with more uniform contrast over the area of the displayed image. Further, by providing an optical display assembly that is largely comprised of air, the weight of the compact optical display assembly is substantially reduced. By using coincident optical axes for the illumination light **5437** and the image light **5435** and overlapping the illumination light **5437** and image light **5435** for a substantial portion of the optical display assembly, the overall size of the compact optical display assembly is reduced. Where the coincident optical axes are provided by passing the illumination light **5437** and the image light **5435** in opposite directions through the field lens **5420**. To maintain a uniform polarization state for the illumination light **5437**, the field lens **5420** is made from a low birefringence material such as glass or a plastic such as OKP4 as available from Osaka Gas Chemicals. By positioning the polarized light source **5450** and the associated illumination light **5437** below the field lens **5420**, and by folding the optical path of both the illumination light **5437** at the reflective polarizer **5430** and the image light **5435** at the beam splitter **5470**, the overall height of the compact optical display assembly is greatly reduced. For example the overall height of the compact optical display assembly can be less than 24 mm as measured from the reflective image source **5410** to the bottom edge of the rotationally curved partial mirror **5460** for a display that provides a 30 degree diagonal field of view with a 6x10 mm eyebox.

In a preferred case, the light control structure in the polarized light source **5450** includes a positive lens, such as for example a positive Fresnel lens, a positive diffractive lens or a positive refractive lens. Wherein a positive Fresnel lens or a positive diffractive lens is preferred because they can be very thin. The illumination light **5437** is thereby focused to form a smaller area or pupil at the reflective polarizer **5430** that has a direct relationship to the area of an eyebox **5482** at the other end of the optics wherein image light **5435** is provided to the user's eye **5480** as shown in FIG. **54**. Where the positive lens concentrates the illumination light **5437** from the polarized light source **5450** both in terms of intensity and angular distribution to match the etendue of the optical system and thereby fills the eyebox with image light **5435**. By using the positive lens to converge the light from the polarized light source **5450** as provided to the reflective polarizer **5430** and then using the field lens **5420** to expand the illumination light **5437** to illuminate the active area of the reflective image source **5410**, efficiency is improved since illumination light **5437** is substantially delivered only where needed to form image light **5435**. Further, illumination light **5437** outside the pupil can be controlled by the positive lens and clipped by masked edges of the positive lens. By focusing the illumination light **5437** and clipping light outside the pupil, illumination light **5437** is prevented from impinging adjacent surfaces at grazing angles in the compact optical display assembly to reduce scattering of light and thereby increase contrast in the image provided to the user's eye **5480** by providing blacker blacks.

It should be noted that while FIGS. **54**, **55** and **56** show optical layouts wherein the illumination light **5437** is pro-

vided from behind the rotationally curved partial mirror **5460**, other optical layouts are possible within the invention. The location of the polarized light source **5450** can be changed for example to be at the side of the rotationally curved partial mirror **5460** wherein the reflective polarizer **5430** is oriented to receive the illumination light **5437** from the side. And reflect it toward the reflective image source **5410** (not shown).

In a further embodiment, the portion of the image light **5435** that is reflected back toward the polarized light source **5450** is recycled in the polarized light source **5450** to increase the efficiency of the polarized light source **5450**. In this case, a diffuser and a reflective surface is provided behind the polarized light source **5450** so the polarization of the light is scrambled and reflected back toward the reflective polarizer **5430**.

In yet another embodiment, another reflective polarizer is provided in the polarized light source **5450** and behind the linear polarizer previously disclosed. Wherein the respective transmission axes of the reflective polarizer and the linear polarizer are parallel to one another. The other reflective polarizer then reflects the light back into the backlight that has the polarization state that would not be transmitted by the linear polarizer. The light that is reflected back into the backlight passes through diffusers associated with the polarized light source **5450** where the polarization state is scrambled and reemitted thereby recycling the light and increasing efficiency.

In another embodiment, the system according to the principles of the present invention includes an eye imaging system. FIG. **55** is an illustration of a compact optical display assembly, which includes an eye imaging camera **5592** that captures an image of the user's eye **5480** that is coaxial with the displayed image provided to the user so that a full image of the user's iris can be reliably captured. The eye imaging camera **5592** is reflected into the lower optics by a reflective polarizer **5530** that includes a notch mirror coating, facing the eye imaging camera **5592**, that reflects the wavelengths of light that are captured by the eye imaging camera **5592** (e.g. near infrared wavelengths) while transmitting wavelengths associated with the image light **5435** (e.g. visible wavelengths). Eye light rays **5595** shown in FIG. **55** illustrate how the field of view associated with the eye imaging camera **5592** is a relatively narrow field of view because it is multiply reflected through the lower optics to capture an image of the user's eye **5480**. However, to enable the eye imaging camera **5592** to focus onto the user's eye **5480**, the eye imaging camera **5592** needs to have a very near focus distance (e.g. 35 mm). In addition, the field of view and focus distance of the eye imaging camera must take into account the reducing effect of the optical power provided by the rotationally curved partial mirror **5460**. To increase the efficiency of capturing the light reflected from the user's eye **5480** and thereby enable a brighter image of the eye, the rotationally curved partial mirror **5460** can be coated with a partial mirror coating that acts as a full mirror in the wavelengths being captured by the eye imaging camera **5592**, for example the coating can reflect 50% of visible light associated with the image light and 90% of near infrared light associated with the eye light **5595**. Where the reflections and associated changes in polarization state are similar to those associated with the image light **5435** but in the opposite order since the eye light rays **5595** are coming from the user's eye **5480**. LEDs or other miniature lights are provided adjacent to the user's eye **5480** to illuminate the user's eye **5480** wherein the wavelengths associated with the LED's or other miniature lights are different than the wave-

lengths associated with the image light **5435** such as for example near infrared wavelengths (e.g. 850 nm, 940 nm or 1050 nm). Alternatively, the image light **5435** is used to illuminate the user's eye **5480** and a reflective polarizer **5530** with a low extinction ratio in reflection (e.g. reflective extinction ratio <15) is used so that some of the eye light rays are reflected toward the eye imaging camera **5592**.

In an alternative embodiment, the reflective and partially reflective surfaces can extend laterally to the sides of the areas used for displaying an image to the user. In this case, the eye imaging camera can be located adjacent to the field lens and pointed in a direction to image the user's eye after reflecting from the beam splitter and the rotationally curved partial mirror as shown in FIG. **56**. Where FIG. **56** is an illustration that shows an eye imaging camera **5692** positioned to the side of the field lens **5420** and reflective polarizer **5430**. The eye imaging camera **5692** is pointed such that the field of view captured by the eye imaging camera **5692** includes the user's eye **5480** as illustrated by the eye light rays **5695**. The quarter wave film **5490** is also extended laterally to change the polarization state of the eye light **5695** in the same way that the polarization state of the image light is changed so that the eye light passes through the beam splitter **5470** and quarter wave **5490**, is partially reflected by the rotationally curved partial mirror **5460** and is then reflected by the beam splitter **5470** and is then captured by the eye imaging camera **5692**. By positioning the eye imaging camera **5692** to the side of the field lens **5420** and reflective polarizer **5430**, the complexity of the optics associated with displaying an image to the user is reduced. In addition, the space available for the eye imaging camera **5692** is increased since interferences with the display optics are reduced. By positioning the eye imaging camera **5692** adjacent to the display optics, the eye image is captured nearly coaxially with the displayed image.

In a yet another embodiment, the systems according to the principles of the present invention include a field lens with an internal reflective polarizer and one or more surfaces with optical power. FIG. **57** is an illustration of the upper optics including a field lens **5721** comprised of upper prism **5722** and lower prism **5723**. The upper prism **5722** and the lower prism **5723** can be molded to shape or grind and polished. A reflective polarizer **5724** is interposed on the flat surface between the upper prism **5722** and the lower prism **5723**. The reflective polarizer **5724** can be a wiregrid polarizer film or a multilayer dielectric polarizer as previously mentioned. The reflective polarizer **5724** can be bonded into place with a transparent UV curable adhesive that has the same refractive index as the upper prism **5722** or the lower prism **5723**. Typically the upper prism **5722** and the lower prism **5723** would have the same refractive index. Wherein upper prism **5722** includes an angled surface for illumination light **5437** to be provided to illuminate the reflective image source **5410**. The illumination light is provided by a light source that includes lights such as LEDs, a backlight **5751**, a diffuser **5752** and a polarizer **5753** as has been previously described. The lower prism **5723** includes a curved surface on the exit surface for controlling the wavefront of the image light **5435** as supplied to the lower optics. The upper prism may also include a curved surface on the upper surface next to the reflective image source **5410** as shown in FIG. **57** for manipulating the chief ray angles of the light at the surface of the reflective image source **5410**. Illumination light **5437** is polarized by the polarizer **5753** prior to entering the upper prism **5722**. The transmission axes of the polarizer **5753** and the reflective polarizer **5724** are perpendicular to one another so that the illumination light **5437** is reflected by the

reflective polarizer **5724** so that the illumination light is redirected toward the reflective image source **5410**. The polarization state of the illumination light **5437** is then changed by the reflective image source **5410** in correspondence with the image content to be displayed as previously described and the resulting image light **5435** then passes through the reflective polarizer **5724** to form the bright and dark areas associated with the image that is displayed to the user's eye **5480**.

In another embodiment, the field lens **5721** of FIG. **57** comprises a polarizing beam splitter cube including two prisms, upper prism **5722** and lower prism **5723**. In this case, the reflective polarizer **5724** is replaced by a coating that is polarization sensitive so that light of one polarization state (typically S polarized light for example) is reflected and light of the other polarization state is transmitted. The illumination light **5437** is then provided with the polarization state that is reflected by the coating and the image light is provided with the polarization state that is transmitted by the coating. As shown in FIG. **57**, the beam splitter cube includes one or more curved surfaces in the upper prism **5722** or the lower prism **5723**. The beam splitter cube can also include one or more angled surfaces where the illumination light is supplied. The angled surface can include light control structures such as a microlens array to improve the uniformity of the illumination light **5437**, or a lenticular array to collimate the illumination light **5437**.

In yet another embodiment, the curved surface(s) or the angled surface(s) illustrated in FIG. **57** can be molded onto a rectangularly shaped beam splitter cube by casting a UV curable material (e.g. UV curable acrylic) onto a flat surface of a beam splitter cube, placing a transparent mold with a cavity that has the desired curve onto the flat surface to force the UV curable material into the desired curve and applying UV light to cure the UV curable material. The beam splitter cube can be made of a material that has the same or different refractive index than the UV curable material.

In a further embodiment, polarization sensitive reflective coatings such as dielectric partial mirror coatings, can be used in place of reflective polarizers or beam splitters as shown in FIG. **54**. In this case, the reflective films and plates that comprise the reflective polarizers **5430** and beam splitters **5470** include polarization sensitive coatings that substantially reflect light with one polarization state (e.g. S polarization) while substantially transmitting light with the other polarization state (e.g. P polarization). Since the illumination light source includes a polarizer **5753**, the illumination light **5437** is one polarization state and it is not important that the reflective polarizer **5724** be sensitive to the polarization state in reflection, the polarization state just needs to be maintained and presented uniformly over the surface of the reflective image source **5410**. However, it is important that the reflective polarizer **5724** be highly sensitive to polarization state in transmission (e.g. extinction

ratio >200) to be an effective polarizer analyzer and to provide a high contrast image (e.g. contrast ratio >200) to the user's eye **5480**.

In a further embodiment, the field lens **5721** shown in FIG. **57** can comprise a reflective polarizer **5724** with a curved surface (not shown) instead of a flat surface and wherein the reflective polarizer **5724** is not a film and instead is a polarization sensitive coating, a printed wiregrid polarizer or a molded wiregrid pattern that is then metallized. In this case, the upper prism **5722** and the lower prism **5723** are made as a matched pair with mating curved surfaces that together form the surface of the reflective polarizer. Wherein the polarization sensitive coating, the printed wiregrid or the molded wiregrid pattern are applied to the mating curved surface associated either the upper prism **5722** or the lower prism **5723** and a transparent adhesive is applied to the other mating surface to bond the upper prism **5722** and lower prism **5723** together to form the field lens **5721** with an internal curved reflective polarizer **5721**.

Although embodiments of HWC have been described in language specific to features, systems, computer processes and/or methods, the appended claims are not necessarily limited to the specific features, systems, computer processes and/or methods described. Rather, the specific features, systems, computer processes and/or methods are disclosed as non-limited example implementations of HWC. All documents referenced herein are hereby incorporated by reference.

We claim:

1. An optical system for a head-worn computer, comprising:
 - a polarized light source including a lens with positive optical power positioned in the head-worn computer within an upper optical assembly provides illumination light, wherein the illumination light is projected away from a reflective image source and towards a partially reflective partially transmissive surface and wherein the lens converges the illumination light into a small area in a central region of the partially reflective partially transmissive surface to prevent the illumination light from impinging on sidewalls of the upper optical assembly and thereby reduce scattering;
 - the partially reflective partially transmissive surface positioned to reflect the polarized light through a field lens and towards the reflective display, wherein the field lens expands the illumination light to illuminate an active area of the reflective image source; and
 - an eye image display optical assembly positioned to receive image light reflected from the reflective display, through the field lens and through the partially reflective partially transmissive surface and present the image light to an eye of a user wearing the head-worn computer.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,798,148 B2
APPLICATION NO. : 15/155139
DATED : October 24, 2017
INVENTOR(S) : John N. Border et al.

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On sheet 1 of 82, in Figure 1, Line 3, delete “Extenally” and insert -- Externally --, therefor.

On sheet 8 of 82, in Figure 5, reference numeral 502, Line 1, delete “Light” and insert -- Light --, therefor.

On sheet 21 of 82, in Figure 10, reference numeral 1008, Line 1, delete “Unifrom” and insert -- Uniform --, therefor.

In Column 6, Line 60, delete “HWD” and insert -- HWC --, therefor.

In Column 7, Lines 34-35, delete “device)computer” and insert -- device) computer --, therefor.

In Column 7, Line 36, delete “DLP3000” and insert -- DLP 3000 --, therefor.

In Column 8, Line 1, delete ““on”” and insert -- “on” --, therefor.

In Column 11, Line 55, delete ““off”” and insert -- “off” --, therefor.

In Column 12, Line 52, delete “fiberous” and insert -- fibrous --, therefor.

In Column 19, Lines 14-15, delete “emersive” and insert -- immersive --, therefor.


In Column 27, Line 53, delete “inteface(s)” and insert -- interface(s) --, therefor.

In Column 28, Line 51, after “like)” insert -- . --.

In Column 28, Line 53, delete “2000” and insert -- 20 --, therefor.

In Column 29, Line 5, delete “replacable” and insert -- replaceable --, therefor.

Signed and Sealed this
Twentieth Day of February, 2018



Andrei Iancu
Director of the United States Patent and Trademark Office

CERTIFICATE OF CORRECTION (continued)
U.S. Pat. No. 9,798,148 B2

In Column 32, Line 41, delete “scenerios” and insert -- scenarios --, therefor.

In Column 32, Line 61, delete “a a” and insert -- a --, therefor.

In Column 32, Line 65, delete “len” and insert -- lens --, therefor.

In Column 33, Line 37, after “pdf” insert -- . --.

In Column 33, Line 55, delete “mwsid” and insert -- mwsld --, therefor.

In Column 33, Line 57, after “pdf” insert -- . --.

In Column 38, Line 51, delete “shortpass” and insert -- short pass --, therefor.