



US009852418B2

(12) **United States Patent**
Mardikar

(10) **Patent No.:** **US 9,852,418 B2**
(45) **Date of Patent:** **Dec. 26, 2017**

(54) **TRUSTED SERVICE MANAGER (TSM) ARCHITECTURES AND METHODS**

(71) Applicant: **PAYPAL, INC.**, San Jose, CA (US)

(72) Inventor: **Upendra Mardikar**, San Jose, CA (US)

(73) Assignee: **PayPal, Inc.**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1054 days.

(21) Appl. No.: **13/794,025**

(22) Filed: **Mar. 11, 2013**

(65) **Prior Publication Data**

US 2013/0198086 A1 Aug. 1, 2013

Related U.S. Application Data

(60) Continuation of application No. 13/331,801, filed on Dec. 20, 2011, now Pat. No. 8,417,643, which is a (Continued)

(51) **Int. Cl.**

H04W 12/06 (2009.01)

G06Q 20/32 (2012.01)

(Continued)

(52) **U.S. Cl.**

CPC **G06Q 20/3227** (2013.01); **G06Q 20/1085** (2013.01); **G06Q 20/20** (2013.01); **G06Q 20/204** (2013.01); **G06Q 20/32** (2013.01); **G06Q 20/3223** (2013.01); **G06Q 20/3278** (2013.01); **G06Q 20/367** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC combination set(s) only.

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,355,413 A * 10/1994 Ohno G06Q 20/341
705/67
5,918,158 A * 6/1999 LaPorta H04M 3/5307
340/7.29

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1908981 A 2/2007
EP 1737181 12/2006

(Continued)

OTHER PUBLICATIONS

Abstract of CN 1908981 A, Feb. 7, 2007, Fujitsu Ltd.

(Continued)


Primary Examiner — Mamon Obeid

(74) *Attorney, Agent, or Firm* — Haynes and Boone, LLP

(57) **ABSTRACT**

A client device comprises a first secure element and a second secure element. The first secure element comprises a first computer-readable medium having a payment application comprising instructions for causing the client device to initiate a financial transaction. The second secure element comprises a second computer-readable medium having a security key, a payment instrument, stored authentication data and instructions for generating a secure payment information message responsive to the payment application. The secure payment information message comprises the payment instrument and is encrypted in accordance with the security key.

20 Claims, 9 Drawing Sheets



Related U.S. Application Data

division of application No. 12/339,850, filed on Dec. 19, 2008, now Pat. No. 8,108,318.
 (60) Provisional application No. 61/059,395, filed on Jun. 6, 2008, provisional application No. 61/059,907, filed on Jun. 9, 2008.

(51) **Int. Cl.**

G06Q 20/10 (2012.01)
G06Q 20/20 (2012.01)
G06Q 20/36 (2012.01)
G06Q 20/38 (2012.01)
G06Q 20/40 (2012.01)
G06Q 40/00 (2012.01)
G07C 9/00 (2006.01)
G07F 7/08 (2006.01)
H04L 9/32 (2006.01)
H04L 29/06 (2006.01)

(52) **U.S. Cl.**

CPC **G06Q 20/3674** (2013.01); **G06Q 20/382** (2013.01); **G06Q 20/3821** (2013.01); **G06Q 20/3829** (2013.01); **G06Q 20/40** (2013.01); **G06Q 20/4012** (2013.01); **G06Q 20/40145** (2013.01); **G06Q 40/00** (2013.01); **G07C 9/00087** (2013.01); **G07F 7/0826** (2013.01); **H04L 9/3231** (2013.01); **H04L 63/0823** (2013.01); **H04L 63/0861** (2013.01); **H04W 12/06** (2013.01); **H04L 2209/56** (2013.01); **H04L 2209/80** (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,269,348 B1 7/2001 Pare, Jr. et al.
 6,516,996 B1 * 2/2003 Hippelainen G06Q 20/04
 235/379
 6,581,042 B2 6/2003 Pare, Jr. et al.
 7,206,847 B1 * 4/2007 Alberth, Jr. G06Q 20/102
 235/379
 7,392,941 B2 * 7/2008 Choi G06F 21/84
 235/380
 7,512,567 B2 3/2009 Bommel et al.
 7,543,156 B2 6/2009 Campisi
 7,689,497 B2 * 3/2010 May G06Q 30/08
 705/36 R
 7,702,898 B2 * 4/2010 Tan G06F 21/72
 380/247
 7,844,082 B2 11/2010 Baentsch et al.
 7,877,605 B2 1/2011 Labrou et al.
 7,917,769 B2 3/2011 Campisi
 8,108,318 B2 * 1/2012 Mardikar G06Q 20/1085
 340/5.2
 8,417,643 B2 * 4/2013 Mardikar G06Q 20/1085
 235/379
 8,543,091 B2 * 9/2013 Mardikar H04L 51/38
 380/232
 8,554,689 B2 * 10/2013 Mardikar G06Q 20/1085
 705/64
 8,768,854 B2 * 7/2014 Neville G06Q 20/04
 705/24
 9,060,271 B2 * 6/2015 Mardikar H04L 51/38
 9,143,622 B2 * 9/2015 Sprigg G06Q 20/16
 9,185,234 B2 * 11/2015 Horel G06Q 20/16
 9,185,538 B2 * 11/2015 Oliver G06Q 20/123
 9,232,077 B2 * 1/2016 Yu H04L 12/14
 9,537,839 B2 * 1/2017 Mardikar H04L 51/38
 2001/0018660 A1 * 8/2001 Sehr G06Q 10/02
 705/5
 2001/0049785 A1 * 12/2001 Kawan G06F 21/32
 713/156

2002/0059530 A1 * 5/2002 Talvitie H04L 63/0853
 726/8
 2002/0111918 A1 * 8/2002 Hoshino G06Q 20/06
 705/65
 2002/0152390 A1 * 10/2002 Furuyama G06F 21/64
 713/180
 2003/0154405 A1 * 8/2003 Harrison G06Q 20/341
 726/9
 2003/0171993 A1 * 9/2003 Chappuis G06Q 20/04
 705/16
 2003/0236981 A1 * 12/2003 Marmigere H04L 51/38
 713/168
 2004/0059921 A1 * 3/2004 Bianchi H04L 63/0428
 713/185
 2004/0059923 A1 3/2004 ShamRao
 2004/0157584 A1 * 8/2004 Bensimon H04W 12/06
 455/411
 2005/0033988 A1 * 2/2005 Chandrashekhar . H04L 63/0435
 726/4
 2005/0171898 A1 * 8/2005 Bishop G06Q 20/00
 705/39
 2005/0182710 A1 * 8/2005 Andersson G06Q 20/0425
 705/39
 2005/0187782 A1 * 8/2005 Grear H04L 12/66
 705/64
 2005/0240778 A1 10/2005 Saito
 2005/0246253 A1 * 11/2005 Barthelemy G06Q 20/02
 705/35
 2005/0273609 A1 12/2005 Enronen
 2006/0079284 A1 * 4/2006 Lu H04W 92/08
 455/558
 2006/0080548 A1 * 4/2006 Okamura G06F 21/32
 713/186
 2006/0080549 A1 * 4/2006 Okamura G06F 21/32
 713/186
 2006/0098678 A1 * 5/2006 Tan G06F 21/72
 370/441
 2006/0136735 A1 * 6/2006 Plotkin G06F 21/85
 713/182
 2006/0183489 A1 * 8/2006 Modeo G06Q 20/20
 455/466
 2006/0265743 A1 11/2006 Kusunoki et al.
 2007/0019622 A1 * 1/2007 Alt H04L 29/06027
 370/352
 2007/0022058 A1 1/2007 Labrou et al.
 2007/0033149 A1 * 2/2007 Kanngard G06F 21/31
 705/65
 2007/0092112 A1 4/2007 Awatsu et al.
 2007/0198837 A1 * 8/2007 Koodli H04L 63/0272
 713/171
 2007/0219926 A1 9/2007 Korn
 2007/0220273 A1 9/2007 Campisi
 2007/0255662 A1 * 11/2007 Tumminaro G06Q 20/027
 705/79
 2008/0046988 A1 * 2/2008 Baharis H04L 9/3271
 726/7
 2008/0065885 A1 3/2008 Nagai et al.
 2008/0091614 A1 * 4/2008 Bas Bayod G06Q 20/04
 705/71
 2008/0130895 A1 * 6/2008 Jueneman H04L 9/3066
 380/277
 2008/0287162 A1 * 11/2008 Gaillard H04W 88/02
 455/558
 2009/0046069 A1 * 2/2009 Griffin G06F 1/1626
 345/173
 2009/0164799 A1 6/2009 Takagi
 2009/0182676 A1 * 7/2009 Barbier G06Q 20/102
 705/75
 2009/0191846 A1 7/2009 Shi
 2009/0265552 A1 * 10/2009 Moshir H04L 63/0464
 713/168
 2009/0305673 A1 * 12/2009 Mardikar H04L 51/38
 455/411
 2009/0307142 A1 * 12/2009 Mardikar G06Q 20/1085
 705/72

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0323673 A1* 12/2009 Gabbay H04M 1/2535
370/352
2010/0117791 A1 5/2010 Inoue et al.
2011/0138192 A1* 6/2011 Kocher G06F 21/602
713/189
2011/0179284 A1 7/2011 Suzuki et al.
2011/0238578 A1* 9/2011 Hurry G06Q 20/085
705/65
2012/0089520 A1* 4/2012 Mardikar G06Q 20/1085
705/71
2013/0198086 A1* 8/2013 Mardikar G06Q 20/1085
705/71
2014/0185806 A1* 7/2014 Mardikar H04L 51/38
380/270
2014/0208099 A1* 7/2014 Rajsic H04L 9/14
713/161
2014/0372323 A1* 12/2014 Balasubramanian .. G06Q 20/04
705/76
2017/0111797 A1* 4/2017 Mardikar H04L 51/38

FOREIGN PATENT DOCUMENTS

GB 2396472 6/2004
WO WO 2008034937 3/2008

OTHER PUBLICATIONS

English Translation of Second Chinese Office Action in Chinese
Application No. 200980121058.9.
Chinese Version of Second Office Action in Chinese Application
No. 200980121058.9.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5a




FIG. 5b




FIG. 6a

OTA Payment at POS




FIG. 6b




FIG. 6c

TRUSTED SERVICE MANAGER (TSM) ARCHITECTURES AND METHODS

RELATED APPLICATIONS

This application is a continuation of co-pending U.S. patent application Ser. No. 13/331,801, filed Dec. 20, 2011, which is a divisional application of U.S. patent application Ser. No. 12/339,850, filed Dec. 19, 2008, now U.S. Pat. No. 8,108,318 issued Jan. 31, 2013, which claims priority to U.S. Provisional Application Ser. No. 61/059,395 filed on Jun. 6, 2008, and U.S. Provisional Application Ser. No. 61/059,907 filed on Jun. 9, 2008, all of which are hereby incorporated by reference.

BACKGROUND

Technical Field

Embodiments of the present disclosure generally relate to financial transactions and more particularly to secure financial transactions initiated from an electronic device.

Related Art

“Contactless technology” refers to short distance communications between two devices that are not physically connected. A wide variety of “contactless technology” exists today. Near Field Communication (NFC) is a specific type of “contactless technology” that is of high importance to Mobile Network Operators (MNOs) and to Service Providers (SP), for example, banks. NFC is a short-range high frequency wireless communication technology that enables the exchange of data between devices typically over about a 10 centimeter (or about 4 inch) distance, thus providing a fast, simple and secure way for a user to experience a range of contactless services with a mobile device.

Wireless mobile devices that include an NFC device and a smart card, which may use an RFID for identification purposes, allow a person to make financial transactions, such as purchasing a retail item. Typically, a consumer waves or taps the wireless mobile NFC device on a reader to effect a monetary transfer, and a price of the item is deducted from a total amount that is available and stored on the smart card of the wireless mobile device. Optionally, the amount of the item may be forwarded to a server that can identify the identification code of the particular device and subsequently charge the person for the purchase of the retail item. Such NFC-based point of sale (POS) transactions provide advantages such as eliminating the need to carry cash and enabling a faster financial transaction.

In addition to NFC based POS payments, there are several prevalent models of payments in the mobile industry including Short Message Service (SMS), a communications protocol that allows the interchange of short text messages between mobile devices, and Mobile Internet-based payments, by which customers search for and purchase products and services through electronic communications with online merchants over electronic networks such as the Internet. In this regard, individual customers may frequently engage in transactions with a variety of merchants through, for example, various merchant websites. A credit card may be used for making payments over the Internet. A disadvantage of credit card usage is that online merchants may be exposed to high fraud costs and “chargeback fees,” bearing liability because there is no credit card signature with an online sale.

Using mobile devices, for example personal electronic devices, to make financial transactions involving a transfer of funds from an SP to a vendor via an MNO network using SMS, NFC at the POS and Mobile Internet-based transac-

tions create security issues or problems. For example, such methods involve credit card/financial instrument information, a user name and a password flowing through the network. In addition, a user may, at different times, use several different payment applications for different Service Providers. To the extent that each payment application has its own, separate security registration and verification procedures, the user experience may be cumbersome in that a user must separately load and run separate dedicated applications, each of which must be separately registered and verified for making secure financial transactions. Moreover, the security of each of these applications may be compromised by viruses, Trojans, key loggers and the like since the applications and their security information may be resident on the same data storage element. Moreover, unique biometric identifying information, for example a thumb or finger-print read from a biometric reader on the device, may be captured by any of the several applications loaded on the device. Additional security measures may be desirable to enable more secure Service Provider/Vendor financial transactions over a network or networks.

Mobile payment services using SMS communication may be insecure or use cumbersome security measures. For example, one method involves using an interactive voice response (IVR) call to call back for a PIN. This approach, used for example in PayPal Mobile 1.x, may result in a less-than-optimal user experience for users who may not want to be burdened with entering the PIN. Other approaches involve key management in the software and/or downloading client applications (e.g. interfaces available from kryptext.co.uk and Fortress SMS).

SUMMARY

According to one embodiment, a client device comprises a first secure element and a second secure element. The first secure element comprises a first computer-readable medium having a payment application comprising instructions for causing the client device to initiate a financial transaction. The second secure element comprises a second computer-readable medium having a security key, a payment instrument, stored authentication data and instructions for generating a secure payment information message responsive to the payment application. The secure payment information message comprises the payment instrument and is encrypted in accordance with the security key.

These and other features and advantages of the present invention will be more readily apparent from the detailed description of the embodiments set forth below taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 illustrates a block diagram of an ecosystem or environment for making financial transactions over a network.

FIG. 2 illustrates a payment system according to an example embodiment of the present disclosure.

FIG. 3 illustrates a block diagram of an overview of an example embodiment of a system for conducting a purchase transaction between a customer/user and a merchant/service provider, paid for by making a financial transaction using a financial Service Provider.

FIG. 4 is a block diagram of an exemplary embodiment of a client device.

FIGS. 5a and 5b illustrate an exemplary system for registering a client device.

FIGS. 6a through 6c illustrate an exemplary embodiment of a method 600 of conducting a near-field communication (NFC) transaction at a point of sale (POS).

Exemplary embodiments and their advantages are best understood by referring to the detailed description that follows. It should be appreciated that like reference numerals are used to identify like elements illustrated in one or more of the figures, wherein showings therein are for purposes of illustrating exemplary embodiments and not for purposes of limiting the same.

DETAILED DESCRIPTION

Embodiments of the present disclosure relate to systems and methods for making secure financial transactions over a network. A user may use a client device, for example a personal electronic device, to make a payment from a Service Provider to a merchant/vendor or other payee. The device may include at least two separate secure elements (SEs), one dedicated to running various Service Provider applications (App SE) and another dedicated to providing security for the applications and financial transactions (Crypto SE). The device may include a biometric sensor for providing biometric information to the Crypto SE to provide transactional security for transactions conducted from the device. The device may provide other means of authentication for non-repudiation of a transaction, including a secure payment mode, in which security information or personal identifier number (PIN) may be securely tunneled directly to the Crypto SE, without otherwise being stored or captured on the device or elsewhere. A trusted service manager (TSM) may enable secure SMS communication between and among the user device, the MNO and the Service Providers. The device may be capable of near field communication (NFC) and may be capable of making secure financial transactions at an NFC point of sale (POS).

FIG. 1 illustrates an example embodiment of an “Ecosystem” or environment in which various embodiments of this disclosure may be used. The ecosystem may comprise or involve any number of various parties. One such ecosystem has been developed by the Global System for Mobile communication Association (GSMA), a global trade association representing over 700 GSM mobile phone operators throughout the world. See “Mobile NFC Services,” GSMA, Version 1.0, February 2007. A mobile ecosystem may include various parties, including:

Customer—the customer subscribes to a Mobile Network Operator (MNO) and a service provider and is a customer of a merchant/vendor. The customer may be an individual or a company.

Mobile Network Operator (MNO)—the MNO provides a full range of mobile services to the Customer. Also, the MNO may provide UICC and NFC terminals plus Over the Air (OTA) transport mechanisms. Examples of MNOs include Sprint, Verizon, and ATT.

Service Provider (SP)—the SP provides contactless services to the Customer. Examples of SPs include banks, credit card issuers as well as public transport companies, loyalty programs owners, etc.

Retailer/Merchant—the retailer/merchant may operate an NFC capable point of sales terminal with an NFC reader.

Trusted Service Manager (TSM)—the TSM securely distributes and manages NFC applications and may have, for example, a direct relation or a relation via clearing houses to SPs.

Handset, NFC Chipset and UICC Manufacturer—the manufacturers produce mobile NFC/communication devices and the associated UICC hardware.

Reader Manufacturer—the reader manufacturer makes NFC reader devices.

Application Developer—the application developer designs and develops mobile NFC applications.

Standardization bodies and industry for a—develop a global standard for NFC, enabling interoperability, backward compatibility and future development of NFC applications and services.

NFC-based financial transactions may require cooperation among the various players of the ecosystem. Each player may have its own expectations, for example, the Customer expects convenient, friendly and secure services within a trusted environment; the SPs want their applications to be housed and used in as many mobile devices as possible; and the MNOs want to provide new mobile contactless services that are secure, high quality and consistent with the existing services experienced by the Customer. But although each player may have its own culture and expectations, they all have the same basic requirement—the need for security and confidentiality.

The Trusted Service Manager (TSM), in particular, may help bring trust and convenience to the complex, multi-player NEC ecosystem. The TSM role includes providing a single point of contact for the SPs, e.g., banks, to access their customer base through the MNOs, and to provide secure download and lifecycle management for mobile NFC applications on behalf of the SPs. The TSM may not disrupt the SP’s business model as the TSM may not participate in the transaction stage of the service.

FIG. 2 illustrates a payment system 200 according to an embodiment of the present disclosure. A financial transaction using, for example, an NFC based Point of Sale (POS) payment system, may be made using a client device 400 (see FIG. 4) such as an NFC enabled mobile device through a retailer or merchant server 210. It should be appreciated that although an NFC application is illustrated in this embodiment, the system is not limited to NFC applications, but may also apply to other types of applications, for example, SMS, mobile internet or other forms of communication.

Client device 400 may be implemented using any appropriate combination of hardware and/or software configured for wired and/or wireless communication over a network. For example, in one embodiment, client device 400 may be implemented as a personal computer of a user 220 (also referred to as a “customer” or “consumer”) in communication with the Internet or another network. In other embodiments, client device 400 may be implemented as a wireless telephone, personal digital assistant (PDA), notebook computer and/or other types of electronic computing and/or communications devices. Furthermore, client device 400 may be enabled for NFC, Bluetooth, online, infrared communications and/or other types of communications.

Client device 400 may include various applications as may be desired in particular embodiments to provide desired features to client device 400. For example, in various embodiments, applications may include security applications for implementing client-side security features, programmatic client applications for interfacing with appropriate application programming interfaces (APIs) over a network, or other types of applications.

Client device 400 may further include one or more user identifiers that may be implemented, for example, as operating system registry entries, cookies associated with a browser application, identifiers associated with hardware of

client device **400**, or other appropriate identifiers. Identifiers associated with hardware of the client device **400** may be, for example, the International Mobile Equipment Identity number (IMEI #) or the Secure Element ID number. In one embodiment, a user identifier may be used by a payment service provider or TSM **240** to associate client device **400** or user **220** with a particular account maintained by payment service provider **240** as further described herein.

Merchant server **210** may be maintained, for example, by a retailer or by an online merchant offering various products and/or services in exchange for payment to be received over a network such as the Internet. Merchant server **210** may be configured to accept payment information from user **220** via, for example, client device **400** and/or from a TSM **240** over a network. It should be appreciated that although a user-merchant transaction is illustrated in this embodiment, the system may also be applicable to user-user, merchant-merchant and/or merchant-user transactions.

Merchant server **210** may use a secure gateway **212** to connect to an acquirer **215**. Alternatively, merchant server **210** may connect directly with acquirer **215** or processor **220**. Once verified, acquirer **215**, which has a relation or subscription with payment service provider **240**, processes the transaction through processor **220** or TSM **240**. Brands **225**, for example, payment card issuers, which also have a relation or subscription with the TSM **240**, are then involved in the payment transaction which will enable user **120** to finalize the purchase.

TSM **240** may have data connections **255**, **256**, **257** and **258** with subscriber client device **400**, subscriber acquirer **215**, subscriber processor **220**, and/or subscriber brand **225**, respectively, to communicate and exchange data. Such data connections **255**, **256**, **257** and **258** may take place, for example, via SMS or a Wireless Application Protocol (WAP) over a network. In addition, according to one or more embodiments, payment service provider **240** may have a data connection or connections (not shown) with subscriber Internet companies, Internet mortgage companies, Internet brokers or other Internet companies (not shown).

FIG. 3 illustrates a block diagram illustrating an overview of an example embodiment of a system **300** for conducting a purchase transaction between a customer/user **305** and a merchant/service provider **310**, paid for by making a financial transaction using a financial Service Provider **315**. The overview illustrates the relationships and roles of the various participants in such a transaction. Customer **305** may use device **400** (FIG. 4) that communicates over a network via a Mobile Network Operator (MNO) **320**, for example Sprint, Verizon or other mobile network service providers. Customer **305** may desire to purchase or pay for goods or services provided by merchant/service provider **310**. The customer **305** may desire to make the payment by using financial services provided by SP **315**.

In an example embodiment, a Trusted Service Manager (TSM) **325** may provide a single point of contact for Service Provider **315**, or providers, to access their customers **305** through any of various MNOs **320**. The TSM **325** may manage the secure download and life-cycle management of the mobile payment applications **450** (FIG. 4), for example NFC applications, on behalf of the Service Providers **315**. Although an NFC is illustrated and generally discussed herein with regard to various embodiments, the TSM's role or the role of other entities discussed herein is not limited to NFC and can be applied to other types of electronic communication including technologies such as Bluetooth, infrared, SMS (Short Message Service), and/or other wireless or contactless technologies.

A central issue with mobile NFC or other wireless technology is the need for cooperation among the many involved parties to meet the needs of the customer via secure over-the-air (OTA) link. The payment provider system may act as the TSM **325** to provide a single point of contact for the service provider to access their customer base through the MNOs **320**. More specifically, with the ever changing electronic communications environment including the emergence of NFC, service providers **315** may not be ready or willing to change their working methods or the functions they provide, but they may still want to participate in the new mode of service operation by enhancing the services they offer while maintaining existing core processes. This conflict is solved by the TSM **325** who may help service providers securely distribute and manage contactless services for their customers using the MNOs **320**. In this regard, the TSM may manage the secure download and life-cycle management of the mobile NFC applications on behalf of the service providers.

In an example embodiment, the duties or roles of one or more involved parties may be combined and preformed by a single entity. For example, service providers **315**, banks, or other financial institutions are those entities that typically issue credit and provide authorization for conducting financial transactions between the customer and the merchant. TSM **325** may act as a payment provider system (PP), such as PayPal, and may provide payment processing for online transactions on behalf of the customer so that the customer does not expose payment information directly to the merchant. Instead, the customer may pre-register his account with the payment provider system, map the account to an email address, and then use the payment provider system to make purchases when redirected to the payment provider system from the merchant's site. After the financial transaction is authorized, the TSM **325** or payment provider system completes the transaction.

In online and/or contactless financial transactions, the role of the TSM **325** or payment provider system may be expanded to include or share duties generally associated with the service provider **315** such that customers may use the payment provider system as a credit issuer, and for services such as electronic bank transfers from one account to another account, and/or provide access to other related financial activities through electronic communications over electronic networks operated by the MNO **320**, such as the Internet. The payment provider system may provide an infra-structure, software, and services that enable customers and merchants to make and receive payments.

Client Device

FIG. 4 shows an example embodiment of a block diagram of a client device **400**, for example a communications device such as a mobile phone, cellular phone, personal digital assistant (PDA) or other contactless, electronic communication device. The client device **400** may include a communication chip **405**, an antenna **407**, secure elements **410**, **420**, a keypad **430** and a biometric sensor **440**.

In an example embodiment, the communication chip **405** may support one or more modes of communication, including, for example, Near Field Communication (NFC), Bluetooth, infrared, GSM, UMTS and CDMA cellular phone protocols, SMS and Internet access via a mobile network or local network, for example WAP and/or other wireless or contactless technologies. Near Field Communication is a short-range, high frequency, wireless communication technology which enables the exchange of data between devices over about a very short distance, for example around four inches. NFC may be an extension of the ISO 14443 prox-

imity-card standard, for example contactless card or RFID, and may combine the interface of a smart card and a reader into a single device. An NFC device may communicate with both existing ISO 14443 smart cards and readers, as well as with other NFC devices, and may be compatible with existing contactless infrastructure already in use for public transportation and payment. For example, the device **400** may be compatible with Near Field Communication Point of Sale devices (NFC POS) located at the point of sale at a vendor's place of business.

In an example embodiment, the keypad **430** may include any form of manual key press or touch sensor or other means of inputting information to the device, for example a telephone touch-pad, qwerty or qwertz full or partial keyboard or any other arrangement of input buttons, physical or displayed on a touch screen device, which may be pressed or selected in sequence to input characters, numbers or letters indicative of a PIN. The keypad may include a "Payment Mode" button **439** for placing the device **400** into a payment mode, for example a secure payment mode, for making NFC POS transactions. The "Payment Mode" button may be on the keyboard **430** or anywhere else on the device, or may be on a remote control device coupled with the device for input to the device. In an example embodiment, the secure payment mode may be used even though the telephone communication mode is turned off, for example in an airplane or other location where cell phones are required or requested to be silenced or turned off. In an example embodiment, tunneling circuitry **435** may provide for input directly, without otherwise being stored or captured on the device or elsewhere, to the Crypto or Payment SE **420** (discussed below) when in the secure payment mode, in order to provide secure entry of passwords or PINs during a financial transaction.

Biometric Sensor

In an example embodiment, the biometric sensor **440** may be any sensor that provides data representative of a unique, biological user attribute that may be used to identify a user, for example a finger/thumb-print sensor, retina scan or voice identifier. In this description, the term biometric "sensor" **440** is used to refer not just to the physical sensor that receives the raw biometric data, but to the arrangement of sensor, logic, algorithms and the like that collectively sense, measure, evaluate and generate a data signal or signals representative of the user's biometric signature. The biometric signature data from the biometric sensor **440** may be tunneled through a biometric tunneling circuit **441**, directly to the Crypto SE **420** (discussed below), without being captured by any application on a separate App SE **410** (discussed below). The biometric signature may be stored as authentication data **446** on the Crypto SE **420**.

Secure Elements

In an example embodiment, the device **400** may include at least two Secure Elements (SEs) **410, 420**. An SE may be, for example, a smart card, for example a Universal Integrated Circuit Card (UICC) or smart-card like chip embedded inside device **400**, for example inside of a cell phone. A smart card is a small, relatively tamper-proof computer. The smart card itself may contain a CPU and some non-volatile storage. In most cards, some of the storage may be tamper-proof while the rest may be accessible to any application that can talk to the card. This capability makes it possible for the card to keep some secrets, such as the private keys associated with any certificates it holds. The card itself may perform its own cryptographic operations.

SE **410, 420** may include data storage and may be pre-loaded with applications and/or may be capable of

downloading various applications, for example applications for facilitating financial transactions over a network, key pairs, payment instruments and/or a Certifying Authority (CA) certificate.

In an example embodiment, each SE **410, 420** may have logical, end-to-end security. For example, there may be an authenticated and encrypted channel for communication with the SE. In an example embodiment, an SE may have physical security. For example, an SE may adhere to certain security standards, for example, FIPS 140-2 Level 3 (tamper proof and copy protection) and Common Criteria ISO 15408 EAL 4+, or other standard as required or desired.

In an example embodiment, SE **410, 420** may be global. In other words, an SE may be compatible with a variety of communications protocols or systems. For example, a device may be compatible with GSM, UMTS and/or CDMA cellular phone protocols.

In an example embodiment, SE **410, 420** may be portable, in that it may be easily transferred from one device **400** to another. This may be achieved, for example, by porting the SE **410, 420** or by having Trusted Service Manager (TSM) **325** (FIG. 3) port the applications. Portability may enable a user who has registered his/her device **400** to register any other devices of that user. For example, a user may have one phone for business and one for home, where transactions from each phone are specifically for business or personal use.

In an example embodiment, SE **410, 420** may be compatible with Over-The-Air (OTA) loading or dynamic remote management. For example, applications resident in the App SE may be compatible with OTA management for life cycle management of the applications. For example, resident applications may be managed, updated, altered, and/or fixed to avoid newly discovered vulnerabilities in the applications or update the application to add or change features.

In an example embodiment, SE **410, 420** may be standardized. For example, they may be compatible with standards set out by a known standards or protocols, for example those established by GlobalPlatform.org and/or Bearer Independent Protocol.

In an example embodiment, an SE may work even when the device is turned off. For example, an NFC communication mode may permit a device to make NFC POS transactions or purchases even when a phone's other cellular and/or wireless communication modes are turned off or disabled. This may be particularly desirable and/or convenient in situations where the device is turned off or when the device must be turned off, for example when on an airplane or other location where electronic devices may be required to be turned off. In an example embodiment, secure payment mode button **439** may be used to switch on or prepare the NFC payment components for making an NFC payment without powering up other communications modes. The lower-power, short range of NFC communications may be permissible even where higher power/longer range communications modes are undesirable.

Separate Secure Elements

In an example embodiment, the device may have more than one SE, for example two SEs **410, 420**. One SE may be referred to as an Application SE (App SE) **410** and a separate SE may be referred to as a payment, credential, wallet or crypto SE **420** (Crypto SE) (throughout this description, the term "Crypto SE" is used to refer to any one of payment, credential, wallet or crypto SE, unless otherwise specified). Splitting the App SE **410** from the Crypto SE **420** may enable certifying a particular device **400** for use just once,

through the Crypto SE, while permitting changes to be made to the App SE, changes that may not require additional certification or re-certification since the security and certification information is kept securely on a separate Crypto SE **420**.

App SE

In an example embodiment, the App SE **410** may be designated for and arranged for storing various, resident financial transaction or payment applications **450**, each of which may facilitate financial transactions for a different financial Service Provider. Applications **450** may include, for example, a PayPal application or other payment applications provided by alternate service providers and which facilitate financial transactions over a network.

The App SE **410** may be, for example, a SIM card. A SIM card may securely store a service-subscriber key (IMP used to identify a subscriber). The SIM card allows users to change phones by simply removing the SIM card from one mobile phone and inserting it into another mobile phone or broadband telephony device. The App SE may not include any payment instruments, certificates, keys, certificates or credentials, all of which may be stored in the separate Crypto SE **420**. The App SE **410** may be a dynamic SE, on which applications may be dynamically managed and changed, for example through OTA management. All applications **450** may be signed by a common Trusted Service Manager (TSM) public key. The App SE applications may have virtual environments (like MFC smart cards).

In an example embodiment, applications **450** may include instructions for periodically checking whether an update to the application is available. If the update is available and customer is registered, apps are downloaded and signature is verified. Once the signature is matched, the new application is activated.

OTA Management

In an example embodiment, the applications **450**, for example mobile financial services applications, may be managed over the air (OTA). The OTA management may be securely provided by the TSM for multiple service providers. An App SE may be shared by more than one such application **450** for various SPs. The SPs may desire that the services that they provide via their applications **450** be Secure, Isolated, under their control, have a Life Cycle that they dictate for their respective applications, and be certified. In an example, embodiment, OTA updates, upgrades or other changes for the Apps **450** may require a signature by the TSM public key.

Crypto SE

In an example embodiment, the Crypto SE **420** may be designated for and arranged for loading and storing authentication data **446** (for example a PIN or biometric signature), payment instruments **447**, certificates **424**, crypto keys **421** and other security-related information, including, for example, unique biometric authentication information related to a specific user. The Crypto SE may be primarily static, although certain credentials or other sensitive data may be dynamic. The Crypto SE **420** may provide verification and authentication for multiple applications stored in the App SE **410**.

Splitting the App SE from the Crypto SE may enable a single Trusted Service Manager to verify and authenticate the identity of a user for each of a number of various Service Providers. Splitting the Crypto SE **420** from the App SE **410** may improve user experience by reducing the necessity of registering and verifying various applications **450** separately for each Service Provider and/or re-certification after any changes to any of the applications **450**. Splitting the Crypto

SE from the App SE **410** may also reduce the likelihood of security information on the Crypto SE **420** being compromised by viruses, Trojans, key loggers and the like that may find their way onto the App SE **410**.

5 An authentication application **442**, for example a biometric authentication application, may reside on the Crypto SE **420** and may evaluate the biometric data and compare the data to data from a registered user, or may register the data where the data is being collected as part of a registration or certification procedure.

10 The Crypto SE **420** may also have a communication application **443**, a counter **444** and a clock **445**. The communication application **443** may enable or control communication by the SE. A counter **444** and a clock **445** may be used to identify and/or timestamp particular communications to prevent against replays.

15 In an example embodiment, the Crypto SE **420** may be certified, for example by a credit processing company such as MasterCard or VISA. The Crypto SE may be certified, for example, using the biometric sensor **440** and biometric authentication application **442**. Once the Crypto SE portion is certified, the device **400** is certified for use. Additional financial applications **450** may be added or updated on the App SE without any additional certification or recertification requirement. As a result, the user experience may be enhanced by minimizing the number of times that a user must register or certify his device **400** and/or new or updated applications **450** on his device **400**. This is because the App SE is split or separated from the Crypto SE.

20 In an example embodiment, Crypto SE **420** may include one or several key-pairs, for example an X509 key-pair **421a**, EMV (Europay, MasterCard, VISA) key-pair **421b** or ECC key-pair **421c**. The key-pair or pairs may be pre-loaded on the Crypto SE **420**. A Trusted Service Manager credential **424** or certificate, for example a Root Certificate of Authority (CA) may also be pre-loaded on the Crypto SE **420**.

Public Key Infrastructure

25 In cryptography, a public key infrastructure (PKI) is an arrangement that binds public keys with respective user identities by means of a certificate authority (CA). The user identity must be unique for each CA. The binding is established through the registration and issuance process which, depending on the level of assurance the binding has, may be carried out by software at the CA. A Registration Authority (RA) assures this binding. For each user, the user identity, the public key, their binding, validity conditions and other attributes are made unforgeable in public key certificates issued by the CA. In an example embodiment, a Trusted Service Manager (TSM) may act as the CA and may work with the device and/or chip manufacturers to preload the Root Certificate of Authority (CA) **424** on a client device **400**, for example on the Crypto SE **420** of the device.

Registration

30 FIGS. **5a** and **5b** illustrate an exemplary system **500** for registering client device **400**. In an example embodiment, a device user may be required to register their device with the trusted service manager **505** only one time. Such registration may unlock a payment credential or CA certificate **424** (FIG. **4**) pre-loaded on the device **400**. Registration may include registering a biometric attribute, for example a thumb-print or finger-print, to unlock payment. All applications on the device may be registered with and deployed via the trusted service manager. Registering all applications with one trusted service manager may provide improved security for payment applications loaded and run on the device.

35 In an example embodiment, a user may unlock a payment credential **424** (FIG. **4**) pre-loaded on device **400**. In an

example embodiment, the payment credential may be unlocked by registering the user's unique biometric profile using the biometric sensor **440** (FIG. 4). The credential **424** may be unlocked, for example, by registering a thumb-print twice using a thumb-print/finger print biometric sensor. In an example embodiment, all payment applications **450** (FIG. 4) may be registered and used using a common TSM signature.

In an example, when a customer invokes pre-loaded app **450** (FIG. 4), SCEP/CRMF (Simple Certificate Enrollment Protocol/Certificate Request Message Format) is invoked. A user's TSM credential or certificate **424** is entered and associated with the Service Provider's user account. A random counter may be generated by counter **444** (FIG. 4) on the Crypto SE and stored in the Crypto SE for counter based replay protection. In an alternative embodiment, clock **426 445** (FIG. 4) may generate a timestamp for timestamp-based replay protection. In an example embodiment, this information, for example a tuple, may be sent along with the SCEP and a certificate may be issued to the device.

Payment Account Number Deployment

In an example embodiment, payment account numbers may be deployed OTA. For example, a payment account number may be randomly generated by the Service Provider along with CVV (card verification value). In an example embodiment, a payment account number, CVV and counter/timestamp (to prevent replay attacks) may be encrypted using the Public key of the mobile phone and signed using the TSM's private key.

In an example embodiment, the counter may be checked and payment account number and CVV may be stored in the Crypto SE. The number may be obtained from the Service Provider separately, such as from a representative, either by phone, e-mail, or other method of inquiry.

Customer Manual Entry:

In an example embodiment, a customer may manually enter a known account number using a keypad on the device. This may be done only after activating the biometric credential and registering the device. The App may then load the Crypto SE with a payment instrument **447**, identified by its account number.

Customer NEC Transaction

FIGS. **6a**, **6b** and **6c** illustrate a method **600** of conducting a near-field communication (NFC) transaction at a point of sale (POS). A customer may prepare **602** device **400** for use. Preparing a device for use may include opening the device **400**, taking the device in hand, selecting "payment mode," entering a payment application or other suitable method if the device does not need to be "opened" for use. For example, user **220** may select a payment mode or secure payment mode by pressing a payment mode button provided on the device **400** or otherwise appropriately selecting payment, for example by saying "Payment" or other word associated with such a function for a device with voice recognition technology or any other appropriate method of selection as appropriate for a particular device.

In an exemplary embodiment, preparing the device for payment may prompt a payment application resident on the App SE **410** of the device **400** to check **604** the biometric sensor for biometric input. A user may then input **606** their biometric identifying data (ID) or signature by placing or swiping a thumb or finger on biometric sensor **440**. The input biometric ID may be directly sent or tunnelled **608** to Crypto SE **420** via provided tunnel circuitry **441**. In an example embodiment, the tunnel circuitry **441** may be FIPS

140-2 level 3 compliant and may be arranged so that biometric ID is input directly into the Crypto SE for authentication/unlocking.

In an example embodiment, the application resident on the App SE **410** may send a message **610** to Crypto SE **420** for approval/disapproval of the payment and payment information in the event of approval. The Crypto SE may contain an Access Control System that may authenticate Applications in App SE for the types of requests Applications on the App SE **410** are entitled to perform. Once a user's biometric identity is authenticated properly, the Crypto SE **420** may send **612** an approval/disapproval message and payment or other information to the App SE. The App SE **410** may then send the payment information **614** to the communication chip **405** for further transmission or transport to a reader or other communication reception device located at the POS, for example a POS NFC reader located at a merchant/vendor's place of business.

In other example embodiments, the Crypto SE **420** may establish a direct, secure transmission between the Crypto SE **410** and the POS. The secure transmission may be established, for example, using technologies like Secure Socket Layer (SSL), Internet Protocol Security (IPSec) or regular symmetric/asymmetric encryption, if supported by the POS. In such embodiments, the payment instruments may also never be shown in clear in the App SE. If SSL or IPSec is used, a known Root CA may be stored in Crypto SE. The POS certificate may be issued using this Root CA. During the SSL or IPSec handshake, the certificate chain containing POS's certificate and Root CA is sent by POS to crypto SE directly. The Crypto SE may then work as an SSL/IPSec/Crypto Client. The Crypto SE may verify the POS's certificate against the Root CA that it already has. If the certificate matches, it may give payment information using an SSL/IPSec/secure channel.

The device **400** may transmit the information, for example by NFC technology, when the customer waves or taps the device on or near the POS reader **650**. The Payment information may include payment information, such as amount and account number, and may include a CVV. In other embodiments, the payment information may be transmitted by alternate methods of communication as desired or necessary in a particular embodiment or circumstance, for example by SMS, discussed below.

When a payment is made at a merchant POS **650** using Visa/MC/AmEx, the last four digits of the payment instrument may be sent to the TSM (using, for example, an application provided on the App SE by the TSM). This information may be correlated with signature information, collated and offered to financial institutions like Banks, Visa/MC, as well as Charles Schwab, eTrade, Amazon as service by ensuring the privacy information is not leaked. The only information collected by the TSM may be the last four digits of the financial instrument and signature information. The TSM may collect and analyze such data and offer information developed through that analysis as a fraud engine. Signature information is used to identify the client device and its user.

Authentication to the Crypto Authorization Application Instead of on the POS

In an example embodiment, customer **220** may need to enter a PIN to complete a payment, for example where a debit card is used. Using a PIN may provide an additional level of security. In other embodiments, a PIN or other alpha-numeric code may be required and may be entered securely, in conjunction with biometric authentication or alone. A POS PIN may be entered directly onto keyboard

430 on device 400, instead of entering the PIN on a POS keypad or making a signature at a POS electronic signature screen.

In an example embodiment, a user may first authenticate their phone 602-608 for secure keyboard PIN entry by using the biometric sensor and biometric authentication application on their device, as discussed above. Biometric authentication of the phone may open or create the secure tunnel circuitry, directly from the keyboard to the Crypto SE, for secure keyboard entry on the device 400. A payment application on the App SE may prompt a user to enter a PIN 616, the user may enter a PIN 618, and the PIN may be tunneled 620 directly to the Crypto SE 420 via tunneling circuitry 441. The Crypto SE 420 may behave as Chip and PIN Authentication and/or as ARQC-ARPC. The secure entry mode may be initiated by pressing a payment or secure payment key 439 on the device 400, by biometric authentication of the device and/or by the payment application when entry of a PIN is required.

In some POS payment systems, the customer's PIN may otherwise be entered on a keypad attached to a card scanner or NFC reader or a signature made on a pressure-sensitive surface at the POS that electronically records a signature as a record of the authentication of the transaction, for example a credit card, electronic check or debit card transaction. Since banking regulations do not permit entering a PIN on a non-encrypted PIN pad, a client device with a secure payment mode with secure keyboard tunneling circuitry and a separate, dedicated Crypto SE may provide an acceptable, convenient and desirable means for making a debit card, credit card, electronic check or other transaction in which use of a secure PIN entry is required or desired.

In an example embodiment, a user may first authenticate the device biometrically and then be prompted to enter a PIN. When fully authenticated by the PIN and/or the biometric signature, the Crypto SE 420 may send 612 the payment information to the App SE 410 for forwarding via NFC or other communication mode. The entire payment may be made with the device "off", in other words when the cellular phone, WAP or other communications modes are disabled and only the NFC mode may be operational. In this way, a user may make a payment without turning a device completely on, which may be convenient on an airplane or other location where wireless telephone devices or other communications devices are required to be turned off or desired to be left off.

The payment information may be transmitted to the reader 650 at the POS, be forwarded further to and processed by merchant server 210, to acquirer/processor 215, 220, brands 225 and service provider (SP) 315, for example a card issuer or bank, to complete the payment transaction from an account of the user to the merchant/vendor in accordance with the payment information sent from the client device 400.

Secure SMS for Transaction

In an example embodiment, payments and financial transactions may be made using secure SMS communication. A TSM may generate a random key (AES-256 and SHA-512) and send the random key to a Crypto SE of a client device. The keys may be encrypted using the client device's public certificate and may be signed by the TSM. The keys may be sent over the SMS channel, for example through multiple SMSes. The client device may then verify the signature, decrypt the keys and store the keys in Crypto SE. The Crypto SE, in turn, may be able to generate, encrypt, and send

encrypted SIMs to the TSM. The TSM may generate, or establish keys using the Diffie-Hellman (D-H) key exchange.

In an example embodiment, a user may desire to make payments using an SMS interface, where NFC is not available and where WAP is either unavailable or undesirable. Having a separate App SE and Crypto SE may enable secure SMS communication without those drawbacks. The TSM may preload a public key inside a Crypto SE, for example an SIM/SE. A client application on the App SE of a client device, with help of the Crypto SE, may generate a symmetric key and a MAC key. The application may then encrypt payload with the symmetric key and MAC key. The keys will be encrypted using the TSM's public key that can be then used to create a digital envelope. The size of an SMS is 160 characters total. If 1024 bits are used, then the binary value of data is 128 bytes. If the 128 bytes is Base 64 encoded, then the output is 171 bytes and there is no room to send the message itself. Hence Elliptic Curve Cryptography (ECC) may be used. ECC output is 24 bytes and Base 64 encoding this, the output is 32 bytes. The payload can be then less than $160 - 32 = 128$ bytes. In an example embodiment, the client device may also be able to send secure SMS messages to one another as well.

Secure SMS may be implemented by a TSM in conjunction with various cell phone manufacturers, for example Nokia, with a SIM card and/or SE on mobile phones and ECC. The keys are dynamic and managed by hardware. In an example embodiment, when an SMS is sent, the data is encrypted using AES-256, and a counter is used for replay protection and SHA-512 HMAC is attached. SHA-512 HMAC is 64 bytes in binary. Truncation is used to bring the data to 32 bytes of BASE-64 encoding. The TSM may receive an SMS and determine to whom the message is to be sent or forwarded—and forward the message to the appropriate addressee, for example a Service Provider, to complete the payment transaction. The TSM may also have the keys registered for a recipient's device. The TSM may decrypt and re-encrypt the message using receiver phone's keys. Timestamps may be used to prevent replays. Keys may be rotated periodically using the SMS key establishment scheme.

In implementation of the various embodiments, the mobile device may comprise a personal computing device, such as a personal computer, laptop, PDA, cellular phone or other personal computing or communication devices. The payment provider system may comprise a network computing device, such as a server or a plurality of servers, computers, or processors, combined to define a computer system or network to provide the payment services provided by a payment provider system.

In this regard, a computer system may include a bus or other communication mechanism for communicating information, which interconnects subsystems and components, such as processing component (e.g., processor, micro-controller, digital signal processor (DSP), etc.), system memory component (e.g., RAM), static storage component (e.g., ROM), disk drive component (e.g., magnetic or optical), network interface component (e.g., modem or Ethernet card), display component (e.g., CRT or LCD), input component (e.g., keyboard or keypad), and/or cursor control component (e.g., mouse or trackball). In one embodiment, disk drive component may comprise a database having one or more disk drive components.

The computer system may perform specific operations by processor and executing one or more sequences of one or more instructions contained in a system memory compo-

15

ment. Such instructions may be read into the system memory component from another computer readable medium, such as static storage component or disk drive component. In other embodiments, hard-wired circuitry may be used in place of or in combination with software instructions to implement the invention.

Logic may be encoded in a computer readable medium, which may refer to any medium that participates in providing instructions to the processor for execution. Such a medium may take many forms, including but not limited to, non-volatile media, volatile media, and transmission media. In various implementations, non-volatile media includes optical or magnetic disks, such as disk drive component, volatile media includes dynamic memory, such as system memory component, and transmission media includes coaxial cables, copper wire, and fiber optics, including wires that comprise bus. In one example, transmission media may take the form of acoustic or light waves, such as those generated during radio wave and infrared data communications.

Some common forms of computer readable media includes, for example, floppy disk, flexible disk, hard disk, magnetic tape, any other magnetic medium, CD-ROM, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, RAM, PROM, EPROM, FLASH-EPROM, any other memory chip or cartridge, carrier wave, or any other medium from which a computer is adapted.

In various embodiments, execution of instruction sequences for practicing the invention may be performed by a computer system. In various other embodiments, a plurality of computer systems coupled by communication link (e.g., LAN, WLAN, PTSN, or various other wired or wireless networks) may perform instruction sequences to practice the invention in coordination with one another.

Computer system may transmit and receive messages, data, information and instructions, including one or more programs (i.e., application code) through communication link and communication interface. Received program code may be executed by processor as received and/or stored in disk drive component or some other non-volatile storage component for execution.

Where applicable, various embodiments provided by the present disclosure may be implemented using hardware, software, or combinations of hardware and software. Also, where applicable, the various hardware components and/or software components set forth herein may be combined into composite components comprising software, hardware, and/or both without departing from the spirit of the present disclosure. Where applicable, the various hardware components and/or software components set forth herein may be separated into sub-components comprising software, hardware, or both without departing from the scope of the present disclosure. In addition, where applicable, it is contemplated that software components may be implemented as hardware components and vice-versa.

Software, in accordance with the present disclosure, such as program code and/or data, may be stored on one or more computer readable mediums. It is also contemplated that software identified herein may be implemented using one or more general purpose or specific purpose computers and/or computer systems, networked and/or otherwise. Where applicable, the ordering of various steps described herein may be changed, combined into composite steps, and/or separated into sub-steps to provide features described herein.

16

The foregoing disclosure is not intended to limit the present invention to the precise forms or particular fields of use disclosed. It is contemplated that various alternate embodiments and/or modifications to the present invention, whether explicitly described or implied herein, are possible in light of the disclosure. Having thus described various example embodiments of the disclosure, persons of ordinary skill in the art will recognize that changes may be made in form and detail without departing from the scope of the invention. Thus, the invention is limited only by the claims.

What is claimed is:

1. A trusted service manager (TSM) server comprising:
a non-transitory machine-readable memory containing instructions to facilitate transactions via short message service (SMS) over a network; and

one or more hardware processors coupled to the non-transitory machine-readable memory and configured to read instructions from the non-transitory machine-readable memory to cause the TSM server to perform operations comprising:

generating a random key for a client device;

encrypting the random key using a public certificate of the client device;

transmitting, via a first encrypted channel, the random key to a crypto secure element included in the client device;

registering the client device with the TSM server via the crypto secure element by storing authentication data in the crypto secure element, the client device being registered exclusive of an app secure element that is physically separate from the crypto secure element, wherein the random key, the authentication data, and data corresponding to a payment instrument are excluded from the app secure element;

signing a payment application using a public key of the TSM server;

transmitting, via a second encrypted channel, the payment application to the app secure element of the client device;

after the transmitting the payment application to the app secure element, receiving, from the payment application, an encrypted SMS message comprising a payment certificate and an address of a service provider (SP), wherein the payment certificate is sent from the crypto secure element to the payment application in response to the crypto secure element authenticating biometric information of a user associated with the client device inputted to the crypto secure element via a secure tunnel, and wherein the SMS message from the client device is encrypted in accordance with the random key; decrypting the SMS message using the random key and determining the address of the SP;

re-encrypting the SMS message using a second stored key corresponding to the SP; and

forwarding the re-encrypted SMS message to the SP.

2. The trusted service manager server of claim 1, wherein the operations further comprise:

signing a second payment application using the public key of the TSM server, the second payment application corresponding to a second SP that is different from the SP; and

transmitting the second payment application to the app secure element, wherein the transmitting the payment application and the transmitting the second payment application are performed based on the registering the client device with the TSM server.

3. The trusted service manager server of claim 1, wherein the random key is established using Diffie-Hellman (D-H) key exchange.

4. The trusted service manager server of claim 1, wherein the encrypted SMS message is a secure SMS message addressed to the trusted service manager (TSM) and comprising the address for the service provider (SP) to which the TSM server is to forward the encrypted SMS message.

5. The trusted service manager server of claim 1, wherein the encrypted SMS message is sent by a secure SMS, wherein when an SMS is sent, the message is encrypted using AES-256, and SHA-512 HMAC is attached.

6. The trusted service manager server of claim 1, wherein: the encrypted SMS message is sent by a secure SMS, wherein when an SMS is sent, the message is encrypted using AES-256, and SHA-512 HMAC is attached, and the SHA-512 HMAC is 64 bytes in binary and truncation is used to bring data to 32 bytes of BASE-64 encoding.

7. The trusted service manager server of claim 1, wherein: the encrypted SMS message is sent by a secure SMS, wherein when an SMS is sent, the message is encrypted using AES-256, and SHA-512 HMAC is attached, and a counter tags the encrypted SMS message for replay protection.

8. A method of facilitating transactions via short message service (SMS) over a network comprising:

generating, by a trusted service manager (TSM) server, a random key for a client device;

encrypting the random key using a public certificate of the client device;

transmitting, via a first encrypted channel, the random key to a crypto secure element included in the client device;

registering the client device with the TSM server via the crypto secure element by storing authentication data in the crypto secure element, the client device being

registered exclusive of an app secure element that is physically separate from the crypto secure element,

wherein the random key, the authentication data, and data corresponding to a payment instrument are excluded from the app secure element;

signing a payment application using a public key of the TSM server;

transmitting, via a second encrypted channel, the payment application to the app secure element of the client device;

after the transmitting the payment application to the app secure element, receiving, from the payment application, an encrypted SMS message comprising a payment certificate and an address of a service provider (SP), wherein the payment certificate is sent from the crypto secure element to the payment application in response to the crypto secure element authenticating biometric information of a user associated with the client device inputted to the crypto secure element via a secure tunnel, and wherein the SMS message from the client device is encrypted in accordance with the random key;

decrypting the SMS message using the random key and determining the address of the SP;

re-encrypting the SMS message using a second stored key corresponding to the SP; and

forwarding the re-encrypted SMS message to the SP.

9. The method of claim 8, wherein the random key comprises AES-256 and SHA-512.

10. The method of claim 8, wherein the random key is established using Diffie-Hellman (D-H) key exchange.

11. The method of claim 8, wherein the encrypted SMS message is a secure SMS message addressed to the trusted

service manager (TSM) server and comprising the address for the service provider (SP) to which the TSM server is to forward the encrypted SMS message.

12. The method of claim 8, wherein the encrypted SMS message is sent by a secure SMS, wherein when an SMS is sent, the message is encrypted using AES-256, and SHA-512 HMAC is attached.

13. The method of claim 8, wherein:

the encrypted SMS message is sent by a secure SMS, wherein when an SMS is sent, the message is encrypted using AES-256, and SHA-512 HMAC is attached, and the SHA-512 HMAC is 64 bytes in binary and truncation is used to bring data to 32 bytes of BASE-64 encoding.

14. The method of claim 8, wherein:

the encrypted SMS message is sent by a secure SMS, wherein when an SMS is sent, the message is encrypted using AES-256, and SHA-512 HMAC is attached, and a counter tags the encrypted SMS message for replay protection.

15. A non-transitory machine-readable medium having stored thereon machine-readable instructions executable to cause a trusted service manager (TSM) server to perform operations comprising:

generating a random key for a client device;

encrypting the random key using a public certificate of the client device;

transmitting, via a first encrypted channel, the random key to a crypto secure element included in the client device;

registering the client device with the TSM server via the crypto secure element by storing authentication data in the crypto secure element, the client device being registered exclusive of an app secure element that is physically separate from the crypto secure element, wherein the random key, the authentication data, and data corresponding to a payment instrument are excluded from the app secure element;

signing a payment application using a public key of the TSM server;

transmitting, via a second encrypted channel, the payment application to the app secure element of the client device;

after the transmitting the payment application to the app secure element, receiving, from the payment application, an encrypted SMS message comprising a payment certificate and an address of a service provider (SP), wherein the payment certificate is sent from the crypto secure element to the payment application in response to the crypto secure element authenticating biometric information of a user associated with the client device inputted to the crypto secure element via a secure tunnel, and wherein the SMS message from the client device is encrypted in accordance with the random key;

decrypting the SMS message using the random key and determining the address of the SP;

re-encrypting the SMS message using a second stored key corresponding to the SP; and

forwarding the re-encrypted SMS message to the SP.

16. The non-transitory machine-readable medium of claim 15, wherein the random key comprises AES-256 and SHA-512.

17. The non-transitory machine-readable medium of claim 15, wherein the random key is established using Diffie-Hellman (D-H) key exchange.

18. The non-transitory machine-readable medium of claim 15, wherein the encrypted SMS message is a secure SMS message addressed to the trusted service manager

(TSM) server and comprising the address for the service provider (SP) to which the TSM is to forward the encrypted SMS message.

19. The non-transitory machine-readable medium of claim **15**, wherein the encrypted SMS message is sent by a secure SMS, wherein when an SMS is sent, the message is encrypted using AES-256, and SHA-512 HMAC is attached.

20. The non-transitory machine-readable medium of claim **15**, wherein:

the encrypted SMS message is sent by a secure SMS, wherein when an SMS is sent, the message is encrypted using AES-256, and SHA-512 HMAC is attached, and the SHA-512 HMAC is 64 bytes in binary and truncation is used to bring data to 32 bytes of BASE-64 encoding.

* * * * *

15