

(12) **United States Patent**  
**Samson**

(10) **Patent No.:** **US 9,852,714 B2**  
(45) **Date of Patent:** **\*Dec. 26, 2017**

(54) **ENERGY CONSERVATION IN A  
CONTROLLER USING DYNAMIC  
FREQUENCY SELECTION**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Intel Corporation**, Santa Clara, CA  
(US)

5,953,020 A 9/1999 Wang et al.  
7,634,668 B2 12/2009 White et al.  
(Continued)

(72) Inventor: **Eric C. Samson**, Folsom, CA (US)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Intel Corporation**, Santa Clara, CA  
(US)

CN 1666166 A 9/2005  
WO 2013/101829 A1 7/2013

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 83 days.  
  
This patent is subject to a terminal dis-  
claimer.

OTHER PUBLICATIONS

International Preliminary Report on Patentability received for PCT  
Application No. PCT/US2012/071653, dated Jul. 10, 2014, 7 pages.  
(Continued)

(21) Appl. No.: **14/747,682**

*Primary Examiner* — Nitin Patel

(22) Filed: **Jun. 23, 2015**

*Assistant Examiner* — Danny Chan

(74) *Attorney, Agent, or Firm* — Jordan IP Law, LLC

(65) **Prior Publication Data**

US 2015/0294648 A1 Oct. 15, 2015

**Related U.S. Application Data**

(63) Continuation of application No. 13/340,129, filed on  
Dec. 29, 2011.

(51) **Int. Cl.**

**G09G 5/18** (2006.01)  
**G06F 1/32** (2006.01)  
**G09G 5/36** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G09G 5/18** (2013.01); **G09G 5/363**  
(2013.01); **G06F 1/324** (2013.01);  
(Continued)

(58) **Field of Classification Search**


None

See application file for complete search history.

(57) **ABSTRACT**

Systems and methods of adjusting a frequency of a graphics controller may include a logic to determine a metric associated with an input/output (I/O) queue. The metric may be used to determine whether an I/O limited condition exists. The I/O limited condition may be associated with a graphics controller. There may be a logic to cause a frequency of the graphics controller to be decreased when the I/O limited condition exists, and a logic to cause the frequency of the graphics controller to be increased when the I/O limited condition does not exist. The I/O limited condition may exist when a magnitude of the metric is equal to or greater than a first threshold. The I/O limited condition may not exist when the magnitude of the metric is equal to or less than a second threshold.

**20 Claims, 6 Drawing Sheets**



(52) **U.S. Cl.**  
CPC ... *G09G 2310/08* (2013.01); *G09G 2330/021*  
(2013.01); *G09G 2360/02* (2013.01); *G09G*  
*2360/12* (2013.01)


2010/0274938	A1	10/2010	Anand et al.
2011/0022871	A1	1/2011	Bouvier et al.
2012/0169746	A1	7/2012	Samson
2014/0002467	A1	1/2014	Linda


(56) **References Cited**  
U.S. PATENT DOCUMENTS

7,886,164	B1	2/2011	Alben et al.
8,099,618	B2	1/2012	Vorbach et al.
8,193,831	B1	6/2012	Kadosh et al.
8,250,394	B2	8/2012	Agrawal
8,335,941	B2	12/2012	Chang et al.
2001/0011356	A1	8/2001	Lee et al.
2001/0029556	A1	10/2001	Priem et al.
2002/0099964	A1	7/2002	Zdravkovic
2002/0169990	A1	11/2002	Sherburne, Jr.
2003/0007394	A1	1/2003	Phi et al.
2003/0115428	A1	6/2003	Zaccarin et al.
2003/0210247	A1	11/2003	Cui et al.
2005/0289377	A1	12/2005	Luong et al.
2006/0161799	A1	7/2006	Degenhardt
2006/0259804	A1	11/2006	Fry
2007/0206683	A1	9/2007	Lin
2008/0235364	A1	9/2008	Gorbatov et al.
2010/0218029	A1	8/2010	Floyd et al.

OTHER PUBLICATIONS

Supplementary European Search Report for European Patent Application No. 12862668.6, dated Jun. 1, 2015, 7 pages.  
International Preliminary Report on Patentability and Written Opinion received for PCT Patent Application No. PCT/US2012/071653, dated Jul. 10, 2014, 7 pages.  
Office Action received for U.S. Appl. No. 13/539,414, dated Nov. 10, 2014, 12 pages.  
Office Action received for U.S. Appl. No. 13/539,414, dated Jul. 16, 2014, 16 pages.  
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2012/071653 dated Apr. 29, 2013.  
Hurd, “Programmable Power Performance Optimization for Graphics Cores”, U.S. Appl. No. 13/539,414, filed Jun. 30, 2012, 47 pages.  
European Communication pursuant to Article 94(3) EPC, for Application No. 12 862 668.6 1094, dated Jan. 26, 2016, 6 pages.  
Office Action for European Patent Application No. 12862668.6, dated Dec. 23, 2016, 6 pages.  
Texas Instruments, “Green-Mode Flyback Controller”, Jan. 1, 2009, [farnell.com/datasheets/1535775.pdf](http://farnell.com/datasheets/1535775.pdf), 39 pages.

**FIG. 1**

**FIG. 2**




FIG. 3






FIG. 4





FIG. 5

**FIG. 6**



## 1

# ENERGY CONSERVATION IN A CONTROLLER USING DYNAMIC FREQUENCY SELECTION

## CROSS-REFERENCE TO RELATED APPLICATIONS

The present application claims the benefit of priority to U.S. Non-Provisional patent application Ser. No. 13/340,129 filed Dec. 29, 2011.

## BACKGROUND

A graphics workload may exhibit diverse behaviors during a course of a frame draw, wherein processing different parts of a frame may be limited by different factors. For example, the processing of one part of the frame may be limited by available resources inside a graphics controller, while the processing of another part of the frame may be limited by input/output (I/O) bandwidth.

## BRIEF DESCRIPTION OF THE DRAWINGS

The various advantages of the embodiments of the present invention will become apparent to one skilled in the art by reading the following specification and appended claims, and by referencing the following drawings, in which:

FIG. 1 is a block diagram that illustrates an example computer system, in accordance with some embodiments;

FIG. 2 is a block diagram that illustrates an example graphics system, in accordance with some embodiments;

FIG. 3 is a diagram that illustrates example graphic frames, in accordance with some embodiments;

FIG. 4 is a diagram that illustrates thresholds that may be used with an input/output (I/O) metric, in accordance with some embodiments;

FIG. 5 is a block diagram that illustrates an example I/O metric and timeout periods, in accordance with some embodiments; and

FIG. 6 is a flowchart of an example method of adjusting the frequency of a graphics controller based on an I/O limited condition, in accordance with some embodiments.

## DETAILED DESCRIPTION

Embodiments may involve an apparatus which may include logic to determine a metric associated with an input/output (I/O) queue. The metric may be used to determine whether an I/O limited condition exists, wherein the I/O limited condition may be associated with a graphics controller. There may be logic to cause a frequency of the graphics controller to be decreased when the I/O limited condition exists, and logic to cause the frequency of the graphics controller to be increased when the I/O limited condition does not exist.

Embodiments may involve a system which may include a processor and a graphics controller coupled to the processor. The graphics controller may be configured to operate at a decreased frequency based on being input/output (I/O) limited and at an increased frequency based on not being I/O limited. An I/O limited condition may exist when a magnitude of a metric associated with an I/O queue is at or greater than a first threshold. The I/O limited condition may not exist when the magnitude of the metric is at or less than a second threshold.

Embodiments may involve a computer implemented method which may include determining a metric associated

## 2

with an input/output (I/O) queue. A magnitude of the metric may be high when the I/O queue is full and low when the I/O queue is not full, wherein the I/O queue may be associated with a graphics controller. The method may also include decreasing a frequency of the graphics controller when the magnitude of the metric is at or greater than a first threshold, and increasing the frequency of the graphics controller when the magnitude of the metric is at or less than a second threshold. The second threshold may be associated with a value less than a value associated with the first threshold.

Embodiments may involve a system which may include a processor, an external power supply coupled to the processor, and a graphics controller coupled to the processor. The system may include logic to decrease a frequency of the graphics controller based on being input/output (I/O) limited and increase the frequency based on not being I/O limited. An I/O limited condition may exist when a magnitude of a metric associated with an I/O queue is at or greater than a first threshold. The I/O limited condition may not exist when the magnitude of the metric is at or less than a second threshold.

Turning to FIG. 1, a block diagram that illustrates an example computer system **100** is shown, in accordance with some embodiments. The computer system **100** may include a central processing unit (CPU) **105**, a graphics and memory controller hub (GMCH) **110**, and an input/output controller hub (ICH) **125**. The GMCH **110** may be coupled to the CPU **105** via bus **107**. The ICH **125** may be coupled to the GMCH **110** via bus **122**. The GMCH **110** may also be coupled to memory devices **115** and display devices **120**. The ICH **125** may be coupled to I/O devices **130**. The GMCH **110** may include a graphics system **200** (shown in FIG. 2). Although the CPU **105**, the GMCH **110** and the ICH **125** may be illustrated as separate components, the functions of two or more of these components may be combined. A power supply **150** may be used to provide power to the computer system **100**. The power supply **150** may be a battery or an external power source. The computer system **100** may also include many other components; however, for simplicity, they are not shown.

Turning to FIG. 2, a block diagram that illustrates an example graphics system **200** is shown, in accordance with some embodiments. The graphics system **200** may include a graphics controller **205**, frequency decision logic **210**, graphics I/O controller **215**, I/O limiting detector **220**, I/O limiting logic generator, and I/O queue **230**.

The I/O queue **230** may be configured to store graphics I/O requests so that they may be managed by the graphics I/O controller **215**. Since the graphics controller **205** may operate at much faster speed than the graphics I/O controller **215**, the graphics controller **205** may be able to make many more I/O requests than the graphics I/O controller **215** may be capable of handling those requests. As a result, the graphics controller **205** may have to wait until the I/O requests are serviced. This condition may be referred to as being I/O limited. In general, when the I/O queue **230** is full, the graphics controller **205** may be I/O limited. When the I/O queue **230** is not full, the graphics controller **205** may not be I/O limited.

The graphics controller **205** may be operating at a base frequency. For some embodiments, when the I/O limited condition exists, the frequency of the graphics controller **205** may be decreased to a lower frequency because there may not be any performance advantage for the graphics controller **205** to stay at the base frequency. Reducing the frequency of the graphics controller **205** when the I/O limited condition exists may be advantageous because it may enable reducing



power consumption of the graphics controller **205** relative to the power consumption at the base frequency.

The I/O limiting logic generator **225** may be coupled to the graphics I/O controller **215** and the I/O queue **230**. For some embodiments, the I/O limiting logic generator **225** may be configured to monitor an I/O metric that may be used to detect whether an I/O limited condition may exist. A magnitude of the I/O metric may vary depending on the status of the I/O queue **230**. For example, the magnitude of the I/O metric may be based on the processing of the I/O requests in the I/O queue **230** by the graphics I/O controller **215**. The magnitude of the I/O metric may be high when the I/O limited condition may exist for an extended period of time.

The I/O limiting logic generator **225** may be configured to generate a first signal and transmit the first signal to the I/O limiting detector **220** when the I/O limited condition exists. The first signal may cause the frequency of the graphics controller **205** to be decreased. For some embodiments, the I/O limiting logic generator **225** may also be configured to generate and transmit a second signal to the I/O limiting detector **220** when the I/O limited condition may no longer exist. The second signal may cause the frequency of the graphics controller **205** to be increased.

The I/O limiting detector **220** may be configured to determine whether an I/O limited condition exists beyond a threshold. It may be anticipated that when the I/O limited condition exists beyond the threshold, it may continue to exist for an extended period of time. When the threshold is met or exceeded, the I/O limiting detector **220** may generate a signal which may cause the frequency decision logic **210** to perform operations to throttle the frequency of the graphics controller **205**. The frequency decision logic **210** may be coupled to a phase lock loop (PLL) (not shown) which may be configured to provide the frequency used by the graphics controller **205**.

Turning to FIG. 3, a diagram **300** that illustrates two example frames is shown, in accordance with some embodiments. The diagram **300** may include frames **305** and **310** separated by frame boundary **308**. Each of the frames **305** and **310** may be broken up into the same number of phases or states. For example, the frame **305** may include states **S0**, **S1**, **S2** and **S3** separated from one another by a state boundary. For example, the illustrated states **S0** and **S1** of the frame **305** are separated by state boundary **315**. Each of the states **S0**, **S1**, **S2** and **S3** may be associated with a different duration. A line (not shown) may represent the base frequency of the graphics controller **205**. Curve **330** may represent the I/O metric at any particular instance while the frames **305** and **310** and their states are being processed by the graphics controller **205**. Line **335** may represent a time line.

In general, the I/O limited condition may tend to be bursty with a burst lasting about 1 millisecond (ms) in duration. As a comparison, a frame may generally last between 16 ms to 20 ms. In the current example, at time **t0**, the I/O metric **330** may indicate that the graphics controller **205** may be partially I/O limited. At time **t1**, the I/O metric **330** may indicate that the graphics controller **205** may be fully I/O limited and may benefit from operating at a low frequency (e.g., a frequency that is lower than the base frequency). At time **t2**, the I/O metric **330** may indicate that the graphics controller **205** may be least likely to be I/O limited and may benefit from operating at a higher frequency (e.g., a frequency that is closer to or at the base frequency). At time **t3**, the I/O metric **330** may indicate that the graphics controller **205** may

not be I/O limited, and therefore it may be acceptable for the graphics controller **205** to operate at the base frequency.

It may be noted that the magnitude of the I/O metric **330** may vary at any particular time within the same state. For example, it may be possible to have the situations described at the times **t1** and **t2** occurring within the same state (e.g., state **S2**). As such, it may be possible to decrease the frequency of the graphics controller **205** from the base frequency and then increase the frequency of the graphics controller **205** within the same state (e.g., state **S2**). For some embodiments, the evaluation of the magnitude of the I/O metric **330** may be independent of the frame boundary **308** and the state boundary **315**. Thus, if the immediate past indicates that the graphics controller **205** is I/O limited or if the current instantaneous status indicates that the graphics controller **205** is I/O limited, then the frequency of the graphics controller **205** may be reduced instantaneously without having to be aware of which frame is currently being processed by the graphics controller **205**. The technique of changing of the frequency of the graphics controller **205** during workload execution using the dynamic information from the I/O metric **330** may be referred to as a dynamic frequency limiter (DFL) technique.

Turning to FIG. 4, a diagram **400** that illustrates thresholds that may be used with the I/O metric is shown, in accordance with some embodiments. The diagram **400** may include an I/O metric **430**, an up threshold **405** and a down threshold **410**. The up threshold **405** may be associated with an interrupt that may be triggered based on the I/O metric **430** being at or above the up threshold **405**. Similarly, the down threshold **410** may be associated with an interrupt that may be triggered based on the I/O metric **430** being at or below the down threshold **410**. For some embodiments, the I/O metrics **430** may be considered to be in an acceptable range when its magnitude is between the up threshold **405** and the down threshold **410**.

For some embodiments, instead of immediately reducing a frequency of a graphics controller as soon as an I/O metric reaches or goes above an up threshold (e.g., the time period between **t4** and **t5**), a short delay may be necessary to confirm that the I/O metric continues to exceed the up threshold long enough to justify the decrease of the frequency of the graphics controller. For example, at time **t4**, the I/O metric **430** may start to exceed the up threshold **405** which can indicate that the I/O limited condition may exist. A delay or up timeout **420** lasting from the time **t4** to the time **t5** may be necessary before the reduction of the frequency of the graphics controller **205** (shown in FIG. 2) may be triggered.

Similarly, instead of immediately increasing a frequency of a graphics controller as soon as a magnitude of the I/O metric reaches or goes below a down threshold (e.g., the time period between **t6** and **t7**), a short delay may be necessary to confirm that the I/O metric may continue to go below the down threshold long enough to justify the increase of the frequency of the graphics controller. For example, at time **t6**, the I/O metric **430** may start to go below the down threshold **410** which can indicate that the I/O limited condition may no longer exist. A delay or down timeout **425** lasting from the time **t6** to the time **t7** may be necessary before the increase of the frequency of the graphics controller **205** may be triggered. The up timeout **420** and the down timeout **425** may be used to reduce the potential of changing the frequency of the graphics controller **205** too frequently which may impact the performance of the graphics controller **205**. For example, if the I/O limited condition



## 5

may exist for only one micro second, it may be difficult to estimate whether the I/O limited condition may continue, or it may end.

For some embodiments, when the I/O limited condition exists and the decrease of the frequency of the graphics controller **205** is triggered, the level of decrease of the frequency of the graphics controller **205** may be determined based on a current magnitude of the I/O metric. For example, when the current magnitude of the I/O metric is very high (such as at point **450**), the frequency of the graphics controller **205** may be decreased by a large amount. When the current magnitude of the I/O metric is not very high (such as at point **455**), the frequency of the graphics controller **205** may be decreased by a small amount. Similarly, when the current magnitude of the I/O metric **430** is very low (such as at point **460**), the frequency of the graphics controller **205** may be increased by a large amount. When the current magnitude of the I/O metric is not very low (such as at point **465**), the frequency of the graphics controller **205** may be increased by a small amount. For some embodiments, the frequency of the graphics controller **205** may be increased at most to the base frequency. For some embodiments, the increase and decrease of the frequency of the graphics controller is based on bins which may be a graphics frequency step sizing.

Turning to FIG. 5, a diagram **500** that includes an example I/O metric and timeout periods is shown, in accordance with some embodiments. The diagram **500** may include an I/O metric **530**, an up threshold **505** and a down threshold **510**. Interval **590** may represent a hysteresis interval associated with the I/O metric **530** and may be large enough prevent any potential of getting an interrupt to cause a change in the frequency of the graphics controller **205** (shown in FIG. 2) too quickly. A timeout period **520** may be set to be a multiple of the interval **590**. In this example, the up threshold **505** may be associated with a value of 62, and the down threshold **510** may be associated with a value of 60. When a magnitude of the I/O metric **530** is above the up threshold **505** at least for the timeout period **520**, an interrupt may be generated which may cause the frequency of the graphics controller **205** (shown in FIG. 2) to be decreased. When a magnitude of the I/O metric **530** is below the down threshold **510** at least for the timeout period **520**, an interrupt may be generated which may cause the frequency of the graphics controller **205** to be decreased. As shown in FIG. 5, the timeout period **520** is met after the time intervals **550**, **555**, **560** and **565** and their respective interrupts **551**, **556**, **561** and **566** may be generated after each of these time intervals. The timeout period **520** is not met after the time intervals **570**, **575**, **580** and **585** and therefore no interrupt may be generated.

Turning to FIG. 6, a method **600** of adjusting the frequency of a graphics controller based on an I/O limited condition is shown, in accordance with some embodiments. The method **600** may be associated with a process performed by a graphics system such as the graphics system **200** of FIG. 2. At block **605**, the I/O metric may be evaluated to determine its magnitude at a particular instance. At block **610**, a comparison may be performed to determine whether an I/O limited condition may exist. The comparison may be based on the magnitude of the I/O metric at the particular instance and a high or up threshold value (e.g., up threshold **505** shown in FIG. 5). As described above, a timeout period (e.g., timeout period **520** shown in FIG. 5) may be used to determine when the I/O limited condition may exist.

When the I/O limited condition exists, the process may flow to block **615** where the frequency of the graphics

## 6

controller may be decreased. The decrease of the frequency may be based on an amount difference between the up threshold value and a current magnitude of the I/O metric. When the difference is high, the decrease may be more. When the difference is low, the decrease may be less. Alternatively, the decrease of the frequency may be performed iteratively. For example, the frequency may continue to be decreased in small amounts until the I/O metric indicates that the I/O limited condition does not exist, or until there is impact on the performance of the graphics controller. The decrease of the frequency may be based on the bins (e.g., two bins per decrease) until the I/O metrics is in an acceptable range. From block **615**, the process may continue at block **605**.

From the block **610**, when the I/O limited condition does not exist, the process may flow to block **620** where it may be determined whether a current magnitude of the I/O metric is at or lower than a low or down threshold (e.g., down threshold **510** shown in FIG. 5). From the block **620**, if the current magnitude of the I/O metric is not at or lower than the down threshold, the process may flow to block **605**. However, if the current magnitude of the I/O metric is at or lower than the down threshold, the process may then flow to block **625** where the frequency of the graphics controller may be increased. The increase of the frequency may be based on a difference between the down threshold and a current magnitude of the I/O metric. When the difference is high, the increase may be more. When the difference is low, the increase may be less. Alternatively, the increase of the frequency may be performed iteratively. For example, the frequency may continue to be increased in small amounts until the current magnitude the I/O metric indicates that is in the acceptable range (e.g., between the up threshold **505** and the down threshold **510** shown in FIG. 5). The increase of the frequency may be based on the frequency bins (e.g., two bins per increase) until the I/O metrics is in an acceptable range. From the block **625**, the process may continue at block **605**.

The method described above may be implemented as a set of logic instructions stored in a machine- or computer-readable storage medium such as random access memory (RAM), read only memory (ROM), programmable ROM (PROM), flash memory, etc., in configurable logic such as programmable logic arrays (PLAs), field-programmable gate arrays (FPGAs), complex programmable logic devices (CPLDs), in fixed-functionality logic hardware using circuit technology such as application-specific integrated circuit (ASIC), complementary-symmetry metal-oxide-semiconductor (CMOS) or transistor-transistor logic (TTL) technology, or any combination thereof. For example, computer program code to carry out operations shown in the method may be written in any combination of one or more programming languages, including an object oriented programming language such as C++ or the like and conventional procedural programming languages, such as the "C" programming language or similar programming languages.

In embodiments, the invention may be incorporated into a personal computer (PC), laptop computer, ultra-laptop computer, tablet, touch pad, portable computer, handheld computer, palmtop computer, personal digital assistant (PDA), cellular telephone, combination cellular telephone/PDA, television, smart device (e.g., smart phone, smart tablet or smart television), mobile internet device (MID), messaging device, data communication device, and so forth.

Example sizes/models/values/ranges may have been given, although embodiments of the present invention are not limited to the same. As manufacturing techniques (e.g.,



photolithography) mature over time, it is expected that devices of smaller size could be manufactured. In addition, well known power/ground connections to integrated circuit (IC) chips and other components may or may not be shown within the figures, for simplicity of illustration and discussion, and so as not to obscure certain aspects of the embodiments of the invention. Further, arrangements may be shown in block diagram form in order to avoid obscuring embodiments of the invention, and also in view of the fact that specifics with respect to implementation of such block diagram arrangements are highly dependent upon the platform within which the embodiment is to be implemented, i.e., such specifics should be well within purview of one skilled in the art. Where specific details (e.g., circuits) are set forth in order to describe example embodiments of the invention, it should be apparent to one skilled in the art that embodiments of the invention can be practiced without, or with variation of, these specific details. The description is thus to be regarded as illustrative instead of limiting.

The term "coupled" may be used herein to refer to any type of relationship, direct or indirect, between the components in question, and may apply to electrical, mechanical, fluid, optical, electromagnetic, electromechanical or other connections. In addition, the terms "first", "second", etc. might be used herein only to facilitate discussion, and carry no particular temporal or chronological significance unless otherwise indicated.

Those skilled in the art will appreciate from the foregoing description that the broad techniques of the embodiments of the present invention can be implemented in a variety of forms. Therefore, while the embodiments of this invention have been described in connection with particular examples thereof, the true scope of the embodiments of the invention should not be so limited since other modifications will become apparent to the skilled practitioner upon a study of the drawings, specification, and following claims.

I claim:

1. An apparatus comprising:

a first controller;

an input/output (I/O) queue to store I/O requests;

an I/O controller to manage the queue;

logic to determine whether an I/O limited condition exists based on a metric associated with the input/output (I/O) queue wherein the I/O limited condition is to be associated with the first controller;

logic to cause a frequency of the first controller to be decreased if the I/O limited condition exists to enable a reduction of power consumption by the first controller after a first condition is met; and

logic to cause the frequency of the first controller to be increased if the I/O limited condition does not exist after a second condition is met,

wherein the I/O controller has a frequency that can be maintained as the frequency of the first controller varies, and

wherein the first controller is to be configured to process a graphics workload having multiple frames, and wherein the logic is to increase or decrease the frequency of the first controller independently of a frame boundary associated with the workload.

2. The apparatus of claim 1, wherein the I/O limited condition exists if a magnitude of the metric is equal to or greater than a first threshold, and wherein the I/O limited condition does not exist if the magnitude of the metric is equal to or less than a second threshold.

3. The apparatus of claim 2, wherein the first controller is a graphics controller, the I/O controller is a graphics I/O

controller, the I/O queue is to store graphics I/O requests, the graphics controller is to be configured to process a graphics workload having multiple frames, and wherein the logic is to decrease or increase the frequency of the graphics controller independently of a frame boundary associated with the frames.

4. The apparatus of claim 3, wherein the logic to cause the frequency of the graphics controller to be decreased includes logic to wait for a first time period after determining that the I/O condition exists, and logic to indicate whether the I/O limited condition still exists after the first time period.

5. The apparatus of claim 4, wherein the logic to cause the frequency of the graphics controller to be increased includes logic to wait for a second time period after determining that the I/O condition does not exist, and logic to indicate that the I/O limited condition still does not exist after the second time period.

6. The apparatus of claim 5, wherein the frequency of the graphics controller is decreased or increased by iteratively changing the frequency of the graphics controller by a frequency amount and checking to determine whether the I/O limited condition exists.

7. The apparatus of claim 6, wherein the frequency amount corresponds to a frequency bin.

8. The apparatus of claim 5, wherein the frequency of the graphics controller is decreased or increased based on a difference between a current magnitude of the metric and a respective first threshold or second threshold.

9. The apparatus of claim 8, wherein the frequency of the graphics controller is decreased or increased by a first amount when the difference between the current magnitude of the metric and the respective first threshold or second threshold is relatively large and by a second amount when the difference between the current magnitude of the metric and the respective first threshold or second threshold is relatively small, wherein the first amount is to be greater than the second amount.

10. A computer-implemented method comprising:

determining a metric associated with an input/output (I/O) queue that is associated with a first controller, wherein the input/output queue is managed by an I/O controller, and wherein a magnitude of the metric is high if the I/O queue is full and low if the I/O queue is not full;

decreasing a frequency of the first controller if the I/O queue is full and a first condition is met; and

increasing a frequency of the first controller if the I/O queue is not full and a second condition is met, wherein the decreasing and increasing of the frequency of the first controller is performed independently of a frame boundary associated with frames of a graphical workload.

11. The method of claim 10, wherein the first controller is a graphics controller, and the I/O controller is a graphics I/O controller, further including:

decreasing a frequency of the first controller when the magnitude of the metric is at or greater than a first threshold; and

increasing the frequency of the first controller when the magnitude of the metric is at or less than a second threshold, wherein the second threshold is associated with a value less than a value associated with the first threshold,

wherein the decreasing and increasing of the frequency of the graphics controller is performed independently of a frame boundary associated with frames to be processed by the graphics controller.



9

12. The method of claim 11, wherein the decreasing the frequency of the graphics controller is performed based on the magnitude of the metric continuing to be at or greater than the first threshold after a first time period.

13. The method of claim 12, wherein the increasing the frequency of the graphics controller is performed based on the magnitude of the metric continuing to be at or less than the second threshold after a second time period.

14. The method of claim 13, wherein the decreasing or increasing the frequency of the graphics controller is performed iteratively based on changing the frequency of the graphics controller and comparing the magnitude of the metric with the respective first threshold or second threshold.

15. The method of claim 14, wherein the frequency of the graphics controller is decreased or increased based on a frequency bin.

16. The method of claim 13, wherein the frequency of the graphics controller is decreased or increased based on the magnitude of the metric relative to the respective first threshold or second threshold.

17. A system comprising:

a processor;

an external power supply coupled to the processor;

a first controller coupled to the processor; and

logic to determine whether an I/O limited condition exists based on a metric associated with an input/output (I/O) queue managed by an I/O controller, wherein the I/O limited condition is to be associated with the first controller; and

logic to decrease a frequency of the first controller if an input/output (I/O) limited condition exists and a first

10

condition is met, and to increase the frequency if the I/O limited condition does not exist and a second condition is met,

wherein the first controller is to be configured to process a graphics workload having multiple frames, wherein the logic is to increase or decrease the frequency of the first controller independently of a frame boundary associated with the workload.

18. The system of claim 17, wherein the I/O limited condition exists if a magnitude of a metric associated with the I/O queue that is managed by the I/O controller is at or greater than a first threshold, and wherein the I/O limited condition does not exist when the magnitude of the metric is at or less than a second threshold, and

wherein the frequency of the first controller is decreased based on the I/O limited condition continuing to exist after a first time period, and wherein the frequency of the first controller is increased based on the I/O limited condition continuing not to exist after a second time period.

19. The system of claim 18, wherein the first controller is a graphics controller and the I/O controller is a graphics I/O controller, wherein the graphics controller is configured to operate at the decreased or increased frequency independently of a frame boundary associated with frames to be processed by the graphics controller.

20. The system of claim 19, wherein the frequency of the graphics controller is decreased or increased by iteratively changing the frequency of the graphics controller and checking to determine whether the I/O limited condition exists.

\* \* \* \* \*