



US009881218B2

(12) **United States Patent**
Ogata et al.

(10) **Patent No.:** **US 9,881,218 B2**
(45) **Date of Patent:** **Jan. 30, 2018**

(54) **LOCATION CALCULATION SYSTEM AND NON-TRANSITORY COMPUTER-READABLE MEDIUM**

(71) Applicant: **ZENRIN Co., LTD.**, Kitakyushu-shi (JP)

(72) Inventors: **Shinji Ogata**, Fukuoka (JP); **Hiroyuki Ohara**, Kitakyushu (JP); **Hiroyuki Inatsuka**, Kitakyushu (JP); **Tatsuya Yuba**, San Bruno, CA (US); **Junichi Nakamura**, Kitakyushu (JP)

(73) Assignee: **ZENRIN Co., LTD.**, Kitakyushu-shi (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 201 days.

(21) Appl. No.: **14/815,645**

(22) Filed: **Jul. 31, 2015**

(65) **Prior Publication Data**

US 2016/0063341 A1 Mar. 3, 2016

(30) **Foreign Application Priority Data**

Aug. 29, 2014 (JP) 2014-175912

(51) **Int. Cl.**

G06K 9/00 (2006.01)
H04N 5/225 (2006.01)
H04N 5/232 (2006.01)
G01S 19/45 (2010.01)
G06T 7/73 (2017.01)

(52) **U.S. Cl.**

CPC **G06K 9/00798** (2013.01); **G01S 19/45** (2013.01); **G06K 9/00791** (2013.01); **G06K 9/00818** (2013.01); **G06K 9/00825** (2013.01); **G06T 7/74** (2017.01); **H04N 5/225** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC G06K 9/00791; G06K 9/00798; G06K 9/00825

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,868,821 B2 * 1/2011 Hoshizaki G01S 19/45 342/357.42
2005/0135658 A1 * 6/2005 Yamamoto G06K 9/00798 382/104

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2005-265494 9/2005


Primary Examiner — Utpal Shah

(74) *Attorney, Agent, or Firm* — Oblon, McClelland, Maier & Neustadt, L.L.P.

(57) **ABSTRACT**

A location calculation system that includes circuitry that stores vector information regarding a plurality of first vectors each connecting a specific point-relevant location, that is associated with each of a plurality of specific points set along a road, with a location of a predetermined feature, in relation to position information regarding each position of the plurality of specific points; stores predetermined feature location information regarding the location of the predetermined feature; obtains image data ahead of a moving body; calculates a location of the predetermined feature in an image of the image data as obtained by the circuitry; calculates a location of the moving body based on the location of the predetermined feature as calculated by the circuitry and the vector information; and outputs the location of the moving body as calculated by the circuitry.

17 Claims, 17 Drawing Sheets



(52) **U.S. Cl.**
CPC *H04N 5/23229* (2013.01); *G06T*
2207/30252 (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2014/0003709 A1* 1/2014 Ranganathan G06K 9/00798
382/159
2015/0310283 A1* 10/2015 Mori B60W 30/12
382/104
2016/0101779 A1* 4/2016 Katoh G06T 7/60
340/435
2017/0008521 A1* 1/2017 Braunstein G01C 21/32

* cited by examiner

Fig.1




Fig.2




Fig.3

SPECIFIC POINT ID	POSITION INFO	FIRST VECTOR	OBJECT FEATURE ID
p1	(X1,Y1,Z1)	(dx1,dy1,dz1)	L1
p2	(X2,Y2,Z2)	(dx2,dy2,dz2)	L1
p3	(X3,Y3,Z3)	(dx3,dy3,dz3)	L1

Fig.4

FEATURE ID	LOCATION INFO	SHAPE	SIZE	POLYGON ID
L1	(X11,Y11,Z11)	CIRCLE	R=300mm	PG1
L2	(X12,Y12,Z12)	SQUARE	900*900mm	PG2

Fig.5




Fig.6




Fig.7




Fig.8

SECOND EMBODIMENT




Fig.9

SECOND EMBODIMENT

SPECIFIC POINT ID	POSITION INFO	FOURTH VECTOR	OBJECT FEATURE ID
p1	(X1,Y1,Z1)	(dx7,dy7,dz7)	L1
p2	(X2,Y2,Z2)	(dx8,dy8,dz8)	L1
p3	(X3,Y3,Z3)	(dx9,dy9,dz9)	L1

Fig. 10


SECOND EMBODIMENT

Fig.11




Fig.12

THIRD EMBODIMENT




Fig.13A

THIRD EMBODIMENT




Fig.13B

THIRD EMBODIMENT




Fig.14

FOURTH EMBODIMENT

SPECIFIC POINT ID	POSITION INFO	FIRST VECTOR	OBJECT FEATURE ID	ANGLES
p5	(X5,Y5,Z5)	(dx5,dy5,dz5)	L11	($\theta_{x5}, \theta_{y5}, \theta_{z5}$)
p6	(X6,Y6,Z6)	(dx6,dy6,dz6)	L11	($\theta_{x6}, \theta_{y6}, \theta_{z6}$)
p7	(X7,Y7,Z7)	(dx7,dy7,dz7)	L11	($\theta_{x7}, \theta_{y7}, \theta_{z7}$)
p8	(X8,Y8,Z8)	(dx8,dy8,dz8)	L11	($\theta_{x8}, \theta_{y8}, \theta_{z8}$)

Fig.15

FOURTH EMBODIMENT




Fig.16




Fig.17

FIFTH EMBODIMENT




Fig.18

FIFTH EMBODIMENT




Fig. 19

FIFTH EMBODIMENT




Fig.20

FIFTH EMBODIMENT





Fig.21

FIFTH EMBODIMENT



1

**LOCATION CALCULATION SYSTEM AND
NON-TRANSITORY COMPUTER-READABLE
MEDIUM**

CROSS-REFERENCE TO RELATED
APPLICATIONS

The present application claims priority from Japanese Patent Application No. 2014-175912 filed on Aug. 29, 2014, the entirety of disclosure of which is hereby incorporated by reference into this application.

BACKGROUND

Technical Field

The present disclosure relates to specifying the location of a vehicle.

Description of the Related Art

A proposed apparatus analyzes an image taken by a vehicle-mounted camera and specifies the current location of a vehicle during driving. For example, a proposed apparatus stores in advance information regarding road marking lines representing boundaries of lanes and map information including information regarding landmarks such as road surface markings and signs, analyzes a taken image to extract landmarks and road marking lines, and identify a location of highest matching with the extracted landmarks and road marking lines in a map indicated by the map information.

The prior art apparatus described above, however, analyzes the entire taken image for extraction of landmarks and road marking lines and accordingly has a problem of increasing the processing load and requiring the long time for specifying the location of the vehicle. This may lead to a problem of delayed control of steering or power output in an application that automatically controls the steering or the power output of the vehicle based on the specified location of the vehicle. This problem is not limited to the vehicle-mounted camera but is commonly found in any location specifying apparatus that analyzes an image obtained by a reflected wave of any wavelength, for example, a millimeter waveband radar or a laser to specify the location of the vehicle.

SUMMARY

According to one aspect of the disclosure, there is provided a location calculation system that includes circuitry that stores vector information regarding a plurality of first vectors each connecting a specific point-relevant location, that is associated with each of a plurality of specific points set along a road, with a location of a predetermined feature, in relation to position information regarding each position of the plurality of specific points; stores predetermined feature location information regarding the location of the predetermined feature; obtains image data ahead of a moving body; calculates a location of the predetermined feature in an image of the image data as obtained by the circuitry; calculates a location of the moving body based on the location of the predetermined feature as calculated by the circuitry and the vector information; and outputs the location of the moving body as calculated by the circuitry.

The disclosure may be implemented by various other aspects, for example, a vehicle control apparatus, a drive assist system, a vehicle, a method of specifying location of a vehicle, a computer program implementing each of these

2

apparatuses and methods, and a non-transitory recording medium storing such a computer program.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a block diagram illustrating the schematic configuration of a location specifying apparatus **100** according to one embodiment of the disclosure;

FIG. 2 is a diagram illustrating first vectors according to the first embodiment;

FIG. 3 is a diagram showing one example of settings in the vector table stored in the first vector information storage unit **141** shown in FIG. 1;

FIG. 4 is a diagram showing an example of settings in the feature table stored in the feature information storage unit **143** shown in FIG. 1;

FIG. 5 is a flowchart showing a procedure of vehicle location specifying process according to the first embodiment;

FIG. 6 is a diagram illustrating a third vector V_{gp} according to the first embodiment;

FIG. 7 is a diagram illustrating one example of the existing area estimated at step **S125**;

FIG. 8 is a block diagram illustrating the schematic configuration of a location specifying apparatus **100a** according to a second embodiment;

FIG. 9 is a diagram illustrating one example of settings in the vector table of the second embodiment;

FIG. 10 is a flowchart showing a procedure of vehicle location specifying process according to the second embodiment;

FIG. 11 is a flowchart showing a procedure of vehicle location specifying process according to a third embodiment;

FIG. 12 is a flowchart showing a procedure of vehicle location specifying process according to a third embodiment;

FIG. 13A shows an image **F1** obtained in a previous cycle of the vehicle location specifying process;

FIG. 13B shows an image **F11** obtained in a current cycle of the vehicle location specifying process;

FIG. 14 is a diagram showing one example of settings in a vector table according to a fourth embodiment;

FIG. 15 is a diagram illustrating one example of settings in the angle field of the vector table;

FIG. 16 is a flowchart showing a procedure of vehicle location specifying process according to the fourth embodiment;

FIG. 17 is a block diagram illustrating the schematic configuration of a location specifying apparatus **100b** according to a fifth embodiment;

FIG. 18 is a diagram illustrating a sixth vector in the fifth embodiment;

FIG. 19 is a flowchart showing a procedure of vehicle location specifying process according to the fifth embodiment;

FIG. 20 is a diagram illustrating an existing area according to the fifth embodiment; and

FIG. 21 is a diagram schematically illustrating the processing detail of steps **S250** and **S255**.

DESCRIPTION OF EMBODIMENTS

A. First Embodiment

A1. Configuration of Apparatus

FIG. 1 is a block diagram illustrating the schematic configuration of a location specifying apparatus 100 according to one embodiment of the disclosure. The location specifying apparatus 100 shown in FIG. 1 is mounted on a vehicle (not shown) to specify the location of the vehicle. The vehicle may perform automatic control of steering or power output, give an alarm to the driver or perform route search or route guidance, based on the location specified by the location specifying apparatus 100. The term “vehicle” here denotes any vehicle enabled to run on the road, for example, a motor truck, taxi, bus, motorbike or a bicycle.

As shown in FIG. 1, the location specifying apparatus 100 includes a Central Processing Unit (CPU) 110, a Random Access Memory (RAM) 120, a Read Only Memory (ROM) 130, a hard disk drive 140, an image input interface (I/F) module 150 and a GPS input interface (I/F) module 160. These components are respectively connected with an internal bus 190.

The CPU 110 performs a control program stored in the ROM 130 to serve as an image data acquirer 111, a positioning result acquirer 112, an area estimator 113 and a locator 114.

The image data acquirer 111 obtains image data of an image taken by an imaging camera 200 and stores the obtained image data in the hard disk drive 140. According to this embodiment, the imaging camera 200 is a digital video camera having a Charge Coupled Device (CCD) and obtains video data (image data) in a specified number of pixels. According to this embodiment, the imaging camera 200 is mounted on the vehicle to have an imaging range ahead of the vehicle.

The positioning result acquirer 112 obtains information regarding the current location (latitude, longitude and altitude) as the positioning result by a Global Positioning System (GPS) positioning device 300. The GPS positioning device 300 is a known device that computes the current location based on signals output from global positioning system (GPS) satellites, and is thus not specifically described herein. According to this embodiment, the location of the vehicle is specified as the location of the GPS positioning device 300 mounted on the vehicle. According to this embodiment, the locations at which the imaging camera 200 and the GPS positioning device 300 are installed in the vehicle are fixed and are not changed.

The area estimator 113 estimates an existing area where an object feature exists in the taken image in a vehicle location specifying process described later. The object feature and the existing area will be described later in detail.

The hard disk drive 140 includes a first vector information storage unit 141, a second vehicle information storage unit 142 and a feature information storage unit 143. The first vehicle information storage unit 141 stores in advance information regarding first vectors associated with respective specific points described later, in the form of a vector table.

FIG. 2 is a diagram illustrating first vectors according to the first embodiment. In this embodiment, points where vector information is set (hereinafter referred to as “specific points”) are set at predetermined intervals with respect to each lane where the vehicle runs. More specifically, as shown in FIG. 2, specific points are set on a middle line 55 of a lane 50 located between a center line 60 and a curbstone

70 at predetermined intervals along the middle line 55. For convenience of illustration, only three specific points p1, p2 and p3 are shown in FIG. 2. A sign 10 is placed near outside of the lane 50 to be visible from vehicles running on the lane 50. The sign 10 has a circular shape in planar view. The shape, the design and the location of the sign 10 are unlikely to change. Accordingly, the sign 10 is used as a landmark in the process of specifying the location of the vehicle. In addition to the sign 10, another sign different from the sign 10, a power pole or a road surface marking may also be used as a landmark in the process of specifying the location of the vehicle. According to this embodiment, a feature used as a landmark in the process of specifying the location of the vehicle as described above (hereinafter called “object feature”) is set in advance related to each specific point.

According to this embodiment, with respect to each of the specific points, a vector directed from the specific point to the landmark is set as a first vector Vps. More specifically, for example, with respect to a specific point p1, a vector directed from the specific point p1 to the sign 10 is set as a first vector Vps1. Similarly, with respect to a specific point p2, a vector directed from the specific point p2 to the sign 10 is set as a first vector Vps2. With respect to a specific point p3, a vector directed from the specific point p3 to the sign 10 is set as a first vector Vps3. According to this embodiment, the position of the end point of each first vector is set at a center point of a representative surface of the sign 10. This “representative surface of the sign 10” denotes a surface on which a mark as the sign is shown, so as to serve as a landmark.

FIG. 3 is a diagram showing one example of settings in the vector table stored in the first vector information storage unit 141 shown in FIG. 1. The vector table includes a “specific point identifier” field, a “position information” field, a “first vector” field and an “object feature identifier” field. The specific point identifier field stores identifiers of the respective specific points. The position information field stores position information (latitude, longitude and altitude) of the respective specific points. The first vector field stores information regarding first vectors associated with the respective specific points. The object feature identifier field stores an identifier of each object feature. In the example of FIG. 3, the vector table has registry of three records set with respect to the three specific points p1 to p3 shown in FIG. 2. More specifically, the topmost record of FIG. 3 is a record regarding the specific point p1 and includes the settings of “p1” as the identifier of the specific point p1, “X1,Y1,Z1” as the position information of the specific point p1, “dx1,dy1,dz1” as the first vector of the specific point p1 (more specifically, as the first vector Vps1 directed from the specific point p1 to the sign 10), and “L1” as the identifier of the object feature (more specifically, the sign 10) related to the specific point p1. Similarly, the second top record of FIG. 3 is a record regarding the specific point p2, and the third top record of FIG. 3 is a record regarding the specific point p3. The settings of the vector table are specified in advance by an administrator. The feature used as the object feature is set by the administrator as a feature that is likely to be included in an image taken by the imaging camera 200 when the vehicle is located near the relevant specific point. The values of the respective fields in FIG. 3 are given as typical values.

The second vector information storage unit 142 shown in FIG. 1 stores information regarding second vectors. According to this embodiment, the second vector denotes a vector directed from the GPS positioning device 300 to the imaging camera 200.

The feature information storage unit **143** shown in FIG. **1** stores information regarding features such as signs placed near the road and road surface markings (hereinafter referred to as “feature information”) in the form of a feature table.

FIG. **4** is a diagram showing an example of settings in the feature table stored in the feature information storage unit **143** shown in FIG. **1**. The feature table includes a “feature identifier” field, a “location information” field, a “shape” field, a “size” field and a “polygon identifier” field. The feature identifier field stores identifiers of respective features. The location information field stores location information (latitude, longitude and altitude) of the respective features. The shape field stores external shapes of representative surfaces of the respective features. The size field stores information regarding sizes of the representative surfaces of the respective features. The polygon identifier field stores identifiers of polygons representing the respective features. Polygon data of the respective features are related to the above polygon identifiers and are stored in the hard disk drive **140**. In the example of FIG. **4**, the feature table has registry of two records. The record with the feature identifier “L1” is a record regarding the sign **10** and includes the settings of “X11,Y11,Z11” as the location information of the sign **10**, “circle” as the shape of the sign **10**, “R (radius)=300 mm” as the size of the sign **10**, and “PG1” as the polygon identifier of the sign **10**. The record with the feature identifier “L2” is a record regarding a square sign (for example, a sign indicating the direction of each lane) and includes the settings of “X12,Y12,Z12” as the location information, “square” as the shape, “900 mm×900 mm” as the size and “PG2” as the polygon identifier.

The positioning result by the GPS positioning device **300** inevitably includes some error, so that the current location of the vehicle may not be accurately specified using only the positioning result by the GPS positioning device **300**. Accordingly, the location specifying apparatus **100** of the first embodiment performs a vehicle location specifying process described later, in order to specify the current location of the vehicle accurately.

The image input interface module **150** shown in FIG. **1** has an interface for connection with the imaging camera **200** and sends image data obtained by the imaging camera **200** to the CPU **110** via the internal bus **190**. The GPS input interface module **160** has an interface for connection with the GPS positioning device **300** and sends information regarding the positioning result by the GPS positioning device **300** to the CPU **110** via the internal bus **190**.

The position of a specific point in this embodiment corresponds to the specific point-relevant location in the claims. The first vector information storage unit **141** corresponds to the first vector information storage unit in the claims. The image data obtained by the imaging camera **200** corresponds to the image data ahead of the moving body in the claims. The GPS positioning device **300** corresponds to the location sensor in the claims. The positioning result acquirer **112** corresponds to the location information acquirer in the claims. The CCD of the imaging camera **200** corresponds to the receiver in the claims. The feature information storage unit **143** corresponds to the predetermined feature location information storage unit and the shape information storage unit in the claims.

A2. Vehicle Location Specifying Process

FIG. **5** is a flowchart showing a procedure of vehicle location specifying process according to the first embodiment. After the power-on, the vehicle location specifying process is performed repeatedly in the location specifying apparatus **100**. The image data acquirer **111** first controls the

imaging camera **200** to take a still image and obtains image data of the taken still image (step **S105**).

The positioning result acquirer **112** obtains a positioning result by the GPS positioning device **300** at the image-taking time as information regarding the estimated current location of the vehicle when the image data is obtained (hereinafter referred to as “estimated location information”) (step **S110**). As described above, the GPS positioning includes some error, so that the procedure of the embodiment treats the positioning result of the GPS positioning device **300** as the estimated current location of the vehicle.

The area estimator **113** uses the estimated location information obtained at step **S110** and calculates vectors directed from the GPS positioning device **300** to the respective specific points (hereinafter referred to as “third vectors V_{gp} ”) (step **S115**).

FIG. **6** is a diagram illustrating a third vector V_{gp} according to the first embodiment. FIG. **6** illustrates a side view of a vehicle **500** running on the lane **50** and the sign **10**. FIG. **6** shows only a third vector V_{gp} directed from the GPS positioning device **300** to the specific point **p1** as a representative of the third vectors V_{gp} directed from the GPS positioning device **300** to the respective specific points. FIG. **6** also shows the first vector V_{ps} (V_{ps1}) described above (vector directed from the specific point **p1** to the sign **10**) and a second vector V_{gc} (vector directed from the GPS positioning device **300** to the imaging camera **200**), in addition to the third vector V_{gp} . FIG. **6** also shows a fourth vector V_{cs} and a fifth vector V_{gs} described later, in addition to the first to the third vectors. The details of the fourth and the fifth vectors will be described later.

The position information of the respective specific points is stored in the vector table shown in FIG. **3**, and the location of the GPS positioning device **300** (estimated location when the image data is obtained) is obtained at step **S110**. At step **S115**, the third vectors V_{gp} are calculated based on the positions of the respective specific points and the estimated location. More specifically, at step **S115**, the area estimator **113** calculates third vectors V_{gp} with regard to only specific points in a predetermined area (for example, a circular area with a radius of 50 m) about the location indicated by the estimated location information obtained at step **S110**. In a modified procedure, the area estimator **113** may calculate a third vector V_{gp} with regard to only a specific point nearest to the location indicated by the estimated location information (hereinafter referred to as “nearest point”). Accordingly, at step **S115**, the area estimator **113** may calculate a third vector V_{gp} directed from the GPS positioning device **300** to each specific point near to the location indicated by the estimated location information.

Referring back to FIG. **5**, the area estimator **113** uses the first to the third vectors to calculate a vector directed from the imaging camera **200** to the sign **10** (fourth vector V_{cs} mentioned above) (step **S120**). More specifically, the area estimator **113** calculates the fourth vector V_{cs} by summing up the third vector V_{gp} and the first vector V_{ps} shown in FIG. **6** and subtracting the second vector V_{gc} from the sum. As described above, the third vectors V_{gp} are calculated with regard to the specific points in the predetermined area about the location indicated by the estimated location information, so that a plurality of fourth vectors V_{cs} may be calculated based on these third vectors V_{gp} . At step **S120**, the area estimator **113** determines a mean vector of the plurality of fourth vectors V_{cs} and uses the determined mean vector as the fourth vector V_{cs} for the processing of and after step **S125**.

Referring back to FIG. 5, the area estimator **113** estimates an area where an object feature exists (hereinafter referred to as “existing area”) in the taken image, based on the fourth vector V_{cs} calculated at step **S120** (step **S125**). More specifically, in the procedure of the embodiment the area estimator **113** estimates either a right half area or a left half area of the taken image as the existing area. This existing area corresponds to the predetermined feature existing area in the claims.

FIG. 7 is a diagram illustrating one example of the existing area estimated at step **S125**. For convenience of explanation, FIG. 7 shows a fourth vector V_{cs} included in an image **F1** obtained at step **S105**. In the illustrated example of FIG. 7, the fourth vector V_{cs} is given as a vector directed from center C_p of the image **F1** to the sign **10**. At step **S125**, the area estimator **113** determines a projection vector of the fourth vector V_{cs} to a plane perpendicular to the moving direction of the vehicle, i.e., a plane perpendicular to the middle line **55** and identifies whether the projection vector is a vector directed rightward relative to the moving direction of the vehicle or a vector directed leftward relative to the moving direction of the vehicle. The area estimator **113** estimates the right half area of the taken image as the existing area when identifying the projection vector as a vector directed rightward, and estimates the left half area of the taken image as the existing image when identifying the projection vector as a vector directed leftward. In the example of FIG. 7, the projection vector of the fourth vector V_{cs} is identified as a vector directed leftward relative to the moving direction of the vehicle, so that a left half area A_{r1} of the image **F1** is estimated as the existing area.

Referring back to FIG. 5, the locator **114** extracts features that are possible candidates for the object feature (hereinafter referred to as “candidate features”) in the existing area estimated at step **S125**, from the taken image (step **S130**). In an exemplary procedure, the CPU **110** may register in advance profile patterns of features that are possibly selected as the object feature. At step **S130**, the locator **114** may extract profiles by, for example, edge extraction, in the image and compare the extracted profiles with the registered profile patterns to extract the candidate features.

The locator **114** performs pattern matching for each of the candidate features extracted at step **S130** with the polygons of object features related to the respective specific points, so as to identify the object feature included in the taken image (step **S135**).

The locator **114** subsequently calculates a vector directed from the vehicle (GPS positioning device **300**) to the object feature identified at step **S135** (fifth vector V_{gs} mentioned above) (step **S140**). As described above, the location information of the respective features are registered in the feature table shown in FIG. 4. The locator **114** accordingly uses this location information and the estimated location information obtained at step **S110** to determine the fifth vector V_{gs} .

The locator **114** refers to the vector table, compares the fifth vector V_{gs} calculated at step **S140** with the respective first vectors V_{ps} to identify the first vector V_{ps} most approximate to the fifth vector V_{gs} and then identifies a specific point related to the identified first vector V_{ps} (step **S145**).

The locator **114** then specifies the position of the specific point identified at step **S145**, as the location of the vehicle (step **S150**).

The location specifying apparatus **100** of the first embodiment described above estimates an existing area of the object feature in the taken image and makes only the estimated existing area subjected to the extraction process of

candidate features. This configuration reduces the processing load of the CPU **110** and shortens the time required for specifying the location of the vehicle, compared with a configuration that makes the entire area of the taken image subjected to the extraction process of candidate features. The location specifying apparatus **100** of the first embodiment calculates the vector directed from the imaging camera **200** to the sign **10** (fourth vector V_{cs}) and estimates the existing area based on the calculated vector. This enables the area where the sign **10** is included in the taken image to be estimated with high accuracy.

The location specifying apparatus **100** of the first embodiment stores the position information of the respective specific points and stores the information regarding the first vectors V_{ps} associated with the respective specific points. This enables the fourth vector V_{cs} to be calculated with high accuracy by using the first vectors V_{ps} .

The location specifying apparatus **100** of the first embodiment also stores the location information of the object feature and thereby enables the vector directed from the vehicle (GPS positioning device **300**) to the sign **10** (fifth vector V_{gs}) to be calculated when the object feature is identified. Additionally, the first vector V_{ps} related to a specific point closer to the current location of the vehicle is more approximate to the calculated fifth vector V_{gs} . The location specifying apparatus **100** of the first embodiment accordingly specifies the position of the specific point related to the first vector V_{ps} most approximate to the fifth vector V_{gs} , as the location of the vehicle. This enables the location of the vehicle to be specified with high accuracy.

B. Second Embodiment

FIG. 8 is a block diagram illustrating the schematic configuration of a location specifying apparatus **100a** according to a second embodiment. The location specifying apparatus **100a** of the second embodiment differs from the location specifying apparatus **100** of the first embodiment shown in FIG. 1 by that the hard disk drive **140** includes a fourth vector information storage unit **144** in place of the first vector information storage unit **141**. Otherwise the configuration of the location specifying apparatus **100a** of the second embodiment is similar to the configuration of the location specifying apparatus **100** of the first embodiment. The like components are expressed by the like symbols and are not specifically described.

The fourth vector information storage unit **144** stores in advance information regarding fourth vectors V_{cs} associated with the respective specific points, in the form of a vector table.

FIG. 9 is a diagram illustrating one example of settings in the vector table of the second embodiment. The vector table of the second embodiment differs from the vector table of the first embodiment shown in FIG. 3 by replacement of the first vector field with a fourth vector field. Otherwise the configuration of the vector table of the second embodiment is similar to the configuration of the vector table of the first embodiment and is thus not specifically described. As shown in FIG. 9, in the vector table of the second embodiment, information regarding fourth vectors is set in relation to respective specific points. In this embodiment, vectors directed from the imaging camera **200** to an object feature when the vehicle (GPS positioning device **300**) is located vertically above respective specific points are set as fourth vectors V_{cs} in the vector table. These fourth vectors V_{cs} are set in advance in the vector table by the administrator.

FIG. 10 is a flowchart showing a procedure of vehicle location specifying process according to the second embodiment. The vehicle location specifying process of the second embodiment differs from the vehicle location specifying process of the first embodiment shown in FIG. 5 by replacement of steps S115 and S120 with steps S116 and S121 and replacement of step S145 with step S145a. Otherwise the vehicle location specifying process of the second embodiment is similar to the vehicle location specifying process of the first embodiment. The like steps are shown by the like step numbers and are not specifically described.

As shown in FIG. 10, after the estimated location information is obtained at step S110, the area estimator 113 specifies a nearest point (step S116). The area estimator 113 subsequently refers to the vector table stored in the fourth vector information storage unit 144 to identify a fourth vector V_{cs} related to the nearest point specified at step S116 (step S121). The fourth vector V_{cs} related to the specific point nearest to the location estimated as the current location of the vehicle is approximate to a vector directed from the imaging camera 200 to the object feature at the current location of the vehicle.

After the processing of step S121, the CPU 110 performs the processing of steps S125 to S140 described above. After the processing of step S140, the locator 114 compares the fifth vector V_{gs} calculated at step S140 with the fourth vectors V_{cs} in relation to the respective specific points to identify the fourth vector V_{cs} most approximate to the fifth vector V_{gs} , and then identifies a specific point related to the identified fourth vector V_{cs} (step S145a). The procedure subsequently performs the processing of step S150 described above.

The location specifying apparatus 100a of the second embodiment described above has the similar advantageous effects to those of the location specifying apparatus 100 of the first embodiment. Additionally, the location specifying apparatus 100a of the second embodiment identifies the fourth vector V_{cs} related to the specific point nearest to the location estimated as the current location of the vehicle and estimates the existing area based on the fourth vector V_{cs} . The fourth vector V_{cs} related to the specific point nearest to the location estimated as the current location of the vehicle is approximate to the vector directed from the imaging camera 200 to the object feature at the current location of the vehicle. This ensures estimation of the existing area with high accuracy. The location specifying apparatus 100a of the second embodiment registers the fourth vectors V_{cs} in advance in the vector table and selects and identifies the fourth vector V_{cs} by referring to this table. This reduces the processing load required for identifying the fourth vector V_{cs} . Accordingly, this further shortens the time required for specifying the location of the vehicle.

The fourth vector V_{cs} of the second embodiment corresponds to the first vector in the claims.

C. Third Embodiment

FIGS. 11 and 12 are flowchart showing a procedure of vehicle location specifying process according to a third embodiment. A location specifying apparatus of the third embodiment has a configuration similar to the configuration of the location specifying apparatus 100 of the first embodiment shown in FIG. 1. The like components are expressed by the like symbols and are not specifically described. The vehicle location specifying process of the third embodiment differs from the vehicle location specifying process of the first embodiment shown in FIG. 5 by addition of steps S111,

S112 and S113. Otherwise the vehicle location specifying process of the third embodiment is similar to the vehicle location specifying process of the first embodiment. The like steps are shown by the like step numbers and are not specifically described.

The vehicle location specifying process of the third embodiment moves (shifts) an area estimated as the existing area in the image under a predefined condition. The following describes its concrete process with reference to FIGS. 11 and 12.

As shown in FIG. 11, after the estimated location information is obtained at step S110, the area estimator 113 specifies a nearest point (step S111). This step S111 is identical with step S116 of the second embodiment described above.

The area estimator 113 subsequently refers to the vector table to identify an object feature related to the nearest point specified at step S111 and determines whether this identified object feature is identical with an object feature related to a specific point previously specified as the location of the vehicle (step S112).

When it is determined that the object feature related to the nearest point is identical with the object feature related to the specific point previously specified as the location of the vehicle (step S112: YES), the area estimator 113 estimates an area shifted toward the edge of the taken image from the previously estimated existing area, as a current existing area (step S113). When the previously estimated existing area is located in the left half area of the taken image, the area estimator 113 estimates an area shifted by a predetermined amount toward the left edge of the taken image, as a current existing area. When the previously estimated existing area is located in the right half area of the taken image, on the other hand, the area estimator 113 estimates an area shifted by a predetermined amount toward the right edge of the taken image, as a current existing area.

FIGS. 13A and 13B are diagrams illustrating one example of the processing of step S113. FIG. 13A shows an image F1 obtained in a previous cycle of the vehicle location specifying process, and FIG. 13B shows an image F11 obtained in a current cycle of the vehicle location specifying process. The image F1 of FIG. 13A is similar to the image F1 of FIG. 7, with addition of a center point $Ac1$ of an existing area $Ar1$ in FIG. 13A. FIG. 13B shows a fourth vector V_{cs} in the image F11, like FIG. 13A.

As shown in FIG. 13A, in the previous cycle of the vehicle location specifying process, a left half area $Ar1$ of the image F1 is identified as the existing area. At step S113 in the current cycle of the vehicle location specifying process, as shown in FIG. 13B, an area $Ar11$ shifted toward the left edge in the image F11 is specified as a new existing area. In this embodiment, "shifting toward the left edge" means shifting a center point of an area toward the left edge. More specifically, a center point $Ac2$ of the existing area $Ar11$ shown in FIG. 13B is shifted by AA toward the left edge from the center point $Ac1$ of the existing area $Ar1$ shown in FIG. 13A. The position of the shifted center point has no change in the vertical direction in the existing area. According to this embodiment, the left edge of the existing area is identical with the left edge of the image. Accordingly, the left edge of the existing area does not shift accompanied with a leftward shift of the center point of the existing area. The existing area $Ar11$ shown in FIG. 13B is accordingly smaller than the existing area $Ar1$ shown in FIG. 13A.

As shown in FIG. 13, the sign 10 placed on the left side of the lane 50 shifts leftward in the view from the imaging camera 200 with the move of the vehicle. Accordingly, the

11

location of the sign **10** in the taken image is moved leftward in an image obtained at the later time. In the case of extraction of the same object feature, the area shifted toward the edge in the image obtained at the later time is thus estimated as the existing area. According to this embodiment, the shift amount AA of the existing area is stored in advance as a predefined amount according to the vehicle speed in the ROM **130**. For example, the shift amount AA may be set to increase with an increase in current vehicle speed.

As shown in FIG. **12**, after the processing of step **S113** described above, the processing of and after step **S130** is then executed as described above.

When it is determined at step **S112** that the object feature related to the nearest point is not identical with the object feature related to the specific point previously specified as the location of the vehicle (step **S112**: NO), as shown in FIG. **12**, the procedure performs the processing of and after step **S115** as described above. In this case, the area estimator **113** calculates the third vectors **Vgp** and the fourth vector **Vcs** and estimates the existing area based on the fourth vector **Vcs**. When the object feature related to the nearest point is not identical with the object feature related to the specific point previously specified as the location of the vehicle, the object feature in the current cycle of the vehicle location specifying process is more likely to be different from the previous object feature. Accordingly, it is not reasonable to estimate the area shifted toward the edge in the image obtained at the later time as the new existing area as described above. For this reason, like the first embodiment, the area estimator **113** newly calculates the fourth vector **Vcs** and estimates the new existing area based on the fourth vector **Vcs**.

The location specifying apparatus of the third embodiment described above has the similar advantageous effects to those of the location specifying apparatus **100** of the first embodiment. Additionally, when the object feature identified in the current cycle of the vehicle location specifying process is expected to be the same as the previously identified object feature, the location specifying apparatus of the third embodiment estimates the area shifted toward the edge of the image from the previously identified area, as the new existing area. This ensures estimation of the existing area with the higher accuracy. Shifting the area toward the edge of the image narrows the estimated existing area. This further reduces the processing load of the CPU **110** in the process of extracting candidate features. Accordingly, this further shortens the time required for specifying the location of the vehicle.

D. Fourth Embodiment

FIG. **14** is a diagram showing one example of settings in a vector table according to a fourth embodiment. A location specifying apparatus of the fourth embodiment differs from the location specifying apparatus **100** of the first embodiment by the settings in the vector table. Otherwise the configuration of the location specifying apparatus of the fourth embodiment is similar to the configuration of the location specifying apparatus **100** of the first embodiment. The like components are expressed by the like symbols and are not specifically described.

As shown in FIG. **14**, the vector table of the fourth embodiment differs from the vector table of the first embodiment shown in FIG. **3** by addition of an "angle" field. Otherwise the configuration (fields) of the vector table of the fourth embodiment is similar to the configuration of the

12

vector table of the first embodiment and is thus not specifically described. The vector table of FIG. **14** has registry of four records with respect to four specific points **p5**, **p6**, **p7** and **p8** which are different from the specific points **p1** to **p3** described above. According to this embodiment, the angle field stores angles between first vectors and a normal line of a representative surface of an object feature.

FIG. **15** is a diagram illustrating one example of settings in the angle field of the vector table. In the example of FIG. **15**, four specific points **p5** to **p8** are set on a middle line **56** of a lane **51**. A sign **11** is set as the object feature related to these four specific points **p5** to **p8**. An object feature identifier "L11" shown in FIG. **14** is the identifier of the sign **11**. As shown in FIG. **15**, first vectors **Vps5** to **Vps8** are respectively set in relation to four specific points **p5** to **p8**.

As shown in broken-line bubbles of FIG. **15**, angles between a normal vector **PL** of a representative surface **Sr** of the sign **11** and the first vectors **Vps5** to **Vps8** (hereinafter called "object feature angles") are set in relation to the respective specific points **p5** to **p8**. According to this embodiment, the "angle between the normal vector **PL** and the first vector **Vps**" denotes the smaller angle between two angles obtained by projecting these two vectors **PL** and **Vps** on three planes, i.e., X-Y plane, X-Z plane and Y-Z plane and determining angles between two projection vectors on each plane. According to this embodiment, the X-Y plane denotes a horizontal plane at the installation position of the sign **11**. The X-Z plane denotes a plane perpendicular to the X-Y plane and parallel to the middle line **56**. The Y-Z plane denotes a plane perpendicular to the X-Y plane and orthogonal to the middle line **56**. FIG. **15** shows the angles between the projection vectors on the X-Y plane as the representative of the angles between the normal vector **PL** and the first vectors **Vps** associated with the respective specific points **p5** to **p8**.

As shown in FIGS. **14** and **15**, an angle $\theta \times 5$ between the normal vector **PL** and the first vector **Vps5** is set as part of the object feature angles with respect to the specific point **p5**. Similarly, an angle $\theta \times 6$ between the normal vector **PL** and the first vector **Vps6** is set as part of the object feature angles with respect to the specific point **p6**. An angle $\theta \times 7$ between the normal vector **PL** and the first vector **Vps7** is set as part of the object feature angles with respect to the specific point **p7**. An angle $\theta \times 8$ between the normal vector **PL** and the first vector **Vps8** is set as part of the object feature angles with respect to the specific point **p8**.

As shown in FIG. **15**, with respect to the object feature angles, the angle between the projection vectors on the X-Y plane is set to the larger value at the specific point nearer to the sign **11**. In the example of FIG. **15**, the specific point **p8** is located lateral to the sign **11** along the middle line **56** and has the object feature angle of 90 degrees. Different specific points have different object feature angles in this manner and thereby have different external shapes of the representative surface of the object feature in the taken image.

FIG. **16** is a flowchart showing a procedure of vehicle location specifying process according to the fourth embodiment. The vehicle location specifying process of the fourth embodiment differs from the vehicle location specifying process of the first embodiment shown in FIG. **5** by addition of step **S131** and replacement of step **S135** with step **S135a**. Otherwise the vehicle location specifying process of the fourth embodiment is similar to the vehicle location specifying process of the first embodiment. The like steps are shown by the like step numbers and are not specifically described.

After extraction of candidate features at step S130, the locator 114 corrects the shape of each of the extracted candidate features based on the object feature angles related to a nearest point (step S131). More specifically, the locator 114 specifies a nearest point and refers to the vector table to identify the object feature angles related to the nearest point. The locator 114 subsequently performs image processing using the identified object feature angles such that a representative surface of each candidate feature faces the front in the image (such as to make the normal vector PL of the sign 11 parallel to the first vector Vps) and thereby corrects (deforms) the shape of the candidate feature. Any of known techniques may be employed for such image processing.

The locator 114 performs pattern matching for each of the corrected candidate features with object features related to the respective specific points, so as to identify the object feature included in the taken image (step S135a). After the processing of step S135a, the processing of steps S140 to S150 is then executed as described above.

The location specifying apparatus of the fourth embodiment described above has the similar advantageous effects to those of the location specifying apparatus 100 of the first embodiment. Additionally, the location specifying apparatus of the fourth embodiment sets in advance object feature angles in relation to the respective specific points and corrects (deforms) the shape of each candidate feature based on the object feature angles related to the nearest point. Irrespective of the location of the vehicle on the middle line 56 of the lane 51 relative to the object feature, this enables the object feature to be identified with high accuracy by pattern matching for the candidate features.

E. Fifth Embodiment

E1. Configuration of Apparatus

FIG. 17 is a block diagram illustrating the schematic configuration of a location specifying apparatus 100b according to a fifth embodiment. The location specifying apparatus 100b of the fifth embodiment differs from the location specifying apparatus 100 of the first embodiment shown in FIG. 1 by that a laser scanner input interface (I/F) module 170 is additionally provided and that the hard disk drive 140 includes a sixth vector information storage unit 145 in place of the second vector information storage unit 142. Otherwise the configuration of the location specifying apparatus 100b of the fifth embodiment is similar to the configuration of the location specifying apparatus 100 of the first embodiment. The like components are expressed by the like symbols and are not specifically described.

The laser scanner input interface module 170 has an interface for connection with a laser scanner 400 and is connected with the laser scanner 400. The laser scanner input interface module 170 is also connected with the internal bus 190 and sends the measurement result by the laser scanner 400 to the CPU 110 via the internal bus 190. The laser scanner 400 emits a laser pulse and receives its reflected wave to measure a distance, a horizontal angle and a vertical angle of an object relative to the position of the laser scanner 400.

FIG. 18 is a diagram illustrating a sixth vector in the fifth embodiment. The sixth vector is stored in advance in the sixth vector information storage unit 145 shown in FIG. 17. As shown in FIG. 18, a sixth vector Vpc denotes a vector directed from a specific point to the imaging camera 200 when the GPS positioning device 300 is located vertically above the specific point. FIG. 18 shows the sixth vector Vpc when the GPS positioning device 300 is located vertically

above a specific point p1. This sixth vector Vpc is, however, a fixed vector irrespective of the location of the vehicle. More specifically, when the GPS measuring device 300 is located vertically above another specific point, a vector directed from this another specific point to the imaging camera 200 is identical with the sixth vector Vpc shown in FIG. 18. When the GPS measuring device 300 is located vertically above any position other than any specific point, a vector directed from this position to the imaging camera 200 is identical with the sixth vector Vpc shown in FIG. 18. This sixth vector Vpc may be determined in advance by measurement.

E2. Vehicle Location Specifying Process

FIG. 19 is a flowchart showing a procedure of vehicle location specifying process according to the fifth embodiment. After the power-on, the vehicle location specifying process is performed repeatedly in the location specifying apparatus 100b. The image data acquirer 111 first obtains image data (step S205). This step S205 is similar to step S105 in the above embodiments and is not specifically described.

The area estimator 113 specifies nearby specific points around the estimated current location of the vehicle, based on the positioning result by the GPS positioning device 300 at the image-taking time (step S210). The GPS positioning device 300 receives signals from a plurality of GPS satellites and respectively specifies a plurality of areas estimated to include the current location, based on the respective signals. The area estimator 113 specifies specific points included in an overlap area of the plurality of specified areas, as the nearby specific points around the estimated current location at step S210. The method of specifying the nearby specific points around the estimated current location is not limited to this procedure, but another procedure as described below may be employed for the same purpose. The area estimator 113 may specify specific points included in a predetermined area (for example, a circular area with a predetermined radius) about the location determined by the positioning result of the GPS positioning device 300, as the nearby specific points around the estimated current location. In the description below, it is assumed that the above three specific points p1, p2 and p3 shown in FIG. 2 are specified at step S210.

With regard to each of the nearby specific points specified at step S210, the area estimator 113 identifies the end point of a first vector Vps in the taken image on the assumption that the first vector Vps is included in the taken image and specifies a predetermined area about the position of the identified end point as an area that is a possible candidate for the existing area (hereinafter referred to as "candidate existing area") (step S215). According to this embodiment, the area estimator 113 specifies a square area with a predetermined number of pixels on each side about the position of the end point of the first vector Vps in the image, as the candidate existing area. The length of each side of this candidate existing area is set according to the distance between the specific point and the object feature (magnitude of the first vector Vps). More specifically, the length of each side of the candidate existing area is set to the larger value in relation to the specific point having the smaller distance from the object feature. The size of an identical object feature in the taken image decreases with an increase in distance of the vehicle from the object feature. The above configuration accordingly enables an area of adequate size to be specified with elapse of time, as the candidate existing area. After the processing of step S215, the area estimator

15

113 sums up all the candidate existing areas with regard to the respective specific points obtained at step S215, as an existing area (step S220).

FIG. 20 is a diagram illustrating an existing area according to the fifth embodiment. An image F1 of FIG. 20 differs from the image F1 of FIG. 7 by replacement of the existing area Ar1 with an existing area Ar20 but is otherwise similar to the image F1 of FIG. 7.

In FIG. 20, the existing area Ar20 is shown as an area encompassed by the thick solid line. This existing area Ar20 is a total area of a candidate existing area Ar11, a candidate existing area Ar12 and a candidate existing area Ar13. The candidate existing area Ar11 denotes a candidate existing area with regard to the specific point p1. More specifically, the candidate existing area Ar11 denotes an estimated area where the object feature (sign 10) is expected to exist in the taken image when the current location of the vehicle is at the specific point p1. Similarly, the candidate existing area Ar12 denotes a candidate existing area with regard to the specific point p2, and the candidate existing area Ar13 denotes a candidate existing area with regard to the specific point p3. Among the three specific points p1, p2 and p3, the specific point p1 is most distant from the sign 10 as the object feature, the specific point p2 is second most distant from the sign 10, and the specific point p3 is nearest to the sign 10. Accordingly, the candidate existing area Ar11 is the smallest, the candidate existing area Ar12 is the second smallest and the candidate existing area Ar13 is the largest as shown in FIG. 20.

Referring back to FIG. 19, after the processing of step S220, the locator 114 performs the processing of steps S225 and S230. These two steps are respectively similar to steps S130 and S135 in the above embodiments and are thus not specifically described.

After identification of an object feature at step S230, the locator 114 specifies a vector directed from the imaging camera 200 to the identified object feature in the taken image (step S235). In the example of FIG. 20, a vector Vf directed from the center Cp of the image F1 to the center point of the object feature is specified at step S235, as the vector directed from the imaging camera 200 to the object feature in the taken image.

The locator 114 controls the laser scanner 400 via the laser scanner input interface module 170 to determine the distance, the horizontal angle and the vertical angle from the laser scanner 400 to the object feature. According to this embodiment, the laser scanner 400 is placed in the vicinity of the imaging camera 200. Accordingly, the distance, the horizontal angle and the vertical angle from the laser scanner 400 to the object feature can be regarded as the distance, the horizontal angle and the vertical angle from the imaging camera 200 to the object feature. Accordingly, the locator 114 determines the distance, the horizontal angle and the vertical angle from the imaging camera 200 to the object feature (step S240).

The locator 114 subsequently specifies a vector directed from the actual imaging camera 200 (not in the image F1) to the object feature (fourth vector Vcs), based on the vector specified at step S235 (for example, vector Vf) and the distance, the horizontal angle and the vertical angle determined at step S240 (step S245). The locator 114 reads out the sixth vector Vpc stored in the sixth vector information storage unit 145 and adds the sixth vector Vpc to the fourth vector Vcs specified at step S245, so as to determine a vector directed from the current location to the object feature (step S250). The locator 114 then specifies the current location of

16

the vehicle, based on the vector obtained at step S250 and the coordinates of the object feature (step S255).

FIG. 21 is a diagram schematically illustrating the processing detail of steps S250 and S255. As described above, the fourth vector Vcs shown in FIG. 21 is specified at step S245. A vector directed from a current location pp of the vehicle to the sign 10 as the object feature (vector Vt) is accordingly determined by adding the sixth vector Vpc to this fourth vector Vcs. The coordinates of the current location pp are then specified, based on this vector Vt and the known coordinates of the sign 10.

The location specifying apparatus 100b of the fifth embodiment described above has the similar advantageous effects to those of the location specifying apparatus 100 of the first embodiment. As clearly understood from the above respective embodiments, it is not essential to store the second vector Vgc in advance in the location specifying apparatus. Like this embodiment, a vector Vpc directed from a certain point (point vertically below the GPS positioning device 300) to the imaging camera 200 may alternatively be stored in advance.

E3. Modification of Fifth Embodiment

The procedure of the vehicle location specifying process of the fifth embodiment may be modified as described below. After the processing of steps S205 to S230, the CPU 110 may identify the candidate existing area in which the identified object feature (more specifically, center point of the object feature) is located in the taken image. The CPU 110 may subsequently specify the position of the specific point related to the identified candidate existing area in which the object feature is located, as the current location of the vehicle. In the example of FIG. 20, the sign 10 is located in the candidate existing area Ar12, so that the position of the specific point p2 is specified as the current location of the vehicle. The candidate existing area is set as an area in which the object feature is possibly included in the taken image when the vehicle is located at the specific point related to the candidate existing area. The presence of the object feature in a certain candidate existing area accordingly shows that the vehicle is located at or closest to the specific point related to the candidate existing area. The configuration of this modification accordingly enables the current location of the vehicle to be specified with high accuracy. Additionally, this configuration simplifies the processing and reduces the overall processing load of the vehicle location specifying process, thus shortening the time required for specifying the current location of the vehicle.

F. Modifications

F1. Modification 1

In the above embodiments other than the second and the fifth embodiments, the vehicle location specifying process identifies the first vector Vps most approximate to the fifth vector Vgs at step S145. The disclosure is, however, not limited to this configuration. For example, in a modified procedure the CPU 110 may calculate a vector (Vgs-Vgp) with regard to each specific point by subtracting the third vector Vgp from the fifth vector Vgs, compare the first vector Vps associated with the specific point with this calculated vector and identify a specific point having the smallest difference between these two vectors. The vector (Vgs-Vgp) obtained by subtracting the third vector Vgp from the fifth vector Vgs is more approximate to the first vector Vps. Identifying a specific point related to the first vector Vps most approximate to this obtained vector accordingly leads to identifying the specific point closest to the

actual location of the vehicle and thereby enables the location of the vehicle to be specified with higher accuracy.

Similarly, in the second embodiment, the vehicle location specifying apparatus **100a** identifies the fourth vector V_{cs} most approximate to the fifth vector V_{gs} at step **S145a**. The disclosure is, however, not limited to this configuration. For example, in a modified procedure the CPU **110** may calculate a vector ($V_{gs}-V_{gc}$) with regard to each specific point by subtracting the second vector V_{gc} from the fifth vector V_{gs} , compare the fourth vector V_{cs} associated with the specific point with this calculated vector and identify a specific point having the smallest difference between these two vectors. The vector ($V_{gs}-V_{gc}$) obtained by subtracting the second vector V_{gc} from the fifth vector V_{gs} is more approximate to the fourth vector V_{cs} . Identifying a specific point related to the fourth vector V_{cs} most approximate to this obtained vector accordingly leads to identifying the specific point closest to the actual location of the vehicle and thereby enables the location of the vehicle to be specified with higher accuracy.

F2. Modification 2

In the above embodiments other than the second and the fifth embodiments, the position of the specific point identified at step **S145** is specified as the location of the vehicle. In the second embodiment, the position of the specific point identified at step **S145a** is specified as the location of the vehicle. The disclosure is, however, not limited to these configurations. As the vehicle moves during the time period of obtaining image data at step **S105** and specifying the location of the vehicle at step **S150**, the location of the vehicle specified at step **S150** is deviated from the actual location of the vehicle when step **S150** is actually performed. In a modified procedure the CPU **110** may accordingly measure the time required from the start of step **S105** to the end of step **S150**, estimate a moving distance of the vehicle from the start of step **S105** to the end of step **S150** based on the calculated time and the vehicle speed, correct the position of the specific point identified at step **S145** or **S145a** in the moving direction of the vehicle based on the estimated moving distance, and specify this corrected position as the location of the vehicle. This modification enables the current location of the vehicle to be specified with higher accuracy.

F3. Modification 3

In the above embodiments other than the third and the fifth embodiments, the existing area is estimated as either a right half area or a left half area of an image. The disclosure is, however, not limited to this configuration. For example, the existing area may be estimated as one of four divisional areas, upper left, lower left, upper right and lower right areas of an image. With reference to the example of FIG. 7, in a modified procedure the area estimator **113** may determine a projection vector of the fourth vector V_{cs} on the plane perpendicular to the middle line **55**, identify whether the projection vector is a vector directed rightward or a vector directed leftward as well as whether the projection vector is a vector directed upward or a vector directed downward, and estimate one of the four areas as the existing area.

The shape of the existing area is not limited to the rectangular shape but may be any shape such as circular shape or triangular shape. When the object feature is not a road surface marking but is a feature placed outside of the road such as a sign or a power pole, the existing area may be estimated after exclusion of an area distinctly estimated as the road from the taken image. In a procedure employed for specifying the area estimated as the road the area estimator **113** may detect a road marking line and a curb-

stone by, for example, pattern matching and specify an area (lane) defined by such detection result as the area as the road.

F4. Modification 4

In the second embodiment, the fourth vector V_{cs} set in the vector table is the vector directed from the imaging camera **200** to the object feature when the vehicle (GPS positioning device **300**) is located vertically above each specific point. The disclosure is, however, not limited to this configuration. For example, a vector directed from the imaging camera **200** to the object feature when the vehicle (GPS positioning device **300**) is located at a point offset by a predetermined distance along the moving direction of the vehicle or its opposite direction from the position vertically above each specific point may be set as the fourth vector V_{cs} in the vector table.

F5. Modification 5

In the above embodiments, the specific points are set on the middle line **55** or on the middle line **56**. The specific points may alternatively be set at any positions along the lane **50** or the lane **51**, instead of the middle line **55** or **56**. The specific points are set at predetermined intervals along the middle line **55** or **56** in the above embodiments but may be set at various intervals.

F6. Modification 6

In the above embodiments, only one type of the second vector V_{gc} is stored in advance in the hard disk drive **140**. Instead of only one type, any number of different types of vectors may be stored as the second vectors V_{gc} . For example, in an application of the location specifying apparatus **100** to a plurality of different types of vehicles, the different types of vehicles may have different installation positions of the GPS positioning device **300** and different installation positions of the imaging camera **200**. The second vectors V_{gc} for the respective types of vehicles may thus be stored in the hard disk drive **140**. In a modified procedure the CPU **110** may identify the type of the vehicle prior to or during the vehicle location specifying process and use the second vector V_{gc} corresponding to the identified type of the vehicle. In this modified configuration the CPU **110** uses the vector reflecting the actual locations of the GPS positioning device **300** and the imaging camera **200** in the vehicle, as the second vector V_{gc} . This accordingly enables the location of the vehicle to be specified with higher accuracy.

F7. Modification 7

In the above embodiments, the start point and the end point of each of the first to the fourth vectors may be exchanged with each other. For example, in the first embodiment, vectors directed from an object feature as the start point to respective specific points as the end point may be employed as the first vectors V_{ps} . In the second embodiment, vectors directed from an object feature as the start point to the position of the imaging camera **200** as the end point when the vehicle (GPS positioning device **300**) is located vertically above the respective specific points may be employed as the fourth vectors V_{cs} .

F8. Modification 8

In the fourth embodiment, the candidate features are subjected to correction of the shape based on the object feature angles at step **S131** in FIG. 16. In place of or in addition to the candidate features, the shapes of polygons of object features related to the respective specific points may be subjected to correction.

F9. Modification 9

In the fourth embodiments, the angles associated with each specific point (object feature angles) are the angles between the normal vector PL and the first vector V_{ps} . These angles may be replaced with angles between the represen-

tative surface S_r of the object feature and the first vector V_{ps} . These angles may be specified as follows. The locator **114** may project the representative surface S_r and the first vector V_{ps} on the X-Y plane, the X-Z plane and the Y-Z plane and specify the smallest angle among the angles between the projection of the representative surface S_r and the projection of the first vector V_{ps} on each plane, as the angle between the representative surface S_r and the first vector V_{ps} . In general, any angle associated with an angle between a representative surface of a predetermined feature and a first vector may be employed as the relevant angle in the location specifying apparatus of the disclosure.

F10. Modification 10

The configurations of the location specifying apparatuses **100** and **100a** of the above embodiments are only illustrative and may be modified in various ways. For example, the first vector information storage unit **141**, the second vector information storage unit **142** and the feature information storage unit **143** are all stored in the hard disk drive **140** in the above embodiments but may be stored in the ROM **130** instead of the hard disk drive **140**. In the above embodiments, the imaging camera **200** and the GPS positioning device **300** are provided separately from the location specifying apparatus **100**. At least one of the imaging camera **200** and the GPS positioning device **300** may, however, be provided integrally with the location specifying apparatus **100**. The imaging camera **200** is installed to have the imaging range ahead of the vehicle in the above embodiments but may alternatively be installed to have the imaging range behind the vehicle. The object features described in the above embodiments are the signs **10** and **11** respectively located outside of the lane **50** and the outside of the lane **51**. The object feature may, however, be a road surface marking. The GPS positioning device **300** may be replaced with a Galileo system being created by the EU. In the above embodiments, the image data used in the vehicle location specifying process is data obtained by the imaging camera **200**. The disclosure is, however, not limited to this configuration. For example, the image data may be data defined by reflected waves of radio waves in millimeter waveband or laser emitted from the vehicle.

F11. Modification 11

In the above embodiments, part of the configuration implemented by the hardware may be replaced by software configuration, while part of the configuration implemented by the software may be replaced by hardware configuration. When part or all of the functions of the disclosure is implemented by the hardware, the hardware may be provided as various circuits including integrated circuits and discrete circuits or as various combinations of these circuits. When part or all of the functions of the disclosure is implemented by the software, the software (computer program) may be provided in the form of storage in a computer readable recording medium. In the description hereof, the "computer readable recording medium" is not limited to a portable recording medium such as a flexible disk or a CD-ROM but includes internal storage devices of the computer such as various RAMs and ROMs, as well as external storage devices fixed to the computer such as hard disk drives. In other words, the "computer readable recording medium" is used in the broad sense including various recording media that are capable of storing data in a non-transitory manner.

The above embodiments illustrate and describe on the assumption that the vehicle **500** keeps to the left side of the road. The disclosure is, however, not limited to this configuration, but the vehicle **500** may keep to the right side of

the road. In other words, the vehicle **500** may keep to the left or keep to the right in conformity with the traffic regulations in each nation where the apparatus and the non-transitory computer readable recording medium of the disclosure are applied. In the above embodiments, the sign **10** is not limited to the sign shown in FIG. 7 and FIGS. 13A and 13B. The sign **10** may be any sign used in each nation where the apparatus and the non-transitory computer readable recording medium of the disclosure are applied. As described above, the non-essential descriptions in the above embodiments and modifications may be changed according to, for example, the traffic regulations and the culture of each nation.

The disclosure is not limited to the embodiments and the modifications described above but may be implemented by a diversity of other configurations without departing from the scope of the disclosure. For example, the technical features of any of the above embodiments and their modifications corresponding to the technical features of each of the aspects described in Summary may be replaced or combined appropriately, in order to solve part or all of the problems described above or in order to achieve part or all of the advantageous effects described above. Any of the technical features may be omitted appropriately unless the technical feature is described as essential in the description hereof.

For example, according to one aspect of the disclosure, there is provided a location specifying apparatus that specifies a location of a moving body. This location specifying apparatus comprises a first vector information storage unit configured to store vector information regarding a first vector connecting a specific point-relevant location, which is associated with each of a plurality of specific points set along a road, with a location of a predetermined feature, related to position information regarding a position of the specific point; a predetermined feature location information storage unit configured to store predetermined feature location information regarding the location of the predetermined feature; an image data acquirer configured to obtain image data ahead of the moving body; and a locator configured to identify a location of the predetermined feature in an image shown by the image data and specify the location of the moving body based on the identified location of the predetermined feature and the vector information.

The location specifying apparatus of this aspect stores the vector information (information regarding the first vector connecting the specific point-relevant position with the location of the predetermined feature) related to the position information regarding the position of the specific point. The location specifying apparatus of this aspect uses this vector information to identify the location of the predetermined feature in the image and thereby makes only part of the area in the image subjected to processing. Compared with a configuration that makes the entire area of the image subjected to processing, this configuration reduces the processing load of the location specifying apparatus. Accordingly this aspect shortens the time required for specifying the location of the vehicle.

The location specifying apparatus of the above aspect may further comprise a location information acquirer configured to obtain estimated location information from a location sensor mounted on the moving body to detect the estimated location information, wherein the estimated location information is regarding a location estimated as a current location of the moving body when the image data is obtained; and an area estimator configured to estimate a partial area in the image shown by the image data as a

predetermined feature existing area in which the predetermined feature exists, based on the vector information related to a specific point near to a position indicated by the obtained estimated location information, wherein the locator analyzes image data of the predetermined feature existing area in the obtained image data to identify the location of the predetermined feature in the image, and specifies the location of the moving body, based on the identified location of the predetermined feature, the estimated location information and the vector information. The location specifying apparatus of this aspect estimates a partial area in the image as the predetermined feature existing area, analyzes the image data of the predetermined feature existing area to identify the location of the predetermined feature, and specifies the location of the moving body. Compared with a configuration that analyzes the image data with regard to the entire area in the image, this configuration reduces the processing load of the location specifying apparatus. Accordingly this aspect shortens the time required for specifying the location of the vehicle.

The location specifying apparatus of the above aspect may further comprise a receiver configured to receive a reflected wave, in order to obtain the image data ahead of the moving body; and a second vector information storage unit configured to store information regarding a second vector connecting a location of the location sensor with a location of the receiver. The specific point-relevant location may be an absolute position of each specific point. The area estimator may be configured to specify a third vector connecting the location indicated by the obtained estimated location information with the position of each specific point; specify a fourth vector connecting the location of the receiver with the location of the predetermined feature when the image data is obtained, by using the first vector, the second vector and the third vector; and estimate the predetermined feature existing area, based on the fourth vector. The location specifying apparatus of this aspect specifies the fourth vector connecting the location of the receiver and the location of the predetermined feature when the image data is obtained, and estimates the predetermined feature existing area based on the fourth vector. This aspect enables the area where the predetermined feature exists to be estimated in the image with high accuracy.

In the location specifying apparatus of the above aspect, the second vector information storage unit may store a plurality of vectors according to different types of the moving bodies, as the second vector. The location specifying apparatus of this aspect stores a plurality of vectors according to the different types of the moving bodies as the second vector and thereby selectively uses the vector to be used as the second vector according to the type of the moving body on which the location specifying apparatus is mounted. This configuration uses the vector suitable for the actual locations of the location sensor and the receiver in the moving body, as the second vector. This aspect thus enables the location of the moving body to be specified with higher accuracy.

The location specifying apparatus of the above aspect may further comprise a receiver configured to receive a reflected wave, in order to obtain the image data ahead of the moving body. The specific point-relevant location may be a location of the receiver when the receiver is located at a predetermined position above each specific point. The area estimator may identify a first vector related to a specific point nearest to the location indicated by the estimated location information, and may estimate the predetermined feature existing area based on the identified first vector. The first vector related to the specific point nearest to the location

indicated by the estimated location information is more approximate to a vector connecting the location of the receiver with the location of the predetermined feature at the actual current location of the moving body, compared with the first vectors related to the other specific points. Accordingly, the location specifying apparatus of this aspect ensures estimation of the predetermined feature existing area with high accuracy.

In the location specifying apparatus of the above aspect, the locator may specify a fifth vector connecting the identified location of the predetermined feature with the location indicated by the estimated location information. The locator may identify a first vector most approximate to the specified fifth vector out of the first vectors related to the plurality of specific points, and may specify the location of the moving body based on a position of a specific point related to the identified first vector. The first vector related to the specific point nearer to the current location of the moving body is more likely to be approximate to the fifth vector. Accordingly the location specifying apparatus of this aspect enables the location of the moving body to be specified with high accuracy.

In the location specifying apparatus of the above aspect, the image data acquirer may obtain a plurality of image data at different times. The area estimator may estimate the predetermined feature existing area with respect to each of a plurality of images shown by the plurality of image data, such that with respect to an image shown by image data obtained at a later time, an area nearer to an edge of the image is estimated as the predetermined feature existing area. In general, the location of the predetermined feature in the image becomes closer to the edge of the image with a decrease in distance from the predetermined feature. Accordingly the location specifying apparatus of this aspect ensures estimation of the predetermined feature existing area with higher accuracy.

In the location specifying apparatus of the above aspect, the image data acquirer may obtain a plurality of image data at different times. The area estimator may estimate the predetermined feature existing area with respect to each of a plurality of images shown by the plurality of image data, such that with respect to an image shown by image data obtained at a later time, a smaller area is estimated as the predetermined feature existing area. In general, the location of the predetermined feature in the image becomes closer to the edge of the image with a decrease in distance from the predetermined feature. It is accordingly reasonable that a narrower (smaller) area nearer to the edge of the image is estimated as the predetermined feature existing area, with respect to the image obtained at the later time. The location specifying apparatus of this aspect estimates the smaller area as the predetermined feature existing area with respect to the image obtained at the later time and thereby further reduces the processing load for analysis of the image data.

The location specifying apparatus of the above aspect may further comprise a shape information storage unit configured to store shape information regarding a shape of the predetermined feature specified by a reflected wave from the predetermined feature. The first vector information storage unit may store a relevant angle associated with an angle between a representative surface of the predetermined feature and the first vector, related to the position information regarding the position of the specific point, in addition to the vector information. The locator may correct at least one of a shape of a feature in image data of the predetermined feature existing area and the shape of the predetermined feature shown by the shape information stored in the shape

23

information storage unit, based on the relevant angle, and may identify a location of the predetermined feature in the image using a corrected shape. In general, the shape of the predetermined feature specified by the reflected wave differs at different points. The location specifying apparatus of this aspect, however, corrects at least one of the shape of the feature in the image data of the predetermined feature existing area and the shape of the predetermined feature shown by the shape information stored in the shape information storage unit, based on the relevant angle associated with the angle between the representative surface of the predetermined feature and the first vector, and identifies the location of the predetermined feature in the reflected wave image using the corrected shape. This configuration enables the location of the predetermined feature to be identified with high accuracy, irrespective of the location of the vehicle.

According to another aspect of the disclosure, there is provided a non-transitory computer-readable medium that has encoded thereon a data structure that includes at least one data table storing vector information executed in a process of specifying a location of a moving body. In the non-transitory computer-readable medium the vector information regarding a vector connecting a specific point-relevant location, which is associated with each of a plurality of specific points set along a road, with a location of a predetermined feature is related to position information regarding a positions of the specific point.

The invention claimed is:

1. A location calculation system comprising: circuitry configured to:
 - store vector information regarding a plurality of first vectors each connecting a specific point-relevant location, that is associated with each of a plurality of specific points set along a road, with a location of a predetermined feature, in relation to position information regarding each position of the plurality of specific points;
 - store predetermined feature location information regarding the location of the predetermined feature;
 - obtain image data ahead of a moving body;
 - calculate a location of the predetermined feature in an image of the image data as obtained by the circuitry;
 - calculate a location of the moving body based on the location of the predetermined feature as calculated by the circuitry and the vector information; and
 - output the location of the moving body as calculated by the circuitry.
2. The location calculation system according to claim 1, wherein the circuitry is configured to:
 - obtain estimated location information of the moving body from a location sensor mounted on the moving body to detect the estimated location information, the estimated location information indicating a location estimated as a current location of the moving body when the image data is obtained;
 - estimate a partial area in the image of the image data as a predetermined feature existing area in which the predetermined feature would exist, based on the vector information related to a specific point of the plurality of specific points near to a position indicated by the estimated location information;
 - analyze image data of the predetermined feature existing area in the image data as obtained by the circuitry to calculate the location of the predetermined feature in the image; and

24

calculate the location of the moving body based on the location of the predetermined feature as calculated by the circuitry, the estimated location information, and the vector information.

3. The location calculation system according to claim 2, wherein the circuitry is configured to:

- store information regarding a second vector connecting a location of the location sensor with a location of a receiver configured to receive a reflected wave in order to obtain the image data ahead of the moving body;
- calculate a third vector connecting a location indicated by the estimated location information with a position of each of the plurality of specific points, which is the specific point-relevant location;
- calculate a fourth vector connecting the location of the receiver with the location of the predetermined feature when the image data is obtained, based on the first vector, the second vector and the third vector; and
- calculate the predetermined feature existing area based on the fourth vector.

4. The location calculation system according to claim 3, further comprising:

- a receiver that receives a reflected wave in order to obtain the image data ahead of the moving body.

5. The location calculation system according to claim 4, wherein

- the circuitry stores, as the second vector, a plurality of vectors according to different types of the moving body.

6. The location calculation system according to claim 2, wherein

- the specific point-relevant location is a location of a receiver configured to receive a reflected wave in order to obtain the image data ahead of the moving body when the receiver is located at a predetermined position above each of the plurality of the specific points, and the circuitry identifies a vector related to a specific point of the plurality of the specific points nearest to the location indicated by the estimated location information from among the plurality of the first vectors, and estimates the predetermined feature existing area based on the first vector as identified by the circuitry.

7. The location calculation system according to claim 2, wherein

- the circuitry is configured to:
 - calculate a fifth vector connecting the location of the predetermined feature as calculated by the circuitry with the location indicated by the estimated location information;
 - identify a vector most approximate to the specified fifth vector from among the plurality of the first vectors; and
 - calculate the location of the moving body based on a position of a specific point of the plurality of the specific points related to the vector as identified by the circuitry.

8. The location calculation system according to claim 2, wherein

- the circuitry is configured to:
 - obtain a plurality of the image data at different times; and
 - estimate the predetermined feature existing area with respect to each of a plurality of images of the plurality of image data, such that with respect to an image of the image data obtained at a later time, an area nearer to an edge of the image is estimated as the predetermined feature existing area.

9. The location calculation system according to claim 2, wherein

25

the circuitry is configured to:
 obtain a plurality of the image data at different times; and
 estimate the predetermined feature existing area with
 respect to each of a plurality of images of the plurality
 of image data, such that with respect to an image of
 image data obtained at a later time, a smaller area is
 estimated as the predetermined feature existing area.

10. The location calculation system according to claim 1,
 wherein

the circuitry is configured to:
 store shape information regarding a shape of the prede-
 termined feature specified by a reflected wave from the
 predetermined feature;

store a relevant angle information associated with an
 angle between a representative surface of the prede-
 termined feature and the first vector, in relation to the
 position information regarding each position of the
 plurality of specific points, in addition to the vector
 information;

correct at least one of a shape of a feature in the image
 data of the predetermined feature existing area and a
 shape of the predetermined feature of the shape infor-
 mation, based on the relevant angle; and

identify a location of the predetermined feature in the
 image using the shape as corrected by the circuitry.

11. The location calculation system according to claim 1,
 further comprising:

a location sensor mounted on the moving body that
 detects an estimated location information of the moving
 body.

12. The location calculation system according to claim 1,
 wherein

the predetermined feature is a sign on the road.

13. The location calculation system according to claim 8,
 wherein

the circuitry is configured to store an amount of shift
 between the predetermined feature existing areas at
 different times according to a speed of the moving
 body.

14. The location calculation system according to claim 13,
 wherein

26

the circuitry is configured to increase the amount of shift
 as a current speed of the moving body increases.

15. The location calculation system according to claim 1,
 further comprising:

a laser scanner that emits a laser pulse and receives a
 reflected wave of the laser pulse to measure at least one
 of a distance, a horizontal angle and a vertical angle of
 the predetermined feature relative to a position of the
 laser scanner.

16. The location calculation system according to claim 15,
 wherein

the circuitry is configured to calculate a fourth vector
 connecting the location of a receiver configured to
 receive a reflected wave in order to obtain the image
 data ahead of the moving body with the location of the
 predetermined feature when the image data is obtained,
 based on the distance, the horizontal angle and the
 vertical angle.

17. A non-transitory computer-readable medium includ-
 ing executable instructions, which when executed by cir-
 cuitry cause the circuitry to:

store vector information regarding a plurality of first
 vectors each connecting a specific point-relevant loca-
 tion, that is associated with each of a plurality of
 specific points set along a road, with a location of a
 predetermined feature, in relation to position informa-
 tion regarding each position of the plurality of specific
 points;

store predetermined feature location information regard-
 ing the location of the predetermined feature;

obtain image data ahead of a moving body;

calculate a location of the predetermined feature in an
 image of the image data as obtained by the circuitry;

calculate a location of the moving body based on the
 location of the predetermined feature as calculated by
 the circuitry and the vector information; and

output the location of the moving body as calculated by
 the circuitry.

* * * * *