

US009883873B2

(12) **United States Patent**
Kulas et al.

(10) **Patent No.:** **US 9,883,873 B2**
(45) **Date of Patent:** **Feb. 6, 2018**

(54) **SURGICAL BURS WITH GEOMETRIES HAVING NON-DRIFTING AND SOFT TISSUE PROTECTIVE CHARACTERISTICS**

408/109, 202, 227, 230, 147; 433/72, 75, 433/102, 134, 143, 144

See application file for complete search history.

(71) Applicant: **Medtronic PS Medical, Inc.**, Fort Worth, TX (US)

(56) **References Cited**

(72) Inventors: **John W. Kulas**, Eules, TX (US);
Donald E. Stearns, Fort Worth, TX (US)

U.S. PATENT DOCUMENTS

180,554 A	8/1876	Cubberley
372,400 A	11/1887	Browne
533,573 A	2/1895	Wilkins
1,309,706 A	7/1919	Taylor
2,847,885 A	8/1956	Wagner

(Continued)

(73) Assignee: **Medtronic PS Medical, Inc.**, Louisville, CO (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 3 days.

CN	101745679	6/2010
CN	201565651	9/2010

(Continued)

(21) Appl. No.: **13/944,650**

OTHER PUBLICATIONS

(22) Filed: **Jul. 17, 2013**

End Mill and Cutting Tool Design Criteria and Technical Features. Melin Tool Company. Retrieved from <http://www.endmill.com/pages/training/design.html> on Jun. 14, 2013. (pp. 1-4).

(65) **Prior Publication Data**

US 2015/0025559 A1 Jan. 22, 2015

(Continued)

(51) **Int. Cl.**
A61B 17/16 (2006.01)
B23C 5/10 (2006.01)
A61C 3/02 (2006.01)

Primary Examiner — Tatiana Nobrega
Assistant Examiner — Marcela I. Shirsat
(74) *Attorney, Agent, or Firm* — Harness Dickey


(52) **U.S. Cl.**
CPC **A61B 17/1695** (2013.01); **A61B 17/1615** (2013.01); **B23C 5/1009** (2013.01); **A61C 3/02** (2013.01); **B23C 2210/0407** (2013.01)

(57) **ABSTRACT**

A surgical bur includes a body and a drill point. The body includes flutes and lands. Each of the flutes includes a cutting edge, a rake face, and a clearance surface. Each of the lands is convex-shaped and disposed between a pair of the flutes. The drill point includes axial relief surfaces. Each of the axial relief surfaces has a planar area, is distinct from the lands and borders (i) a distal portion of one of the cutting edges, (ii) one of the lands, and (iii) one of the clearance surfaces.

(58) **Field of Classification Search**
CPC . A61B 17/16; A61B 17/1695; A61B 17/1615; A61B 17/1642; A61B 17/1617; B23C 5/02; B23C 5/1009; A61C 1/084; A61C 1/082; A61C 1/085; A61C 1/186; A61C 3/02; A61C 5/40
USPC 606/79-80, 180, 102, 107, 187, 83;

43 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,795,979 A 6/1957 Zerwick
 2,847,895 A 8/1958 Wagner
 2,903,922 A 9/1959 Ernst
 3,387,511 A 6/1968 Ackart, Sr.
 3,872,594 A 3/1975 Gerteisen
 3,937,222 A 2/1976 Banko
 4,445,509 A 5/1984 Auth
 4,594,034 A 6/1986 Maier
 4,600,006 A 7/1986 Baker
 4,602,900 A 7/1986 Arpaio, Jr. et al.
 4,699,550 A 10/1987 Baker
 4,740,121 A 4/1988 Arnold
 4,803,982 A 2/1989 Baker
 4,830,000 A 5/1989 Shutt
 4,951,690 A 8/1990 Baker
 4,975,003 A 12/1990 Hosoi
 4,978,350 A 12/1990 Wagenknecht
 5,007,911 A 4/1991 Baker
 5,011,342 A * 4/1991 Hsu 408/224
 5,122,134 A 6/1992 Borzone et al.
 5,143,490 A 9/1992 Koprass
 5,190,548 A 3/1993 Davis
 5,209,612 A 5/1993 Kish
 5,236,291 A 8/1993 Agapiou et al.
 5,302,059 A 4/1994 Fabiano
 5,429,504 A 7/1995 Peltier et al.
 5,467,837 A 11/1995 Miller et al.
 5,514,141 A 5/1996 Prizzi, Jr.
 5,575,650 A 11/1996 Niznick et al.
 5,579,185 A 11/1996 Tsai et al.
 D378,780 S 4/1997 Shuler
 5,618,293 A 4/1997 Sample et al.
 5,658,305 A 8/1997 Baker
 5,810,517 A 9/1998 Bostic
 5,833,402 A 11/1998 Martin
 5,846,035 A 12/1998 Karafillis et al.
 5,855,581 A 1/1999 Koblish et al.
 5,913,867 A 6/1999 Dion
 5,964,553 A * 10/1999 Blomberg et al. 408/224
 5,980,525 A 11/1999 Bryant et al.
 6,068,632 A 5/2000 Carchidi et al.
 6,132,448 A 10/2000 Perez et al.
 6,238,398 B1 5/2001 Lechot
 6,258,093 B1 7/2001 Edwards et al.
 6,332,886 B1 12/2001 Green et al.
 6,431,801 B2 8/2002 Vasudeva et al.
 6,435,780 B1 8/2002 Flynn
 6,511,493 B1 1/2003 Moutafis et al.
 6,514,258 B1 2/2003 Brown et al.
 6,547,495 B2 4/2003 Meece et al.
 6,562,046 B2 5/2003 Sasso
 6,579,298 B1 6/2003 Bruneau et al.
 6,682,349 B1 * 1/2004 Logeart A61C 3/02
 408/226
 6,783,533 B2 8/2004 Green et al.
 7,520,703 B2 4/2009 Rompel
 7,862,263 B2 1/2011 van Iperen
 8,414,228 B2 4/2013 Wells et al.
 8,460,298 B2 6/2013 O'Donoghue
 2003/0097133 A1 5/2003 Green et al.
 2004/0057803 A1 3/2004 Walrath
 2005/0203526 A1 9/2005 Ellis
 2005/0272004 A1 12/2005 Desrosiers
 2005/0273107 A1 12/2005 Stevens
 2005/0283160 A1 12/2005 Knisely et al.
 2006/0045639 A1 3/2006 Flynn et al.
 2006/0067797 A1 3/2006 Calamia
 2006/0085005 A1 4/2006 Kenealy et al.
 2006/0142775 A1 6/2006 Heneberry et al.
 2007/0010822 A1 1/2007 Zalenski et al.
 2007/0160437 A1 7/2007 Shultz et al.
 2007/0163416 A1 7/2007 Burgess
 2007/0213736 A1 9/2007 Ducharme
 2007/0280792 A1 12/2007 Kochan et al.
 2007/0298376 A1 12/2007 Kmiecz et al.

2008/0132929 A1 6/2008 O'Sullivan et al.
 2008/0140078 A1 * 6/2008 Nelson A61B 17/1615
 606/80
 2008/0167653 A1 7/2008 Watlington et al.
 2008/0177294 A1 7/2008 O'Neil et al.
 2008/0193234 A1 8/2008 Davancens et al.
 2008/0215148 A1 9/2008 Lesinski et al.
 2009/0023988 A1 1/2009 Korner et al.
 2009/0024129 A1 1/2009 Gordon et al.
 2009/0048602 A1 2/2009 O'Donoghue
 2009/0138015 A1 5/2009 Conner et al.
 2009/0216235 A1 8/2009 Ellis
 2009/0222009 A1 9/2009 Ellis
 2009/0264888 A1 10/2009 Neumeyer et al.
 2010/0054884 A1 3/2010 Masuda et al.
 2010/0057087 A1 3/2010 Cha
 2010/0121365 A1 5/2010 O'Sullivan et al.
 2010/0145341 A1 6/2010 Ranck et al.
 2010/0178631 A1 7/2010 Gordils Wallis et al.
 2010/0209200 A1 8/2010 Delacretaz
 2010/0286695 A1 11/2010 Hannani et al.
 2011/0015634 A1 1/2011 Smith et al.
 2011/0054884 A1 3/2011 Drakwall et al.
 2011/0098710 A1 4/2011 Spratt et al.
 2011/0112540 A1 5/2011 McLean et al.
 2011/0208194 A1 8/2011 Steiner et al.
 2011/0211922 A1 9/2011 Maeda et al.
 2011/0238070 A1 9/2011 Santangelo et al.
 2011/0238099 A1 9/2011 Loreth
 2012/0150209 A1 6/2012 Gubellini et al.
 2012/0158028 A1 6/2012 O'Sullivan et al.
 2012/0330315 A1 12/2012 Ranck et al.
 2013/0028677 A1 1/2013 Schwaegert et al.
 2013/0051937 A1 2/2013 Volokh et al.
 2013/0274779 A1 10/2013 Kulas et al.
 2014/0058423 A1 2/2014 Smith et al.
 2015/0297243 A1 10/2015 Kulas et al.

FOREIGN PATENT DOCUMENTS

DE 19826276 C1 11/1999
 EP 1872739 A1 1/2008
 JP H06155126 A 6/1994
 JP 10-263914 10/1998
 JP H10-263914 A 10/1998
 JP 2003291024 A 10/2003
 JP 2010-510042 A 4/2010
 WO WO-2007010389 A1 1/2007
 WO WO-2008061711 A2 5/2008
 WO WO-2008064350 A2 5/2008
 WO WO-2010061933 A1 6/2010
 WO WO-2011023381 A1 3/2011
 WO WO-2011132876 A2 10/2011
 WO WO-2012083468 A1 6/2012
 WO WO-2014037518 A1 3/2014
 WO WO-2015160884 A1 10/2015

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Oct. 10, 2014 for PCT/US2014/046827 claiming benefit of U.S. Appl. No. 13/944,650 filed Jul. 17, 2013.
 Find Your Perfect Balance. Midas Rex Legend 7.5. cm Attachments and Tools. Medtronic brochure. (2012) 3 pages.
 Table of Contents, RedLine Tools catalog, www.redlinetools.com/Images/PDFs/Redline09/RL062009_Sec1_Front%20pl-9_72.pdf, pp. 1-8.
 Innovations 2005 catalog, Komet GEBR. BRASSELER GmbH & Co., KG, Lemgo, Germany, 28 pages.
 Komet Burs mini catalogue 2007, Henry Schein Halas, www.henryschein.com.au, 19 pages.
 Komet Surgery catalog, Mar. 2011, 8 pages.
 Stryker Neuro Spine ENT brochure, Zyphr Burs, Kalamazoo, Michigan, www.stryker.com, 2011, 6 pages.
 International Search Report and Written Opinion dated Aug. 28, 2013 for PCT/US2013/036269, claiming priority to U.S. Appl. No. 13/447,372, filed Apr. 16, 2012.

(56)

References Cited

OTHER PUBLICATIONS

International Preliminary Report on Patentability and Written Opinion dated Oct. 21, 2014 for PCT/US2013/036269, claiming priority to U.S. Appl. No. 13/447,372, filed Apr. 16, 2012.

International Preliminary Report on Patentability and Written Opinion mailed Jan. 19, 2016 for PCT/US2014/046827, claiming priority to U.S. Appl. No. 13/944,650, filed Jul. 17, 2013.

U.S. Appl. No. 14/664,258, 2015-0297243, filed Mar. 20, 2015, Kulas.

U.S. Appl. No. 14/664,002, filed Mar. 31, 2015, Kulas.

U.S. Appl. No. 14/840,217, filed Aug. 31, 2015, Vu.

U.S. Appl. No. 14/992,400, 2016-0120552, filed Jan. 11, 2016, Kulas.

Canadian Office Action dated Sep. 29, 2015 for Canadian Application 2,870,689 claiming benefit of International Application PCT/US2013/036269 claiming benefit of U.S. Appl. No. 13/447,372, filed Apr. 16, 2012.

Chinese Office Action (English translation) dated May 24, 2016 for Chinese Application No. 2013800311659 which claims benefit of PCT/2013/036269 filed Apr. 12, 2013.

International Search Report and Written Opinion dated Jul. 25, 2016 for PCT/US2016/023349 which claims benefit the benefit of U.S. Appl. No. 14/674,002, filed Mar. 31, 2015.

Japanese Office Action dated Nov. 10, 2015 for Japanese Application No. 2015-507064 claiming benefit of PCT/US2014/046827 claiming benefit of U.S. Appl. No. 13/944,650 filed Jul. 17, 2013.

Japanese Office Action dated Jun. 21, 2016 for Japanese Application No. 2015-50764 claiming benefit of PCT/US2013/036269 claiming benefit of U.S. Appl. No. 13/447,372 filed Apr. 12, 2013 with English translation.

Canadian Office Action dated Aug. 4, 2016 for CA Application No. 2870689 for PCT/US2013/036269 which claims benefit of U.S. Appl. No. 13/447,372, filed Apr. 16, 2012.

Korean Office Action dated Mar. 16, 2016 for KR Application No. 10-2014-7031869 for PCT/US2013/036269 which claims benefit of U.S. Appl. No. 13/447,372, filed Apr. 16, 2012 with English translation.

Australian Office Action dated Jun. 23, 2015 for AU Application No. 2013249626 for PCT/US2013/036269 which claims benefit of U.S. Appl. No. 13/447,372, filed Apr. 16, 2012.

Korean Office Action dated Sep. 30, 2016 for Korean Application No. 10-2014-7031869 corresponding to PCT/US2013/036269 which claims benefit of U.S. Appl. No. 13/447,372, filed Apr. 16, 2012 with English translation.

Australian Office Action dated Mar. 15, 2017 for AU Application No. 2015247768.

Canadian Office Action dated Sep. 29, 2015 for Canadian Application No. 2,870,689 claiming benefit of PCT/US2013/036269.

Canadian Office Action dated May 1, 2017 for CA Application No. 2,917,601.

Chinese Office Action (English translation) dated May 24, 2016 for Chinese Application No. 2013800311669 which claims benefit of PCT/2013/036269 filed Apr. 12, 2013.

International Search Report and Written Opinion dated Jul. 25, 2016 for Application No. PCT/US2014/046827 which claims benefit of U.S. Appl. No. 13/944,650, filed Jul. 17, 2013.

Japanese Office Action dated Nov. 10, 2015 for Japanese Application No. 2015-507064 claiming benefit of PCT/US2014/046827 claiming benefit of U.S. Appl. No. 13/944,650, filed Jul. 17, 2013.

Japanese Office Action dated Jun. 21, 2016 for Japanese Application No. 2015-50764 claiming benefit of PCT/US2013/036269 claiming benefit of U.S. Appl. No. 13/447,372, filed Apr. 12, 2013 with English translation.

International Preliminary Report on Patentability dated Oct. 27, 2016 for Application No. PCT/US2015/025867 filed Apr. 15, 2015.

International Search Report and Written Opinion dated Jan. 3, 2017 for PCT/US2016/049464 claiming benefit of U.S. Appl. No. 14/840,217, filed Aug. 31, 2015.

International Search Report and Written Opinion dated Oct. 22, 2015 corresponding to PCT/US2015/025867 filed Apr. 15, 2015.

Extended European Search Report dated Jul. 3, 2017 in corresponding European Application No. 17151461.5.

European Office Action dated Jul. 27, 2017 in corresponding European Application No. 14747254.2.

International Preliminary Report on Patentability dated Oct. 12, 2017 in corresponding/related International Application No. PCT/US2016/023349.

Canadian Office Action dated Aug. 22, 2017 in corresponding/related Canadian Application No. 2,945,806.

* cited by examiner




FIG. 1
Prior Art




FIG. 2
Prior Art




FIG. 3
Prior Art




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

1

**SURGICAL BURS WITH GEOMETRIES
HAVING NON-DRIFTING AND SOFT TISSUE
PROTECTIVE CHARACTERISTICS**

FIELD

The disclosure relates to a surgical systems for bone cutting or shaping, and more particularly to surgical burs.

BACKGROUND

This section provides background information related to the present disclosure which is not necessarily prior art.

Surgical burs need sharp and durable cutting edges in order to efficiently dissect, cut and/or shape bone during a surgical procedure. Human anatomy tends to locate sensitive soft tissue structures, such as nerves and blood vessels, near bones for protection. These structures can include the dura mater. Dura mater (or dura) refers to the outermost layer of protective soft tissue surrounding the brain and spinal column of a patient. During cranial and spinal procedures, the distal end of a bur can come in contact with dura mater. The term "distal" means furthest away from a medical practitioner holding a surgical tool with a rotating bur. The term "proximal" means towards the medical practitioner and away from the patient.

Damage to the dura mater can increase risks of infections (e.g., meningitis) and/or result in surgical complications (e.g., swelling of the brain). Thus, in order to preserve the integrity of the dura mater, it is desirable for surgical burs, intended for dissection of bone, to have a high-level of control (minimal flail or chatter) and have a geometry not predisposed to dissect soft tissue.

SUMMARY

This section provides a general summary of the disclosure, and is not a comprehensive disclosure of its full scope or all of its features.

A surgical bur is provided and includes a body and a drill point. The body includes flutes and lands. Each of the flutes includes a cutting edge, a rake face, and a clearance surface. Each of the lands is convex-shaped and disposed between a pair of the flutes. The drill point includes axial relief surfaces. Each of the axial relief surfaces has a planar area, is distinct from the lands and borders (i) a distal portion of one of the cutting edges, (ii) one of the lands, and (iii) one of the clearance surfaces.

In other features, a surgical bur is provided and includes a body and a drill point. The body includes flutes and lands. Each of the flutes includes a cutting edge and a clearance surface. Each of the lands is disposed between a pair of the flutes. The drill point includes axial relief surfaces. Each of the axial relief surfaces is distinct from the lands and borders (i) a distal portion of one of the cutting edges, (ii) one of the lands, and (iii) one of the clearance surfaces. At least one axial relief angle of the axial relief surfaces is within a predetermined range.

In other features, a surgical bur is provided and includes a body and a drill point. The body includes flutes and lands. Each of the flutes includes a cutting edge and a clearance surface. Each of the lands is disposed between a pair of the flutes. The drill point includes axial relief surfaces. Each of the axial relief surfaces is distinct from the lands and borders (i) a distal portion of one of the cutting edges, (ii) one of the

2

lands, and (iii) one of the clearance surfaces. The drill point has a drill point angle of greater than or equal to a predetermined angle.

Further areas of applicability will become apparent from the description provided herein. The description and specific examples in this summary are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

DRAWINGS

The drawings described herein are for illustrative purposes only of selected embodiments and not all possible implementations, and are not intended to limit the scope of the present disclosure.

FIG. 1 is a side perspective view of three drill bits illustrating drill point angles.

FIG. 2 is a side view of a dissection tool.

FIG. 3 is an end view of the dissection tool of FIG. 2.

FIG. 4 is a perspective view of a surgical dissection cutter assembly incorporating a bur and in use on a patient in accordance with an embodiment of the present disclosure.

FIG. 5 is a perspective view of the surgical dissection cutter assembly of FIG. 4.

FIG. 6 is a perspective view of a portion of a surgical bur illustrating a rake angle and a relief angle in accordance with an embodiment of the present disclosure.

FIG. 7 is a perspective view of a dissection tool including a surgical bur in accordance with an embodiment of the present disclosure.

FIG. 8 is a side view of the dissection tool of FIG. 7.

FIG. 9 is a side view of the surgical bur of FIG. 7 orthogonal to the distal end portion of one of multiple cutting edges of the surgical bur.

FIG. 10 is another side view of the dissection tool of FIG. 7.

FIG. 11 is a distal end view of the surgical bur of FIG. 7.

FIG. 12 is a perspective view of another dissection tool having a surgical bur in accordance with another embodiment of the present disclosure.

FIG. 13 is a distal end view of the dissection tool of FIG. 12.

FIG. 14 is a side view of the surgical bur of FIG. 12 illustrating a drill point angle.

Corresponding reference numerals indicate corresponding parts throughout the several views of the drawings.

DETAILED DESCRIPTION

Drill bits for machining naturally occurring and/or engineered materials, such as metal, wood and plastic have drill point geometries for improved cutting efficiency, stability, and feed rates, as well as for minimized thermal energy build-up during machining. In general, drill point angles for machining softer materials are more acute than those for machining harder materials.

FIG. 1 shows side views of three drill bits 10, 12, 14 and corresponding drill point angles 16, 18, 20. A drill point angle refers to an angle between tip cutting edges (e.g., tip cutting edges 22, 24) of a tip (e.g., tip 26) of a drill bit. The tip cutting edges extend radially away from (i) a center (e.g., center 28) of the tip, and (ii) respective ends of a chisel edge (e.g., chisel edge 30) of the drill bit.

The drill bits 10, 12, 14 are shaped to work on materials having different hardness characteristics. The drill point angle 16 of the first drill bit 10 may be, for example, 118° and is for materials having a first hardness. The first drill bit

10 has the tip cutting edges **22, 24**. The drill point angle **18** of the second drill bit **12** may be, for example, 135° and is for materials having a second hardness. The second hardness is greater than the first hardness. The second drill bit **12** has tip cutting edges **32, 34**. The drill point angle **20** of the third drill bit **14** may be, for example, 90° and is for materials have a third hardness. The third hardness is less than the second hardness and the first hardness. The third drill bit **14** has tip cutting edges **36, 38**.

The drill bits **10, 12, 14** have respective tips **26, 39, 40**. Each of the tips **26, 39, 40** includes relief surfaces that extend away from the respective cutting edges **22, 24, 32, 34, 36, 38**. Although the relief surfaces are distinct surfaces, the relief surfaces are identified by numerical designator **41**. The relief surfaces **41** are convex-shaped.

Each of the drill bits **10, 12, 14** has two helically shaped lands and two flutes. Although the lands are distinct surfaces, the lands are identified by numerical designator **40**. Although the flutes are distinct from each other, the flutes are identified by numerical designator **42**. The lands **40** are not convex-shaped. Each of the flutes **42** is located between a pair of the lands **40** and has a corresponding chip space **43** along and in the flutes. The lands **40** are in respective 180° locations about a corresponding longitudinal axis (the longitudinal axes are identified by numerical designator **44**). The flutes **42** are also in respective 180° locations about a corresponding longitudinal axis.

FIG. 2-3 show side and distal end views of a predicate dissection tool **50** including a surgical bur **52**. The surgical bur **52** includes three cam shaped lands **54** and three flutes **56**. Each of the flutes **56** is located between a pair of the lands **54** and has a corresponding chip space **57**. The lands **54** are equally spaced about a longitudinal axis **58** of the surgical bur **52**. The longitudinal axis **58** is shown by point **60** in FIG. 2. Distal portions **62** of the lands **54** are referred to as axial relief surfaces **63**, which are convex-shaped. The axial relief surfaces **62** are not distinct from the lands **54** because: the lands **54** and the axial relief surfaces **62** are both convex-shaped (or have the same type of surface); and the axial relief surfaces **62** are continuous with the lands **54** without transitional surfaces or borders between the axial relief surfaces **62** and the lands **54**.

The flutes **56** are also equally spaced about the longitudinal axis **58**. Each of the flutes **56** has a rake face **64** with a cutting edge **66** and a clearance surface **68**. Each of the clearance surfaces **68** includes distal portion (or surface) and a proximal portion (or surface). The distal portions of the clearance surfaces **68** are identified by numerical designator **70**. The proximal portions of the clearance surfaces **68** are identified by numerical designator **72**.

The geometries of the drill bits **10, 12, 14** of FIG. 1 and the surgical bur **52** of FIGS. 2-3 have associated disadvantages. Although the drill bits **10, 12, 14** provide cutting efficiency and stability due to the corresponding drill point angles, the geometries of the drill bits **10, 12, 14** would be inappropriate for surgical use in certain procedures. This is because the drill bits would likely cut dura mater and can be difficult to use for shaping purposes. The tips **26, 39, 40** of the drill bits **10, 12, 14** have a minimal amount of contact surface area, which increases chances of cutting dura mater. Although the surgical bur **52** is rounded and has a less tendency to cut dura mater than the drill bits **10, 12, 14**, the surgical bur **52** has an increased tendency to drift due to the geometries of a distal end or tip **74** of the surgical bur **52**. The surgical bur **52** also has a greater amount of contact area, requiring more irrigation to mitigate friction and the concomitant torsional shear forces that may be exerted on an

underlying soft tissue structure. For at least these reasons, it is desirable to construct surgical burs (or drilling tools) with geometries including a rounded tip and certain rake, axial relief and drill point angles, such that the surgical burs do not engage soft tissue and/or dura mater.

The following description discloses rotatable surgical burs (referred to below as the surgical burs). The surgical burs have fewer tendencies to cut dura mater and increased tendency to cut bone more efficiently as compared to predicate burs due to the geometries of the surgical burs. The surgical burs also have fewer tendencies to drift into sensitive anatomy. The surgical burs have tips with distal geometries that allow the surgical burs, with adequate irrigation, to glide over the dura mater without engaging and/or tearing the dura mater. The distal geometries include: axial relief surfaces with planar shapes and increased surface area; drill point angles in predetermined ranges; and axial relief angles in predetermined ranges. The distal geometries are set for maximum cutting and stability performance and for minimal tendencies to engage dura mater. The gliding aspect occurs over dura mater as opposed to bone due to the soft flexible nature of dura mater and the balance of surface area, shapes, and angles of the axial relief surfaces. The surgical burs have an increased tendency to cut into bone where the surgical burs are placed without drifting into nearby anatomy.

Although the surgical burs disclosed herein may be used, for example, for cutting and shaping bone, the surgical burs may be used for other dissecting, cutting, and/or shaping purposes. The disclosed implementations include bur configurations that minimize risk for challenges to sensitive anatomy, in particular, dura mater. The surgical burs are constructed with geometry to allow a practitioner to perform a procedure (e.g., a craniotomy) including casual contact atop dura mater. The surgical burs allow the practitioner to create a bore through a bone and/or a lateral path in the bone without tearing dura mater.

Example embodiments will now be described more fully with reference to the accompanying drawings. The following description is merely exemplary in nature and is not intended to limit the present disclosure, application, or uses. It should be understood that throughout the drawings, corresponding reference numerals indicate like or corresponding parts and features.

FIG. 4 shows a surgical dissection cutter assembly **100** incorporating a rotating surgical bur in use on a patient **102**. The patient is undergoing a neurological operation. Access to the brain or other neurological structures often requires delicate dissection of bone and other tissues. FIG. 4 is provided for example purposes only, the surgical burs disclosed herein may be used in different tools and/or cutter assemblies and may be used for other procedures and/or operations. The dissection cutter assembly **100** includes a dissection tool driver **104**, which is being utilized to dissect a portion of bone and adjacent tissue of the patient **102** in the surgical access site **106**.

FIG. 5 is a perspective view of the surgical dissection cutter assembly **100**. The dissection tool driver **104** includes a motor housing **108** connected to a hose or cable assembly **110**. The hose assembly **110** supplies external power and control for the motor housing **108**. The dissection tool driver **104** further includes an attachment housing **112** that connects to a dissection tool **118**. A distal end of the dissection tool **118** includes a surgical bur **120**. Examples of the dissection tool **118** are shown and described below with reference to FIGS. 6-13.

FIG. 6 is a perspective view of a portion **130** of a surgical bur. The portion **130** includes a rake face **132** with a cutting

5

edge **134** and a relief surface **136**. The cutting edge **134** may be at a distal end of the surgical bur and adjacent to the axial relief surface **136**. A rake angle **138** of the rake face **132** may be between (i) a line (or plane) **140** on the rake face **132** and a plane perpendicular to the cutting edge **134** and (ii) a line (or plane) **142** extending perpendicular to a surface **144** of a bone **145** into which the surgical bur is cutting and extending in a direction of the cut and/or a line (or plane) **146** perpendicular to line **142**. An axial relief angle **148** may be between (i) a line (or plane) **150** on the axial relief surface **136** and a plane perpendicular to the cutting edge **134** and (ii) the line **146**.

Although the following surgical burs are shown as having a particular number of flutes, lands, axial relief surfaces, clearance surfaces, etc., the surgical burs may have other quantities of each of these items.

FIG. 7 is a perspective view of a dissection tool **170**. The dissection tool **170** includes a shaft **172** and a surgical bur **174**. The surgical bur **174** includes a body **176**. The body **176** has three cam shaped lands **178** and three flutes **180**. Each of the flutes **180** is located between a pair of the lands **178** and has a corresponding chip space **181**. The lands **178** are convex-shaped and/or rounded and may be in respective 120° locations about a longitudinal axis **182** of the dissection tool **170**, the shaft **172**, and/or the surgical bur **174**. The flutes **180** may also be in respective 120° locations about the longitudinal axis **182**. Each of the flutes **180** has a rake face **184** with a cutting edge **186** and a clearance surface **188**. Each of the clearance surfaces **188** includes a distal portion (or surface) **190** and a proximal portion (or surface) **192**.

The surgical bur **174** includes a drill point **194** at a distal end of the surgical bur **174**. The drill point **194** may include a center point **196** and three axial relief surfaces **198**. The longitudinal axis **182** passes through the center point **196**. The axial relief surfaces **198** are at ends of the flutes **180** and are distinct from the lands **178**. The axial relief surfaces **198** are distinct from the lands **178** because: the axial relief surfaces **198** are a different type of surface than the lands (e.g., the lands **178** may be convex-shaped and the axial relief surfaces **198** may be planar shaped); there are transitional surfaces (or borders) between the axial relief surfaces **198** and the lands **178**; and/or the axial relief surfaces **198** do provide a non-transitional (or continuous surface) with the lands.

Each of the axial relief surfaces **198** are bordered by (i) a respective distal end portion **200** of one of the cutting edges **186**, (ii) a distal end portion **202** of one of the lands **178**, and (iii) one of the distal portions **190** of one of the clearance surfaces **188**. The axial relief surfaces **198** may be flat (or planar) surfaces, as shown. Each of the axial relief surfaces **198** are triangular-shaped with two nominally straight edges (two of the nominally straight edges are identified by numerical designator **204**) and a curved edge (one of the curved edges is identified by numerical designator **206**). The curved edges **206** of the axial relief surfaces **198** border respectively the lands **178**.

FIG. 8 shows another side view of the dissection tool **170** including the surgical bur **174** is shown. The surgical bur **174** includes the cutting edges **186**. The cutting edges **186** may provide a right-hand helix, straight or left-hand helix with respect to the longitudinal axis **182**. The cutting edges **186** are shown as providing a right-hand helix. When viewed from the side and as shown, the cutting edges **186** of the right-hand helix configuration extend along the longitudinal axis **182**, generally from above to below the, and towards the drill point **194**. When viewed from the side, the cutting edges **186** of the straight configuration extend towards the

6

drill point **194** and parallel with the longitudinal axis **182**. When viewed from the side, the cutting edges **186** of the left-hand helix configuration extend along the longitudinal axis **182**, generally from below to above, and towards the drill point **194**.

The surgical bur **174** also includes the clearance surfaces **188** having the distal surfaces **190**. The distal surfaces **190** have corresponding gash angles (one gash angle **210** is shown). Each of the gash angles refers to an angle between (i) a line (or plane) **212** extending parallel to one of the distal surfaces **190** and away from the center point **196** and/or the longitudinal axis **182** and (ii) a line (or plane) **214** extending perpendicular to the longitudinal axis **182**.

FIG. 9 shows another side view of the surgical bur **174** orthogonal to the distal end portion **200** of one of the cutting edges **186**. The surgical bur **174** includes the axial relief surfaces **198** (one is shown in FIG. 9) and the rake faces **184** (one is shown in FIG. 9) with corresponding cutting edges **186** therebetween.

Each of the axial relief surfaces **198** has a corresponding axial relief angle (one axial relief angle **220** is shown) and axial rake angle (one axial rake angle **221** is shown). Each axial relief angle **220** can be measured between (i) a first line (or plane) **224** on an axial relief surface and observed perpendicular to the distal end portion **200** of one of the cutting edges **186** and (ii) a second line (or plane) **226** perpendicular to the longitudinal axis **182**. The second plane **226** may also extend across a surface of an object (e.g., a surface of a bone) being cut. Each axial rake angle refers to an angle between (i) a third line (or plane) **230** on one of the rake faces **184** and observed perpendicular to the distal end portion **200** of one of the cutting edges **186** and (ii) a fourth line (or plane) extending along, passing through, and/or parallel to the longitudinal axis **182**.

Each distal portion **222** of the cutting edges **186**, along a corresponding one of the axial relief surfaces **198**, has a corresponding axial relief surface angle, a drill point angle, and a remainder angle. The axial relief surface angle (e.g., axial relief surface angle **220**) refers to an angle between (i) a line (or plane) **224** extending along and parallel to one of the axial relief surfaces **198** and away from the longitudinal axis **182** and/or distal portion **222** of one of the cutting edges **186**, and (ii) a line (or plane) **226** extending perpendicular to the longitudinal axis **182** and passing through the center point **196**.

A remainder angle (e.g., remainder angle **218**) may refer to an angle between (i) a line (or plane) **230** on one of the rake faces **184** and observed perpendicular to the distal end portion **200** of one of the cutting edges **186** and (ii) the line (or plane) **224** extending along and parallel to one of the axial relief surfaces **198** and away from the longitudinal axis **182** and/or the distal portion **222** of one of the cutting edges **186**. The remainder angle **218** is shown in FIGS. 7 and 9. The remainder angle **218** may be an acute, right, or obtuse angle. In one implementation, the remainder angle **218** is an obtuse angle.

A drill point angle is described with respect to FIG. 10 and an example drill point angle is shown in FIG. 14. FIG. 10 shows a side view of the dissection tool **170** including the surgical bur **174** is shown. Multiple techniques may be used to determine the drill point angle. A drill point angle DP (not shown in FIG. 9) may be equal to 180° minus two times an acute angle (AA) (or $DP=180^\circ-2AA$). The acute angle AA refers to an angle between (i) a line (or plane) **240** extending perpendicular to the longitudinal axis and tangent to the center point **196** and (ii) a line (or plane) **242** extending parallel to the distal portion **222** of one of the cutting edges

186. When a surgical bur has two flutes and/or opposing cutting edges with distal portions 180° apart and extending away from a center point, a corresponding drill point angle of the surgical bur refers to an angle between distal portions of the cutting edges. An example surgical bur with two flutes is shown in FIGS. 12-13.

FIG. 11 shows a distal end view of the surgical bur **174**. The surgical bur **174** includes the rake faces **184**. Each of the rake faces **184** has a corresponding radial rake angle **250**. A radial rake angle **250** refers to an angle between (i) a line (or plane) **252** parallel to a rake face and (ii) a line (or plane) **254** passing through the cutting edge **186** and the longitudinal axis. Radial rake angles **250** of the rake faces **184** may be associated with a left-hand helix, straight or righted-hand helix with respect to the longitudinal axis **182** (shown in previous FIGS. 7-9). The rake faces **184** of the surgical bur **174** as shown provide a right-hand helix.

FIGS. 12 and 13 show perspective and distal end views of another dissection tool **300** having a surgical bur **302**. The surgical bur **302** as shown has a straight configuration. The surgical bur **302** has a body **304** with two flutes **306** equally spaced around longitudinal axis **357**.

Each of the flutes **306** has a rake face **308** with a cutting edge **310** and a clearance surface **312**. Each clearance surface **312** may include a proximal portion (or surface) **314**, a center portion (or surface) **316**, and a distal portion (or surface) **318**. A land **320** exists between each cutting edge **310** and a corresponding clearance surface **312**. The lands **320** are convex-shaped.

The surgical bur **302** also includes a drill point **322** with a center point **324** and axial relief surfaces **326**. The axial relief surfaces **326** may be flat (or planar) surfaces. A bridge **328** may extend between the axial relief surfaces **326** and/or be part of the axial relief surfaces **326**. The bridge **328** may extend across the center point **324** and have a corresponding thickness and/or a chisel edge **330**. In one implementation, the bridge **328** does not include a chisel edge. The chisel edge **330** may extend across the bridge **328** between the flutes **306**. Each of the axial relief surfaces **326** includes two straight edges **340** and a curved edge **342**. The curved edges **342** border respectively the lands **320**. Each of the axial relief surfaces **326** may include circular areas **346**. In one implementation, the circular areas **346** are flat (or planar), protrude from the remainder of the axial relief surfaces **326**, and do not protrude from (or in a more distal direction than) the bridge **328**. In another implementation, the axial relief surfaces **326** do not include the circular areas **346**.

The rake faces **308**: extend parallel to each other; are not in alignment with each other; are offset from each other; and have overlapping portions (i.e. the portions are side-by-side) at the bridge **328**. Similarly, the straight edges **340**: extend parallel to each other; are not in alignment with each other; are offset from each other; and have overlapping portions (i.e. the portions are side-by-side) at the bridge **328**.

FIG. 14 shows a side view of the surgical bur **302**. The surgical bur **302** includes the cutting edges **310** and axial relief surfaces **326**. The distal portions **352** of the cutting edges **310** have an associated drill point angle **354**. The drill point angle **354** is an obtuse angle. Acute angles between (i) distal portions **352** and (ii) a line (or plane) **356**. A sum of the drill point angle **354** and the acute angles **356**, **358** is equal to 180°. The plane **356** is perpendicular to a longitudinal axis **357** of the surgical bur **302**. Lines (or planes) **358** tangent to the axial relief surfaces **326** are shown.

The above-disclosed implementations include surgical bur configurations designed to cut and shape bone efficiently while allowing contact with sensitive soft tissue structures

(e.g., nerves, blood vessels, membranes, etc.) without tearing the soft tissue structures. This is especially applicable in neurological and spinal procedures where the dura mater can be exposed to a distal portion of a bur.

In certain implementations, drill point angles of surgical burs (e.g., the surgical burs **174** and **302**) are obtuse angles greater than or equal to a first predetermined angle (e.g., 140°) and/or are within a first predetermined range (e.g., between 140°-160°). Corresponding axial relief angles of the surgical burs are less than or equal to a second predetermined angle (e.g., 25°) and/or are within a second predetermined range (e.g., between 5°-25°. An example drill point angle is shown in FIG. 14. An example axial relief angles are shown in FIGS. 6 and 9. These drill point angles and axial relief angles provide stable cutting of hard surfaces (such as surfaces of bone) while allowing the surgical burs to glide over soft surfaces (e.g., surfaces of dura mater). This is further improved by having the axial relief surfaces be planar surfaces. Rake angles of the surgical burs may also be within predetermined ranges and based on the application of use.

As a result, “skating” over hard surfaces is prevented providing improved and consistent drilling control while not challenging (or negatively affecting) integrity of dura mater. Reduced skating improves cutting quality while reducing risk of surgical complications concomitant with dural tears. The geometry of the surgical burs including the drill point angles and axial relief angles are tunable (i.e. can be adjusted) based on the application of use.

Example embodiments are provided so that this disclosure will be thorough, and will fully convey the scope to those who are skilled in the art. Numerous specific details are set forth such as examples of specific components, devices, and methods, to provide a thorough understanding of embodiments of the present disclosure. It will be apparent to those skilled in the art that specific details need not be employed, that example embodiments may be embodied in many different forms and that neither should be construed to limit the scope of the disclosure. In some example embodiments, well-known processes, well-known device structures, and well-known technologies are not described in detail.

The terminology used herein is for the purpose of describing particular example embodiments only and is not intended to be limiting. As used herein, the singular forms “a,” “an,” and “the” may be intended to include the plural forms as well, unless the context clearly indicates otherwise.

The foregoing description of the embodiments has been provided for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure. Individual elements or features of a particular embodiment are generally not limited to that particular embodiment, but, where applicable, are interchangeable and can be used in a selected embodiment, even if not specifically shown or described. The same may also be varied in many ways. Such variations are not to be regarded as a departure from the disclosure, and all such modifications are intended to be included within the scope of the disclosure.

What is claimed is:

1. A surgical bur comprising:

- a body that is spherically-shaped, wherein the body comprises
 - a plurality of flutes, wherein each of the plurality of flutes comprises a cutting edge, a rake face and a clearance surface, and
 - a plurality of lands, each of the plurality of lands is convex-shaped and disposed between a pair of the plurality of flutes; and

9

a drill point comprising a plurality of axial relief surfaces, wherein each of the plurality of axial relief surfaces has a planar area, is distinct from the plurality of lands and borders (i) a distal portion of one of the cutting edges, (ii) one of the plurality of lands, and (iii) one of the clearance surfaces;

wherein widths of the plurality of axial relief surfaces narrow towards a distal end of the drill point; and

wherein lengths of proximal most edges of the plurality of axial relief surfaces are equal to lengths of distal most edges of the plurality of lands.

2. The surgical bur of claim 1, wherein drill point angles of distal portions of the cutting edges are each between 140°-160°.

3. The surgical bur of claim 1, wherein axial relief angles of the plurality of axial relief surfaces are each between 5°-25°.

4. The surgical bur of claim 1, wherein the plurality of axial relief surfaces are planar surfaces and meet at a center point.

5. The surgical bur of claim 4, wherein: entire areas of the plurality of axial relief surfaces are respectively between the plurality of lands and the center point; and the plurality of axial relief surfaces separate the plurality of lands from the center point.

6. The surgical bur of claim 1, wherein: drill point angles of distal portions of the cutting edges are each between 140°-160°; and axial relief angles of the plurality of axial relief surfaces are each between 5°-25°.

7. The surgical bur of claim 1, wherein: the plurality of axial relief surfaces are triangular-shaped and comprise two straight edges and a curved edge; and each of the curved edges of the plurality of axial relief surfaces border a respective one of the plurality of lands.

8. The surgical bur of claim 1, wherein the planar areas are circular in shape.

9. The surgical bur of claim 1, wherein: at least one axial relief angle of the plurality of axial relief surfaces is less than or equal to a predetermined angle such that the surgical bur while rotating has a tendency to cut a first type of surface and not a second type of surface;

the first type of surface has a first hardness; and the second type of surface has a second hardness that is less than the first hardness.

10. The surgical bur of claim 1, wherein: the plurality of flutes are non-opposing flutes; and the plurality of axial relief surfaces are connected via a bridge.

11. The surgical bur of claim 1, wherein each of the plurality of lands is convex-shaped along a longitudinal center axis of the surgical bur and from a proximal end of the body to a corresponding one of the plurality of axial relief surfaces.

12. The surgical bur of claim 11, wherein each of the plurality of lands is convex-shaped in a lateral direction between adjacent ones of the plurality of flutes.

13. The surgical bur of claim 1, wherein each of the cutting edges extend along a longitudinal center axis of the surgical bur from a proximal end of the surgical bur to a distal end of the surgical bur.

14. The surgical bur of claim 1, wherein each of the cutting edges, in a distal portion of the surgical bur, abuts a

10

respective one of the plurality of lands and a respective one of the plurality of axial relief surfaces.

15. The surgical bur of claim 1, wherein:

the plurality of axial relief surfaces are planar surfaces, meet at a center point at a distal end of the surgical bur, and are triangular-shaped;

each of the plurality of axial relief surfaces has three edges;

the first edges border respectively the plurality of lands; the second edges border respectively the clearance surfaces; and

the third edges border respectively the cutting edges.

16. The surgical bur of claim 15, wherein:

each of the second edges of the plurality of axial relief surfaces extends along a respective one of the clearance surfaces; and

points of the plurality of axial relief surfaces between the second edges and the third edges meet at the center point.

17. The surgical bur of claim 1, wherein a proximal end of each of the plurality of axial relief surfaces that borders a respective one of the plurality of lands is at an acute remainder angle relative to a respective one of the cutting edges bordering the respective one of the plurality of lands.

18. The surgical bur of claim 1, wherein:

each of the plurality of axial relief surfaces is a single surface having a respective peripheral boundary;

each of the plurality of axial relief surfaces are void of a transitional edge within the corresponding peripheral boundary; and

a transitional edge refers to an edge between two distinct surfaces.

19. The surgical bur of claim 1, wherein:

each of the plurality of axial relief surfaces comprises three edges;

the cutting edges extend along the first edges of the plurality of axial relief surfaces;

the plurality of lands have distal edges that extend along the second edges of the plurality of axial relief surfaces; and

the clearance surfaces have distal edges that extend along the third edges of the plurality of axial relief surfaces.

20. The surgical bur of claim 1, wherein the rake faces are offset from each other, are not in alignment with each other; and have overlapping portions.

21. The surgical bur of claim 20, wherein:

the rake faces extend parallel to each other; and

the overlapping portions are side-by-side to provide a bridge between the planar areas.

22. The surgical bur of claim 1, wherein each of the plurality of axial relief surfaces is planar-shaped.

23. The surgical bur of claim 1, wherein each of the plurality of axial relief surfaces is distal to a respective one of the clearance surfaces.

24. The surgical bur of claim 1, wherein each of the plurality of axial relief surfaces is distal to a respective one of the plurality of lands.

25. The surgical bur of claim 1, wherein the plurality of axial relief surfaces, the clearance surfaces and the cutting edges meet at a distal center end point of the surgical bur.

26. A surgical bur comprising:

a body that is spherically-shaped, wherein the body comprises

a plurality of flutes, wherein each of the plurality of flutes comprises a cutting edge, a rake face, and a clearance surface, and

11

a plurality of lands, each of the plurality of lands is disposed between a pair of the plurality of flutes; and a drill point comprising a plurality of axial relief surfaces, wherein each of the plurality of axial relief surfaces is distinct from the plurality of lands and borders (i) a distal portion of one of the cutting edges, (ii) one of the plurality of lands, and (iii) one of the clearance surfaces, wherein a proximal most edge of each of the plurality of axial relief surfaces borders a distal most edge of a respective one of the plurality of lands; wherein widths of the plurality of axial relief surfaces narrow towards a distal end of the drill point; and wherein lengths of the proximal most edges of the plurality of axial relief surfaces are equal to lengths of the distal most edges of the plurality of lands.

27. The surgical bur of claim 26, wherein: each of the plurality of lands is convex-shaped; and the plurality of axial relief surfaces are planar surfaces.

28. The surgical bur of claim 26, wherein: at least one axial relief angle of the plurality of axial relief surfaces is less than or equal to a predetermined angle such that the surgical bur while rotating has a tendency to cut a first type of surface and not a second type of surface;

the first type of surface has a first hardness; and the second type of surface has a second hardness that is less than the first hardness.

29. The surgical bur of claim 26, wherein axial relief angles of the plurality of axial relief surfaces are each less than or equal to 25°.

30. The surgical bur of claim 26, wherein axial relief angles of the plurality of axial relief surfaces are each between 5°-25°.

31. The surgical bur of claim 26, wherein drill point angles of distal portions of the cutting edges are each between 140°-160°.

32. The surgical bur of claim 26, wherein the plurality of axial relief surfaces are planar surfaces.

33. The surgical bur of claim 26, wherein each axial relief surface of the surgical bur is distal to a respective one of the plurality of lands or a respective one of the clearance surfaces.

34. The surgical bur of claim 26, wherein each axial relief surface of the surgical bur is distal to a respective one of the plurality of lands and a respective one of the clearance surfaces.

35. The surgical bur of claim 26, wherein each of the proximal most edges of the axial relief surfaces extends laterally between a respective one of the clearance surfaces and a respective one of the rake faces.

36. A surgical bur comprising:

a body that is spherically-shaped, wherein the body comprises

a plurality of flutes, wherein each of the plurality of flutes comprises a cutting edge and a clearance surface, and

a plurality of lands, each of the plurality of lands is disposed between a pair of the plurality of flutes, wherein each of the cutting edges borders a respective one of the plurality of lands in a distal portion of the surgical bur; and

a drill point comprising a plurality of axial relief surfaces, wherein each of the plurality of axial relief surfaces is

12

distinct from the plurality of lands and borders (i) a distal portion of one of the cutting edges, (ii) one of the plurality of lands, and (iii) one of the clearance surfaces, wherein the drill point has a drill point angle of greater than or equal to a predetermined angle, and wherein a proximal end of each of the plurality of axial relief surfaces that borders a respective one of the plurality of lands is at an acute remainder angle relative to a respective one of the cutting edges bordering the respective one of the plurality of lands.

37. The surgical bur of claim 36, wherein: the drill point angle is within a predetermined range such that the surgical bur while rotating has a tendency to cut a first type of surface and not a second type of surface; the first type of surface has a first hardness; and the second type of surface has a second hardness that is less than the first hardness.

38. The surgical bur of claim 37, wherein drill point angles of distal portions of the cutting edges are each between 140°-160°.

39. The surgical bur of claim 36, wherein axial relief angles of the plurality of axial relief surfaces are each between 5°-25°.

40. The surgical bur of claim 36, wherein the plurality of axial relief surfaces are planar surfaces.

41. A surgical bur comprising:

a body comprising

a plurality of flutes, wherein each of the plurality of flutes comprises a cutting edge, a rake face and a clearance surface, and

a plurality of lands, wherein each of the plurality of lands is convex-shaped and disposed between a pair of the plurality of flutes; and

a drill point comprising a plurality of axial relief surfaces, wherein each of the plurality of axial relief surfaces has a planar area, is distinct from the plurality of lands and borders (i) a distal portion of one of the cutting edges, (ii) one of the plurality of lands, and (iii) one of the clearance surfaces,

wherein each of the plurality of lands comprises

a first portion convex-shaped in a lateral direction between the plurality of flutes and is not convex-shaped along a longitudinal axis of the surgical bur, and

a second portion convex-shaped in a lateral direction between the plurality of flutes and convex-shaped along the longitudinal axis of the surgical bur;

wherein a proximal end of each of the plurality of axial relief surfaces that borders a respective one of the plurality of lands is at an acute remainder angle relative to a respective one of the cutting edges bordering the respective one of the plurality of lands.

42. The surgical bur of claim 41, wherein each axial relief surface of the surgical bur is distal to a respective one of the plurality of lands or a respective one of the clearance surfaces.

43. The surgical bur of claim 41, wherein each axial relief surface of the surgical bur is distal to a respective one of the plurality of lands and a respective one of the clearance surfaces.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,883,873 B2
APPLICATION NO. : 13/944650
DATED : February 6, 2018
INVENTOR(S) : Kulas et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page

Page 2, Applicant Information: Delete "Louisville, CO" and insert --Fort Worth, TX--
therefore;


In the Specification

Column 3, Detailed Description, Line 28: Delete "FIG." and insert --FIGS.-- therefore;

Column 3, Detailed Description, Line 36: Delete "63," and insert --62,-- therefore; and

Column 8, Detailed Description, Line 12: Delete "5°-25°." and insert --5°-25°).-- therefore.

Signed and Sealed this
Eighth Day of May, 2018



Andrei Iancu
Director of the United States Patent and Trademark Office