

US009889058B2

(12) **United States Patent**
Horst et al.

(10) **Patent No.:** **US 9,889,058 B2**
(45) **Date of Patent:** **Feb. 13, 2018**

(54) **ORTHOTIC DEVICE DRIVE SYSTEM AND METHOD**

(71) Applicant: **ALTERG, INC.**, Fremont, CA (US)

(72) Inventors: **Robert W. Horst**, San Jose, CA (US);
Richard R. Marcus, Mountain View, CA (US)

(73) Assignee: **AlterG, Inc.**, Fremont, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 288 days.

(21) Appl. No.: **14/769,119**

(22) PCT Filed: **Mar. 13, 2014**

(86) PCT No.: **PCT/US2014/026041**

§ 371 (c)(1),

(2) Date: **Aug. 20, 2015**

(87) PCT Pub. No.: **WO2014/151584**

PCT Pub. Date: **Sep. 25, 2014**

(65) **Prior Publication Data**

US 2015/0374573 A1 Dec. 31, 2015

Related U.S. Application Data

(60) Provisional application No. 61/798,101, filed on Mar. 15, 2013.

(51) **Int. Cl.**

A61H 1/02 (2006.01)

A61H 3/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61H 1/024** (2013.01); **A61F 5/013** (2013.01); **A61F 5/0125** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC A61H 1/024; A61H 1/0277; A61H 3/00;
A61H 2201/0184; A61H 2201/1215;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,286,482 A 12/1918 Yoder

1,366,904 A 2/1921 Davis

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1138286 A2 10/2001

EP 1410780 A1 4/2004

(Continued)

OTHER PUBLICATIONS

Advanced Mechatronics Lab (Univ. of Tokyo); Dual Excitation Multiphase Electrostatic Drive (DEMED); http://www.intellect.pe.u-tokyo.ac.jp/research/es_motor/demed_e.html; pp. 1-5; (printed) Nov. 21, 2002.

(Continued)

Primary Examiner — Ophelia A Hawthorne


(74) *Attorney, Agent, or Firm* — Shay Glenn LLP

(57)

ABSTRACT

An orthosis includes a first portion and a second portion configured to attach on opposite sides of a joint. An actuator is configured to apply a force between the first and second portions. The actuator includes a first spool and a second spool rotatably mounted to the first portion. An output pulley is mounted to the second portion. A belt has a first end wrapped around the first spool, a second end wrapped around the second spool, and a mid-portion wrapped around the output pulley. The actuator is configured to rotate the first and second spools. The rotation of the first spool pulls the belt a given length, and the rotation of the second spool feeds

(Continued)



the belt less than the given length, so as to pull the output pulley towards the first portion to pull the second portion towards the first portion.

37 Claims, 19 Drawing Sheets

- (51) **Int. Cl.**
A61F 5/01 (2006.01)
F16H 19/06 (2006.01)
- (52) **U.S. Cl.**
CPC *A61H 1/0277* (2013.01); *A61H 3/00* (2013.01); *F16H 19/0631* (2013.01); *A61F 2005/0155* (2013.01); *A61F 2005/0188* (2013.01); *A61H 2201/0184* (2013.01); *A61H 2201/1215* (2013.01); *A61H 2201/1463* (2013.01); *A61H 2201/164* (2013.01); *A61H 2201/165* (2013.01); *A61H 2201/501* (2013.01); *A61H 2201/5061* (2013.01); *A61H 2201/5064* (2013.01); *A61H 2201/5069* (2013.01); *A61H 2201/5071* (2013.01); *A61H 2201/5092* (2013.01); *A61H 2230/605* (2013.01); *F16H 2019/0695* (2013.01)
- (58) **Field of Classification Search**
CPC A61H 2201/1463; A61H 2201/164; A61H 2201/165; A61H 2201/501; A61H 2201/5061; A61H 2201/5064; A61H 2201/5069; A61H 2201/5071; A61H 2201/5092; A61H 2230/605; A61F 5/0125; A61F 5/013; A61F 2005/0155; A61F 2005/0188; A61F 5/0123; A61F 2005/0139; A61F 5/0102; A61F 2005/0167; F16H 19/0631; F16H 2019/0695

See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS

1,391,290	A	9/1921	Welffens
1,513,473	A	10/1924	Ackerman
1,739,053	A	12/1929	Wilhelm
1,847,720	A	3/1932	Marcellis
2,169,813	A	8/1939	Parkin
3,059,490	A	10/1962	McDuffie
3,200,666	A	8/1965	Schrodt et al.
3,358,678	A	12/1967	Kultsar
3,398,248	A	8/1968	Klauss et al.
3,402,942	A	9/1968	Shimano et al.
3,631,542	A	1/1972	Potter
3,641,843	A	2/1972	Lemmens
3,863,512	A	2/1975	Crawley
3,899,383	A	8/1975	Schultz et al.
3,925,131	A	12/1975	Krause
3,976,057	A	8/1976	Barclay
4,273,113	A	6/1981	Hofstein
4,474,176	A	10/1984	Farris et al.
4,507,104	A	3/1985	Clark et al.
4,538,595	A	9/1985	Hajianpour
4,549,555	A	10/1985	Fraser et al.
4,588,040	A	5/1986	Albright, Jr. et al.
4,647,918	A	3/1987	Goforth
4,649,488	A	3/1987	Osanai et al.
4,665,899	A	5/1987	Farris et al.
4,678,354	A	7/1987	Olsen
4,679,548	A	7/1987	Pechoux
4,691,694	A	9/1987	Boyd et al.
4,697,808	A	10/1987	Larson et al.
4,731,044	A	3/1988	Mott

4,745,930	A	5/1988	Confer
4,754,185	A	6/1988	Gabriel et al.
4,796,631	A	1/1989	Grigoryev
4,801,138	A	1/1989	Airy et al.
4,807,874	A	2/1989	Little
4,814,661	A	3/1989	Ratzlaff et al.
4,825,852	A	5/1989	Genovese et al.
4,872,665	A	10/1989	Chareire
4,878,663	A	11/1989	Luquette
4,883,445	A	11/1989	Gomoll et al.
4,922,925	A	5/1990	Crandall et al.
4,934,694	A	6/1990	McIntosh
4,944,713	A	7/1990	Salerno
4,953,543	A	9/1990	Grim et al.
4,981,116	A	1/1991	Trinquard
4,983,146	A	1/1991	Charles et al.
5,020,790	A	6/1991	Beard et al.
5,046,375	A	9/1991	Salisbury et al.
5,052,681	A	10/1991	Williams
5,078,152	A	1/1992	Bond et al.
5,117,814	A	6/1992	Luttrell et al.
5,170,776	A	12/1992	Pechoux
5,170,777	A	12/1992	Reddy et al.
5,195,617	A	3/1993	Clemens
5,203,321	A	4/1993	Donovan et al.
5,209,223	A	5/1993	McGorry et al.
5,213,094	A *	5/1993	Bonutti A61F 5/0123 601/33
5,239,222	A	8/1993	Higuchi et al.
5,241,952	A	9/1993	Ortiz
5,282,460	A	2/1994	Boldt
5,303,716	A	4/1994	Mason et al.
5,313,968	A	5/1994	Logan et al.
5,345,834	A	9/1994	Hayashi
5,358,468	A	10/1994	Longo et al.
5,378,954	A	1/1995	Higuchi et al.
5,395,303	A	3/1995	Bonutti et al.
5,399,147	A	3/1995	Kaiser
5,410,488	A	4/1995	Andersen
5,421,798	A	6/1995	Bond et al.
5,440,945	A	8/1995	Penn
5,448,124	A	9/1995	Higuchi et al.
5,463,526	A	10/1995	Mundt
5,476,441	A	12/1995	Durfee et al.
5,509,894	A	4/1996	Mason et al.
5,520,627	A	5/1996	Malewicz
5,525,642	A	6/1996	Cipriano et al.
5,534,740	A	7/1996	Higuchi et al.
5,541,465	A	7/1996	Higuchi et al.
5,573,088	A	11/1996	Daniels
5,582,579	A	12/1996	Chism et al.
5,585,683	A	12/1996	Higuchi et al.
5,608,599	A	3/1997	Goldman
5,624,390	A	4/1997	Van Dyne
5,653,680	A	8/1997	Cruz
5,662,594	A	9/1997	Rosenblatt
5,662,693	A	9/1997	Johnson et al.
5,674,262	A	10/1997	Tumey
5,678,448	A	10/1997	Fullen et al.
5,683,351	A	11/1997	Kaiser et al.
5,695,859	A	12/1997	Burgess
5,704,440	A	1/1998	Urban et al.
5,708,319	A	1/1998	Ban et al.
5,728,017	A	3/1998	Bellio et al.
5,746,684	A	5/1998	Jordan
5,746,704	A	5/1998	Schenck et al.
5,755,303	A	5/1998	Yamamoto et al.
5,789,843	A	8/1998	Higuchi et al.
5,833,257	A	11/1998	Kohlheb et al.
5,865,770	A	2/1999	Schectman
5,916,689	A	6/1999	Collins et al.
5,931,756	A	8/1999	Ohsono et al.
5,976,063	A	11/1999	Joutras et al.
6,001,075	A	12/1999	Clemens et al.
6,030,351	A	2/2000	Schmidt et al.
6,033,330	A	3/2000	Wong et al.
6,033,370	A	3/2000	Reinbold et al.
6,062,096	A	5/2000	Lester
6,119,539	A	9/2000	Papanicolaou

(56)

References Cited

U.S. PATENT DOCUMENTS

6,146,341 A	11/2000	Sato et al.	2003/0120183 A1	6/2003	Simmons
6,149,612 A	11/2000	Schnapp et al.	2003/0184310 A1	10/2003	Lurtz
6,162,189 A	12/2000	Girone et al.	2003/0195638 A1	10/2003	Kajitani et al.
6,183,431 B1	2/2001	Gach, Jr.	2003/0212356 A1	11/2003	Scorvo
6,217,532 B1	4/2001	Blanchard et al.	2004/0015112 A1	1/2004	Salutterback et al.
6,221,032 B1	4/2001	Blanchard et al.	2004/0049139 A1	3/2004	Craciunescu
6,290,662 B1	9/2001	Morris et al.	2004/0054311 A1	3/2004	Sterling
6,314,835 B1	11/2001	Lascelles et al.	2004/0078091 A1	4/2004	Elkins
6,375,619 B1	4/2002	Ohdachi	2004/0106881 A1	6/2004	McBean et al.
6,387,066 B1	5/2002	Whiteside	2005/0014600 A1	1/2005	Clauson
6,440,093 B1	8/2002	McEwen et al.	2005/0085346 A1	4/2005	Johnson
6,472,795 B2	10/2002	Hirose et al.	2005/0085353 A1	4/2005	Johnson
6,494,798 B1	12/2002	Onogi	2005/0101887 A1	5/2005	Stark et al.
6,500,138 B1	12/2002	Irby et al.	2005/0151420 A1	7/2005	Crombez et al.
6,517,503 B1	2/2003	Naft et al.	2005/0173994 A1	8/2005	Pfister et al.
6,525,446 B1	2/2003	Yasuda et al.	2005/0210557 A1	9/2005	Falconer
6,527,671 B2	3/2003	Paalasmaa et al.	2005/0221926 A1	10/2005	Naude
6,533,742 B1	3/2003	Gach, Jr.	2005/0245849 A1	11/2005	Cordo
6,537,175 B1	3/2003	Blood	2005/0251067 A1	11/2005	Terry
6,554,773 B1	4/2003	Nissila et al.	2005/0253675 A1	11/2005	Davison
6,572,558 B2	6/2003	Masakov et al.	2005/0273022 A1	12/2005	Diaz et al.
6,599,255 B2	7/2003	Zhang	2006/0004265 A1	1/2006	Pulkkinen et al.
6,659,910 B2	12/2003	Gu et al.	2006/0046907 A1	3/2006	Rastegar et al.
6,666,796 B1	12/2003	MacCready, Jr.	2006/0069336 A1	3/2006	Krebs et al.
6,689,075 B2	2/2004	West	2006/0108954 A1	5/2006	Sebille et al.
6,694,833 B2	2/2004	Hoehn et al.	2006/0132069 A1	6/2006	Hemphill et al.
6,709,411 B1	3/2004	Olinger	2006/0157010 A1	7/2006	Moriwaki et al.
6,796,926 B2	9/2004	Reinkensmeyer et al.	2006/0206045 A1	9/2006	Townsend et al.
6,805,677 B2	10/2004	Simmons	2006/0249315 A1	11/2006	Herr et al.
6,821,262 B1	11/2004	Muse et al.	2006/0251179 A1	11/2006	Ghoshal
6,827,579 B2	12/2004	Burdea et al.	2006/0293624 A1	12/2006	Enzerink et al.
6,836,744 B1	12/2004	Asphahani et al.	2007/0015611 A1	1/2007	Noble et al.
6,872,187 B1	3/2005	Stark et al.	2007/0038161 A1	2/2007	Bonutti et al.
6,878,122 B2	4/2005	Cordo	2007/0055163 A1	3/2007	Asada et al.
6,936,994 B1	8/2005	Gimlan	2007/0093729 A1	4/2007	Ewing
6,966,882 B2	11/2005	Horst	2007/0105695 A1	5/2007	Susta
7,041,069 B2	5/2006	West	2007/0149899 A1	6/2007	Shechtman et al.
7,124,321 B2	10/2006	Garnett et al.	2007/0155557 A1	7/2007	Horst et al.
7,137,938 B2	11/2006	Gottlieb	2007/0155558 A1	7/2007	Horst et al.
7,171,331 B2	1/2007	Vock et al.	2007/0155560 A1	7/2007	Horst et al.
7,190,141 B1	3/2007	Ashrafiuon et al.	2007/0155588 A1	7/2007	Stark et al.
7,192,401 B2	3/2007	Saalasti et al.	2007/0162152 A1	7/2007	Herr et al.
7,217,247 B2	5/2007	Dariussh et al.	2007/0173747 A1	7/2007	Knotts
7,239,065 B2	7/2007	Horst	2007/0225620 A1	9/2007	Carignan et al.
7,252,644 B2	8/2007	Dewald et al.	2007/0248799 A1	10/2007	DeAngelis et al.
7,309,320 B2	12/2007	Schmehl	2007/0265534 A1	11/2007	Martikka et al.
7,324,841 B2	1/2008	Reho et al.	2007/0270265 A1	11/2007	Miller et al.
7,365,463 B2	4/2008	Horst et al.	2007/0287302 A1	12/2007	Lindberg et al.
7,410,471 B1	8/2008	Campbell et al.	2007/0287928 A1	12/2007	Kiviniemi et al.
7,416,537 B1	8/2008	Stark et al.	2008/0039731 A1	2/2008	McCombie et al.
7,431,707 B2	10/2008	Ikeuchi	2008/0097269 A1	4/2008	Weinberg et al.
7,457,724 B2	11/2008	Vock et al.	2008/0152463 A1	6/2008	Chidambaram et al.
7,458,922 B2	12/2008	Pisciottano	2008/0177208 A1	7/2008	Borschneck
7,537,573 B2	5/2009	Horst	2008/0200994 A1	8/2008	Colgate et al.
7,559,909 B2	7/2009	Katoh et al.	2008/0234608 A1	9/2008	Sankai
7,578,799 B2	8/2009	Thorsteinsson et al.	2008/0281436 A1	11/2008	Townsend et al.
7,648,436 B2 *	1/2010	Horst F16H 19/06 474/117	2009/0007983 A1	1/2009	Healy
7,731,670 B2	6/2010	Aguirre-Ollinger et al.	2009/0036804 A1	2/2009	Horst
7,833,178 B2	11/2010	Lee et al.	2009/0048686 A1	2/2009	Ikeuchi et al.
7,880,345 B2	2/2011	Hoffmann et al.	2009/0093353 A1	4/2009	Weiner
7,998,092 B2	8/2011	Avni et al.	2009/0131839 A1	5/2009	Yasuhara
8,052,629 B2	11/2011	Smith et al.	2009/0171469 A1	7/2009	Thorsteinsson et al.
8,058,823 B2	11/2011	Horst et al.	2009/0235739 A1	9/2009	Morris-Bamberg et al.
8,167,829 B2	5/2012	Sterling et al.	2009/0260426 A1	10/2009	Lieberman et al.
8,274,244 B2	9/2012	Horst et al.	2009/0265018 A1	10/2009	Goldfarb et al.
8,353,854 B2	1/2013	Horst et al.	2009/0306548 A1	12/2009	Bhugra et al.
8,639,455 B2	1/2014	Horst et al.	2010/0049102 A1	2/2010	Yasuhara
8,679,040 B2	3/2014	Horst	2010/0113986 A1	5/2010	Ashihara et al.
8,771,210 B2	7/2014	Smith et al.	2010/0114329 A1	5/2010	Casler et al.
9,131,873 B2	9/2015	Horst et al.	2010/0125229 A1	5/2010	Rudolph et al.
2001/0029343 A1	10/2001	Seto et al.	2010/0224844 A1	9/2010	Boussaton et al.
2002/0029911 A1	3/2002	Richards	2010/0234775 A1	9/2010	Yasuhara et al.
2002/0128552 A1	9/2002	Nowlin et al.	2010/0256537 A1	10/2010	Menga
2003/0104886 A1	6/2003	Gajewski	2010/0280628 A1	11/2010	Sankai
			2010/0298746 A1	11/2010	Shimizu et al.
			2010/0318006 A1	12/2010	Horst
			2011/0012869 A1	1/2011	Klinghult
			2011/0015498 A1	1/2011	Mestrovic et al.
			2011/0175744 A1	7/2011	Englert et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0291564 A1 11/2012 Amos et al.
 2012/0297885 A1 11/2012 Hou et al.
 2012/0316475 A1 12/2012 Bhugra et al.
 2013/0079687 A1 3/2013 Horst et al.
 2013/0165817 A1 6/2013 Horst et al.
 2013/0261511 A1 10/2013 Smith et al.
 2013/0345601 A1 12/2013 Bhugra et al.
 2014/0207037 A1 7/2014 Horst
 2014/0323936 A1 10/2014 Smith et al.

FOREIGN PATENT DOCUMENTS

JP 63-136978 A 6/1988
 JP 02-275162 A 11/1990
 JP 04-104180 A 4/1992
 JP 05-038948 A 2/1993
 JP 05-260766 10/1993
 JP 06-038551 A 2/1994
 JP 07-274540 A 10/1995
 JP 08-033360 A 2/1996
 JP 08-149858 6/1996
 JP 08-154304 A 6/1996
 JP 09-133196 A 5/1997
 JP 09-261975 A 10/1997
 JP 2001-353675 A 12/2001
 JP 2002-191654 A 7/2002
 WO WO 90/11049 A1 10/1990
 WO WO 03/088865 A2 10/2003
 WO WO 2005/057054 A1 6/2005
 WO WO 2007/027673 A2 3/2007
 WO WO 2007/041303 A2 4/2007

OTHER PUBLICATIONS

Advanced Mechatronics Lab (Univ. of Tokyo); High-power electrostatic motor; http://www.intellect.pe.u-tokyo.ac.jp/research/es_motor/es_motor_e.html; pp. 1-2; (printed) Nov. 21, 2002.
 Advanced Mechatronics Lab (Univ. of Tokyo); Pulse driven induction electrostatic motor; http://www.intellect.pe.u-tokyo.ac.jp/research/es_motor/pim_e.html; pp. 1-5; (printed) Nov. 21, 2002.
 ASEL (Univ. of Delaware); Powered orthosis project; <http://www.asel.udel.edu/robotics/orthosis/orthosis.html>, 1 pg.; (update) Jan. 17, 1999.
 British Tech. Group; Demonstration of energy saving in vehicles by integrating an infinitely variable transmission with an optimized petrol engine; prj. No. TR/00087/92; pp. 1-19; (version) Jul. 15, 1998.
 Coronel et al.; The Coronel effect positively infinitely variable transmission; U.C. Davis; No. 04CVT-51; pp. 1-8; (year of pub. sufficiently earlier than effective US filed and any foreign priority date) 2004.
 Fitch, C. J.; Development of the electrostatic clutch; IBM Journal; pp. 49-56; Jan. 1957.
 Frank, Andrew; Engine optimization concepts . . . ; U.C. Davis; No. 04CVT-56; pp. 1-12; (year of pub. sufficiently earlier than effective US filed and any foreign priority date) 2004.
 Gongola et al.; Design of a PZT-actuated proportional drum brake; IEEE ASME Trans. on Mech.; vol. 4; No. 4; pp. 409-416; Dec. 1999.
 Howard Leitch, PPT LTD.; Waveform Gearing; Motion System Design; pp. 33-35; Nov. 2002.
 James et al.; Increasing power density in a full toroidal variator; 3rd Int'l. IIR-Symposium; Innovative Automotive Transmission; pp. 1-11; Dec. 2004.
 Kawamoto et al.; Power assist system HAL-3 for GAIT disorder person; ICCHP 2002; LNCS 2398; pp. 196-203; Aug. 2002.

Kim et al.; On the energy efficiency of CVT-based mobile robots; Proc. 2000 IEEE; Int. Conf. on Robotics & Automation; pp. 1539-1544; San Francisco, CA; Apr. 2000.

Kluger et al.; An overview of current automatic, manual and continuously variable transmission efficiencies and their projected future improvements; Int. Congress and Expo. (No. 1999-1-1259); pp. 1-6; Detroit, MI; Mar. 1-4, 1999.

Krebs et al.; A paradigm shift for rehabilitation robotics; Eng. In Medicine and Biology Magazine, IEEE; vol. 27; Issue 4; pp. 61-70; Jul. 2008.

Misuraca et al.; Lower limb human enhancer; Int. Mech. Eng. Conf. and Expo.; New York, NY; pp. 1-7; Nov. 11-16, 2001.

Niino et al.; Electrostatic artificial muscle: compact, high-power linear actuators with multiple-layer structures; Proc. IEEE Workshop on Micro Electro Mechanical Systems; Oiso, Japan; pp. 130-135; Jan. 1994.

Nugent, James; Design and performance of an exponential roller gear . . . ; U.C. Davis; No. 04CVT-18; pp. 1-8; (year of pub. sufficiently earlier than effective US filed and any foreign priority date) 2004.

Ohhashi, Toshio et al.; Human perspiration measurement; Physiological Measurement; vol. 19; pp. 449-461; Nov. 1998.

Otto Bock Health Care; (3C100 C-Leg® System) Creating a new standard for prosthetic control; http://www.ottobockus.com/products/op_lower_cleg.asp; pp. 1-2; (printed) Nov. 22, 2002.

Otto Bock Health Care; (3C100 C-Leg® System) New generation leg system revolutionizes lower limb prostheses; http://www.ottobockus.com/products/op_lower_cleg4.asp; pp. 1-2; (printed) Nov. 22, 2002.

Otto Bock Health Care; Sensor Walk White Paper; ID No. 09031595.1; pp. 1-12; May 2009.

Patras et al.; Electro-rheological fluids in the design of clutch systems for robotic applications; IEEE; pp. 554-558; Nov. 11-13, 1992.

Powell et al.; Computer model for a parallel hybrid electric vehicle (PHEV) with CVT; Proc. AACC; pp. 1011-1015; Chicago, IL; Jun. 2000.

Shastri et al.; Comparison of energy consumption and power losses of a conventionally controlled CVT with a servo-hydraulic controlled CVT and with a belt and chain as the torque transmitting element; U.C. Davis; No. 04CVT-55; pp. 1-11; Sep. 2004.

Shriner's Hospitals; Your new orthosis; <http://www.shrinershq.org/patientedu/orthosis.html>; pp. 1-3; (printed) Nov. 22, 2002.

Takaki et al.; Load-sensitive continuously variable transmission for powerful and inexpensive robot hands; IEEE; pp. 45-46; Nov. 2004.

Takesue et al.; Development and experiments of actuator using MR fluid; IEEE; pp. 1838-1843; Oct. 2000.

Townsend Design; Functional Bracing Solutions (AIR Townsend & Ultra AIR); <http://www.townsenddesign.com/air.html>; 2 pgs; (printed) Nov. 21, 2002.

Townsend Design; Functional Knee Bracing Solutions; <http://www.townsenddesign.com/functional.html>; pp. 1; (printed) Nov. 21, 2002.

Townsend Design; Patented Motion Hinge (Planes of Motion); <http://www.townsenddesign.com/motion.html>; pp. 1; (printed) Nov. 21, 2002.

Trimmer et al.; An operational harmonic electrostatic motor; IEEE; pp. 13-16; Feb. 1989.

Smith et al., U.S. Appl. No. 12/471,299 entitled "Therapy and mobility assistance system," filed May 22, 2009.

Bhugra, Kern; U.S. Appl. No. 12/363,567 entitled "System and method for controlling the joint motion of a user based on a measured physiological property," filed Jan. 30, 2009.

Horst et al.; U.S. Appl. No. 14/932,796 entitled "Multi-mode active orthotic sensor," filed Nov. 4, 2015.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C






FIG. 6D






FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B






FIG. 12C






FIG. 14




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 14D




FIG. 14E




FIG. 15A






FIG. 15B






FIG. 17A




FIG. 17B

1

**ORTHOTIC DEVICE DRIVE SYSTEM AND
METHOD****CROSS REFERENCE TO RELATED
APPLICATIONS**

This application claims priority to U.S. Provisional Application No. 61/798,101 titled "Orthotic Device Drive System and Method," and filed Mar. 15, 2013, the entirety of which is incorporated by reference herein.

INCORPORATION BY REFERENCE

All publications and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication or patent application was specifically and individually indicated to be incorporated by reference.

FIELD

Embodiments of the present invention relate generally to orthotics, and more specifically to drive systems, components and methods for active orthotics.

BACKGROUND

Wearable active orthotic devices can be used to amplify the residual intention to extend or flex a joint of patients recovering from neuromuscular deficiencies arising from conditions including stroke, traumatic brain injury and multiple sclerosis, or patients recovering from complex orthopedic injuries. Such orthotic devices can be attached across various joints to which movement assistance is provided, such as across a knee, elbow or ankle. The active orthotic device typically has a first portion that attaches to the patient on one side of the joint, a second portion that attaches on the other side of the joint, and an actuator that movably couples the first and second orthotic portions to provide force(s) to assist with movement of the joint. For example, in a knee augmentation device, the first portion is attached around the thigh and the second portion is attached around the calf. The intention to extend the joint may be sensed by a foot pressure sensor.

Considerable force may be required when assisting a joint such as the knee or elbow. The requirements for the actuator are difficult to provide in a compact, lightweight, battery-operated, wearable device.

Many assistive devices use actuators in which a motor is coupled to a lead screw, which may be an Acme screw or ball screw. The lead screw provides both a rotary to linear motion transformation as well as a gear reduction. It may take 10's of rotations of the ball screw to flex the joint less than 180 degrees, thereby providing an effective gear ration that may typically fall in the range of 20:1 to 100:1. The total ratio to the motor may be further increased by using a gear reduction or pulley coupling with different diameter pulleys. The use of a ball screw can meet the basic requirements, but has several disadvantages. The stroke of a ball screw is determined by the length of the screw and the size of the actuator cannot be reduced beyond the length necessary to supply the stroke required to link with the orthotic device. If the linkage is changed to provide the same range of motion with a shorter stroke, the force of the linear actuator must be increased and that may exceed the strength of the screw or available torque of the driving motor.

2

Other actuators have a difficult time meeting the output torque requirements while keeping size and weight low. If the actuator uses direct gearing, such as planetary gears, spur gears, or harmonic drive, the final gear must supply the entire torque and requires a large, heavy gear. Direct gearing also does not have a mode in which the drive mechanism is completely decoupled from the output linkage. Such decoupling is highly desirable for rehabilitation robotics in which the patient should be allowed free swing of the leg or arm in between the times when the powered assistance lifts, supports and/or assists the patient. Further, direct drive has a single gear ratio. In powered assistance of the knee, smaller motors can be used if the drive mechanism has different drive ratios to accommodate the need for high torque (for sit-to-stand or stair ascent) when the knee is bent near 90 degrees, and to provide higher speed (with less torque) for fast walking when the knee is nearly straight.

What would be desirable, but is not provided by the prior art, is an actuator that obtains high force without ball screws or large output gears, allows free movement of a patient when no movement assistance is desired, and varies the drive ratio during the stroke.

SUMMARY OF THE DISCLOSURE

The present invention relates to orthotics, and more specifically to drive systems, components, and methods for active orthotics.

In some embodiments, an active assistance orthosis is provided with a first portion configured to attach to a patient on one side of a joint, a second portion configured to attach to the patient on an opposite side of the joint, and an actuator configured to apply a force between the first and the second portions of the orthosis. In some embodiments, the actuator comprises a first spool rotatably mounted to the first portion, a second spool also rotatably mounted to the first portion, an output pulley mounted to the second portion, and a belt. The belt may have a first end wrapped around the first spool, a second end wrapped around the second spool, and a mid-portion wrapped around the output pulley. The actuator in these embodiments is configured to pull the output pulley toward the first portion when the first spool is rotated to pull the belt a given length and the second spool is rotated to feed the belt less than the given length.

In some of the above embodiments, the second spool is configured to feed the belt less than the given length pulled by the first spool due to a diameter of belt turns on the first spool exceeding a diameter of belt turns on the second spool. The first spool and the second spool may be configured to rotate at a same speed. The first spool and the second spool may be configured to rotate in the same direction or in opposite directions.

The actuator may include a belt tensioner configured to take up slack in the belt. This belt tensioner may include a rotatable drum separate from the first spool, the second spool and the output pulley. In some embodiments, the rotatable drum includes at least one moving roller configured to interact with at least one fixed roller to increase a belt path length. The belt tensioner may include a rotational position sensor coupled to the rotatable drum. In some embodiments, the sensor is configured to communicate with a controller to indicate a belt tension when there is no slack in the belt.

In some embodiments, the orthosis may include a belt having a thickness no greater than about 0.005 inches. In some embodiments, the orthosis may include a polycentric hinge coupling the first portion to the second portion. In these embodiments, the orthosis may include a bell crank

3

linkage coupling the first portion to the second portion, and the output pulley may be located on the bell crank linkage.

In some embodiments, the orthosis may include an actuator configured to provide a winch ratio between the first spool and an angle of the orthosis, wherein the winch ratio is higher when the orthosis is bent (near 90°) than when it is straight. In these embodiments, the actuator may be configured to provide a first winch ratio when the orthosis is positioned at about a 90° angle and a second winch ratio when the orthosis is positioned at about a 0° angle. The first winch ratio may be configured to be at least twice the second winch ratio. In some embodiments, the first winch ratio may be configured to be about four times or more greater than the second winch ratio.

Methods of assisting movement of a patient are also provided. In some embodiments, the method includes attaching a first portion of an orthosis to a patient on one side of a joint, attaching a second portion of an orthosis to the patient on an opposite side of the joint, and detecting a residual intention of the patient to move the joint. The patient is assisted with the intended movement by applying an assistive force to the patient with an actuator applying a force between the first and the second portions of the orthosis. In some embodiments, the actuator comprises a first spool rotatably mounted to the first portion, a second spool also rotatably mounted to the first portion, an output pulley mounted to the second portion, and a belt. The belt may have a first end wrapped around the first spool, a second end wrapped around the second spool, and a mid-portion wrapped around the output pulley.

In some embodiments, the assisting step of the method includes rotating the first spool to pull the belt a given length, and rotating the second spool to feed the belt less than the given length such that the output pulley on the second portion is pulled towards the first portion of the orthosis.

In some embodiments, the attaching a first portion step includes attaching the first portion of the orthosis around a thigh of the patient, and the attaching a second portion step includes attaching the second portion around a calf of the patient. In other embodiments, the attaching a first portion step includes attaching the first portion of the orthosis around an upper arm of the patient, and the attaching a second portion step includes attaching the second portion around a lower arm of the patient.

In general, in one embodiment, a harmonic winch includes a first spool rotatably mounted to a first housing. A second spool is rotatably mounted to the first housing. An output pulley is mounted to the second housing. A belt has a first end wrapped around the first spool, a second end wrapped around the second spool, and a mid-portion wrapped around the output pulley. A motor is configured to rotate the first spool and the second spool. The rotation of the first spool pulls the belt a given length and the rotation of the second spool feeds the belt less than the given length so as to pull the output pulley and the second housing towards the first housing.

In general, in one embodiment, an active assistance orthosis includes a first portion configured to attach to a patient on one side of a joint. A second portion is configured to attach to the patient on an opposite side of the joint. An actuator is configured to apply a force between the first and the second portions of the orthosis. The actuator includes a first spool rotatably mounted to the first portion. A second spool is rotatably mounted to the first portion. An output pulley is mounted to the second portion. A belt has a first end wrapped around the first spool, a second end wrapped

4

around the second spool, and a mid-portion wrapped around the output pulley. The actuator is configured to rotate the first spool and the second spool. The rotation of the first spool pulls the belt a given length and the rotation of the second spool feeds the belt less than the given length so as to pull the output pulley towards the first portion. Pulling the output pulley towards the first portion pulls at least part of the second portion towards at least part of the first portion.

Any of these embodiments can include one or more of the following features. The second spool can be configured to feed the belt less than the given length pulled by the first spool due to a diameter of belt turns on the first spool exceeding a diameter of belt turns on the second spool. The first spool and the second spool can be configured to rotate at a same speed. The first spool and the second spool can be configured to rotate in a same direction. The first spool and the second spool can be configured to rotate in opposite directions. The actuator can further include a belt tensioner configured to take up slack in the belt. The belt tensioner can include a rotatable drum separate from the first spool, the second spool, and the output pulley. The rotatable drum can include at least one moving roller configured to interact with at least one fixed roller to increase a belt path length. The belt tensioner can include a rotational position sensor coupled to the rotatable drum, and the sensor can be configured to communicate with a controller to indicate a belt tension when there is no slack in the belt. The belt can have a thickness no greater than about 0.005 inches.

Any of these embodiments can include one or more of the following features. The orthosis can further include a polycentric hinge coupling the first portion to the second portion. The orthosis can further include a bell crank linkage coupling the first portion to the second portion, and the output pulley can be located on the bell crank linkage. The actuator can be configured to provide a winch ratio between the first spool rotation and the orthosis hinge rotation. The winch ratio can be higher when the orthosis is bent than when it is straight. The actuator can be configured to provide a first winch ratio when the orthosis is positioned at about a 90° angle and a second winch ratio when the orthosis is positioned at about a 0° angle. The first winch ratio can be more than twice the second winch ratio. The orthosis can further include a hinge coupling the first portion to the second portion. Pulling at least part of the second portion towards at least part of the first portion can include rotating the first portion relative to the second portion about the hinge. The actuator can be configured to apply a lower torque and higher speed as the hinge angle between the first portion and the second portion decreases.

Any of these embodiments can include one or more of the following features. The orthosis can further include a motor configured to drive rotation of the first spool and the second spool, a drive sprocket connected to the motor, and a driven sprocket connected to the first spool. The drive sprocket and the driven sprocket can be connected by a second belt. The driven sprocket can have a larger diameter than the drive sprocket.

Any of these embodiments can include one or more of the following features. Rotating the first spool and the second spool to pull at least part of the second portion towards at least part of the first portion can include rotating the first spool and the second spool in a first direction. The actuator can be further configured to rotate the first spool and the second spool in a second direction to allow the output pulley to move away from the first portion so as allow the at least part of the second portion to move away from the at least part of the first portion. The first portion can be configured

5

to attach above the patient's knee and the second portion can be configured to attach below the patient's knee. The orthosis can further include a rotational position sensor coupled to the actuator. The rotational position sensor can be configured to communicate with a controller to indicate a position of the first portion relative to the second portion. The orthosis can further include a belt tensioner, tensioner position sensor, and spool rotation counter, and the rotational position of the first portion relative to the second portion can be determined by a controller based on the spool rotation counter and belt tensioner position.

In general, in one embodiment, a method of assisting movement of a patient includes (1) attaching a first portion of an orthosis to a patient on one side of a joint; (2) attaching a second portion of the orthosis to the patient on an opposite side of the joint; (3) detecting a residual intention of the patient to move the joint; and (4) assisting the patient with the intended movement by applying an assistive force to the patient with an actuator. The actuator includes a first spool rotatably mounted to the first portion, a second spool also rotatably mounted to the first portion, and an output pulley mounted to the second portion. The actuator further includes a belt having a first end wrapped around the first spool, a second end wrapped around the second spool, and a mid-portion wrapped around the output pulley.

Any of these embodiments can include one or more of the following features. The assisting step can include rotating the first spool to pull the belt a given length and rotating the second spool to feed the belt less than the given length such that the output pulley on the second portion is pulled towards the first portion of the orthosis. Attaching a first portion can include attaching the first portion of the orthosis around a thigh of the patient, and attaching a second portion can include attaching the second portion around a calf of the patient. Attaching a first portion can include attaching the first portion of the orthosis around an upper arm of the patient, and attaching a second portion step can include attaching the second portion around a lower arm of the patient.

The actuator or winch can be used to provide assistance during extension of a joint while allowing unassisted movement during flexion of the joint. The spools can be rotated to a position where there is slack in the belt to allow unassisted movement of the joint.

In addition to use in active orthotic devices as detailed herein, the compact high-force actuator systems, components and methods of this disclosure are useful in a variety of other applications as well. These applications may include, but are not limited to, patient lifts, rehabilitation equipment, exercise equipment, and mechanical devices for lifting, hauling and positioning.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features of the invention are set forth with particularity in the claims that follow. A better understanding of the features and advantages of the present invention will be obtained by reference to the following detailed description that sets forth illustrative embodiments, in which the principles of the invention are utilized, and the accompanying drawings of which:

FIG. 1 shows an active knee orthosis.

FIG. 2 illustrates a mechanical linkage between an actuator and the body attachment of an orthosis.

FIG. 3 is a block diagram showing the electronics used to drive and control an active muscle assistance device.

6

FIG. 4 is flowchart showing the modes of operation of a muscle assistance device.

FIG. 5 is a flowchart of the modes of operation of a knee joint muscle assistance device.

FIG. 6A is a side view of an exemplary harmonic winch actuator shown at the beginning of its stroke.

FIG. 6B is a side view of the actuator of FIG. 6A shown at the end of its stroke.

FIG. 6C is a side view of a variation of the actuator of FIGS. 6A and 6B wherein the first and second spools are gear coupled to rotate in opposite directions.

FIG. 6D is a side view of another variation of the actuator of FIGS. 6A and 6B wherein the first and second spools have different diameters and turn at different speeds.

FIG. 7A is a side elevation view of an exemplary harmonic winch actuator. FIG. 7B is a top plan view of the actuator shown in FIG. 7A.

FIGS. 8A-8C are a sequence of side views showing the use of a harmonic winch on an orthosis having a single pivot point.

FIG. 8D is a side view showing the use of a harmonic winch on an orthosis having a polycentric hinge.

FIGS. 9A-9C are a sequence of side views showing details of a belt tensioner of the actuator shown in FIGS. 7A-7B.

FIG. 10A is a graph showing the relationship of various parameters to the joint angle for a simple linkage orthosis.

FIG. 10B is a graph showing the relationship of various parameters to the actuator stroke for a simple linkage orthosis.

FIG. 11A is a graph showing the relationship of various parameters to the joint angle for an orthosis having a bell crank linkage.

FIG. 11B is a graph showing the relationship of various parameters to the actuator stroke for an orthosis having a bell crank linkage.

FIGS. 12A-12C are various views showing details of an embodiment for attaching the ends of a belt of a harmonic winch to the spools.

FIG. 13A is a side elevation view showing another exemplary embodiment of a harmonic winch actuator.

FIG. 13B is a top plan view showing the actuator of FIG. 13A.

FIG. 14 shows various details of an alternative spool-mounted belt tensioner.

FIG. 14A shows a close-up of the front of the spool with a belt keyway of FIG. 14.

FIG. 14B shows the back of the spool of FIG. 14A.

FIG. 14C shows the gear with stop of FIG. 14.

FIG. 14D shows the spool with stop of FIG. 14.

FIG. 14E shows the belt with end loop of FIG. 14.

FIG. 15A is a side elevation view showing another exemplary embodiment of a harmonic winch actuator.

FIG. 15B is a top plan view showing the actuator of FIG. 15A.

FIGS. 16A-16B show another exemplary harmonic winch actuator.

FIGS. 17A-17B show two different views of another exemplary harmonic winch actuator.

DETAILED DESCRIPTION

General Overview of a Knee Orthosis

FIG. 1 schematically shows an exemplary active muscle support orthosis according to one embodiment of the invention. The device 10 is an active knee orthosis or brace used

to offload some of the stress from the quadriceps when extending or flexing the leg. For different parts of the body, other devices are constructed with a suitable shape, but the principles presented here apply by analogy to such devices. The device **10** is particularly useful in helping someone with muscle weakness in the everyday tasks of standing, sitting, walking, climbing stairs, and descending stairs. The device **10** includes an upper portion **16** configured to be placed around the user's upper legs (such as the thighs), a lower portion **14** configured to be placed around the user's lower legs (such as the calf), and an actuator **12** therebetween. The support to the muscle is defined by the position of the actuator **12** applying force to the moving parts of the orthosis **10**. Namely, as the actuator **12** rotates, and with it the moving (rigid) parts of the orthosis, the position of the actuator **12** defines the relative position of the joint and thereby supports the corresponding muscle. The actuator **12** can be used principally to provide assistance during extension of a joint. As described further below, the actuator **12** can be a harmonic winch actuator that advantageously provides high torque, varies the drive or winch ratio during the stroke, and provides for free movement of the joint when assistance is not desired.

The device **10** can provide assistance and/or resistance to the muscles that extend and flex a joint. In some embodiments, resistance can be provided to resist the force exerted by the muscles, and/or resistance can also be provided to resist or oppose the force of gravity. The device **10** can be configured so as to not directly connect to the muscle, but rather be attached in such a way that it can exert external forces to the limbs.

The device **10** can be built from an underlying structural frame (such as of lightweight aluminum or carbon fiber), padding, and straps (not shown) that can be tightened to the desired pressure. The structural frame of the device **10** includes a rigid upper portion **16** above the knee connected to a hinge **18** at the medial and lateral sides. The upper portion **16** can extend up to the mid-thigh. The structural frame **10** further includes a rigid lower portion **14** below the knee that extends from the hinge **18** down to the mid-calf. In the thigh and calf regions, the frame extends around from medial to lateral sides around approximately half the circumference of the leg. The remaining portion of the circumference is spanned by straps that can be tightened with clips, laces, hook and loop closures (such as Velcro®), clip-type connectors **17**, and/or by a zipper type fastener. Understandably, this allows easier attachment and removal of the device. The rigid portions **14**, **16** can be either on the anterior or posterior side. The number and width of straps can vary, but the straps must be sufficient to hold the device in place with the axis of rotation of the hinge in approximately the same axis as that of rotation of the knee. The hinge **18** itself may be more complex than a single pivot point to match the rotation of the knee. In more general terms, in some embodiments, the device **10** has a frame that has a first structural portion that is attached to the body above or proximally the joint, a second structural portion that is attached to the body below or distally to the joint, and an articulating joint portion connecting the first structural portion with the second structural portion.

Cushioning material may be added to the device **10** to improve comfort. In some embodiments, a manufacturer may choose to produce several standard sizes of the device **10**, each with enough adjustments to be comfortable for a range of patients. In other embodiments, the manufacturer may use a mold or tracing of the leg to produce individually customized devices **10**. In still other embodiments, a single

size of the device **10** may be produced that may be adjusted to fit a wide variety of patients.

A microcontroller-based control system can drive control information to the actuator (such as the winch actuator described below), receive user input from a control panel function, and receive sensor information including joint position and external applied forces. For example, pressure information is obtained from the foot-pressure sensor **19**. Based on the sensor input and desired operation mode, the control system can apply forces to resist the muscle, apply force to assist the muscle, or allow the muscle to move the joint freely.

FIG. **2** illustrates a side-view diagram of an orthotic system according to an exemplary embodiment of the invention. In the illustrated embodiment, orthotic system **300** includes: linear actuator **301** (which may be replaced by the harmonic winch actuator described further below); bell crank **302**; thigh orthotic structure **303**; lower leg orthotic structure **304**; tibia anterior structure **305**; tibia posterior structure **306**; connector link **307**; hinge **308**; tibia suspension system **309**; lateral support structures **310**; ankle suspension structure **311**; footpad sensor system **312**; lower leg textiles **313**; thigh textile **314**; upper shin textile **315**; toe strap **326**; and anti-foot drop system **327**. However, this is given by way of example and not limitation, as the orthotic system described herein may include fewer or more components. The linear actuator **301** acts directly on a linkage point of a bell crank rocker arm **302**. Further, the linear actuator **301** is mounted on a pivot **321** at the upper most end of the thigh orthotic structure **303**. However, other embodiments can include the linear actuator **301** being constrained on a fixed plane or fixed via pivot on any portion of the thigh orthotic structure **303** or lower leg orthotic structure **304** or other structural parts. Alternate embodiments can also include indirect actuation via an input link between the linear actuator **301** and the bell crank **302**.

FIG. **3** is a block diagram showing an exemplary electronics and control system for an orthosis as described herein. The operation of the device may be controlled by a program running in a microcontroller **402**. To minimize the physical size of the control system, the microcontroller may be selected based on the scope of its internal functionality.

In the exemplary embodiment of FIG. **3**, the microcontroller **402** is coupled to a control panel **404** to provide user control and information on the desired mode of operation. The control panel includes a set of switches that can be read through the input buffers **418** of the microcontroller. The control panel also may have a display panel or lights to display information, such as operational mode and battery state. The control panel also includes means to adjust the strength of assistance and resistance in order to customize the forces to the ability of the user. Another embodiment of the control panel is a wired or wireless connection port to a handheld, laptop or desktop computer. The connection port can also be used to communicate diagnostic information and previously stored performance information.

The control panel may be part of the actuator or may be attached to another part of the structural frame with wires connected to the actuator. In some embodiments, buttons of the control panel can be of the type that can be operated through clothing to allow the device mode to be changed when the device is hidden under the clothes. In other embodiments, the device can be worn on top of clothing or can be worn directly on the skin and remain uncovered.

Outputs of the microcontroller, provided from the output buffers **426**, can be directed in part to the actuator **1012** (such as the winch actuator described below) through a power

driver circuit **410** and in part to the control panel **404**. In one embodiment, the driver circuit converts the outputs to high voltage phases to drive an electrostatic actuator. The power driver circuit includes transformers and rectifiers to step up a-c waveforms generated by the microcontroller. In instances where the actuator is a DC motor, servomotor, or gear motor, the power driver circuit may be designed to generate high-current multi-phase signals.

When the operation mode of the muscle assistance device is set to apply a force that opposes the motion of the joint, the energy input from that 'external' force must be absorbed by the control circuit. While this energy can be dissipated as heat in a resistive element, it may also be returned to the battery in the actuator power supply **408** via a regeneration braking circuit **412**. This concept is similar to "regenerative braking" found in some types of electric and hybrid vehicles to extend the operation time before the battery needs to be recharged.

In some embodiments, the microcontroller **402** can receive digital information via a digital interface connection **430** from a muscle stress sensor **416** that includes an analog to digital converter. In other embodiments, the analog to digital converter can be located in the microcontroller **402** and the muscle stress sensor **416** can output analog data. The joint angle sensor **414** provides the joint angle via a belt position sensor, potentiometer or optical sensor of a type known in the art, or by an encoder coupled to a lead screw or other drive component.

When the orthotic device is used to assist leg extension, the muscle stress sensor **416** may be implemented as a foot-pressure sensor (such as pressure sensor **19** in FIG. **1**) wired to the active orthosis. In one embodiment, this sensor is implemented with parallel plates separated by a dielectric that changes total capacitance under pressure. The foot sensor may be a plastic sheet with conductive plates on both sides so that when pressure is applied on the knee the dielectric between the plates compresses. The change in the dielectric changes the capacitance and that capacitance change can be signaled to the microcomputer indicating to it how much pressure there is on the foot. Other pressure sensors may use resistive ink that changes resistance when pressure is applied on it. Yet another type of pressure sensor, such as a strain gauge can be alternatively used to supply the pressure information. Further sensor constructs are subsequently described in more detail. These sensors are configured to detect the need or intention to exert a muscle. For example, the foot pressure sensor in conjunction with joint angle sensor detects the need to exert the quadriceps to keep the knee from buckling. Other types of sensors, such as strain gauges, can detect the intention by measuring the expansion of the leg circumference near the quadriceps. In another embodiment, surface mounted electrodes and signal processing electronics measure the myoelectric signals controlling the quadriceps muscle. When the orthotic device is used for other muscle groups in the body, appropriate sensors can be used to detect either the need or intention to flex or extend the joint being assisted. It is noted that there may be a certain threshold (minimum amount of force), say 5 pounds on the foot, above which movement of the actuator is triggered.

Power for the muscle assistance devices described herein can come from one or more battery sources feeding power regulation circuits. The power for the logic and electronics is derived from the primary battery (in the power supply **408**). The battery-charge state is fed to the microcontroller for battery charge status display or for activating low battery alarms. Such alarms can be audible, visible, or a vibration

mode of the actuator itself. Alternatively, a separate battery can power the electronics portion.

Turning now to FIG. **4**, the operation of an exemplary muscle assistance device is illustrated with a block diagram. The algorithm in this diagram is implemented by embedded program code executing in the microcontroller. In the first step of FIG. **4**, the user selects a mode of operation **502**. The modes include: idle **506**, assist **508**, monitor **510**, rehabilitate **512**, and resist **514**.

In the idle mode **506**, the actuator is set to neither impede nor assist movement of the joint. This is a key mode in some implementations because it allows the device to move freely or remain in place when the user does not require assistance or resistance, or if battery has been drained to the point where the device can no longer operate. In idle mode, the actuator allows free movement with a clutch or an inherent free movement mode of the actuator, for example, even when primary power is not available.

In the monitor mode **510**, the actuator is in free movement mode (not driven), but the electronics are activated to record information for later analysis. Measured parameters include a sampling of inputs from the sensors and counts of movement repetitions in each activation mode. This data may be used later by physical therapists or physicians to monitor and alter rehabilitation programs.

In the assist mode **508**, the actuator is programmed to assist movements initiated by the muscle. This mode augments the muscle, supplying extra strength and stamina to the user. In the assist mode **508**, the device can also resist the force exerted by gravity. This use of the term "resist" is not to be confused with the way the term "resist" is used in the description of the resist mode **514**, as described below. Again, as mentioned herein with respect to FIGS. **4** and **5**, "resist" can refer to both resisting gravity as described in the assist mode and to resisting the force exerted by muscle as described below in the resist mode.

In the resist mode **514**, the device is operating as an exercise device. Any attempted movement is resisted by the actuator. Resistance intensity controls on the control panel determine the amount of added resistance. In the resist mode **514**, the device resists the force exerted by the muscle.

In the rehabilitate mode **512**, the device provides a combination of assistance and resistance in order to speed recovery or muscle strength while minimizing the chance of injury. Assistance is provided whenever the joint is under severe external stress, and resistance is provided whenever there is movement while the muscle is under little stress. This mode levels out the muscle usage by reducing the maximum muscle force and increasing the minimum muscle force while moving. The average can be set to give a net increase in muscle exertion to promote strength training. A front panel control can provide the means for setting the amplitude of the assistance and resistance.

Then, assuming that the rehabilitate mode **510** is selected, a determination is made as to whether the muscle is under stress. The indicia of a muscle under stress is provided as the output of the muscle stress sensor reaching a predetermined minimum threshold. That threshold is set by the microcontroller in response to front panel functions.

If the muscle is not under stress or if the resist mode **514** is selected, a further determination is made as to whether the joint is moving **522**. The output of the joint position sensor, together with its previous values, indicates whether the joint is currently in motion. If it is, and the mode is either rehabilitate or resist, the actuator is driven to apply force opposing the joint movement **524**. The amount of resistance is set by the microcontroller in response to front panel

11

settings. The resistance may be non-uniform with respect to joint position. The resistance may be customized to provide optimal training for a particular individual or for a class of rehabilitation.

If the joint is not in motion **522** or the monitor mode **510** is selected, the actuator is de-energized to allow free movement of the joint **526**. This may be accomplished by using an actuator that has an unpowered clutch mode.

Additionally, if the muscle is under stress **520** or **522** and either the rehabilitate or the assist modes are selected, the actuator is energized to apply force for assisting the muscle **528**. The actuator force directed to reduce the muscle stress. The amount of assistance may depend on the amount of muscle stress, the joint angle, and the front panel input from the user. Typically, when there is stress on the muscle and the joint is flexed at a sharp angle, the largest assistance is required. In the case of knee assistance, this situation would be encountered when rising from a chair or other stressful activities.

As mentioned before, when the device is in monitor mode **510**, measurements are recorded to a non-volatile memory such as the flash memory of the microcontroller (item **420** in FIG. 3). Measurements may include the state of all sensors, count of number of steps, time of each use, user panel settings, and battery condition. This and the step of uploading and analyzing the stored information are not shown in the diagram.

FIG. 5 is a flow diagram specific to an active knee assistance device. This diagram assumes a specific type of muscle stress sensor that measures the weight on the foot. Relative to the diagram of FIG. 5, this diagram also shows a step (**620**) to determine whether the knee is bent or straight (within some variation). If the knee is straight, no bending force is needed **624** and power can be saved by putting the actuator in free-movement mode **630**. To prevent problems such as buckling of the knee, the transitions, i.e., de-energizing the actuator, in both FIGS. 5 and 6 may be dampened to assure that they are smooth and continuous.

The software running on the microcontroller may be architected in many different ways. One architecture is to structure the embedded program code into subroutines or modules that communicate with each other and receive external interrupts (see item **424** in FIG. 3). Other embodiments are not interrupt driven. In one implementation the primary modules include control panel, data acquisition, supervisor, actuator control, and monitor modules. A brief description of these modules is outlined below.

The control panel responds to changes in switch settings or remote communications to change the mode of operation. Settings may be saved in a nonvolatile memory, such as a bank of flash memory.

The data acquisition module reads the sensors and processes data into a format useful to the supervisor. For instance, reading position from a capacitive position sensor involves reading the current voltage, driving a new voltage through a resistance, then determining the RC time constant by reading back the capacitor voltage at a later time.

The supervisor module may be a state machine for keeping track of high-level mode of operation, joint angle, and movement direction. States are changed based on user input and sensor position information. The desired torque, direction and speed to the actuator control the functioning of this module. The supervisor module may also include training, assistance, or rehabilitation profiles customized to the individual.

The actuator control module is operative to control the actuator (low level control) and includes a control loop to

12

read fine position of the actuator and then drive phases to move the actuator in the desired direction with requested speed and torque. The monitor module monitors the battery voltage and other parameters such as position, repetition rates, and sensor values. It also logs parameters for later analysis and generates alarms for parameters out of range. This module uses the front panel or vibration of the actuator to warn of low voltage from the battery.

A number of variations in the above described system and method include, for example, variations in the power sources, microcontroller functionality, and the like. Specifically, power sources such as super capacitors, organic batteries, disposable batteries and different types of rechargeable batteries can be used in place of a regular rechargeable battery. Moreover, microcontroller functionality can be split among several processors or a different mix of internal and external functions. Also, different types of orthotic devices, with or without hinges and support frames, may be used for attachment to the body, and they may be of different lengths. Various ways of communicating the 'weight-on-foot' may be used, either through wired or wireless connections to the control circuitry, or by making the orthosis long enough to reach the foot.

Harmonic Winch Actuator

Referring to FIGS. 6A-17B, various exemplary embodiments of harmonic winch actuators will now be described. FIGS. 6A-6D highlight basic concepts of construction and operation of some of these embodiments. Referring first to FIGS. 6A and 6B, a first embodiment is schematically shown. FIG. 6A shows harmonic winch actuator **710** at the beginning of its stroke and FIG. 6B shows winch actuator **710** at the end of its stroke. Winch actuator **710** includes a first spool **712**, a second spool **714**, and a belt **716** coupled between the two spools **712**, **714**. Belt **716** has a first end attached to first spool **712**, a second end attached to second spool **714**, and a mid-portion that loops around a pulley **718**. First spool **712** and second spool **714** are rotatably mounted to first housing **720**, and pulley **718** is rotatably mounted to second housing **722**. In operation, winch actuator **710** moves second housing **722** with respect to first housing **720**. For example, first housing **720** may be located on an upper portion of a knee orthosis and second housing **722** may be located on a lower portion of the knee orthosis, such that winch actuator **710** is able to drive (e.g., rotate) the lower portion of the orthosis relative to the upper portion.

When winch actuator **710** is at the beginning of its stroke as shown in FIG. 6A, roughly equal amounts of belt **716** are wound around first spool **712** and second spool **714**. In this mode, first spool **712** operates as a pull spool, and second spool **714** operates as a feed spool. In this embodiment, first spool **712** and second spool **714** are both driven together at the same rate and in the same direction, such as by an electric motor and a common chain, timing belt, or gear drive (e.g. with an intermediate gear between the gears for first spool **712** and second spool **714**). Because the effective radii of first spool **712** and second spool **714** are roughly the same at the beginning of the stroke, the same amount of belt **716** is fed from second spool **714** as is taken up by first spool **712**, and therefore pulley **718** rotates, but does not move laterally. As more belt **716** accumulates on first spool **712**, its effective radius gets larger. Similarly, as more belt **716** is released from second spool **714**, its effective radius gets smaller. With the effective radius of first spool **712** getting larger than that of second spool **714**, more belt **712** is wound around first spool **712** than is released from second

spool 714 with each turn of the two spools 712, 714. This action shortens the loop of belt 716 that extends around pulley 718, and therefore pulley 718 and second housing 722 are pulled (such as laterally pulled or rotationally pulled) towards spools 712 and 714 and first housing 720.

At the beginning of a stroke, winch actuator 710 is in a high torque, low speed mode. As winch actuator 710 progresses from a beginning of stroke configuration as shown in FIG. 6A towards an end of stroke configuration as shown in FIG. 6B, winch actuator 710 transitions from a high force, low speed configuration to a low torque, high speed configuration, pulling pulley 718 and second housing 722 faster towards first housing 720. In other words, the mechanical advantage of winch actuator 710 changes from the beginning of the stroke to the end of the stroke. In embodiments where linear movement is achieved by the actuator 710 (as shown in FIGS. 6A-6D), the mechanical advantage can be determined by the number of rotations of the first spool 712 required to provide a unit of linear movement. In embodiments where rotary movement of a joint is achieved by a harmonic actuator (such as described, for example, below with respects to FIGS. 8A-8C), the mechanical advantage can be determined by the winch ratio, which is equivalent to the speed of rotation of the first spool 712 to the speed of rotation of the joint.

Referring now to FIG. 6C, a variation of the harmonic winch of FIGS. 6A and 6B will be described. In this embodiment, first spool 712 and second spool 714 are configured to rotate in opposite directions. This can be accomplished, for example, by driving the two spools with gears directly coupled together. The harmonic winch actuator 710' in this embodiment operates in the same manner as actuator 710 of FIGS. 6A and 6B except that belt 716 is paid out from the bottom of second spool 714 instead of the top, such that a second spool 714 rotates in a counterclockwise direction to pay out belt 716, rather than in a clockwise direction as in FIGS. 6A and 6B.

Referring to FIG. 6D, another variation 710" of the harmonic winch actuator of FIGS. 6A and 6B is shown. In this embodiment, first spool 712' and a second spool 714' have different diameters. For example, first spool 712' may have a diameter that is twice the diameter of second spool 714'. Additionally, the two spools 712', 714' are coupled to each other via gears or pulleys with the same diameter ratio as the diameter ratio of first spool 712' and second spool 714' in order to drive the spools in the same direction but at different rates. In this example, first spool 712' is driven at a rate that is half the rate of second spool 714'. With this arrangement, the second spool 714' pulls in belt 716 at a rate roughly the same as the rate that first spool 712' pays out belt 716 at the beginning of the stroke when both spools have roughly the same amount of belt 716 on them. As in other embodiments, the winch ratio increases as the amount of belt 716 on the pull spool 714' increases, and the amount of belt 716 on the feed spool 712' decreases. An advantage of this configuration is that the rate of winch ratio change is more gradual than when the spools are of the same diameter and driven at the same speed. This is because the diameter of feed spool 712' changes more slowly in this embodiment. As such, there is less variation in the winch ratio from the beginning of the stroke to the end of the stroke in this embodiment as compared with the previous embodiments.

In some embodiments, such as those shown depicted in FIGS. 6A-6D, a separate belt tensioner need not be provided. In these embodiments, first and second spools 712 and 714 may act as belt tensioners by pulling slack out of belt 716 when output pulley 718 is located in a position

where no force is being put on belt 716. In other embodiments, no tensioner is necessary because tension is provided by an external tensioner or because there is always a force (such as gravity) pulling second housing 722 away from first housing 720. It is to be understood that the embodiments shown in FIGS. 6A-6D are simplified schematics and that any of the details described elsewhere in this disclosure can apply to the embodiments described with respect to FIGS. 6A-6D.

Referring now to FIGS. 7A and 7B, a side elevation view and a top plan view, respectively, of a more detailed embodiment of a harmonic winch actuator 710 are shown. Harmonic winch actuator 710 includes an electric motor 724 with a gear head 726 coupled to its output. Gear head 726 is provided with a motor drive sprocket 728 on its output. Drive sprocket 728 is coupled to a driven sprocket 730 with a motor drive chain 732. Driven sprocket 730 is twice the diameter of drive sprocket 728 in this embodiment to further reduce the rotational speed output by motor 724. This arrangement allows motor 724 to drive first spool 712. Further, first spool 712 and second spool 714 are each provided with a spool sprocket 734 of the same diameter and interconnected with inter-spool chain 736 such that they are both driven in the same direction and at the same speed of rotation by the motor 724. In the embodiment of FIGS. 7A and 7B, as was described in reference to FIGS. 6A and 6B, first spool 712 is shown on the left and serves as a pull spool while second spool 714 is shown on the right and serves as a feed spool. As before, pull spool 712 takes in belt 716 from the bottom while feed spool 714 pays out belt 716 from the top, and both spools 712, 714 turn clockwise to pull housing 722 towards housing 720. In contrast, when the spools 712, 714 are turned counter-clockwise, belt 716 is released more quickly by the first spool 712 than belt 716 is pulled in by the second spool 714. As a result, the length of the belt 716 between housing 722 and housing 720 is increased, and housing 722 is allowed to move away from housing 712.

Harmonic winch actuator 710 may also be provided with a belt tensioner 738 as shown to pull slack out of belt 716 during operation of winch actuator 710. In this embodiment, belt tensioner 738 is mounted between first spool 712 and second spool 714 and is configured to rotate up to about 180 degrees about an axis that is parallel to the axes of rotation of spools 712 and 714. Belt tensioner 738 may include a spiral torsion spring 740 located at one end as shown. Torsion spring 740 causes tensioner 738 to rotate and apply just enough force to belt 716 to remove the slack from the belt 716 without impeding the motion of the output pulley 718 and second housing 722 when no force is being applied by actuator 710. Belt tensioner 738 will subsequently be described in more detail with reference to FIGS. 9A-9C.

Rotational position sensors, such as encoders 742, may also be provided on belt tensioner 738 and motor 724 as shown. Encoder 742 may be used for position feedback to the electronics in order to control the sequencing of motor drive phases to motor 724 when it is a brushless 3-phase DC motor. The electronics may also use position information obtained from encoder 742, along with knowledge of the drive ratio from motor 724 to pull spool 712, to count rotations of the spools 712, 714. By doing so, the total length of the belt 716 between the spools 712, 714 can be determined. This information in turn can determine the maximum extended position of housing 722, which can be used to determine the maximum amount of flexion of an orthotic brace using the winch actuator 710 (such as orthotic brace 10, 300, 300', or 810 described herein). Moreover, belt tensioner 738 may be used in conjunction with encoders 742

15

to indicate to the controlling electronics and/or software the amount of slack in belt **716** at any given time during operation. When belt **716** is being pulled tightly, small variations in the position of the tensioner can be used to detect the force that is being applied by actuator **710**.

In this exemplary embodiment, belt **716** can be 0.005 inches thick, 1 inch wide, and about 5 feet long. Belt **716** may be made out of a UHMWPE (ultra-high molecular weight polyethylene) such as Dyneema® or Spectra. Other suitable materials include PBO (poly(p-phenylene-2,6-benzobisoxazole)) such as Zylon, liquid crystal polymer such as Vectran, and para-aramids such as Kevlar®. Belt **716** may be made of a single, homogeneous material. Alternatively, belt **716** may be formed from laminated layers, coatings and/or woven or reinforcing fibers of the same or of different materials. It is beneficial to use a high-strength material and/or construct that can provide a sufficient tensile force without stretching, even with a small belt thickness. The thinner the belt **716** is, the smaller the effective radius change is as belt **716** moves from feed spool **714** to pull spool **712** of winch actuator **710**. This means that more rotations of spools **712** and **714** are required to move pulley **718** and second housing **722** towards first housing **720** from the beginning of the stroke to the end of the stroke. In other words, a higher mechanical advantage and ratio are provided by using a thinner belt **716** in actuator **710**.

Referring to FIGS. **8A-8C**, harmonic winch actuator **710** is shown coupled to an exemplary joint assistance device **810**. Device **810** may be an orthosis configured to attach adjacent to a patient's knee and actively assist the patient with walking and/or other leg movements, as described above with respect to FIGS. **1** and **2**. A first portion **812** of device **810** is configured to attach to the patient on one side of the joint, such as above the knee on the thigh, as previously described. A second portion **814** is configured to attach to the patient on an opposite side of the joint, such as below the knee on the calf. In this embodiment, the first portion **812** and the second portion **814** of device **810** are rotatably coupled together by a single pivot point **816**. However, the first and second portions **812** and **814** need not be connected by a single pivot point, as will be subsequently described with reference to other embodiments. As shown in FIG. **8A-8C**, first and second spools **712** and **714** may be located on the first portion **812** of device **810**. Output pulley **718** may be located on the second portion **814** of device **810** as shown. In other embodiments, the locations of these components may be reversed. In operation, pivot point **816** can be located adjacent to the knee or other joint. Belt **716** loops around second spool **714** and spans between first portion **812** and second portion **814** of device **810**.

The harmonic winch actuator **710** can be used to rotate the second portion **814** of the device **810** relative to the first portion **812**. For example, the winch actuator **710** can be used to provide assistance during extension of the patient's leg (and thus decreasing the angle formed by the device **810**). FIG. **8C** shows device **810** in a bent configuration where the first portion **812** forms an angle of 90° with second portion **814**, such as when the patient is sitting. In this position, the belt **716** is relatively long between the first portion **812** and the second portion **814**. As the actuator rotates the spools **712**, **714**, the diameter of the spool **712** can increase while the diameter of the spool **714** decreases, thereby causing the length of the belt **716** to decrease between the first portion **812** and the second portion **814**. This shortening of the belt **716** causes the upper sections of the first and second portions **812**, **814** to move closer together by pivoting around the pivot point **816**. FIG. **8A**

16

shows device **810** move into a straight configuration wherein the first portion **812** forms an angle of 0° with second portion **814**. The winch actuator **710** can thus be used to assist the patient in extending a leg from sitting (approximately 90° to approximately 0°). Likewise, the harmonic winch actuator **710** can be used to extend the leg during walking. For example, FIG. **8B** shows device **810** in a partially bent configuration wherein the first portion **812** forms an angle of 45° with second portion **814**. This orientation may occur during the patient's stride when walking. Similar to as described with respect to FIG. **8C**, the actuator can be used to shorten the length of the belt **716**, thereby pulling the upper sections of the first and second portions **712**, **714** together about the pivot point **816**, thereby assisting in extending the leg to 0° as shown in FIG. **8A**.

In some embodiments, to flex the leg when wearing the device **810**, the belt **716** can be loosened by rotating the rollers **712**, **714** in the opposite direction. Loosening the belt **716** (or creating slack in the belt **716**) in turn allows the upper sections of the first and second portions **812**, **814** to move apart from one another about the pivot point **816**, thereby allowing the leg to flex. The winch actuator **710** can therefore advantageously provide assisted extension of the device **810** while allowing free flexion of the device. Moreover, the device **810** can be set to provide both free (unassisted) extension and flexion by simply extending the belt **716** fully for both extension and flexion.

In the exemplary embodiment of FIGS. **8A-8C**, device **810** as a range of motion of about 90°. In other embodiments, the range of motion may be more or less than 90°.

Referring to FIG. **8D**, a harmonic winch actuator **710** is shown mounted to a multi-fit orthotic system **300'** similar to system **300** originally shown in FIG. **2**. As shown, first spool **712** and second spool **714** of actuator **710** are located on thigh portion **303** of orthosis **300'**. Output pulley **718** is coupled to bell crank **302** such that when belt **716** pulls output pulley **718** towards the spools **712**, **714**, bell crank **302** is rotated counter-clockwise around pivot point **350**. Bell crank **302** in turn pulls linkage **307**, which rotates calf portion **304** about dual pivot coupling **308** to the straight or 0° position shown. Dual pivot coupling **308** forms a polycentric hinge which allows calf portion **304** to pivot about two axes with respect to thigh portion **303** of orthosis **300'**. This method of orthosis **300'** articulation with the polycentric hinge more closely mimics the articulation that naturally occurs in the adjacent knee of the patient.

Referring to FIGS. **9A-9C**, detailed construction and operation of the exemplary belt tensioner **738** first introduced with reference to FIGS. **7A** and **7B** will now be described. In this embodiment, tensioner **738** includes four moving rollers **910**, **912**, **914** and **916** and three fixed rollers **918**, **920** and **922**. Each of the moving rollers **910**, **912**, **914**, **916** and the fixed rollers **918**, **920**, **922** may be configured to rotate about its own axis, such as on bearings, to reduce friction as belt **716** moves with respect to the respective roller. Additionally, the moving rollers **910**, **912**, **914** and **916** are mounted on a drum **924** or disk such that they rotate with drum **924** about its central axis **926**. In this embodiment, drum **924** may rotate through a range of about 180°. Slot **928** is provided through drum **924** to allow fixed roller **920** to protrude through drum **924** without impeding its range of rotation. FIG. **9A** shows tensioner **738** in a 0° position with belt **716** passing through tensioner **738** in a straight or nearly straight path. FIG. **9B** shows tensioner **738** in a 90° position with belt **916** being drawn around fixed rollers **918**, **920** and **922** by moving rollers **910** and **912**. FIG. **9C** shows tensioner **738** in a 180° position with belt

916 being drawn further around fixed rollers 918, 920 and 922 by moving rollers 910, 912, 914 and 916. With this arrangement of rollers, the belt 716 at no point touches another portion of the belt 716 and rests only on rolling supports, thus avoiding friction and wear of the belt 716. It can be appreciated that the serpentine belt path shown in FIG. 9C is considerably longer than the straight belt path shown in FIG. 9A. As such, tensioner 738 is able to take up a large amount of slack in belt 916 without rotating very far.

During operation of the harmonic winch actuator 710 when belt 716 is applying a load to the output pulley 728, belt tensioner 738 is typically in an orientation close to the 0° state shown in FIG. 9A. In this state, moving rollers 910 and 912 contact belt 716 and deflect it by a small amount, even when high force is being exerted by the winch actuator 710. By measuring the small amount of belt deflection with the previously mentioned encoder, the system controller can determine the amount of force being exerted by belt 716 on the output pulley. As tension in belt 716 drops off, such as when a patient moves his leg ahead of the position being driven by the harmonic winch actuator, belt tensioner 738 rotates up to 180° to take up the belt slack. The tensioner rotation is provided automatically by spiral torsion spring 740, shown in FIGS. 7A and 7B.

FIG. 10A is a graph showing the relationship of torque, effective ratio and number of spool turns from full joint flexion in the exemplary harmonic winch actuator 710 as a function of knee angle for an orthosis having a fixed radius joint linkage (in other words, a joint linkage such as shown in FIGS. 8A-8C). In this graph, it is assumed that the linear motion of actuator 710 is converted directly to rotary motion of the output joint at a radius of 1.3 inches from the single rotation axis of the joint. The graph line 1010 showing the number of spool turns shows the number of turns starting at 6 and increasing to about 16 turns. The first through fifth spool turns are not shown on the graph, since at this point the effective diameters of the spools are nearly equal, creating an effective winch ratio near infinity. In other words, when the spools are exactly the same diameter, the amount of belt paid out and pulled in is the same and the same-diameter spools could be rotated an infinite number of times without changing the belt path length. Dividing the pull spool speed by the zero speed of the joint gives an infinite ratio that produces almost no output movement.

The graph line 1020 shows the effective winch ratio going from about 18, increasing to about 37 and dropping back down to about 28 over the course of the winch stroke. This shows that there is a mechanical advantage wherein the rotation of the spools is at least 18 times faster than the rotation of the orthosis joint. In some embodiments, a gear head 726 may be used that, when coupled with drive sprocket 728 and driven sprocket 730 as shown in FIGS. 7A-7B, produces a gear ratio of 12.9 to 1. When this front end gear ratio of 12.9 is multiplied by the winch ratios shown in FIG. 10A, total reduction ratios ranging from about 232 to about 477 are achieved in this exemplary embodiment. These high ratios are used to go from the rotation of the high-speed motor to the slow but high torque rotation needed to move a person's leg. Graph line 1020 of FIG. 10A also shows that when a patient's leg is bent between 60° and 120°, and more particularly when it is bent at about 90°, the exemplary harmonic winch actuator is configured with a high winch ratio to provide higher torque at lower speeds, such as when a patient is moving from a sit to a standard position or is climbing stairs. Conversely, when a patient's leg is bent less than 30°, the actuator provides a

lower winch ratio with less torque and more speed, such as when a patient is walking fast.

FIG. 10B is a graph similar to that of FIG. 10A, but the relationship of torque, effective ratio and number of spool turns is shown as a function of actuator stroke rather than knee or joint angle. Graph line 1030 shows the number of spool turns made from the beginning of the stroke. Graph line 1040 shows the effective winch ratio over the course of the actuator stroke. Graph line 1040 shows that near the beginning of the actuator stroke (which corresponds to a high joint angle in FIG. 10A), the exemplary actuator provides a high reduction ratio and high torque. Conversely, near the end of the stroke (which corresponds to a low joint angle in FIG. 10A), the actuator provides a low reduction ratio and low torque, which allows for higher speed.

FIG. 11A is a graph similar to that shown in FIG. 10A, but for an orthosis having a bell crank type linkage (such as shown in FIG. 8D) instead of a fixed radius linkage. Graph line 1110 shows the relationship between the number of spool turns as a function of joint angle. Graph line 1120 shows the relationship between the winch ratio as a function of joint angle. Both graph lines show the interaction between the linkage and the harmonic winch actuator. As before, this graph shows that the actuator provides a high reduction ratio with high torque when the patient's leg is bent at a high angle such as 90°, and a much lower reduction ratio with lower torque and therefore higher speed when the patient's leg is straight or close to being straight (i.e. at 30° or less), such as during the swing phase of a walking gait.

FIG. 11B is a graph similar to that shown in FIG. 11A, but the relationship of torque, effective ratio and number of spool turns is shown as a function of actuator stroke rather than knee or joint angle. Graph line 1130 shows the number of spool turns from the beginning of the stroke. Graph line 1140 shows the effective winch ratio over the course the actuator stroke.

Referring to FIGS. 12A-12C, details of one option of attaching belt 716 to the spools of the exemplary harmonic winch actuator are shown. As best seen in FIG. 12A, a longitudinally oriented keyway 1210 may be provided along all or a portion of the length of central shaft 1212 that forms the center of previously described first spool 712 and second spool 714. Keyway 1210 is sized to receive a key 1214 along with an end portion of belt 716. In some embodiments, a permanent loop may be constructed at the end of belt 716, as shown in FIG. 12B. To attach the end of belt 716 to shaft 1212, key 1214 is slid into the loop and placed into keyway 1210. In other embodiments, the end of the belt 716 may not include a loop but is wrapped at least 180° around key 1214. After key 1214 is placed into keyway 1210, several wraps of belt 716 are then turned around shaft 1212 to help hold key 1214 in place in keyway 1210. As shown in FIG. 12C, two washers 1216 and or two bearings 1218 may be slid along shaft 1212 to cover each end of key 1214 to further lock the key in place. In other embodiments (not shown), the cross-section of the shaft keyway 1210 may be narrower at its outer opening so that it is wide enough only for belt 716 to pass therethrough, but not wide enough to allow key 1214 to exit outwardly from the keyway. In these embodiments, key 1214 and the end portion of belt 716 are slid longitudinally into the keyway during assembly. In each of the above-described embodiments, the ends of belt 716 are securely fastened to the central shaft 1212 of each of the spools so that they do not slip even when high loads are applied to the belt.

Referring to FIGS. 13A and 13B, another embodiment of harmonic winch actuator is shown. In this embodiment,

actuator **1310** includes a motor **724** that drives a pinion gear **1312**. Pinion gear **1312** drives a larger gear **1314** attached to one end of an idler shaft **1316**. At the other end of idler shaft **1316**, another pinion gear **1318** drives a spool gear **1320**. Gears **1312**, **1314**, **1318** and **1320** are sized relative to one another to provide the desired amount of gear reduction between motor **724** and first spool **712**. Second spool **714** is also provided with a spool gear **1320** that meshes with the spool gear **1320** of the first spool **712**, such that first spool **712** drives second spool **714** at the same speed but in an opposite direction through the gears **1320**. In this embodiment, belt **716** wraps around the bottom of first spool **712** and second spool **714** such that first spool **712** serves as a pull spool and second spool **714** serves as a feed spool. A guide roller **1322** may also be provided between second spool **714** and output pulley **718**.

Referring to FIGS. **14A-E**, details of a spool-mounted belt tensioner **1410** are shown. While only first spool **712** is shown, the construction and operation of second spool **714** is a mirror image of that of first spool **712**. In this embodiment, one flange of spool **712** is provided with an outwardly protruding shaft stop **1412**. Spool gear **1320** is similarly provided with an inwardly protruding spool stop **1414**. A torsion spring **1416** may be provided between shaft stop **1412** and spool stop **1414**. In operation, spool gear **1320** only drives spool **712** when spool stop **1414** rotationally engages with shaft stop **1412**. When spool stop **1414** is not engaged with shaft stop **1412**, torsion spring **1416** rotates spool **712** to pull slack out of belt **716**. When force is being applied, belt torque is applied to shaft **1212** through keyway **1210** and key **1214**. If the belt **716** is slack and an external force is applied at **722**, spools **712** and **714** rotate in opposite directions until they encounter the spools stops. At that point, chain or belt **1512** is tight and prevents further movement of the output. Once the belt **716** is not slack, further movement of the output depends on rotation of the different diameters of the winds on the spools. In other words, spools **712** and **714** rotate in opposite directions while applying force, and in the same direction to pull out slack. In this embodiment, each spool-mounted tensioner **1410** is configured to pull in belt slack equivalent to one wrap of the belt **716** around the spool **712**. This embodiment can advantageously have a smaller size due to the elimination of the separate tensioner.

Referring to FIGS. **15A** and **15B**, another embodiment of a harmonic winch actuator **1510** is shown. In this embodiment, actuator **1510** includes a timing belt **1512** to drive first spool **712** and second spool **714** at the same speed and in the same direction. First spool **712** serves as a pull spool while second spool **714** serves as a feed spool. Two fixed-position guide rollers **1514** may be provided between first spool **712** and second spool **714**. A movable-position guide roller **1516** may be provided on a rotating arm **1518** which pivots about the same axis as the second spool **714**. A torsion spring **1520** may be provided on rotating arm **1518** to bias it in a clockwise direction. Tension on belt **716** will bias rotating arm **1518** in a counterclockwise direction towards the position shown in FIG. **15A**. When slack occurs in belt **716** during operation, rotating arm **1518** with movable roller **1516** will rotate clockwise to the various positions shown in phantom line in FIG. **15A** to take up the slack in belt **716** by increasing the length of the belt path. A load cell **1522**, or other force sensor such as a pressure sensitive resistor, may be provided beneath rotating arm **1518** to measure the tension in belt **716** when there is no slack in the belt.

Referring to FIGS. **16A** and **16B**, another embodiment of a harmonic winch actuator **1610** is shown. The harmonic

winch actuator **1610** is similar to the winch actuator **710** of FIGS. **7A-7B** with a few differences. In this embodiment, the motor **724** drives a pinion gear **1626**, which in turn drives an intermediate gear **1628**. The intermediate gear is coupled to a sprocket **1630**, which in turn drives a belt or chain **736** (shown as a chain in FIG. **16A** and a belt in FIG. **16B**). Rotation of the belt or chain **736** then causes the pull spool **712** to rotate through a sprocket **1638**. The winch actuator **1610** thus eliminates the gearhead of FIG. **7A**, which can provide a wider range of gear ratios, but can also be more expensive than the coupling gears of system **1610**.

Another embodiment of a harmonic winch actuator is shown in FIGS. **17A** and **17B**. This embodiment is similar to the winch actuator **710** of FIGS. **7A** and **7B**, but the belt tensioner **1738** includes a standard torsion spring **1716** instead of a spiral torsion spring. Further, in contrast to winch actuator **710**, in this embodiment, the spring **1738** is on the same side of the housing **720** as the motor encoder **1642a** while the tensioner encoder **1642b** is on the opposite side of the housing **720** as the spring **1716**. Further, actuator **1710** includes a first chain **1636** (coupling the gearhead pinion **726** to the pull spool **712**) and a second chain **1696** (coupling the pull spool **712** to the feed spool **714**) on opposite sides of the housing **720**. Finally, an additional tensioner **1695** is coupled with the chain **1696**. Coupled with the tensioner **1695** are a chain tensioner spring **1696**, a chain tensioner pivot shaft **1697**, and a chain tensioner sprocket shaft **1698**. The tensioner **1695** can advantageously allow for the relaxation of the required tolerances in placement of the sprockets and allows for stretching of the chain **1696** over time.

The actuator **12** (such as the winch actuator described herein) can be coupled to an orthosis to provide the force needed to assist or resist the leg muscle(s). Although it is intended to be relatively small in size, the actuator **12** may be located on the lateral side to avoid interference with the other leg. The actuator **12** may also be located on an anterior region to allow a single orthotic device to be used on either the right or left leg of a patient. The actuator **12** may be coupled to both the upper and lower portions **16**, **14** of the structural frame to provide assistance and/or resistance with leg extension and/or flexion. If the center of rotation of the actuator is located a distance away from the joint, a variety of coupling mechanisms can be used to couple the actuator to a portion of the orthosis on the other side of the joint. The coupling mechanism can be constructed using belts, gears, chains or linkages as is known in the art. These couplings can optionally change the ratio of actuator rotation to joint rotation.

In the above-described embodiments, the exemplary harmonic winch actuators described are described as driving an orthosis in only one direction: extension of the joint. In other embodiments (not shown), the actuator may be configured to drive the joint in another direction, such as flexion of the joint by coupling between the inside parts of the hinge or by using pulleys to reverse the motion and push on a rigid linkage to force flexion. In some embodiments, more than one harmonic winch actuator may be provided on the orthosis for driving it in more than one direction, with one coupling the inside and another coupling the outside of the joint, or with one pushing and the other pulling on the linkage. In some embodiments, the orthosis may be driven in one direction by the harmonic winch actuator and driven in the opposite direction by the patient, gravity, a biasing spring, or some other form of actuator.

While the actuator and orthosis are described above as being used primarily with the knee, application to other

21

joints is possible. For instance, a device to aid in wrist movement may have elastic bands coupling a small actuator to the hand and wrist. Joints with more than one degree of freedom may have a single device to assist/resist the primary movement direction, or may have multiple actuators for different degrees of freedom. Other potential candidates for assistance include the ankle, hip, elbow, shoulder and neck.

The above described orthosis, components and methods provide a light weight active muscle assistance system. Although the systems have been described in considerable detail with reference to certain embodiments thereof, other versions are possible. For example, any feature disclosed in connection with any particular embodiment can be combined with any other feature disclosed in any other embodiment. Therefore, the spirit and scope of the appended claims should not be limited to the description of the exemplary versions contained herein.

What is claimed is:

1. An active assistance orthosis comprising:
 - a first portion configured to attach to a patient on one side of a joint;
 - a second portion configured to attach to the patient on an opposite side of the joint; and
 - an actuator configured to apply a force between the first and the second portions of the orthosis, the actuator comprising:
 - a first spool rotatably mounted to the first portion;
 - a second spool rotatably mounted to the first portion;
 - an output pulley mounted to the second portion; and
 - a belt having a first end wrapped around the first spool, a second end wrapped around the second spool, and a mid-portion wrapped around the output pulley,
 wherein the actuator is configured to rotate the first spool and the second spool, the rotation of the first spool pulling the belt a given length and the rotation of the second spool feeding the belt less than the given length so as to pull the output pulley towards the first portion, wherein pulling the output pulley towards the first portion pulls at least part of the second portion towards at least part of the first portion.
2. The orthosis of claim 1, wherein the actuator further comprises a belt tensioner configured to take up slack in the belt.
3. The orthosis of claim 2, wherein the belt tensioner comprises a rotatable disk separate from the first spool, the second spool and the output pulley.
4. The orthosis of claim 3, wherein the rotatable disk comprises at least one moving roller configured to interact with at least one fixed roller to increase a belt path length.
5. The orthosis of claim 3, wherein the belt tensioner comprises a rotational position sensor coupled to the rotatable disk, and wherein the sensor is configured to communicate with a controller to indicate a belt tension when there is no slack in the belt.
6. The orthosis of claim 1, further comprising a hinge coupling the first portion to the second portion, and wherein pulling at least part of the second portion towards at least part of the first portion comprises rotating the first portion relative to the second portion about the hinge.
7. The orthosis of claim 6, wherein the actuator is configured to provide a winch ratio between a rate of first spool rotation and a rate of orthosis hinge rotation, and wherein the winch ratio is higher when the orthosis is bent than when it is straight.
8. The orthosis of claim 6, wherein the actuator is configured to provide a first winch ratio when the orthosis is

22

positioned at about a 90° angle and a second winch ratio when the orthosis is positioned at about a 0° angle, and wherein the first winch ratio is more than twice the second winch ratio.

9. The orthosis of claim 6, wherein the actuator is configured to apply a lower torque and higher speed as a hinge angle between the first portion and the second portion decreases.

10. The orthosis of claim 1, further comprising a polycentric hinge coupling the first portion to the second portion.

11. The orthosis of claim 10, further comprising a bell crank linkage coupling the first portion to the second portion, wherein the output pulley is located on the bell crank linkage.

12. The orthosis of claim 1, wherein rotating the first spool and the second spool to pull at least part of the second portion towards at least part of the first portion comprises rotating the first spool and the second spool in a first direction.

13. The orthosis of claim 12, wherein the actuator is further configured to rotate the first spool and the second spool in a second direction to allow the output pulley to move away from the first portion so as to allow at least part of the second portion to move away from the at least part of the first portion.

14. The orthosis of claim 1, wherein the second spool is configured to feed the belt less than the given length pulled by the first spool due to a diameter of belt turns on the first spool exceeding a diameter of belt turns on the second spool.

15. The orthosis of claim 1, wherein the first spool and the second spool are configured to rotate at a same speed.

16. The orthosis of claim 1, wherein the first spool and the second spool are configured to rotate in a same direction.

17. The orthosis of claim 1, wherein the first spool and the second spool are configured to rotate in opposite directions.

18. The orthosis of claim 1, wherein the belt has a thickness no greater than about 0.005 inches.

19. The orthosis of claim 1, further comprising:

- a motor configured to drive rotation of the first spool and the second spool;
- a drive sprocket connected to the motor; and
- a driven sprocket connected to the first spool, the drive sprocket and the driven sprocket connected by a second belt, the driven sprocket having a larger diameter than the drive sprocket.

20. The orthosis of claim 1, wherein the first portion is configured to attach above the patient's knee and the second portion is configured to attach below the patient's knee.

21. The orthosis of claim 1, further comprising a rotational position sensor coupled to the actuator, wherein the rotational position sensor is configured to communicate with a controller to indicate a position of the first portion relative to the second portion.

22. The orthosis of claim 1, further comprising a belt tensioner, a tensioner position sensor, a spool rotation counter, and a controller, wherein a rotational position of the first portion relative to the second portion is determined by the controller based on the spool rotation counter and belt tensioner position.

23. A harmonic winch, comprising:

- a first spool rotatably mounted to a first housing;
- a second spool rotatably mounted to the first housing;
- an output pulley mounted to a second housing;
- a belt having a first end wrapped around the first spool, a second end wrapped around the second spool, and a mid-portion wrapped around the output pulley; and

23

a motor configured to rotate the first spool and the second spool, the rotation of the first spool pulling the belt a given length and the rotation of the second spool feeding the belt less than the given length so as to pull the output pulley and the second housing towards the first housing.

24. The harmonic winch of claim **23**, wherein the actuator further comprises a belt tensioner configured to take up slack in the belt.

25. The harmonic winch of claim **24**, wherein the belt tensioner comprises a rotatable disk separate from the first spool, the second spool and the output pulley.

26. The harmonic winch of claim **25**, wherein the rotatable disk comprises at least one moving roller configured to interact with at least one fixed roller to increase a belt path length.

27. The harmonic winch of claim **25**, wherein the belt tensioner comprises a rotational position sensor coupled to the rotatable disk, and wherein the sensor is configured to communicate with a controller to indicate a belt tension when there is no slack in the belt.

28. The harmonic winch of claim **23**, wherein the second spool is configured to feed the belt less than the given length pulled by the first spool due to a diameter of belt turns on the first spool exceeding a diameter of belt turns on the second spool.

29. The harmonic winch of claim **23**, wherein the first spool and the second spool are configured to rotate at a same speed.

30. The harmonic winch of claim **23**, wherein the first spool and the second spool are configured to rotate in a same direction.

31. The harmonic winch of claim **23**, wherein the first spool and the second spool are configured to rotate in opposite directions.

32. The harmonic winch of claim **23**, wherein the belt has a thickness no greater than about 0.005 inches.

33. The harmonic winch of claim **23**, further comprising: a motor configured to drive rotation of the first spool and the second spool;

a drive sprocket connected to the motor; and

24

a driven sprocket connected to the first spool, the drive sprocket and the driven sprocket connected by a second belt, the driven sprocket having a larger diameter than the drive sprocket.

34. A method of assisting movement of a patient, comprising:

attaching a first portion of an orthosis to a patient on one side of a joint;

attaching a second portion of the orthosis to the patient on an opposite side of the joint;

detecting a residual intention of the patient to move the joint; and

assisting the patient with the intended movement by applying an assistive force to the patient with an actuator, the actuator comprising:

a first spool rotatably mounted to the first portion;

a second spool also rotatably mounted to the first portion;

an output pulley mounted to the second portion; and

a belt having a first end wrapped around the first spool, a second end wrapped around the second spool, and a mid-portion wrapped around the output pulley.

35. The method of claim **34**, wherein the assisting step comprises rotating the first spool to pull the belt a given length and rotating the second spool to feed the belt less than the given length such that the output pulley on the second portion is pulled towards the first portion of the orthosis.

36. The method of claim **34**, wherein the attaching a first portion step comprises attaching the first portion of the orthosis around a thigh of the patient, and the attaching a second portion step comprises attaching the second portion around a calf of the patient.

37. The method of claim **34**, wherein the attaching a first portion step comprises attaching the first portion of the orthosis around an upper arm of the patient, and the attaching a second portion step comprises attaching the second portion around a lower arm of the patient.

* * * * *