



US009893768B2

(12) **United States Patent**
Leabman et al.

(10) **Patent No.:** **US 9,893,768 B2**
(45) **Date of Patent:** **Feb. 13, 2018**

(54) **METHODOLOGY FOR MULTIPLE
POCKET-FORMING**

- (71) Applicant: **ENERGOUS CORPORATION**, San Jose, CA (US)
- (72) Inventors: **Michael A. Leabman**, San Ramon, CA (US); **Gregory Scott Brewer**, Livermore, CA (US)
- (73) Assignee: **Energous Corporation**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 427 days.

(21) Appl. No.: **14/583,640**

(22) Filed: **Dec. 27, 2014**

(65) **Prior Publication Data**

US 2016/0099755 A1 Apr. 7, 2016

Related U.S. Application Data

(63) Continuation-in-part of application No. 13/891,430, filed on May 10, 2013, now abandoned, and a (Continued)

(51) **Int. Cl.**
H02J 5/00 (2016.01)
H04B 5/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04B 5/0037** (2013.01); **H02J 7/025** (2013.01); **H02J 17/00** (2013.01); **H02J 50/23** (2016.02); **H02J 50/40** (2016.02)

(58) **Field of Classification Search**
USPC 307/104
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

787,412 A 4/1905 Tesla
3,434,678 A 3/1969 Brown et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 203826555 U 9/2014
CN 104090265 A 10/2014
(Continued)

OTHER PUBLICATIONS

Zhai, Huiqing, "A practical wireless charging system based on ultra-wide band Retro-Reflective beam forming" 2010 IEEE, Antennas and Propagation Society International Symposium, Toronto, CN, 2010, pp. 1-4.*

(Continued)

Primary Examiner — Rexford Barnie


Assistant Examiner — Xuan Ly

(74) *Attorney, Agent, or Firm* — Morgan, Lewis & Bockius LLP

(57) **ABSTRACT**

The embodiments described herein include a transmitter that transmits a power transmission signal (e.g., radio frequency (RF) signal waves) to create a three-dimensional pocket of energy. At least one receiver can be connected to or integrated into electronic devices and receive power from the pocket of energy. The transmitter can locate the at least one receiver in a three-dimensional space using a communication medium (e.g., Bluetooth® technology). The transmitter generates a waveform to create a pocket of energy around each of the at least one receiver. The transmitter uses an algorithm to direct, focus, and control the waveform in three dimensions. The receiver can convert the transmission signals (e.g., RF signals) into electricity for powering an electronic device. Accordingly, the embodiments for wireless power transmission can allow powering and charging a plurality of electrical devices without wires.

26 Claims, 23 Drawing Sheets



Related U.S. Application Data

continuation-in-part of application No. 13/925,469, filed on Jun. 24, 2013, and a continuation-in-part of application No. 13/946,082, filed on Jul. 19, 2013, and a continuation-in-part of application No. 13/891,399, filed on May 10, 2013, and a continuation-in-part of application No. 13/891,445, filed on May 10, 2013, and a continuation-in-part of application No. 13/926,020, filed on Jun. 25, 2013, now Pat. No. 9,124,125.

(60) Provisional application No. 61/720,798, filed on Oct. 31, 2012, provisional application No. 61/668,799, filed on Jul. 6, 2012, provisional application No. 61/677,706, filed on Jul. 31, 2012.

(51) **Int. Cl.**

H02J 7/02 (2016.01)
H02J 17/00 (2006.01)
H02J 50/40 (2016.01)
H02J 50/23 (2016.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

3,696,384 A 10/1972 Lester
 3,754,269 A 8/1973 Clavin
 4,101,895 A 7/1978 Jones, Jr.
 4,360,741 A 11/1982 Fitzsimmons et al.
 4,944,036 A 7/1990 Hyatt
 4,995,010 A 2/1991 Knight
 5,200,759 A 4/1993 McGinnis
 5,211,471 A 5/1993 Rohrs
 5,548,292 A 8/1996 Hirshfield et al.
 5,556,749 A 9/1996 Mitsuhashi et al.
 5,568,088 A 10/1996 Dent et al.
 5,646,633 A 7/1997 Dahlberg
 5,697,063 A 12/1997 Kishigami et al.
 5,712,642 A 1/1998 Hulderman
 5,936,527 A 8/1999 Isaacman
 5,982,139 A 11/1999 Parise
 6,046,708 A 4/2000 MacDonald, Jr. et al.
 6,127,799 A 10/2000 Krishnan
 6,127,942 A 10/2000 Welle
 6,163,296 A 12/2000 Lier et al.
 6,289,237 B1 9/2001 Mickle et al.
 6,329,908 B1 12/2001 Frecska
 6,421,235 B2 7/2002 Ditzik
 6,437,685 B2 8/2002 Hanaki
 6,456,253 B1 9/2002 Rummeli et al.
 6,476,795 B1 11/2002 Derocher et al.
 6,501,414 B2 12/2002 Arndt et al.
 6,583,723 B2 6/2003 Watanabe et al.
 6,597,897 B2 7/2003 Tang
 6,615,074 B2 9/2003 Mickle et al.
 6,664,920 B1 12/2003 Mott et al.
 6,798,716 B1 9/2004 Charych
 6,803,744 B1 10/2004 Sabo
 6,853,197 B1 2/2005 McFarland
 6,856,291 B2 2/2005 Mickle et al.
 6,911,945 B2 6/2005 Korva
 6,960,968 B2 11/2005 Odendaal et al.
 6,967,462 B1 11/2005 Landis
 6,988,026 B2 1/2006 Breed et al.
 7,003,350 B2 2/2006 Denker et al.
 7,027,311 B2 4/2006 Vanderelli et al.
 7,068,234 B2 6/2006 Sievenpiper
 7,068,991 B2 6/2006 Parise
 7,183,748 B1 2/2007 Unno et al.
 7,191,013 B1 3/2007 Miranda et al.
 7,196,663 B2 3/2007 Bolzer et al.
 7,205,749 B2 4/2007 Hagen et al.
 7,222,356 B1 5/2007 Yonezawa et al.

7,274,334 B2 9/2007 o’Riordan et al.
 7,274,336 B2 9/2007 Carson
 7,351,975 B2 4/2008 Brady et al.
 7,359,730 B2 4/2008 Dennis et al.
 7,392,068 B2 6/2008 Dayan
 7,403,803 B2 7/2008 Mickle et al.
 7,451,839 B2 11/2008 Perlman
 7,463,201 B2 12/2008 Chiang et al.
 7,471,247 B2 12/2008 Saily
 7,535,195 B1 5/2009 Horovitz et al.
 7,614,556 B2 11/2009 Overhultz et al.
 7,639,994 B2 12/2009 Greene et al.
 7,643,312 B2 1/2010 Vanderelli et al.
 7,652,577 B1 1/2010 Madhow et al.
 7,702,771 B2 4/2010 Ewing et al.
 7,786,419 B2 8/2010 Hyde et al.
 7,812,771 B2 10/2010 Greene et al.
 7,830,312 B2 11/2010 Choudhury et al.
 7,844,306 B2 11/2010 Shearer et al.
 7,868,482 B2 1/2011 Greene et al.
 7,898,105 B2 3/2011 Greene et al.
 7,904,117 B2 3/2011 Doan et al.
 7,911,386 B1 3/2011 Ito et al.
 7,925,308 B2 4/2011 Greene et al.
 8,055,003 B2 11/2011 Mittleman et al.
 8,070,595 B2 12/2011 Alderucci et al.
 8,072,380 B2 12/2011 Crouch
 8,092,301 B2 1/2012 Alderucci et al.
 8,099,140 B2 1/2012 Arai
 8,115,448 B2 2/2012 John
 8,159,090 B2 4/2012 Greene et al.
 8,159,364 B2 4/2012 Zeine
 8,180,286 B2 5/2012 Yamasuge
 8,228,194 B2 7/2012 Mickle
 8,264,101 B2 9/2012 Hyde et al.
 8,264,291 B2 9/2012 Morita
 8,276,325 B2 10/2012 Clifton et al.
 8,278,784 B2 10/2012 Cook et al.
 8,284,101 B2 10/2012 Fusco
 8,310,201 B1 11/2012 Wright
 8,362,745 B2 1/2013 Tinaphong
 8,380,255 B2 2/2013 Shearer et al.
 8,410,953 B2 4/2013 Zeine
 8,411,963 B2 4/2013 Luff
 8,432,062 B2 4/2013 Greene et al.
 8,432,071 B2 4/2013 Huang et al.
 8,446,248 B2 5/2013 Zeine
 8,447,234 B2 5/2013 Cook et al.
 8,451,189 B1 5/2013 Fluhler
 8,452,235 B2 5/2013 Kirby et al.
 8,457,656 B2 6/2013 Perkins et al.
 8,461,817 B2 6/2013 Martin et al.
 8,467,733 B2 6/2013 Leabman
 8,497,658 B2 7/2013 Von Novak et al.
 8,552,597 B2 8/2013 Song et al.
 8,558,661 B2 10/2013 Zeine
 8,560,026 B2 10/2013 Chanterac
 8,604,746 B2 12/2013 Lee
 8,614,643 B2 12/2013 Leabman
 8,621,245 B2 12/2013 Shearer et al.
 8,626,249 B2 1/2014 Kuusilinna et al.
 8,629,576 B2 1/2014 Levine
 8,653,966 B2 2/2014 Rao et al.
 8,674,551 B2 3/2014 Low et al.
 8,686,685 B2 4/2014 Moshfeghi
 8,712,355 B2 4/2014 Black et al.
 8,712,485 B2 4/2014 Tam
 8,718,773 B2 5/2014 Wills et al.
 8,729,737 B2 5/2014 Schatz et al.
 8,736,228 B1 5/2014 Freed et al.
 8,760,113 B2 6/2014 Keating
 8,770,482 B2 7/2014 Ackermann et al.
 8,772,960 B2 7/2014 Yoshida
 8,823,319 B2 9/2014 Von Novak, III et al.
 8,854,176 B2 10/2014 Zeine
 8,860,364 B2 10/2014 Low et al.
 8,897,770 B1 11/2014 Frolov et al.
 8,923,189 B2 12/2014 Leabman
 8,928,544 B2 1/2015 Massie et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,937,408 B2	1/2015	Ganem et al.	2004/0142733 A1	7/2004	Parise
8,946,940 B2	2/2015	Kim et al.	2004/0145342 A1	7/2004	Lyon
8,963,486 B2	2/2015	Kirby et al.	2004/0196190 A1	10/2004	Mendolia et al.
8,970,070 B2	3/2015	Sada et al.	2004/0207559 A1	10/2004	Milosavljevic
8,989,053 B1	3/2015	Skaaksrud et al.	2004/0218759 A1	11/2004	Yacobi
9,000,616 B2	4/2015	Greene et al.	2004/0259604 A1	12/2004	Mickle et al.
9,001,622 B2	4/2015	Perry	2004/0263124 A1	12/2004	Wieck et al.
9,006,934 B2	4/2015	Kozakai et al.	2005/0007276 A1	1/2005	Barrick et al.
9,021,277 B2	4/2015	Shearer et al.	2005/0030118 A1	2/2005	Wang
9,030,161 B2	5/2015	Lu et al.	2005/0046584 A1	3/2005	Breed
9,059,598 B2	6/2015	Kang et al.	2005/0055316 A1	3/2005	Williams
9,059,599 B2	6/2015	Won et al.	2005/0093766 A1	5/2005	Turner
9,077,188 B2	7/2015	Moshfeghi	2005/0116683 A1	6/2005	Cheng
9,088,216 B2	7/2015	Garrity et al.	2005/0117660 A1	6/2005	Vialle et al.
9,124,125 B2	9/2015	Leabman et al.	2005/0171411 A1	8/2005	KenKnight
9,130,397 B2	9/2015	Leabman et al.	2005/0198673 A1	9/2005	Kit et al.
9,130,602 B2	9/2015	Cook	2005/0227619 A1	10/2005	Lec et al.
9,142,998 B2	9/2015	Yu et al.	2005/0232469 A1	10/2005	Schofield
9,143,000 B2	9/2015	Leabman et al.	2005/0282591 A1	12/2005	Shaff
9,143,010 B2	9/2015	Urano	2006/0013335 A1	1/2006	Leabman
9,178,389 B2	11/2015	Hwang	2006/0019712 A1	1/2006	Choi
9,225,196 B2	12/2015	Huang et al.	2006/0030279 A1	2/2006	Leabman et al.
9,242,411 B2	1/2016	Kritchman et al.	2006/0092079 A1	5/2006	de Rochemont
9,244,500 B2	1/2016	Cain et al.	2006/0094425 A1	5/2006	Mickle et al.
9,252,628 B2	2/2016	Leabman et al.	2006/0113955 A1	6/2006	Nunally
9,270,344 B2	2/2016	Rosenberg	2006/0119532 A1	6/2006	Yun et al.
9,282,582 B1	3/2016	Dunsbergen et al.	2006/0136004 A1	6/2006	Cowan et al.
9,294,840 B1	3/2016	Anderson et al.	2006/0160517 A1	7/2006	Yoon
9,297,896 B1	3/2016	Andrews	2006/0183473 A1	8/2006	Ukon
9,318,898 B2	4/2016	John	2006/0190063 A1	8/2006	Kanzius
9,368,020 B1	6/2016	Bell et al.	2006/0192913 A1	8/2006	Shutou et al.
9,401,977 B1	7/2016	Gaw	2006/0199620 A1	9/2006	Greene et al.
9,438,045 B1	9/2016	Leabman	2006/0238365 A1	10/2006	Vecchione et al.
9,438,046 B1	9/2016	Leabman	2006/0266564 A1	11/2006	Perlman et al.
9,444,283 B2	9/2016	Son et al.	2006/0266917 A1	11/2006	Baldis et al.
9,450,449 B1	9/2016	Leabman et al.	2006/0278706 A1	12/2006	Hatakayama et al.
9,461,502 B2	10/2016	Lee et al.	2006/0284593 A1	12/2006	Nagy et al.
9,520,725 B2	12/2016	Masaoka et al.	2006/0287094 A1	12/2006	Mahaffey et al.
9,520,748 B2	12/2016	Hyde et al.	2007/0007821 A1	1/2007	Rossetti
9,522,270 B2	12/2016	Perryman et al.	2007/0019693 A1	1/2007	Graham
9,537,354 B2	1/2017	Bell et al.	2007/0021140 A1	1/2007	Keyes
9,537,357 B2	1/2017	Leabman	2007/0060185 A1	3/2007	Simon et al.
9,537,358 B2	1/2017	Leabman	2007/0070490 A1	3/2007	Tsunoda et al.
9,538,382 B2	1/2017	Bell et al.	2007/0093269 A1	4/2007	Leabman et al.
9,544,640 B2	1/2017	Lau	2007/0097653 A1	5/2007	Gilliland et al.
9,559,553 B2	1/2017	Bac	2007/0103110 A1	5/2007	Sagoo
9,564,773 B2	2/2017	Pogorelik et al.	2007/0106894 A1	5/2007	Zhang
9,571,974 B2	2/2017	Choi et al.	2007/0109121 A1	5/2007	Cohen
9,590,444 B2	3/2017	Walley	2007/0139000 A1	6/2007	Kozuma
9,620,996 B2	4/2017	Zeine	2007/0149162 A1	6/2007	Greene et al.
2002/0001307 A1	1/2002	Nguyen et al.	2007/0173196 A1	7/2007	Gallic
2002/0028655 A1	3/2002	Roscner et al.	2007/0173214 A1	7/2007	Mickle et al.
2002/0034958 A1	3/2002	Oberschmidt et al.	2007/0178857 A1	8/2007	Greene et al.
2002/0054330 A1	5/2002	Jinbo et al.	2007/0178945 A1	8/2007	Cook et al.
2002/0065052 A1	5/2002	Pande et al.	2007/0182367 A1	8/2007	Partovi
2002/0072784 A1	6/2002	Sheppard et al.	2007/0191074 A1	8/2007	Harrist et al.
2002/0095980 A1	7/2002	Breed et al.	2007/0191075 A1	8/2007	Greene et al.
2002/0103447 A1	8/2002	Terry	2007/0197281 A1	8/2007	Stronach
2002/0133592 A1	9/2002	Matsuda	2007/0210960 A1	9/2007	Rofougaran et al.
2002/0172223 A1	11/2002	Stilp	2007/0222681 A1	9/2007	Greene et al.
2003/0005759 A1	1/2003	Breed et al.	2007/0257634 A1	11/2007	Leschin et al.
2003/0058187 A1	3/2003	Billiet et al.	2007/0273486 A1	11/2007	Shiotsu
2003/0076274 A1	4/2003	Phelan et al.	2007/0298846 A1	12/2007	Greene et al.
2003/0179152 A1	9/2003	Watada et al.	2008/0014897 A1	1/2008	Cook et al.
2003/0179573 A1	9/2003	Chun	2008/0048917 A1	2/2008	Achour et al.
2003/0192053 A1	10/2003	Sheppard et al.	2008/0062062 A1	3/2008	Borau et al.
2004/0019624 A1	1/2004	Sukcgawa	2008/0062255 A1	3/2008	Gal
2004/0020100 A1	2/2004	O'Brian et al.	2008/0067874 A1	3/2008	Tseng
2004/0036657 A1	2/2004	Forster et al.	2008/0074324 A1	3/2008	Puzella et al.
2004/0066251 A1	4/2004	Eleftheriades et al.	2008/0089277 A1	4/2008	Aledander et al.
2004/0107641 A1	6/2004	Walton et al.	2008/0113816 A1	5/2008	Mahaffey et al.
2004/0113543 A1	6/2004	Daniels	2008/0122297 A1	5/2008	Arai
2004/0119675 A1	6/2004	Washio et al.	2008/0123383 A1	5/2008	Shionoiri
2004/0130425 A1	7/2004	Dayan et al.	2008/0129536 A1	6/2008	Randall et al.
2004/0130442 A1	7/2004	Breed	2008/0169910 A1	7/2008	Greene et al.
			2008/0197802 A1	8/2008	Onishi
			2008/0204342 A1	8/2008	Kharadly
			2008/0204350 A1	8/2008	Tam et al.
			2008/0210762 A1	9/2008	Osada et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0211458 A1	9/2008	Lawther et al.	2010/0181961 A1	7/2010	Novak et al.
2008/0248758 A1	10/2008	Schedelbeck et al.	2010/0181964 A1	7/2010	Huggins et al.
2008/0248846 A1	10/2008	Stronach et al.	2010/0194206 A1	8/2010	Burdo et al.
2008/0278378 A1	11/2008	Chang et al.	2010/0201189 A1	8/2010	Kirby et al.
2008/0309452 A1	12/2008	Zeine	2010/0201201 A1	8/2010	Mobarhan et al.
2009/0002493 A1	1/2009	Kates	2010/0201314 A1	8/2010	Toncich et al.
2009/0019183 A1	1/2009	Wu et al.	2010/0207572 A1	8/2010	Kirby et al.
2009/0036065 A1	2/2009	Siu	2010/0210233 A1	8/2010	Cook et al.
2009/0047998 A1	2/2009	Alberth, Jr.	2010/0214177 A1	8/2010	Parsche
2009/0058354 A1	3/2009	Harrison	2010/0225270 A1	9/2010	Jacobs et al.
2009/0058361 A1	3/2009	John	2010/0227570 A1	9/2010	Hendin
2009/0067208 A1	3/2009	Martin et al.	2010/0231470 A1	9/2010	Lee et al.
2009/0096412 A1	4/2009	Huang	2010/0237709 A1	9/2010	Hall et al.
2009/0096413 A1	4/2009	Partovi	2010/0244576 A1	9/2010	Hillan et al.
2009/0102292 A1	4/2009	Cook et al.	2010/0256831 A1	10/2010	Abramo et al.
2009/0102296 A1	4/2009	Greene et al.	2010/0259110 A1	10/2010	Kurs et al.
2009/0108679 A1	4/2009	Porwal	2010/0259447 A1	10/2010	Crouch
2009/0122847 A1	5/2009	Nysen et al.	2010/0264747 A1	10/2010	Hall et al.
2009/0128262 A1	5/2009	Lee et al.	2010/0277003 A1	11/2010	Von Novak et al.
2009/0157911 A1	6/2009	Aihara	2010/0277121 A1	11/2010	Hall et al.
2009/0200985 A1	8/2009	Zane et al.	2010/0279606 A1	11/2010	Hillan et al.
2009/0206791 A1	8/2009	Jung	2010/0289341 A1	11/2010	Ozaki et al.
2009/0207092 A1	8/2009	Nysen et al.	2010/0295372 A1	11/2010	Hyde et al.
2009/0218884 A1	9/2009	Soar	2010/0308767 A1	12/2010	Rofougaran et al.
2009/0218891 A1	9/2009	McCollough	2010/0309079 A1	12/2010	Rofougaran et al.
2009/0219903 A1	9/2009	Alamouti et al.	2010/0309088 A1	12/2010	Hyvonen et al.
2009/0243397 A1	10/2009	Cook et al.	2010/0315045 A1*	12/2010	Zeine H02J 7/025
2009/0264069 A1	10/2009	Yamasuge	2010/0316163 A1	12/2010	Forenza et al.
2009/0280866 A1	11/2009	Lo et al.	2010/0327766 A1	12/2010	Recker et al.
2009/0281678 A1	11/2009	Wakamatsu	2010/0328044 A1	12/2010	Waffenschmidt et al.
2009/0284082 A1	11/2009	Mohammadian	2010/0332401 A1	12/2010	Prahlad et al.
2009/0284083 A1	11/2009	Karalis et al.	2011/0018360 A1	1/2011	Baarman et al.
2009/0284220 A1	11/2009	Toncich et al.	2011/0028114 A1	2/2011	Kerselaers
2009/0284227 A1	11/2009	Mohammadian et al.	2011/0031928 A1	2/2011	Soar
2009/0284325 A1	11/2009	Rossiter et al.	2011/0032149 A1	2/2011	Leabman
2009/0286475 A1	11/2009	Toncich et al.	2011/0032866 A1	2/2011	Leabman
2009/0291634 A1	11/2009	Saarisalo	2011/0034190 A1	2/2011	Leabman
2009/0299175 A1	12/2009	Bernstein et al.	2011/0034191 A1	2/2011	Leabman
2009/0312046 A1	12/2009	Clevenger et al.	2011/0043047 A1	2/2011	Karalis et al.
2009/0315412 A1	12/2009	Yamamoto et al.	2011/0043163 A1	2/2011	Baarman et al.
2009/0322281 A1	12/2009	Kamijo et al.	2011/0043327 A1	2/2011	Baarman et al.
2010/0001683 A1	1/2010	Huang et al.	2011/0050166 A1	3/2011	Cook et al.
2010/0007307 A1	1/2010	Baarman et al.	2011/0055037 A1	3/2011	Hayashigawa et al.
2010/0007569 A1	1/2010	Sim et al.	2011/0056215 A1	3/2011	Ham
2010/0019686 A1	1/2010	Gutierrez, Jr.	2011/0057607 A1	3/2011	Carobolante
2010/0026605 A1	2/2010	Yang et al.	2011/0062788 A1	3/2011	Chen et al.
2010/0027379 A1	2/2010	Saulnier et al.	2011/0074342 A1	3/2011	MacLaughlin
2010/0029383 A1	2/2010	Dai	2011/0074349 A1	3/2011	Ghovanloo
2010/0033021 A1*	2/2010	Bennett H02J 17/00	2011/0074620 A1	3/2011	Wintermantel
		307/104	2011/0078092 A1	3/2011	Kim et al.
2010/0033390 A1	2/2010	Alamouti et al.	2011/0090126 A1	4/2011	Szini et al.
2010/0034238 A1	2/2010	Bennett	2011/0114401 A1	5/2011	Kanno et al.
2010/0041453 A1	2/2010	Grimm, Jr.	2011/0115303 A1	5/2011	Baarman et al.
2010/0044123 A1	2/2010	Perlman et al.	2011/0115432 A1	5/2011	El-Maleh
2010/0054200 A1	3/2010	Tsai	2011/0115605 A1	5/2011	Dimig et al.
2010/0060534 A1	3/2010	Oodachi	2011/0121660 A1	5/2011	Azancot et al.
2010/0075607 A1	3/2010	Hosoya	2011/0122026 A1	5/2011	DeLaquil et al.
2010/0079005 A1	4/2010	Hyde et al.	2011/0127845 A1	6/2011	Walley et al.
2010/0082193 A1	4/2010	Chiappetta	2011/0127952 A1	6/2011	Walley et al.
2010/0087227 A1	4/2010	Francos et al.	2011/0133655 A1	6/2011	Recker et al.
2010/0090524 A1	4/2010	Obayashi	2011/0133691 A1	6/2011	Hautanen
2010/0090656 A1	4/2010	Shearer et al.	2011/0148578 A1	6/2011	Aloi et al.
2010/0109443 A1	5/2010	Cook et al.	2011/0151789 A1	6/2011	Viglione et al.
2010/0119234 A1	5/2010	Suematsu et al.	2011/0154429 A1	6/2011	Stantchev
2010/0123618 A1	5/2010	Martin et al.	2011/0156494 A1	6/2011	Mashinsky
2010/0123624 A1	5/2010	Miner et al.	2011/0156640 A1	6/2011	Moshfeghi
2010/0127660 A1	5/2010	Cook et al.	2011/0163128 A1	7/2011	Taguchi et al.
2010/0142418 A1	6/2010	Nishioka et al.	2011/0175455 A1	7/2011	Hashiguchi
2010/0142509 A1	6/2010	Zhu et al.	2011/0175461 A1	7/2011	Tinaphong
2010/0151808 A1	6/2010	Toncich et al.	2011/0181120 A1	7/2011	Liu et al.
2010/0156721 A1	6/2010	Alamouti et al.	2011/0182245 A1	7/2011	Malkamaki et al.
2010/0164433 A1	7/2010	Janefalkner et al.	2011/0184842 A1	7/2011	Melen
2010/0171461 A1	7/2010	Baarman et al.	2011/0188207 A1	8/2011	Won et al.
2010/0174629 A1	7/2010	Taylor et al.	2011/0194543 A1	8/2011	Zhao et al.
2010/0176934 A1	7/2010	Chou et al.	2011/0195722 A1	8/2011	Walter et al.
			2011/0199046 A1	8/2011	Tsai et al.
			2011/0215086 A1	9/2011	Yeh
			2011/0217923 A1	9/2011	Ma

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0220634	A1	9/2011	Yeh	2012/0248888	A1	10/2012	Kesler et al.
2011/0221389	A1	9/2011	Won et al.	2012/0248891	A1	10/2012	Drennen
2011/0222272	A1	9/2011	Yeh	2012/0249051	A1	10/2012	Son et al.
2011/0243040	A1	10/2011	Khan et al.	2012/0262002	A1	10/2012	Widmer et al.
2011/0243050	A1	10/2011	Yanover	2012/0265272	A1	10/2012	Judkins
2011/0244913	A1	10/2011	Kim et al.	2012/0267900	A1	10/2012	Huffman et al.
2011/0248573	A1	10/2011	Kanno et al.	2012/0268238	A1	10/2012	Park et al.
2011/0248575	A1	10/2011	Kim et al.	2012/0274154	A1	11/2012	Deluca
2011/0249678	A1	10/2011	Bonicatto	2012/0280650	A1	11/2012	Kim et al.
2011/0254503	A1	10/2011	Widmer et al.	2012/0286582	A1	11/2012	Kim et al.
2011/0259953	A1	10/2011	Baarman et al.	2012/0292993	A1	11/2012	Mettler et al.
2011/0273977	A1	11/2011	Shapira et al.	2012/0293021	A1	11/2012	Teggatz et al.
2011/0278941	A1	11/2011	Krishna et al.	2012/0293119	A1	11/2012	Park et al.
2011/0279226	A1	11/2011	Chen et al.	2012/0299389	A1	11/2012	Lee et al.
2011/0281535	A1	11/2011	Low et al.	2012/0299540	A1	11/2012	Perry
2011/0282415	A1	11/2011	Eckhoff et al.	2012/0299541	A1	11/2012	Perry
2011/0285213	A1	11/2011	Kowalewski	2012/0299542	A1	11/2012	Perry
2011/0286374	A1	11/2011	Shin et al.	2012/0300588	A1	11/2012	Perry
2011/0291489	A1	12/2011	Tsai et al.	2012/0300592	A1	11/2012	Perry
2011/0302078	A1	12/2011	Failing	2012/0300593	A1	11/2012	Perry
2011/0304216	A1	12/2011	Baarman	2012/0306705	A1	12/2012	Sakurai et al.
2011/0304437	A1	12/2011	Beeler	2012/0309295	A1	12/2012	Maguire
2012/0013196	A1	1/2012	Kim et al.	2012/0309308	A1	12/2012	Kim et al.
2012/0013198	A1	1/2012	Uramoto et al.	2012/0309332	A1	12/2012	Liao
2012/0013296	A1	1/2012	Heydari et al.	2012/0313449	A1	12/2012	Kurs
2012/0019419	A1	1/2012	Prat et al.	2012/0326660	A1	12/2012	Lu et al.
2012/0043887	A1	2/2012	Mesibov	2013/0002550	A1	1/2013	Zalewski
2012/0051109	A1	3/2012	Kim et al.	2013/0024059	A1	1/2013	Miller et al.
2012/0051294	A1	3/2012	Guillouard	2013/0026981	A1	1/2013	Van Der Lee
2012/0056486	A1	3/2012	Endo et al.	2013/0026982	A1	1/2013	Rothenbaum
2012/0056741	A1	3/2012	Zhu et al.	2013/0032589	A1	2/2013	Chung
2012/0074891	A1	3/2012	Anderson et al.	2013/0033571	A1	2/2013	Steen
2012/0231856	A1	3/2012	Lee et al.	2013/0038124	A1	2/2013	Newdoll et al.
2012/0080957	A1	4/2012	Cooper et al.	2013/0038402	A1	2/2013	Karalis et al.
2012/0086284	A1	4/2012	Capanella et al.	2013/0043738	A1	2/2013	Park et al.
2012/0095617	A1	4/2012	Martin et al.	2013/0049471	A1	2/2013	Olcynik
2012/0098350	A1	4/2012	Campanella et al.	2013/0049475	A1	2/2013	Kim et al.
2012/0098485	A1	4/2012	Kang et al.	2013/0057078	A1	3/2013	Lee
2012/0099675	A1	4/2012	Kitamura et al.	2013/0057205	A1	3/2013	Lee et al.
2012/0103562	A1	5/2012	Clayton	2013/0057210	A1	3/2013	Negaard et al.
2012/0104849	A1	5/2012	Jackson	2013/0057364	A1	3/2013	Kesler et al.
2012/0105252	A1	5/2012	Wang	2013/0063082	A1	3/2013	Lee et al.
2012/0112532	A1	5/2012	Kesler et al.	2013/0063143	A1	3/2013	Adalsteinsson et al.
2012/0119914	A1	5/2012	Uchida	2013/0069444	A1	3/2013	Waffenschmidt et al.
2012/0126743	A1	5/2012	Rivers, Jr.	2013/0077650	A1	3/2013	Traxler et al.
2012/0132647	A1	5/2012	Beverly et al.	2013/0078918	A1	3/2013	Crowley et al.
2012/0133214	A1	5/2012	Yun et al.	2013/0082651	A1	4/2013	Park et al.
2012/0146426	A1	6/2012	Sabo	2013/0082653	A1	4/2013	Lee et al.
2012/0146576	A1	6/2012	Partovi	2013/0083774	A1	4/2013	Son et al.
2012/0146577	A1	6/2012	Tanabe	2013/0088082	A1	4/2013	Kang et al.
2012/0147802	A1	6/2012	Ukita et al.	2013/0088090	A1	4/2013	Wu
2012/0149307	A1	6/2012	Terada et al.	2013/0088192	A1	4/2013	Eaton
2012/0150670	A1	6/2012	Taylor et al.	2013/0088331	A1	4/2013	Cho
2012/0153894	A1	6/2012	Widmer et al.	2013/0093388	A1	4/2013	Partovi
2012/0157019	A1	6/2012	Li	2013/0099389	A1	4/2013	Hong et al.
2012/0161531	A1	6/2012	Kim et al.	2013/0099586	A1	4/2013	Kato
2012/0161544	A1	6/2012	Kashiwagi et al.	2013/0106197	A1	5/2013	Bae et al.
2012/0169276	A1	7/2012	Wang	2013/0107023	A1	5/2013	Tanaka et al.
2012/0169278	A1	7/2012	Choi	2013/0119777	A1	5/2013	Rees
2012/0173418	A1	7/2012	Beardsmore et al.	2013/0119929	A1	5/2013	Partovi
2012/0179004	A1	7/2012	Roesicke et al.	2013/0120217	A1	5/2013	Ueda et al.
2012/0181973	A1	7/2012	Lvden	2013/0132010	A1	5/2013	Winger et al.
2012/0182427	A1	7/2012	Marshall	2013/0134923	A1	5/2013	Smith
2012/0187851	A1	8/2012	Huggins et al.	2013/0137455	A1	5/2013	Xia
2012/0193999	A1	8/2012	Zeine	2013/0141037	A1	6/2013	Jenwatanavet et al.
2012/0201153	A1	8/2012	Bharadia et al.	2013/0148341	A1	6/2013	Williams
2012/0201173	A1	8/2012	Jian et al.	2013/0149975	A1	6/2013	Yu et al.
2012/0206299	A1	8/2012	Valdes-Garcia	2013/0154387	A1	6/2013	Lee et al.
2012/0212072	A1	8/2012	Miyabayashi et al.	2013/0155748	A1	6/2013	Sundstrom
2012/0214536	A1	8/2012	Kim et al.	2013/0157729	A1	6/2013	Tabe
2012/0200399	A1	9/2012	Chae	2013/0169061	A1	7/2013	Microshnichenko et al.
2012/0228956	A1	9/2012	Kamata	2013/0169219	A1	7/2013	Gray
2012/0235636	A1	9/2012	Partovi	2013/0169348	A1	7/2013	Shi
2012/0242283	A1	9/2012	Kim et al.	2013/0171939	A1	7/2013	Tian et al.
2012/0248886	A1	10/2012	Kesler et al.	2013/0178253	A1	7/2013	Karaoguz
				2013/0181881	A1	7/2013	Christie et al.
				2013/0190031	A1	7/2013	Persson et al.
				2013/0193769	A1	8/2013	Mehta et al.
				2013/0197320	A1	8/2013	Albert et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0200064	A1	8/2013	Alexander	2014/0177399	A1	6/2014	Teng et al.
2013/0207477	A1	8/2013	Nam et al.	2014/0184148	A1	7/2014	Van Der Lee et al.
2013/0207604	A1	8/2013	Zeine	2014/0184155	A1	7/2014	Cha
2013/0210357	A1	8/2013	Qin et al.	2014/0184163	A1	7/2014	Das et al.
2013/0221757	A1	8/2013	Cho et al.	2014/0184170	A1	7/2014	Jeong
2013/0234530	A1	9/2013	Miyauchi	2014/0191568	A1	7/2014	Partovi
2013/0234536	A1	9/2013	Chemishkian et al.	2014/0194092	A1	7/2014	Wanstedt et al.
2013/0234658	A1	9/2013	Endo et al.	2014/0194095	A1	7/2014	Wanstedt et al.
2013/0241306	A1	9/2013	Aber et al.	2014/0206384	A1	7/2014	Kim et al.
2013/0241468	A1	9/2013	Moshfeghi	2014/0210281	A1	7/2014	Ito et al.
2013/0241474	A1	9/2013	Moshfeghi	2014/0217955	A1	8/2014	Lin
2013/0249478	A1	9/2013	Hirano	2014/0217967	A1	8/2014	Zeine et al.
2013/0249479	A1	9/2013	Partovi	2014/0225805	A1	8/2014	Pan et al.
2013/0254578	A1	9/2013	Huang et al.	2014/0232320	A1	8/2014	Ento July et al.
2013/0264997	A1	10/2013	Lee et al.	2014/0239733	A1	8/2014	Mach et al.
2013/0268782	A1	10/2013	Tam et al.	2014/0241231	A1	8/2014	Zeine
2013/0270923	A1	10/2013	Cook et al.	2014/0245036	A1	8/2014	Oishi
2013/0278209	A1	10/2013	Von Novak	2014/0246416	A1	9/2014	White
2013/0285477	A1	10/2013	Lo et al.	2014/0247152	A1	9/2014	Proud
2013/0285606	A1	10/2013	Ben-Shalom et al.	2014/0252813	A1	9/2014	Lee et al.
2013/0288600	A1	10/2013	Kuusilinna et al.	2014/0252866	A1	9/2014	Walsh et al.
2013/0293423	A1	11/2013	Moshfeghi	2014/0265725	A1	9/2014	Angle et al.
2013/0310020	A1	11/2013	Kazuhiro	2014/0265727	A1	9/2014	Berte
2013/0311798	A1	11/2013	Sultenfuss	2014/0265943	A1	9/2014	Angle et al.
2013/0328417	A1	12/2013	Takeuchi	2014/0266025	A1	9/2014	Jakubowski
2013/0334883	A1	12/2013	Kim et al.	2014/0273892	A1	9/2014	Nourbakhsh
2013/0339108	A1	12/2013	Ryder et al.	2014/0281655	A1	9/2014	Angle et al.
2013/0343251	A1	12/2013	Zhang	2014/0292090	A1	10/2014	Cordeiro et al.
2014/0001846	A1	1/2014	Mosebrook	2014/0312706	A1	10/2014	Fiorello et al.
2014/0001875	A1	1/2014	Nahidipour	2014/0325218	A1	10/2014	Shimizu et al.
2014/0001876	A1	1/2014	Fujiwara et al.	2014/0327320	A1	11/2014	Muhs et al.
2014/0006017	A1	1/2014	Sen	2014/0327390	A1	11/2014	Park et al.
2014/0008992	A1	1/2014	Leabman	2014/0346860	A1	11/2014	Aubry et al.
2014/0008993	A1	1/2014	Leabman	2014/0354063	A1	12/2014	Leabman et al.
2014/0009108	A1	1/2014	Leabman	2014/0354221	A1	12/2014	Leabman et al.
2014/0009110	A1	1/2014	Lee	2014/0355718	A1	12/2014	Guan et al.
2014/0011531	A1	1/2014	Burstrom et al.	2014/0357309	A1	12/2014	Leabman et al.
2014/0015336	A1	1/2014	Weber et al.	2014/0368048	A1	12/2014	Leabman
2014/0015344	A1	1/2014	Mohamadi	2014/0368161	A1	12/2014	Leabman et al.
2014/0021907	A1	1/2014	Yu et al.	2014/0375253	A1	12/2014	Leabman et al.
2014/0021908	A1	1/2014	McCool	2014/0375255	A1	12/2014	Leabman et al.
2014/0035524	A1	2/2014	Zeine	2014/0375258	A1	12/2014	Arkhipenkov
2014/0035526	A1	2/2014	Tripathi et al.	2014/0375261	A1	12/2014	Manova-Elssibony et al.
2014/0043248	A1	2/2014	Yeh	2014/0376646	A1	12/2014	Leabman et al.
2014/0054971	A1	2/2014	Kissin	2015/0001949	A1	1/2015	Leabman et al.
2014/0055098	A1	2/2014	Lee et al.	2015/0002086	A1	1/2015	Matos et al.
2014/0057618	A1	2/2014	Zinvas et al.	2015/0003207	A1	1/2015	Lee et al.
2014/0089422	A1	2/2014	Von Novak et al.	2015/0008980	A1	1/2015	Kim et al.
2014/0062395	A1	3/2014	Kwon et al.	2015/0011160	A1	1/2015	Uurgovan et al.
2014/0082435	A1	3/2014	Kitgawa	2015/0015180	A1	1/2015	Miller et al.
2014/0086125	A1	3/2014	Polo et al.	2015/0015182	A1	1/2015	Brandtman et al.
2014/0086592	A1	3/2014	Nakahara et al.	2015/0015192	A1	1/2015	Leabman et al.
2014/0091756	A1	4/2014	Ofstein et al.	2015/0015194	A1	1/2015	Leabman et al.
2014/0091968	A1	4/2014	Harel et al.	2015/0015195	A1	1/2015	Leabman et al.
2014/0103869	A1	4/2014	Radovic	2015/0021990	A1	1/2015	Myer et al.
2014/0111147	A1	4/2014	Soar	2015/0022008	A1	1/2015	Leabman et al.
2014/0113689	A1	4/2014	Lee	2015/0022009	A1	1/2015	Leabman et al.
2014/0117946	A1	5/2014	Muller et al.	2015/0022010	A1	1/2015	Leabman et al.
2014/0118140	A1	5/2014	Amis	2015/0023204	A1	1/2015	Wil et al.
2014/0132210	A1	5/2014	Partovi	2015/0028688	A1	1/2015	Masaoka
2014/0133279	A1	5/2014	Khuri-Yakub	2015/0028694	A1	1/2015	Leabman et al.
2014/0139034	A1	5/2014	Sankar et al.	2015/0028697	A1	1/2015	Leabman et al.
2014/0139039	A1	5/2014	Cook et al.	2015/0029397	A1	1/2015	Leabman et al.
2014/0139180	A1	5/2014	Kim et al.	2015/0035715	A1	2/2015	Kim et al.
2014/0141838	A1	5/2014	Cai et al.	2015/0041459	A1	2/2015	Leabman et al.
2014/0142876	A1	5/2014	John et al.	2015/0042264	A1	2/2015	Leabman et al.
2014/0143933	A1	5/2014	Low et al.	2015/0042265	A1	2/2015	Leabman et al.
2014/0145879	A1	5/2014	Pan	2015/0044977	A1	2/2015	Ramasamy et al.
2014/0152117	A1	6/2014	Sanker	2015/0046526	A1	2/2015	Bush et al.
2014/0159651	A1	6/2014	Von Novak et al.	2015/0061404	A1	3/2015	Lamenza et al.
2014/0159652	A1	6/2014	Hall et al.	2015/0076917	A1	3/2015	Leabman et al.
2014/0159662	A1	6/2014	Furui	2015/0076927	A1	3/2015	Leabman et al.
2014/0159667	A1	6/2014	Kim et al.	2015/0077036	A1	3/2015	Leabman et al.
2014/0175893	A1	6/2014	Sengupta et al.	2015/0077037	A1	3/2015	Leabman et al.
2014/0176054	A1	6/2014	Porat et al.	2015/0091520	A1	4/2015	Blum et al.
				2015/0097663	A1	4/2015	Sloo et al.
				2015/0102681	A1	4/2015	Leabman et al.
				2015/0102764	A1	4/2015	Leabman et al.
				2015/0102769	A1	4/2015	Leabman et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0108848 A1 4/2015 Joehren
 2015/0115877 A1 4/2015 Aria et al.
 2015/0115878 A1 4/2015 Park
 2015/0123483 A1 5/2015 Leabman et al.
 2015/0123496 A1 5/2015 Leabman et al.
 2015/0128733 A1 5/2015 Taylor et al.
 2015/0130285 A1 5/2015 Leabman et al.
 2015/0130293 A1 5/2015 Hajimiri et al.
 2015/0148664 A1 5/2015 Stolka et al.
 2015/0155737 A1 6/2015 Mayo
 2015/0155738 A1 6/2015 Leabman et al.
 2015/0162751 A1 6/2015 Leabman et al.
 2015/0162779 A1 6/2015 Lee et al.
 2015/0171656 A1 6/2015 Leabman et al.
 2015/0171658 A1 6/2015 Manova-Elssibony et al.
 2015/0171931 A1 6/2015 Won et al.
 2015/0177326 A1 6/2015 Chakraborty et al.
 2015/0180133 A1 6/2015 Hunt
 2015/0188352 A1 7/2015 Peek et al.
 2015/0199665 A1 7/2015 Chu
 2015/0207333 A1 7/2015 Baarman et al.
 2015/0207542 A1 7/2015 Zeine
 2015/0222126 A1 8/2015 Leabman et al.
 2015/0236520 A1 8/2015 Baarman
 2015/0244187 A1 8/2015 Horie
 2015/0244201 A1 8/2015 Chu
 2015/0244341 A1 8/2015 Ritter et al.
 2015/0249484 A1 9/2015 Mach et al.
 2015/0255989 A1 9/2015 Walley et al.
 2015/0263534 A1 9/2015 Lee et al.
 2015/0263548 A1 9/2015 Cooper
 2015/0270741 A1 9/2015 Leabman et al.
 2015/0280484 A1 10/2015 Radziemski et al.
 2015/0288438 A1 10/2015 Maltsev et al.
 2015/0318729 A1 11/2015 Leabman
 2015/0326024 A1 11/2015 Bell et al.
 2015/0326025 A1 11/2015 Bell et al.
 2015/0326063 A1 11/2015 Leabman et al.
 2015/0326068 A1 11/2015 Bell et al.
 2015/0326069 A1 11/2015 Petras et al.
 2015/0326070 A1 11/2015 Petras et al.
 2015/0326072 A1 11/2015 Petras et al.
 2015/0326142 A1 11/2015 Petras et al.
 2015/0326143 A1 11/2015 Petras et al.
 2015/0333528 A1 11/2015 Leabman
 2015/0333529 A1 11/2015 Leabman
 2015/0333573 A1 11/2015 Leabman
 2015/0333800 A1 11/2015 Perry et al.
 2015/0340759 A1 11/2015 Bridgelall et al.
 2015/0340903 A1 11/2015 Bell et al.
 2015/0340909 A1 11/2015 Bell et al.
 2015/0340910 A1 11/2015 Petras et al.
 2015/0340911 A1 11/2015 Bell et al.
 2015/0341087 A1 11/2015 Moore et al.
 2015/0349574 A1 12/2015 Leabman
 2015/0358222 A1 12/2015 Berger et al.
 2015/0365138 A1 12/2015 Miller et al.
 2016/0005068 A1 1/2016 Im et al.
 2016/0012695 A1 1/2016 Bell et al.
 2016/0013656 A1 1/2016 Bell et al.
 2016/0013677 A1 1/2016 Bell et al.
 2016/0013678 A1 1/2016 Bell et al.
 2016/0013855 A1 1/2016 Campos
 2016/0020636 A1 1/2016 Khlal
 2016/0020649 A1 1/2016 Bell et al.
 2016/0020830 A1 1/2016 Bell et al.
 2016/0042206 A1 2/2016 Pesavento et al.
 2016/0054395 A1 2/2016 Bell et al.
 2016/0054396 A1 2/2016 Bell et al.
 2016/0054440 A1 2/2016 Younis
 2016/0056635 A1 2/2016 Bell
 2016/0056640 A1 2/2016 Mao
 2016/0056669 A1 2/2016 Bell
 2016/0056966 A1 2/2016 Bell
 2016/0065005 A1 3/2016 Won et al.

2016/0079799 A1 3/2016 Khlal
 2016/0094092 A1 3/2016 Davlantes et al.
 2016/0099601 A1 4/2016 Leabman et al.
 2016/0099602 A1 4/2016 Leabman et al.
 2016/0099609 A1 4/2016 Leabman et al.
 2016/0099610 A1 4/2016 Leabman et al.
 2016/0099611 A1 4/2016 Leabman et al.
 2016/0099612 A1 4/2016 Leabman et al.
 2016/0099613 A1 4/2016 Leabman et al.
 2016/0099614 A1 4/2016 Leabman et al.
 2016/0099755 A1 4/2016 Leabman et al.
 2016/0099756 A1 4/2016 Leabman et al.
 2016/0099757 A1 4/2016 Leabman et al.
 2016/0099758 A1 4/2016 Leabman et al.
 2016/0100124 A1 4/2016 Leabman et al.
 2016/0100312 A1 4/2016 Bell et al.
 2016/0126752 A1 5/2016 Vuori et al.
 2016/0126776 A1 5/2016 Kim et al.
 2016/0141908 A1 5/2016 Jakl et al.
 2016/0164563 A1 6/2016 Khawand et al.
 2016/0181854 A1 6/2016 Leabman
 2016/0181867 A1 6/2016 Daniel et al.
 2016/0181873 A1 6/2016 Mitcheson et al.
 2016/0191121 A1 6/2016 Bell
 2016/0204622 A1 7/2016 Leabman
 2016/0204642 A1 7/2016 Oh
 2016/0238365 A1 8/2016 Wixcv et al.
 2016/0299210 A1 10/2016 Zeine
 2016/0323000 A1 11/2016 Liu et al.
 2016/0336804 A1 11/2016 Son et al.
 2016/0339258 A1 11/2016 Perryman et al.
 2016/0359367 A1 12/2016 Rothschild
 2017/0005516 A9 1/2017 Leabman et al.
 2017/0005530 A1 1/2017 Zeine et al.
 2017/0025903 A1 1/2017 Song et al.
 2017/0026087 A1 1/2017 Tanabe
 2017/0043675 A1 2/2017 Jones et al.
 2017/0047784 A1 2/2017 Jung et al.
 2017/0077735 A1 3/2017 Leabman
 2017/0077736 A1 3/2017 Leabman
 2017/0077764 A1 3/2017 Bell et al.
 2017/0077765 A1 3/2017 Bell et al.
 2017/0077995 A1 3/2017 Leabman
 2017/0085120 A1 3/2017 Leabman et al.
 2017/0085437 A1 3/2017 Condeixa et al.
 2017/0092115 A1 3/2017 Sloo et al.
 2017/0110887 A1 4/2017 Bell et al.
 2017/0134686 A9 5/2017 Leabman
 2017/0163076 A1 6/2017 Park et al.
 2017/0179763 A9 6/2017 Leabman

FOREIGN PATENT DOCUMENTS

EP 1028482 A2 8/2000
 EP 1081506 A1 3/2001
 EP 2397973 A1 6/2010
 EP 2346136 A1 7/2011
 EP 2545635 A2 1/2013
 JP 2006157586 A 6/2006
 JP 2007043432 A 2/2007
 JP 2008167017 A 7/2008
 KR 20060061776 A 6/2006
 KR 20070044302 A 4/2007
 KR 100755144 B1 9/2007
 KR 20110132059 A 12/2011
 KR 20110135540 A1 12/2011
 KR 20120009843 A 2/2012
 KR 20120108759 A 10/2012
 KR 10 2013 0026977 A 3/2013
 WO 9952173 10/1999
 WO WO 200111716 A1 2/2001
 WO 2004077550 A1 9/2004
 WO 2003091943 A1 11/2006
 WO WO 2006122783 11/2006
 WO 2008156571 A2 12/2008
 WO 2010022181 A1 2/2010
 WO WO 2010039246 A1 4/2010
 WO 2010138994 A1 12/2010
 WO 2011112022 A2 9/2011

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO 2012177283	A1	12/2012
WO	2013031988	A1	3/2013
WO	2013035190	A1	3/2013
WO	WO 2013038074	A2	3/2013
WO	WO 2013042399	A1	3/2013
WO	WO 2013052950	A1	4/2013
WO	WO 2013105920	A2	7/2013
WO	2014075103	A1	5/2014
WO	WO 2014132258	A1	9/2014
WO	2014182788	A2	11/2014
WO	2014182788	A3	11/2014
WO	2014197472	A1	12/2014
WO	2014209587	A1	12/2014
WO	2015038773	A1	3/2015
WO	WO 2015097809	A1	7/2015
WO	WO 2015161323	A1	10/2015
WO	WO 2016048512	A1	3/2016
WO	WO 2016187357	A1	11/2016

OTHER PUBLICATIONS

Zhai, Huiqing, "A practical wireless charging system based on ultra-wide band Retro-Reflective beam forming" 2010 IEEE, Antennas and Propagation Society International, Toronto, CN, 2010, pp. 1-4.*

International Search Report dated Oct. 16, 2014 corresponding to International Patent Application No. PCT/US2014/041546, 4 pages.

International Search Report dated Sep. 12, 2014 corresponding to International Patent Application No. PCT/US2014/037072, 3 pages.

International Search Report dated Jan. 27, 2015 corresponding to International Patent Application No. PCT/US2014/037170, 4 pages.

International Search Report dated Oct. 13, 2014 corresponding to International Patent Application No. PCT/US2014/041534, 4 pages.

International Search Report dated Nov. 12, 2014 corresponding to International Patent Application No. PCT/US2014/046956, 4 pages.

Written Opinion of the International Searching Authority dated Nov. 12, 2014 corresponding to International Patent Application No. PCT/US2014/046956, 6 pages.

United States Final Office Action issued in U.S. Appl. No. 13/925,469 dated May 31, 2016.

United States Non-Final Office Action issued in U.S. Appl. No. 13/925,469 dated Dec. 2, 2015.

International Search Report issued in International Application No. PCT/US2014/055195 dated Dec. 22, 2014.

International Search Report and Written Opinion of the International Searching Authority dated Mar. 30, 2016 in International Application No. PCT/US15/67250, 12 pages.

United States Notice of Allowance issued in U.S. Appl. No. 13/926,020 dated May 15, 2015.

United States Non-Final Office Action issued in U.S. Appl. No. 13/926,020 dated Mar. 19, 2015.

United States Non-Final Office Action issued in U.S. Appl. No. 13/583,630 dated Mar. 23, 2016.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration issued in International Application No. PCT/US15/67243 dated Mar. 10, 2016.

Singh, V. et al., "Wireless Power Transfer Using Metamaterial Bonded Microstrip Antenna for Smart Grid WSN," In Fourth International Conference on Advances in Computing and Communications (ICACC), Aug. 27-29, 2014, Abstract, p. 299.

International Search Report issued in International Application No. PCT/722014/037109 dated Apr. 8, 2016.

United States Final Office Action issued in U.S. Appl. No. 13/891,430 dated Jan. 14, 2016.

United States Non-Final Office Action issued in U.S. Appl. No. 13/891,430 dated Jul. 17, 2016.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration issued in International Application No. PCT/US15/67242 dated Mar. 16, 2016.

United States Non-Final Office Action issued in U.S. Appl. No. 13/891,399 dated Nov. 2, 2015.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration issued in International Application No. PCT/US15/67245 dated Mar. 17, 2016.

United States Final Office Action issued in U.S. Appl. No. 13/891,445 dated Jan. 12, 2016.

International Search Report and Written Opinion of the International Searching Authority dated Mar. 3, 2016 in International Application No. PCT/US15/67275, 33 pages.

International Search Report and Written Opinion of the International Searching Authority dated Mar. 20, 2015 in International Application No. PCT/US2014/068568, 10 pages.

International Search Report and Written Opinion dated Dec. 22, 2014 in International Application No. PCT/US2014/055195, 12 pages.

International Search Report and Written Opinion dated May 11, 2016 in International Application No. PCT/US2015/067246, 18 pages.

International Search Report and Written Opinion of the International Searching Authority dated Mar. 29, 2016 in International Application No. PCT/US2015/067249, 14 pages.

Supplementary European Search Report, dated Jul. 21, 2016 in European Patent Application No. EP 14818136.5, 9 pages.

L.H. Hsieh et al., Development of a Retrodirective Wireless Microwave Power Transmission System, IEEE, 2003, pp. 393-396.

B.D. Van Veen et al., Beamforming: A Versatile Approach to Spatial Filtering, IEEE ASSP Magazine, Apr. 1988, pp. 4-24.

M. Leabman, Adaptive Band-Partitioning for Interference Cancellation in Communication Systems, Thesis, Massachusetts Institute of Technology, Feb. 1997, pp. 1-70.

Energous Corp., IPRP, PCT/US2014/046956, dated Jan. 19, 2016, 7 pgs.

Energous Corp., Written Opinion, PCT/US2014/037072, dated Sep. 12, 2014, 5 pgs.

Energous Corp., IPRP, PCT/US2014/037072, dated Nov. 10, 2015, 6 pgs.

Energous Corp., IPRP, PCT/US2015/067291, dated Jul. 4, 2017, 4 pgs.

Energous Corp., IPRP, PCT/US2015/067242, dated Jun. 27, 2017, 7 pgs.

Energous Corp., IPRP, PCT/US2015/067243, dated Jun. 27, 2017, 7 pgs.

Energous Corp., IPRP, PCT/US2015/067275, dated Jul. 4, 2017, 7 pgs.

Energous Corp., IPRP, PCT/US2015/067245, dated Jun. 27, 2017, 7 pgs.

Energous Corp., IPRP, PCT/US2014/041546, dated Dec. 29, 2015, 9 pgs.

Energous Corp., IPRP, PCT/US2015/67250, dated Mar. 30, 2016, 10 pgs.

Energous Corp., IPRP, PCT/US2015/067325, dated Jul. 4, 2017, 8 pgs.

Energous Corp., IPRP, PCT/US2015/067249, dated Jun. 27, 2017, 7 pgs.

Energous Corp., IPRP, PCT/US2015/067246, dated Jun. 27, 2017, 9 pgs.

Energous Corp., IPRP, PCT/US2015/067279, dated Jul. 4, 2017, 7 pgs.

Energous Corp., ISRWO, PCT/US2014/059871, dated Jan. 23, 2015, 12 pgs.

Energous Corp., IPRP, PCT/US2014/059871, dated Apr. 12, 2016, 9 pgs.

Energous Corp., ISRWO, PCT/US2014/045102, dated Oct. 28, 2014, 14 pgs.

Energous Corp., IPRP, PCT/US2014/045102, dated Jan. 12, 2016, 11 pgs.

Energous Corp., ISRWO, PCT/US2014/059340, dated Jan. 15, 2015, 13 pgs.

Energous Corp., IPRP, PCT/US2014/059340, dated Apr. 12, 2016, 11 pgs.

(56)

References Cited

OTHER PUBLICATIONS

- Energous Corp., ISRWO, PCT/US2015/067282, dated Jul. 5, 2016, 7 pgs.
- Energous Corp., IPRP, PCT/US2015/067282, dated Jul. 4, 2017, 6 pgs.
- Energous Corp., ISRWO, PCT/US2014/041558, dated Oct. 10, 2014, 8 pgs.
- Energous Corp., IPRP, PCT/US2014/041558, dated Dec. 29, 2015, 6 pgs.
- Energous Corp., ISRWO, PCT/US2014/045119, dated Oct. 13, 2014, 11 pgs.
- Energous Corp., IPRP, PCT/US2014/045119, dated Jan. 12, 2016, 9 pgs.
- Energous Corp., ISRWO PCT/US2014/045237, dated Oct. 13, 2014, 16 pgs.
- Energous Corp., IPRP, PCT/US2014/045237, dated Jan. 12, 2016, 12 pgs.
- Energous Corp., ISRWO, PCT/US2014/054897, dated Feb. 17, 2015, 10 pgs.
- Energous Corp., IPRP, PCT/US2014/054897, dated Mar. 15, 2016, 8 pgs.
- Energous Corp., ISRWO, PCT/US2015/067334, dated Mar. 3, 2016, 6 pgs.
- Energous Corp., IPRP, PCT/US2015/067334, dated Jul. 4, 2017, 5 pgs.
- Energous Corp., ISRWO, PCT/US2014/047963, dated Nov. 7, 2014, 13 pgs.
- Energous Corp., IPRP, PCT/US2014/047963, dated Jan. 26, 2016, 10 pgs.
- Energous Corp., ISRWO, PCT/US2014/054891, dated Dec. 18, 2014, 12 pgs.
- Energous Corp., IPRP, PCT/US2014/054891, dated Mar. 15, 2016, 10 pgs.
- Energous Corp., ISRWO, PCT/US2014/054953, dated Dec. 4, 2014, 7 pgs.
- Energous Corp., IPRP, PCT/US2014/054953, dated Mar. 22, 2016, 5 pgs.
- Energous Corp., ISRWO, PCT/US2015/067294, dated Mar. 29, 2016, 7 pgs.
- Energous Corp., IPRP, PCT/US2015/067294, dated Jul. 4, 2017, 6 pgs.
- Energous Corp., ISRWO, PCT/US2014/062672, dated Jan. 26, 2015, 11 pgs.
- Energous Corp., IPRP, PCT/US2014/062672, dated May 10, 2016, 8 pgs.
- Energous Corp., ISRWO, PCT/US2014/044810, dated Oct. 21, 2014, 12 pgs.
- Energous Corp., IPRP, PCT/US2014/044810, dated Jan. 5, 2016, 10 pgs.
- Energous Corp., ISRWO, PCT/US2015/067271, dated Mar. 11, 2016, 6 pgs.
- Energous Corp., IPRP, PCT/US2015/067271, dated Jul. 4, 2017, 5 pgs.
- Energous Corp., ISRWO, PCT/US2014/040648, dated Oct. 10, 2014, 11 pgs.
- Energous Corp., IPRP, PCT/US2014/040648, dated Dec. 8, 2015, 8 pgs.
- Energous Corp., ISRWO, PCT/US2014/049673, dated Nov. 18, 2014, 10 pgs.
- Energous Corp., IPRP, PCT/US2014/049673, dated Feb. 9, 2016, 6 pgs.
- Energous Corp., ISRWO, PCT/US2014/068282, dated Mar. 19, 2015, 13 pgs.
- Energous Corp., IPRP, PCT/US2014/068282, dated Jun. 7, 2016, 10 pgs.
- Energous Corp., ISRWO, PCT/US2014/068586, dated Mar. 20, 2015, 11 pgs.
- Energous Corp., IPRP, PCT/US2014/068586, dated Jun. 14, 2016, 8 pgs.
- Energous Corp., ISRWO, PCT/US2016/068504, dated Mar. 30, 2017, 8 pgs.
- Energous Corp., ISRWO, PCT/US2016/068495, dated Mar. 30, 2017, 9 pgs.
- Energous Corp., IPRP, PCT/US2015/067287, dated Jul. 4, 2017, 6 pgs.
- Energous Corp., ISRWO, PCT/US2016/068551, dated Mar. 17, 2017, 8 pgs.
- Energous Corp., ISRWO, PCT/US2016/068498, dated May 17, 2017, 8 pgs.
- Energous Corp., ISRWO, PCT/US2016/068993, dated Mar. 13, 2017, 12 pgs.
- Energous Corp., ISRWO, PCT/US2016/068565, dated Mar. 8, 2017, 11 pgs.
- Energous Corp., ISRWO, PCT/US2016/068987, dated May 8, 2017, 10 pgs.
- Energous Corp., ISRWO, PCT/US2016/069316, dated Mar. 16, 2017, 15 pgs.
- European Search Report, EP Patent Application No. EP16189052.0, dated Jan. 31, 2017, 11 pgs.
- European Search Report, EP Patent Application No. EP16189319-3, dated Feb. 1, 2017, 9 pgs.
- European Search Report, EP Patent Application No. EP14822971, dated Feb. 1, 2017, 9 pgs.
- European Search Report, EP Patent Application No. EP16189987, dated Feb. 1, 2017, 8 pgs.
- European Search Report, EP Patent Application No. 16196205.5, dated Mar. 28, 2017, 7 pgs.
- European Search Report, EP Patent Application No. 16189300, dated Feb. 28, 2017, 4 pgs.
- European Search Report, EP Patent Application No. 16189988.5, dated Mar. 1, 2017, 4 pgs.
- European Search Report, EP Patent Application No. 16189982.5, dated Jan. 27, 2017, 9 pgs.
- European Search Report, EP Patent Application No. 16189974, dated Mar. 2, 2017, 5 pgs.
- European Search Report, EP Patent Application No. 16193743, dated Feb. 2, 2017, 5 pgs.
- European Search Report, EP Patent Application No. 14868901.1, dated Jul. 7, 2017, 5 pgs.
- Panda, SIW based Slot Array Antenna and Power Management Circuit for Wireless Energy Harvesting Applications, IEEE APSURSI, Jul. 2012, 2 pgs.
- Singh, Wireless Power Transfer Using Metamaterial Bonded Microstrip Antenna for Smart Grid WSN: In Fourth International Conference on Advances in Computing and Communications (ICACC), Aug. 27-29, 2014, Abstract 299.
- T. Gill et al. "A System for Change Detection and Human Recognition in Voxel Space using the Microsoft Kinect Sensor," 2011 IEEE Applied Imagery Pattern Recognition Workshop. 8 pgs.
- J. Han et al. Enhanced Computer Vision with Microsoft Kinect Sensor: A Review, IEEE Transactions on Cybernetics vol. 43, No. 5. pp. 1318-1334.
- Zhai, "A Practical wireless charging system based on ultra-wideband retro-reflective beamforming" 2010 IEEE Antennas and Propagation Society International Symposium, Toronto, ON 2010, pp. 1-4.
- Mao: BeamStar: An Edge-Based Approach to Routing in Wireless Sensors Networks, IEEE Transactions on Mobile Computing, IEEE Service Center, Los Alamitos, CA US, vol. 6, No. 11, Nov. 1, 2007, 13 pgs.
- Smolders—Institute of Electrical and Electronics Engineers: "Broadband microstrip array antennas" Digest of the Antennas and Propagation Society International Symposium. Seattle, WA Jun. 19-24, 1994. Abstract 3 pgs.
- Paolo Nenzi et al; "U-Helix: On-chip short conical antenna", 2013 7th European Conference on Antennas and Propagation (EUCAP), ISBN:978-1-4673-2187-7, IEEE, Apr. 8, 2013, 5 pgs.
- Adamiuk G et al; "Compact, Dual-Polarized UWB-Antenna, Embedded in a Dielectric" IEEE Transactions on Antenna and Propagation, IEEE Service Center, Piscataway, NJ, US vol. 56, No. 2, ISSN: 0018-926X, abstract Figure 1, Feb. 1, 2010, 8 pgs.

(56)

References Cited

OTHER PUBLICATIONS

Mascarenas et al.; "Experimental Studies of Using Wireless Energy Transmission for Powering Embedded Sensor Nodes." Nov. 28, 2009, Journal of Sound and Vibration, pp. 2421-2433.

Energous Corp., Written Opinion, PCT/US2014/037170, dated Sep. 15, 2014, 7 pgs.

Energous Corp., IPRP, PCT/US2014/037170, dated Nov. 10, 2015, 8 pgs.

Energous Corp., Written Opinion, PCT/US2014/041534, dated Oct. 13, 2014, 6 pgs.

Energous Corp., IPRP, PCT/US2014/041534, dated Dec. 29, 2015, 7 pgs.

Energous Corp., IPRP, PCT/US2014/068568, dated Jun. 14, 2016, 8 pgs.

Energous Corp., IPRP, PCT/US2014/055195, dated Mar. 22, 2016, 9 pgs.

Energous Corp., ISRWO, PCT/US2015/067291, dated Mar. 4, 2016, 10 pgs.

Energous Corp., IPRP, PCT/US2014/037109, dated Apr. 12, 2016, 9 pgs.

Energous Corp., ISRWO, PCT/US2014/041546, dated Oct. 16, 2014, 12 pgs.

Energous Corp., ISRWO, PCT/US2015/067325, dated Mar. 10, 2016, 9 pgs.

Energous Corp., ISRWO, PCT/US2014/040697, dated Oct. 1, 2014, 12 pgs.

Energous Corp., IPRP, PCT/US2014/040697, dated Dec. 8, 2015, 9 pgs.

Energous Corp., ISRWO, PCT/US2014/040705, dated Sep. 23, 2014, 8 pgs.

Energous Corp., IPRP, PCT/US2014/040705, dated Dec. 8, 2015, 6 pgs.

Energous Corp., ISRWO, PCT/US2015/067246, dated May 11, 2016, 18 pgs.

Energous Corp., ISRWO, PCT/US2014/059317, dated Feb. 24, 2015, 13 pgs.

Energous Corp., IPRP, PCT/US2014/059317, dated Apr. 12, 2016, 10 pgs.

Energous Corp., ISRWO, PCT/US2014/049669, dated Nov. 13, 2014, 10 pgs.

Energous Corp., IPRP, PCT/US2014/049669, dated Feb. 9, 2016, 8 pgs.

Energous Corp., ISRWO, PCT/US2014/041323, dated Oct. 1, 2014, 10 pgs.

Energous Corp., IPRP, PCT/US2014/041323, dated Dec. 22, 2015, 8 pgs.

Energous Corp., ISRWO, PCT/US2014/048002, dated Nov. 13, 2014, 11 pgs.

Energous Corp., IPRP, PCT/US2014/048002, dated Feb. 12, 2015, 8 pgs.

Energous Corp., ISRWO, PCT/US2014/062682, dated Feb. 12, 2015, 10 pgs.

Energous Corp., IPRP, PCT/US2014/062682, dated May 3, 2016, 8 pgs.

Energous Corp., ISRWO, PCT/US2014/049666, dated Nov. 10, 2014, 7 pgs.

Energous Corp., IPRP, PCT/US2014/049666, dated Feb. 9, 2016, 5 pgs.

Energous Corp., ISRWO, PCT/US2014/046961, dated Nov. 24, 2014, 16 pgs.

Energous Corp., IPRP, PCT/US2014/046961, dated Jan. 19, 2016, 8 pgs.

Energous Corp., ISRWO, PCT/US2015/067279, dated Mar. 11, 2015, 13 pgs.

Energous Corp., ISRWO, PCT/US2014/041342, dated Jan. 27, 2015, 10 pgs.

Energous Corp., IPRP, PCT/US2014/041342, dated Dec. 15, 2015, 8 pgs.

Energous Corp., ISRWO, PCT/US2014/046941, dated Nov. 6, 2014, 11 pgs.

Energous Corp., IPRP, PCT/US2014/046941, dated Jan. 19, 2016, 9 pgs.

Energous Corp., ISR, PCT/US2014/062661, dated Jan. 27, 2015, 3 pgs.

Energous Corp., Written Opinion, PCT/US2014/062661, dated Jan. 27, 2015, 9 pgs.

Energous Corp., IPRP, PCT/US2014/062661, dated May 3, 2016, 10 pgs.

Energous Corp., ISRWO, PCT/US2015/067287, dated Feb. 2, 2016, 8 pgs.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12




FIG. 13A




FIG. 13B




FIG. 14




FIG. 15A




FIG. 15B




FIG. 16




FIG. 17




FIG. 18A

FIG. 18B




FIG. 1900B




FIG. 1900A




FIG. 20A




FIG. 20C




FIG. 20B




FIG. 21A




FIG. 21B




FIG. 22

METHODOLOGY FOR MULTIPLE POCKET-FORMING

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part application of U.S. Non-Provisional patent application Ser. No. 13/891,430, filed May 10, 2013, entitled "Methodology For Pocket-Forming," which claims priority to U.S. Provisional Patent Application Nos. 61/720,798, filed Oct. 31, 2012, entitled "Scalable Antenna Assemblies For Power Transmission," 61/668,799, filed Jul. 6, 2012, entitled "Receivers For Power Transmission," and 61/677,706, filed Jul. 31, 2012, entitled "Transmitters For Wireless Power Transmission," the entire contents of which are incorporated herein by reference in their entirety.

This application is a continuation-in-part of U.S. Non-Provisional patent application Ser. No. 13/925,469, filed Jun. 24, 2013, entitled "Methodology for Multiple Pocket-Forming," the entire contents of which is incorporated herein by reference in its entirety.

This application is a continuation-in-part of U.S. Non-Provisional patent application Ser. No. 13/946,082, filed Jul. 19, 2013, entitled "Method for 3 Dimensional Pocket-Forming," the entire contents of which is incorporated herein by reference in its entirety.

This application is a continuation-in-part of U.S. Non-Provisional patent application Ser. No. 13/891,399, filed May 10, 2013, entitled "Receivers for Wireless Power Transmission," which claims priority to U.S. Provisional Patent Application Nos. 61/720,798, filed Oct. 31, 2012, entitled "Scalable Antenna Assemblies For Power Transmission," 61/668,799, filed Jul. 6, 2012, entitled "Receivers For Power Transmission," and 61/677,706, filed Jul. 31, 2012, entitled "Transmitters For Wireless Power Transmission," the entire contents of which are incorporated herein by reference in their entirety.

This application is a continuation-in-part of U.S. Non-Provisional patent application Ser. No. 13/891,445, filed May 10, 2013, entitled "Transmitters for Wireless Power Transmission," which claims priority to U.S. Provisional Patent Application Nos. 61/720,798, filed Oct. 31, 2012, entitled "Scalable Antenna Assemblies For Power Transmission," 61/668,799, filed Jul. 6, 2012, entitled "Receivers For Power Transmission," and 61/677,706, filed Jul. 31, 2012, entitled "Transmitters For Wireless Power Transmission," the entire contents of which are incorporated herein by reference in their entirety.

This application is a continuation-in-part of U.S. Non-Provisional patent application Ser. No. 13/926,020, filed Jun. 25, 2013, entitled "Wireless Power Transmission with Selective Range," the entire contents of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

The present disclosure relates generally to wireless power transmission.

BACKGROUND

Portable electronic devices such as smart phones, tablets, notebooks and other electronic devices have become an everyday need in the way we communicate and interact with others. The frequent use of these devices may require a significant amount of power, which may easily deplete the

batteries attached to these devices. Therefore, a user is frequently needed to plug in the device to a power source, and recharge such device. This may require having to charge electronic equipment at least once a day, or in high-demand electronic devices more than once a day.

Such an activity may be tedious and may represent a burden to users. For example, a user may be required to carry chargers in case his electronic equipment is lacking power. In addition, users have to find available power sources to connect to. Lastly, users must plugin to a wall or other power supply to be able to charge his or her electronic device. However, such an activity may render electronic devices inoperable during charging.

Current solutions to this problem may include devices having rechargeable batteries. However, the aforementioned approach requires a user to carry around extra batteries, and also make sure that the extra set of batteries is charged. Solar-powered battery chargers are also known, however, solar cells are expensive, and a large array of solar cells may be required to charge a battery of any significant capacity. Other approaches involve a mat or pad that allows charging of a device without physically connecting a plug of the device to an electrical outlet, by using electromagnetic signals. In this case, the device still requires to be placed in a certain location for a period of time in order to be charged. Assuming a single source power transmission of electromagnetic (EM) signal, an EM signal power gets reduced by a factor proportional to $1/r^2$ over a distance r , in other words, it is attenuated proportional to the square of the distance. Thus, the received power at a large distance from the EM transmitter is a small fraction of the power transmitted. To increase the power of the received signal, the transmission power would have to be boosted. Assuming that the transmitted signal has an efficient reception at three centimeters from the EM transmitter, receiving the same signal power over a useful distance of three meters would entail boosting the transmitted power by 10,000 times. Such power transmission is wasteful, as most of the energy would be transmitted and not received by the intended devices, it could be hazardous to living tissue, it would most likely interfere with most electronic devices in the immediate vicinity, and it may be dissipated as heat.

In yet another approach such as directional power transmission, it would generally require knowing the location of the device to be able to point the signal in the right direction to enhance the power transmission efficiency. However, even when the device is located, efficient transmission is not guaranteed due to reflections and interference of objects in the path or vicinity of the receiving device. In addition, in many use cases the device is not stationary, which is an added difficulty.

For the foregoing reasons, there is a need for a wireless power transmission system where electronic devices may be powered without requiring extra chargers or plugs, and where the mobility and portability of electronic devices may not be compromised. Therefore, a wireless power transmission method solving the aforementioned problems is desired.

SUMMARY

The embodiments described herein include a transmitter that transmits a power transmission signal (e.g., radio frequency (RF) signal waves) to create a three-dimensional pocket of energy. At least one receiver can be connected to or integrated into electronic devices and receive power from the pocket of energy. The transmitter can locate the at least

one receiver in a three-dimensional space using a communication medium (e.g., Bluetooth technology). The transmitter generates a waveform to create a pocket of energy around each of the at least one receiver. The transmitter uses an algorithm to direct, focus, and control the waveform in three dimensions. The receiver can convert the transmission signals (e.g., RF signals) into electricity for powering an electronic device. Accordingly, the embodiments for wireless power transmission can allow powering and charging a plurality of electrical devices without wires.

In one embodiment, a method for multiple pocket-forming in wireless power transmission, the method comprises establishing, by a transmitter, a first communication connection associating the transmitter with a first receiver in response to the transmitter receiving a first communication signal from the first receiver; transmitting, by the transmitter, one or more power transmission waves in a direction of the first receiver based on the first communication signal received from the first receiver; adjusting, by the transmitter, a phase of the power transmission waves and a gain of the one or more power transmission waves to converge at a location with respect to the receiver in accordance with the first communication signal received from the first receiver, thereby forming a pocket of energy at the location that the one or more power transmission waves converge; responsive to the transmitter receiving a second communication signal from a second receiver: establishing, by the transmitter, a second communication connection associating the transmitter with the second receiver; and identifying, by the transmitter, a second subset of one or more antennas from an array of antennas of the transmitter, wherein the second subset is associated with the second receiver, and wherein a first subset of one or more antennas is associated with the first receiver; and transmitting, by the transmitter, one or more power transmission waves in the direction of the second receiver based on the second signal received from the second receiver, wherein the second subset of antennas transmits the one or more power transmission waves to the second receiver.

In another embodiment, a system for multiple pocket-forming in wireless power transmission, the system comprises a transmitter comprising: a first communication component configured to establish one or more communication connections with one or more receivers respectively in response to receiving an advertisement signal from a respective receiver, the first communication component further configured to transmit and receive at a given interval one or more communications signals with each respective receiver over each respective communication connection; an integrated circuit configured to generate power transmission waves based on data derived from each respective communication signal, and to modify the power transmission waves in accordance with each respective communication signal to form a pocket of energy at a location associated with the respective receiver; and a plurality of antennas configured to transmit the one or more power transmission waves to a respective receiver, wherein a first subset of the plurality of antennas transmits to a first receiver of one or more receivers, and wherein one or more subsets of antennas are respectively assigned to transmit to each of the one or more receivers; and a receiver comprising: a communication component configured to transmit the advertisement signal identifying the receiver, and to transmit and receive communications signals with the transmitter over the communication channel, wherein the communication signal of the receiver indicates the amount of power derived from the pocket of energy; a plurality of antennas configured to

receive the one or more power transmission waves from the transmitter, wherein the power transmission waves are derived from the pocket of energy formed at the location associated with the receiver; power circuitry, in response to the antennas deriving the power transmission waves from the pocket of energy, configured to convert the power transmission waves of the pocket of energy into a electrical energy and providing the electrical energy to a electronic device associated with the receiver; and a processor configured to determine the amount of energy derived from the pocket of energy and instruct the communication component to transmit the communication signal indicating the amount of energy to the transmitter.

In another embodiment, a system for multiple pocket-forming in wireless power transmission, the system comprises a transmitter comprising: at least two antennas configured to transmit power transmission waves converging in constructive interference patterns to form one or more pockets of energy; communication circuitry configured to generate the power transmission waves and one or more communications signals containing data associated with the power transmission waves; and a first micro-controller configured to control the constructive interference patterns of the power transmission waves to form the one or more pockets of energy at one or more locations associated with one or more receivers, and to control the communication circuitry, wherein an integrated chip associated with the micro-controller is configured to adjust a phase and a magnitude of the power transmission waves to form the pockets of energy at each respective location; and an electronic device comprising a receiver integrated in the electronic device comprising: at least one antenna configured to derive energy from a pocket of energy at a location of the receiver; and a micro-controller configured to generate one or more communication signals indicating the energy requirements of the electronic device to the transmitter.

In another embodiment, a method of forming pockets of energy, the method comprises capturing, by a transmitter, a first signal of one or more communications signals from a first receiver device; establishing, by the transmitter, a first communication connection hosting communication signals between the transmitter and the first receiver; assigning, by the transmitter, a first subset of one or more antennas of the transmitter to transmit one or more power transmission waves to the first receiver device; at a predetermined interval: ceasing, by the transmitter, processing of the communications signals arriving over the first communication connection at a predetermined interval; capturing, by the transmitter, a second signal of one or more communications signals from a second receiver; establishing, by the transmitter, a second communication connection hosting communication signals between the transmitter and the second receiver; and assigning, by the transmitter, a second subset of antennas of the transmitter to transmit one or more power transmission waves to the second receiver device.

Additional features and advantages of an embodiment will be set forth in the description which follows, and in part will be apparent from the description. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the exemplary embodiments in the written description and claims hereof as well as the appended drawings.

It is to be understood that both the foregoing general description and the following detailed description are exem-

plary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The present disclosure can be better understood by referring to the following figures. The components in the figures are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the disclosure. In the figures, reference numerals designate corresponding parts throughout the different views. Non-limiting embodiments of the present disclosure are described by way of example with reference to the accompanying figures, which are schematic and are not intended to be drawn to scale. Unless indicated as representing the background art, the figures represent aspects of the disclosure.

FIG. 1 illustrates a system overview, according to an exemplary embodiment.

FIG. 2 illustrates steps of wireless power transmission, according to an exemplary embodiment.

FIG. 3 illustrates an architecture for wireless power transmission, according to an exemplary embodiment.

FIG. 4 illustrates components of a system of wireless power transmission using pocket-forming procedures, according to an exemplary embodiment.

FIG. 5 illustrates steps of powering a plurality of receiver devices, according to an exemplary embodiment.

FIG. 6A illustrates waveforms for wireless power transmission with selective range, which may get unified in single waveform.

FIG. 6B illustrates waveforms for wireless power transmission with selective range, which may get unified in single waveform.

FIG. 7 illustrates wireless power transmission with selective range, where a plurality of pockets of energy may be generated along various radii from transmitter.

FIG. 8 illustrates wireless power transmission with selective range, where a plurality of pockets of energy may be generated along various radii from transmitter.

FIGS. 9A and 9B illustrate a diagram of an architecture for wirelessly charging client computing platform, according to an exemplary embodiment.

FIG. 10A illustrates wireless power transmission using multiple pocket-forming, according to an exemplary embodiment.

FIG. 10B illustrates multiple adaptive pocket-forming, according to an exemplary embodiment.

FIG. 11 illustrates a diagram of a system architecture for wirelessly charging client devices, according to an exemplary embodiment.

FIG. 12 illustrates a method for determining receiver location using antenna element, according to an exemplary embodiment.

FIG. 13A illustrates an array subset configuration, according to an exemplary embodiment.

FIG. 13B illustrates an array subset configuration, according to an exemplary embodiment.

FIG. 14 illustrates a flat transmitter, according to an exemplary embodiment.

FIG. 15A illustrates a transmitter, according to an exemplary embodiment.

FIG. 15B illustrates a box transmitter, according to an exemplary embodiment.

FIG. 16 illustrates a diagram of an architecture for incorporating transmitter into different devices, according to an exemplary embodiment.

FIG. 17 illustrates a transmitter configuration according to an exemplary embodiment.

FIG. 18A illustrates multiple rectifiers connected in parallel to an antenna element, according to an exemplary embodiment.

FIG. 18B illustrates multiple antenna elements connected in parallel to a rectifier, according to an exemplary embodiment.

FIG. 19A illustrates multiple antenna elements outputs combined and connected to parallel rectifiers, according to an exemplary embodiment.

FIG. 19B illustrates groups of antenna elements connected to different rectifiers, according to an exemplary embodiment.

FIG. 20A illustrates a device with an embedded receiver, according to an exemplary embodiment.

FIG. 20B illustrates a battery with an embedded receiver, according to an exemplary embodiment.

FIG. 20C illustrates external hardware that may be attached to a device, according to an exemplary embodiment.

FIG. 21A illustrates hardware in the form of case, according to an exemplary embodiment.

FIG. 21B illustrates hardware in the form of a printed film or flexible printed circuit board, according to an exemplary embodiment.

FIG. 22 illustrates internal hardware according to an exemplary embodiment.

DETAILED DESCRIPTION

The present disclosure is here described in detail with reference to embodiments illustrated in the drawings, which form a part here. Other embodiments may be used and/or other changes may be made without departing from the spirit or scope of the present disclosure. The illustrative embodiments described in the detailed description are not meant to be limiting of the subject matter presented here. Furthermore, the various components and embodiments described herein may be combined to form additional embodiments not expressly described, without departing from the spirit or scope of the invention.

Reference will now be made to the exemplary embodiments illustrated in the drawings, and specific language will be used here to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended. Alterations and further modifications of the inventive features illustrated here, and additional applications of the principles of the inventions as illustrated here, which would occur to one skilled in the relevant art and having possession of this disclosure, are to be considered within the scope of the invention.

I. Systems and Methods for Wireless Power Transmissions

A. Components System Embodiment

FIG. 1 shows a system 100 for wireless power transmission by forming pockets of energy 104. The system 100 may comprise transmitters 101, receivers 103, client devices 105, and pocket detectors 107. Transmitters 101 may transmit power transmission signals comprising power transmission waves, which may be captured by receivers 103. The receivers 103 may comprise antennas, antenna elements, and other circuitry (detailed later), which may convert the captured waves into a useable source of electrical energy on behalf of client devices 105 associated with the receivers 103. In some embodiments, transmitters 101 may transmit power transmission signals, made up of power transmission waves, in one or more trajectories by manipulating the phase, gain,

and/or other waveform features of the power transmission waves, and/or by selecting different transmit antennas. In such embodiments, the transmitters **101** may manipulate the trajectories of the power transmission signals so that the underlying power transmission waves converge at a location in space, resulting in certain forms of interference. One type of interference generated at the convergence of the power transmission waves, “constructive interference,” may be a field of energy caused by the convergence of the power transmission waves such that they add together and strengthen the energy concentrated at that location—in contrast to adding together in a way to subtract from each other and diminish the energy concentrated at that location, which is called “destructive interference”. The accumulation of sufficient energy at the constructive interference may establish a field of energy, or “pocket of energy” **104**, which may be harvested by the antennas of a receiver **103**, provided the antennas are configured to operate on the frequency of the power transmission signals. Accordingly, the power transmission waves establish pockets of energy **104** at the location in space where the receivers **103** may receive, harvest, and convert the power transmission waves into useable electrical energy, which may power or charge associated electrical client devices **105**. Detectors **107** may be devices comprising a receiver **103** that are capable of producing a notification or alert in response to receiving power transmission signals. As an example, a user searching for the optimal placement of a receiver **103** to charge the user’s client device **105** may use a detector **107** that comprises an LED light **108**, which may brighten when the detector **107** captures the power transmission signals from a single beam or a pocket of energy **104**.

1. Transmitters

The transmitter **101** may transmit or broadcast power transmission signals to a receiver **103** associated with a device **105**. Although several of the embodiments mentioned below describe the power transmission signals as radio frequency (RF) waves, it should be appreciated that the power transmission may be physical media that is capable of being propagated through space, and that is capable of being converted into a source of electrical energy **103**. The transmitter **101** may transmit the power transmission signals as a single beam directed at the receivers **103**. In some cases, one or more transmitters **101** may transmit a plurality of power transmission signals that are propagated in a multiple directions and may deflect off of physical obstructions (e.g., walls). The plurality of power transmission signals may converge at a location in a three-dimensional space, forming a pocket of energy **104**. Receivers **103** within the boundaries of an energy pocket **104** may capture and convert the power transmission signals into a useable source of energy. The transmitter **101** may control pocket-forming based on phase and/or relative amplitude adjustments of power transmission signals, to form constructive interference patterns.

Although the exemplary embodiment recites the use of RF wave transmission techniques, the wireless charging techniques should not be limited to RF wave transmission techniques. Rather, it should be appreciated that possible wireless charging techniques may include any number of alternative or additional techniques for transmitting energy to a receiver converting the transmitted energy to electrical power. Non-limiting exemplary transmission techniques for energy that can be converted by a receiving device into electrical power may include: ultrasound, microwave, resonant and inductive magnetic fields, laser light, infrared, or other forms of electromagnetic energy. In the case of ultrasound, for example, one or more transducer elements may be

disposed so as to form a transducer array that transmits ultrasound waves toward a receiving device that receives the ultrasound waves and converts them to electrical power. In the case of resonant or inductive magnetic fields, magnetic fields are created in a transmitter coil and converted by a receiver coil into electrical power. In addition, although the exemplary transmitter **101** is shown as a single unit comprising potentially multiple transmitters (transmit array), both for RF transmission of power and for other power transmission methods mentioned in this paragraph, the transmit arrays can comprise multiple transmitters that are physically spread around a room rather than being in a compact regular structure.

The transmitter includes an antenna array where the antennas are used for sending the power transmission signal. Each antenna sends power transmission waves where the transmitter applies a different phase and amplitude to the signal transmitted from different antennas. Similar to the formation of pockets of energy, the transmitter can form a phased array of delayed versions of the signal to be transmitted, then applies different amplitudes to the delayed versions of the signal, and then sends the signals from appropriate antennas. For a sinusoidal waveform, such as an RF signal, ultrasound, microwave, or others, delaying the signal is similar to applying a phase shift to the signal.

2. Pockets of Energy

A pocket of energy **104** may be formed at locations of constructive interference patterns of power transmission signals transmitted by the transmitter **101**. The pockets of energy **104** may manifest as a three-dimensional field where energy may be harvested by receivers **103** located within the pocket of energy **104**. The pocket of energy **104** produced by transmitters **101** during pocket-forming may be harvested by a receiver **103**, converted to an electrical charge, and then provided to electronic client device **105** associated with the receiver **103** (e.g., laptop computer, smartphone, rechargeable battery). In some embodiments, there may be multiple transmitters **101** and/or multiple receivers **103** powering various client devices **105**. In some embodiments, adaptive pocket-forming may adjust transmission of the power transmission signals in order to regulate power levels and/or identify movement of the devices **105**.

3. Receivers

A receiver **103** may be used for powering or charging an associated client device **105**, which may be an electrical device coupled to or integrated with the receiver **103**. The receiver **103** may receive power transmission waves from one or more power transmission signals originating from one or more transmitters **101**. The receiver **103** may receive the power transmission signals as a single beam produced by the transmitter **101**, or the receiver **103** may harvest power transmission waves from a pocket of energy **104**, which may be a three-dimensional field in space resulting from the convergence of a plurality of power transmission waves produced by one or more transmitters **101**. The receiver **103** may comprise an array of antennas **112** configured to receive power transmission waves from a power transmission signal and harvest the energy from the power transmission signals of the single beam or pocket of energy **104**. The receiver **103** may comprise circuitry that then converts the energy of the power transmission signals (e.g., the radio frequency electromagnetic radiation) to electrical energy. A rectifier of the receiver **103** may translate the electrical energy from AC to DC. Other types of conditioning may be applied, as well. For example, a voltage conditioning circuit may increase or decrease the voltage of the electrical energy as required by

the client device **105**. An electrical relay may then convey the electrical energy from the receiver **103** to the client device **105**.

In some embodiments, the receiver **103** may comprise a communications component that transmits control signals to the transmitter **101** in order to exchange data in real-time or near real-time. The control signals may contain status information about the client device **105**, the receiver **103**, or the power transmission signals. Status information may include, for example, present location information of the device **105**, amount of charge received, amount of charge used, and user account information, among other types of information. Further, in some applications, the receiver **103** including the rectifier that it contains may be integrated into the client device **105**. For practical purposes, the receiver **103**, wire **111**, and client device **105** may be a single unit contained in a single packaging.

4. Control Signals

In some embodiments, control signals may serve as data inputs used by the various antenna elements responsible for controlling production of power transmission signals and/or pocket-forming. Control signals may be produced by the receiver **103** or the transmitter **101** using an external power supply (not shown) and a local oscillator chip (not shown), which in some cases may include using a piezoelectric material. Control signals may be RF waves or any other communication medium or protocol capable of communicating data between processors, such as Bluetooth®, RFID, infrared, near-field communication (NFC). As detailed later, control signals may be used to convey information between the transmitter **101** and the receiver **103** used to adjust the power transmission signals, as well as contain information related to status, efficiency, user data, power consumption, billing, geo-location, and other types of information.

5. Detectors

A detector **107** may comprise hardware similar to receivers **103**, which may allow the detector **107** to receive power transmission signals originating from one or more transmitters **101**. The detector **107** may be used by users to identify the location of pockets of energy **104**, so that users may determine the preferable placement of a receiver **103**. In some embodiments, the detector **107** may comprise an indicator light **108** that indicates when the detector is placed within the pocket of energy **104**. As an example, in FIG. 1, detectors **107a**, **107b** are located within the pocket of energy **104** generated by the transmitter **101**, which may trigger the detectors **107a**, **107b** to turn on their respective indicator lights **108a**, **108b**, because the detectors **107a**, **107b** are receiving power transmission signals of the pocket of energy **104**; whereas, the indicator light **108c** of a third detector **107c** located outside of the pockets of energy **104**, is turned off, because the third detector **107c** is not receiving the power transmission signals from the transmitter **101**. It should be appreciated that the functions of a detector, such as the indicator light, may be integrated into a receiver or into a client device in alternative embodiments as well.

6. Client Device

A client device **105** may be any electrical device that requires continuous electrical energy or that requires power from a battery. Non-limiting examples of client devices **105** may include laptops, mobile phones, smartphones, tablets, music players, toys, batteries, flashlights, lamps, electronic watches, cameras, gaming consoles, appliances, GPS devices, and wearable devices or so-called “wearables” (e.g., fitness bracelets, pedometers, smartwatch), among other types of electrical devices.

In some embodiments, the client device **105a** may be a physical device distinct from the receiver **103a** associated with the client device **105a**. In such embodiments, the client device **105a** may be connected to the receiver over a wire **111** that conveys converted electrical energy from the receiver **103a** to the client device **105a**. In some cases, other types of data may be transported over the wire **111**, such as power consumption status, power usage metrics, device identifiers, and other types of data.

In some embodiments, the client device **105b** may be permanently integrated or detachably coupled to the receiver **103b**, thereby forming a single integrated product or unit. As an example, the client device **105b** may be placed into a sleeve that has embedded receivers **103b** and that may detachably couple to the device’s **105b** power supply input, which may be typically used to charge the device’s **105b** battery. In this example, the device **105b** may be decoupled from the receiver, but may remain in the sleeve regardless of whether or not the device **105b** requires an electrical charge or is being used. In another example, in lieu of having a battery that holds a charge for the device **105b**, the device **105b** may comprise an integrated receiver **105b**, which may be permanently integrated into the device **105b** so as to form an indistinct product, device, or unit. In this example, the device **105b** may rely almost entirely on the integrated receiver **103b** to produce electrical energy by harvesting pockets of energy **104**. It should be clear to someone skilled in the art that the connection between the receiver **103** and the client device **105** may be a wire **111** or may be an electrical connection on a circuit board or an integrated circuit, or even a wireless connection, such as inductive or magnetic.

B. Method of Wireless Power Transmission

FIG. 2 shows steps of wireless power transmission, according to an exemplary method **200** embodiment.

In a first step **201**, a transmitter (TX) establishes a connection or otherwise associates with a receiver (RX). That is, in some embodiments, transmitters and receivers may communicate control data over using a wireless communication protocol capable of transmitting information between two processors of electrical devices (e.g., Bluetooth®, Bluetooth Low Energy (BLE), Wi-Fi, NFC, Zig-Bee®). For example, in embodiments implementing Bluetooth® or Bluetooth® variants, the transmitter may scan for receiver’s broadcasting advertisement signals or a receiver may transmit an advertisement signal to the transmitter. The advertisement signal may announce the receiver’s presence to the transmitter, and may trigger an association between the transmitter and the receiver. As described herein, in some embodiments, the advertisement signal may communicate information that may be used by various devices (e.g., transmitters, client devices, sever computers, other receivers) to execute and manage pocket-forming procedures. Information contained within the advertisement signal may include a device identifier (e.g., MAC address, IP address, UUID), the voltage of electrical energy received, client device power consumption, and other types of data related to power transmission. The transmitter may use the advertisement signal transmitted to identify the receiver and, in some cases, locate the receiver in a two-dimensional space or in a three-dimensional space. Once the transmitter identifies the receiver, the transmitter may establish the connection associated in the transmitter with the receiver, allowing the transmitter and receiver to communicate control signals over a second channel.

In a next step **203**, the transmitter may use the advertisement signal to determine a set of power transmission signal

features for transmitting the power transmission signals, to then establish the pockets of energy. Non-limiting examples of features of power transmission signals may include phase, gain, amplitude, magnitude, and direction among others. The transmitter may use information contained in the receiver's advertisement signal, or in subsequent control signals received from the receiver, to determine how to produce and transmit the power transmission signals so that the receiver may receive the power transmission signals. In some cases, the transmitter may transmit power transmission signals in a way that establishes a pocket of energy, from which the receiver may harvest electrical energy. In some embodiments, the transmitter may comprise a processor executing software modules capable of automatically identifying the power transmission signal features needed to establish a pocket of energy based on information received from the receiver, such as the voltage of the electrical energy harvested by the receiver from the power transmission signals. It should be appreciated that in some embodiments, the functions of the processor and/or the software modules may be implemented in an Application Specific Integrated Circuit (ASIC).

Additionally or alternatively, in some embodiments, the advertisement signal or subsequent signal transmitted by the receiver over a second communications channel may indicate one or more power transmission signals features, which the transmitter may then use to produce and transmit power transmission signals to establish a pocket of energy. For example, in some cases the transmitter may automatically identify the phase and gain necessary for transmitting the power transmission signals based on the location of the device and the type of device or receiver; and, in some cases, the receiver may inform the transmitter the phase and gain for effectively transmitting the power transmission signals.

In a next step **205**, after the transmitter determines the appropriate features to use when transmitting the power transmission signals, the transmitter may begin transmitting power transmission signals, over a separate channel from the control signals. Power transmission signals may be transmitted to establish a pocket of energy. The transmitter's antenna elements may transmit the power transmission signals such that the power transmission signals converge in a two-dimensional or three-dimensional space around the receiver. The resulting field around the receiver forms a pocket of energy from which the receiver may harvest electrical energy. One antenna element may be used to transmit power transmission signals to establish two-dimensional energy transmissions; and in some cases, a second or additional antenna element may be used to transmit power transmission signals in order to establish a three-dimensional pocket of energy. In some cases, a plurality of antenna elements may be used to transmit power transmission signals in order to establish the pocket of energy. Moreover, in some cases, the plurality of antennas may include all of the antennas in the transmitter; and, in some cases, the plurality of antennas may include a number of the antennas in the transmitter, but fewer than all of the antennas of the transmitter.

As previously mentioned, the transmitter may produce and transmit power transmission signals, according to a determined set of power transmission signal features, which may be produced and transmitted using an external power source and a local oscillator chip comprising a piezoelectric material. The transmitter may comprise an RFIC that controls production and transmission of the power transmission signals based on information related to power transmission and pocket-forming received from the receiver. This control

data may be communicated over a different channel from the power transmission signals, using wireless communications protocols, such as BLE, NFC, or ZigBee®. The RFIC of the transmitter may automatically adjust the phase and/or relative magnitudes of the power transmission signals as needed. Pocket-forming is accomplished by the transmitter transmitting the power transmission signals in a manner that forms constructive interference patterns.

Antenna elements of the transmitter may use concepts of wave interference to determine certain power transmission signals features (e.g., direction of transmission, phase of power transmission signal wave), when transmitting the power transmission signals during pocket-forming. The antenna elements may also use concepts of constructive interference to generate a pocket of energy, but may also utilize concepts of deconstructive interference to generate a transmission null in a particular physical location.

In some embodiments, the transmitter may provide power to a plurality of receivers using pocket-forming, which may require the transmitter to execute a procedure for multiple pocket-forming. A transmitter comprising a plurality of antenna elements may accomplish multiple pocket-forming by automatically computing the phase and gain of power transmission signal waves, for each antenna element of the transmitter tasked with transmitting power transmission signals the respective receivers. The transmitter may compute the phase and gains independently, because multiple wave paths for each power transmission signal may be generated by the transmitter's antenna elements to transmit the power transmission signals to the respective antenna elements of the receiver.

As an example of the computation of phase/gain adjustments for two antenna elements of the transmitter transmitting two signals, say X and Y where Y is 180 degree phase shifted version of X ($Y=-X$). At a physical location where the cumulative received waveform is $X-Y$, a receiver receives $X-Y=X+X=2X$, whereas at a physical location where the cumulative received waveform is $X+Y$, a receiver receives $X+Y=X-X=0$.

In a next step **207**, the receiver may harvest or otherwise receive electrical energy from power transmission signals of a single beam or a pocket of energy. The receiver may comprise a rectifier and AC/DC converter, which may convert the electrical energy from AC current to DC current, and a rectifier of the receiver may then rectify the electrical energy, resulting in useable electrical energy for a client device associated with the receiver, such as a laptop computer, smartphone, battery, toy, or other electrical device. The receiver may utilize the pocket of energy produced by the transmitter during pocket-forming to charge or otherwise power the electronic device.

In next step **209**, the receiver may generate control data containing information indicating the effectiveness of the single beam or energy pockets providing the receiver power transmission signals. The receiver may then transmit control signals containing the control data, to the transmitter. The control signals may be transmitted intermittently, depending on whether the transmitter and receiver are communicating synchronously (i.e., the transmitter is expecting to receive control data from the receiver). Additionally, the transmitter may continuously transmit the power transmission signals to the receiver, irrespective of whether the transmitter and receiver are communicating control signals. The control data may contain information related to transmitting power transmission signals and/or establishing effective pockets of energy. Some of the information in the control data may inform the transmitter how to effectively produce and trans-

mit, and in some cases adjust, the features of the power transmission signals. Control signals may be transmitted and received over a second channel, independent from the power transmission signals, using a wireless protocol capable of transmitting control data related to power transmission signals and/or pocket-forming, such as BLE, NFC, Wi-Fi, or the like.

As mentioned, the control data may contain information indicating the effectiveness of the power transmission signals of the single beam or establishing the pocket of energy. The control data may be generated by a processor of the receiver monitoring various aspects of receiver and/or the client device associated with the receiver. The control data may be based on various types of information, such as the voltage of electrical energy received from the power transmission signals, the quality of the power transmission signals reception, the quality of the battery charge or quality of the power reception, and location or motion of the receiver, among other types of information useful for adjusting the power transmission signals and/or pocket-forming.

In some embodiments, a receiver may determine the amount of power being received from power transmission signals transmitted from the transmitter and may then indicate that the transmitter should “split” or segment the power transmission signals into less-powerful power transmission signals. The less-powerful power transmission signals may be bounced off objects or walls nearby the device, thereby reducing the amount of power being transmitted directly from the transmitter to the receiver.

In a next step 211, the transmitter may calibrate the antennas transmitting the power transmission signals, so that the antennas transmit power transmission signals having a more effective set of feature (e.g., direction, phase, gain, amplitude). In some embodiments, a processor of the transmitter may automatically determine more effective features for producing and transmitting the power transmission signals based on a control signal received from the receiver. The control signal may contain control data, and may be transmitted by the receiver using any number of wireless communication protocols (e.g., BLE, Wi-Fi, ZigBee®). The control data may contain information expressly indicating the more effective features for the power transmission waves; or the transmitter may automatically determine the more effective features based on the waveform features of the control signal (e.g., shape, frequency, amplitude). The transmitter may then automatically reconfigure the antennas to transmit recalibrated power transmission signals according to the newly determined more-effective features. For example, the processor of the transmitter may adjust gain and/or phase of the power transmission signals, among other features of power transmission feature, to adjust for a change in location of the receiver, after a user moved the receiver outside of the three-dimensional space where the pocket of energy is established.

C. System Architecture of Power Transmission System

FIG. 3 illustrates an architecture 300 for wireless power transmission using pocket-forming, according to an exemplary embodiment. “Pocket-forming” may refer to generating two or more power transmission waves 342 that converge at a location in three-dimensional space, resulting in constructive interference patterns at that location. A transmitter 302 may transmit and/or broadcast controlled power transmission waves 342 (e.g., microwaves, radio waves, ultrasound waves) that may converge in three-dimensional space. These power transmission waves 342 may be controlled through phase and/or relative amplitude adjustments to form constructive interference patterns (pocket-forming)

in locations where a pocket of energy is intended. It should be understood also that the transmitter can use the same principles to create destructive interference in a location thereby creating a transmission null—a location where transmitted power transmission waves cancel each other out substantially and no significant energy can be collected by a receiver. In typical use cases the aiming of a power transmission signal at the location of the receiver is the objective; and in other cases it may be desirable to specifically avoid power transmission to a particular location; and in other cases it may be desirable to aim power transmission signal at a location while specifically avoiding transmission to a second location at the same time. The transmitter takes the use case into account when calibrating antennas for power transmission.

Antenna elements 306 of the transmitter 302 may operate in single array, pair array, quad array, or any other suitable arrangement that may be designed in accordance with the desired application. Pockets of energy may be formed at constructive interference patterns where the power transmission waves 342 accumulate to form a three-dimensional field of energy, around which one or more corresponding transmission null in a particular physical location may be generated by destructive interference patterns. Transmission null in a particular physical location may refer to areas or regions of space where pockets of energy do not form because of destructive interference patterns of power transmission waves 342.

A receiver 320 may then utilize power transmission waves 342 emitted by the transmitter 302 to establish a pocket of energy, for charging or powering an electronic device 313, thus effectively providing wireless power transmission. Pockets of energy may refer to areas or regions of space where energy or power may accumulate in the form of constructive interference patterns of power transmission waves 342. In other situations there can be multiple transmitters 302 and/or multiple receivers 320 for powering various electronic equipment for example smartphones, tablets, music players, toys and others at the same time. In other embodiments, adaptive pocket-forming may be used to regulate power on electronic devices. Adaptive pocket-forming may refer to dynamically adjusting pocket-forming to regulate power on one or more targeted receivers.

Receiver 320 may communicate with transmitter 302 by generating a short signal through antenna elements 324 in order to indicate its position with respect to the transmitter 302. In some embodiments, receiver 320 may additionally utilize a network interface card (not shown) or similar computer networking component to communicate through a network 340 with other devices or components of the system 300, such as a cloud computing service that manages several collections of transmitters 302. The receiver 320 may comprise circuitry 308 for converting the power transmission signals 342 captured by the antenna elements 324, into electrical energy that may be provided to and electric device 313 and/or a battery of the device 315. In some embodiments, the circuitry may provide electrical energy to a battery of receiver 335, which may store energy without the electrical device 313 being communicatively coupled to the receiver 320.

Communications components 324 may enable receiver 320 to communicate with the transmitter 302 by transmitting control signals 345 over a wireless protocol. The wireless protocol can be a proprietary protocol or use a conventional wireless protocol, such as Bluetooth®, BLE, Wi-Fi, NFC, ZigBee, and the like. Communications component 324 may then be used to transfer information, such as an identifier for

the electronic device **313**, as well as battery level information, geographic location data, or other information that may be of use for transmitter **302** in determining when to send power to receiver **320**, as well as the location to deliver power transmission waves **342** creating pockets of energy. In other embodiments, adaptive pocket-forming may be used to regulate power provided to electronic devices **313**. In such embodiments, the communications components **324** of the receiver may transmit voltage data indicating the amount of power received at the receiver **320**, and/or the amount of voltage provided to an electronic device **313b** or battery **315**.

Once transmitter **302** identifies and locates receiver **320**, a channel or path for the control signals **345** can be established, through which the transmitter **302** may know the gain and phases of the control signals **345** coming from receiver **320**. Antenna elements **306** of the transmitter **302** may start to transmit or broadcast controlled power transmission waves **342** (e.g., radio frequency waves, ultrasound waves), which may converge in three-dimensional space by using at least two antenna elements **306** to manipulate the power transmission waves **342** emitted from the respective antenna element **306**. These power transmission waves **342** may be produced by using an external power source and a local oscillator chip using a suitable piezoelectric material. The power transmission waves **342** may be controlled by transmitter circuitry **301**, which may include a proprietary chip for adjusting phase and/or relative magnitudes of power transmission waves **342**. The phase, gain, amplitude, and other waveform features of the power transmission waves **342** may serve as inputs for antenna element **306** to form constructive and destructive interference patterns (pocket-forming). In some implementations, a micro-controller **310** or other circuit of the transmitter **302** may produce a power transmission signal, which comprises power transmission waves **342**, and that may be split into multiple outputs by transmitter circuitry **301**, depending on the number of antenna elements **306** connected to the transmitter circuitry **301**. For example, if four antenna elements **306a-d** are connected to one transmitter circuit **301a**, the power transmission signal will be split into four different outputs each output going to an antenna element **306** to be transmitted as power transmission waves **342** originating from the respective antenna elements **306**.

Pocket-forming may take advantage of interference to change the directionality of the antenna element **306** where constructive interference generates a pocket of energy and destructive interference generates a transmission null. Receiver **320** may then utilize pocket of energy produced by pocket-forming for charging or powering an electronic device and therefore effectively providing wireless power transmission.

Multiple pocket-forming may be achieved by computing the phase and gain from each antenna **306** of transmitter **302** to each receiver **320**.

D. Components of Systems Forming Pockets of Energy

FIG. 4 shows components of an exemplary system **400** of wireless power transmission using pocket-forming procedures. The system **400** may comprise one or more transmitters **402**, one or more receivers **420**, and one or more client devices **446**.

1. Transmitters

Transmitters **402** may be any device capable of broadcasting wireless power transmission signals, which may be RF waves **442**, for wireless power transmission, as described herein. Transmitters **402** may be responsible for performing tasks related to transmitting power transmission signals, which may include pocket-forming, adaptive pocket-form-

ing, and multiple pocket-forming. In some implementations, transmitters **402** may transmit wireless power transmissions to receivers **420** in the form of RF waves, which may include any radio signal having any frequency or wavelength. A transmitter **402** may include one or more antenna elements **406**, one or more RFICs **408**, one or more microcontrollers **410**, one or more communication components **412**, a power source **414**, and a housing that may allocate all the requested components for the transmitter **402**. The various components of transmitters **402** may comprise, and/or may be manufactured using, meta-materials, micro-printing of circuits, nano-materials, and the like.

In the exemplary system **400**, the transmitter **402** may transmit or otherwise broadcast controlled RF waves **442** that converge at a location in three-dimensional space, thereby forming a pocket of energy **444**. These RF waves may be controlled through phase and/or relative amplitude adjustments to form constructive or destructive interference patterns (i.e., pocket-forming). Pockets of energy **444** may be fields formed at constructive interference patterns and may be three-dimensional in shape; whereas transmission null in a particular physical location may be generated at destructive interference patterns. Receivers **420** may harvest electrical energy from the pockets of energy **444** produced by pocket-forming for charging or powering an electronic client device **446** (e.g., a laptop computer, a cell phone). In some embodiments, the system **400** may comprise multiple transmitters **402** and/or multiple receivers **420**, for powering various electronic equipment. Non-limiting examples of client devices **446** may include: smartphones, tablets, music players, toys and others at the same time. In some embodiments, adaptive pocket-forming may be used to regulate power on electronic devices.

2. Receivers

Receivers **420** may include a housing where at least one antenna element **424**, one rectifier **426**, one power converter **428**, and a communications component **430** may be included.

Housing of the receiver **420** can be made of any material capable of facilitating signal or wave transmission and/or reception, for example plastic or hard rubber. Housing may be an external hardware that may be added to different electronic equipment, for example in the form of cases, or can be embedded within electronic equipment as well.

3. Antenna Elements

Antenna elements **424** of the receiver **420** may comprise any type of antenna capable of transmitting and/or receiving signals in frequency bands used by the transmitter **402A**. Antenna elements **424** may include vertical or horizontal polarization, right hand or left hand polarization, elliptical polarization, or other polarizations, as well as any number of polarization combinations. Using multiple polarizations can be beneficial in devices where there may not be a preferred orientation during usage or whose orientation may vary continuously through time, for example a smartphone or portable gaming system. For devices having a well-defined expected orientation (e.g., a two-handed video game controller), there might be a preferred polarization for antennas, which may dictate a ratio for the number of antennas of a given polarization. Types of antennas in antenna elements **424** of the receiver **420**, may include patch antennas, which may have heights from about 1/8 inch to about 6 inches and widths from about 1/8 inch to about 6 inches. Patch antennas may preferably have polarization that depends upon connectivity, i.e., the polarization may vary depending on from which side the patch is fed. In some embodiments, the type of antenna may be any type of antenna, such as patch

antennas, capable of dynamically varying the antenna polarization to optimize wireless power transmission.

4. Rectifier

Rectifiers **426** of the receiver **420** may include diodes, resistors, inductors, and/or capacitors to rectify alternating current (AC) voltage generated by antenna elements **424** to direct current (DC) voltage. Rectifiers **426** may be placed as close as is technically possible to antenna elements **A24B** to minimize losses in electrical energy gathered from power transmission signals. After rectifying AC voltage, the resulting DC voltage may be regulated using power converters **428**. Power converters **428** can be a DC-to-DC converter that may help provide a constant voltage output, regardless of input, to an electronic device, or as in this exemplary system **400**, to a battery. Typical voltage outputs can be from about 5 volts to about 10 volts. In some embodiments, power converter may include electronic switched mode DC-DC converters, which can provide high efficiency. In such embodiments, the receiver **420** may comprise a capacitor (not shown) that is situated to receive the electrical energy before power converters **428**. The capacitor may ensure sufficient current is provided to an electronic switching device (e.g., switch mode DC-DC converter), so it may operate effectively. When charging an electronic device, for example a phone or laptop computer, initial high-currents that can exceed the minimum voltage needed to activate operation of an electronic switched mode DC-DC converter, may be required. In such a case, a capacitor (not shown) may be added at the output of receivers **420** to provide the extra energy required. Afterwards, lower power can be provided. For example, $\frac{1}{80}$ of the total initial power that may be used while having the phone or laptop still build-up charge.

5. Communications Component

A communications component **430** of a receiver **420** may communicate with one or more other devices of the system **400**, such as other receivers **420**, client devices, and/or transmitters **402**. Different antenna, rectifier or power converter arrangements are possible for a receiver as will be explained in following embodiments.

E. Methods of Pocket Forming for a Plurality of Devices

FIG. **5** shows steps of powering a plurality of receiver devices, according to an exemplary embodiment.

In a first step **501**, a transmitter (TX) establishes a connection or otherwise associates with a receiver (RX). That is, in some embodiments, transmitters and receivers may communicate control data over using a wireless communication protocol capable of transmitting information between two processors of electrical devices (e.g., Bluetooth®, BLE, Wi-Fi, NFC, ZigBee®). For example, in embodiments implement Bluetooth® or Bluetooth® variants, the transmitter may scan for receiver's broadcasting advertisement signals or a receiver may transmit an advertisement signal to the transmitter. The advertisement signal may announce the receiver's presence to the transmitter, and may trigger an association between the transmitter and the receiver. As described later, in some embodiments, the advertisement signal may communicate information that may be used by various devices (e.g., transmitters, client devices, sever computers, other receivers) to execute and manage pocket-forming procedures. Information contained within the advertisement signal may include a device identifier (e.g., MAC address, IP address, UUID), the voltage of electrical energy received, client device power consumption, and other types of data related to power transmission waves. The transmitter may use the advertisement signal transmitted to identify the receiver and, in some cases, locate the receiver in a two-dimensional space or in a three-dimen-

sional space. Once the transmitter identifies the receiver, the transmitter may establish the connection associated in the transmitter with the receiver, allowing the transmitter and receiver to communicate control signals over a second channel.

As an example, when a receiver comprising a Bluetooth® processor is powered-up or is brought within a detection range of the transmitter, the Bluetooth processor may begin advertising the receiver according to Bluetooth® standards. The transmitter may recognize the advertisement and begin establishing connection for communicating control signals and power transmission signals. In some embodiments, the advertisement signal may contain unique identifiers so that the transmitter may distinguish that advertisement and ultimately that receiver from all the other Bluetooth® devices nearby within range.

In a next step **503**, when the transmitter detects the advertisement signal, the transmitter may automatically form a communication connection with that receiver, which may allow the transmitter and receiver to communicate control signals and power transmission signals. The transmitter may then command that receiver to begin transmitting real-time sample data or control data. The transmitter may also begin transmitting power transmission signals from antennas of the transmitter's antenna array.

In a next step **505**, the receiver may then measure the voltage, among other metrics related to effectiveness of the power transmission signals, based on the electrical energy received by the receiver's antennas. The receiver may generate control data containing the measured information, and then transmit control signals containing the control data to the transmitter. For example, the receiver may sample the voltage measurements of received electrical energy, for example, at a rate of 100 times per second. The receiver may transmit the voltage sample measurement back to the transmitter, 100 times a second, in the form of control signals.

In a next step **507**, the transmitter may execute one or more software modules monitoring the metrics, such as voltage measurements, received from the receiver. Algorithms may vary production and transmission of power transmission signals by the transmitter's antennas, to maximize the effectiveness of the pockets of energy around the receiver. For example, the transmitter may adjust the phase at which the transmitter's antenna transmit the power transmission signals, until that power received by the receiver indicates an effectively established pocket energy around the receiver. When an optimal configuration for the antennas is identified, memory of the transmitter may store the configurations to keep the transmitter broadcasting at that highest level.

In a next step **509**, algorithms of the transmitter may determine when it is necessary to adjust the power transmission signals and may also vary the configuration of the transmit antennas, in response to determining such adjustments are necessary. For example, the transmitter may determine the power received at a receiver is less than maximal, based on the data received from the receiver. The transmitter may then automatically adjust the phase of the power transmission signals, but may also simultaneously continue to receive and monitor the voltage being reported back from receiver.

In a next step **511**, after a determined period of time for communicating with a particular receiver, the transmitter may scan and/or automatically detect advertisements from other receivers that may be in range of the transmitter. The

transmitters may establish a connection to the second receiver responsive to Bluetooth® advertisements from a second receiver.

In a next step **513**, after establishing a second communication connection with the second receiver, the transmitter may proceed to adjust one or more antennas in the transmitter's antenna array. In some embodiments, the transmitter may identify a subset of antennas to service the second receiver, thereby parsing the array into subsets of arrays that are associated with a receiver. In some embodiments, the entire antenna array may service a first receiver for a given period of time, and then the entire array may service the second receiver for that period of time.

Manual or automated processes performed by the transmitter may select a subset of arrays to service the second receiver. In this example, the transmitter's array may be split in half, forming two subsets. As a result, half of the antennas may be configured to transmit power transmission signals to the first receiver, and half of the antennas may be configured for the second receiver. In the current step **513**, the transmitter may apply similar techniques discussed above to configure or optimize the subset of antennas for the second receiver. While selecting a subset of an array for transmitting power transmission signals, the transmitter and second receiver may be communicating control data. As a result, by the time that the transmitter alternates back to communicating with the first receiver and/or scan for new receivers, the transmitter has already received a sufficient amount of sample data to adjust the phases of the waves transmitted by second subset of the transmitter's antenna array, to transmit power transmission waves to the second receiver effectively.

In a next step **515**, after adjusting the second subset to transmit power transmission signals to the second receiver, the transmitter may alternate back to communicating control data with the first receiver, or scanning for additional receivers. The transmitter may reconfigure the antennas of the first subset, and then alternate between the first and second receivers at a predetermined interval.

In a next step **517**, the transmitter may continue to alternate between receivers and scanning for new receivers, at a predetermined interval. As each new receiver is detected, the transmitter may establish a connection and begin transmitting power transmission signals, accordingly.

In one exemplary embodiment, the receiver may be electrically connected to a device like a smart phone. The transmitter's processor would scan for any Bluetooth devices. The receiver may begin advertising that it's a Bluetooth device through the Bluetooth chip. Inside the advertisement, there may be unique identifiers so that the transmitter, when it scanned that advertisement, could distinguish that advertisement and ultimately that receiver from all the other Bluetooth devices nearby within range. When the transmitter detects that advertisement and notices it is a receiver, then the transmitter may immediately form a communication connection with that receiver and command that receiver to begin sending real time sample data.

The receiver would then measure the voltage at its receiving antennas, send that voltage sample measurement back to the transmitter (e.g., 100 times a second). The transmitter may start to vary the configuration of the transmit antennas by adjusting the phase. As the transmitter adjusts the phase, the transmitter monitors the voltage being sent back from the receiver. In some implementations, the higher the voltage, the more energy may be in the pocket. The antenna phases may be altered until the voltage is at the highest level and there is a maximum pocket of energy around the receiver.

The transmitter may keep the antennas at the particular phase so the voltage is at the highest level.

The transmitter may vary each individual antenna, one at a time. For example, if there are 32 antennas in the transmitter, and each antenna has 8 phases, the transmitter may begin with the first antenna and would step the first antenna through all 8 phases. The receiver may then send back the power level for each of the 8 phases of the first antenna. The transmitter may then store the highest phase for the first antenna. The transmitter may repeat this process for the second antenna, and step it through 8 phases. The receiver may again send back the power levels from each phase, and the transmitter may store the highest level. Next the transmitter may repeat the process for the third antenna and continue to repeat the process until all 32 antennas have stepped through the 8 phases. At the end of the process, the transmitter may transmit the maximum voltage in the most efficient manner to the receiver.

In another exemplary embodiment, the transmitter may detect a second receiver's advertisement and form a communication connection with the second receiver. When the transmitter forms the communication with the second receiver, the transmitter may aim the original 32 antennas towards the second receiver and repeat the phase process for each of the 32 antennas aimed at the second receiver. Once the process is completed, the second receiver may get as much power as possible from the transmitter. The transmitter may communicate with the second receiver for a second, and then alternate back to the first receiver for a predetermined period of time (e.g., a second), and the transmitter may continue to alternate back and forth between the first receiver and the second receiver at the predetermined time intervals.

In yet another implementation, the transmitter may detect a second receiver's advertisement and form a communication connection with the second receiver. First, the transmitter may communicate with the first receiver and re-assign half of the exemplary **32** the antennas aimed at the first receiver, dedicating only 16 towards the first receiver. The transmitter may then assign the second half of the antennas to the second receiver, dedicating 16 antennas to the second receiver. The transmitter may adjust the phases for the second half of the antennas. Once the 16 antennas have gone through each of the 8 phases, the second receiver may be obtaining the maximum voltage in the most efficient manner to the receiver.

F. Wireless Power Transmission with Selective Range 1. Constructive Interference

FIG. **6A** and FIG. **6B** show an exemplary system **600** implementing wireless power transmission principles that may be implemented during exemplary pocket-forming processes. A transmitter **601** comprising a plurality of antennas in an antenna array, may adjust the phase and amplitude, among other possible attributes, of power transmission waves **607**, being transmitted from antennas of the transmitter **601**. As shown in FIG. **6A**, in the absence of any phase or amplitude adjustment, power transmission waves **607a** may be transmitted from each of the antennas will arrive at different locations and have different phases. These differences are often due to the different distances from each antenna element of the transmitter **601a** to a receiver **605a** or receivers **605a**, located at the respective locations.

Continuing with FIG. **6A**, a receiver **605a** may receive multiple power transmission signals, each comprising power transmission waves **607a**, from multiple antenna elements of a transmitter **601a**; the composite of these power transmission signals may be essentially zero, because in this

example, the power transmission waves add together destructively. That is, antenna elements of the transmitter **601a** may transmit the exact same power transmission signal (i.e., comprising power transmission waves **607a** having the same features, such as phase and amplitude), and as such, when the power transmission waves **607a** of the respective power transmission signals arrive at the receiver **605a**, they are offset from each other by 180 degrees. Consequently, the power transmission waves **607a** of these power transmission signals “cancel” one another. Generally, signals offsetting one another in this way may be referred to as “destructive,” and thus result in “destructive interference.”

In contrast, as shown in FIG. 6B, for so-called “constructive interference,” signals comprising power transmission waves **607b** that arrive at the receiver exactly “in phase” with one another, combine to increase the amplitude of the each signal, resulting in a composite that is stronger than each of the constituent signals. In the illustrative example in FIG. 6A, note that the phase of the power transmission waves **607a** in the transmit signals are the same at the location of transmission, and then eventually add up destructively at the location of the receiver **605a**. In contrast, in FIG. 6B, the phase of the power transmission waves **607b** of the transmit signals are adjusted at the location of transmission, such that they arrive at the receiver **605b** in phase alignment, and consequently they add constructively. In this illustrative example, there will be a resulting pocket of energy located around the receiver **605b** in FIG. 6B; and there will be a transmission null located around receiver in FIG. 6A.

FIG. 7 depicts wireless power transmission with selective range **700**, where a transmitter **702** may produce pocket-forming for a plurality of receivers associated with electrical devices **701**. Transmitter **702** may generate pocket-forming through wireless power transmission with selective range **700**, which may include one or more wireless charging radii **704** and one or more radii of a transmission null at a particular physical location **706**. A plurality of electronic devices **701** may be charged or powered in wireless charging radii **704**. Thus, several spots of energy may be created, such spots may be employed for enabling restrictions for powering and charging electronic devices **701**. As an example, the restrictions may include operating specific electronics in a specific or limited spot, contained within wireless charging radii **704**. Furthermore, safety restrictions may be implemented by the use of wireless power transmission with selective range **700**, such safety restrictions may avoid pockets of energy over areas or zones where energy needs to be avoided, such areas may include areas including sensitive equipment to pockets of energy and/or people which do not want pockets of energy over and/or near them. In embodiments such as the one shown in FIG. 7, the transmitter **702** may comprise antenna elements found on a different plane than the receivers associated with electrical devices **701** in the served area. For example the receivers of electrical devices **701** may be in a room where a transmitter **702** may be mounted on the ceiling. Selective ranges for establishing pockets of energy using power transmission waves, which may be represented as concentric circles by placing an antenna array of the transmitter **702** on the ceiling or other elevated location, and the transmitter **702** may emit power transmission waves that will generate ‘cones’ of energy pockets. In some embodiments, the transmitter **701** may control the radius of each charging radii **704**, thereby establishing intervals for service area to create pockets of energy that are pointed down to an area at a lower plane,

which may adjust the width of the cone through appropriate selection of antenna phase and amplitudes.

FIG. 8 depicts wireless power transmission with selective range **800**, where a transmitter **802** may produce pocket-forming for a plurality of receivers **806**. Transmitter **802** may generate pocket-forming through wireless power transmission with selective range **800**, which may include one or more wireless charging spots **804**. A plurality of electronic devices may be charged or powered in wireless charging spots **804**. Pockets of energy may be generated over a plurality of receivers **806** regardless the obstacles **804** surrounding them. Pockets of energy may be generated by creating constructive interference, according to the principles described herein, in wireless charging spots **804**. Location of pockets of energy may be performed by tacking receivers **806** and by enabling a plurality of communication protocols by a variety of communication systems such as, Bluetooth® technology, infrared communication, Wi-Fi, FM radio, among others.

G. Exemplary System Embodiment Using Heat Maps

FIGS. 9A and 9B illustrate a diagram of architecture **900A**, **900B** for a wirelessly charging client computing platform, according to an exemplary embodiment. In some implementations, a user may be inside a room and may hold on his hands an electronic device (e.g. a smartphone, tablet). In some implementations, electronic device may be on furniture inside the room. The electronic device may include a receiver **920A**, **920B** either embedded to the electronic device or as a separate adapter connected to electronic device. Receivers **920A**, **920B** may include all the components described in FIG. 11. A transmitter **902A**, **902B** may be hanging on one of the walls of the room right behind user. Transmitters **902A**, **902B** may also include all the components described in FIG. 11.

As user may seem to be obstructing the path between receivers **920A**, **920B** and transmitters **902A**, **902B**, RF waves may not be easily aimed to the receivers **920A**, **920B** in a linear direction. However, since the short signals generated from receivers **920A**, **920B** may be omnidirectional for the type of antenna element used, these signals may bounce over the walls **944A**, **944B** until they reach transmitters **902A**, **902B**. A hot spot **944A**, **944B** may be any item in the room which will reflect the RF waves. For example, a large metal clock on the wall may be used to reflect the RF waves to a user’s cell phone.

A micro controller in the transmitter adjusts the transmitted signal from each antenna based on the signal received from the receiver. Adjustment may include forming conjugates of the signal phases received from the receivers and further adjustment of transmit antenna phases taking into account the built-in phase of antenna elements. The antenna element may be controlled simultaneously to steer energy in a given direction. The transmitter **902A**, **902B** may scan the room, and look for hot spots **944A**, **944B**. Once calibration is performed, transmitters **902A**, **902B** may focus RF waves in a channel following a path that may be the most efficient paths. Subsequently, RF signals **942A**, **942B** may form a pocket of energy on a first electronic device and another pocket of energy in a second electronic device while avoiding obstacles such as user and furniture.

When scanning the service area, the room in FIGS. 9A and 9B, the transmitter **902A**, **902B** may employ different methods. As an illustrative example, but without limiting the possible methods that can be used, the transmitter **902A**, **902B** may detect the phases and magnitudes of the signal coming from the receiver and use those to form the set of transmit phases and magnitudes, for example by calculating

conjugates of them and applying them at transmit. As another illustrative example, the transmitter may apply all possible phases of transmit antennas in subsequent transmissions, one at a time, and detect the strength of the pocket of energy formed by each combination by observing information related to the signal from the receiver 920A, 920B. Then the transmitter 902A, 902B repeats this calibration periodically. In some implementations, the transmitter 902A, 902B does not have to search through all possible phases, and can search through a set of phases that are more likely to result in strong pockets of energy based on prior calibration values. In yet another illustrative example, the transmitter 902A, 902B may use preset values of transmit phases for the antennas to form pockets of energy directed to different locations in the room. The transmitter may for example scan the physical space in the room from top to bottom and left to right by using preset phase values for antennas in subsequent transmissions. The transmitter 902A, 902B then detects the phase values that result in the strongest pocket of energy around the receiver 920a, 920b by observing the signal from the receiver 920a, 920b. It should be appreciated that there are other possible methods for scanning a service area for heat mapping that may be employed, without deviating from the scope or spirit of the embodiments described herein. The result of a scan, whichever method is used, is a heat-map of the service area (e.g., room, store) from which the transmitter 902A, 902B may identify the hot spots that indicate the best phase and magnitude values to use for transmit antennas in order to maximize the pocket of energy around the receiver.

The transmitters 902A, 902B, may use the Bluetooth connection to determine the location of the receivers 920A, 920B, and may use different non-overlapping parts of the RF band to channel the RF waves to different receivers 920A, 920B. In some implementations, the transmitters 902A, 902B, may conduct a scan of the room to determine the location of the receivers 920A, 920B and forms pockets of energy that are orthogonal to each other, by virtue of non-overlapping RF transmission bands. Using multiple pockets of energy to direct energy to receivers may inherently be safer than some alternative power transmission methods since no single transmission is very strong, while the aggregate power transmission signal received at the receiver is strong.

H. Exemplary System Embodiment

FIG. 10A illustrates wireless power transmission using multiple pocket-forming 1000A that may include one transmitter 1002A and at least two or more receivers 1020A. Receivers 1020A may communicate with transmitters 1002A, which is further described in FIG. 11. Once transmitter 1002A identifies and locates receivers 1020A, a channel or path can be established by knowing the gain and phases coming from receivers 1020A. Transmitter 1002A may start to transmit controlled RF waves 1042A which may converge in three-dimensional space by using a minimum of two antenna elements. These RF waves 1042A may be produced using an external power source and a local oscillator chip using a suitable piezoelectric material. RF waves 1042A may be controlled by RFIC, which may include a proprietary chip for adjusting phase and/or relative magnitudes of RF signals that may serve as inputs for antenna elements to form constructive and destructive interference patterns (pocket-forming). Pocket-forming may take advantage of interference to change the directionality of the antenna elements where constructive interference generates a pocket of energy 1060A and destructive interference generates a transmission null. Receivers 1020A may then

utilize pocket of energy 1060A produced by pocket-forming for charging or powering an electronic device, for example, a laptop computer 1062A and a smartphone 1052A and thus effectively providing wireless power transmission.

Multiple pocket forming 1000A may be achieved by computing the phase and gain from each antenna of transmitter 1002A to each receiver 1020A. The computation may be calculated independently because multiple paths may be generated by antenna element from transmitter 1002A to antenna element from receivers 1020A.

I. Exemplary System Embodiment

FIG. 10B is an exemplary illustration of multiple adaptive pocket-forming 1000B. In this embodiment, a user may be inside a room and may hold on his hands an electronic device, which in this case may be a tablet 1064B. In addition, smartphone 1052B may be on furniture inside the room. Tablet 1064B and smartphone 1052B may each include a receiver either embedded to each electronic device or as a separate adapter connected to tablet 1064B and smartphone 1052B. Receiver may include all the components described in FIG. 11. A transmitter 1002B may be hanging on one of the walls of the room right behind user. Transmitter 1002B may also include all the components described in FIG. 11. As user may seem to be obstructing the path between receiver and transmitter 1002B, RF waves 1042B may not be easily aimed to each receiver in a line of sight fashion. However, since the short signals generated from receivers may be omni-directional for the type of antenna elements used, these signals may bounce over the walls until they find transmitter 1002B. Almost instantly, a micro-controller which may reside in transmitter 1002B, may recalibrate the transmitted signals, based on the received signals sent by each receiver, by adjusting gain and phases and forming a convergence of the power transmission waves such that they add together and strengthen the energy concentrated at that location—in contrast to adding together in a way to subtract from each other and diminish the energy concentrated at that location, which is called “destructive interference” and conjugates of the signal phases received from the receivers and further adjustment of transmit antenna phases taking into account the built-in phase of antenna elements. Once calibration is performed, transmitter 1002B may focus RF waves following the most efficient paths. Subsequently, a pocket of energy 1060B may form on tablet 1064B and another pocket of energy 1060B in smartphone 1052B while taking into account obstacles such as user and furniture. The foregoing property may be beneficial in that wireless power transmission using multiple pocket-forming 1000B may inherently be safe as transmission along each pocket of energy is not very strong, and that RF transmissions generally reflect from living tissue and do not penetrate.

Once transmitter 1002B identifies and locates receiver, a channel or path can be established by knowing the gain and phases coming from receiver. Transmitter 1002B may start to transmit controlled RF waves 1042B that may converge in three-dimensional space by using a minimum of two antenna elements. These RF waves 1042B may be produced using an external power source and a local oscillator chip using a suitable piezoelectric material. RF waves 1042B may be controlled by RFIC that may include a proprietary chip for adjusting phase and/or relative magnitudes of RF signals, which may serve as inputs for antenna elements to form constructive and destructive interference patterns (pocket-forming). Pocket-forming may take advantage of interference to change the directionality of the antenna elements where constructive interference generates a pocket

of energy and deconstructive interference generates a null in a particular physical location. Receiver may then utilize pocket of energy produced by pocket-forming for charging or powering an electronic device, for example a laptop computer and a smartphone and thus effectively providing wireless power transmission.

Multiple pocket-forming **1000B** may be achieved by computing the phase and gain from each antenna of transmitter to each receiver. The computation may be calculated independently because multiple paths may be generated by antenna elements from transmitter to antenna elements from receiver.

An example of the computation for at least two antenna elements may include determining the phase of the signal from the receiver and applying the conjugate of the receive parameters to the antenna elements for transmission.

In some embodiments, two or more receivers may operate at different frequencies to avoid power losses during wireless power transmission. This may be achieved by including an array of multiple embedded antenna elements in transmitter **1002B**. In one embodiment, a single frequency may be transmitted by each antenna in the array. In other embodiments some of the antennas in the array may be used to transmit at a different frequency. For example, $\frac{1}{2}$ of the antennas in the array may operate at 2.4 GHz while the other $\frac{1}{2}$ may operate at 5.8 GHz. In another example, $\frac{1}{3}$ of the antennas in the array may operate at 900 MHz, another $\frac{1}{3}$ may operate at 2.4 GHz, and the remaining antennas in the array may operate at 5.8 GHz.

In another embodiment, each array of antenna elements may be virtually divided into one or more antenna elements during wireless power transmission, where each set of antenna elements in the array can transmit at a different frequency. For example, an antenna element of the transmitter may transmit power transmission signals at 2.4 GHz, but a corresponding antenna element of a receiver may be configured to receive power transmission signals at 5.8 GHz. In this example, a processor of the transmitter may adjust the antenna element of the transmitter to virtually or logically divide the antenna elements in the array into a plurality of patches that may be fed independently. As a result, $\frac{1}{4}$ of the array of antenna elements may be able to transmit the 5.8 GHz needed for the receiver, while another set of antenna elements may transmit at 2.4 GHz. Therefore, by virtually dividing an array of antenna elements, electronic devices coupled to receivers can continue to receive wireless power transmission. The foregoing may be beneficial because, for example, one set of antenna elements may transmit at about 2.4 GHz and other antenna elements may transmit at 5.8 GHz, and thus, adjusting a number of antenna elements in a given array when working with receivers operating at different frequencies. In this example, the array is divided into equal sets of antenna elements (e.g., four antenna elements), but the array may be divided into sets of different amounts of antenna elements. In an alternative embodiment, each antenna element may alternate between select frequencies.

The efficiency of wireless power transmission as well as the amount of power that can be delivered (using pocket-forming) may be a function of the total number of antenna elements **1006** used in a given receivers and transmitters system. For example, for delivering about one watt at about 15 feet, a receiver may include about 80 antenna elements while a transmitter may include about 256 antenna elements. Another identical wireless power transmission system (about 1 watt at about 15 feet) may include a receiver with about 40 antenna elements, and a transmitter with about 512 antenna elements. Reducing in half the number of antenna

elements in a receiver may require doubling the number of antenna elements in a transmitter. In some embodiments, it may be beneficial to put a greater number of antenna elements in transmitters than in a receivers because of cost, because there will be much fewer transmitters than receivers in a system-wide deployment. However, the opposite can be achieved, e.g., by placing more antenna elements on a receiver than on a transmitter as long as there are at least two antenna elements in a transmitter **1002B**.

II. Transmitters—Systems and Methods for Wireless Power Transmissions

Transmitters may be responsible for the pocket-forming, adaptive pocket-forming and multiple pocket-forming using the components described below. Transmitters may transmit wireless power transmission signals to receivers in the form of any physical media capable of propagating through space and being converted into useable electrical energy; examples may include RF waves, infrared, acoustics, electromagnetic fields, and ultrasound. It should be appreciated by those skilled in the art that power transmission signals may be most any radio signal, having any frequency or wavelength. Transmitters are described within with reference to RF transmissions, only as an example, and not to limit the scope to RF transmission only.

Transmitters may be located in number of locations, surfaces, mountings, or embedded structures, such as, desks, tables, floors, walls, and the like. In some cases, transmitters may be located in a client computing platforms, which may be any computing device comprising processors and software modules capable of executing the processes and tasks described herein. Non-limiting examples of client computing platforms may include a desktop computer, a laptop computer, a handheld computer, a tablet computing platform, a netbook, a smartphone, a gaming console, and/or other computing platforms. In other embodiments, the client computing platforms may be a variety of electronic computing devices. In such embodiments, each of the client computing platforms may have distinct operating systems, and/or physical components. The client computing platforms may be executing the same operating system and/or the client computing platforms may be executing different operating systems. The client computing platforms and or devices may be capable of executing multiple operating systems. In addition, box transmitters may contain several arrangements of printed circuit board (PCB) layers, which may be oriented in X, Y, or Z axis, or in any combination of these.

It should be appreciated that wireless charging techniques are not limited to RF wave transmission techniques, but may include alternative or additional techniques for transmitting energy to a receiver converting the transmitted energy to electrical power. Non-limiting exemplary transmission techniques for energy that can be converted by a receiving device into electrical power may include: ultrasound, micro-wave, resonant and inductive magnetic fields, laser light, infrared, or other forms of electromagnetic energy. In the case of ultrasound, for example, one or more transducer elements may be disposed so as to form a transducer array that transmits ultrasound waves toward a receiving device that receives the ultrasound waves and converts them to electrical power. In the case of resonant or inductive magnetic fields, magnetic fields are created in a transmitter coil and converted by a receiver coil into electrical power.

A. Components of Transmitter Devices

FIG. **11** illustrates a diagram of a system **1100** architecture for wirelessly charging client devices, according to an exemplary embodiment. The system **1100** may comprise a

transmitter **1101** and a receiver **1120** that may each comprise an application-specific integrated circuit (ASIC). The transmitter **1101** ASIC may include one or more printed circuit boards (PCB) **1104**, one or more antenna elements **1106**, one or more radio frequency integrated circuits (RFIC) **1108**,
 5 one or more microcontrollers (MCs) **1110**, a communication component **1112**, a power source **1114**. The transmitter **1101** may be encased in a housing, which may allocate all the requested components for transmitter **1101**. Components in transmitter **1101** may be manufactured using meta-materials,
 10 micro-printing of circuits, nano-materials, and/or any other materials. It should be obvious to someone skilled in the art that the entire transmitter or the entire receiver can be implemented on a single circuit board, as well as having one or more of the functional blocks implemented in separate circuit boards.

1. Printed Circuit Boards

In some implementations, the transmitter **1101** may include a plurality of PCB **1104** layers, which may include
 20 antenna element **1106** and/or RFIC **1108** for providing greater control over pocket-forming and may increase response for targeting receivers. The PCB **1104** may mechanically support and electrically connect the electronic component described herein using conductive tracks, pads
 25 and/or other features etched from copper sheets laminated onto a non-conductive substrate. PCBs may be single sided (one copper layer), double sided (two copper layers), and/or multi-layer. Multiple PCB **1104** layers may increase the range and the amount of power that could be transferred by
 30 transmitter **1101**. PCB **1104** layers may be connected to a single MC **1110** and/or to dedicated MCs **1110**. Similarly, RFIC **1108** may be connected to antenna element **1106** as depicted in the foregoing embodiments.

In some implementations, a box transmitter, including a
 35 plurality of PCB **1104** layers inside it may include antenna element **1108** for providing greater control over pocket-forming and may increase the response for targeting receivers. Furthermore, range of wireless power transmission may be increased by the box transmitter. Multiple PCB **1104**
 40 layers may increase the range and the amount of power waves (e.g., RF power waves, ultrasound waves) that could be transferred and/or broadcasted wirelessly by transmitter **1101** due the higher density of antenna element **1106**. The PCB **1104** layers may be connected to a single microcon-
 45 troller **1110** and/or to dedicated microcontroller **1110** for each antenna element **1106**. Similarly, RFIC **1108** may control antenna element **1101** as depicted in the foregoing embodiments. Furthermore, box shape of transmitter **1101** may increase action ratio of wireless power transmission.

2. Antenna Elements

Antenna element **1106** may be directional and/or omni-
 50 directional and include flat antenna elements, patch antenna elements, dipole antenna elements, and any other suitable antenna for wireless power transmission. Suitable antenna types may include, for example, patch antennas with heights from about $\frac{1}{8}$ inch to about 6 inches and widths from about
 55 $\frac{1}{8}$ inch to about 6 inches. The shape and orientation of antenna element **1106** may vary in dependency of the desired features of transmitter **1101**; orientation may be flat
 60 in X, Y, and Z axis, as well as various orientation types and combinations in three dimensional arrangements. Antenna element **1106** materials may include any suitable material that may allow RF signal transmission with high efficiency, good heat dissipation and the like. The amount of antenna
 65 elements **1106** may vary in relation with the desired range and power transmission capability on transmitter **1101**; the

more antenna elements **1106**, the wider range and higher power transmission capability.

Antenna element **1106** may include suitable antenna types for operating in frequency bands such as 900 MHz, 2.5 GHz or 5.8 GHz as these frequency bands conform to Federal
 5 Communications Commission (FCC) regulations part 18 (industrial, scientific, and medical equipment). Antenna element **1106** may operate in independent frequencies, allowing a multichannel operation of pocket-forming.

In addition, antenna element **1106** may have at least one
 10 polarization or a selection of polarizations. Such polarization may include vertical polarization, horizontal polarization, circularly polarized, left hand polarized, right hand polarized, or a combination of polarizations. The selection of polarizations may vary in dependency of transmitter **1101**
 15 characteristics. In addition, antenna element **1106** may be located in various surfaces of transmitter **1101**. Antenna element **1106** may operate in single array, pair array, quad array and any other suitable arrangement that may be
 20 designed in accordance with the desired application.

In some implementations, the entire side of the printed circuit board PCB **1104** may be closely packed with antenna
 25 element **1106**. The RFIC **1108** may connect to multiple antenna elements **1106**. Multiple antenna elements **1106** may surround a single RFIC **1108**.

3. Radio Frequency Integrated Circuits

The RFIC **1108** may receive an RF signal from the MC
 30 **1110**, and split the RF signal into multiple outputs, each output linked to an antenna element **1106**. For example, each RFIC **1108** may be connected to four antenna elements **1106**. In some implementations, each RFIC **1108** may be connected to eight, sixteen, and/or multiple antenna elements
 35 **1106**.

The RFIC **1104** may include a plurality of RF circuits that
 40 may include digital and/or analog components, such as, amplifiers, capacitors, oscillators, piezoelectric crystals and the like. RFIC **1104** may control features of antenna element **1106**, such as gain and/or phase for pocket-forming and manage it through direction, power level, and the like. The phase and the amplitude of pocket-forming in each antenna
 45 element **1106** may be regulated by the corresponding RFIC **1108** in order to generate the desired pocket-forming and transmission null steering. In addition, RFIC **1108** may be connected to MC **1110**, which may utilize digital signal processing (DSP), ARM, PIC-Class microprocessor, central
 50 processing unit, computer, and the like. The lower number of RFICs **1108** present in the transmitter **1101** may correspond to desired features such as lower control of multiple pocket-forming, lower levels of granularity, and a less expensive embodiment. In some implementations, RFIC
 55 **1108** may be coupled to one or more MCs **1110**, and MC **1110** may be included into an independent base station or into the transmitter **1101**.

In some implementations of transmitter **1101**, the phase
 60 and the amplitude of each pocket-forming in each antenna element **1106** may be regulated by the corresponding RFIC **1108** in order to generate the desired pocket-forming and transmission null steering. RFIC **1108** singled coupled to each antenna element **1106** may reduce processing require-
 65 ment and may increase control over pocket-forming, allowing multiple pocket-forming and a higher granular pocket-forming with less load over MC **1110**, and a higher response of higher number of multiple pocket-forming may be allowed. Furthermore, multiple pocket-forming may charge a higher number of receivers and may allow a better trajectory to such receivers.

RFIC **1108** and antenna element **1106** may operate in any suitable arrangement that may be designed in accordance with the desired application. For example, transmitter **1101** may include antenna element **1106** and RFIC **1108** in a flat arrangement. A subset of 4, 8, 16, and/or any number of antenna elements **1106** may be connected to a single RFIC **1108**. RFIC **1108** may be directly embedded behind each antenna element **1106**; such integration may reduce losses due the shorter distance between components. In some implementations, a row or column of antenna elements **1106** may be connected to a single MC **1110**. RFIC **1108** connected to each row or column may allow a less expensive transmitter **1101** that may produce pocket-forming by changing phase and gain between rows or columns. In some implementations, the RFIC **1108** may output between 2-8 volts of power for the receiver **1120** to obtain.

In some implementations, a cascade arrangement of RFICs **1108** may be implemented. A flat transmitter **1101** using a cascade arrangement of RFICs **1108** may provide greater control over pocket-forming and may increase response for targeting receivers **1106**, as well as a higher reliability and accuracy may be achieved because multiple redundancy of RFICs **1108**.

4. Microcontrollers

The MC **1110** may comprise a processor running ARM and/or DSP. ARM is a family of general purpose microprocessors based on a reduced instruction set computing (RISC). A DSP is a general purpose signal processing chip may provide a mathematical manipulation of an information signal to modify or improve it in some way, and can be characterized by the representation of discrete time, discrete frequency, and/or other discrete domain signals by a sequence of numbers or symbols and the processing of these signals. DSP may measure, filter, and/or compress continuous real-world analog signals. The first step may be conversion of the signal from an analog to a digital form, by sampling and then digitizing it using an analog-to-digital converter (ADC), which may convert the analog signal into a stream of discrete digital values. The MC **1110** may also run Linux and/or any other operating system. The MC **1110** may also be connected to Wi-Fi in order to provide information through a network **1140**.

MC **1110** may control a variety of features of RFIC **1108** such as, time emission of pocket-forming, direction of the pocket-forming, bounce angle, power intensity and the like. Furthermore, MC **1110** may control multiple pocket-forming over multiple receivers or over a single receiver. Transmitter **1101** may allow distance discrimination of wireless power transmission. In addition, MC **1110** may manage and control communication protocols and signals by controlling communication component **1112**. MC **1110** may process information received by communication component **1112** that may send and receive signals to and from a receiver in order to track it and concentrate radio frequency signals **1142** (i.e., pockets of energy) on it. Other information may be transmitted from and to receiver **1120**; such information may include authentication protocols among others through a network **1140**.

The MC **1110** may communicate with the communication component **1112** through serial peripheral interface (SPI) and/or inter-integrated circuit (I²C) protocol. SPI communication may be used for short distance, single master communication, for example in embedded systems, sensors, and SD cards. Devices communicate in master/slave mode where the master device initiates the data frame. Multiple slave devices are allowed with individual slave select lines.

I²C is a multi-master, multi-slave, single-ended, serial computer bus used for attaching low-speed peripherals to computer motherboards and embedded systems

5. Communications Component

Communication component **1112** may include and combine Bluetooth technology, infrared communication, Wi-Fi, FM radio among others. MC **1110** may determine optimum times and locations for pocket-forming, including the most efficient trajectory to transmit pocket forming in order to reduce losses because obstacles. Such trajectory may include direct pocket-forming, bouncing, and distance discrimination of pocket-forming. In some implementations, the communication component **1112** may communicate with a plurality of devices, which may include receivers **1120**, client devices, or other transmitters **1101**.

6. Power Source

Transmitters **1101** may be fed by a power source **1114** that may include AC or DC power supply. Voltage, power, and current intensity provided by power source **1114** may vary in dependency with the required power to be transmitted. Conversion of power to radio signal may be managed by MC **1110** and carried out by RFIC **1108** that may utilize a plurality of methods and components to produce radio signals in a wide variety of frequencies, wavelength, intensities, and other features. As an exemplary use of a variety of methods and components for radio signal generation, oscillators and piezoelectric crystals may be used to create and change radio frequencies in different antenna elements **1106**. In addition, a variety of filters may be used for smoothing signals as well as amplifiers for increasing power to be transmitted.

Transmitter **1101** may emit RF power waves that are pocket-forming with a power capability from few watts to a predetermined number of watts required by a particular chargeable electronic device. Each antenna may manage a certain power capacity. Such power capacity may be related with the application

7. Housing

In addition to a housing, an independent base station may include MC **1110** and power source **1114**, thus, several transmitters **1101** may be managed by a single base station and a single MC **1110**. Such capability may allow the location of transmitters **1101** in a variety of strategic positions, such as ceiling, decorations, walls, and the like. Antenna elements **1106**, RFIC **1108**, MC **1110**, communication component **1112**, and power source **1114** may be connected in a plurality of arrangements and combinations, which may depend on the desired characteristics of transmitter **1101**.

B. Exemplary Method of Transmitting Power

FIG. **12** is a method for determining receiver location **1200** using antenna element. Method for determining receiver location **1200** may be a set of programmed rules or logic managed by MC. The process may begin step **1201** by capturing first signal with a first subset of antennas from the antenna array. The process may follow immediately by switching to a different subset of antenna element and capturing, at a next step **1203**, a second signal with a second subset of antennas. For example, a first signal may be captured with a row of antennas and the second capturing may be done with a column of antennas. A row of antennas may provide a horizontal degree orientation such an azimuth in a spherical coordinate system. A column of antennas may provide a vertical degree orientation such as elevation. Antenna elements used for capturing first signal and capturing second signal may be aligned in straight, vertical, horizontal, or diagonal orientation. The first subset and

second subset of antennas may be aligned in a cross like structure in order to cover degrees around transmitter.

Once both vertical and horizontal values have been measured, the MC may, in a next step **1205**, determine the appropriate values of phase and gain for the vertical and horizontal antenna elements used to capture the signal. Appropriate values for phase and gain may be determined by the relationship of the position of the receiver to the antenna. The values may be used by MC in order to adjust antenna elements to form pockets of energy that may be used by a receiver in order to charge an electronic device.

Data pertaining to initial values of all antenna elements in transmitter may be calculated and stored previously for use by MC in order to assist in the calculation of appropriate values for antenna elements. In a next step, **1207**, after the appropriate values for the vertical and horizontal antennas used for capturing the signal have been determined, the process may continue by using the stored data to determine appropriate values for all the antennas in the array. Stored data may contain initial test values of phase and gain for all antenna elements in the array at different frequencies. Different sets of data may be stored for different frequencies and MC may select the appropriate data set accordingly. In a next step **1209**, MC may then adjust all antennas through RFIC in order to form pockets of energy at the appropriate locations.

C. Array Subset Configuration

FIG. **13A** illustrates an example embodiment of an array subset configuration **1300A** that may be used in method for determining receiver location. Transmitter may include an array of antennas **1306A**. A row of antennas **1368A** may be used first for capturing a signal sent by a receiver. Row of antennas **1368A** may then transfer the signal to the RFIC, where the signal may be converted from a radio signal to a digital signal and passed on to MC for processing. MC may then determine appropriate adjustments for phase and gain in row of antennas **1368A** in order to form pockets of energy at the appropriate locations based on the receiver locations. A second signal may be captured by a column of antennas **1370A**. Column of antennas **1370A** may then transfer the signal to the RFIC, where the signal may be converted from a radio signal to a digital signal and passed on to MC for processing. MC may then determine appropriate adjustments for phase and gain in column of antennas **1370A** in order to form pockets of energy at the appropriate locations based on the receiver locations. Once the appropriate adjustments have been determined for row of antennas **1368A** and column of antennas **1370A** MC may determine the appropriate values for the rest of antenna elements **1306A** in array of antennas **1368A** by using previously stored data about the antennas and adjusting accordingly with the results from row of antennas **1368A** and column of antennas **1370A**.

D. Configurations for Transmitters, Transmitter Components, Antenna Tiles, and Systems Related to Transmitters

1. Exemplary System

FIG. **13B** illustrates another example embodiment of an array subset configuration **1300B**. In array subset configuration **1300B**, both initial signals are captured by two diagonal subsets of antennas. The process follows the same path, such that each subset is adjusted accordingly. Based on adjustments made and the previously stored data, the rest of antenna elements **1306B** in array of antennas are adjusted.

2. Flat Transmitter

FIG. **14** depicts a flat transmitter **1402** in a front view and a several embodiments of rear views. Transmitter **1402** may include antenna element **1406** and RFIC **1408** in a flat arrangement. RFIC **1408** may be directly embedded behind

each antenna element **1406**; such integration may reduce losses due the shorter distance between components.

In one embodiment (i.e., View 1) in transmitter **1402**, the phase and the amplitude of the pocket-forming for each antenna element **1406** may be regulated by the corresponding RFIC **1408** in order to generate the desired pocket-forming and transmission null steering. RFIC **1408** singled coupled to each antenna element **1406** may reduce processing requirement and may increase control over pocket-forming, allowing multiple pocket-forming and a higher granular pocket-forming with less load over MC **1410**; thus, a higher response of higher number of multiple pocket-forming may be allowed. Furthermore, multiple pocket-forming may charge a higher number of receivers and may allow a better trajectory to such receivers. As described in the embodiment of FIG. **11**, RFIC **1408** may be coupled to one or more MCs **1410**, and microcontroller **1410** may be included into an independent base station or into the transmitter **1402**.

In another embodiment (i.e., View 2), a subset of 4 antenna elements **1406** may be connected to a single RFIC **1408**. The lower number of RFICs **1408** present in the transmitter **1402** may correspond to desired features such as: lower control of multiple pocket-forming, lower levels of granularity and a less expensive embodiment. As described in the embodiment of FIG. **11**, RFIC **1408** may be coupled to one or more MCs **1410**, and microcontroller **1410** may be included into an independent base station or into the transmitter **1402**.

In yet another embodiment (i.e., View 3), transmitter **1402** may include antenna element **1406** and RFIC **1408** in a flat arrangement. A row or column of antenna elements **1406** may be connected to a single MC **1410**. The lower number of RFICs **1408** present in the transmitter **1402** may correspond to desired features such as: lower control of multiple pocket-forming, lower levels of granularity and a less expensive embodiment. RFIC **1408** connected to each row or column may allow a less expensive transmitter **1402**, which may produce pocket-forming by changing phase and gain between rows or columns. As described in the embodiment of FIG. **11**, RFIC **1408** may be coupled to one or more MCs **1410**, and microcontroller **1410** may be included into an independent base station or into the transmitter **1402**.

In some embodiments (i.e., View 4), transmitter **1402** may include antenna element **1406** and RFIC **1408** in a flat arrangement. A cascade arrangement is depicted in this exemplary embodiment. Two antenna elements **1406** may be connected to a single RFIC **1408** and this in turn to a single RFIC **1408**, which may be connected to a final RFIC **1408** and this in turn to one or more MCs **1410**. Flat transmitter **1402** using a cascade arrangement of RFICs **1408** may provide greater control over pocket-forming and may increase response for targeting receivers. Furthermore, a higher reliability and accuracy may be achieved because multiple redundancy of RFICs **1408**. As described in the embodiment of FIG. **11**, RFIC **1408** may be coupled to one or more MCs **1410**, and microcontroller **1410** may be included into an independent base station or into the transmitter **1402**.

3. Multiple Printed Circuit Board Layers

FIG. **15A** depicts a transmitter **1502A**, which may include a plurality of PCB layers **1204A** that may include antenna element **1506A** for providing greater control over pocket-forming and may increase response for targeting receivers. Multiple PCB layers **1504A** may increase the range and the amount of power that could be transferred by transmitter **1502A**. PCB layers **1504A** may be connected to a single MC

or to dedicated MC. Similarly, RFIC may be connected antenna element **1506A** as depicted in the foregoing embodiments. RFIC may be coupled to one or more MCs. Furthermore, MCs may be included into an independent base station or into the transmitter **1502A**.

4. Box Transmitter

FIG. **15B** depicts a box transmitter **1502B**, which may include a plurality of PCB layers **1504B** inside it, which may include antenna element **1506B** for providing greater control over pocket-forming and may increase response for targeting receivers. Furthermore, range of wireless power transmission may be increased by the box transmitter **1502B**. Multiple PCB layers **1504B** may increase the range and the amount of RF power waves that could be transferred or broadcasted wirelessly by transmitter **1502B** due the higher density of antenna element **1506B**. PCB layers **1504B** may be connected to a single MC or to dedicated MC for each antenna element **1506B**. Similarly, RFIC may control antenna element **1506B** as depicted in the foregoing embodiments. Furthermore, box shape of transmitter **800** may increase action ratio of wireless power transmission; thus, box transmitter **1502B** may be located on a plurality of surfaces such as, desks, tables, floors, and the like. In addition, box transmitter **1502B** may comprise several arrangements of PCB layers **1504B**, which may be oriented in X, Y, and Z axis, or any combination these. The RFIC may, be coupled to one or more MCs. Furthermore, MCs may be included into an independent base station or into the transmitter **1502B**.

5. Irregular Arrays for Various Types of Products

FIG. **16** depicts a diagram of architecture **1600** for incorporating transmitter **1602** into different devices. For example, the flat transmitter **1602** may be applied to the frame of a television **1646** or across the frame of a sound bar **1648**. Transmitter **1602** may include multiple tiles **1650** with antenna elements and RFICs in a flat arrangement. The RFIC may be directly embedded behind each antenna elements; such integration may reduce losses due the shorter distance between components.

For example, a television **1646** may have a bezel around a television **1646**, comprising multiple tiles **1650**, each tile comprising of a certain number of antenna elements. For example, if there are 20 tiles **1650** around the bezel of the television **1646**, each tile **1650** may have 24 antenna elements and/or any number of antenna elements.

In tile **1650**, the phase and the amplitude of each pocket-forming in each antenna element may be regulated by the corresponding RFIC in order to generate the desired pocket-forming and transmission null steering. RFIC singled coupled to each antenna element may reduce processing requirement and may increase control over pocket-forming, allowing multiple pocket-forming and a higher granular pocket-forming with less load over microcontroller, thus, a higher response of higher number of multiple pocket-forming may be allowed. Furthermore, multiple pocket-forming may charge a higher number of receivers and may allow a better trajectory to such receivers.

RFIC may be coupled to one or more microcontrollers, and the microcontrollers may be included into an independent base station or into the tiles **1650** in the transmitter **1602**. A row or column of antenna elements may be connected to a single microcontroller. In some implementations, the lower number of RFICs present in the transmitters **1602** may correspond to desired features such as: lower control of multiple pocket-forming, lower levels of granularity and a less expensive embodiment. RFICs connected to each row or column may allow reduce costs by having fewer compo-

nents because fewer RFICs are required to control each of the transmitters **1602**. The RFICs may produce pocket-forming power transmission waves by changing phase and gain, between rows or columns.

5 In some implementations, the transmitter **1602** may use a cascade arrangement of tiles **1650** comprising RFICs that may provide greater control over pocket-forming and may increase response for targeting receivers. Furthermore, a higher reliability and accuracy may be achieved from multiple redundancies of RFICs.

10 In one embodiment, a plurality of PCB layers, including antenna elements, may provide greater control over pocket-forming and may increase response for targeting receivers. Multiple PCB layers may increase the range and the amount of power that could be transferred by transmitter **1602**. PCB layers may be connected to a single microcontroller or to dedicated microcontrollers. Similarly, RFIC may be connected to antenna elements.

15 A box transmitter **1602** may include a plurality of PCB layers inside it, which may include antenna elements for providing greater control over pocket-forming and may increase response for targeting receivers. Furthermore, range of wireless power transmission may be increased by the box transmitter **1602**. Multiple PCB layers may increase the range and the amount of RF power waves that could be transferred or broadcasted wirelessly by transmitter **1602** due the higher density of antenna elements. PCB layers may be connected to a single microcontroller or to dedicated microcontrollers for each antenna element. Similarly, RFIC may control antenna elements. The box shape of transmitter **1602** may increase action ratio of wireless power transmission. Thus, box transmitter **1602** may be located on a plurality of surfaces such as, desks, tables, floors, and the like. In addition, box transmitter may comprise several arrangements of PCB layers, which may be oriented in X, Y, and Z axis, or any combination these.

6. Plurality of Antenna Elements

FIG. **17** is an example of a transmitter configuration **1700** that includes a plurality of antenna elements **1706**. Antenna element **1706** may form an array by arranging rows of antennas **1768** and columns of antennas **1770**. Transmitter configuration may include at least one RFIC **1708** to control features of antenna element **1706**, such as gain and/or phase for pocket-forming and manage it through direction, power level, and the like. The array of antenna elements **1706** may be connected to a MC **1710**, which may determine optimum times and locations for pocket-forming, including the most efficient trajectory to transmit pocket forming in order to reduce losses because of obstacles. Such trajectory may include direct pocket-forming, bouncing, and distance discrimination of pocket-forming.

55 A transmitter device may utilize antenna element **1706** to determine the location of a receiver in order to determine how to adjust antenna element **1706** to form pockets of energy in the appropriate location. A receiver may send a train signal to transmitter in order to provide information. The train signal may be any conventional know signals that may be detected by antenna element **1706**. The signal sent by receiver may contain information such as phase and gain.

III. Receivers—Systems and Methods for Receiving and Utilizing Wireless Power Transmissions

A. Components of Receiver Devices

65 Returning to FIG. **11**, which illustrates a diagram of a system **1100** architecture for wirelessly charging client devices, according to an exemplary embodiment, the system **1100** may comprise transmitter **1101** and receivers **1120** that may each comprise an application-specific integrated circuit

(ASIC). The ASIC of the receivers **1120** may include a printed circuit board **1122**, an antenna element **1124**, a rectifier **1126**, a power converter **1129**, a communications component **1130**, and/or a power management integrated circuit (PMIC) **1132**. Receivers **1120** may also comprise a housing that may allocate all the requested components. The various components of receivers **1120** may comprise, or may be manufactured using, meta-materials, micro-printing of circuits, nano-materials, and the like.

1. Antenna Elements

Antenna elements **1124** may include suitable antenna types for operating in frequency bands similar to the bands described for antenna elements **1106** of a transmitter **1101**. Antenna element **1124** may include vertical or horizontal polarization, right hand or left hand polarization, elliptical polarization, or other suitable polarizations as well as suitable polarization combinations. Using multiple polarizations can be beneficial in devices where there may not be a preferred orientation during usage or whose orientation may vary continuously through time, for example a smartphone or portable gaming system. On the contrary, for devices with well-defined orientations, for example a two-handed video game controller, there might be a preferred polarization for antennas, which may dictate a ratio for the number of antennas of a given polarization. Suitable antenna types may include patch antennas with heights from about 1/8 inch to about 6 inches and widths from about 1/8 inch to about 6 inches. Patch antennas may have the advantage that polarization may depend on connectivity, i.e., depending on which side the patch is fed, the polarization may change. This may further prove advantageous as a receiver, such as receiver **1120**, may dynamically modify its antenna polarization to optimize wireless power transmission. Different antenna, rectifier, or power converter arrangements are possible for a receiver, as is described in the embodiments herein.

2. Rectifiers

A rectifier **1126** may convert alternating current (AC), which periodically reverses direction, to direct current (DC), which takes non-negative values. Because of the alternating nature of the input AC sine wave, the process of rectification alone produces a DC current that, though non-negative, consists of pulses of current. The output of the rectifier may be smoothed by an electronic filter to produce a steady current. The rectifier **1126** may include diodes and/or resistors, inductors and/or capacitors to rectify the alternating current (AC) voltage generated by antenna element **1124** to direct current (DC) voltage.

In some implementations, the rectifier **1126** may be a full-wave rectifier. A full-wave rectifier may convert the whole of the input waveform to one of constant polarity (positive or negative) at its output. Full-wave rectification may convert both polarities of the input waveform to pulsating DC (direct current), and yield a higher average output voltage. Two diodes and a center tapped transformer and/or four diodes in a bridge configuration and any AC source (including a transformer without center tap) may be utilized for a full-wave rectifier. For single-phase AC, if the transformer is center-tapped, then two diodes back-to-back (cathode-to-cathode or anode-to-anode, depending upon output polarity required) may be utilized to form a full-wave rectifier. Twice as many turns may be required on the transformer secondary to obtain the same output voltage than for a bridge rectifier, but the power rating is unchanged.

Rectifier **1126** may be placed as close as is technically possible to antenna element **1124** to minimize losses. After rectifying AC voltage, DC voltage may be regulated using power converter **1129**.

3. Power Converters

Power converter **1129** can be a DC-to-DC converter that may help provide a constant voltage output and/or to help boost the voltage to the receiver **1120**. In some implementations, the DC-to-DC converter may be a maximum power point tracker (MPPT). A MPPT is an electronic DC-to-DC converter that converts a higher voltage DC output down to the lower voltage needed to charge batteries. Typical voltage outputs can be from about 5 volts to about 10 volts. In some embodiments, power converter **1129** may include electronic switched mode DC-to-DC converters, which can provide high efficiency. In such a case, a capacitor may be included before power converter **1129** to ensure sufficient current is provided for the switching device to operate. When charging an electronic device, for example a phone or laptop computer, initial high-currents that can exceed the minimum level of power needed to activate the operation of an electronic switched mode DC-to-DC converter, may be required. In such a case, a capacitor may be added at the output of receiver **1120** to provide the extra energy required. Afterwards, lower power can be provided, as required to provide the appropriate amount electric current; for example, 1/80 of the total initial power used while having the phone or laptop still building-up charge.

In one embodiment, multiple rectifiers **1126** can be connected in parallel to antenna element **1124**. For example, four rectifiers **1126** may be connected in parallel to antenna element **1124**. However, several more rectifiers **1126** can be used. This arrangement may be advantageous because each rectifier **1126** may only need to handle 1/4 of the total power. If one watt is to be delivered to an electronic device, then each rectifier **1126** may only need to handle a quarter of a watt. The arrangement may greatly diminish cost because using a plurality of low-power rectifiers **1126** can be cheaper than utilizing one high-power rectifier **1126** while handling the same amount of power. In some embodiments, the total power handled by rectifier **1126** can be combined into a power converter **1129**. In other embodiments, there may be a power converter **1129** per each rectifier **1126**.

In other embodiments, multiple antenna elements **1124** may be connected in parallel to a rectifier **1126**, after which DC voltage may be regulated through a power converter **1129**. In this example, four antenna elements **1124** may be connected in parallel to a single rectifier **1126**. This arrangement may be advantageous because each antenna element **1124** may only handle 1/4 of the total power. In addition, the arrangement may enable usage of antenna element **1124** of different polarizations with a single rectifier **1126** because signals may not cancel each other. Because of the foregoing property, the arrangement may be suitable for electronic client devices with an orientation that is not well-defined or otherwise varies over time. Lastly, the arrangement may be beneficial when using antenna element **1124** of equal polarization and configured for phases that do not differ greatly. In some embodiments, however, there can be a rectifier **1126** per antenna element **1124** and/or multiple rectifiers **1126** per antenna element **1124**.

In an exemplary implementation, an arrangement where multiple antenna elements **1124** outputs can be combined and connected to parallel rectifiers **1126** whose output may further be combined in one power converter **1129** may be implemented. There may be 16 antenna elements **1124** whose output may be combined at four parallel rectifiers

1126. In other embodiments, antenna elements **1124** may be subdivided into groups (of four for example) and may connect to independent rectifiers **1126**.

In yet another embodiment, an arrangement where groups of antenna elements **1124** may be connected to different rectifiers **1126** which may in turn also be connected to different power converters **1129** may be implemented. In this embodiment, four groups of antenna elements **1124** (each containing four antenna elements **1124** in parallel) may each connect independently to four rectifiers **1126**. In this embodiment, the output of each rectifier **1126** may connect directly to a power converter **1129** (four in total). In other embodiments, the output of all four rectifiers **1126** can be combined before each power converter **1129** to handle the total power in parallel. In some embodiments, the combined outputs of each rectifier **1126** may connect to a single power converter **1129**. This arrangement may be beneficial in that it allows great proximity between rectifier **1126** and antenna element **1124**. This property may be desirable as it may keep losses at a minimum.

4. Communications Component

A communications component **1130**, similar to that of transmitter **1101**, may be included in receiver **1120** to communicate with a transmitter or to other electronic equipment. In some implementations, receiver **1120** can use a built-in communications component of the device (for example, Bluetooth) for communicating to a given transmitter **1120** based on requirements provided by processor such as battery level, user predefined charging profile or others transmitters **1101** may include one or more printed circuit boards (PCB) **1104**, one or more antenna elements **1106**, one or more radio frequency integrated circuits (RFIC) **1108**, one or more microcontrollers (MCs) **1110**, a communication component **1112**, and a power source **1114**. The transmitter **1101** may be encased in a housing, which may allocate all the requested components for transmitter **1101**. Components in transmitter **1101** may be manufactured using meta-materials, micro-printing of circuits, nano-materials, and/or any other materials. The types of information communicated by the communications components between the receiver and the transmitter include but not limited to the present power levels in the batteries, signal strength and power level being received at the receiver, timing information, phase and gain information, user identification, client device privileges, security related signaling, emergency signaling, and authentication exchanges, among other things.

5. PMICs

A power management integrated circuit (PMIC) **1132** is an integrated circuit and/or a system block in a system-on-a-chip device for managing power requirements of the host system. The PMIC **1132** may include battery management, voltage regulation, and charging functions. It may include a DC-to-DC converter to allow dynamic voltage scaling. In some implementations, the PMIC **1132** may provide up to a 95% power conversion efficiency. In some implementations, the PMIC **1132** may integrate with dynamic frequency scaling in a combination. The PMIC **1132** may be implemented in a battery-operated device such as mobile phones and/or portable media players. In some implementations, the battery may be replaced with an input capacitor and an output capacitor. The PMIC **1132** may be directly connected to the battery and/or capacitors. When the battery is being charged directly, a capacitor may not be implemented. In some implementations, the PMIC **1132** may be coiled around the battery. The PMIC **1132** may comprise a power management chip (PMC) that acts as a battery charger, and is connected to the battery. The PMIC **1132** can use pulse-

frequency modulation (PFM) and pulse-width modulation (PWM). It can use switching amplifier (Class-D electronic amplifier). In some implementations, an output converter, a rectifier, and/or a BLE may also be included in the PMIC **1132**.

6. Housing

Housing can be made of any suitable material that may allow for signal or wave transmission and/or reception, for example plastic or hard rubber. Housing may be an external hardware that may be added to different electronic equipment, for example in the form of cases, or can be embedded within electronic equipment as well.

7. Network

The network **1140** may comprise any common communication architecture that facilitates communication between transmitter **1101** and the receiver **1120**. One having ordinary skill in the art would appreciate that the network **1140** may be the Internet, a private intranet, or some hybrid of the two. It should also be obvious to one skilled in the art that the network components may be implemented in dedicated processing equipment, or alternatively in a cloud processing network.

B. Configurations for Receivers, Receiver Components, and Systems Related to Receivers

1. Multiple Rectifiers Connected in Parallel to an Antenna Element

FIG. **18A** illustrates an arrangement **1800A** where multiple rectifiers **1826A** can be connected in parallel to an antenna element **1824A**. In this example, four rectifiers **1826A** may be connected in parallel to an antenna elements **1824A**. However, several more rectifiers **1826A** may be used. Arrangement **1800A** may be advantageous because each rectifier **1826A** may only need to handle $\frac{1}{4}$ of the total power. If one watt is to be delivered to an electronic device, then each rectifier **1826F** may only need to handle a quarter of a watt. Arrangement **1800A** may greatly diminish cost because using a plurality of low-power rectifiers **1826A** can be cheaper than utilizing one high-power rectifier **1826A** while handling the same amount of power. In some embodiments, the total power handled by rectifier **1826A** can be combined into one DC-DC converter **1828A**. In other embodiments, there may a DC-DC converter **1828A** per rectifier **1826A**.

2. Multiple Antenna Elements Connected in Parallel to a Rectifier

FIG. **18B** illustrates an arrangement **1800B** where multiple antenna elements **1824B** may be connected in parallel to a rectifier **1826B**, after which DC voltage may be regulated through a DC-DC converter **1828B**. In this example, four antenna elements **1824B** may be connected in parallel to a single rectifier **1826B**. Arrangement **1800B** may be advantageous because each antenna element **1824B** may only handle $\frac{1}{4}$ of the total power. In addition, arrangement **1800B** may enable usage of antenna element **1824B** of different polarizations with a single rectifier **1826B** because signals may not cancel each other. Because of the foregoing property, arrangement **1800B** may be suitable for electronic devices with an orientation that is not well-defined or otherwise varies over time. Lastly, arrangement **1800B** may be beneficial when using antenna element **1824B** of equal polarization and configured for phases that do not differ greatly. In some embodiments, however, there can be a rectifier **1826B** per antenna element **1824B** or multiple rectifiers **1826B** (as described in FIG. **18A**) per antenna element **1824B**.

3. Multiple Antenna Elements Connected in Parallel to Multiple Rectifiers

FIG. 19A illustrates an arrangement 1900A where multiple antenna elements 1924A outputs can be combined and connected to parallel rectifier 1926A whose output may further be combined in one DC converter 1928A. Arrangement 1900A shows, by way of exemplification, 16 antenna elements 1924A whose output may be combined at four parallel rectifiers 1926A. In other embodiments, antenna elements 1924A may be subdivided in groups (e.g., four groups) and may connect to independent rectifiers as shown in FIG. 19B below.

4. Permutations of Groupings

FIG. 19B illustrates an arrangement 1900B where groups of antenna elements 1924B may be connected to different rectifiers 1926B, which may in turn also be connected to different DC converters 1928B. In arrangement 1900B, four groups of antenna elements 1924B (each containing four antenna elements 1924B in parallel) may each connect independently to four rectifiers 1926B. In this embodiment, the output of each rectifiers 1926B may connect directly to a DC converter 1928B (four in total). In other embodiments, the output of all four rectifiers 1926B can be combined, before each DC converter 1928B, to handle the total power in parallel. In other embodiments, the combined outputs of each rectifier 1926B may connect to a single DC converter 1928B. Arrangement 1900B may be beneficial in that it allows great proximity between rectifier 1926B and antenna element 1924B. This property may be desirable as it may keep losses at a minimum.

A receiver may be implemented on, connected to or embedded in electronic devices or equipment that may rely on power for performing its intended functions, for example a phone, laptop computer, a television remote, a children's toys or any other such devices. A receiver utilizing pocket-forming can be used to fully charge a device's battery while being "On" or "Off," or while being used or not. In addition, battery lifetime can be greatly enhanced. For example, a device operating on two watts utilizing a receiver that may deliver one watt may increase its battery duration up to about 50%. Lastly, some devices currently running on batteries can fully be powered using a receiver after which a battery may no longer be required. This last property may be beneficial for devices where replacing batteries can be tedious or hard to accomplish such as in wall-clocks. Embodiments below provide some examples of how integration of receivers may be carried out on electronic devices.

5. Embedded Receiver

FIG. 20A illustrates an implementation scheme where a device 2000A that may represent a typical phone, computer or other electronic device may include an embedded receiver 2020A. Device 2000A may also include a power source, a communications component 2030A, and a processor. Receiver 2020A may utilize pocket-forming for providing power to power source from device 2000A. In addition, receiver 2020A can use built-in communications component 2030A of device 2000A (for example, Bluetooth) for communicating to a given transmitter based on requirements provided by processor such as battery level, user predefined charging profile or others.

6. Battery with an Embedded Receiver

FIG. 20B illustrates another implementation scheme where a device 2000B may include a battery with an embedded receiver 2020B. Battery may receive power wirelessly through pocket-forming and may charge through its embedded receiver 2020B. Battery may function as a supply for power source, or may function as back-up supply. This

configuration may be advantageous in that battery may not need to be removed for charging. This may particularly be helpful in gaming controllers, or gaming devices where batteries, typically AA or AAA may be continuously replaced.

7. External Communication Component

FIG. 20C illustrates an alternate implementation scheme 2000C where receiver 2020C and a communications component 2030C may be included in an external hardware that may be attached to a device. Hardware can take appropriate forms such as cases that may be placed on phones, computers, remote controllers and others, which may connect thorough suitable interfaces such as Universal Serial Bus (USB). In other embodiments, hardware may be printed on flexible films, which may then be pasted or otherwise attached to electronic equipment. This option may be advantageous as it may be produced at low cost and can easily be integrated into various devices. As in previous embodiments, a communications component 2030C may be included in hardware that may provide communication to a transmitter or to electronic equipment in general.

8. Casing or Housing of Receiver Connecting to USB

FIG. 21A illustrates hardware in the form of case including a receiver 2102A that may connect through flex cables or USB to a smartphone and/or any other electronic device. In other embodiments, the housing or case can be a computer case, phone case, and/or camera case among other such options.

9. PCB on Printed Film

FIG. 21B illustrates hardware in the form of a printed film or flexible printed circuit board (PCB) which may include a plurality of printed receivers 2102B. Printed film can be pasted or otherwise attached to electronic devices and can connect through suitable interfaces such as USB. Printed film may be advantageous in that sections can be cut from it to meet specific electronic device sizes and/or requirements. The efficiency of wireless power transmission as well as the amount of power that can be delivered (using pocket-forming) may be a function of the total number of antenna elements used in a given receiver and transmitter system. For example, for delivering about one watt at about 15 feet, a receiver may include about 80 antenna elements while a transmitter may include about 256 antenna elements. Another identical wireless power transmission system (about 1 watt, at about 15 feet) may include a receiver with about 40 antenna elements, and a transmitter with about 512 antenna elements. Reducing in half the number of antenna elements in a receiver may require doubling the number of antenna elements in a transmitter. In some cases, it may be cost-effective to put a greater number of antenna elements in a transmitter than in a receiver. However, the opposite can be achieved by placing more antenna elements on a receiver than on a transmitter, as long as there are at least two antenna elements in a transmitter.

IV. Antenna Hardware and Functionality

A. Spacing Configuration

FIG. 22 illustrates internal hardware, where receiver 2220 may be used for receiving wireless power transmission in an electronic device 2252 (e.g., smartphone). In some implementations, the electronic device 2252 may include receiver 2220, which may be embedded around the internal edge of the case 2254 (e.g., smartphone case) of the electronic device 2252. In other embodiments, the receiver 2220 may be implemented covering the back side of the case 2254. The case 2254 may be one or more of: a smartphone cover, a laptop cover, camera cover, GPS cover, a game controller

cover and/or tablet cover, among other such options. The case 2254 may be made out of plastic, rubber and/or any other suitable material.

Receiver 2220 may include an array of antenna elements 2224 strategically distributed on the grid area shown in FIG. 22. The case 2254 may include an array of antenna elements 2224 located around the edges and/or along the backside of case 2254 for optimal reception. The number, spacing, and type of antenna elements 2224 may be calculated according to the design, size, and/or type of electronic device 2252. In some embodiments, there may be a spacing (e.g., 1 mm-4 mm) and/or a meta-material between the case 2254 containing the antenna element 2224 and the electronic device 2252. The spacing and/or meta-material may provide additional gain for RF signals. In some implementations, the meta-materials may be used in creating a multi-layer PCB to implement into the case 2254.

B. Metamaterial

The internal hardware may be in the form of a printed film 2256 and/or flexible PCB may include different components, such as a plurality of printed antenna elements 2224 (connected with each other in serial, parallel, or combined), rectifier, and power converter elements. Printed film 2256 may be pasted or otherwise attached to any suitable electronic devices, such as electronic device 2252 and/or tablets. Printed film 2256 may be connected through any suitable interfaces such as flexible cables 2258. Printed film 2256 may exhibit some benefits; one of those benefits may be that sections can be cut from it to meet specific smart mobile device sizes and/or requirements. According to one embodiment, the spacing between antenna elements 2224 for receiver 2220 may range from about 2 nm to about 12 nm, being most suitable about 7 nm.

Additionally, in some implementations, the optimal amount of antenna elements 2224 that may be used in receiver 2220 for an electronic device 2252 such as a smartphone may range from about 20 to about 30. However, the amount of antenna elements 2224 within receiver 2220 may vary according to electronic device 2252 design and size. Antenna element 2224 may be made of different conductive materials such as copper, gold, and silver, among others. Furthermore, antenna element 2224 may be printed, etched, or laminated onto any suitable non-conductive flexible substrate, such as flexible PCB, among others. The disclosed configuration and orientation of antenna element 2224 may exhibit a better reception, efficiency, and performance of wireless charging.

The foregoing method descriptions and the process flow diagrams are provided merely as illustrative examples and are not intended to require or imply that the steps of the various embodiments must be performed in the order presented. As will be appreciated by one of skill in the art the steps in the foregoing embodiments may be performed in any order. Words such as "then," "next," and the like, are not intended to limit the order of the steps; these words are simply used to guide the reader through the description of the methods. Although process flow diagrams may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be re-arranged. A process may correspond to a method, a function, a procedure, a subroutine, a subprogram, etc. When a process corresponds to a function, its termination may correspond to a return of the function to the calling function or the main function.

The various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the

embodiments disclosed herein may be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present invention.

Embodiments implemented in computer software may be implemented in software, firmware, middleware, microcode, hardware description languages, or any combination thereof. A code segment or machine-executable instructions may represent a procedure, a function, a subprogram, a program, a routine, a subroutine, a module, a software package, a class, or any combination of instructions, data structures, or program statements. A code segment may be coupled to another code segment or a hardware circuit by passing and/or receiving information, data, arguments, parameters, or memory contents. Information, arguments, parameters, data, etc. may be passed, forwarded, or transmitted via any suitable means including memory sharing, message passing, token passing, network transmission, etc.

The actual software code or specialized control hardware used to implement these systems and methods is not limiting of the invention. Thus, the operation and behavior of the systems and methods were described without reference to the specific software code being understood that software and control hardware can be designed to implement the systems and methods based on the description herein.

When implemented in software, the functions may be stored as one or more instructions or code on a non-transitory computer-readable or processor-readable storage medium. The steps of a method or algorithm disclosed herein may be embodied in a processor-executable software module that may reside on a computer-readable or processor-readable storage medium. A non-transitory computer-readable or processor-readable media includes both computer storage media and tangible storage media that facilitate transfer of a computer program from one place to another. A non-transitory processor-readable storage media may be any available media that may be accessed by a computer. By way of example, and not limitation, such non-transitory processor-readable media may comprise RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other tangible storage medium that may be used to store desired program code in the form of instructions or data structures and that may be accessed by a computer or processor. Disk and disc, as used herein, include compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk, and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above should also be included within the scope of computer-readable media. Additionally, the operations of a method or algorithm may reside as one or any combination or set of codes and/or instructions on a non-transitory processor-readable medium and/or computer-readable medium, which may be incorporated into a computer program product. The preceding description of the disclosed embodiments is provided to enable any person skilled in the art to make or use the present invention. Various modifications to these embodiments will be readily apparent to those

skilled in the art, and the generic principles defined herein may be applied to other embodiments without departing from the spirit or scope of the invention. Thus, the present invention is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the following claims and the principles and novel features disclosed herein. While various aspects and embodiments have been disclosed, other aspects and embodiments are contemplated. The various aspects and embodiments disclosed are for purposes of illustration and are not intended to be limiting, with the true scope and spirit being indicated by the following claims.

What is claimed is:

1. A method for multiple pocket-forming in wireless power transmission, the method comprising:
 - establishing, by a transmitter, a first communication connection associating the transmitter with a first receiver in response to the transmitter receiving a first communication signal from the first receiver;
 - transmitting, by the transmitter, one or more first power transmission waves in a direction of the first receiver based on the first communication signal received from the first receiver;
 - adjusting, by the transmitter, a phase of the one or more first power transmission waves and a gain of the one or more first power transmission waves to cause the one or more first power transmission waves to converge at a first location with respect to the first receiver in accordance with the first communication signal received from the first receiver, thereby forming a pocket of energy at the first location at which the one or more first power transmission waves converge;
 - responsive to the transmitter receiving a second communication signal from a second receiver:
 - establishing, by the transmitter, a second communication connection associating the transmitter with the second receiver; and
 - identifying, by the transmitter, a second subset of one or more antennas from an array of antennas of the transmitter, wherein the second subset is associated with the second receiver, and wherein a first subset of one or more antennas is associated with the first receiver;
 - transmitting, by the transmitter, one or more second power transmission waves in the direction of the second receiver based on the second communication signal received from the second receiver, wherein the second subset of antennas transmits the one or more second power transmission waves to the second receiver; and
 - adjusting, by the transmitter, based on the second communication signal, a phase and a gain of the one or more second power transmission waves transmitted in the direction of the second receiver to cause the one or more second power transmission waves to converge at a second location respective to the second receiver, thereby forming a second pocket of energy at the second location.
2. The method according to claim 1, wherein receiving, by the transmitter, the second communication signal from the second receiver further comprises:
 - scanning, by the transmitter, at a given interval for an additional advertisement signal identifying an additional receiver.
3. The method according to claim 2, further comprising alternating, by the transmitter, at the given interval between

scanning for the additional advertisement signal and using one or more communication connections to communicate with respective receivers.

4. The method according to claim 2, wherein the transmitter halts the scanning for the additional advertisement signal or uses a respective communication connection to communicate with a respective receiver at the given interval.

5. The method according to claim 1, further comprising receiving, by the transmitter, an indication of a voltage amount received at the first receiver from the one or more first power transmission waves,

wherein the transmitter adjusts the one or more first power transmission waves based on the indication of the voltage amount.

6. The method according to claim 5, wherein the transmitter transmits a first power transmission wave of the one or more first power transmission waves in a first trajectory and a second power transmission wave of the one or more first power transmission waves in a second trajectory.

7. The method according to claim 6, wherein the first power transmission wave deflects off an obstruction in the first trajectory en route to converging with the second power transmission wave.

8. The method according to claim 1, wherein the one or more first and second power transmission waves are a type of physical medium selected from the group consisting of: radio waves, microwaves, electromagnetic waves, acoustics, and ultrasound.

9. A system for multiple pocket-forming in wireless power transmission, the system comprising:

a transmitter comprising:

- a first communication component configured to establish one or more communication connections with one or more receivers respectively, including establishing, in response to receiving an advertisement signal from a first receiver, a first communication connection with the first receiver, and the first communication component is further configured to transmit and receive at a given interval one or more communication signals with each respective receiver over each respective communication connection;

- an integrated circuit configured to generate power transmission waves based on data derived from each respective communication signal, and to modify the power transmission waves in accordance with each respective communication signal to form a respective pocket of energy at respective locations associated with each respective receiver; and

- a plurality of antennas configured to transmit one or more power transmission waves to each respective receiver, wherein a first subset of the plurality of antennas transmits to the first receiver of the one or more receivers, and wherein one or more subsets of antennas are respectively assigned to transmit to each of the one or more receivers; and

the first receiver comprising:

- a receiver communication component configured to transmit the advertisement signal identifying the first receiver, and to transmit and receive first communications signals with the transmitter over the first communication connection, wherein a respective first communication signal of the first communication signals of the first receiver indicates the amount of power derived from a respective pocket of energy formed at a first location associated with the first receiver;

45

a plurality of antennas configured to receive one or more first power transmission waves from the transmitter, wherein the one or more first power transmission waves are derived from the respective pocket of energy formed at the first location associated with the first receiver;

power circuitry, in response to the plurality of antennas deriving the one or more first power transmission waves from the respective pocket of energy, configured to convert the one or more first power transmission waves of the respective pocket of energy into an electrical energy and provide the electrical energy to an electronic device associated with the first receiver; and

a processor configured to determine the amount of energy derived from the respective pocket of energy and instruct the receiver communication component to transmit the respective first communication signal indicating the amount of energy to the transmitter.

10. The system according to claim **9**, wherein the one or more communication signals are based on a wireless communication protocol selected from the group consisting of: Bluetooth, Bluetooth low-energy, wireless fidelity (Wi-Fi), near-field communication (NFC), and ZigBee.

11. The system according to claim **9**, wherein the power circuitry includes radar, infrared cameras, or sound devices configured for sonic triangulation for determining a position of the electronic device to converge the power transmission waves in three-dimensional space for the pocket of energy for charging or powering the electronic device.

12. The system according to claim **11**, wherein the electronic device is selected from the group consisting of: a wristwatch, a headset, a battery, and a toy.

13. The system according to claim **9**, wherein an antenna of the transmitter comprises plastic or rubber and is configured to transmit in a frequency range of about 900 MHz to about 5.8 GHz, and wherein an antenna of the receiver comprises plastic or rubber and is configured to receive in the frequency range of about 900 MHz to about 5.8 GHz.

14. The system according to claim **9**, wherein the plurality of antennas of the transmitter is configured to transmit power transmission waves that are selected from the group consisting of: electromagnetic wave, radio wave, microwave, acoustics, ultrasound, and magnetic resonance.

15. A system for multiple pocket-forming in wireless power transmission, the system comprising:

a transmitter comprising:

at least two antennas configured to transmit power transmission waves converging in constructive interference patterns to form one or more pockets of energy, wherein each respective antenna transmits each respective power transmission wave in a direction irrespective of the at least two antennas of the transmitter;

communication circuitry configured to generate the power transmission waves and one or more communications signals containing data associated with the power transmission waves; and

a first micro-controller configured to:

control generation of the constructive interference patterns of the power transmission waves to form the one or more pockets of energy at one or more locations associated with one or more receivers;

control the communication circuitry, wherein an integrated chip associated with the micro-controller is configured to adjust a phase and a magnitude

46

of the power transmission waves to form the one or more pockets of energy at each respective location; and

compute a phase and a gain of each respective power transmission wave transmitted from each respective antenna of the transmitter, wherein the phase and the gain of each respective power transmission wave is determined irrespective of the at least two antennas; and

an electronic device comprising a receiver integrated in the electronic device comprising:

at least one antenna configured to derive energy from a respective pocket of energy of the one or more pockets of energy at a location of the receiver; and
a second micro-controller configured to generate one or more communication signals indicating energy requirements of the electronic device to the transmitter.

16. The system according to claim **15**, wherein each antenna of the receiver operates at a different frequency.

17. The system according to claim **15**, the transmitter further comprising an array of antennas embedded into the transmitter, wherein the array of antennas comprises one or more antennas from the at least two antennas, and wherein each antenna of the array transmits at a same frequency.

18. The system according to claim **15**, wherein the transmitter comprises a plurality of arrays of antennas, wherein one or more antennas of a first array of the plurality of arrays of the transmitter operate at a frequency of 2.4 GHz, and wherein one or more antennas of a second array of the plurality of arrays of the transmitter operate at a frequency of 5.8 GHz.

19. The system according to claim **15**, wherein the transmitter comprises at least one array of antennas having a plurality of antennas configured to transmit power transmission waves to a plurality of receivers,

wherein a first subset of antennas from a first array of the at least one array transmits at a first frequency matching a first set of antennas of a first receiver of the plurality of receivers, and

wherein a second subset of antennas of the first array transmits at a second frequency matching a second set of antennas of a second receiver of the plurality of receivers.

20. The system according to claim **15**, wherein the first and second micro-controllers communicate on wireless communication protocols selected from the group consisting of: Bluetooth, Wi-Fi, NFC, and Zigbee.

21. The system according to claim **15**, wherein at least one antenna of the transmitter operates in a frequency range of about 900 MHz to about 5.8 GHz, and wherein at least one antenna of the receiver operates in the frequency range of about 900 MHz to about 5.8 GHz.

22. The system according to claim **15**, wherein the electronic device comprising the integrated receiver is selected from the group consisting of: a tablet, a smartphone and a notebook computer.

23. The system according to claim **15**, wherein the receiver of the electronic device receives power transmission waves from the respective pocket of energy using a primary frequency, and wherein the electronic device further comprises a secondary transmitter configured to transmit secondary power transmission waves to a second electronic device, wherein the secondary power transmission waves establish a secondary pocket of energy using a secondary frequency.

47

24. The system according to claim 15, wherein the micro-controller within the transmitter adjusts the gain and the phase of each respective power transmission wave based on the one or more communication signals received from the receiver.

25. The system according to claim 24, wherein the first micro-controller of the transmitter is further configured to adjust the phase to form conjugates taking into account a built-in phase of each omni-directional antenna of the at least two antennas of the transmitter to focus power transmission waves in two channels following paths that are most efficient paths to form pockets of energy relative to each of one or more receivers while avoiding obstacles.

26. A method of forming pockets of energy, the method comprising:

capturing, by a transmitter, a first signal of one or more communications signals from a first receiver device;

establishing, by the transmitter, a first communication connection hosting first communication signals between the transmitter and the first receiver;

assigning, by the transmitter, a first subset of one or more antennas of the transmitter to transmit one or more first power transmission waves to the first receiver, the one or more first power transmission waves having a phase and a gain that cause the one or more first power transmission waves to converge at a first location with

48

respect to the first receiver based on one or more of the first communication signals, thereby forming a first pocket of energy at the first location;
at a predetermined interval:

ceasing, by the transmitter, processing of the communications signals arriving over the first communication connection at a predetermined interval;

capturing, by the transmitter, a second signal of one or more communications signals from a second receiver;

establishing, by the transmitter, a second communication connection hosting second communication signals between the transmitter and the second receiver;
and

assigning, by the transmitter, a second subset of antennas of the transmitter to transmit one or more second power transmission waves to the second receiver device, the one or more second power transmission waves having a phase and a gain that cause the one or more second power transmission waves to converge at a second location with respect to the second receiver based on one or more of the second communication signals, thereby forming a second pocket of energy at the second location.

* * * * *