



US009957622B2

(12) **United States Patent**  
**Mosby et al.**

(10) **Patent No.:** **US 9,957,622 B2**  
(45) **Date of Patent:** **May 1, 2018**

(54) **DEVICE AND METHOD OF OBTAINING DIOLS AND OTHER CHEMICALS USING DECARBOXYLATION**

(58) **Field of Classification Search**  
CPC ..... C25B 3/00; C25B 1/003; C25B 9/00  
(Continued)

(71) Applicant: **FIELD UPGRADING LIMITED,**  
Calgary (CA)

(56) **References Cited**

(72) Inventors: **James Mosby,** Salt Lake City, UT (US); **Sai Bhavaraju,** West Jordan, UT (US); **Mukund Karanjikar,** West Valley City, UT (US)

U.S. PATENT DOCUMENTS

2,760,926 A 8/1956 Kronenthal  
2,867,569 A 1/1959 Kronenthal  
(Continued)

(73) Assignee: **FIELD UPGRADING LIMITED,**  
Calgary, Alberta (CA)

FOREIGN PATENT DOCUMENTS

CN 101089231 A 12/2007  
CN 101336313 A 12/2008  
(Continued)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days. days.

OTHER PUBLICATIONS

(21) Appl. No.: **13/790,744**

Palit, Santi R., "The Solubility of Soaps and of Some Salts in Mixtures of Solvents, One of Which Is of Glycolic Type", *Utah Consortia UALC*, vol. 69, (Dec. 1947),3120-29.

(22) Filed: **Mar. 8, 2013**

(Continued)

(65) **Prior Publication Data**

US 2013/0186770 A1 Jul. 25, 2013

*Primary Examiner* — Zulmariam Mendez

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 12/840,401, filed on Jul. 21, 2010, now abandoned, and a  
(Continued)

(57) **ABSTRACT**


A method for converting carboxylic acids (including carboxylic acids derived from biomass) into hydrocarbons. The produced hydrocarbons will generally have at least two oxygen containing substituents (or other substituents). In one example of application, the electrolysis converts alkali salts of carboxylic acids into diols which can then be used as solvents or be dehydrated to produce dienes, which can then be used to produce elastic polymeric materials. This process allows custom synthesis of high value chemicals from renewable feed stocks such as carboxylic acids derived from biomass.

(51) **Int. Cl.**  
**C25B 9/08** (2006.01)  
**C25B 15/00** (2006.01)

(Continued)

(52) **U.S. Cl.**  
CPC ..... **C25B 3/10** (2013.01); **C10G 3/00** (2013.01); **C25B 9/08** (2013.01);  
(Continued)

**25 Claims, 9 Drawing Sheets**



**Related U.S. Application Data**

- continuation-in-part of application No. 12/840,913, filed on Jul. 21, 2010, now Pat. No. 8,647,492, and a continuation-in-part of application No. 12/840,508, filed on Jul. 21, 2010, now Pat. No. 8,506,789, and a continuation-in-part of application No. 13/612,192, filed on Sep. 12, 2012, now abandoned, and a continuation-in-part of application No. 13/092,685, filed on Apr. 22, 2011, now Pat. No. 9,051,656.
- (60) Provisional application No. 61/258,557, filed on Nov. 5, 2009, provisional application No. 61/228,078, filed on Jul. 23, 2009, provisional application No. 61/260,961, filed on Nov. 13, 2009.
- (51) **Int. Cl.**  
**C25B 9/06** (2006.01)  
**C25B 3/10** (2006.01)  
**C10G 3/00** (2006.01)
- (52) **U.S. Cl.**  
 CPC .. *C10G 2300/1011* (2013.01); *C10G 2300/44* (2013.01); *Y02P 30/20* (2015.11)
- (58) **Field of Classification Search**  
 USPC ..... 205/413; 204/193, 194, 242; 568/853, 568/854  
 See application file for complete search history.

(56) **References Cited**

## U.S. PATENT DOCUMENTS

3,193,479	A	7/1965	Baizer	
3,249,521	A	5/1966	Baizer	
3,885,626	A	5/1975	Gale et al.	
3,896,011	A *	7/1975	Isoya .....	C25B 3/10 205/418
3,992,471	A	11/1976	Priegnitz	
3,994,471	A	11/1976	Priegnitz	
4,006,065	A	2/1977	Meresz et al.	
4,093,521	A	6/1978	Renton et al.	
4,123,336	A	10/1978	Seko et al.	
4,182,661	A	1/1980	Lynch et al.	
4,402,804	A	9/1983	Jackson	
4,450,059	A	5/1984	Eskamani et al.	
4,464,236	A	8/1984	Noding	
5,084,146	A	1/1992	Huang	
5,290,404	A	3/1994	Toomey	
5,290,405	A	3/1994	Joshi et al.	
5,580,430	A	12/1996	Balagopal et al.	
5,625,059	A *	4/1997	Sedelmeier .....	C07D 205/08 540/310
5,633,400	A	5/1997	Wagner et al.	
5,841,002	A	11/1998	Harrison et al.	
5,892,107	A	4/1999	Farone et al.	
6,193,872	B1	2/2001	Reason et al.	
6,238,543	B1	5/2001	Law et al.	
6,362,380	B1	3/2002	Eicken et al.	
6,392,091	B2 *	5/2002	Lin .....	562/485
7,166,724	B2	1/2007	Hilarious et al.	
8,506,789	B2	8/2013	Bhavaraju et al.	
8,647,492	B2	2/2014	Karanjekar et al.	
8,821,710	B2	9/2014	Bhavaraju et al.	
8,853,463	B2	10/2014	Karanjekar et al.	
2001/0019020	A1	9/2001	Merk et al.	
2004/0035715	A1	2/2004	Putter et al.	
2005/0126926	A1	6/2005	Ogihara et al.	
2005/0177008	A1	8/2005	Balagopal et al.	
2007/0012578	A1	1/2007	Albers et al.	
2007/0074975	A1	4/2007	Buschmann et al.	
2007/0181437	A1	8/2007	Stapley et al.	
2008/0177114	A1	7/2008	Goossen et al.	
2008/0245671	A1	10/2008	Balagopal et al.	
2009/0057162	A1	3/2009	Balagopal et al.	

2009/0074611	A1	3/2009	Monzyk et al.	
2009/0305942	A1 *	12/2009	Day et al. ....	510/437
2010/0044242	A1	2/2010	Bhavaraju et al.	
2010/0159553	A1	6/2010	Bradin	
2010/0258447	A1	10/2010	Fan	
2010/0324310	A1	12/2010	Dumesic et al.	
2010/0331170	A1	12/2010	Balagopal et al.	
2011/0000782	A1	1/2011	Reddy et al.	
2011/0024288	A1	2/2011	Bhavaraju et al.	
2011/0027848	A1	2/2011	Karanjekar et al.	
2011/0035995	A1	2/2011	Williams	
2011/0111475	A1	5/2011	Kuhry et al.	
2011/0168569	A1	7/2011	Bhavaraju et al.	
2011/0226633	A1	9/2011	Bhavaraju et al.	
2011/0240484	A1	10/2011	Pendleton et al.	
2012/0031769	A1	2/2012	Bhavaraju et al.	
2012/0035403	A1	2/2012	Flytzani-Stephanopoulos et al.	
2012/0123168	A1	5/2012	Bhavaraju	
2012/0142945	A1	6/2012	Hwang et al.	
2012/0316093	A1	12/2012	Zhan et al.	
2013/0001095	A1	1/2013	Bhavaraju et al.	
2013/0284607	A1	10/2013	Bhavaraju et al.	
2014/0154766	A1	6/2014	Karanjekar et al.	
2015/0361565	A1	12/2015	Mosby et al.	

## FOREIGN PATENT DOCUMENTS

EP	0838435	4/1998
GB	787976	12/1957
JP	06271499	9/1994
SU	979325	12/1982
WO	WO-2007/095215	8/2007
WO	WO2011133906	10/2011
WO	2012103529	8/2012
WO	WO2012103529	8/2012

## OTHER PUBLICATIONS

- Park, Sang Ho "PCT International Search Report", Int. App. No. PCT/US2010/042715, (dated Apr. 29, 2011),1-3.
- Park, Sang Ho "PCT Written Opinion", Int. App. No. PCT/US2010/042715, (dated Apr. 29, 2011),1-4.
- Kang, Sang Yoon "PCT International Search Report", Int. App. No. PCT/US2010/042756, (dated Feb. 28, 2011),1-3.
- Kang, Sang Yoon "PCT Written Opinion", Int. App. No. PCT/US2010/042756, (dated Feb. 28, 2011),1-4.
- Park, Sang Ho "PCT International Search Report", Int. App. No. PCT/US2010/042780, (dated May 2, 2011),1-3.
- Park, Sang Ho "PCT Written Opinion", Int. App. No. PCT/US2010/042780, (dated May 2, 2011),1-4.
- Bozell, Joseph J., "Connecting Biomass and Petroleum Processing with a Chemical Bridge", *Science*, (Jul. 30, 2010),vol. 329: 522-523.
- Bond, Jesse Q., et al., "Integrated Catalytic Conversion of gamma-Valerolactone of Liquid Alkenes for Transportation Fuels", *Science*, (Feb. 26, 2010),vol. 327: 1110-1114.
- Chum, H L., et al., "Photoelectrochemistry of Levulinic Acid on Undoped Platinized n-TiO<sub>2</sub> Powders", *J. Phys. Chem.*, (1983),vol. 87: 3089-3093.
- Schafer, Hans-Jurgen "Recent Contributions of Kolbe Electrolysis to Organic Synthesis", *Topics in Current Chemistry*, (1990),vol. 152: 91-151.
- Rabjohn, et al., "Kolbe Electrosynthesis of Alkanes with Multiple Quaternary Carbon Atoms", *J. Org. Chem.*, (1981),vol. 46, pp. 4082-4083.
- Wong, Edna "USPTO Office Action", U.S. Appl. No. 12/840,508, (dated Nov. 2, 2011),17 pages.
- Kobzeva, et al., "Effect of a solvent on anode processes", *Elektrokhimiya*, vol. 11. No. 5, (1975),1 page abstract.
- Ono, et al., "Electrolysis of fatty acids I", *Ind. Chem. Sect.* 53, (1950),1 page.
- Minami, et al., "Electrolysis of Fatty Acids II", *Kogyo Kagaku Zasshi*, vol. 53, (1950),1 page abstract.
- Obermuller, "Saponification by Sodium Ethoxide", *J Chem. Soc.*, Abstr. 62, (1892),1 page abstract.

(56)

## References Cited

## OTHER PUBLICATIONS

- Wong, Edna "USPTO Office Action", U.S. Appl. No. 12/840,913, (dated Nov. 16, 2011), 16 pages.
- Wong, Edna "Non-Final Office Action", U.S. Appl. No. 12/840,508, (dated Apr. 26, 2012), 1-32.
- Wong, Edna "Non-Final Office Action", U.S. Appl. No. 12/840,913, (dated Apr. 10, 2012), 1-12.
- Mendez, Zulmariam "Non-Final Office Action", U.S. Appl. No. 12/840,401, (dated Jun. 5, 2012), 1-12.
- Wong, Edna "Non-Final Office Action", U.S. Appl. No. 13/357,463, (dated Jun. 4, 2012), 1-25.
- Pande, et al., "Studies on Kolbe's Electrosynthesis", *Electrochimica Acta*, Aug. 1961, vol. 4, (Aug. 1961), 215-231.
- Ho, Park S., "International Search Report", PCT US 2011/035782 (corresponding to U.S. Appl. No. 13/103,716, (dated Feb. 9, 2012), 1-3.
- Ho, Park S., "Written Opinion of the International Searching Authority", PCT US 2011/035782 (corresponding to U.S. Appl. No. 13/103,716, (dated Feb. 9, 2012), 1-4.
- Ko, et al., "Computer Translation of the Detailed Description of JP 6-271499", Japanese Patent publication 06-271499, (Sep. 27, 1994), 1-8.
- Aslanov, N. N. "English Language Bibliographical Information and Abstract", SU Patent No. 979325, (Dec. 7, 1982), 1-3.
- Choi, et al., "Recovery of lactic acid from sodium lactate by ion substitution using ion-exchange membrane", *Separation and Purification Technology* 28 (2002), Elsevier, (Mar. 4, 2002), 69-79.
- Habova, et al., "Application of Electrodialysis for Lactic Acid Recovery", *Czech J. Food Sci.*, vol. 19, No. 2 (2001), (Jan. 1, 2001), 73-80.
- Huang, et al., "Application of electrodialysis to the production of organic acids: State-of-the-art and recent developments", *Journal of Membrane Science* 288 (2007), Elsevier, (Nov. 25, 2006), 1-12.
- Lu, et al., "Modeling of the mass transfer and conduction behavior in electro-electrodialysis with oil/water emulsion as the catholyte", *Journal of Membrane Science* 322 (2008), Elsevier, (Jun. 5, 2008), 265-274.
- Moon, et al., "Competitive Anion Transport in Desalting Mixtures of Organic Acids by Batch Electrodialysis", *Journal of Membrane Science* 141 (1998), Elsevier, (Apr. 1, 1998), 75-89.
- Palaty, et al., "Continuous dialysis of carboxylic acids. Permeability of Neosepta-AMH membrane", *Desalination* 216 (2007), Elsevier, (Oct. 1, 2007), 345-355.
- Prado Rubio, et al., "Modeling Reverse Electro-Enhanced Dialysis for Integration with Lactic Acid Fermentation", *CAPEC*, Department of Chemical and Biochemical Engineering Technical University of Denmark (DTU), DK-2800 Lyngby, Denmark, 2009, Available as "A-DK-Prado Rubio-OA-1" at Docstoc.com, <http://www.docstoc.com/search/modeling%20reverse%20electro-enhanced%20dialysis%20for%20integration%20with%20lactic%20acid%20fermentation?catid=0>, (Jan. 1, 2009), 1-2.
- Yi, et al., "An in situ coupling separation process of electro-electrodialysis with back-extraction", *Journal of Membrane Science* 255 (2005), Elsevier, (Mar. 21, 2005), 57-65.
- Park, Sang H., "International Search Report", PCT Application No. PCT/US2011/033626 (corresponding to U.S. Appl. No. 13/092,685, (dated Feb. 8, 2012), 1-3.
- Park, Sang H., "Written Opinion of the International Searching Authority", PCT Application No. PCT/US2011/033626 (corresponding to U.S. Appl. No. 13/092,685, (dated Feb. 8, 2012), 1-4.
- Paul, et al., "Reactions of Sodium Metal with Aromatic Hydrocarbons", *J. Am. Chem. Soc.*, 1956, 78 (1), (Jan. 1956), 116-120.
- Conway, et al., "New Approaches to the Study of Electrochemical Decarboxylation and the Kolbe Reaction. I. The Model Reaction with Formate", *Canadian Journal of Chemistry* (no month, 1963), vol. 41, (1963), 21-37.
- Wong, Edna "Final Office Action", U.S. Appl. No. 12/840,913, (dated Aug. 14, 2012), 1-28.
- Wong, Edna "Final Office Action", U.S. Appl. No. 12/840,508, (dated Nov. 27, 2012), 1-25.
- Wong, Edna "Final Office Action", U.S. Appl. No. 13/357,463, (dated Sep. 19, 2012), 1-17.
- Dzik, et al., "Carboxylates as sources of carbon nucleophiles and electrophiles: comparison of decarboxylative and decarbonylative pathways", *Chemical Science*, 2012, vol. 3, Issue No. 9 (2012), (May 3, 2012), 2671-78.
- Mendez, Zulmariam "Final Office Action", U.S. Appl. No. 12/840,401, (dated Mar. 15, 2013), 1-12.
- Wong, Edna "Non Final Office Action", U.S. Appl. No. 12/840,913, (dated Mar. 28, 2013), 1-31.
- Sekine, Isao et al., "Effect of the Concentration of Acetate or Propionate on the Abnormal Phenomena in the Kolbe Reaction", *Denki Kagaku*, vol. 41(9), (1973), 702-707.
- Wong, Edna "Non Final Office Action", U.S. Appl. No. 13/357,463, (dated Apr. 9, 2013), 1-21.
- Stapley, et al., "English Language Abstract", CN101336313A, (Dec. 31, 2008), 1.
- Hongyou, et al., "English Language Abstract", CN101089231A, (Dec. 19, 2007), 1.
- Le, Zhikang "Chinese Office Action", Chinese Application No. 201080024541.8, (dated Jan. 21, 2014), 1-10.
- Wong, Edna "Notice of Allowance", U.S. Appl. No. 12/840,913, (dated Oct. 4, 2013), 1-11.
- Wong, Edna "Final Office Action", U.S. Appl. No. 13/357,463, (dated Sep. 6, 2013), 1-16.
- Wong, Edna "Non-Final Office Action", U.S. Appl. No. 13/612,192, (dated Dec. 10, 2013), 1-33.
- Wong, Edna "Final Office Action", U.S. Appl. No. 13/357,463, (dated Jan. 3, 2014), 1-14.
- Shafer, Hans J., "Electrochemical Conversion of Fatty Acids", *European Journal of Lipid Science and Technology*, vol. 114, Issue 1, (Oct. 11, 2011), 2-9.
- Mendez, Zulmariam "Non Final Office Action", U.S. Appl. No. 12/840,401, (dated Jul. 30, 2013), 1-15.
- Wong, Edna "Final Office Action", U.S. Appl. No. 12/840,913, (dated Jul. 18, 2013), 1-16.
- Wong, Edna "Notice of Allowance", U.S. Appl. No. 12/840,508, (dated Apr. 29, 2013), 1-11.
- Kim, Su M., "International Search Report", PCT Application No. PCT/US2014/020786 (Corresponding to U.S. Appl. No. 14/198,026), (dated Jun. 26, 2014), 1-3.
- Kim, Su M., "Written Opinion of the International Searching Authority", PCT Application No. PCT/US2014/020786 (Corresponding to U.S. Appl. No. 14/198,026), (dated Jun. 26, 2014), 1-3.
- Mendez, Zulmariam "Non-Final Office Action", U.S. Appl. No. 12/840,401, (dated Aug. 26, 2014), 1-18.
- Wong, Edna "Final Office Action", U.S. Appl. No. 13/612,192, (dated Aug. 15, 2014), 1-18.
- Wong, Edna "Non-Final Office Action", U.S. Appl. No. 13/930,211, (dated Jul. 23, 2014), 1-43.
- Klocke, et al., "Influences on the Selectivity of the Kolbe versus the Non-Kolbe Electrolysis in the Anodic Decarboxylation of Carboxylic Acids", *Electroorganic Synthesis*, (Nov. 2, 1992), 1-8.
- Shin, Ju C., "International Search Report", PCT Application No. PCT/US2014/028842 (Corresponding to U.S. Appl. No. 13/834,569), (dated Aug. 14, 2014), 1-3.
- Shin, Ju C., "Written Opinion of the International Searching Authority", PCT Application No. PCT/US2014/028842 (Corresponding to U.S. Appl. No. 13/834,569), (dated Aug. 14, 2014), 1-7.
- Shin, Ju C., "International Search Report", PCT/US2014/021927 (Corresponding to U.S. Appl. No. 13/790,744), (dated Jul. 10, 2014), 1-3.
- Shin, Ju C., "Written Opinion of the International Searching Authority", PCT/US2014/021927 (Corresponding to U.S. Appl. No. 13/790,744), (dated Jul. 10, 2014), 1-7.
- Mendez, Zulmariam "Final Office Action", U.S. Appl. No. 12/840,401, (dated Mar. 13, 2014), 1-23.
- Wong, Edna "Non-Final Office Action", U.S. Appl. No. 13/612,192, (dated Apr. 8, 2014), 1-24.
- Keeling, Alexander W., "Non-Final Office Action", U.S. Appl. No. 13/092,685, (dated May 20, 2014), 1-20.
- Wong, Edna "Non-Final Office Action", U.S. Appl. No. 13/103,716, (dated Jun. 24, 2014), 1-15.

(56)

## References Cited

## OTHER PUBLICATIONS

- Wong, Edna "Non-Final Office Action", U.S. Appl. No. 13/612,192, (dated Dec. 5, 2014),1-37.
- Glasstone, et al., "Studies in Electrolysis Oxydation Part V11. The Electrolysis of Acetates in Non-Aqueous Solutions.", *J. Chem. Soc.*, (Jan. 1, 1936),820-827.
- Wong, Edna "Final Office Action", U.S. Appl. No. 13/930,211, (dated Nov. 21, 2014),1-32.
- Wong, Edna "Final Office Action", U.S. Appl. No. 13/103,716, (dated Nov. 20, 2014),1-15.
- Wong, Edna "Non-Final Office Action", U.S. Appl. No. 14/198,026, (dated Nov. 14, 2014),1-20.
- Keeling, Alexander W., "Notice of Allowance", U.S. Appl. No. 13/092,685, (dated Feb. 19, 2015),1-18.
- Wong, Edna "Notice of Allowance", U.S. Appl. No. 13/103,716, (dated Feb. 26, 2015),1-9.
- Li, Maoying "Chinese Office Action", Chinese Application No. 2011800079268, (dated Sep. 12, 2014),1-12.
- Mendez, Zulmariam "Final Office Action", U.S. Appl. No. 12/840,401, (dated Apr. 3, 2015),1-20.
- Wong, Edna "Final Office Action", U.S. Appl. No. 14/198,026, (dated Apr. 3, 2015),1-11.
- Li, Weishan "Organic Synthesis using Kolbe reaction", *Ghangzhou Chemical Industry* vol. 20, No. 4, pp. 18-21, (Dec. 30, 1992),1-5.
- Wong, Edna "Final Office Action", U.S. Appl. No. 13/612,192, (dated Apr. 14, 2015),1-12.
- Mendez, Zulmariam "Non Final Office Action", U.S. Appl. No. 13/834,569, (dated Jul. 15, 2015),1-15.
- Li, Maoying "Non-Final Office Action", Chinese Patent Application No. 201180007926.8, (dated Aug. 18, 2015),1-15.
- Kokubo, Atsunori "First Office Action", Japanese Patent Application No. 2013-550666, (dated Aug. 25, 2015),1-13.
- Wong, Edna "Non-Final Office Action", U.S. Appl. No. 14/322,037, (dated Sep. 1, 2015),1-18.
- Weiper, et al., "Mixed Kolbe Electrolysis with Sugar Carboxylic Acids", *Angew. Chem. Int. Ed. Engl.*;(no month, 1990) vol. 29 No. 2; pp. 195-197, (1990),195-197.
- Akhir, Sharul Kamal B., "Malaysian Search Report", Malaysia Patent Application No. PI 2011004930, (dated Feb. 26, 2015),1.
- Keeling, Alexander W., "Non-Final Office Action", U.S. Appl. No. 14/206,981, (dated Oct. 7, 2015),1-18.
- Ebersson, L., "Studies on the Kolbe Electrolytic Synthesis", *Acta. Chem. Scand.*, vol. 17, No. 7, 1963. pp. 2004-2018, XP002751055, 1963, 1-15.
- Haufe, et al., "Bifunktionelle Verbindungen durch Kolbe-Elektolyse", *Chemie-Ing. Techn.*, vol. 42, No. 4, 1970, pp. 170-175, XP002751054, 1970, 1-6.
- Keeling, Alexander W., "Final Office Action", U.S. Appl. No. 14/206,981, dated Feb. 25, 2016, 1-20.
- Kleidernigg, Oliver, "European Search Report", EP Patent Application No. 12739864.2, dated Nov. 18, 2015, 1-9.
- Mendez, Zulmariam, "Final Office Action", U.S. Appl. No. 13/834,569, dated Feb. 23, 2016, 1-17.
- Mendez, Zulmariam, "Non Final Office Action", U.S. Appl. No. 13/790,744, dated Dec. 28, 2015, 1-15.
- Thomas, Ciel P., "Non-Final Office Action", U.S. Appl. No. 14/469,878, dated Mar. 3, 2016, 1-13.
- Unknown, "Notice of Allowance", Japanese Patent Application No. 2013-550666, dated Feb. 2, 2016, 1-4.
- Wong, Edna, "Non Final Office Action", U.S. Appl. No. 14/098,000, dated Dec. 29, 2015, 1-27.
- Wong, Edna, "Final Office Action", U.S. Appl. No. 14/322,037, dated Dec. 18, 2015, 1-21.
- Wong, Edna, "Non Final Office Action", U.S. Appl. No. 14/322,037, dated Mar. 29, 2016, 1-18.
- Ebersson, Lennart, "Studies on the Kolbe Electrolytic Synthesis", *Acta Chemica Scandinavica*, vol. 17, No. 5, Jan. 1, 1963 (Jan. 1, 1963), pp. 1196-1202, Jan. 1, 1963, 1-7.
- Keeling, Alexander W., "Notice of Allowance", U.S. Appl. No. 14/206,981, dated Jul. 14, 2016, 1-10.
- Mendez, Zulmariam, "Final Office Action", U.S. Appl. No. 13/790,744, dated Aug. 9, 2016, 1-18.
- Mendez, Zulmariam, "Non Final Office Action", U.S. Appl. No. 13/834,569, dated Jul. 22, 2016, 1-15.
- Ritter, Thomas, "European Search Report", European Patent Application No. 118149293, dated Sep. 12, 2016, 1-11.
- Ritter, Thomas, "European Search Report", European Patent Application No. 147608897, dated Sep. 12, 2016, 1-11.
- Ritter, Thomas, "European Search Report", European Patent Application No. 147608889, dated Sep. 12, 2016, 1-7.
- Sharkey, et al., "2,7-Dimethyl-2,7-Dinitrooctane", *Organic Syntheses*, vol. 41, Jan. 1, 1961 (Jan. 1, 1961), p. 24, Jan. 1, 1961, 1-5.
- Thomas, Ciel P., "Final Office Action", U.S. Appl. No. 14/469,878, Nov. 3, 2016, 1-7.
- Unknown, "English Transation of Non Final Office Action", Korean Patent Application No. 10-2012-7027450, dated Oct. 27, 2016, 1-5.
- Unknown, "Non-Final Office Action", Korean Patent Application No. 10-2012-7027450, dated Oct. 27, 2016, 1-3.
- Unknown, "Notice of Allowance", Chinese Patent Application No. 201180007926.8, dated May 24, 2016, 1-4.
- Wong, Edna, "Final Office Action", U.S. Appl. No. 14/322,037, dated Jul. 25, 2016, 1-21.
- Wong, Edna, "Final Office Action", U.S. Appl. No. 14/098,000, dated Jun. 6, 2016, 1-34.
- Wong, Edna, "Non-Final Office Action", U.S. Appl. No. 14/098,000, dated Oct. 13, 2016, 1-18.
- Zhuo, et al., "Degradation of Perfluorinated Compounds on a Boron-Doped Diamond Electrode", *Electrochimica Acta*, Elsevier Science Publishers, Barking, GB, vol. 77, Apr. 14, 2012 (Apr. 14, 2012), pp. 17-22, Apr. 14, 2012, 17-22.
- Hibino, et al., "Oxidative Coupling of CH<sub>4</sub> using Alkali-Metal Ion Conductors as a Solid Electrolyte", *J. Chem. Soc., Faraday Trans.* (no month, 1996), vol. 92, No. 13, pp. 2393-2396, Jan. 1, 1996, 2393-2396.
- Thomas, Ciel P., "Non-Final Office Action", U.S. Appl. No. 14/704,783, dated Apr. 5, 2017, 1-16.
- Unknown, "Notice of Allowance", Korean Patent Application No. 10-2012-7027450, dated Apr. 27, 2017, 1-3.
- Wong, Edna, "Final Office Action", U.S. Appl. No. 14/322,037, dated May 9, 2017, 1-18.
- Wong, Edna, "Notice of Allowance", U.S. Appl. No. 14/098,000, dated May 10, 2017, 1-7.
- Thomas, Ciel P., "Notice of Allowance", U.S. Appl. No. 14/469,878, dated Feb. 15, 2017, 1-20.
- Wong, Edna, "Final Office Action", U.S. Appl. No. 14/098,000, dated Feb. 28, 2017, 1-19.
- Wong, Edna, "Non-Final Office Action", U.S. Appl. No. 14/322,037, dated Nov. 23, 2016, 1-10.

\* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4






FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9

**DEVICE AND METHOD OF OBTAINING  
DIOLS AND OTHER CHEMICALS USING  
DECARBOXYLATION**

RELATED APPLICATIONS

This application is a continuation-in-part of U.S. patent application Ser. No. 12/840,401, filed Jul. 21, 2010, which in turn, claims the benefit of U.S. Provisional Patent Applications Nos. 61/258,557 filed Nov. 5, 1999, 61/228,078 filed Jul. 23, 2009, and 61/260,961 filed Nov. 13, 2009. This application is also a continuation-in-part of U.S. patent application Ser. No. 12/840,913, filed Jul. 21, 2010. This application is also a continuation-in-part of U.S. patent application Ser. No. 12/840,508, filed Jul. 21, 2010. This application also a continuation-in-part of U.S. patent application Ser. No. 13/612,192 filed Sep. 12, 2012. This application is also a continuation-in-part of U.S. patent application Ser. No. 13/092,685, filed Apr. 22, 2011.

All of the above-recited provisional and non-provisional applications are expressly incorporated herein by reference.

TECHNICAL FIELD

The present disclosure relates to a method of producing hydrocarbon materials such as diols. More specifically, the present disclosure provides an electrochemical decarboxylation process whereby diols, or other similar chemicals, may be formed.

BACKGROUND

The above-recited patent applications teach methods of forming hydrocarbons and other molecules using an electrochemical decarboxylation process ("EDP"). The reader is presumed to be familiar with the disclosure and content of these prior applications.

Many organic molecules are used in industry and in commercial processing. One type of these molecules are dienes, such as, for example, 1,3-butadiene. Butadiene has a structure  $\text{CH}_2\text{CHCHCH}_2$ . Dienes have two double bonds in the molecule.

Commercially, diene monomers are produced by one of the four conventional methods; 1) by catalytic dehydrogenation of concentrate n-butylenes, 2) by catalytic dehydrogenation of n-butane, 3) as a by-product in low yields from severe high-temperature cracking of liquid hydrocarbons, and 4) from alcohols and/or diols by a combination of catalytic dehydrogenation and/or hydration. U.S. Pat. No. 3,992,471 describes the production of dienes and is incorporated herein by reference.)

One of the most widely used methods to produce dienes is the dehydration of the corresponding diol, for example 1,3-butadiene is obtained from the dehydration of either 1,4-butanediol or 2,3-butanediol. Such diol molecules are conventionally obtained using the Reppe reaction, hydrolysis of halogenated compounds, or the hydrogenation of anhydrides. All of these conventional pathways involve multiple processes which require high temperature catalytic reactions using petroleum based feedstock.

It would be advantageous to find a manufacturing method to produce diene monomers for the vastly important elastic materials from non-petroleum sources, such as bio generated feedstock and using more economically sustainable processes, for example processes that do not rely on expensive catalysis, high temperatures and pressures. It is the aim of the disclosed invention to synthesize diene monomers start-

ing from biomass, which are then electrochemically converted to diols followed by the conversion to dienes by a dehydration step. Such a process affords a non-petroleum source of diene monomers using a methodology that requires only one catalytic high temperature process.

SUMMARY

The present embodiments relate to methods to synthesize hydrocarbons such as, for example, hydrocarbons that have at least two oxygen containing functional groups. These methods may produce such hydrocarbons from inexpensive bio-generated precursors using an electrochemical decarboxylation process. The decarboxylation process converts alkali salts of carboxylic acids to hydrocarbon compounds which have two or more oxygen containing substituents.

In one example, the decarboxylation process is used to produce diols which can then be dehydrated to form dienes. One benefit of this process is that the final structure of the diene can be tuned by the choice of the carboxylic acid used as the precursor. There are a large number of carboxylic acids available from both natural and synthetic sources (including biomass), which allows the structure and functional group of the diene to be tailored for specific properties and functionalities. The diene that is produced can then be used in a variety of different applications. For example, the diene may be used as a starting material for the production of synthetic rubber. The ability to control the structure and functional groups in the diene allows the rubber to be designed and tailored, as desired. Besides providing a low temperature route to custom organic molecules containing multiple oxygen containing function groups, the present embodiments provide a synthetic methodology to produce custom organic molecules from various feedstocks (including renewable bio-generated feedstocks). Thus, the present embodiments may operate to produce dienes from renewable feedstocks (biomass) instead of currently used petroleum based feedstocks.

The production of diols is used herein as an example to demonstrate the present processes for producing hydrocarbons or other organic molecules with multiple functional groups. Conversion of the diols to dienes may produce dienes in which the double bonds are located at the terminal positions of the carbon chain. Some non-limiting examples are; 1,3-butadiene, 1,4-pentadiene, isoprene, and 1,5-hexadiene. Such monomers can then be used to make a variety of polymer products including acrylonitrile butadiene styrene (ABS). (ABS is the largest used (by volume) thermoplastic with over 1 million tons per year produced globally, and thus, the present embodiments provide methods for producing the starting materials for ABS from a renewable, non-petroleum based sources.)


In one example, the present processes may involve four (4) processing steps. These steps include: 1) fermentation to produce carboxylic acids from biomass, 2) saponification of the carboxylic acids to form alkali metal carboxylate salts, 3) decarboxylation of the alkali carboxylates forming diols, and 4) dehydration of the diols to form the desired diene monomer.

The fermentation of biomass to produce carboxylic acids is a well-known and studied process that is used to produce starting materials for a variety of bio-generated products. The fermentation is performed on a slurry of the biomass, using specific bacteria chosen for the production of the desired carboxylic acid. The composition of the biomass slurry used for the fermentation depends on the feedstock and conditions that are required by the bacteria. For most

carboxylic acids, there are a variety of bacteria that are used in industry, permitting the carboxylic acid to be produced from a variety of biomass materials. For example, lactic acid can be produced via the fermentation of glucose, molasses, corn or cheese whey. Depending on the bacteria used in the fermentation process, the pH of the resulting carboxylic stream can be low enough that the pure acid is directly obtained or it could have a pH range in which salts of the carboxylic acid are obtained. For example, lactic acid is most commonly produced as calcium lactate because the low solubility allows this to be easily isolated from the fermentation bath as taught by U.S. Patent Application Publication No. 2012/0142945, which application is incorporated herein by reference. The calcium lactate is then acidified allowing the lactic acid to be obtained. For the present embodiments, the carboxylic acid may be in the acidic form and may have additional functional groups present which provide the desired functionality of the final synthesized compound.

Lactic acid is produced commercially on hundreds of thousands metric tons annual through the fermentation of carbohydrates such as sucrose, glucose, or lactose. Glucose which can be converted from sucrose or directly obtained from starch is converted into two moles of lactic acid during the fermentation process. The fermentation of lactose, which is a dairy by-product, in the presence of water produces four moles of lactic acid. These well established routes to produce lactic acid from biomass make it a renewable and economical precursor for producing butadiene, which is currently produce using petroleum based hydrocarbons.


The saponification of carboxylic acid follows from the generally accepted procedure of reacting the carboxylic acid with an alkali metal base (MOH) at an elevated temperature. Some non-limiting examples of alkali metal bases are lithium hydroxide, sodium hydroxide, potassium hydroxide, etc. A generic neutralization reaction is written as follows:



where "R" represents organic moieties, M represents an alkali metal, such as, for example sodium or lithium.


In one embodiment, this saponification reaction is carried out in a solvent with an alkoxide present such that the reaction forms an alkali carboxylate which precipitates out of solution. In such an embodiment, the alkali carboxylate salt can be easily isolated to prepare the anolyte needed for the subsequent decarboxylation step.

The alkali carboxylate may be electrochemically decarboxylated to form a radical coupling product, because the starting carboxylate has at least one additional functional group present, the resulting coupling product will have two functional groups present, forming (for example) a diol. This process is performed using a two compartment electrochemical cell, which employs a ceramic membrane commercially available from Ceramatec, Inc. of Salt Lake City, Utah. Ceramatec sells this membrane under the NaSelect® trademark. The electrolysis in the anolyte compartment follows the generic reaction scheme known as a modified Kolbe electrolysis reaction:




where "R" represents organic moieties, M represents an alkali metal, such as, for example sodium or lithium.

In another embodiment, the electrolysis in the anolyte compartment leads to products derived from a "non-Kolbe electrolysis" pathway. One of the possible products of a non-Kolbe electrolysis is an aldehyde:



This pathway can be promoted by the location and type of the additional functional groups on the carboxyl anion. The obtained aldehyde can then be reacted to form a hydroxyl-ketone following, for example, the nucleophilic addition that occurs in a basic medium. A non-exclusive summary of this reaction pathway is below.



In some embodiments, the compound obtained directly from the non-Kolbe electrolysis is economically viable, as is the case shown above in which the process produces acetoin. (Acetoin is useful as a food additive.) In other embodiments, the hydroxyl-ketone can be reduced to a diol with an additional processing step.

Once the diol is obtained (whether through the Kolbe or non-Kolbe pathway), the diol may then be subjected to a dehydration reaction, thereby producing water and a diene. The dehydration can be carried out many ways, for example in the presence of acid and a catalyst.

It should be noted that a conventional Kolbe process does not permit radical-radical coupling when there is an electron donating group in the alpha-position to the carboxylic acid group. However, by using the present techniques, there is more control over the voltage across the cell, thereby giving a diol yield. Apparently, in a traditional Kolbe reaction, the voltage across the cell is too high to allow radical-radical coupling of compounds with an electron donating group in this position. Thus, the present embodiments provide for significant advantages.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a schematic drawing of method through which biomass may be converted into alkali metal salts of carboxylic acids, which in turn, may be converted into diols and further processed, if desired, into dienes;

FIG. 2 is a schematic drawing of an electrochemical cell that may be used to decarboxylate the alkali metal salt of the carboxylic acid;

FIG. 3 is a plot of the potential and current density of an electrochemical decarboxylation of sodium 3-hydroxypropionate;

FIG. 4 shows a gas chromatogram of the products obtained from the electrochemical decarboxylation of sodium 3-hydroxypropionate;

FIG. 5 is a plot of the potential and current density of an electrochemical decarboxylation of sodium L-lactate decarboxylation;

FIG. 6 shows a gas chromatogram of the products obtained from the electrochemical decarboxylation of sodium L-lactate in methanol;

FIG. 7 shows another gas chromatogram of the products obtained from the electrochemical decarboxylation of sodium L-lactate in methanol;

FIG. 8 is a plot of the potential and current density of an electrochemical decarboxylation of sodium L-lactate in ethyl lactate; and

FIG. 9 is a gas chromatogram of the products obtained from the electrochemical decarboxylation of sodium L-lactate in ethyl lactate.

#### DETAILED DESCRIPTION

Some terms and their definitions that will be used throughout the description of the disclosed invention follows. "Bio generated" or "bio-generated," as used herein, refers to substances, either solid or fluid, which are derived from a renewable resource of biological origin. "Hydrocarbon," is defined as a compound consisting of carbon and hydrogen and can refer to saturated or unsaturated compounds. "Diene," is defined as a hydrocarbon with two double bonds, these can be conjugated or non-conjugated. "Diol," is defined as a compound with two alcohol groups present. "Carboxylic acid," is a compound with the general formula  $\text{RCO}_2\text{H}$ , where the "R" can represent saturated or unsaturated hydrocarbon chains. "Decarboxylation," as used herein refers to the process of removing  $\text{CO}_2$  from a compound, specifically from a carboxylic acid or anion. "Elastic," as used herein, is defined as the property of a material to return to its original shape after removing an external stress that causes deformation. "Symmetric" as used herein, refers to chemical structures that have at least one mirror plan symmetry element and "non-symmetric" refers to chemical structures that do not have a mirror plan. "Substituent" and "functional group" are used interchangeably, and herein refer to an atom or group of atoms that has substituted a hydrogen atom on a carbon chain of a hydrocarbon.

The present embodiments are generally directed to methods used to synthesize organic compounds with at least two oxygen containing functional groups, from inexpensive bio-generated precursors using an electrochemical decarboxylation process (EDP). In an example demonstrating the utility of this invention, the oxygen containing organic compounds are used to produce dienes.

Referring now to FIG. 1, a flow chart is illustrated which indicates how the biomass may be converted into diols, dienes and/or other useful organic molecules. More specifically, FIG. 1, shows a method by which biomass **1** may be converted into a diol **14** or diene **15**. In this method, a sample of biomass **1** is obtained. FIG. 1 shows a variety of different processes by which the biomass may be converted into a carboxylic acid **8**. The most direct way for this conversion is through a fermentation reaction **4**.

In other embodiments, the biomass **1** may be converted (separated) into carbohydrates **2**, which may undergo hydrolysis reaction **5** to obtain the carboxylic acid **8**. Alternatively, instead of using the hydrolysis reaction **5**, the carbohydrate **2** may undergo a conversion reaction **7** that results in the formation of a carboxylic acid **8**.

In other embodiments, the biomass **1** may be converted (separated) into lignins, tall oil and/or resins **3**. This material **3** may then undergo a conversion reaction **9** to obtain the carboxylic acid **8**. In other embodiments, the biomass **1** may be converted (separated) into lipids **6** which may be converted into the carboxylic acid **8**, or may undergo, as needed, a conversion reaction **9** to obtain the carboxylic acid **8**.

Following the formation of the carboxylic acids **8**, these materials may be converted to alkali salts of carboxylic acids **10**. These alkali salts **10** are the preferred precursor for the electrochemical decarboxylation process. This process may transform the alkali salts **10** into the diols **14**. At the same time, this decarboxylation reaction may form carbon dioxide **11**, a hydroxyl alkalide **12** and an alkali hydroxide or an

alkali methylate **13**. It should be noted that once the diol **14** is obtained, it may be converted into the diene **15**.

According to the disclosed embodiments, shown in FIG. **1**, the final structure of the oxygen functionalized organic compound is dependent on the carboxylic acid therefor dependent on the biomass used. It should be appreciated by one skill in the art that there are numerous sources of biomass and carboxylic acids derived from them, which thus, can lead to a large number of organic compounds that can be produced following the process flow given in FIG. **1**.

As noted here, the dienes that are produced in the present embodiments may be dienes that can be used as monomers for the production of elastic materials. The large number of carboxylate substrates that can be obtained from biomass permits the monomer to be tailored in order to obtain an elastic material with the desired properties. Some non-limiting examples of the variances that can be tailored into the monomer are; number of carbons, degree of branching in the carbon chain, and the ability to include other functional groups. Besides providing a low temperature route to custom monomers, this invention provides a methodology to produce said monomers from a renewable feedstock instead of relying on petroleum based feedstocks.

Referring now to FIG. **2**, a schematic of an electrochemical cell **110** that may be used in the decarboxylation reaction of FIG. **1**. The cell **110** comprises two separate compartments, namely an anolyte compartment **16** and a catholyte compartment **17**. The two compartments **16**, **17** may be separated by a scaffold **112** which houses an alkali metal ion selective membrane **18**. The membrane may be, for example, a NaSelect® membrane from Ceramatec Inc. of Salt Lake City, Utah.

The anolyte compartment **16** is in fluid communication with an anolyte reservoir **22**. The anolyte reservoir houses a quantity of anolyte **116**. The anolyte **116** may be pumped from the anolyte reservoir **22** into the anolyte compartment **16**. The anolyte compartment **16** houses an anode **19**. Thus, when the anolyte solution **116** is pumped into the anolyte compartment **16**, the anolyte **116** will contact the anode **19** (so that the anodic reaction may take place). As shown in FIG. **2**, the anolyte **116** may comprise a solution of the alkali metal salt of the carboxylic acid **130**. (As known in the art, this alkali salt  $\text{RCO}_2\text{M}$  **130**, may dissociate into its constituent ions ( $\text{RCO}_2^-$  and  $\text{M}^+$ ), depending upon the particular solvent **146** that is used).

The catholyte compartment **17** is also in fluid communication with a catholyte reservoir **21**. The catholyte reservoir **21** houses a quantity of catholyte **117**. The catholyte **117** may be pumped from the catholyte reservoir **21** into the catholyte compartment **17**. The catholyte compartment **17** houses a cathode **20**. Thus, when the catholyte solution **117** is pumped into the catholyte compartment **17**, the catholyte **117** will contact the cathode **20** (so that the cathodic reaction may take place). As shown in FIG. **2**, the catholyte **117** may comprise a solution of an alkali metal hydroxide **140** (MOH) or an alkali metal alkoxide **150** (MOR). (As known in the art, this alkali metal hydroxide **140** may dissociate into its constituent ions ( $\text{OH}^-$  and  $\text{M}^+$ ) and the alkali metal alkoxide **150** may dissociate into  $\text{M}^+$  and  $\text{OR}^-$ , depending upon the particular solvent **145** that is used). The anolyte **116** and the catholyte **117** may both comprise a solvent **145**, **146**, which may be the same solvent or a different solvent, depending upon the particular embodiment.

When a voltage source **26** applies a potential across the cell **110**, alkali ions ( $\text{M}^+$ ) travel across the membrane **18** as reduction at the cathode **20** forms hydrogen **23** which evolves from the cell **110**. At the anode **19**, oxidation



produces radicals which form the radically-coupled product **24** as well as carbon dioxide **25**.

During the electrochemical reaction, oxidation at surface of the anode **19** occurs causing the decarboxylation of the carboxyl functional group forming a radical and CO<sub>2</sub>. According to one embodiment of the invention the radical then reacts directly with a second radical to form a symmetric organic molecule with at least two oxygen containing functional groups. For a non-limiting example, the radicals combine to make a diol. According to another embodiment of the invention a two electron oxidation occurs at the surface of the anode **19**. This is then followed by a nucleophilic addition, making an unsymmetrical compound which has at least two oxygen containing functional groups. In one embodiment, this unsymmetrical compound can easily be converted to a diol. In another embodiment, the anolyte contains multiple types of carboxylate salts, and upon oxidation the radicals form heterocoupling products. It should be noted that the heterocoupling will lead to non-symmetric compounds with oxygen containing functional groups, whereas the homocoupling leads to symmetric compounds.

On the other side of the cell **110**, the reduction of the catholyte **117** is occurring and to maintain charge balance a positive ion (M<sup>+</sup>) must transfer from the anode **19** to the cathode **20**, and in the case when the anolyte **116** and catholyte **117** are separated there needs to be a path for the positive ions to transfer between compartments. In one embodiment, the ion conducting membrane **18** selectively transfers alkali ions (M<sup>+</sup>), including but not limited to the ions of, sodium, lithium, and potassium, from the anolyte **116** to the catholyte **117** under the influence of an applied electrical field. In one embodiment, a NaSelect® membrane **18** selectively transfers sodium ions between the anolyte **116** and catholyte **117**.

In one particular embodiment, the ion conductive membrane **18** is between 10 and 5000 microns thick, or more preferably the membrane **18** is between 100 and 1000 microns thick, or even more preferably, the membrane **18** is between 200 and 700 microns thick. In one embodiment the membrane **18** is in the form of a disk with a planar configuration. The disk may have diameters between 0.25-25 cm. In one embodiment, the disk diameter is between 1.27-12.7 cm. In other embodiments, the disk diameter is between 2.54-7.62 cm. There may be more than one disk and the disk or disks may be assembled in a scaffold **112**. In another embodiment, the membrane **18** has a cylindrical configuration with an average diameter of the cylinder being between 0.25-25 cm. In other embodiments, the diameter of the cylinder may be between 1.27-12.7 cm. In yet other embodiments, the diameter of the cylinder may be between 2.54-7.62 cm.

The electrochemical cell **110** can be in a parallel plate configuration which uses flat membranes and electrodes, for example as shown in FIG. 2. In another embodiment, the electrochemical cell is in a tubular configuration which uses tubular electrodes and membranes. It should be clear to one skilled in the art that the cell configurations listed above both have advantages and disadvantages which would lead to one being chosen over the other depending on the requirements of the specific carboxylic salt being decarboxylated. It should also be clear to one skilled in the art that the process described by the present invention can be applied in a variety of cell designs.

The anode **19** can comprise any suitable material that allows oxidation reactions to occur in the anolyte compartment **16** when an electrical potential is applied by voltage source **26** between the anode **19** and cathode **20**. Some

non-limiting examples of anode materials include, but are not limited to, platinum, titanium, nickel, cobalt, iron, stainless steel, lead dioxide, metal alloys, combination thereof, and other known or novel anode materials. In one embodiment, the anode **19** may comprise iron-nickel alloys such as KOVAR® or INVAR®. In other embodiments, the anode **19** may comprise carbon based electrodes such as boron doped diamond, glassy carbon, and synthetic carbon. Additionally, in some embodiments the anode comprises a dimensionally stable anode (DSA), which may include, but is not limited to, rhenium dioxide and tantalum pentoxide on a titanium substrate.

The cathode **20** may also be fabricated of any suitable cathode material that allows the reduction of water or methanol producing hydroxide or methoxide ions and hydrogen gas. The cathode may comprise of the materials used for the anode **19**. Alternatively, the cathode **20** may be comprised of materials different from that which was used for the anode **19**. Some non-limiting examples of suitable cathode materials include without limitation, nickel, stainless steel, graphite, and any other suitable cathode material that is known or novel.

In one embodiment, the electrodes have a smooth morphology such as a foil or thin film. In another embodiment, the anode **19** and cathode **20** have a high surface area morphology, for example, but not limited to, a foam, grit, or other porous structure. In some embodiments, the anode **19** and the cathode **20** have the same morphology, while in other embodiments, the electrodes may have a different morphology.

It should be noted that the embodiment shown in FIG. 2 is a divided cell that comprises two distinct chambers. Other embodiments may be constructed in which the cell is a single-chambered cell, such that the electrolyte is fed into this chamber without an ion-selective membrane **18**.

In order to create a diol according to the present embodiments, the alkali salt **130** of the carboxylic acid may comprise one or more alcohol (OH) functional groups.

The anolyte solution **116** may comprise of a polar organic solvent **146**. Some non-limiting examples of suitable polar organic solvents include without limitation, methanol, ethanol, isopropanol, n-propanol, acetone, acetonitrile, dioxane, butanol, DMSO, CS<sub>2</sub>, diethyl carbonate, ethylene carbonate, and glycerol. In one embodiment, the solvent is an ethyl ester which is formed from a carboxylic acid and ethanol, or more preferably a carboxylic acid similar in carbon number to the anion being oxidized and ethanol. Most preferably, the solvent is an ester formed from the carboxylic acid of the anion being oxidized and ethanol. An example of this type of solvent would be ethyl lactate.

In other embodiments, the anolyte solution **116** may comprise of an ionic liquid (IL). A non-limiting example is an IL with a phosphonium based cation with four substituents. In one embodiment, the four substituents of the phosphonium cation are each independently an alkyl group, a cycloalkyl group, an alkenyl group and an aryl group. In another embodiment, some/all of the substituents are of a similar group. In a further embodiment, some/all of the substituents are the same. In some embodiments, the anion of the ionic liquid is a carboxylate ion, more preferably the carboxylate ion is similar to the carboxylate anion being oxidized during the electrolysis, or most preferably the carboxylate ion is the same anion being oxidized during the electrolysis.

Certain alkali ion conductive membranes, for example NaSICON and LiSICON-type membranes, have a high temperature tolerance and thus the anolyte solution **116** may

be heated to a higher temperature without substantially affecting the temperature of the catholyte solution **117** or the functionality of the membrane **18**. This means molten salts or acids may be used to dissolve the carboxylate salts in the anolyte **116**. Thus, in one embodiment, the anolyte **116** is the molten salt of the carboxylate anion that is being oxidized.

The anolyte solution **116** may optionally contain a supporting electrolyte which is soluble in the solvent and provides high electrolyte conductivity in the anolyte solution. Non-limiting examples of supporting electrolytes include alkali metal hydroxide, alkali metal salts, tetrafluoroborate, tetramethylammonium hexafluorophosphate, tetrabutylammonium tetrafluoroborate, tetramethylammonium perchlorate, and tetraethylammonium perchlorate. It should be appreciable to those skilled in the art that other soluble ionic compounds may be used.

The catholyte **21** may comprise of a solvent **145** that is the same or different than the anolyte solvent **146**. This is afforded because the ion conductive membrane **18** isolates the compartments from each other. Thus, the anolyte solvent **146** and the catholyte solvent **145** may be separately selected specifically for the reactions that occur in each compartment and/or the solubility of the chemicals required for the specific reactions. (A mixture of solvents may be used as the solvents **145**, **146**, as desired.) This permits one to design an inexpensive catholyte **117** which may have different properties than the anolyte **116**, for example to have high ionic conductivity.

In one embodiment of the invention the catholyte **117** is comprised of water and an unsaturated alkali hydroxide **140**. The hydroxide concentration is between 0.1-50% by weight, or more preferably between 5-25% by weight, or most preferably between 7-15% by weight. Another embodiment may be constructed in which the catholyte **117** consists of alkali methylate **150**. The temperature of the catholyte **117** may or may not be the same temperature of the anolyte **116**.

When a potential is applied to the cathode **20**, a reduction reaction occurs. When the catholyte solution **117** is an aqueous based solution, water is reduced to hydrogen gas **23** and hydroxide ions. The hydroxide formed can then combine with the alkali ion that is transported through the ion conducting membrane **18**, causing the alkali hydroxide concentration of the catholyte **117** to increase as the electrolysis is performed. It will be appreciated that the catholyte product stream comprises a base which may be used to neutralize the carboxylic acid to produce the alkali metal salt of the carboxylic acid **10** (as shown in FIG. 1). Thus, the base consumed by the acid neutralization step may be produced in the catholyte compartment **17**, recovered and re-used in future acid neutralization reactions or other chemical processes.

When an electrical potential is applied to the anode **19**, oxidation occurs. In one embodiment, the oxidation of a carboxylic acid or a carboxylate anion leads to decarboxylation, producing carbon dioxide and an alkyl radical. The radical can then combine with another radical to form alkyl-alkyl coupling products, following a modified Kolbe electrolysis process or it can react with other species present at the electrode's surface following non-Kolbe electrolysis. In another embodiment, when there is an electron donating group in the alpha position to the carboxyl group, the decarboxylation leads to the formation of  $\text{CO}_2$  and a carbocation from a two electron oxidation. Following its formation, the carbocation can then participate in nucleophilic reactions instead of coupling reactions. These potential mechanisms are discussed in greater detail herein.

In one embodiment, the electrolytic cell **110** may be operated in a continuous mode. In continuous mode, the cell **110** is initially filled with anolyte solution **116** and catholyte solution **117** and then, during operation, additional solution is fed into the cell **110**, and products, by-products, and/or diluted solutions are removed from the cell **110** without ceasing operation of the cell. In another embodiment, the electrolytic cell **110** is operated in batch mode. In batch mode, the anolyte solution **116** and catholyte solution **117** are fed initially into the cell **110** and then the cell **110** is operated until a desired concentration of the product is produced, then the cell **110** is emptied and the products are collected. The cell **110** is then re-filled to start the process again. Also, in either method, the feeding of solution may be done using a premade solution or using components that form the solution in situ. It should be noted in both continuous and batch mode, the anolyte **116** can be added to the solution to maintain the alkali ion concentration at a certain level.

As disclosed above, the anolyte solution **116** comprises a solvent **146**, and an alkali metal salt of a carboxylic acid **130**. The choice of carboxylic acid is dependent on the desired product and can be chosen from any class of carboxylic acids. Some non-limiting examples are fatty acids, alkyl carboxylic acids, amino acids, aryl carboxylic acids, and di- and tri-carboxylic acids. The carboxylic acid can also have multiple substituents present, in addition to, the carboxylic group. These additional functional groups can be located at any carbon site of the carboxylic acid, and, in some embodiments, are located in the alpha position to the carboxylate carbon. Both electron donating and withdrawing substituent can be present on the carboxylic acid. Some non-limiting examples of electron donating substituents are hydroxyl, amine, amide, and ether groups. Some non-limiting examples of electron withdrawing substituents are halogens, nitriles, carbonyl, nitro, and nitride groups. The functional group present in the alpha position to the carboxylate will determine whether the decarboxylation will follow a one electron or two electron oxidation mechanism. In one embodiment, one electron oxidation will occur, favoring radical-radical coupling because there is no substituent present in the alpha position or the substituent is an electron withdrawing group. In another embodiment, the two electron oxidation is favored, because there is an electron donating group present in the alpha position to the carboxylate group.


As noted above in conjunction with FIG. 1, the carboxylic acid ( $\text{RCO}_2\text{H}$ ) may be converted into the corresponding alkali salt ( $\text{RCO}_2\text{M}$ ) via acid neutralization. In some embodiments, the R group of the carboxylic acid is a hydrocarbon having a  $\text{C}_2$  to  $\text{C}_{22}$  hydrocarbon chain and at least one hydrogen that has been substituted for a functional group containing oxygen. Some non-limiting examples of functional groups that can be present are hydroxyl, phenyl, esters, ethers, and ketones. In one embodiment, the carboxylic acid has other substituents which do not contain oxygen such as: halide, nitrile, amine, amide, and sulfide. For example, in the production of monomers for elastic materials, the additional substituents can impart additional properties or be used to modify the elastic material after the dienes have been polymerized. In one embodiment, the carboxylic acid is obtained from biomass with the additional substituent already present. In another embodiment, the biomass derived carboxylic acid is first modified to include the additional functional groups.

The alkali carboxylate is added to a suitable electrolyte which is used as the anolyte solution **116**. The anolyte


## 11

solution **116** may optionally include a supporting electrolyte if the conductivity of the alkali carboxylate is low and causes high solution resistance. The anolyte solution is fed either continuously or in batch mode into the electrochemical cell **110**.

The particular reactions at the cathode **20** and anode **19** will now be described. Specifically, at the anode **19**, decarboxylation occurs:






Once the radical (R.) is formed, it will react with other species at the electrode's surface, and if it reacts with another radical of the same carboxylate anion, it will form a homocoupling product:




The coupled product may be a symmetric compound containing at least two oxygen containing functional groups. This product can be in itself the chemical of interest, for example as a solvent, or it can be converted into a chemical of interest. For example, the function groups can be converted into double bonds and the diene can be used as monomers for the production of elastic material. If the radical combines with a radical of a different carboxylate anion, then a heterocoupling product will be formed and an unsymmetrical compound will be obtained.

Another embodiment involves decarboxylation of a carboxylate anion that has an electron donating group present in the alpha position of the carbon chain. In this case, the radical formed during decarboxylation may follow a different pathway and will either go through a rearrangement reaction or lose an additional electron according to the following reactions:



In these reactions, the Y represents an electron donating group in the alpha position to the carboxylic group. The compounds formed in these equations can be of interest by themselves, or can be converted into compounds of interest with additional steps. Not limited by reaction pathway, the products of the reactions above can for example be converted into a diol and then into a diene. A non-limiting example of these additional chemical steps is shown below.



One method to promote radical-radical coupling is to perform the decarboxylation at high current densities. To

## 12

achieve these high current densities with low voltages, a highly conductive catholyte is used in the cathode compartment of the cell. Non-limiting examples of such catholytes are aqueous alkali hydroxide and non-aqueous methanol/alkali methoxide solutions. These solutions are reduced at the cathode leading to the formation of hydrogen gas and alkali metal hydroxides.

Some advantages of this embodiment, using the alkali metal salt of the alkyl carboxylic acid instead of the carboxylic acid itself, are: 1)  $\text{RCO}_2\text{M}$  is more polar than  $\text{RCO}_2\text{H}$  and so more probable to decarboxylate at lower voltages, 2) The electrolyte conductivity may be higher for alkali metal salts than the acid solutions, 3) The anolyte and catholyte solution can be completely different allowing favorable reactions to take place at either/both electrodes.

The following non-limiting examples are given to illustrate various embodiments within the scope of the present invention.

## EXAMPLES

Several examples will be given to demonstrate the technical feasibility of converting inexpensive carboxylic acids into functionalized hydrocarbons using the electrochemical decarboxylation process at low temperatures and pressures. The examples demonstrate the decarboxylation of sodium salts of carboxylic acids with hydroxyl groups using electrolytic cells equipped with a NaSelect® NaSICON membrane manufactured by Ceramtec, Inc., Salt Lake City, Utah. The decarboxylation produces compounds with at least two functional groups containing oxygen, which have application as solvents or food additives, and, with an additional step, can be converted into diene monomers for the production of elastic materials.

The examples disclosed herein used an experimental setup which is schematically shown in FIG. 2. The cell employed for these experiments was a micro flow cell, allowing both the anolyte and catholyte to be pumped through the cell while minimizing the distance between the electrodes and the membrane. The membranes used in the examples consisted of 2.54 cm diameter NaSICON disks of about 1 mm thickness which were housed on scaffolds in the center of the cells. As the scaffold and membrane physically separate the anode and cathode compartments, there was a separate reservoir and temperature controlled hotplate for the anolyte and catholyte. This allowed the chemistry and

conditions of each electrolyte to be optimized for the respective electrode reactions. A multiple-head parasitic pump was

used to pump both electrolytes into the electrolysis cell, and, depending on the temperature of the electrolytes the tubing between the cell, pump, and reservoir was insulated.

The anolyte, which contains the sodium salt of the carboxylic acid, is made by dissolving at least 10% of the salt into a polar organic solvent. This was conducted using two methods. For the first method, the sodium salt was prepared directly in the polar organic solvent by the addition of the carboxylic acid and NaOH. To ensure the complete deprotonation of the acid, the cell was operated at a pH (8-12) indicative of excess NaOH. The second method consisted of preparing the sodium salt in a separate solution following conventional saponification reactions and then dissolving the prepared salt into a polar organic solvent. For this method, a general saponification procedure was used during which the sodium carboxylate forms as the carboxylic acid is neutralized. The catholyte can be made from any solution containing sodium salts, and for the examples given herein an aqueous sodium hydroxide solution was used. To obtain low solution resistance, the temperatures of the electrolytes were increased to 50° C. to improve both the solubility and conductivity.

Once the reservoirs reached the desired temperatures, a power supply (BP Precision 1786B) was connected and a current density between 10 and 100 mA/cm<sup>2</sup> was applied. During the electrolysis the voltage and current were monitored using a Data Acquisition Unit (Agilent 3490A) controlled by LabVIEW. The applied current density caused oxidation to occur at the anode (smooth platinum) and reduction to occur at the cathode (nickel), with each electrode having an area of 11 cm<sup>2</sup>. As the power supply transports electrons from the anode to the cathode, a charge balance must be maintained across the cell by the diffusion of positively charge ions. Given the high selectivity of the NaSICON membrane for Na-ions, it is the only species that can provide this balance, thus a high concentration of the sodium salt was desired.

As the classic solvent for Kolbe electrolysis, methanol was one of the solvents used in the examples provided. In methanol, the solubility of the Na-lactate was found to be 20% after the addition of mild heat. A second example using ethyl lactate as the solvent is given demonstrating one of the embodiments of the present invention, and the solubility the sodium lactate in the ethyl lactate was found to be just below 20%.

Gas chromatography (GC) was used to characterize the products obtained in the examples given below. A high polarity polyethylene glycol (PEG) column (HP INNOWax, 30 m, 0.25 mm, 0.25 μm) was used with a temperature program that held 125° C. for 5 min, then increased at 10° C./min to 250° C. and held this temperature for 5 min. Because the reaction solutions contained sodium salts, which can cause problems with different components of a GC instrument, a post reaction processing step was employed to remove the sodium salts from the sample.

Distillation was one method employed to separate the products from the salts of the reaction solution. The high boiling points of the products obtained (148-135° C.) caused a "slurry of salts" to be precipitated out as the methanol was distilled from the reaction solution. This issue was circumvented by performing the distillation using a mixture of the reaction solution and glycerol (BP 290° C.). This permitted the distillation to be carried out at temperatures that were required to distill the product, while the glycerol acted as a distillation medium, keeping the salts from precipitating out and inhibiting the distillation of the product.



The second post reaction treatment was used to remove the sodium salt from the reaction solution, via acidification with sulfuric acid. The addition of H<sub>2</sub>SO<sub>4</sub> acidified the carboxylate ion present and caused the Na-ions to precipitate out of the solution as Na<sub>2</sub>SO<sub>4</sub>. After filtering the Na<sub>2</sub>SO<sub>4</sub> from the solution it could be directly injected into the GC for analysis. To quantify the amount of product produced while using one of the two post reaction treatments, 1-butanol was used as an internal standard to make the calibration curves.

#### Example 1

The electrochemical decarboxylation process disclosed in the present invention was used to convert the sodium salt of a carboxylic acid with a hydroxyl group to a diol. The diol produced can be used as a solvent or it can be further converted into a diene. The anolyte for this decarboxylation consisted of 10% by weight sodium 3-hydroxypropionate in methanol, and was prepared by dissolving the acid into methanol then adding NaOH pellets in excess. An aqueous solution containing 10% by weight sodium hydroxide was used as the catholyte.

The electrolysis was conducted in batch mode, during which the anolyte and catholyte were cycled through the corresponding anode and cathode compartments of the cell. The cell was operated until enough charge passed to theoretically convert 80% of the sodium salt. During the electrolysis the temperatures of the electrolytes were maintained at 50° C., and a current density of 18.5 mA/cm<sup>2</sup> was employed.

The reactions that occurred during the electrolysis in the anode and cathode compartment are shown below:



The decarboxylation occurring in the anode compartment produced CO<sub>2</sub> which was bubbled through a calcium hydroxide solution forming calcium carbonate which was then analyzed using TGA. FIG. 3 contains a graph showing the potential and current density transients for the electrolysis. The potential started just below 8 Volts and increased to 31 Volts in 5 hours causing decarboxylation to occur. The potential increased from 7 Volts to 32 Volts in under 5 hours when a current density of 18 mA/cm<sup>2</sup> was applied. The conditions used in this example promoted radical-radical coupling and produced 1,4-butanediol according to the following reaction:



Following the completion of the electrolysis, 1-butanol was added at 1% by weight and the anolyte was acidified using sulfuric acid (30%) until a pH of 3 was obtained. The precipitated sodium sulfate was filtered from the anolyte solution and the filtrate was analyzed using GC. Integrating the 1,4-butanediol peak that eluded at 11.57 minutes (or starting at 11.55 min) in FIG. 4, a 80% yield was obtained based on a calibration curve generated using 1-butanol as the internal standard.

The 1,4-butanediol obtained from the electrolysis of sodium 3-hydroxypropionate has applications as a solvent or can be dehydrated to form 1,3-butadiene. The 1,3-butadiene is an important monomer used in the production of different types of elastic materials.


## 15

## Example 2


As another example of the present invention, a different carboxylic acid with a hydroxyl group was converted into a compound with multiple oxygen containing functional groups. The compound produced can be used as a food additive or converted into a diol, and then if desired into a diene. The anolyte for this decarboxylation consisted of 10% by weight sodium lactate in methanol, and was prepared by dissolving the acid into methanol then adding NaOH pellets in excess. An aqueous solution containing 10% by weight sodium hydroxide was used as the catholyte.

The electrolysis was conducted in batch mode, during which the anolyte and catholyte were cycled into the corresponding anode and cathode compartments of the cell. The electrolysis was operated until enough charge passed to theoretically convert 80% of the sodium salt. During the electrolysis the temperatures of the electrolytes were maintained at 50° C., and a current density of 9 mA/cm<sup>2</sup> was employed.


The reactions that occurred during the electrolysis in the anode and cathode compartment are shown below:



The decarboxylation occurring in the anode compartment produced CO<sub>2</sub> which was bubbled through the calcium hydroxide solution forming calcium carbonate which was then analyzed using TGA. FIG. 5 contains a graph showing potential and current transients for the electrolysis. The potential started just below 8 Volts and increased to 31 Volts in 5 hours causing decarboxylation to occur. The potential decreased from 8 Volts to 7 Volts in 6 hours when a current density of 9.5 mA/cm<sup>2</sup> was applied. The conditions and the alpha-position of the hydroxyl group in the lactate anion promoted the two electron oxidation and produced acetaldehyde following the non-limiting reaction:



The presence of excess NaOH in the solution and the solution temperature of 50° C., further converts the acetaldehyde after the electrolysis is completed following the nucleophilic addition illustrated in the non-limiting reaction:



As the above-reaction proceeds, the clear anolyte solution becomes light to dark yellow which is indicative to the formation of acetoin. The solution was then acidified using sulfuric acid and added to equal volume of glycerol. The glycerol based solution was then distilled permitting the different fractions to be collected at the corresponding boiling points and leaving any remaining salts in the glycerol. The GC analysis of the distillate shown in FIG. 6 shows acetoin eluded at 3.8 min with 80% yield, and the isomers of 2,3-butanediol eluded at 6.5 and 7.1 min with a 5% yield.

The acetoin produced from the decarboxylation reaction above can be used as a food additive or electrochemically reduced to afford 2,3-butanediol. This diol can then be used as a solvent or be dehydrated to 1,3-butadiene which is an important monomer for the polymerization of many industrially produced rubbers.

## Example 3



An example of another embodiment of the present invention will be given, where the same carboxylic acid used in

## 16


EXAMPLE 2 will be converted directly into a diol. The diol produced can be used as a solvent or it can be further converted into a diene. The anolyte for this example consisted of 20% by weight solution of sodium L-lactate in methanol, and was prepared by dissolving sodium L-lactate (98%, Sigma) directly into methanol. An aqueous solution containing 10% by weight sodium hydroxide was used as the catholyte.

The electrolysis was conducted in batch mode, during which the anolyte and catholyte were cycled into the corresponding anode and cathode compartments of the cell. The electrolysis was continued until enough charge passed to theoretically convert 80% of the sodium salt. During the electrolysis the temperatures of the electrolytes were maintained at 50° C., and a current density of 18 mA/cm<sup>2</sup> was employed.

The reactions that occurred during the electrolysis in the anode and cathode compartment are shown in the following reactions:



The decarboxylation occurring in the anode compartment produced CO<sub>2</sub> which was bubbled through the calcium hydroxide solution forming calcium carbonate which was then analyzed using TGA. Under these conditions the radicals generated undergo homocoupling, forming 2,3-butanediol according to the following reaction:



Following the completion of the electrolysis, 1-butanol was added at 1% by weight and the anolyte was acidified using sulfuric acid (30%) until a pH of 3 was obtained. The precipitated sodium sulfate was filtered from the anolyte solution and the filtrate was analyzed using GC. Two peaks corresponding to the three isomers of 2,3-butanediol were eluded as shown in FIG. 7, and integration of these peaks demonstrated that 20% yield was obtained based on a calibration curve generated using 1-butanol as the internal standard. Two peaks are present from the elution of the three isomers of 2,3-butanediol at 6.5 and 7.1 min.

The 2,3-butanediol obtained from the electrolysis of sodium L-lactate has applications as a solvent or can be dehydrated to form 1,3-butadiene. The 1,3-butadiene has an application as a monomer used in the production of different types of elastic materials.



## Example 4

An example of another embodiment of the present invention will be given, where the same carboxylic acid used in EXAMPLE 2 and EXAMPLE 3 will be converted directly into a diol using a different solvent. The anolyte for this decarboxylation consisted of 20% by weight solution of sodium L-lactate in ethyl lactate, and was prepared by dissolving sodium L-lactate (98%, Sigma) directly into ethyl lactate. An aqueous catholyte containing 10% by weight sodium hydroxide was used as the catholyte.


The electrolysis was conducted in batch mode, during which the anolyte and catholyte were cycled into the corresponding anode and cathode compartments of the cell. The electrolysis was continued until enough charge passed to theoretically convert 80% of the sodium salt. During the electrolysis the temperatures of the electrolytes were maintained at 50° C., and a current density of 9 mA/cm<sup>2</sup> was employed.

## 17

The reactions that occurred during the electrolysis in the anode and cathode compartment are shown below.



The decarboxylation occurring in the anode compartment produced  $\text{CO}_2$  which was bubbled through the calcium hydroxide solution forming calcium carbonate which was then analyzed using TGA. FIG. 8 contains the potential and current density transients of this electrolysis, showing the potential started at 15 Volts and decreased to 13 Volts in 5 hours when a current density of  $9.5 \text{ mA/cm}^2$  was applied. Under these conditions the radicals produced underwent radical-radical coupling, forming 2,3-butanediol according to the following reaction:



Following the completion of the electrolysis, 1-butanol was added at 1% by weight and the anolyte was acidified using sulfuric acid (30%) until a pH of 3 was obtained. The precipitated sodium sulfate was filtered from the anolyte solution and the filtrate was analyzed using GC. Two peaks corresponding to the three isomers of 2,3-butanediol were eluded on the GC shown in FIG. 9, and integration of these peaks demonstrated that 27% yield was obtained based on a calibration curve generated using 1-butanol as the internal standard. The isomers of the 2,3-butanediol eluded at 6.5 and 7.1 min and the ethyl lactate eluded at 4.1 min.

The 2,3-butanediol obtained from the electrolysis of sodium L-lactate in ethyl lactate has applications as a solvent or can be dehydrated to form 1,3-butadiene. The 1,3-butadiene has an application as a monomer used in the production of different types of elastic materials.

All the patent applications and patents listed herein are expressly incorporated herein by reference.

What is claimed is:

1. An electrochemical cell comprising:
  - an anolyte compartment comprising a quantity of anolyte comprising at least one alkali metal salt of a carboxylic acid, the at least one alkali metal salt of a carboxylic acid having at least 3 carbons and a carboxylate group and at least one heteroatom functional group in addition to the carboxylate group;
  - an anode in contact with the anolyte;
  - a catholyte compartment housing a quantity of catholyte;
  - a cathode in contact with the catholyte;
  - an alkali ion conducting membrane; and
  - a voltage source electrically connected to the anode and the cathode, wherein the voltage source decarboxylates the at least one alkali metal salt of the carboxylic acid into alkyl radicals that react to form a coupled radical product, wherein the coupled radical product has at least two heteroatom functional groups.
2. The electrochemical cell as in claim 1, wherein the alkali metal salt of the carboxylic acid has at least one OH functional group in addition to the carboxylic acid moiety such that the coupled radical product comprises at least two OH functional groups.
3. The electrochemical cell as in claim 2, wherein the coupled radical product is a diol.
4. The electrochemical cell as in claim 2, wherein the coupled radical product is 1,4 butanediol or 2,3 butanediol.
5. The electrochemical cell as in claim 2, wherein the OH functional group is in the alpha position with respect to the carboxylic acid moiety.

## 18

6. The electrochemical cell as in claim 1, wherein the coupled radical product is formed via a non-Kolbe pathway.

7. The electrochemical cell as in claim 1, wherein the coupled radical product is acetoin or another a hydroxyl-ketone product.

8. The electrochemical cell as in claim 1, wherein the coupled radical product has two oxygen containing groups.

9. The electrochemical cell of claim 1, wherein the at least one functional group is selected from the group consisting of halide groups, sulfide groups, hydroxyl groups, amine groups, amide groups, and ether groups.

10. The electrochemical cell of claim 3, wherein the diol is converted into a diene.

11. The electrochemical cell of claim 1, wherein the analyte comprises a polar organic solvent or an ionic liquid.

12. The electrochemical cell of claim 1, wherein the anolyte comprises a polar organic solvent comprising an ethyl ester formed from a carboxylic acid and ethanol.

13. The electrochemical cell of claim 12, wherein the polar organic solvent comprises ethyl lactate.

14. The electrochemical cell of claim 1, wherein the ion conductive membrane comprises a thickness of between about 10 and about 5000 microns.

15. The electrochemical cell of claim 14, wherein the ion conductive membrane comprises a thickness of between about 100 and about 1000 microns.

16. The electrochemical cell of claim 15, wherein the ion conductive membrane comprises a thickness of between about 200 and about 700 microns.

17. The electrochemical cell of claim 1, wherein the ion conductive membrane comprises a planar configuration.

18. The electrochemical cell of claim 1, wherein the ion conductive membrane comprises a cylindrical configuration.

19. A method for producing a coupled radical product, comprising:

providing an electrochemical cell comprising an anolyte and a catholyte, the anolyte comprising an alkali metal salt of a carboxylic acid comprising a carboxylate group and at least one heteroatom functional group selected from the group consisting of halide groups, sulfide groups, hydroxyl groups, amine groups, amide groups, and ether groups;

providing a highly conductive catholyte comprising an aqueous alkali metal hydroxide or an alkali metal alkoxide or a mixture thereof; and electrochemically decarboxylating the alkali metal salt of the carboxylic acid into a first radical intermediate that reacts with second radical intermediate, the second radical intermediate being formed by decarboxylation, to form a coupled radical product, wherein the coupled radical product has at least two of the heteroatom functional groups.

20. The method as in claim 19, wherein the alkali metal salt of the carboxylic acid is derived from biomass.

21. The method as in claim 19, wherein the alkali metal salt of the carboxylic acid is formed via a saponification reaction using a base of the formula  $\text{MOH}$  or  $\text{MOR}$ , wherein, "M" represents an alkali metal and "OH" represents a hydroxide anion and "OR" represents an alkoxide anion.

22. The method of claim 21, wherein the base is re-formed as part of the decarboxylation, wherein the base is collected and re-used in a further saponification reaction.

23. The method of claim 19, wherein the coupled radical product is formed via a non-Kolbe pathway.

24. The electrochemical cell of claim 1 further comprising a catholyte reservoir comprising a second quantity of the catholyte and an anolyte reservoir comprising a second quantity of the anolyte.

25. The electrochemical cell of claim 1 wherein the catholyte compartment further comprises an outlet connected to a furcated tube for releasing hydrogen gas from the electrochemical cell and the anolyte compartment further comprises an outlet connected to a furcated tube for releasing carbon dioxide from the electrochemical cell.

5  
10

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 9,957,622 B2  
APPLICATION NO. : 13/790744  
DATED : May 1, 2018  
INVENTOR(S) : Mosby et al.


Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

In Column 18, Claim 11, Line 16, remove “analyte” and replace with -- anolyte --.

Signed and Sealed this  
Eleventh Day of June, 2019



Andrei Iancu  
*Director of the United States Patent and Trademark Office*



UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 9,957,622 B2  
APPLICATION NO. : 13/790744  
DATED : May 1, 2018  
INVENTOR(S) : James Mosby et al.


Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

In Column 18, Claim 7, Line 4, remove “another a hydroxyl-” and replace with -- another alpha hydroxyl --.

Signed and Sealed this  
Fifteenth Day of October, 2019



Andrei Iancu  
*Director of the United States Patent and Trademark Office*