



US009974421B2

(12) **United States Patent**
Wishney et al.

(10) **Patent No.:** **US 9,974,421 B2**
(45) **Date of Patent:** **May 22, 2018**

(54) **CLEANING APPLIANCE**

(75) Inventors: **Adam Andrew Wishney**, Malmesbury (GB); **Damian Henri Lee**, Malmesbury (GB); **James Dyson**, Malmesbury (GB); **Peter David Gammack**, Malmesbury (GB)

1,301,453 A 4/1919 Kendall
1,605,507 A 11/1926 Burke
1,861,402 A 5/1932 Riper
1,918,713 A * 7/1933 Ponselle 417/360
2,125,850 A 8/1938 Norris
RE22,426 E 1/1944 Smellie
2,352,504 A * 6/1944 White 96/382
2,489,100 A 11/1949 Marco
(Continued)

(73) Assignee: **Dyson Technology Limited**, Malmesbury, Wiltshire (GB)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days. days.

CN 1050981 5/1991
CN 1310979 9/2001
(Continued)

(21) Appl. No.: **13/248,808**

OTHER PUBLICATIONS

(22) Filed: **Sep. 29, 2011**

JPH05168577A: Jul. 1993—Machine Translation—English.*
(Continued)

(65) **Prior Publication Data**

US 2012/0079673 A1 Apr. 5, 2012

(30) **Foreign Application Priority Data**

Sep. 30, 2010 (GB) 1016450.7

Primary Examiner — Marc Carlson

(51) **Int. Cl.**

A47L 9/00 (2006.01)
A47L 9/10 (2006.01)
A47L 5/36 (2006.01)
A47L 9/24 (2006.01)

(57) **ABSTRACT**

A cleaning appliance includes separating apparatus for separating dirt from a dirt-bearing fluid flow, a floor engaging rolling assembly housing a motor driven fan unit for drawing the fluid flow through the separating apparatus, a chassis connected to the rolling assembly, and a duct for conveying the fluid flow to the separating apparatus. To improve the stability of the appliance, the duct has an inlet section which is connected to the chassis for pivoting movement relative to the chassis as the appliance is maneuvered over a floor surface. An outlet section for coupling the inlet section to the separating apparatus is releasably connected to the rolling assembly to facilitate the removal of any blockages within the duct.

(52) **U.S. Cl.**

CPC **A47L 5/362** (2013.01); **A47L 9/009** (2013.01); **A47L 9/24** (2013.01)

(58) **Field of Classification Search**


CPC **A47L 5/362**; **A47L 9/009**; **A47L 9/24**
USPC 15/347, 353, 327.4
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

963,139 A 7/1910 Griffiths
1,123,839 A 1/1915 Bridges

22 Claims, 11 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,686,330 A * 8/1954 Wales 15/327.4
 2,699,838 A 1/1955 Holm-Hansen
 2,738,538 A 3/1956 Vance
 2,747,216 A * 5/1956 Tschudy 15/351
 2,771,309 A 11/1956 Clark, Jr.
 2,834,605 A 5/1958 McCollough
 2,876,479 A * 3/1959 Kaufman 15/323
 2,954,802 A * 10/1960 Duff 138/122
 3,038,743 A 6/1962 Zaloumis
 3,310,828 A * 3/1967 Clark A47L 5/365
 15/328
 3,375,541 A 4/1968 Fromknecht
 3,378,877 A 4/1968 Boerrefors
 3,524,211 A 8/1970 Wolf
 3,524,212 A 8/1970 Spencer
 3,608,333 A * 9/1971 Selley et al. 464/177
 4,059,296 A * 11/1977 Panourgias 285/312
 4,114,231 A 9/1978 Nauta
 4,486,037 A 12/1984 Shotbolt
 4,573,236 A 3/1986 Dyson
 5,134,749 A * 8/1992 Sakurai et al. 15/325
 5,144,716 A 9/1992 Watanabe et al.
 5,149,147 A 9/1992 Kastrup et al.
 5,275,444 A 1/1994 Wythoff
 5,353,470 A 10/1994 Bartlett
 5,467,500 A 11/1995 O'Hara et al.
 5,784,757 A 7/1998 Cipolla
 5,815,881 A 10/1998 Sjögren
 5,839,156 A * 11/1998 Park et al. 15/339
 5,842,254 A * 12/1998 Lee A47L 5/00
 15/327.2
 5,937,477 A * 8/1999 Dyson 15/327.2
 5,954,370 A 9/1999 Pietersen
 6,058,559 A * 5/2000 Yoshimi et al. 15/328
 6,079,690 A 6/2000 Yoon
 6,141,822 A * 11/2000 Riviera-Boklund et al. ... 15/325
 6,154,921 A 12/2000 Green et al.
 6,158,781 A 12/2000 Aaron, III
 6,251,296 B1 6/2001 Conrad et al.
 6,317,921 B1 11/2001 Park et al.
 6,345,408 B1 2/2002 Nagai et al.
 6,371,421 B1 4/2002 Ma et al.
 6,474,696 B1 11/2002 Canale
 6,482,246 B1 * 11/2002 Dyson et al. 55/459.1
 6,484,350 B2 11/2002 Yung
 6,536,073 B2 3/2003 Uratani et al.
 6,712,868 B2 3/2004 Murphy et al.
 6,928,690 B2 8/2005 Ji
 7,181,804 B2 2/2007 Hafling et al.
 7,185,389 B2 * 3/2007 Thomason et al. 15/246.4
 7,380,308 B2 6/2008 Oh et al.
 7,425,225 B2 * 9/2008 Genn et al. 55/418
 D591,016 S * 4/2009 Dyson et al. D32/22
 8,020,251 B2 9/2011 Luebbering et al.
 8,079,113 B2 * 12/2011 Chong et al. 15/319
 8,117,713 B2 2/2012 Kasper et al.
 8,359,705 B2 * 1/2013 Conrad 15/329
 8,474,091 B2 7/2013 Dyson et al.
 8,695,155 B2 4/2014 Dyson et al.
 2001/0029641 A1 * 10/2001 Uratani et al. 15/327.4
 2002/0011050 A1 1/2002 Hansen et al.
 2002/0063427 A1 5/2002 Schiemann et al.
 2003/0084537 A1 5/2003 Conrad et al.
 2004/0045121 A1 3/2004 Kim
 2004/0088816 A1 5/2004 Shimizu et al.
 2004/0112019 A1 6/2004 Mountford
 2005/0039297 A1 2/2005 Morgan et al.
 2005/0108849 A1 * 5/2005 Lam 15/353
 2005/0198764 A1 * 9/2005 Heatley 15/323
 2005/0223517 A1 * 10/2005 Courtney 15/351
 2005/0235454 A1 10/2005 Courtney
 2006/0101610 A1 * 5/2006 Oh et al. 15/327.2
 2006/0131876 A1 6/2006 Knowles et al.
 2006/0213023 A1 * 9/2006 Hare et al. 15/327.2
 2007/0039118 A1 2/2007 Choi

2007/0067945 A1 3/2007 Kasper et al.
 2007/0094840 A1 * 5/2007 Zahuranec et al. 15/328
 2008/0196196 A1 8/2008 Conrad
 2008/0263814 A1 10/2008 Bassett et al.
 2008/0282497 A1 11/2008 Griffith et al.
 2009/0007370 A1 1/2009 Gomiciaga-Pereda et al.
 2009/0144928 A1 6/2009 Yoo
 2010/0242208 A1 * 9/2010 Gammack et al. 15/327.1
 2010/0242211 A1 * 9/2010 Sunderland et al. 15/347
 2010/0242212 A1 * 9/2010 Dyson et al. 15/347
 2010/0242213 A1 * 9/2010 Sunderland et al. 15/347
 2010/0242214 A1 * 9/2010 Sunderland et al. 15/347
 2010/0242215 A1 * 9/2010 Dyson et al. 15/347
 2010/0242216 A1 * 9/2010 MacNaughton 15/347
 2010/0242217 A1 * 9/2010 Sunderland et al. 15/347
 2010/0242218 A1 * 9/2010 Genn et al. 15/347
 2010/0242219 A1 * 9/2010 Dyson et al. 15/347
 2010/0242220 A1 * 9/2010 Dyson et al. 15/347
 2011/0088196 A1 * 4/2011 Wills et al. 15/300.1
 2011/0219573 A1 9/2011 Conrad
 2012/0079674 A1 * 4/2012 Dyson et al. 15/347
 2012/0079676 A1 * 4/2012 Sunderland 15/352
 2012/0079677 A1 * 4/2012 Dyson et al. 15/353
 2014/0068890 A1 3/2014 Dyson et al.
 2014/0075715 A1 3/2014 MacNaughton

FOREIGN PATENT DOCUMENTS

CN 1337204 2/2002
 CN 1428122 7/2003
 CN 1593322 3/2005
 CN 2764289 3/2006
 CN 1794941 6/2006
 CN 101262807 9/2008
 DE 299 13 775 2/2000
 DE 10 2006 008556 8/2007
 EP 0 558 101 9/1993
 EP 0558101 9/1993
 EP 0734678 10/1996
 EP 1 129 657 9/2001
 EP 1 210 899 6/2002
 EP 1 457 150 9/2004
 EP 1493373 1/2005
 EP 1474026 11/2005
 EP 1669015 6/2006
 EP 1836941 9/2007
 EP 1 857 032 11/2007
 EP 1915937 4/2008
 FR 1.310.618 11/1962
 FR 2833826 6/2003
 GB 645847 11/1950
 GB 2290462 1/1996
 GB 2290462 A * 1/1996 A47L 5/22
 GB 2368516 5/2002
 GB 2 391 459 2/2004
 GB 2 407 022 2/2006
 GB 2 402 046 9/2006
 GB 2 433 425 6/2007
 GB 2 452 549 3/2009
 GB 2453995 4/2009
 GB 2469038 10/2010
 GB 2469039 10/2010
 GB 2469045 10/2010
 GB 2469046 10/2010
 GB 2469047 10/2010
 GB 2469052 10/2010
 GB 2469055 10/2010
 GB 2475765 6/2011
 GB 2484121 4/2012
 JP 2-107218 4/1990
 JP 3-30 1/1991
 JP 4-103851 9/1992
 JP 5-91956 4/1993
 JP 5-168577 7/1993
 JP 05168577 A * 7/1993 A47L 9/28
 JP 7-163489 6/1995
 JP 07163489 A * 6/1995 A47L 9/00
 JP 7-184809 7/1995
 JP 8-275909 10/1996

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	8-317883	12/1996	
JP	9-276189	10/1997	
JP	10-278835	10/1998	
JP	2001-504001	3/2001	
JP	2001-314356	11/2001	
JP	2002-528250	9/2002	
JP	2002-345693	12/2002	
JP	2002-355199	12/2002	
JP	2003-24249	1/2003	
JP	2003-211025	7/2003	
JP	2003-310491	11/2003	
JP	2003-325392	11/2003	
JP	2004-310385	11/2004	
JP	2005-516712	6/2005	
JP	2005-334450	12/2005	
JP	2006-524062	10/2006	
JP	2006-326186	12/2006	
JP	2007-520294	7/2007	
JP	2007-307352	11/2007	
JP	2009-22403	2/2009	
JP	2009022403 A *	2/2009	
JP	2009-50735	3/2009	
NL	6711520	2/1969	
WO	WO-00/24519	5/2000	
WO	WO-01/56449	8/2001	
WO	WO-03/034888	5/2003	
WO	WO-03/039316	5/2003	
WO	WO-03/068042	8/2003	
WO	WO-2008/090490	7/2008	
WO	WO 2008090490 A2 *	7/2008 A47L 9/24
WO	WO-2008/117945	10/2008	
WO	WO-2009/011482	1/2009	
WO	WO-2009/022759	2/2009	
WO	WO-2009/030885	3/2009	
WO	WO-2010/112887	10/2010	
WO	WO-2011/072388	6/2011	

OTHER PUBLICATIONS

JP2009022403A: Feb. 2009—Machine Translation—English.*
 Search Report dated Oct. 24, 2012, directed to EP Application No. 11 17 9939; 4 pages.
 GB Search Report dated Jan. 27, 2011, directed to GB Application No. 1016450.7; 1 page.
 Dyson et al., U.S. Office Action dated Jun. 10, 2013, directed to U.S. Appl. No. 12/730,428; 7 pages.
 Dyson et al., U.S. Office Action dated Apr. 8, 2013, directed to U.S. Appl. No. 12/729,751; 20 pages.
 Sunderland et al., U.S. Office Action dated Apr. 3, 2013, directed to U.S. Appl. No. 12/729,885; 10 pages.
 Sunderland et al., U.S. Office Action dated Apr. 12, 2013, directed to U.S. Appl. No. 12/730,890; 9 pages.
 Genn et al., U.S. Office Action dated Jul. 30, 2013, directed to U.S. Appl. No. 12/730,900; 5 pages.
 Dyson et al., U.S. Office Action dated Aug. 15, 2013, directed to U.S. Appl. No. 13/250,298; 12 pages.
 Dyson et al., U.S. Office Action dated Aug. 15, 2013, directed to U.S. Appl. No. 13/248,810 10 pages.
 Sunderland et al., U.S. Office Action dated Jun. 20, 2013, directed to U.S. Appl. No. 12/729,643; 7 pages.
 MacNaughton, U.S. Office Action dated Jun. 19, 2013, directed to U.S. Appl. No. 12/730,539; 11 pages.

Dyson et al., U.S. Office Action dated Dec. 23, 2013, directed to U.S. Appl. No. 14/081,652; 7 pages.
 Dyson et al., U.S. Office Action dated Sep. 11, 2013, directed to U.S. Appl. No. 12/729,751; 16 pages.
 Sunderland et al., U.S. Office Action dated Jan. 27, 2014, directed to U.S. Appl. No. 13/248,824; 7 pages.
 Dyson et al., U.S. Office Action dated Jul. 23, 2014, directed to U.S. Appl. No. 14/081,652; 10 pages.
 MacNaughton, U.S. Office Action dated Sep. 22, 2014, directed to U.S. Appl. No. 14/082,903; 10 pages.
 Dyson et al., U.S. Office Action dated Sep. 12, 2014, directed to U.S. Appl. No. 13/250,298; 11 pages.
 Dyson et al., U.S. Office Action dated Jul. 23, 2014, directed to U.S. Appl. No. 13/248,810; 11 pages.
 Dyson et al., U.S. Office Action dated Mar. 21, 2014, directed to U.S. Appl. No. 13/250,298; 10 pages.
 Dyson et al., U.S. Office Action dated Mar. 26, 2014, directed to U.S. Appl. No. 13/248,810 11 pages.
 Dyson et al., U.S. Office Action dated Sep. 6, 2012, directed to U.S. Appl. No. 12/730,428; 12 pages.
 Dyson et al., U.S. Office Action dated Jan. 2, 2013, directed to U.S. Appl. No. 12/730,428; 11 pages.
 Dyson et al., U.S. Office Action dated Apr. 24, 2012, directed to U.S. Appl. No. 12/731,967; 19 pages.
 Dyson et al., U.S. Office Action dated Aug. 8, 2012, directed to U.S. Appl. No. 12/731,967; 14 pages.
 Dyson et al., U.S. Office Action dated Jan. 28, 2013, directed to U.S. Appl. No. 12/731,967; 14 pages.
 Gammack et al., U.S. Office Action dated Dec. 7, 2012, directed to U.S. Appl. No. 12/731,755; 11 pages.
 Gammack et al., U.S. Office Action dated Mar. 14, 2013, directed to U.S. Appl. No. 13/731,755; 9 pages.
 Dyson et al., U.S. Office Action dated Sep. 27, 2012, directed to U.S. Appl. No. 12/729,751; 19 pages.
 Sunderland et al., U.S. Office Action dated Sep. 27, 2012, directed to U.S. Appl. No. 12/729,885; 20 pages.
 Sunderland et al., U.S. Office Action dated Apr. 25, 2012, directed to U.S. Appl. No. 12/729,849; 22 pages.
 Sunderland et al., U.S. Office Action dated Aug. 24, 2012, directed to U.S. Appl. No. 12/729,849; 18 pages.
 Sunderland et al., U.S. Office Action dated Sep. 13, 2012, directed to U.S. Appl. No. 12/729,643; 11 pages.
 Sunderland et al., U.S. Office Action dated Feb. 12, 2013, directed to U.S. Appl. No. 12/729,643; 8 pages.
 MacNaughton, U.S. Office Action dated Feb. 14, 2013, directed to U.S. Appl. No. 12/730,539; 9 pages.
 MacNaughton, U.S. Office Action dated Sep. 13, 2012, directed to U.S. Appl. No. 12/730,539; 9 pages.
 Genn et al., U.S. Office Action dated Sep. 13, 2012, directed to U.S. Appl. No. 12/730,900; 12 pages.
 Genn et al., U.S. Office Action dated Jan. 15, 2013, directed to U.S. Appl. No. 12/730,900; 8 pages.
 Dyson et al., U.S. Office Action dated Sep. 21, 2012, directed to U.S. Appl. No. 12/730,913; 13 pages.
 Sunderland et al., U.S. Office Action dated Dec. 24, 2012, directed to U.S. Appl. No. 12/730,890; 12 pages.
 Dyson et al., U.S. Office Action dated Feb. 20, 2015, directed to U.S. Appl. No. 13/248,810; 12 pages.
 Dyson et al., U.S. Office Action dated Oct. 8, 2015, directed to U.S. Appl. No. 13/248,810; 13 pages.

* cited by examiner




FIG. 1




FIG. 2(a)




FIG. 2(b)




FIG. 2(c)





FIG. 3






FIG. 5(a)




FIG. 5(b)




FIG. 6(a)




FIG. 6(b)

FIG. 7(b)





FIG. 7(a)




FIG. 8

1

CLEANING APPLIANCE

REFERENCE TO RELATED APPLICATIONS

This application claims the priority of United Kingdom Application No. 1016450.7, dated Sep. 30, 2010, the entire contents of which are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to a cleaning appliance, which is preferably in the form of a vacuum cleaning appliance.

BACKGROUND OF THE INVENTION

Cleaning appliances such as vacuum cleaners are well known. The majority of vacuum cleaners are either of the "upright" type or of the "cylinder" type (called canister or barrel machines in some countries). Cylinder vacuum cleaners generally comprise a main body which contains a motor-driven fan unit for drawing a dirt-bearing air flow into the vacuum cleaner, and separating apparatus, such as a cyclonic separator or a bag, for separating dirt and dust from the air flow. The dirt-bearing air flow is introduced to the main body through a suction hose and wand assembly which is connected to the main body. The main body of the vacuum cleaner is dragged along by the hose as a user moves around a room. A cleaning tool is attached to the remote end of the hose and wand assembly.

For example, GB 2,407,022 describes a cylinder vacuum cleaner having a chassis which supports cyclonic separating apparatus. The vacuum cleaner has two main wheels, one on each side of a rear portion of the chassis, and a castor wheel located beneath the front portion of the chassis which allow the vacuum cleaner to be dragged across a surface. Such a castor wheel tends to be mounted on a circular support which is, in turn, rotatably mounted on the chassis to allow the castor wheel to swivel in response to a change in the direction in which the vacuum cleaner is dragged over the surface.

EP 1,129,657 describes a cylinder vacuum cleaner which is in the form of a spherical body connected to the suction hose and wand assembly. The spherical volume of the spherical body incorporates a pair of wheels, one located on each side of the body, and houses an electric blower for drawing a fluid flow through the cleaner, and a dust bag for separating dirt and dust from the fluid flow.

PCT/GB2010/050418 describes a cylinder vacuum cleaner having a generally spherical rolling assembly connected to the chassis for improving the maneuverability of the vacuum cleaner over a floor surface. The rolling assembly comprises a body and a pair of dome shaped wheels connected to the body. The chassis extends forwardly from the body of the rolling assembly, and includes a pair of wheels for steering the vacuum cleaner and for supporting the rolling assembly as the vacuum cleaner is maneuvered over a floor surface.

The chassis also includes a support for supporting cyclonic separating apparatus of the vacuum cleaner. The support is located on an inlet duct for conveying a dirt-bearing air flow to the separating apparatus. To assist with the maneuvering of the vacuum cleaner around objects located on the floor surface, the inlet duct is pivotably connected to the chassis for movement relative to the chassis as the user pulls the vacuum cleaner in different directions over the floor surface. The movement of the duct relative to

2

the chassis actuates a steering mechanism for turning the wheels connected to the chassis. The inlet duct comprises a relatively rigid section connected to the chassis for pivoting movement relative thereto, and a relatively flexible hose located upstream to the rigid section and which tends to flex relative to the rigid section as the duct pivots relative to the chassis.

SUMMARY OF THE INVENTION

The present invention provides a cleaning appliance of the canister type comprising a separating apparatus for separating dirt from a dirt-bearing fluid flow, a floor engaging rolling assembly comprising a system for drawing the fluid flow through the separating apparatus, a chassis connected to the rolling assembly, and a duct comprising an outlet section releasably connected to the rolling assembly for conveying the fluid flow to the separating apparatus, and an inlet section connected to the chassis for pivoting movement relative to the outlet section and the chassis.

The provision of a removable outlet section of the duct enables any blockages to be removed easily from the outlet section of the duct, and facilitates the removal of blockages from the inlet section. Shaping the duct so that the outlet section is releasably connected to the rolling assembly can provide the cleaning appliance with a compact appearance.

The rolling assembly preferably comprises a main body connected to the chassis, and a plurality of floor engaging rolling elements. To reduce the number of components of the cleaning appliance the chassis is preferably integral with part of the main body of the rolling assembly. Preferably, the main body and a plurality of floor engaging rolling elements together define a substantially spherical floor engaging rolling assembly, which term includes a spheroidal rolling assembly. The main body may comprise a plurality of sections, and each rolling element may be connected to a respective one of the sections. The chassis is preferably integral with one of the sections of the main body. The outlet section of the duct preferably comprises a manually operable catch for releasably engaging the main body of the rolling assembly.

Each of the plurality of rolling elements is preferably in the form of a wheel rotatably connected to a respective side of the main body of the rolling assembly. Each of these rolling elements preferably has a curved, preferably dome-shaped, outer surface. Each of the plurality of rolling elements preferably has an outer surface of substantially spherical curvature. The rotational axes of the rolling elements may be inclined upwardly towards the main body with respect to a floor surface upon which the cleaning appliance is located so that the rims of the rolling elements engage the floor surface. The angle of the inclination of the rotational axes is preferably in the range from 4 to 15°, more preferably in the range from 5 to 10°. As a result of the inclination of the rotational axes of the rolling elements, part of the outer surface of the main body is exposed to enable components of the cleaning appliance, such as user-operable switches for activating the motor or a cable-rewind mechanism, to be located on the exposed part of the main body. In a preferred embodiment, one or more ports for exhausting the air flow from the cleaning appliance are located on the outer surface of the main body.

The separating apparatus preferably comprises cyclonic separating apparatus. The appliance preferably comprises a support for supporting the separating apparatus. The support is preferably connected to, and more preferably integral with, part of the separating apparatus. The support is pref-

erably located on the front of the main body. The support preferably comprises a spigot locatable within a recess formed in a base member of the separating apparatus. When the separating apparatus is mounted on the support, the separating apparatus preferably has a longitudinal axis inclined at an acute angle to the vertical when the cleaning appliance moves over a substantially horizontal floor surface. This angle may be in the range from 30 to 70°. The main body may further comprise one or more additional supports for supporting the side surface of the separating apparatus. The side surface of the separating apparatus is preferably cylindrical, and so these additional supports preferably have support surfaces which have a similar curvature to the side surface of the separating apparatus. The outlet section of the duct is preferably shaped to change the direction in which air passes therethrough. In a preferred embodiment, a fluid inlet of the separating apparatus is located on a side surface of the separating apparatus, and so the outlet section is preferably arranged to change the direction in which the air passes therethrough by an angle in the range from 20 to 60°.

The inlet section of the duct preferably passes beneath the support. The duct preferably passes through a sleeve located between the support and the main body of the rolling assembly. The sleeve is preferably integral with the support and the main body. Alternatively, the sleeve may be connected to the chassis. The sleeve preferably extends about a joint between the inlet section and the outlet section of the duct. This joint may comprise one or more sealing members for maintaining a fluid tight seal between the sections of the duct as the inlet section pivots relative to the outlet section.

The support may be configured to inhibit pivoting movement of the outlet section with the inlet section. For example, one of the support and the outlet section may comprise a detent which is locatable within a recess of the other of the support and the outlet section.

The chassis preferably comprises a plurality of floor engaging support members for supporting the rolling assembly as it is maneuvered over a floor surface. Each support member is preferably in the form of a wheel or other rolling member, such as a caster or ball.

The cleaning appliance preferably comprises an outlet duct extending from the separating apparatus to the rolling assembly for conveying the fluid flow to the rolling assembly. Preferably, the duct can be disengaged from the separating apparatus to allow the separating apparatus to be removed from the appliance. To facilitate the disengagement of the duct from the separating apparatus, the duct is preferably pivotably connected to the rolling assembly. The duct is preferably connected to the upper surface of the rolling assembly so that it can be moved between a raised position to allow the separating apparatus to be removed from, and subsequently relocated on, the appliance, and a lowered position, in which the duct engages the separating apparatus. In its lowered position, the duct is preferably configured to retain the separating apparatus on the appliance. The duct is preferably formed from a rigid material, preferably a plastics material, and may include a handle.

The rolling assembly preferably comprises a conduit for receiving the fluid flow from the fluid inlet, and for conveying the fluid flow to said system for drawing a fluid flow through the separating apparatus. The system for drawing the fluid flow through the separating apparatus is preferably in the form of a motor-driven fan unit. In the preferred embodiment, the conduit comprises a fluid inlet for receiving the fluid flow from the duct, and a fluid outlet for conveying the fluid flow to said system for drawing the fluid

flow through the separating apparatus. Depending on the orientation of said mean for drawing the fluid flow through the separating apparatus, the conduit may be arranged to change the direction of the fluid flow by around 90°. A grille or other filter may be provided within the outlet duct for preventing dirt or other objects from entering the conduit when the duct is detached from the separating apparatus, or in the event that a relatively large object is inadvertently located within the filter assembly of the separating apparatus when the outlet duct is in its raised position.

Although an embodiment of the invention is described in detail with reference to a vacuum cleaner, it will be appreciated that the invention can also be applied to other forms of cleaning appliance.

BRIEF DESCRIPTION OF THE DRAWINGS

Preferred features of the invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

FIG. 1 is a front perspective view, from above, of a vacuum cleaner;

FIG. 2(a) is a front perspective view, from above, of the vacuum cleaner, with a separating apparatus of the vacuum cleaner removed, FIG. 2(b) is a side view of the same, and FIG. 2(c) is a top view of the same;

FIG. 3 is a rear perspective view, from above, of the chassis base plate, wheel assemblies, inlet section of the inlet duct and biasing arrangements of the vacuum cleaner;

FIG. 4 is a top sectional view taken along line A-A in FIG. 2(b);

FIG. 5(a) is a front perspective view, from above, of the vacuum cleaner with the separating apparatus removed and the inlet section of the inlet duct pivoted relative to the chassis; and FIG. 5(b) is a top view of the same;

FIG. 6(a) is a side sectional view taken along line C-C in FIG. 2(c), and FIG. 6(b) is a magnified view of part of FIG. 6(a);

FIG. 7(a) is a top view of the separating apparatus, and FIG. 7(b) is a sectional view taken along line D-D in FIG. 7(a); and

FIG. 8 is a rear sectional view taken along line B-B in FIG. 2(c).

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 illustrates an external view of a cleaning appliance in the form of a vacuum cleaner 10. The vacuum cleaner 10 is of the cylinder, or canister, type. In overview, the vacuum cleaner 10 comprises separating apparatus 12 for separating dirt and dust from a fluid flow. The separating apparatus 12 is preferably in the form of cyclonic separating apparatus, and comprises an outer bin 14 having an outer wall 16 which is substantially cylindrical in shape. The lower end of the outer bin 14 is closed by curved base 18 which is pivotably attached to the outer wall 16. A motor-driven fan unit for generating suction for drawing dirt laden fluid into the separating apparatus 12 is housed within a rolling assembly 20 located behind the separating apparatus 12. The rolling assembly 20 comprises a main body 22 and two wheels 24, 26 (see FIG. 2(a)) rotatably connected to the main body 22 for engaging a floor surface. An inlet duct 28 extending beneath the separating apparatus 12 conveys dirt-bearing fluid into the separating apparatus 12, and an outlet duct 30 conveys fluid exhausted from the separating apparatus 12 into the rolling assembly 20. The inlet duct 28 is connected

5

to a hose of a hose and wand assembly (not shown) which the user pulls to maneuver the vacuum cleaner 10 over the floor surface.

A chassis 32 is connected to the main body 22 of the rolling assembly 20. In this example, the chassis 32 is integral with part of the main body 22 of the rolling assembly 20. The chassis 32 is generally in the shape of an arrow head pointing forwardly from the rolling assembly 20. The chassis 32 comprises side edges 34 which extend rearwardly and outwardly from the front tip 36 of the chassis 32, shown in FIGS. 5(b) and 6(a). The front tip 36 of the chassis 32 is located on an axis A extending substantially perpendicular to a vertical plane passing through the center of the rolling assembly 20. The direction in which the vacuum cleaner 10 moves over a floor surface during a cleaning operation extends along the axis A. The angling of the side edges 34 relative to the axis A can assist in maneuvering the vacuum cleaner 10 around corners, furniture or other items upstanding from the floor surface, as upon contact with such an item these side edges 34 tend to slide against the upstanding item to guide the rolling assembly 20 around the upstanding item. As illustrated in the figures, bumpers or pads 38 may be attached to the side edges 34.

A pair of wheels 40 for engaging the floor surface is connected to the chassis 32. The wheels 40 are located behind the side edges 34 of the chassis 32, and in front of the wheels 24, 26 of the rolling assembly 20. As shown in FIG. 3, each wheel 40 is mounted on a respective axle 42 fitted to the chassis 32, for example by press fitting or overmolding, so that the wheel 40 rotates relative to the axle 42, and thus relative to the chassis 32. Each axle 42 is aligned along an axis which is substantially perpendicular to the axis A so that the wheels 40 rotate to move the vacuum cleaner 10 in a direction extending along the axis A.

The wheels 40 also provide support members for supporting the rolling assembly 20 as the vacuum cleaner 10 is maneuvered over a floor surface by restricting rotation of the rolling assembly 20 about the axis A. For increased support to the rolling assembly 20, the distance between the points of contact of the wheels 40 with the floor surface is greater than that between the points of contact of the wheels 24, 26 of the rolling assembly 20 with that floor surface.

As shown in FIG. 2(b), the components of the vacuum cleaner 10 are arranged so that, when the vacuum cleaner 10 is located on a substantially horizontal floor surface F, the center of gravity C of the vacuum cleaner 10 is located within the rolling assembly 20. The center of gravity C is located in a first vertical plane PL1 which passes between a second vertical plane PL2 containing the points of contact between the wheels 24, 26 of the rolling assembly 20 and the floor surface, and a third vertical plane PL3 containing the points of contact between the wheels 40 and the floor surface, preferably substantially mid-way between the two planes PL2, PL3. This can further enhance the stability of the vacuum cleaner 10 as it is maneuvered over the floor surface.

The location of the center of gravity C is indicated above for a situation in which the separating apparatus 12 is connected to the vacuum cleaner 10, and the separating apparatus 12 is in an unloaded state, and with no hose and wand assembly connected to the vacuum cleaner 10.

To reverse the direction in which the vacuum cleaner 10 is moving over a floor surface, the user may raise the wheels 40 of the chassis 32 from the floor surface, using the hose of the hose and wand assembly so that the vacuum cleaner 10 tilts backwards on to the wheels 24, 26 of the rolling

6

assembly 20. Using the hose, the vacuum cleaner 10 may then be “spun” around the point of contact between the rolling assembly 20 and the floor surface until the vacuum cleaner 10 is facing in the required direction. The hose may then be lowered to bring the wheels 40 back into contact with the floor surface, and the vacuum cleaner 10 pulled in the required direction.

To enable the vacuum cleaner 10 to be maneuvered smoothly around an object or the corner of a wall during a cleaning operation, part of the inlet duct 28 is connected to the chassis 32 for pivoting movement relative to the chassis 32, and thus relative to the rolling assembly 20. FIGS. 2(a) to 2(c) illustrate the vacuum cleaner 10 with the separating apparatus 12 to reveal the inlet duct 28. The removal of the separating apparatus 12 from the vacuum cleaner 10 is described in more detail below. The inlet duct 28 comprises an inlet section 44 for receiving the dirt-bearing fluid flow from the hose and wand assembly, and an outlet section 46 for coupling the inlet section 44 to the separating apparatus 12 to convey the dirt-bearing fluid flow into the separating apparatus 12. The inlet section 44 is pivotably connected to the chassis 32, whereas the outlet section 46 is connected to the main body 22 of the rolling assembly 20 so that the inlet section 44 is pivotable relative to the outlet section 46. Alternatively, the outlet section 46 may be connected to the chassis 32.

With particular reference to FIGS. 3, 4, 6(a) and 6(b), in this example the inlet section 44 of the inlet duct 28 comprises a plurality of components. The inlet section 44 comprises a coupling 48 for electrical and/or physical connection to a wand and hose assembly (not shown) for conveying the duct-bearing fluid flow to the inlet duct 28. The wand and hose assembly is connected to a cleaner head (not shown) comprising a suction opening through which a dirt-bearing fluid flow is drawn into the vacuum cleaner 10. The coupling 48 is connected to one end of a cylindrical section 50 of the inlet duct 28. Of course, the section 50 may have an alternative cross-sectional shape, such as an elliptical or polyhedral shape. The other end of the cylindrical section 50 is connected to a curved section 52 of the inlet duct 28. In this example, the cylindrical section 50 is integral with the curved section 52, but these two sections 50, 52 of the inlet duct 28 may be integrally formed. The curved section 52 is shaped to change the direction in which the fluid flows through the inlet duct 28 by around 90°. The curved section 52 has a fluid outlet 54 which is concentric with, and located immediately below, a fluid inlet 56 of the outlet section 46 of the inlet duct 28. One or more annular sealing members 58, 60 are located between the fluid outlet 54 and the fluid inlet 56 to maintain an air tight seal and a relatively low frictional force therebetween during pivoting movement of the inlet section 44 relative to the outlet section 46.

The inlet section 44 is mounted on a cylindrical spindle 62 extending upwardly from the upper surface of the chassis 32. The curved section 52 comprises a cylindrical boss 64 depending downwardly therefrom and which is located over the spindle 62 so as to be substantially concentric with the spindle 62. A plain bearing or sleeve 66 may be located between the spindle 62 and the boss 64 to minimize friction therebetween during rotation of the boss 64 about the spindle 62 and to ensure accurate alignment between the spindle 62 and the boss 64. Alternatively, the spindle 62 may be formed from a low friction material. The longitudinal axis of the spindle 62 thus defines the pivot axis P about which the inlet section 44 pivots relative to the chassis 32 and the outlet section 46. The pivot axis P passes through the center

of the fluid outlet **54** of the inlet section **44** and the fluid inlet **56** of the outlet section **46**. The pivot axis P is substantially vertical when the vacuum cleaner **10** is located on a horizontal floor surface. As the curved section **52** is shaped with a 90° bend, the longitudinal axis of the cylindrical section **50** is substantially orthogonal to the pivot axis P and so during pivoting movement of the inlet section **44** the cylindrical section **50** sweeps orthogonally about the pivot axis P.

The pivoting movement of the inlet section **44** relative to the chassis **32** is guided by a pin or rib **68** depending from the cylindrical section **50**. The rib **68** is moveable within a curved groove or slot **70** which extends about the pivot axis P, and which is formed in a portion of the upper surface of the chassis **32** which is substantially orthogonal to the pivot axis P.

The inlet section **44** is pivotable about the pivot axis P by an angle of $\pm\alpha^\circ$ from a central, rest position. The angle α is preferably in the range from 15 to 45°, and in this example is around 30°. The inlet section **44** is illustrated in its rest position in FIGS. **1** to **4**, **6(a)** and **6(b)**. In this rest position, the inlet section **44** is aligned along the axis A, that is, with the longitudinal axis of the cylindrical section **50** of the inlet section **44** parallel to the axis A. FIGS. **5(a)** and **5(b)** illustrate the vacuum cleaner **10** with the inlet section **44** pivoted by around 30° in the angular direction R_1 , indicated in FIG. **4**, from the rest position. The extent of the pivoting movement of the inlet section **44** away from the rest position is restricted by the abutment of the side of the inlet section **44** with one of a pair of raised walls **72** of the chassis **32**, as illustrated in FIG. **1**.

The inlet section **44** of the inlet duct **28** is biased towards a rest position. Consequently, when the inlet section **44** is pivoted away from the rest position during the maneuvering the vacuum cleaner **10** over a floor surface, for example while the vacuum cleaner **10** is being pulled around an object or piece of furniture, the inlet duct **44** will return automatically to its rest position when the vacuum cleaner **10** has moved away from the object.

The inlet section **44** is biased towards its rest position by a biasing system which engages the inlet section **44** to urge the inlet section **44** towards its rest position. With reference now to FIGS. **3** and **4**, in this example the biasing system comprises a plurality of biasing arrangements **74**, **76** located on opposite sides of the inlet section **44**. A first biasing arrangement **74** is arranged to urge the inlet section **44** towards the rest position when it moves in angular direction R_1 away from the rest position, and a second biasing arrangement **76** is arranged to urge the inlet section **44** towards the rest position when it moves in angular direction R_2 , opposite to R_1 , away from the rest position.

The inlet section **44** comprises a return member for engaging the biasing arrangements **74**, **76** as the inlet section **44** is pivoted away from the rest position. In this example, the return member is in the form of an arm **78** connected to the curved section **52**, and generally on the opposite side of the curved section **52** to the cylindrical section **50**.

The biasing arrangements **74**, **76** are located beneath the chassis **32**. The vacuum cleaner **10** includes a chassis base plate **80** which is connected to the lower section of the chassis **32**, and the biasing arrangements **74**, **76** are located within a housing **82** located between the chassis **32** and the chassis base plate **80**. During assembly, the biasing arrangements **74**, **76** are located within the housing **82**, and the housing **82** is connected to the base plate **80**. The chassis **32** is then connected to the base plate **80**, for example by means of screws or other connectors **84** inserted through apertures in the base plate **80**. The inlet section **44** is then mounted on

the chassis **32**. To engage the biasing arrangements **74**, **76**, the arm **78** of the inlet section **44** extends through a curved slot **86**, indicated in FIG. **6(a)**, formed in the chassis **32** behind the spindle **62** to enter the housing **82**.

With particular reference to FIG. **4**, the housing **82** extends about the pivot axis P. When the inlet section **44** is in its rest position, the arm **78** is located centrally within the housing **82**, between the biasing arrangements **74**, **76**. Each biasing arrangement **74**, **76** is located within a respective compartment of the housing **82**, between which the arm **78** is located when in its rest position. Each biasing arrangement **74**, **76** comprises a resilient element, in this example in the form of a helical compression spring **88**, and a piston, in this example in the form of a circular disc **90**. The spring **88** urges the disc **90** against an annular seat located at one end of the compartment. The other end of the compartment is closed by a closure member **92** connected to the housing **82**.

When the inlet section **44** is pivoted about the pivot axis P in the direction R_1 , for example, the arm **78** enters the compartment housing the biasing arrangement **74**. The biasing force of the spring **88** is selected to allow the arm **78** to move within the compartment towards the closure member **92**, against the biasing force of the spring **88**, without the user having to apply an excessive force to the inlet section **44** using the hose and wand assembly attached thereto. When the user relaxes the force applied to the inlet section **44**, for example when the vacuum cleaner **10** has moved beyond an obstacle on the floor surface, the biasing force of the spring **88** exceeds the force applied to the inlet section **44**. This causes the spring **88** to urge the disc **90** back towards its seat, thereby returning the arm **78** automatically to its rest position.

As mentioned above, the outlet section **46** of the inlet duct **28** provides a static coupling between the separating apparatus **12** and the inlet section **44** of the inlet duct **28**. The fluid inlet **56** of the outlet section **46** is mounted on, and supported by, the annular sealing members **58**, **60** of the inlet duct **28**. The outlet section **46** is removably connected to the main body **22** of the rolling assembly **20** to allow the outlet section **46** to be removed from the vacuum cleaner **10** by the user to allow any blockages within the outlet section **46** to be removed. The removal of the outlet section **46** from the vacuum cleaner **10** also facilitates the removal of blockages from within the inlet section **44** of the inlet duct **28**. As shown in FIG. **6(b)**, the outlet section **46** comprises a manually operable, resilient catch **100** which extends upwardly from a rear surface of the outlet section **46**. The catch **100** engages a catch face **102** located on the main body **22** of the rolling assembly **20**, or alternatively on the chassis **32**, to retain the outlet section **46** on the main body **22**. To remove the outlet section **46**, the user pulls the catch **100** away from the catch face **102** and lifts the outlet section **46** away from the inlet section **44**.

The vacuum cleaner **10** comprises a support **104** for supporting the separating apparatus **12**. The support **104** is connected to, and in this example is integral with, part of the main body **22** of the rolling assembly **20**. The support **104** extends forwardly from the main body **22** so as to extend over the inlet section **44** of the inlet duct **28**. The main body **22**, and therefore the support **104**, is formed from a relatively rigid material, preferably a plastics material, so that, when the separating apparatus is mounted on the support **104**, the support **104** does not deform to such an extent as to engage the upper surface of the inlet section **44**, and thereby interfere with the pivoting movement of the inlet section **44** relative to the chassis **32**. The end of the support **104** which is remote from the main body **22** comprises a spigot **106**

which extends upwardly therefrom for location within a recess (not shown) formed in the base 18 of the outer bin 14. The location of the spigot 106 within the recess ensures correct angular alignment of the separating apparatus 12 relative to the support 104 when it is mounted on the support 104, so that a fluid inlet 108 of the separating apparatus 12 is located over and against a fluid outlet 110 of the outlet section 46. The outlet section 46 is provided with a flexible annular seal surrounding the fluid outlet 110 for forming an air tight seal against the periphery of the fluid inlet 108 of the separating apparatus 12.

When the separating apparatus 12 is mounted on the support 104, the longitudinal axis of the outer bin 14 is inclined to the pivot axis P, in this example by an angle in the range from 30 to 40°. The outer wall 16 of the outer bin 14 is supported by a pair of resilient supports 112 mounted on the main body 22 of the rolling assembly 20.

To provide the vacuum cleaner 10 with a compact appearance, the main body 22 and the support 104 together define a sleeve 114 through which the inlet duct 28 extends. The longitudinal axis of the sleeve 114 is co-linear with the pivot axis P of the inlet section 44. The inlet section 44 and the outlet section 46 of the inlet duct 28 are located on opposite sides of the sleeve 114. The sleeve 114 thus surrounds the fluid outlet 54 of the inlet section 44, the fluid inlet 56 of the outlet section 56, and the annular sealing members 58, 60. The inner surface of the sleeve 114 comprises a recess 116 for receiving a detent 118 located on the outer surface of the outlet section 46 when the outlet section 46 is mounted on the main body 22. The recess 116 has substantially the same profile as the detent 118 to inhibit rotation of the outlet section 46 relative to the sleeve 114, and therefore relative to the separating apparatus 12 and the main body 22, as the inlet section 44 pivots about the pivot axis P.

The separating apparatus 12 is illustrated in FIGS. 7(a) and 7(b). The specific overall shape of the separating apparatus 12 can be varied according to the size and type of vacuum cleaner in which the separating apparatus 12 is to be used. For example, the overall length of the separating apparatus 12 can be increased or decreased with respect to the diameter of the apparatus, or the shape of the base 18 can be altered.

As mentioned above, the separating apparatus 12 comprises an outer bin 14 which has an outer wall 16 which is substantially cylindrical in shape. The lower end of the outer bin 14 is closed by a base 18 which is pivotably attached to the outer wall 16 by means of a pivot 120 and held in a closed position by a catch (not shown) which engages a groove located on the outer wall 16. In the closed position, the base 18 is sealed against the lower end of the outer wall 16. The catch is resiliently deformable so that, in the event that downward pressure is applied to the uppermost portion of the catch, the catch will move away from the groove and become disengaged therefrom. In this event, the base 18 will drop away from the outer wall 16.

With particular reference to FIG. 7(b), the separating apparatus 12 further comprises a dust collector 122 located within the outer bin 14. The dust collector 122 has a generally cylindrical outer wall 124, and a generally cylindrical inner wall 126 connected to the outer wall 124 at the upper end of the dust collector 122, and a base 128 which closes the lower end of the inner wall 126. The outer wall 124 of the dust collector 122 is located radially inwardly of the outer wall 16 and spaced therefrom so as to form an annular chamber 130 therebetween. The outer wall 124 of the dust collector 122 meets the base 18 (when the base 18 is in the closed position) and is sealed against an annular

sealing member 132 carried by the base 18. The fluid inlet 108 is arranged tangentially to the outer bin 14 (as shown in FIG. 6(a)) so as to ensure that incoming dirty fluid is forced to follow a helical path around the annular chamber 124.

A fluid outlet from the annular chamber 130 is provided in the form of a perforated shroud. The shroud has an upper section 134 formed in a frusto-conical shape, a cylindrical section 136 and a skirt 138 depending therefrom. A large number of apertures are formed in the cylindrical section 136. The skirt 138 tapers outwardly from the cylindrical section 136 in a direction towards the outer wall 16.

The upper section 134 of the shroud is connected to a cyclone pack 140. The cyclone pack 140 is mounted on the upper end of the dust collector 122, and comprises a circumferential flange 142 for engaging the upper end of the outer bin 14. The cyclone pack 140 carries an annular seal 144 for sealing against the outer wall 16 adjacent the upper end of the outer bin 14.

The cyclone pack 140 comprises an annular array of cyclones 146. The cyclones 146 are arranged in parallel. In the preferred embodiment there are twelve cyclones 146 for this bin diameter arranged in a ring which is centered on a longitudinal axis of the outer bin 14. Each cyclone 146 has an axis which is inclined downwardly and towards the longitudinal axis. The twelve cyclones 146 can be considered to form a second cyclonic separating unit, with the annular chamber 130 forming the first cyclonic separating unit. In the second cyclonic separating unit, each cyclone 146 has a smaller diameter than the annular chamber 124 and so the second cyclonic separating unit is capable of separating finer dirt and dust particles than the first cyclonic separating unit. It also has the added advantage of being challenged with a fluid flow which has already been cleaned by the first cyclonic separating unit and so the quantity and average size of entrained particles is smaller than would otherwise have been the case. The separation efficiency of the second cyclonic separating unit is higher than that of the first cyclonic separating unit.

Each cyclone 146 is identical to the other cyclones 146, and comprises a cylindrical upper portion having a tangential inlet 148 and a tapering portion depending from the upper portion. The tapering portion of each cyclone 146 is frusto-conical in shape and terminates in a cone opening 150. Each tapering portion protrudes through an aperture formed in the upper end of the dust collector 122 so that the cone opening 150 is located in a chamber 152 located between the outer wall 124 and the inner wall 126 of the dust collector 122.

The inner wall 126 and the base 128 of the dust collector 122 form a lower section of a filter housing 154. An upper section of the filter housing 154 is provided by a generally annular filter housing member 156 mounted on the upper end of the dust collector 122, and which forms a generally continuous inner wall of the filter housing 154 with the inner wall 126 of the dust collector 122. The cyclone pack 140 surrounds the filter housing member 156 and defines with the filter housing member 156 a plenum chamber 158 for conveying fluid which has passed through the apertures in the shroud to the inlets 148 of the cyclones 146.

The open upper ends of the cyclones 146 are closed by an annular exhaust manifold. The exhaust manifold comprises an upper section 160 and a lower section 162. An apertured sealing member 163 may be provided between the cyclone pack 140 and the lower section 162 of the exhaust manifold. The lower section 162 of the exhaust manifold comprises a vortex finder 164 to allow fluid to exit the cyclone 146. Each vortex finder 164 communicates with a manifold finger 166

defined between the upper and lower sections 160, 162 of the exhaust manifold. Each manifold finger 166 is a generally inverted U-shape and extends from the upper end of a respective cyclone 146 to a generally cylindrical exhaust manifold wall 168 formed in the upper section 160 of the exhaust manifold. The wall 168 comprises a plurality of apertures 170 each for receiving fluid from a respective one of the manifold fingers 166. The wall 168 extends about a bore which is generally co-axial with the outer wall 16.

The apertures 170 convey fluid into the filter housing 154. A filter assembly 180 is located within the filter housing 154. The filter assembly 180 is inserted into the filter housing 154 through the bore of the upper section 162 of the exhaust manifold. The filter assembly 180 comprises a body 182 and a filter 184 mounted on the filter body 182. The filter body 182 is preferably a single-piece item, preferably molded from plastics material, but alternatively the filter body 182 may be formed from a plurality of components connected together. The filter body 182 is generally tubular in shape, and comprises an annular body 186, a set of radially extending elongate spokes 188 connected to the inner surface of the body 186 and depending therefrom. A set of elongate fins 190 is connected between the spokes 188 so that each fin 190 is located between adjacent spokes 188. The fins 190 are connected to the spokes 188 by connectors 192. The spokes 188 and the fins 190 together provide a support for supporting the filter 184.

The filter 184 is in the form of a sock filter which extends about the spokes 188 and the fins 190 of the filter body 182. The upper end of the filter 184 comprises a collar 194, which is retained within an annular groove formed in the filter body 182. The lower end of the filter 184 comprises a base or end cap 196 for closing the lower end of the filter 184 for ease of insertion of the filter assembly 180 into the filter housing 154.

The filter 184 further comprises a plurality of tubular filter members of varying levels of filtration for removing dust and other particulates from the fluid flow passing through the filter housing 154. The filter member having the finest level of filtration is preferably has the largest surface area. Each filter member of the filter assembly 180 is manufactured with a rectangular or tapering shape. The filter members are then joined and secured together along their longest edge by stitching, gluing or other suitable technique so as to form a tubular length of filter material having a substantially open cylindrical shape. An upper end of each cylindrical filter member is then attached to the collar 194, while a lower end of each filter member is attached to the end cap 196, for example by over-molding the material of the collar 194 and the end cap 196 during manufacture of the filter assembly 180. Alternative manufacturing techniques for attaching the filter members include gluing, and spin-casting polyurethane around the upper and lower ends of the filter members. In this way the filter members are encapsulated by polyurethane during the manufacturing process to produce a sealed arrangement which is capable of withstanding manipulation and handling by a user.

The filter body 182 comprises an annular sealing member 198 for engaging the air inlet 200 of the outlet duct 30. With reference to FIGS. 1 and 2(a), in this example the air inlet 200 of the outlet duct 30 is generally dome-shaped, and enters the filter assembly 180 through the open upper end 202 of the filter body 182 to engage the sealing member 198 and form an air-tight seal therewith. The sealing member 198 may be overmolded with the filter body 182 during

assembly, or otherwise attached to the filter body 182. Alternatively, the sealing member 198 may be integral with the filter body 182.

The outlet duct 30 is generally in the form of a curved arm extending between the separating apparatus 12 and the rolling assembly 20. The outlet duct 30 is moveable relative to the separating apparatus 12 to allow the separating apparatus 12 to be removed from the vacuum cleaner 10, and to allow the filter assembly 180 to be removed from the filter housing 154 of the separating apparatus 12. The end of the tube outlet duct 30 which is remote from the air inlet 200 of the outlet duct 30 is pivotably connected to the main body 22 of the rolling assembly 20 to enable the outlet duct 30 to be moved between a lowered position in which the outlet duct 30 is in fluid communication with the separating apparatus 12, and a raised position which allows the separating apparatus 12 to be removed from the vacuum cleaner 10.

The outlet duct 30 is biased towards the raised position by a resilient member (not shown) located in the main body 22. The main body 22 comprises a biased catch 204 for retaining the outlet duct 30 in the lowered position against the force of the resilient member, and a catch release button 206. The outlet duct 30 comprises a handle 208 to allow the vacuum cleaner 10 to be carried by the user when the outlet duct 30 is retained in its lowered position. Alternatively, the outlet duct 30 may be used to carry the vacuum cleaner 10. The catch 204 is arranged to co-operate with a finger 210 connected to outlet duct 30 to retain the outlet duct in its lowered position. Depression of the catch release button 206 causes the catch 204 to move away from the finger 210, against the biasing force applied to the catch 204, allowing the resilient member to move the outlet duct 30 to its raised position.

The rolling assembly 20 will now be described with reference to FIGS. 6(a) and 8. The rolling assembly 20 comprises a main body 22 and two curved wheels 24, 26 rotatably connected to the main body 22 for engaging a floor surface. In this embodiment the main body 22 and the wheels 24, 26 define a substantially spherical rolling assembly 20. In this example, the main body 20 comprises an upper section 212 and a lower section 214 connected to the upper section 212. The support 106 is integral with the upper section 212, whereas the chassis 32 is integral with the lower section 214. The wheel 24 is mounted on an axle 216 connected to the lower section 214 of the body 22, whereas the wheel 26 is mounted on an axle 218 connected to the upper section 212 of the body 22. The axles 216, 218 are arranged so that the rotational axes of the wheels 24, 26 are inclined upwardly towards the main body 22 with respect to a floor surface upon which the vacuum cleaner 10 is located so that the rims of the wheels 24, 26 engage the floor surface. The angle of the inclination of the rotational axes of the wheels 24, 26 is preferably in the range from 4 to 15°, more preferably in the range from 5 to 10° to minimize point contact with a floor surface.

Each of the wheels 24, 26 of the rolling assembly 20 is generally dome-shaped. Each wheel 24, 26 comprises an outer wheel member 220 and an inner wheel member 222 connected to the outer member 220 about the periphery thereof. The outer wheel member 220 and the inner wheel member 222 are preferably connected together using a spin welding technique. A plurality of annular connections is preferably made between the wheel members 220, 222. In this example, the wheel members 220, 222 are joined together at three different positions P₁, P₂ and P₃, each of which is illustrated in FIG. 8. Position P₁ is located at or

towards the outer rims of the wheel members **220**, **222**, position P_3 is located at or towards the center of the wheel members **220**, **222**, and position P_2 is located generally midway between positions P_1 and P_3 . The inner surface of the outer wheel member **220** and the outer surface of the inner wheel member **222** comprise interengaging features located at each of these positions. For example, one of the wheel members **220**, **222** may comprise a series of circular grooves each for received a respective raised circular bands formed on the other wheel member **220**, **222**.

The wheel members **220**, **222** are formed from a relatively stiff material, preferably from a plastics material. For example, each of the wheels members **220**, **222** is preferably formed from a glass-filled polypropylene, preferably a 30% glass-filled polypropylene. Alternatively, the wheels members **220**, **222** may be formed from different plastics material. For example, the outer wheel member **220** may be formed from a 20% glass-filled polypropylene.

The inner wheel member **222** is shaped so as to maintain the outer wheel member **220** in a state of tension. This can make the outer surface of the wheels **24**, **26** relatively stiff, thereby making the wheels **24**, **26** less prone to deformation, for example due to impact with objects during a cleaning process.

The inner wheel member **222** comprises an annular bearing arrangement **224** for rotatably supporting the wheel **24**, **26** on its axle **216**, **218**. During assembly, the wheels **24**, **26** are located over their respective axles **216**, **218**, and a fastener **226** is connected over the bearing arrangement **224** to retain the wheel **24**, **26** on its axle **216**, **218**.

The rolling assembly **20** houses a motor-driven fan unit **228**, a cable rewind assembly **230** for retracting and storing within the main body **22** a portion of an electrical cable (not shown) terminating in a plug **232** providing electrical power to, inter alia, the motor of the fan unit **228**, and at least one filter assembly **234**. The fan unit **228** comprises a motor, and an impeller driven by the motor to draw the dirt-bearing fluid flow into and through the vacuum cleaner **10**. The fan unit **228** is housed in a motor bucket **236**. The motor bucket **236** is connected to the lower section **214** of the main body **22** so that the fan unit **228** does not rotate as the vacuum cleaner **10** is maneuvered over a floor surface. In this example, the filter assembly **234** is located downstream of the fan unit **228**. The filter assembly **234** is cuff shaped and located around a part of the motor bucket **236**. A plurality of perforations is formed in a portion of the motor bucket **236** which is surrounded by the filter assembly **234** to allow air to pass from the motor bucket **236** to the filter assembly **234**.

The filter assembly **234** may be periodically removed from the rolling assembly **20** to allow the filter assembly **234** to be cleaned. The filter assembly **234** is accessed by removing the wheel **26** of the rolling assembly **20**. This wheel **26** may be removed, for example, by the user first removing the fastener **226**, and then pulling the wheel **26** from the axle **218**. The filter assembly **234** may then be removed from the rolling assembly **20** by depressing a catch connecting the filter assembly **234** to the motor bucket **236**, and pulling the filter assembly **234** from the rolling assembly **20**.

The main body **22** of the rolling assembly **20** further comprises a motor inlet duct **238** for conveying a fluid flow received from the outlet duct **30** to the motor bucket **236**.

The motor inlet duct **238** is connected to the upper section **212** of the body **22** of the rolling assembly **20**, and has a fluid inlet **240** and a fluid outlet **242**. The cable rewind assembly **230** is mounted on the side of the motor inlet duct **238** which is opposite to the fluid outlet **242**. An annular seal **244** may

be provided between the motor bucket **236** and the motor inlet duct **238**. The fan unit **228** comprises a series of exhaust ducts **246** located around the outer circumference of the fan unit **228**. In the preferred embodiment a plurality of exhaust apertures **246** are arranged around the fan unit **228** and provide communication between the fan unit **228** and the motor bucket **236**.

The main body **22** further comprises an air exhaust port for exhausting cleaned air from the vacuum cleaner **10**. The exhaust port is formed towards the rear of the main body **22**. In the preferred embodiment the exhaust port comprises a number of orifices **248** located in a lower section **214** of the main body **22**, and which are located so as to present minimum environmental turbulence outside of the vacuum cleaner **10**.

A first user-operable switch **250** is provided on the main body and is arranged so that, when it is depressed, the fan unit **228** is energized. The fan unit **228** may also be de-energized by depressing this first switch **250**. A second user-operable switch **252** is provided adjacent the first switch **250**. The second switch **252** enables a user to activate the cable rewind assembly **230**. Circuitry **254** for driving the fan unit **228**, cable rewind assembly **230** and other auxiliary components of the vacuum cleaner **10** is also housed within the rolling assembly **20**.

In use, the fan unit **228** is activated by the user pressing the switch **250**, and a dirt-bearing fluid flow is drawn into the vacuum cleaner **10** through the suction opening in the cleaner head. The dirt-bearing air passes through the hose and wand assembly, and enters the inlet duct **28**. The dirt-bearing air passes through the inlet duct **28** and enters the dirty air inlet **108** of the separating apparatus **12**. Due to the tangential arrangement of the dirty air inlet **108**, the fluid flow follows a helical path relative to the outer wall **16**. Larger dirt and dust particles are deposited by cyclonic action in the annular chamber **130** and collected therein.

The partially-cleaned fluid flow exits the annular chamber **130** via the apertures in the shroud and enters the plenum chamber **158**. From there, the fluid flow enters the twelve cyclones **146**, wherein further cyclonic separation removes some of the dirt and dust still entrained within the fluid flow. This dirt and dust is deposited in the dust collector **122** while the cleaned air exits the cyclones **146** via the vortex finders **164** and enters the manifold fingers **166**. The fluid flow then passes into the filter housing **154** through the apertures **170**. Within the filter housing **154**, the air flow flows through the filter **184** of the filter assembly **180**. The support provided by the spokes **188** and fins **190** of the filter body **182** prevents the filter **184** from collapsing as the air flow passes through the filter **184**. The air flow subsequently passes axially through the filter body **182** to be exhausted through the air outlet **202** of the filter assembly **180** and into the dome-shaped air inlet **200** of the outlet duct **30**.

The air flow passes through the outlet duct **30**, and enters the main body **22** of the rolling assembly **20** through the fluid inlet **240** of the motor inlet duct **238**. The motor inlet duct **238** guides the fluid flow into the fan unit **228**. The fluid flow is subsequently exhausted through the exhaust apertures **246** in the side of the fan unit **228** and into the motor bucket **236**. The fluid flow leaves the motor bucket **236** through the perforations and passes through the filter assembly **234**. Finally the fluid flow follows the curvature of the main body **22** to the orifices **248** in the main body **22**, from which the cleaned fluid flow is ejected from the vacuum cleaner **10**.

Through use, the filter assembly **180** can become clogged, causing a reduction in the filtration efficiency, and so the

15

filter assembly **180** will require periodic cleaning or replacement. In the preferred embodiment the filter assembly **180** is capable of being cleaned by washing. The filter assembly **180** can be accessed by the user for cleaning when the outlet duct **30** is in its raised position. The user removes the filter assembly **180** from the separating apparatus **12** by gripping one of the spokes **188** of the filter body **182**, and pulling the filter assembly **180** from the filter housing **154**. The filter assembly **180** can be washed by rinsing under a household tap and allowed to dry. The filter assembly **180** is then re-inserted into the filter housing **154** of the separating apparatus **12**, the outlet duct **30** is moved to its lowered position and use of the vacuum cleaner **10** can continue.

When the outlet duct **30** is in its raised position, the separating apparatus **12** may be removed from the vacuum cleaner **10** for emptying and cleaning. The separating apparatus **12** comprises a handle **250** for facilitating the removal of the separating apparatus **12** from the vacuum cleaner **10**. The handle **250** is connected to the upper section **160** of the exhaust manifold **122**, for example by a screw or a snap-fit connection. To empty the separating apparatus **12**, the user depresses a button **252** located on the upper section **160** of the exhaust manifold for actuating a mechanism for applying a downward pressure to the uppermost portion of the catch on the base **18**. This causes the catch to deform and disengage from the groove located on the outer wall **16** of the outer bin **14**. This enables the base **18** to move away from the outer wall **16** to allow dirt and dust that has been collected in the separating apparatus **12** to be emptied into a dustbin or other receptacle. The mechanism for applying the force to the catch preferably comprises a series of push rods which are moved towards the catch in response to the depression of the button **252**. The arrangement of push rods allows the outer bin **14** to be separated from the cyclone pack **140**.

The invention claimed is:

1. A canister type cleaning appliance comprising:
 - a separating apparatus for separating dirt from a dirt-bearing fluid flow;
 - a floor engaging rolling assembly comprising a fan enclosed within the floor engaging rolling assembly for drawing the fluid flow through the separating apparatus;
 - a chassis connected to the rolling assembly; and
 - a duct comprising an outlet section releasably connected to the rolling assembly for conveying the fluid flow to the separating apparatus such that the fluid flow flows in a fluid flow direction from the outlet section toward the separating apparatus, and an inlet section connected to the chassis for pivoting movement relative to the outlet section and the chassis as the cleaning appliance is maneuvered over a floor surface during a cleaning operation,
 wherein the outlet section is located external to the rolling assembly, the separating apparatus is located external to the rolling assembly, the outlet section is located between the separating apparatus and the rolling assembly during the cleaning operation, and the fluid flow flowing through the cleaning appliance during the cleaning operation flows through the inlet section, then through the outlet section, then through the separating apparatus, and then through the rolling assembly.

16

2. The cleaning appliance of claim 1, wherein the rolling assembly comprises a main body connected to the chassis, and a plurality of floor engaging rolling elements.

3. The cleaning appliance of claim 2, wherein the main body and the rolling elements together define a substantially spherical rolling assembly.

4. The cleaning appliance of claim 2, wherein each of the plurality of rolling elements has an outer surface of substantially spherical curvature.

5. The cleaning appliance of claim 2, wherein the rotational axes of the rolling elements are inclined upwardly towards the main body with respect to a floor surface upon which the cleaning appliance is located.

6. The cleaning appliance of claim 2, wherein the outlet section of the duct is releasably connected to the main body of the rolling assembly.

7. The cleaning appliance of claim 2, wherein the outlet section of the duct comprises a manually operable catch for releasably engaging the main body of the rolling assembly.

8. The cleaning appliance of claim 1, wherein the separating apparatus comprises cyclonic separating apparatus.

9. The cleaning appliance of claim 1, comprising a support for supporting the separating apparatus.

10. The cleaning appliance of claim 9, wherein the support comprises a spigot locatable within a recess formed in a base member of the separating apparatus.

11. The cleaning appliance of claim 9, wherein the duct passes through a sleeve located between the support and the main body.

12. The cleaning appliance of claim 11, wherein the inlet section is located on the opposite side of the sleeve to the outlet section.

13. The cleaning appliance of claim 9, wherein the inlet section of the duct extends beneath the support.

14. The cleaning appliance of claim 1, comprising a plurality of floor engaging support members connected to the chassis for supporting the rolling assembly as it is maneuvered over a floor surface.

15. The cleaning appliance of claim 14, wherein each support member comprises a wheel.

16. The cleaning appliance of claim 1, wherein the rolling assembly comprises a filter for removing particulates from the fluid flow.

17. The cleaning appliance of claim 1, comprising an outlet duct extending from the separating apparatus to the rolling assembly for conveying the fluid flow to the rolling assembly.

18. The cleaning appliance of claim 17, wherein the outlet duct is detachable from the separating apparatus to allow the separating apparatus to be removed from the cleaning appliance.

19. The cleaning appliance of claim 17, wherein the outlet duct comprises a handle.

20. The cleaning appliance of claim 17, wherein the outlet duct is pivotably connected to the rolling assembly.

21. The cleaning appliance of claim 1, wherein the inlet section is movable relative to the chassis and the outlet section is fixed relative to the chassis.

22. The cleaning appliance of claim 1, wherein the outlet section of the duct is shaped to change the direction in which air passes therethrough.

* * * * *