



US009981713B2

(12) **United States Patent**
Tsai

(10) **Patent No.:** **US 9,981,713 B2**
(45) **Date of Patent:** **May 29, 2018**

(54) **SUSPENSION DEVICE FOR BICYCLE FRONT FORK**

7,011,325 B2 * 3/2006 Kinzler B62K 21/20
188/322.15

(71) Applicant: **Taiwan Hodaka Industrial Co., Ltd.**,
Taipei (TW)

8,181,978 B2 * 5/2012 Kinzler B62K 25/08
280/276

8,499,905 B2 8/2013 Uchiyama et al.

(72) Inventor: **Black Tsai**, Taipei (TW)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Taiwan Hodaka Industrial Co., Ltd.**,
Taipei (TW)

CN 2367529 Y 3/2000

CN 201082744 Y 7/2008

CN 201283982 Y 8/2009

CN 203519242 U 4/2014

CN 105041957 A 11/2015

CN 204756711 U 11/2015

CN 206317954 U * 7/2017

TW 327873 U 3/1998

TW 584115 U 4/2004

TW M440254 U 11/2012

TW I385094 B 2/2013

TW I589481 B 7/2017

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days. days.

(21) Appl. No.: **15/334,370**

(22) Filed: **Oct. 26, 2016**

(65) **Prior Publication Data**

* cited by examiner

US 2018/0111657 A1 Apr. 26, 2018

Primary Examiner — Kevin Hurley

(51) **Int. Cl.**
B62K 25/08 (2006.01)
F16F 7/08 (2006.01)
B62K 21/20 (2006.01)

(74) *Attorney, Agent, or Firm* — Alan D. Kamrath;
Kamrath IP Lawfirm, P.A.

(52) **U.S. Cl.**
CPC **B62K 25/08** (2013.01); **B62K 21/20**
(2013.01); **F16F 7/082** (2013.01); **B62K**
2201/04 (2013.01)

(57) **ABSTRACT**

(58) **Field of Classification Search**
CPC B62K 21/20; B62K 25/04; B62K 25/06;
B62K 25/08
See application file for complete search history.


A suspension device of a bicycle front fork is installed in a head tube of a bicycle handlebar. The suspension device includes: a cylinder with a bottom fixed to a base of the bicycle front fork and a top passed into the head tube; a piston rod with a top fixed to an inner wall of the head tube and a bottom having a piston and extended into the cylinder; a spring device coupled to the piston rod and having a force to push the piston rod away from the cylinder. The cylinder below the piston has an air chamber communicated with an intake valve of the base. The air pressure of air chamber may be adjusted to adjust the buffering pressure of the spring device, so that a user may adjust the shocking pressure of the front fork.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,553,769 A 11/1985 Kawaguchi
5,494,302 A * 2/1996 Farris B62K 21/20
280/276

10 Claims, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

1

SUSPENSION DEVICE FOR BICYCLE FRONT FORK

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a suspension device of a bicycle front fork, and more particularly to the suspension device capable of adjusting the shock pressure of the bicycle front fork.

Description of the Related Art

In general, a conventional suspension device of a bicycle front fork is installed in a head tube of a bicycle handlebar. The suspension device comprises: a cylinder with a bottom coupled to a base of the bicycle front fork and a top passed into the head tube; a piston rod with a top coupled to an inner wall of the head tube and a bottom having a piston and extended into the cylinder; a spring device with a top coupled to the top of the piston rod and a bottom coupled to the cylinder and capable of providing a force to push the head tube and the piston rod upward. The shock absorption and buffering pressure of the suspension device of the bicycle front fork depends entirely on the coefficient of elasticity of the spring device. As long as a bicycle manufacturer has selected a buffering device with a coefficient of elasticity, the shock absorption and buffering pressure of the front fork are fixed, and users cannot make adjustments anymore. Unless the spring device is replaced, the preload pressure of the buffering device is set in the manufacturing process. Therefore, the conventional suspension device cannot meet various different shock absorption requirements. In view of the drawbacks of the conventional suspension device, the inventor of the present invention conducted extensive researches and experiments, and finally developed a suspension device of the present invention to overcome the drawbacks of the prior art.

SUMMARY OF THE INVENTION

Therefore, it is a primary objective of the present invention to provide a suspension device of a bicycle front fork capable of adjusting the shock preload of a bicycle front fork.

To achieve the aforementioned and other objectives, the present invention discloses a suspension device of a bicycle front fork, and the suspension device comprises: an air chamber disposed in a cylinder below a piston and communicated with an intake valve of a base. The air pressure of the air chamber may be adjusted to adjust the buffering pressure of the spring device, so that a user may adjust the shock pressure of the front fork.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a suspension device of a bicycle front fork installed in a head tube of the front fork in accordance with an embodiment of the present invention;

FIG. 2 is a front cross-sectional view of a suspension device of a bicycle front fork installed in a head tube of the front fork in accordance with an embodiment of the present invention;

FIG. 3 is a side cross-sectional view of a suspension device of a bicycle front fork installed in a head tube of the front fork in accordance with an embodiment of the present invention;

2

FIG. 4 is a partial blowup view of FIG. 2;

FIG. 5 is a partial cross-sectional exploded view of a suspension device of a bicycle front fork in accordance with an embodiment of the present invention;

FIG. 6 is a partial blowup view of FIG. 3;

FIG. 7 is a schematic view of a suspension device of a bicycle front fork with air filled in an air chamber in accordance with an embodiment of the present invention; and

FIG. 8 is a schematic view of a suspension device of a bicycle front fork with more air filled in an air chamber in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The technical characteristics, contents, advantages and effects of the present invention will be apparent with the detailed description of a preferred embodiment accompanied with related drawings as follows.

With reference to FIGS. 1 to 5 for a suspension device 1 of a bicycle front fork in accordance with an embodiment of the present invention, the suspension device 1 comprises: a cylinder 10 with a bottom fixed to a base 30 disposed above the bicycle front fork 3 and a top passed into a head tube 2; a piston rod 11 with a top having a coupling seat 111 coupled to an inner wall of the head tube 2, such that the piston rod 11 is integrally linked with the head tube 2 and a bottom extended into the cylinder 10; a spring device 12 with a top fixed to the piston rod 11 and a bottom coupled to the cylinder 10 and having a force for pushing the head tube 2 and the piston rod 11 upward; and a buffer seat 13 with an elasticity and sheathed on the piston rod 11 and disposed between the piston 110 and a limiting wall 100 protruded inwardly from the inner wall of the cylinder 10. The cylinder 10 below the piston 110 has an air chamber 14, and the air chamber 14 is communicated with an intake valve 31 of the base 30, so that the air pressure inside the air chamber 14 can be adjusted.

In FIGS. 2, 3 and 5, the base 30 has an intake pipe 32 disposed therein and extended from an air inlet of the intake valve 31 into the air chamber 14.

In FIGS. 4 to 6, the suspension device 1 has a sleeve 11A disposed therein and sheathed between the outer wall above the cylinder 10 and the head tube 2 for limiting the head tube 2 to move just in the axial direction. The cylindrical surface of the sleeve 11A has a plurality of slots 11B spaced from one another and having a lengthwise opening in an axial direction, and each slot 11B has a ball 11C embedded therein. The outer wall of the cylinder 10 has a plurality of spaced and axially arranged chutes 101, and the ball 11C of the sleeve 11A is embedded into the respective chute 101.

In FIGS. 4 to 6, the spring device 12 is comprised of a first spring 120 and a second spring 121. The first spring 120 is longer than the second spring 121, and the first spring 120 is installed in the second spring 121, and each of the first and second springs 120 121 has a top fixed to the coupling seat 111 and a bottom coupled to a fixed position of the cylinder 10 and provides a force to push the head tube 2 and the piston rod 11 upward.

In FIGS. 4 to 6, the suspension device 1 has a connecting seat 15 sheathed on the piston rod 11 and disposed at the top of the limiting wall 100, and the top of the connecting seat 15 is provided for touching the bottom of the first spring 120.

In FIGS. 4 to 6, the suspension device 1 has a positioning seat 16 sheathed on the piston rod 11 and disposed at the bottom of the limiting wall 100 and limited by the limiting

3

wall **100** from moving towards the top of the limiting wall **100**. The bottom of the positioning seat **16** is attached to the top of the buffer seat **13**.

In an application, if the air chamber **14** is not filled with air, the spring device **12** (including the first spring **120** and the second spring **121**) has an elastic stretch length L (as shown in FIG. 6). If air is filled into the air chamber **14** from the intake valve **31**, the air pressure inside the air chamber **14** will push the piston **110** to compress the buffer seat **13** to slide upward, so that the piston rod **11** and head tube **2** will move upward, and the spring device **12** (including the first spring **120** and the second spring **121**) has an elastic stretch length L_1 (as shown in FIG. 7), and the elastic stretch length L_1 is longer than the elastic stretch length L (as shown in FIG. 6), so as to adjust the shock pressure of the spring device **12**.

In FIG. 8, if more air is filled into the air chamber **14**, the air pressure inside the air chamber **14** will be increased to push the piston **110** to compress the buffer seat **13** with a large force, so that the buffer seat **13** will be deformed, and the piston rod **11** and the head tube **2** will move further upward. Since the first spring **120** and the second spring **121** are pulled and stretched further, the elastic stretch length L_2 will be longer and the suspension stroke of the suspension device **1** will become longer.

Therefore, air may be filled into the air chamber, and the preload of the suspension device **1** may be adjusted by a bicycle rider, and the buffering pressure may be adjusted according to individual requirement.

In summation of the description above, the present invention complies with the patent application requirements, and thus is duly filed for patent application. While the invention has been described by means of specific embodiments, numerous modifications and variations could be made thereto by those skilled in the art without departing from the scope and spirit of the invention set forth in the claims.

What is claimed is:

1. A suspension device of a bicycle front fork, comprising:
 - a cylinder with a bottom fixed to a base of the bicycle front fork and a top passing into a head tube of the bicycle;
 - a piston rod, with a top coupled to a position of an inner wall of the head tube and a bottom having a piston extending into the cylinder;
 - a spring device, installed between the piston rod and the cylinder, and capable of providing a force to push the head tube and the piston rod upward;
 - a buffer seat, sheathed on the piston rod, and disposed between the piston and a limiting wall inside the cylinder; and
 - an air chamber, disposed in the cylinder below the piston, and communicated with an intake valve on the base.

4

2. The suspension device of a bicycle front fork according to claim 1, wherein the base contains an intake pipe disposed therein and extended from an air inlet of the intake valve to the air chamber.

3. The suspension device of a bicycle front fork according to claim 1, further comprising a sleeve passed and sheathed between an outer wall of the cylinder and the head tube, and an outer wall of the sleeve having a plurality of spaced slots with a lengthwise opening arranged in an axial direction, and each slot having a ball embedded therein, and an outer wall at the top of the cylinder having a plurality of spaced and axially arranged chutes, and the ball of the sleeve being embedded in each respective chute.

4. The suspension device of a bicycle front fork according to claim 2, further comprising a sleeve passed and sheathed between an outer wall of the cylinder and the head tube, and an outer wall of the sleeve having a plurality of spaced slots with a lengthwise opening arranged in an axial direction, and each slot having a ball embedded therein, and an outer wall at the top of the cylinder having a plurality of spaced and axially arranged chutes, and the ball of the sleeve being embedded in each respective chute.

5. The suspension device of a bicycle front fork according to claim 3, wherein the spring device is comprised of a first spring and a second spring, and the first spring is longer than the second spring, and the first spring is installed in the second spring, and the first and second springs have a top fixed to the piston rod and a bottom contacted with the cylinder.

6. The suspension device of a bicycle front fork according to claim 4, wherein the spring device is comprised of a first spring and a second spring, and the first spring is longer than the second spring, and the first spring is installed in the second spring, and the first and second springs have a top fixed to the piston rod and a bottom contacted with the cylinder.

7. The suspension device of a bicycle front fork according to claim 5, further comprising a connecting seat sheathed on the piston rod and disposed above the limiting wall, and the top of the connecting seat being coupled to the first spring.

8. The suspension device of a bicycle front fork according to claim 6, further comprising a connecting seat sheathed on the piston rod and disposed above the limiting wall, and the top of the connecting seat being coupled to the first spring.

9. The suspension device of a bicycle front fork according to claim 5, further comprising a positioning seat sheathed on the piston rod and disposed below the limiting wall, and the bottom of the positioning seat being attached to the top of the buffer seat.

10. The suspension device of a bicycle front fork according to claim 6, further comprising a positioning seat sheathed on the piston rod and disposed below the limiting wall, and the bottom of the positioning seat being attached to the top of the buffer seat.

* * * * *