

US009990278B2

(12) **United States Patent**  
**Okada et al.**

(10) **Patent No.:** **US 9,990,278 B2**  
(45) **Date of Patent:** **Jun. 5, 2018**

(54) **OVERLAID ERASE BLOCK MAPPING**

(71) Applicant: **Cypress Semiconductor Corporation**,  
San Jose, CA (US)

(72) Inventors: **Shinsuke Okada**, Kawasaki (JP);  
**Sunil Atri**, Cupertino, CA (US);  
**Hiroyuki Saito**, Kawasaki (JP)

(73) Assignee: **Cypress Semiconductor Corporation**,  
San Jose, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 206 days.

(21) Appl. No.: **14/518,560**

(22) Filed: **Oct. 20, 2014**

(65) **Prior Publication Data**

US 2016/0110282 A1 Apr. 21, 2016

(51) **Int. Cl.**  
**G06F 12/02** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G06F 12/0246** (2013.01)

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

8,028,120 B2 9/2011 Mo et al.  
8,566,510 B2 10/2013 Weingarten  
2004/0019761 A1\* 1/2004 Fukuzumi ..... G06F 12/0246  
711/202  
2009/0204651 A1\* 8/2009 Rhoads ..... G06F 9/441

2010/0180167 A1\* 7/2010 Takasu ..... G06F 11/1004  
714/718  
2014/0181376 A1\* 6/2014 Miyamoto ..... G06F 12/0246  
711/103  
2014/0281151 A1 9/2014 Yu et al.

**OTHER PUBLICATIONS**

International Search Report of the International Searching Authority  
for International Application No. PCT/US15/55112 dated Jan. 7,  
2016; 2 pages.

Written Opinion of the International Searching Authority for Inter-  
national Application No. PCT/US15/55112 dated Jan. 7, 2016; 4  
pages.

\* cited by examiner


*Primary Examiner* — Sean D Rossiter

*Assistant Examiner* — Charles J Choi

(57) **ABSTRACT**

An overlaid erase block (EB) mapping scheme for a flash  
memory provides efficient wear-leveling and reduces mount  
operation latency. The overlaid EB mapping scheme maps a  
first type of EB onto one of a plurality of physical erase  
blocks, in a corresponding portion of the flash memory. The  
first type of EB includes a plurality of pointers. The overlaid  
EB mapping scheme also maps each of second and third  
types of EBs onto one of the physical EBs that is not mapped  
to the first type of EB. The second type of EBs store system  
management information and the third type of EBs store  
user data. When the flash memory is started up, the overlaid  
EB mapping scheme scans the corresponding portion to  
locate the first type of EB, locates the system EBs using the  
pointers, and locates the data EBs using the system man-  
agement information.

**17 Claims, 13 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

700




FIG. 7






FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13

**OVERLAID ERASE BLOCK MAPPING**

## BACKGROUND

Flash memory retains information stored therein without power, and thus is considered “non-volatile” memory. As such, flash memory has become increasingly popular for many types of devices including, for example, removable storage devices and mobile computing devices. Unlike other non-volatile memories that are one-time programmable (OTP), flash memories may be overwritten. Data may be stored in flash memory by erasing one or more blocks of memory cells therein and then writing to one or more memory cells within a block. The blocks of memory cells are usually referred to as erase blocks (EBs). The process of programming and erasing an erase block (EB) is referred to as a program/erase (P/E) cycle. Some characteristics of flash memory tend to degrade as EBs experience more P/E cycles. For example, the flash memory may not be able to store data for an infinitely long period of time without power. Moreover, the flash memory’s programming and erasing characteristics may also degrade. The lifetime of a flash memory is therefore limited by a maximum number of P/E cycles experienced by each EB.

To prolong the lifetime of a flash memory, a flash file system (FFS) with an EB mapping scheme may be employed. One of the functions of the EB mapping scheme is to perform a technique known as wear-leveling (WL), wherein logical EBs are mapped onto physical EBs. In particular, frequently-written logical EBs are mapped onto physical EBs with low P/E cycles, and infrequently-written logical EBs are mapped onto physical EBs with high P/E cycles. The EB mapping scheme strives to distribute the P/E cycles evenly across the physical EBs, such that no EB fails prematurely. Different EB mapping schemes result in different WL efficiencies, wherein the WL efficiency may be considered as the uniformness of the P/E cycles distribution across the physical EBs.

Another function of an EB mapping scheme is to define how user data and system management information are allocated among and stored into the EBs. Among other things, the system management information keeps track of the physical location of user data in the flash memory. EBs that store user data may be referred to as data EBs. EBs that store system management information may be referred to as system EBs. The allocation of data EBs and system EBs dictates a mount latency of a mount operation of the FFS, affecting the boot time of the flash memory. When the flash memory starts up, the mount operation usually comprises locating the system EBs, which in turn point to the data EBs, such that user data can be made available to the user. The mount latency is the time taken to complete the mount operation.

## SUMMARY

Provided herein are method, system and computer program product embodiments, and/or combinations and sub-combinations thereof, for improving the endurance of a flash memory by providing efficient wear-leveling (WL), and enhancing the boot performance of the flash memory by reducing mount latency.

An embodiment includes an erase block (EB) mapping method for a flash memory, which includes a plurality of physical EBs. A super system EB, which includes a plurality of pointers, is mapped onto one of the physical EBs in a corresponding portion of the flash memory. Each of a

plurality of system EBs and data EBs are mapped onto one of the physical EBs that is not mapped to the super system EB. The system EBs store system management information and the data EBs store user data. When the flash memory is started up, the corresponding portion is scanned to locate the super system EB. The system EBs are subsequently located using the pointers, and the data EBs are located using the system management information. One or more reserved EBs are also mapped onto the physical EBs. Each of the reserved EBs is an empty physical EB used for reclaiming a super system EB, a system EB or a data EB. If no reserved EB is available within the corresponding portion to reclaim the super system EB, either a system EB or a data EB is first reclaimed to generate a reserved EB within the corresponding portion.

Another embodiment includes a system with a flash memory and an EB mapping module. The flash memory includes a plurality of physical EBs. The EB mapping module maps a super system EB, which includes a plurality of pointers, onto one of the physical EBs in a corresponding portion of the flash memory. The EB mapping module maps each of a plurality of system EBs and data EBs onto one of the physical EBs that is not mapped to the super system EB. The system EBs store system management information and the data EBs store user data. When the flash memory is started up, the EB mapping module scans the corresponding portion to locate the super system EB. Subsequently, the EB mapping module locates the system EBs using the pointers and the data EBs using the system management information. The EB mapping module also maps one or more reserved EBs onto the physical EBs. Each of the reserved EBs is an empty physical EB used for reclaiming a super system EB, a system EB or a data EB. If no reserved EB is available within the corresponding portion of the flash memory to reclaim the super system EB, the EB mapping module first reclaims either a system EB or a data EB to generate a reserved EB within the corresponding portion.

A further embodiment includes a tangible computer-readable device having instructions stored thereon that, when executed by at least one computing device, cause the computing device to perform EB mapping operations. The EB mapping operations map a super system EB, which includes a plurality of pointers, onto one of a plurality of physical EBs in a corresponding portion of the flash memory. The EB mapping operations map each of a plurality of system EBs and data EBs onto one of the physical EBs that is not mapped to the super system EB. The system EBs store system management information and the data EBs store user data. When the flash memory is started up, the EB mapping operations scan the corresponding portion to locate the super system EB. Subsequently, the EB mapping operations locate the system EBs using the pointers and the data EBs using the system management information. The EB mapping operations also map one or more reserved EBs onto the physical EBs. Each of the reserved EBs is an empty physical EB used for reclaiming a super system EB, a system EB or a data EB. If no reserved EB is available within the corresponding portion to reclaim the super system EB, the EB mapping operations first reclaim either a system EB or a data EB to generate a reserved EB within the corresponding portion.

Further features and advantages of the invention, as well as the structure and operation of various embodiments of the invention, are described in detail below with reference to the accompanying drawings. It is noted that the invention is not limited to the specific embodiments described herein. Such embodiments are presented herein for illustrative purposes

only. Additional embodiments will be apparent to persons skilled in the relevant art(s) based on the teachings contained herein.

### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated herein and form part of the specification, illustrate the present invention and, together with the description, further serve to explain the principles of the invention and to enable a person skilled in the relevant art(s) to make and use the invention.

FIG. 1 illustrates an erase block (EB) mapping scheme, according to an example embodiment.

FIG. 2 illustrates EB erase counts and boot time of an EB mapping scheme, according to an example embodiment.

FIG. 3 illustrates an EB mapping scheme, according to an example embodiment.

FIG. 4 illustrates EB erase counts and boot time of an EB mapping scheme, according to an example embodiment.

FIG. 5 illustrates an EB mapping scheme, according to an example embodiment,

FIG. 6 illustrates EB erase counts and boot time of an EB mapping scheme, according to an example embodiment.

FIG. 7 is a representation of an addressing hierarchy of an EB mapping scheme, according to an example embodiment.

FIG. 8 illustrates a garbage collection of a super system EB, according to an example embodiment.

FIG. 9 illustrates a garbage collection of a super system EB, according to an example embodiment.

FIG. 10 illustrates a garbage collection of a super system EB, according, to an example embodiment.

FIG. 11 is a flowchart illustrating an algorithm for garbage collection of a super system EB, according to an example embodiment.

FIG. 12 illustrates a comparison of EB erase counts and mount latencies of multiple EB mapping schemes, according to various embodiments.

FIG. 13 is an example computer system useful for implementing various embodiments.

The features and advantages of the present invention will become more apparent from the detailed description set forth below when taken in conjunction with the drawings, in which like reference characters identify corresponding elements throughout. In the drawings, like reference numbers generally indicate identical, functionally similar, and/or structurally similar elements. The drawing in which an element first appears is indicated by the leftmost digit(s) in the corresponding reference number.

### DETAILED DESCRIPTION

This specification discloses one or more embodiments that incorporate the features of this invention. The disclosed embodiment(s) merely exemplify the invention. The scope of the invention is not limited to the disclosed embodiment(s). The invention is defined by the claims appended hereto.

The embodiment(s) described, and references in the specification to “one embodiment,” “an embodiment,” “an example embodiment,” etc., indicate that the embodiment(s) described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an

embodiment, it is understood that it is within the knowledge of one skilled in the art to effect such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described.

Embodiments of the invention may be implemented in hardware, firmware, software, or any combination thereof. Embodiments of the invention may also be implemented as instructions stored on a machine-readable medium, which may be read and executed by one or more processors. A machine-readable medium may include any mechanism for storing or transmitting information in a form readable by a machine (e.g., a computing device). For example, a machine-readable medium may include read only memory (ROM); random access memory (RAM); magnetic disk storage media; optical storage media; flash memory devices; electrical, optical, acoustical or other forms of propagated signals, and others. Further, firmware, software, routines, instructions may be described herein as performing certain actions. However, it should be appreciated that such descriptions are merely for convenience and that such actions in fact result from computing devices, processors, controllers, or other devices executing the firmware, software, routines, instructions, etc.

#### Split EB Mapping Scheme

According to an embodiment, FIG. 1 illustrates an example of a split erase block (EB) mapping scheme **100**, which may be incorporated into a flash file system (FFS) of a flash memory. Split erase EB mapping scheme **100** may be viewed as a logical mapping **102** or a physical mapping **112**.

Logical mapping **102** depicts an example arrangement of logical data EBs **104**, logical reserved data EBs **106**, logical system is **108** and logical reserved system EBs **110**, where each EB is a block of memory cells. Split EB mapping scheme **100** maps logical data EBs **104** and logical reserved data EBs **106** onto physical data EBs **114**, and logical system EBs **108** and logical reserved system EBs **110** onto physical system EBs **116**.

Physical mapping **112** depicts an example of the resulting arrangement of physical data EBs **114** and physical system EBs **116**. In a flash memory with an FFS using a split EB mapping scheme, physical data EBs **114** and physical system EBs **116** typically occupy dedicated portions of the flash memory and do not share any EB, hence the term “split.” Moreover, although not explicitly shown in FIG. 1, flash memories typically comprise relatively fewer physical system EBs **116**, including reserved system EBs, than data EBs.

Logical data EBs **104** store user data, while logical system EBs store system management information, which, among other things, keeps track of the physical location of user data in the flash memory. In split EB mapping scheme **100**, logical reserved data EBs **106** are empty EBs used for the garbage collection of logical data EBs **104**, where garbage collection is a process of reclaiming memory cells that are no longer in use. During a garbage collection operation, one or more logical data EBs **104** may be reclaimed by transferring valid data within logical data EBs **104** into one or more logical reserved data EBs **106**. Subsequently, the original logical data EBs **104** may be erased (i.e., reclaimed), forming new logical reserved data EBs **106**. Similarly, one or more logical system EBs **108** may be reclaimed by transferring valid data within the logical system EBs **108** into one or more logical reserved system EBs **110**. The original logical system EBs **108** may then be erased, forming new logical reserved system EBs **110**.

In FIG. 2, diagram **200** illustrates example erase counts corresponding to physical data EBs **114** and physical system EBs **116**, after multiple program/erase (P/E) cycles. As shown by arrow **202**, the erase counts for physical system



EBs **116** may be relatively higher than the erase counts for physical data EBs **114**, resulting in undesirable and uneven wear levels between the two portions. In this example, split EB mapping scheme **100** performs wear-leveling (WL) of data EBs and system EBs independently on each portion. In particular, during garbage collection, frequently-written logical data EBs are mapped onto reserved data EBs with low P/E cycles, and infrequently-written logical data EBs are mapped onto reserved data EBs with high P/E cycles. Similarly, frequently-written logical system EBs are mapped onto reserved system EBs with low P/E cycles, and infrequently-written logical system EBs are mapped onto reserved system EBs with high P/E cycles. Given that there is relatively fewer physical system EBs **116**, physical system EBs **116** undergo higher P/E cycles than physical data EBs **114**.

Split EB mapping scheme **100**, however, allows a flash memory to have relatively faster boot time. During a mount operation, only a particular portion of the flash memory needs to be scanned, as indicated by arrow **204**, to locate valid system EBs. Therefore, split EB mapping scheme **100** provides reduced mount latency, but inefficient WL across a flash memory.

#### Unified EB Mapping Scheme

According to an embodiment, FIG. **3** illustrates an example unified EB mapping scheme **300**, which may be viewed as a logical mapping **302** or a physical mapping **312**. Unlike split EB mapping scheme **100**, as shown by logical mapping **302**, unified EB mapping scheme **300** comprises a set of logical common reserved EBs **306**, instead of separate reserved data EBs and reserved system EBs. Logical common reserved EBs **306** may be used for garbage collection of either logical data EBs **304** or logical system EBs **308**. Furthermore, unified EB mapping scheme **300** maps logical data EBs **304**, logical common reserved EBs **306** and logical systems EBs **308** onto any physical EBs **318**. Unlike split EB mapping scheme **100**, unified EB mapping scheme **300** does not include a demarcation between data EBs and system EBs in physical mapping **312**.

In FIG. **4**, diagram **400** illustrates example erase counts for physical EBs **318**. As indicated by arrow **402**, unified EB mapping scheme **300** usually leads to an even wear across all the EBs. The virtually uniform erase counts result from the capability of the unified EB mapping scheme **300** to perform a WL operation across the flash memory, by mapping frequently-written logical system EBs **308** or logical data EBs **304** onto logical common reserved EBs **306** with low erase counts, and infrequently-written logical system EBs **308** or logical data EBs **304** onto logical common reserved EBs **306** with high erase counts.

The shortcoming of unified EB mapping scheme **300**, however, is a relatively slower boot time indicated by arrow **404**. The slower boot time is due to the fact that unified EB mapping scheme **300** needs to scan all the physical EBs **318** to locate valid system EBs during a mount operation. Thus, unified EB mapping scheme **300** provides efficient WL, but lengthy mount latency.

#### Overlaid EB Mapping Scheme

According to an example embodiment, an overlaid EB mapping scheme, which is capable of concurrently providing reduced mount latency and efficient WL, will now be described with respect to FIGS. **5** through **12**.

FIG. **5** is a representation of an example overlaid EB mapping scheme **500**, which is similar to unified EB mapping scheme **300** in FIG. **3**, except that one of the EBs in the flash memory is a modified system EB. This modified system EB is shown as a super system EB **510** in FIG. **5**. As

will be apparent in the description that follows, super system EB **510** allows for a reduction in mount latency. In FIG. **5**, as shown in logical mapping **502**, overlaid EB mapping scheme includes a set of logical common reserved EBs **506**. Overlaid EB mapping scheme **500** may use the common reserved EBs not only for the garbage collection of the data EBs and system EBs, but also for the garbage collection of super system EB **510**. As in unified EB mapping scheme **300**, logical data EBs **504** and logical system EBs **508** may be mapped onto any physical EBs **518**, with the exception that overlaid EB mapping scheme **500** maps super system EB **510** onto a particular portion of the flash memory. In physical mapping **512**, this particular portion is shown as being overlaid onto the physical EBs **518** and accordingly labeled as overlaid EB area **520**.

In FIG. **6**, diagram **600** illustrates example erase counts for physical EBs **518**. Given that overlaid EB mapping scheme **500** may perform a common WL operation across physical EBs **518** using the common reserved EBs, an even wear may be realized, as indicated by arrow **602**. This is similar to unified EB mapping **300**. However, unlike unified EB mapping **300**, overlaid EB mapping scheme **500** may achieve relatively fast boot time, as indicated by arrow **604**. This is because, during a mount operation, overlaid EB mapping scheme **500** only scans overlaid EB area **520** to locate super system EB **510**, which includes multiple pointers **606** pointing to valid system EBs. Pointers **606** may include metadata, which may include, among other things, address information for valid system EBs. Therefore, once super system EB **510** is located, pointers **606** may be used to locate valid system EBs among physical EBs **518**.

FIG. **7** is a depiction of an example addressing hierarchy **700** of overlaid EB mapping scheme **500**. As indicated by arrow **702**, data EBs typically undergo the highest write traffic or P/E cycles, followed respectively by system EBs and the super system EB. When one or more data EBs are erased, only the location information of the newly reclaimed EBs and the new data EBs are recorded within the system EBs. Thus, it takes longer, compared to data EBs, for system EBs to run out of free memory cells. Similarly, when system EBs are erased, the pointers within the super system EB are updated to point to the new system EBs. Consequently, it takes longer, compared to system EBs, for the super system EB to run out of free memory cells. This results in addressing hierarchy **700**.

FIG. **7** also illustrates how an example flash memory typically has relatively fewer system EBs when compared to data EBs. Fewer system EBs implies not only faster boot time, but also more remaining EBs that may be used for data EBs. Thus, a flash memory with fewer system EBs may provide more space for user data. However, fewer system EBs also implies that the system EBs may undergo higher P/E cycles than data EBs. Therefore, manufacturers and users of flash memories usually need to make trade-offs between the number of system EBs and the allocation of data EBs, depending on their desirability for operational speed (i.e., lower number of system EBs and faster boot time) or endurance (i.e., higher number of system EBs and lower P/E cycles).

One skilled in the art would appreciate that, as the storage capacity of a flash memory increases (i.e., the number of erase blocks increases), one super system EB may not be able to store all the information needed to point to all valid system EBs. In such a case, a plurality of super system EBs may be used. The plurality of super system EBs may all be confined to a particular area of the flash memory, similar to overlaid EB area **520** in FIG. **5**. During a mount operation,

the particular area may be scanned to locate all the super system EBs, which point to the valid system

Alternatively, another modified system EB—a super super system EB, for example—may be used to point to the plurality of super system EBs. The super super system EB may be confined to a particular area, while the super system EBs may be located anywhere in the flash memory. During a mount operation, the particular area may be scanned to locate the super super system EB, which points to the super system EBs, which in turn point to the valid system EBs. One skilled in the art would further appreciate that, as the storage capacity of a flash memory increases even more, the tree concept of having one EB pointing to a plurality of EBs may be extended without expanding the area to be scanned during a mount operation.

#### Super System EB Garbage Collection Algorithm

In one example, in an overlaid EB mapping scheme **500**, it is ensured that super system EB **510** is mapped onto overlaid EB area **520**. As a result, garbage collection of super system EB **510** should be carried out according to a specific algorithm. FIGS. **8** through **10** illustrate different example scenarios covered by such an algorithm for performing garbage collection of super system EB **510**.

According to an embodiment, FIG. **8** shows an example garbage collection operation **800** of super system EB **510**. Physical mapping **812** illustrates an example allocation of data EBs, system EBs, common reserved EBs and super system EB **510**, after multiple P/E cycles. In this scenario, overlaid EB area **520** contains super system EB **510** and two common reserved EBs. Super system EB **510** is labeled as “OLD” because, for example, super system EB **510** may be full (i.e., may have run out of free memory cells). At step **822**, garbage collection may be performed by allocating one of the common reserved EBs within overlaid EB area **520** and transferring valid data from the “OLD” super system EB to the allocated common reserved EB. Thus, a “NEW” super system EB is formed and remains within overlaid EB area **520** as required by overlaid EB mapping scheme **500**. At step **824**, the “OLD” super system EB may be erased to form a common reserved EB.

According to an embodiment, FIG. **9** shows another example garbage collection operation **900** of super system EB **510**. Physical mapping **912** illustrates an example allocation of data EBs, system EBs, common reserved EBs and super system EB **510**, after multiple P/E cycles. In this scenario, overlaid EB area **520** contains super system EB **510** and two system EBs. Similar to the scenario in FIG. **8**, for example, super system EB **510** may be full and is labeled “OLD.” However, in this example scenario, there is no common reserved EB within overlaid EB area **520** to readily perform garbage collection of the “OLD” super system EB. One or more common reserved EBs need to be generated first within overlaid EB area **520**. Therefore, at step **922**, one or more common reserved EBs outside of overlaid EB area **520** may be allocated to reclaim one or more of the system EBs that are within overlaid EB area **520**. FIG. **8** shows, but is not limited to, two system EBs being reclaimed. At step **924**, one or more common reserved EBs may then be generated by erasing the reclaimed system EBs. Subsequently, at step **926** one of the newly generated common reserved EBs may be allocated to reclaim the “OLD” super system EB, forming a “NEW” super system EB. At step **928**, the “OLD” super system EB may be erased to form a common reserved EB within overlaid EB area **520**.

According to an embodiment, FIG. **10** shows another example garbage collection operation **1000** of super system EB **510**. Physical mapping, **1012** illustrates an example

allocation of data EBs, system EBs, common reserved EBs and super system EB **510**, after multiple P/E cycles. In this example scenario, overlaid EB area **520** contains super system EB **510** and two data EBs. Similar to the scenario in FIG. **8**, for example, super system EB **510** may be full and is labeled “OLD.” However, in this example scenario, there is no common reserved EB within overlaid EB area **520** to readily perform garbage collection of the “OLD” super system EB. One or more common reserved EBs need to be generated first within overlaid EB area **520**. Therefore, at step **1022**, one or more common reserved EBs outside of overlaid EB area **520** may be allocated to reclaim one or more of the data EBs that are within overlaid EB area **520**. FIG. **10** shows, but is not limited to, one data EB being reclaimed. At step **1024**, one or more common reserved EBs may then be generated by erasing the reclaimed data EBs. Subsequently, at step **1026** one of the newly generated common reserved EBs may be allocated to reclaim the “OLD” super system EB, forming a “NEW” super system EB. At step **1028**, the “OLD” super system EB may be erased to form a common reserved EB within overlaid EB area **520**.

FIG. **11** depicts an algorithm **1100** employed by overlaid EB mapping scheme **500** to perform garbage collection of a super system EB, according to an example embodiment. FIG. **11** shall be described with reference to FIGS. **8** through **10**, but it should be understood that algorithm **1100** is not limited to the example embodiments depicted in FIGS. **8-10**.

As shown in FIG. **11**, algorithm **1100** begins at step **1102** where control passes to step **1104**. At step **1104**, the locations of common reserved EBs are retrieved, in the form of a random access memory (RAM) table for example. At step **1106**, algorithm **1100** determines whether one or more of the common reserved EBs are located within the overlaid EB area, as shown by overlaid EB area **520** in FIGS. **8-10**.

If there is one or more common reserved EBs within the overlaid EB area, algorithm **1100** moves to step **1108**, wherein one of the common reserved EBs is allocated to be the next super system EB. At step **1110**, valid data from the old super system EB is transferred into the next super system EB. Steps **1108** and **1110** correspond to step **822** in FIG. **8**. At step **1112**, the old super system EB is erased to generate a common reserved EB. Step **1112** corresponds to step **824** in FIG. **8**.

If, at step **1106**, it is determined that no common reserved EB is located within the overlaid EB area, algorithm **1100** moves to step **1116**, wherein the locations of system EBs are retrieved, in the form of a RAM table for example. At step **1118**, algorithm **1100** determines whether one or more of the system EBs are located within the overlaid EB area.

If there is one or more system EBs within the overlaid EB area, algorithm **1100** moves to step **1120**. At step **1120**, one or more of the system EBs are reclaimed to generate one or more common reserved EBs within the overlaid EB area. Step **1120** corresponds to steps **922** and **924** in FIG. **9**. Once one or more common reserved EBs are formed within the overlaid EB area, algorithm **1100** performs steps **1108** through **1112** to reclaim the old super system EB.

If, at step **1118**, it is determined that there is no system EB within the overlaid EB area, algorithm **1100** shifts to step **1122**, wherein one or more data EBs within the overlaid EB area are reclaimed to generate one or more common reserved EBs. Step **1122** corresponds to steps **1022** and **1024** in FIG. **10**. Algorithm **1100** then performs steps **1108** through **1112** to reclaim the old super system EB. Algorithm **1100** ends at step **1114**.

## EB Mapping Schemes Comparison

FIG. 12 provides a comparison between split EB mapping scheme 100, unified EB mapping scheme 300 and overlaid EB mapping scheme 500 when applied to, but not limited to, a 64 megabyte (MB) NOR flash memory.

Graph 1200 illustrates erase counts for the three schemes, while bar chart 1202 illustrates their mount latencies. In graph 1200, it can be seen that unified EB mapping scheme 300 and overlaid EB mapping scheme 500 have similar erase counts across the EBs. However, for split EB mapping scheme 100, a portion of the EBs have higher erase counts, as indicated by arrow 1204. This portion of EBs corresponds to system EBs as described previously.

In bar chart 1202, split EB mapping scheme 100 and overlaid EB mapping scheme 500 have similar mount latencies, but unified EB mapping scheme 300 has higher mount latency. As described previously, during a mount operation, split EB mapping scheme 100 and overlaid EB mapping scheme 500 have to scan a smaller portion of EBs to locate valid system EBs, while unified EB mapping scheme 300 has to scan across all EBs to locate the valid system EBs.

This comparison confirms that overlaid EB mapping scheme 500 provides both efficient WL and reduced mount latency. Although this comparison uses a 64 MB NOR flash memory, similar observations may be made for other flash memories, regardless of their storage capacities or types.

## Example Computer System

Various embodiments can be implemented, for example, using one or more well-known computer systems, such as computer system 1300 shown in FIG. 13. Computer system 1300 can be any well-known computer capable of performing the functions described herein, such as computers available from International Business Machines, Apple, Sun, HP, Dell, Sony, Toshiba, etc.

Computer system 1300 includes one or more processors (also called central processing units, or CPUs), such as a processor 1304. Processor 1304 is connected to a communication infrastructure or bus 1306.

One or more processors 1304 may each be a graphics processing unit (GPU). In an embodiment, a GPU is a processor that is a specialized electronic circuit designed to rapidly process mathematically intensive applications on electronic devices. The GPU may have a highly parallel structure that is efficient for parallel processing of large blocks of data, such as mathematically intensive data common to computer graphics applications, images and videos.

Computer system 1300 also includes user input/output device(s) 1303, such as monitors, keyboards, pointing devices, etc., which communicate with communication infrastructure 1306 through user input/output interface(s) 1302.

Computer system 1300 also includes a main or primary memory 1308, such as random access memory (RAM). Main memory 1308 may include one or more levels of cache. Main memory 1308 has stored therein control logic (i.e., computer software) and/or data.

Computer system 1300 may also include one or more secondary storage devices or memory 1310. Secondary memory 1310 may include, for example, a hard disk drive 1312 and/or a removable storage device or drive 1314. Removable storage drive 1314 may be a floppy disk drive, a magnetic tape drive, a compact disk drive, an optical storage device, tape backup device, and/or any other storage device/drive.

Removable storage drive 1314 may interact with a removable storage unit 1318. Removable storage unit 1318 includes a computer usable or readable storage device

having stored thereon computer software (control logic) and/or data. Removable storage unit 1318 may be a floppy disk, magnetic tape, compact disk, DVD, optical storage disk, and/or any other computer data storage device. Removable storage drive 1314 reads from and/or writes to removable storage unit 1318 in a well-known manner.

According to an exemplary embodiment, secondary memory 1310 may include other means, instrumentalities or other approaches for allowing computer programs and/or other instructions and/or data to be accessed by computer system 1300. Such means, instrumentalities or other approaches may include, for example, a removable storage unit 1322 and an interface 1320. Examples of the removable storage unit 1322 and the interface 1320 may include a program cartridge and cartridge interface (such as that found in video game devices), a removable memory chip (such as an EPROM or PROM) and associated socket, a memory stick and USB port, a memory card and associated memory card slot, and/or any other removable storage unit and associated interface.

Computer system 1300 may further include a communication or network interface 1324. Communication interface 1324 enables computer system 1300 to communicate and interact with any combination of remote devices, remote networks, remote entities, etc. (individually and collectively referenced by reference number 1328). For example, communication interface 1324 may allow computer system 1300 to communicate with remote devices 1328 over communications path 1326, which may be wired and/or wireless, and which may include any combination of LANs, WANs, the Internet, etc. Control logic and/or data may be transmitted to and from computer system 1300 via communication path 1326.

In an embodiment, a tangible apparatus or article of manufacture comprising a tangible computer useable or readable medium having control logic (software) stored thereon is also referred to herein as a computer program product or program storage device. This includes, but is not limited to, computer system 1300, main memory 1308, secondary memory 1310, and removable storage units 1318 and 1322, as well as tangible articles of manufacture embodying any combination of the foregoing. Such control logic, when executed by one or more data processing devices (such as computer system 1300), causes such data processing devices to operate as described herein.

Based on the teachings contained in this disclosure, it will be apparent to persons skilled in the relevant art(s) how to make and use the invention using data processing devices, computer systems and/or computer architectures other than that shown in FIG. 13. In particular, embodiments may operate with software, hardware, and/or operating system implementations other than those described herein.

## Conclusion

It is to be appreciated that the Detailed Description section, and not the Summary and Abstract sections (if any), is intended to be used to interpret the claims. The Summary and Abstract sections (if any) may set forth one or more but not all exemplary embodiments of the invention as contemplated by the inventor(s), and thus, are not intended to limit the invention or the appended claims in any way.

While the invention has been described herein with reference to exemplary embodiments for exemplary fields and applications, it should be understood that the invention is not limited thereto. Other embodiments and modifications thereto are possible, and are within the scope and spirit of the invention. For example, and without limiting the generality of this paragraph, embodiments are not limited to the

software, hardware, firmware, and/or entities illustrated in the figures and/or described herein. Further, embodiments (whether or not explicitly described herein) have significant utility to fields and applications beyond the examples described herein.

Embodiments have been described herein with the aid of functional building blocks illustrating the implementation of specified functions and relationships thereof. The boundaries of these functional building blocks have been arbitrarily defined herein for the convenience of the description. Alternate boundaries can be defined as long as the specified functions and relationships (or equivalents thereof) are appropriately performed. Also, alternative embodiments may perform functional blocks, steps, operations, methods, etc. using orderings different than those described herein.

The breadth and scope of the invention should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

What is claimed is:

1. A method comprising:
  - mapping a first type of erase block (EB), which includes a plurality of pointers, onto one of first physical EBs, of a plurality of physical EBs in a memory;
  - mapping each of second type of EBs and third type of EBs onto at least one of the first physical EBs and second physical EBs of the plurality of physical EBs that is not mapped to the first type of EB, the second type of EBs storing system management information and the third type of EBs storing user data;
  - when the memory is started up, locating the first type of EB through scanning the first physical EBs and without scanning the second physical EBs; and
  - reclaiming the first type of EB using one of a fourth type of EBs, wherein the one of the fourth type of EBs is within the first physical EBs.
2. The method of claim 1, further comprising, when the memory is started up:
  - locating the second type of EBs using the pointers; and
  - locating the third type of EBs using the system management information.
3. The method of claim 1, further comprising:
  - mapping the fourth type of EBs onto the physical EBs; wherein each of the fourth type of EBs is an empty physical EB used for reclaiming one of the first type of EB, the second type of EBs and the third type of EBs.
4. The method of claim 3, further comprising, in response to the first type of EB being full and one or more of the fourth type of EBs being mapped within the first physical EBs:
  - allocating the one of the fourth type of EBs mapped within the first physical EBs to reclaim the first type of EB.
5. The method of claim 3, further comprising, in response to the first type of EB being full, no fourth type of EB being mapped within the first physical EBs and one or more second type of EBs being mapped within the first physical EBs:
  - generating one or more of the fourth type of EBs within the first physical EBs by allocating one or more of the fourth type of EBs outside of the first physical EBs to reclaim one or more of the second type of EBs within the first physical EBs; and
  - allocating the one of the fourth type of EBs generated within the first physical EBs to reclaim the first type of EB.

6. The method of claim 3, further comprising, in response to the first type of EB being full and no fourth type of EB and no second type of EB being mapped within the first physical EBs:

- 5 generating one or more of the fourth type of EBs within the first physical EBs by allocating one or more of the fourth type of EBs outside of the first physical EBs to reclaim one or more of the third type of EBs within the first physical EBs; and
- 10 allocating the one of the fourth type of EBs generated within the first physical EBs to reclaim the first type of EB.

7. A system, comprising:

- a memory including a plurality of physical EBs, the plurality of physical EBs including a first plurality of physical EBs and a second plurality of physical EBs; and

one or more data processing devices configured to:

- 20 map a first type of EB, which includes pointers, onto one of the second plurality of physical EBs,
- map each of second and third types of EBs onto one of the the first plurality of physical EBs or the second plurality of physical EBs that is not mapped to the first type of EB, wherein the second type of EBs store system management information, and the third type of EBs store user data;
- locate the first type of EB through a scan of the second plurality of physical EBs, without a scan of the first plurality of physical EBs, when the memory is started up; and
- reclaim the first type of EB using one of a fourth type of EBs, wherein the one of the fourth type of EBs is within the second plurality of physical EBs.

8. The system of claim 7, the one or more data processing devices further configured to, when the memory is started up:

- locate the second type of EBs using the pointers; and
- locate the third type of EBs using the system management information.

9. The system of claim 7, the one or more data processing devices further configured to:

- 40 map the fourth type of EBs onto the physical EBs, wherein each of the fourth type of EBs is an empty physical EB used for reclaiming one of the first type of EB, the second type of EBs and the third type of EBs.

10. The system of claim 9, the one or more data processing devices further configured to, in response to the first type of EB being full and one or more fourth type of EBs being mapped within the second plurality of physical EBs:

- 50 allocate the one of the fourth type of EBs mapped within the second plurality of physical EBs to reclaim the first type of EB.

11. The system of claim 9, the one or more data processing devices further configured to, in response to the first type of EB being full, no fourth type of EB being mapped within the second plurality of physical EBs and one or more second type of EBs being mapped within the second plurality of physical EBs:

- 55 generate one or more of the fourth type of EBs within the second plurality of physical EBs by allocating one or more of the fourth type of EBs outside of the second plurality of physical EBs to reclaim one or more of the second type of EBs within the second plurality of physical EBs; and
- 60 allocate the one of the fourth type of EBs generated within the second plurality of physical EBs to reclaim the first type of EB.

## 13

12. The system of claim 9, the one or more data processing devices further configured to, in response to the first type of EB being full and no fourth type of EB and no second type of EB being mapped within the second plurality of physical EBs:

generate one or more of the fourth type of EBs within the second plurality of physical EBs by allocating one or more of the fourth type of EBs outside of the second plurality of physical EBs to reclaim one or more of the third type of EBs within the second plurality of physical EBs; and

allocate the one of the fourth type of EBs generated within the second plurality of physical EBs to reclaim the first type of EB.

13. A tangible computer-readable device including a plurality of physical EBs and having instructions stored thereon that, when executed by at least one computing device, causes the at least one computing device to perform EB mapping operations comprising:

mapping a first type of EB, which includes pointers, onto one of first physical EBs of the plurality of physical EBs of the tangible computer-readable device;

mapping each of second and third types of EBs onto one of the first physical EBs or to one of second physical EBs of the plurality of physical EBs that is not mapped to the first type of EB, wherein the second type of EBs store system management information, and the third type of EBs store user data;

mapping a fourth type of EBs respectively onto the physical EBs, wherein each of the fourth type of EBs is an empty physical EB used for reclaiming one of the first type of EBs, the third type of EBs and the second type of EBs;

scanning within the first physical EBs, to locate the first type of EB without scanning the second physical EBs, when the computer-readable device is started up; and reclaiming the first type of EB using one of the fourth type of EBs, wherein the one of the fourth type of EBs is within the first physical EBs of the computer-readable device.

## 14

14. The computer-readable device of claim 13, the EB mapping operations further comprising, when the computer-readable device is started up:

locating the second type of EBs using the pointers; and locating the third type of EBs using the system management information.

15. The computer-readable device of claim 13, the EB mapping operations further comprising, in response to the first type of EB being full and one or more fourth type of EBs being mapped within the first physical EBs:

allocating the one of the fourth type of EBs mapped within the corresponding portion to reclaim the first type of EB.

16. The computer-readable device of claim 13, the EB mapping operations further comprising, in response to the first type of EB being full, no fourth type of EB being mapped within the first physical EBs and one or more second type of EBs being mapped within the first physical EBs:

generating one or more of the fourth type of EBs within the first physical EBs by allocating one or more of the fourth type of EBs outside of the first physical EBs to reclaim one or more of the second type of EBs within the first physical EBs; and

allocating the one of the fourth type of EBs generated within the first physical EBs to reclaim the first type of EB.

17. The computer-readable device of claim 13, the EB mapping operations further comprising, in response to the first type of EB being full and no fourth type of EB and no second type of EB being mapped within the first physical EBs:

generating one or more of the fourth type of EBs within the first physical EBs by allocating one or more of the fourth type of EBs outside of the first physical EBs to reclaim one or more of the third type of EBs within the first physical EBs; and

allocating the one of the fourth type of EBs generated within the first physical EBs to reclaim the first type of EB.

\* \* \* \* \*