

(12)

United States Design Patent

Schultz et al.

(10)

Patent No.:

US D1,030,628 S

(45)

Date of Patent:

** Jun. 11, 2024

(54) **TIRE**

(71) Applicant: **Bridgestone Americas Tire Operations, LLC**, Nashville, TN (US)

(72) Inventors: **David E. Schultz**, Stow, OH (US);
Jordan S. Prise, Medina, OH (US);
Seth B. Gale, Kirtland, OH (US);
Keith A. Dumigan, Kent, OH (US);
Zachary A. Sterba, Akron, OH (US);
Ryan W. Billman, Burbank, OH (US)

(73) Assignee: **Bridgestone Americas Tire Operations, LLC**, Nashville, TN (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/866,008**

(22) Filed: **Aug. 24, 2022**

(51) **LOC (14) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/564**

(58) **Field of Classification Search**
USPC D12/533–567, 604, 900, 901
CPC Y10T 152/10027; B60C 1/0016; B60C 11/0306; B60C 11/0302; B60C 3/06
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D432,059 S	*	10/2000	Feider		D12/603
D499,067 S		11/2004	Wage		
D500,472 S		1/2005	Campana et al.		
D501,446 S		2/2005	Wage		
D508,881 S		8/2005	Corbit		
D537,033 S		2/2007	Dumigan et al.		
D585,817 S		2/2009	Frappart		
D646,219 S		10/2011	Suda et al.		
D656,890 S		4/2012	Rittweger		

D661,643 S	*	6/2012	Kaji		D12/602
D677,616 S		3/2013	Nobunaga		
D724,007 S	*	3/2015	Belarbi		D12/564
D738,811 S		9/2015	Drake		
D739,342 S	*	9/2015	Koog		D12/583
D748,571 S	*	2/2016	Kitajima		D12/583
D751,031 S	*	3/2016	Yamamoto		D12/583
D760,641 S		7/2016	Colombo et al.		
D761,720 S	*	7/2016	Hironaka		D12/564
D763,169 S		8/2016	Deng et al.		
D782,405 S		3/2017	De Giacco		
D823,780 S	*	7/2018	Van Miegroet		D12/536
D823,782 S		7/2018	Bortolet et al.		
D832,774 S	*	11/2018	Dieng		D12/553
D837,134 S	*	1/2019	Zivkovic		D12/566
D858,427 S	*	9/2019	Kochanek		D12/583
D859,296 S	*	9/2019	Marlier		D12/566
D873,761 S	*	1/2020	Kubota		D12/564
D882,503 S	*	4/2020	Schultz		D12/598
D886,033 S		6/2020	Kristen		

(Continued)

Primary Examiner — John A Voytek

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a side perspective view of a tire showing our new design, it being understood that the tread pattern is repeated throughout the circumference of the tire, the opposite side being the same as that shown;



FIG. 2 is a front elevational view of the tire;

FIG. 3 is an enlarged fragmentary view of FIG. 2 taken along line 3-3 of FIG. 2; and,

FIG. 4 is a side elevational view of the left side of the tire, the opposite side being the same as that shown.

The broken lines defining the sidewall, inner bead, and the peripheral boundary between the claimed tire tread and the sidewall depict environmental subject matter that forms no part of the claimed design.

1 Claim, 4 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

D886,715	S	6/2020	Sahashi	
D894,112	S	8/2020	Koog et al.	
D934,786	S	11/2021	Kochanek	
D939,428	S *	12/2021	Bosse	D12/564
D957,316	S *	7/2022	Chiusso	D12/583
D996,350	S *	8/2023	Billman	D12/583
D1,015,999	S *	2/2024	Fujioka	D12/548
D1,019,527	S *	3/2024	Lee	D12/548

* cited by examiner





FIG. 1

FIG. 2






FIG. 3




FIG. 4