

(12) **United States Design Patent**
Kolste et al.

(10) Patent No.: **US D1,035,731 S**

(45) Date of Patent: **** Jul. 16, 2024**

(54) **RADIAL BEARING**

(71) Applicant: **US SYNTHETIC CORPORATION,**
Orem, UT (US)

(72) Inventors: **Tyler Kolste,** American Fork, UT (US);
S. Barrett Peterson, Orem, UT (US);
Jair J. Gonzalez, Provo, UT (US);
Trond Pedersen, Bluffdale, UT (US)

(73) Assignee: **US Synthetic Corporation,** Orem, UT
(US)

(**) Term: **15 Years**

(21) Appl. No.: **29/734,635**

(22) Filed: **May 14, 2020**

2200/00; B60G 2200/14; B60G 2200/142;
B60G 2200/17; B60G 2200/46; B60G
2202/12; B60G 2202/135; B60G
2202/152; B60G 2202/24; B60G
2202/242; B60G 2202/31; B60G
2202/312; B60G 2202/314; B60G
2202/412; B60G 2202/413; B60G
2204/1244; B60G 2204/128; B60G
2204/129; B60G 2204/14; B60G
2204/1431; B60G 2204/416; B60G
2204/4302; B60G 2204/44; B60G
2204/61; B60G 2204/82; B60G
2206/0116; B60G 2206/014; B60G
2206/016; B60G 2206/10; B60G 2206/12;
B60G 2206/16; B60G 2206/424; B60G
2206/606; B60G 2206/7101; B60G
2206/7102; B60G 2206/80; B60G
2206/81; B60G 2206/81012; B60G
2206/8102; B60G 2206/811; B60G
2206/82; B60G 2206/8201; B60G
2206/8207; B60G 2206/83; B60G
2206/91; B60G 2300/02; B60G 2300/07;
B60G 2300/122; B60G 2300/124; B60G
2300/13; B60G 2300/402; B60G 2300/45;
B60G 2400/252; B60G 2400/51; B60G
2400/51222; B60G 2400/60; B60G
2401/172; B60G 2500/201; B60G
2800/01; B60G 2800/012; B60G
2800/162; B60G 2800/20; B60G 3/202;
B60G 5/00; B60G 7/00; B60G 7/005

See application file for complete search history.

Related U.S. Application Data

(62) Division of application No. 29/606,740, filed on Jun.
7, 2017, now Pat. No. Des. 888,787.

(51) **LOC (14) Cl.** **15-03**

(52) **U.S. Cl.**
USPC **D15/143**

(58) **Field of Classification Search**
USPC D15/5, 138, 143; D12/400, 159, 161,
D12/206; D8/358, 359, 356; D14/484;
D3/24
CPC B60G 3/20; B60G 2206/122; B60G 7/02;
B60G 2200/156; B60G 2200/18; B60G
2204/143; B60G 7/001; B60G 7/008;
B60G 11/14; B60G 2200/1424; B60G
2200/144; B60G 2200/154; B60G
2204/148; B60G 2204/41; B60G 2500/30;
B60G 3/02; B60G 3/06; B60G 11/27;
B60G 11/48; B60G 13/003; B60G
13/005; B60G 13/16; B60G 15/02; B60G
15/06; B60G 15/062; B60G 15/065;
B60G 15/12; B60G 17/005; B60G
17/0155; B60G 17/016; B60G 17/017;
B60G 17/0272; B60G 17/052; B60G
17/0521; B60G 17/0523; B60G 17/0526;
B60G 21/007; B60G 21/0551; B60G

(56)

References Cited

U.S. PATENT DOCUMENTS

D28,869 S * 6/1898 Perkins D15/143

D258,828 S * 4/1981 Zrobek D15/143

D436,117 S * 1/2001 Chuang D15/143

D443,627 S * 6/2001 West D15/143

D444,802 S * 7/2001 Dyson D15/143

6,338,754 B1 1/2002 Cannon et al.

7,866,418 B2 1/2011 Bertagnolli et al.

8,236,074 B1 8/2012 Bertagnolli et al.

8,545,104 B2 10/2013 Sexton et al.

D699,272 S * 2/2014 Mochizuki D15/143

8,668,388	B1	3/2014	Peterson	
8,746,979	B2	6/2014	Cooley et al.	
8,950,519	B2	2/2015	Gonzalez et al.	
8,995,742	B1	3/2015	Mukhopadhyay et al.	
9,016,405	B2	4/2015	Sexton et al.	
9,062,505	B2	6/2015	Crockett et al.	
9,062,710	B2 *	6/2015	Lee	F16C 19/381
9,315,881	B2	4/2016	Linford et al.	
9,459,236	B2	10/2016	Bertagnolli et al.	
D770,547	S *	11/2016	Yamamoto	D15/143
D772,964	S *	11/2016	Ban	D15/143
D782,180	S *	3/2017	Eberhard	D3/18
9,664,231	B2 *	5/2017	Omoto	F16C 33/56
9,677,617	B2 *	6/2017	Karlsson	F16C 33/6614
D818,508	S *	5/2018	Ban	D15/143
D824,967	S *	8/2018	Getto	D15/143
D830,435	S *	10/2018	Wakisaka	D15/143
10,294,986	B2	5/2019	Gonzalez	
D861,756	S *	10/2019	Pop	D15/143
D888,787	S *	6/2020	Kolste	D15/143
2003/0026718	A1 *	2/2003	Dziver	F04D 29/047 417/423.9
2008/0112658	A1 *	5/2008	Justin	F16C 17/02 384/107
2009/0260895	A1	10/2009	Vail et al.	
2010/0166347	A1 *	7/2010	Wendling	F16C 33/1075 384/114
2012/0057814	A1	3/2012	Dadson et al.	
2012/0241226	A1	9/2012	Bertagnolli et al.	
2014/0366456	A1	12/2014	Chapman et al.	
2014/0367176	A1	12/2014	Gonzalez et al.	

FOREIGN PATENT DOCUMENTS

WO 2017034787 A1 3/2017

OTHER PUBLICATIONS

International Search Report and Written Opinion from International Application No. PCT/US2018/03190 mailed Jul. 19, 2018.
 Notice of Allowance for U.S. Appl. No. 29/606,740 mailed Feb. 19, 2020.
 Notice of Allowance for U.S. Appl. No. 29/606,797 mailed Feb. 19, 2020.
 Restriction Requirement for U.S. Appl. No. 29/606,740, mailed Sep. 27, 2019.
 Restriction Requirement for U.S. Appl. No. 29/606,797 mailed Sep. 27, 2019.
 U.S. Appl. No. 29/606,740, filed Jun. 7, 2017.
 U.S. Appl. No. 29/606,797, filed Jun. 7, 2017.
 U.S. Appl. No. 62/279,271, filed Jan. 15, 2016.
 U.S. Appl. No. 62/516,226, filed Jun. 7, 2017.
 Issue Notification for U.S. Appl. No. 29/606,740 mailed Jun. 10, 2020.
 Issue Notification for U.S. Appl. No. 29/606,797 mailed Jun. 10, 2020.
 Non-Final Office Action for U.S. Appl. No. 16/614,706 mailed Jul. 20, 2020.
 Notice of Allowance for U.S. Appl. No. 16/614,706 mailed Jan. 22, 2021.

* cited by examiner

Primary Examiner — Khawaja Anwar
 (74) Attorney, Agent, or Firm — BKRIP LLC

(57) CLAIM

The ornamental design for a radial bearing, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a radial bearing including a bearing element having a groove in a bearing surface thereof, according to a first embodiment;

FIG. 2 is a perspective cutaway view of the radial bearing shown in FIG. 1;

FIG. 3 is a side elevational view of the bearing element shown in FIGS. 1 and 2, with the opposing side elevational view being identical;

FIG. 4 is a side elevational view of the bearing element shown in FIGS. 1 and 2 and rotated 90° relative to the side elevational view shown in FIG. 3, with the opposing side elevational view being identical;

FIG. 5 is a perspective view of a radial bearing including a plurality of bearing elements that each have a groove in a bearing surface thereof, according to a second embodiment; FIG. 6 is a perspective cutaway view of the radial bearing shown in FIG. 5;

FIG. 7 is a side elevational view of one of the bearing elements shown in FIGS. 5 and 6, with the opposing side elevational view being identical;

FIG. 8 is a side elevational view of one of the bearing elements shown in FIGS. 5 and 6 and rotated 90° relative to the side elevational view shown in FIG. 7, with the opposing side elevational view being identical;

FIG. 9 is a perspective view of a radial bearing including a plurality of bearing elements that each have a groove in a bearing surface thereof, according to a third embodiment; FIG. 10 is a perspective cutaway view of the radial bearing shown in FIG. 9;

FIG. 11 is a side elevational view of one of the bearing elements shown in FIGS. 9 and 10, with the opposing side elevational view being identical;

FIG. 12 is a side elevational view of one of the bearing elements shown in FIGS. 9 and 10 and rotated 90° relative to the side elevational view shown in FIG. 11, with the opposing side elevational view being identical;

FIG. 13 is a perspective view of a radial bearing including a plurality of bearing elements that each have a groove in a bearing surface thereof, according to an fourth embodiment; FIG. 14 is a perspective cutaway view of the radial bearing shown in FIG. 13;

FIG. 15 is a side elevational view of one of the bearing elements shown in FIGS. 13 and 14, with the opposing side elevational view being identical;

FIG. 16 is a side elevational view of one of the bearing elements shown in FIGS. 13 and 14 and rotated 90° relative to the side elevational view shown in FIG. 15, with the opposing side elevational view being identical;

FIG. 17 is a perspective view of a radial bearing including a plurality of first bearing elements that each have a groove in a bearing surface thereof and a second bearing element that does not include a groove in a bearing surface thereof, according to a fifth embodiment;

FIG. 18 is a perspective cutaway view of the radial bearing shown in FIG. 17;

FIG. 19 is a side elevational view of one of the first bearing elements shown in FIGS. 17 and 18, with the opposing side elevational view being identical;

FIG. 20 is a side elevational view of one of the first bearing elements shown in FIGS. 17 and 18 and rotated 90° relative to the side elevational view shown in FIG. 19, with the opposing side elevational view being identical;

FIG. 21 is a side elevational view of the second bearing element shown in FIGS. 17 and 18, with the opposing side elevational view being identical;

FIG. 22 is a side elevational view of the second bearing element shown in FIGS. 17 and 18, and rotated 90° relative

to the side elevational view shown in FIG. 21, with the opposing side elevational view being identical;

FIG. 23 is a perspective view of a radial bearing including a plurality of first bearing elements that each have a groove in a bearing surface thereof and a plurality of second bearing elements that do not include a groove in a bearing surface thereof, according to a sixth embodiment;

FIG. 24 is a perspective cutaway view of the radial bearing shown in FIG. 23;

FIG. 25 is a side elevational view of one of the first bearing elements shown in FIGS. 23 and 24, with the opposing side elevational view being identical;

FIG. 26 is a side elevational view of one of the first bearing elements shown in FIGS. 23 and 24 and rotated 90° relative to the side elevational view shown in FIG. 25, with the opposing side elevational view being identical;

FIG. 27 is a side elevational view of one of the second bearing elements shown in FIGS. 23 and 24, with the opposing side elevational view being identical;

FIG. 28 is a side elevational view of one of the second bearing elements shown in FIGS. 23 and 24, and rotated 90° relative to the side elevational view shown in FIG. 27, with the opposing side elevational view being identical;

FIG. 29 is a perspective view of a radial bearing including a plurality of bearing elements that each have a groove in a bearing surface thereof, according to an seventh embodiment;

FIG. 30 is a perspective cutaway view of the radial bearing shown in FIG. 29;

FIG. 31 is a side elevational view of one of the bearing elements shown in FIGS. 29 and 30, with the opposing side elevational view being identical;

FIG. 32 is a side elevational view of one of the bearing elements shown in FIGS. 29 and 30 and rotated 90° relative to the side elevational view shown in FIG. 31, with the opposing side elevational view being identical;

FIG. 33 is a perspective view of a radial bearing including a plurality of bearing elements that each have a groove in a bearing surface thereof, according to an eighth embodiment;

FIG. 34 is a perspective cutaway view of the radial bearing shown in FIG. 33;

FIG. 35 is a side elevational view of one of the bearing elements shown in FIGS. 33 and 34, with the opposing side elevational view being identical; and,

FIG. 36 is a side elevational view of one of the bearing elements shown in FIGS. 33 and 34 and rotated 90° relative to the side elevational view shown in FIG. 35, with the opposing side elevational view being identical.

The broken lines shown in the drawings are for illustrative purposes only and form no part of the claimed design.

1 Claim, 26 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36