

[54] **HOLD DOWN DEVICE FOR SECURING A LINE OR FLEXIBLE MEMBER TO THE GROUND**

[76] Inventor: **Lois R. Brown**, 112 Florence Drive, Cordell, Okla. 73632

[**] Term: **14 Years**

[21] Appl. No.: **528,215**

[22] Filed: **Nov. 29, 1974**

[51] Int. Cl. **D8-08**

[52] U.S. Cl. **D8/229**

[58] Field of Search **D86/10 M; 132/36 R, 132/50 R; D8/266, 229**

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,678,945	7/1972	Reynoir	132/46 R
D. 22,642	7/1893	Farmer	D86/10 M
D. 47,452	6/1915	Chacon	D86/10 M

D. 57,645 4/1921 Hake D86/10 M

Primary Examiner—William N. Wertman
Attorney, Agent, or Firm—William R. Laney

[57] **CLAIM**


The ornamental design for a hold down device for securing a line or flexible member to the ground, substantially as shown and described.

DESCRIPTION

FIG. 1 is a front elevation view of a hold down device for securing a line or flexible member to the ground incorporating the design of the present invention.

FIG. 2 is a side elevation view of the hold down device for securing a line or flexible member to the ground shown in FIG. 1.

FIG. 3 is a plan view of the hold down device for securing a line or flexible member to the ground shown in FIG. 1.






FIG. 1



FIG. 2



FIG. 3