

[54] **COMBINED TRANSCEIVER AND
MOUNTING BRACKET FOR USE IN
INTERCOM DEVICES**

[75] Inventor: **Peter Pablik**, Salzburg, Austria

[73] Assignee: **Ring-Control
Electronic-Handelsgesellschaft
m.b.H.**, Salsburg, Austria

[**] Term: **14 Years**

[21] Appl. No.: **628,249**

[22] Filed: **Nov. 3, 1975**

[51] Int. Cl. **D14—03**

[52] U.S. Cl. **D26/14 K**

[58] **Field of Search** 325/492, 15, 16, 111,
325/117, 2; 179/146 R; D26/14 K; D56/4 B

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,070,748 12/1962 Worobey et al. 325/492

3,128,431 4/1064 Walker 179/146 R X

D. 226,093 1/1973 Whiting et al. D26/14 K

D. 234,605 3/1973 Larson ... D26/14 K

D. 237,893 12/1975 Wennerström D26/14 K

Primary Examiner—Bernard Ansher

Attorney, Agent, or Firm—Edwin E. Greigg

[57] **CLAIM**

The ornamental design for a combined transceiver and mounting bracket for use in intercom devices, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of the transceiver mounting bracket, shown separately for illustrative purposes only;

FIG. 2 is a perspective view of the combined transceiver and mounting bracket therefor;

FIG. 3 is a side elevation thereof;


FIG. 4 is a side elevation of the mounting bracket;

FIG. 5 is a rear elevation of the transceiver;

FIG. 6 is a front elevation of the transceiver;

FIG. 7 is a top plan view thereof; and

FIG. 8 is a bottom plan view thereof.






FIG. 1




FIG. 2

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

