

[54] ELECTRICAL OUTLET GUARD

[75] Inventors: Jerry C. Frinzel, Sacramento; Robert H. Britschgi, Fair Oaks, both of Calif.

[73] Assignee: Robert H. Britschgi, Fair Oaks, Calif.

[**] Term: 14 Years

[21] Appl. No.: 619,841

[22] Filed: Oct. 6, 1975

[51] Int. Cl. D8-08

[52] U.S. Cl. D8/499

[58] Field of Search D8/499

[56] References Cited

U.S. PATENT DOCUMENTS

3,477,676 11/1969 Moore 248/201

Primary Examiner—William N. Wertman
Attorney, Agent, or Firm—Robert G. West

[57] CLAIM

The ornamental design for an electrical outlet guard, as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of an electrical outlet guard, showing our new design, the longitudinal clamping slot being in open position;

FIG. 2 is a bottom plan view;

FIG. 3 is an elevational view of the left-hand side of FIG. 1, the opposite side being in mirror symmetry; FIG. 4 is an elevational view of the upper end of FIG. 1;

FIG. 5 is a side elevational view of the lower end of FIG. 1;

FIG. 6 is a sectional view of the hub portion of the device taken on a diameter as indicated by the line 6 — 6 in FIG. 1;

FIG. 7 is a fragmentary longitudinal sectional view of the limb of the device containing the clamping slot, the plane of the section being indicated by the line 7 — 7 in FIG. 1;

FIG. 8 is a transverse sectional view of one of the limbs, the plane of the section being indicated by the line 8 — 8 in FIG. 1;

FIG. 9 is a top plan view, to a reduced scale, showing the longitudinal clamping slot partially closed by a clamping screw spanning the registering threaded openings in the clamping screw bosses on opposite sides of the clamping slot, FIG. 9 also showing the broken line, in order to illustrate the environment, a typical electrical plug clamped in the central hub of the device with the plug in the upper outlet of a typical dual outlet underlying the device; and,

FIG. 10 is a sectional view taken on the plane indicated by the line 10 — 10 in FIG. 9, and showing in broken line, to illustrate the environment, a typical plug clamped in the constricted hub with the contact prongs extending through the cover plate into the upper one of the dual outlets.




FIG-4





FIG-3




FIG-1




FIG-5




FIG-2




FIG. 6



FIG. 8




FIG. 7




FIG. 9




FIG. 10