

[54] **FASTENER**

[76] **Inventor:** Harry E. Mazur, P.O. Box 4508,  
Palm Springs, Calif. 92262

[\*\*] **Term:** 14 Years

[21] **Appl. No.:** 538,539

[22] **Filed:** Jan. 6, 1975

[51] **Int. Cl.** ..... D2-07

[52] **U.S. Cl.** ..... D2/409

[58] **Field of Search** ..... D2/405, 409, 411, 402,  
D2/401; 24/245 L, 245 R, 223; 16/114 R

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

|            |        |         |          |
|------------|--------|---------|----------|
| 623,987    | 5/1899 | Conover | 24/245 L |
| 624,503    | 5/1899 | Krause  | 24/245 L |
| D. 201,277 | 6/1965 | Lillie  | D2/411   |

**FOREIGN PATENT DOCUMENTS**

475,800 11/1937 United Kingdom ..... D2/402 X

*Primary Examiner*—Nelson C. Holtje  
*Attorney, Agent, or Firm*—Manfred M. Warren

[57] **CLAIM**

The ornamental design for a fastener, as shown.

**DESCRIPTION**

FIG. 1 is an exploded perspective view of a fastener showing my new design;


FIG. 2 is a top plan view thereof in the attached position of the parts selectively rotated to position for snap action attachment and detachment;

FIG. 3 is a bottom plan view of FIG. 2 with the parts rotated 90° to their positively locked on position of normal use;

FIG. 4 is a typical side elevational view of FIG. 2;

FIG. 5 is a left end elevational view of FIG. 2; and

FIG. 6 is a right end elevational view of FIG. 2.






Fig. 1





Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6