

[54] **FASTENER**

[76] **Inventor:** Harry E. Mazur, P.O. Box 4508,
Palm Springs, Calif. 92262

[**] **Term:** 14 Years

[21] **Appl. No.:** 538,539

[22] **Filed:** Jan. 6, 1975

[51] **Int. Cl.** D2-07

[52] **U.S. Cl.** D2/409

[58] **Field of Search** D2/405, 409, 411, 402,
D2/401; 24/245 L, 245 R, 223; 16/114 R

[56] **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|------------|--------|---------|----------|
| 623,987 | 5/1899 | Conover | 24/245 L |
| 624,503 | 5/1899 | Krause | 24/245 L |
| D. 201,277 | 6/1965 | Lillie | D2/411 |

FOREIGN PATENT DOCUMENTS

475,800 11/1937 United Kingdom D2/402 X

Primary Examiner—Nelson C. Holtje
Attorney, Agent, or Firm—Manfred M. Warren

[57] **CLAIM**

The ornamental design for a fastener, as shown.

DESCRIPTION

FIG. 1 is an exploded perspective view of a fastener showing my new design;


FIG. 2 is a top plan view thereof in the attached position of the parts selectively rotated to position for snap action attachment and detachment;

FIG. 3 is a bottom plan view of FIG. 2 with the parts rotated 90° to their positively locked on position of normal use;

FIG. 4 is a typical side elevational view of FIG. 2;

FIG. 5 is a left end elevational view of FIG. 2; and

FIG. 6 is a right end elevational view of FIG. 2.






Fig. 1





Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6