

[54] COMBINED SAFETY HARNESS AND LIGHT

[76] Inventor: Hubert King Neyman, 8825 N. Hickory Valley Rd., Chattanooga, Tenn. 37416

[**] Term: 14 Years

[21] Appl. No.: 679,822

[22] Filed: Apr. 23, 1976

[51] Int. Cl. D2-99

[52] U.S. Cl. D2/27

[58] Field of Search D2/25, 27, 28, 36, 80, D2/81, 179, 225, 226, 228, 229, 452; 2/44, 45, 46, 48, 49 R, 50, 51, 88; 224/5 R, 5 A, 5 B, 5 P, 5 T, 5 BC, 5 Y, 6; 119/96; 244/151 R; 182/3, 6, 7; D24/49, 64, 99; D87/1 R; D56/1 E; D10/109, 110, 114

[56] References Cited

U.S. PATENT DOCUMENTS

D. 207,931	6/1967	Huret	D10/114 X
D. 238,208	12/1975	Hesen	D24/64
593,901	11/1897	Murnan	224/5 A

1,784,466	12/1930	Rensonnet	D10/110
3,923,222	12/1975	Groves	D87/1 R

OTHER PUBLICATIONS

Rogers Drums U.S.A. '67-'68 Cat., ©'67, p. 47, item #4464.

Primary Examiner—Joel Stearman

Assistant Examiner—J. Corrigan

Attorney, Agent, or Firm—Joseph C. Redmond, Jr.

[57] CLAIM

The ornamental design for a combined safety harness and light, as shown.

DESCRIPTION

FIG. 1 is a front, top and right side perspective view of a combined safety harness and light showing my new design;

FIG. 2 is a front elevational view;


FIG. 3 is a rear elevational view;

FIG. 4 is a right side elevational view;

FIG. 5 is a left side elevational view;

FIG. 6 is a top plan view; and

FIG. 7 is a bottom plan view.






Fig. 1

Fig. 2




Fig. 3




Fig. 6




Fig. 4




Fig. 7




Fig. 5

