

[54] COMBINED LIGHTHOUSE AND WIND
DIRECTION INDICATOR

[76] Inventor: Joseph O. Tally, Jr., 560 N. St., SW.,
Washington, D.C. 20024

[**] Term: 14 Years

[21] Appl. No.: 742,445

[22] Filed: Nov. 17, 1976

[51] Int. Cl. D10-06; D10-04

[52] U.S. Cl. D10/114; D10/59

[58] Field of Search 73/188; D10/114, 59;
340/28, 29, 366

[56] References Cited

U.S. PATENT DOCUMENTS

D. 84,905	8/1931	Tate		D10/114
1,876,082	9/1932	Shaw et al.		340/28 X
3,732,730	5/1973	Kwolek		73/188

3,869,911	3/1975	Levy		73/188 X
4,046,007	9/1977	Tally, Jr.		73/188

FOREIGN PATENT DOCUMENTS

572,451 3/1933 Fed. Rep. of Germany 73/188

Primary Examiner—Susan J. Lucas

Attorney, Agent, or Firm—J. Gibson Semmes

[57] CLAIM

The ornamental design for a combined lighthouse and
wind direction indicator, as shown and described.


DESCRIPTION

FIG. 1 is a front elevation of the combined lighthouse
and wind direction indicator showing my new design,
the rear being identical.

FIG. 2 is a side elevation thereof, the opposite side
being identical.

FIG. 3 is a top plan thereof.

FIG. 4 is a bottom plan thereof.






FIG. 1




FIG. 2




FIG. 3




FIG. 4