

United States Patent [19]

Genaro et al.

[11] Des. 253,344

[45] ** Nov. 6, 1979

[54] TELEPHONE STAND

- [75] Inventors: **Donald M. Genaro**, Haworth, N.J.;
John N. McGarvey, Drexel Hill, Pa.;
Gordon E. Sylvester, Jamaica, N.Y.
- [73] Assignee: **Bell Telephone Laboratories, Incorporated**, Murray Hill, N.J.
- [*] Notice: The portion of the term of this patent subsequent to Nov. 4, 1989, has been disclaimed.
- [**] Term: **14 Years**
- [21] Appl. No.: **854,503**
- [22] Filed: **Nov. 23, 1977**

Related U.S. Application Data

- [60] Division of Ser. No. 604,592, Aug. 14, 1975, which is a continuation-in-part of Ser. No. 469,855, May 14, 1974, Pat. No. D. 237,506, which is a continuation-in-part of Ser. No. 424,413, Dec. 13, 1973, abandoned, which is a continuation-in-part of Ser. No. 364,704, May 29, 1973, abandoned.
- [51] Int. Cl. **D14—03**
- [52] U.S. Cl. **D14/60; D14/53**
- [58] Field of Search **179/178, 179, 100 D, 179/100 R, 100 C, 184 D; D14/60, 57, 53**

[56] References Cited

U.S. PATENT DOCUMENTS

D. 203,750	2/1966	Wharton	D14/62
D. 211,739	7/1968	Dreyfus	D14/62
D. 224,409	7/1972	Janda	D14/58
D. 231,650	5/1974	Eubank et al.	D14/60
D. 237,506	11/1975	Genaro et al.	D14/60
3,941,951	3/1976	Engstrom	179/100 C

Primary Examiner—Bernard Ansher
Attorney, Agent, or Firm—W. L. Keefauver

[57] CLAIM

The ornamental design for a telephone stand, substantially as shown and described.

DESCRIPTION

FIG. 1 is a side elevation of a telephone stand showing our new design;
FIG. 2 is a front view taken perpendicular to the face of the telephone stand;
FIG. 3 is a top elevation thereof;
FIG. 4 is a bottom elevation thereof;
FIG. 5 is a front view taken perpendicular to the face of a second embodiment of the telephone stand illustrated in FIGS. 1 through 4, the side elevation view being essentially the same as that shown in FIG. 1;
FIG. 6 is a top elevation thereof;
FIG. 7 is a bottom elevation thereof;
FIG. 8 is a front view taken perpendicular to the face of a third embodiment of the telephone stand illustrated in FIGS. 1 through 4, the side elevation thereof being essentially the same as that shown in FIG. 1;
FIG. 9 is a top elevation thereof;
FIG. 10 is a bottom elevation thereof;
FIG. 11 is a front view taken perpendicular to the face of a fourth embodiment of the telephone stand illustrated in FIGS. 1 through 4, the side elevation thereof being essentially the same as that shown in FIG. 1;
FIG. 12 is a top elevation thereof;
FIG. 13 is a bottom elevation thereof;
FIG. 14 is a front view taken perpendicular to the face of a fifth embodiment of the telephone stand illustrated in FIGS. 1 through 4, the side elevation being essentially the same as that shown in FIG. 1;
FIG. 15 is a top elevation thereof;
FIG. 16 is a bottom elevation thereof;
FIG. 17 is a front view taken perpendicular to the face of a sixth embodiment of the telephone stand illustrated in FIGS. 1 through 4, the side elevation being essentially the same as that shown in FIG. 1;
FIG. 18 is a top elevation thereof;
FIG. 19 is a bottom elevation thereof;
FIG. 20 is a front view taken perpendicular to the face of a seventh embodiment of the telephone stand illustrated in FIGS. 1 through 4, the side elevation being essentially the same as that shown in FIG. 1;
FIG. 21 is a top elevation thereof;
FIG. 22 is a bottom elevation thereof;
FIG. 23 is a front view taken perpendicular to the face of an eighth embodiment of the telephone stand illus-

trated in FIGS. 1 through 4, the side elevation being essentially the same as that shown in FIG. 1; FIG. 24 is a top elevation thereof; FIG. 25 is a bottom elevation thereof; FIG. 26 is a front view taken perpendicular to the face of a ninth embodiment of the telephone stand illustrated

in FIGS. 1 through 4, the side elevation being essentially the same as that shown in FIG. 1; FIG. 27 is a top elevation thereof; FIG. 28 is a bottom elevation thereof; and FIG. 29 is a perspective view that is intended to be common for all embodiments of the invention, the stand being broken across its width to indicate that the only difference between embodiments resides in variations in the width of the stand.

U.S. Patent

Nov. 6, 1979

Sheet 1 of 16

Des. 253,344

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 10




U.S. Patent

Nov. 6, 1979

Sheet 4 of 16

Des. 253,344

FIG. II



U.S. Patent Nov. 6, 1979 Sheet 5 of 16 Des. 253,344

FIG. 12




FIG. 13




FIG. 14




FIG. 15





FIG. 16



U.S. Patent

Nov. 6, 1979

Sheet 8 of 16

Des. 253,344

FIG. 17




FIG. 18





FIG. 19



U.S. Patent Nov. 6, 1979 Sheet 10 of 16 Des. 253,344

FIG. 20




FIG. 21





FIG. 22



U.S. Patent Nov. 6, 1979 Sheet 12 of 16 Des. 253,344

FIG. 23




FIG. 24





FIG. 25



U.S. Patent Nov. 6, 1979 Sheet 14 of 16 Des. 253,344

FIG. 26




FIG. 27




FIG. 28




FIG. 29

