

[54] FINGERNAIL POLISHING TOOL

[76] Inventors: Moriko Tsukamoto, 2-3 chome; Chihiro Tsukamoto, 1-3 chome, both of Toyotama-kita, Nerima-ku, Tokyo, Japan

[**] Term: 7 Years

[21] Appl. No.: 836,934

[22] Filed: Sep. 27, 1977

[30] Foreign Application Priority Data

Mar. 29, 1977 [JP] Japan 52-11044

[51] Int. Cl. D28-03

[52] U.S. Cl. D28/59

[58] Field of Search D24/23, 36, 41; D4/19; D28/56, 57, 59, 62, 73, 74; 132/73, 73.5, 75, 75.6, 76.2, 76.4, 76.5

[56] References Cited

U.S. PATENT DOCUMENTS

- D. 55,406 6/1920 Berry D28/59
- D. 70,938 8/1926 Booty D28/59
- D. 147,797 11/1947 Kayer D28/56
- 1,134,088 3/1915 Mendelsohn 132/76.5

FOREIGN PATENT DOCUMENTS

566079 11/1923 France 132/76.4

Primary Examiner—Louis S. Zarfes
Attorney, Agent, or Firm—Frank J. Jordan

[57] CLAIM

The ornamental design for fingernail polishing tool, substantially as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of a fingernail polishing tool showing our new design;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a bottom plan view thereof;

FIG. 4 is a left side elevational view thereof;

FIG. 5 is a right side elevational view thereof; and

FIG. 6 is a perspective view thereof.

The rear is a mirror image of the front.

A rear view is omitted since it is symmetrical with a front view thereof. The function of this design is as follows. This tool is used in polishing fingernails. That is to say, a ring is attached to one end of a block and after inserting a finger into the ring, the surface of a given nail is carefully rubbed by a soft buff member attached to one side of the block held by hand, so that the surface of the nail may be smoothed and polished.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 6

