

[54] COMBINED KEY RING AND CLIP LOCK FOR HOLDING A GAS PUMP TRIGGER IN THE OPEN POSITION

2,564,242 8/1951 Wendt ..... 70/458  
2,994,462 8/1961 Hirsch et al. .... D6/251  
3,346,150 10/1967 Clopton ..... 223/95  
4,095,629 6/1978 Jordan ..... 141/392

[76] Inventor: Gregory S. Hadgis, 14078 Zaremba Dr., Brookpark, Ohio 44142

Primary Examiner—Wallace R. Burke  
Assistant Examiner—B. J. Bullock  
Attorney, Agent, or Firm—Maky, Renner, Otto & Boisselle

[\*\*] Term: 14 Years

[21] Appl. No.: 32,717

[22] Filed: Apr. 23, 1979

[51] Int. Cl. .... D3—01; D6—08; D8—08; D15—02; D23—01

[52] U.S. Cl. .... D3/62; 141/392; D6/247; D6/251; D8/349; D8/354; D15/9.1; D23/37

[58] Field of Search ..... D8/349, 354; D6/247, D6/251; 211/119; 223/DIG. 1, 95, 85; 74/526; 141/392; 251/89, 90, 101; D3/61—65; 70/456; D15/9.1; D23/37

[56] References Cited  
U.S. PATENT DOCUMENTS


1,333,655 3/1920 Davis ..... 70/458


[57] CLAIM

The ornamental design for a combined key ring and clip lock for holding a gas pump trigger in the open position, as shown.


DESCRIPTION

FIG. 1 is a perspective view of a combined key ring and clip lock for holding a gas pump trigger in the open position showing my new design;  
FIG. 2 is a side elevational view thereof;  
FIG. 3 is an end elevational view taken from the left of FIG. 2;  
FIG. 4 is an end elevational view taken from the right of FIG. 2;  
FIG. 5 is a top plan view thereof;  
FIG. 6 is a bottom plan view thereof.






**FIG. 1**



**FIG. 5**




**FIG. 3**



**FIG. 2**



**FIG. 4**



**FIG. 6**