

[54] **HAND TOOL FOR INDUCTIVELY TESTING CONTINUITY IN ELECTRICAL IGNITION SYSTEMS AND FOR REMOVING SPARK PLUG BOOTS**

1,687,574	10/1928	Liss .....	29/630 A
1,843,135	2/1932	Kuhlman .....	7/167
2,048,652	7/1936	Stowell .....	324/17
2,213,297	9/1940	Zitzmann .....	324/17
3,831,274	8/1974	Horrocks .....	30/294

[76] **Inventor:** George G. Martin, 1743 Walnut Rd., Kent, Ohio 44240

[\*\*] **Term:** 14 Years

[21] **Appl. No.:** 863,331

[22] **Filed:** Dec. 21, 1977

[51] **Int. Cl.** ..... D10-04

[52] **U.S. Cl.** ..... D10/77; D8/87; D8/89; 324/396; 254/25

[58] **Field of Search** ..... D8/82-89, D8/48, 105; D10/77; 324/17, 19; 81/3 G, 3 J, 3.8, 3.46; 339/257, 277; 7/115, 166, 167; 254/18-25, 131, 131.5; 29/278, 280, 764, 630 A

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

949,337 2/1910 Trogner ..... 254/25

**OTHER PUBLICATIONS**

Hollingsworth Company Brochure, p. 3, (Spade Flared).

*Primary Examiner*—Peter Feldman  
*Attorney, Agent, or Firm*—E. R. Hamilton

[57] **CLAIM**


The ornamental design for a hand tool for inductively testing continuity in electrical ignition systems and for removing spark plug boots, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of a hand tool for inductively testing continuity in electrical ignition systems and for removing spark plug boots embodying my new design.

FIG. 2 is a bottom plan view thereof.

FIG. 3 is a side view taken from the left of FIG. 2.






FIG. 1




FIG. 2




FIG. 3