

[54] **COMBINED HEAT APPLYING ROLLER
AND CONTROL DEVICE THEREFOR**

[76] Inventors: Rubin Feldman, 46 Rio Vista Dr., St. Louis, Mo. 63124; Wilbur Paddock, 7705 Underhill Dr., St. Louis, Mo. 63133; James S. Eiteljorg, 1214 Orchard Village, Ballwin, Mo. 63011

[**] Term: 14 Years

[21] Appl. No.: 817,840

[22] Filed: Jul. 21, 1977

[51] Int. Cl. D8-05
[52] U.S. Cl. D8/30; 219/244
[58] Field of Search D8/30, 14; D19/66;
156/574, 579; 38/100, 101; 219/240, 241, 227,
244

[56] **References Cited**

U.S. PATENT DOCUMENTS

1,596,181 8/1926 Hills 219/244
3,857,015 12/1974 Clark et al. 219/244

FOREIGN PATENT DOCUMENTS

218068 6/1908 Fed. Rep. of Germany 219/244


Primary Examiner—Peter Feldman
Attorney, Agent, or Firm—Polster, Polster and Lucchesi

[57] **CLAIM**

The ornamental design for a combined heat applying roller and control device therefor, as shown and described.

DESCRIPTION

FIG. 1 is a view in perspective of a combined heat applying roller and control device therefor showing our new design; the cord, coiled spring sleeve, and control device are omitted for ease of illustration; FIG. 2 is a view in side elevation thereof; FIG. 3 is a front view thereof; FIG. 4 is a bottom plan view thereof showing the cord and coiled spring sleeve; FIG. 5 is a view in perspective, corresponding to FIG. 1 showing its associated control device; the undisclosed side of the control device being the same as the side shown; FIG. 6 is an enlarged bottom plan view of the control device of FIG. 5; and FIG. 7 is an enlarged end elevational view of the control device of FIG. 5. The cords are broken away in FIGS. 4 and 5 and fragmentarily shown in FIGS. 6 and 7 to indicate indeterminate length.






FIG. 1.



FIG. 2.




FIG. 3.




FIG.4.




FIG. 5.




FIG. 6.




FIG. 7.