

[54] **PORTABLE SCREENING PLANT**

[75] Inventor: **James L. Read**, Halifax, Mass.
 [73] Assignee: **F. T. Read & Sons, Inc.**, Rockland, Mass.
 [**] Term: **14 Years**
 [21] Appl. No.: **83,971**
 [22] Filed: **Oct. 11, 1979**
 [51] Int. Cl. **D15-04**
 [52] U.S. Cl. **D15/147**
 [58] Field of Search **D15/147; 209/257, 319**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 236,155	7/1975	Lower et al.	D15/147
3,080,860	3/1963	Riccio, Jr.	209/257 X
3,101,314	8/1963	Johnson	209/319
3,215,408	11/1965	Hansen	D15/147 X
4,222,866	9/1980	Wilson	209/257 X


Primary Examiner—A. Hugo Word
Attorney, Agent, or Firm—Hamilton, Brook, Smith & Reynolds

[57] **CLAIM**

The ornamental design for a portable screening plant, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the front and hitch end of all embodiments of my portable screening plant; FIG. 2 is a top view of a first embodiment of the screening plant of FIG. 1; FIG. 3 is a rear elevational view of the embodiment of FIG. 2 showing the underside of the screen; FIG. 4 is an elevational view of the hitch end of the screening plant of FIG. 1; FIG. 5 is an elevational view of the wheel end of the embodiment of FIG. 2; FIG. 6 is a perspective view of the rear and wheel end of the embodiment of FIG. 2 with the screening plant in a raised position in which it is supported by the wheels; FIG. 7 is a perspective view similar to FIG. 1 but with the screening plant in a raised position in which it is supported by the wheels; FIG. 8 is a top view of an alternative embodiment of the screening plant suitable for use with an outfeed conveyor through the wheel end; FIG. 9 is a rear elevational view of the embodiment of FIG. 8 showing a hopper within the plant and below the screen; FIG. 10 is a wheel end elevational view of the embodiment of FIG. 8 showing a conveyor-opening over the wheel axle; FIG. 11 is a rear perspective view of a third embodiment of the screening plant suitable for use with an outfeed conveyor but with a higher conveyor-opening toward the rear of the wheel end and with the rear partially closed.






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11

