

[54] **VEHICLE BATTERY CONDITION INDICATOR**

[75] Inventor: **Chung S. Leung, Kowloon, Hong Kong**

[73] Assignee: **Foster Industries Co., Ltd., Kowloon, Hong Kong**

[**] Term: **14 Years**

[21] Appl. No.: **144,934**

[22] Filed: **Apr. 29, 1980**

[30] **Foreign Application Priority Data**
 Mar. 19, 1980 [GB] United Kingdom 994117

[51] Int. Cl. **D10-04**

[52] U.S. Cl. **D10/75**

[58] Field of Search **D10/46, 75, 78, 77, D10/80; 324/158 P, 126, 133, 437; 340/636**

[56] **References Cited**
U.S. PATENT DOCUMENTS

D. 180,475 6/1957 Dickinson D10/75 X
 D. 213,962 4/1969 Potruch D10/78
 D. 228,914 10/1973 Mackenzie D10/75
 2,991,413 7/1961 Taylor 340/636 X

Primary Examiner—Nelson C. Holtje
Attorney, Agent, or Firm—Wenderoth, Lind & Ponack

[57] **CLAIM**

The ornamental design for a vehicle battery condition indicator, substantially as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of a vehicle battery condition indicator showing my new design;
 FIG. 2 is a bottom plan view thereof;
 FIG. 3 is a left side elevational view thereof, the right side being a mirror image thereto;
 FIG. 4 is a rear elevational view thereof;
 FIG. 5 is a front elevational view thereof;
 FIG. 6 is a top and left front perspective view thereof with the sunvisor in the extended position.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

