

[54] DISPOSABLE SPLINT
[75] Inventor: Morton I. Thomas, Nyack, N.Y.
[73] Assignee: Temco Products, Inc., Passaic, N.J.
[**] Term: 14 Years
[21] Appl. No.: 162,724
[22] Filed: Jun. 25, 1980
[51] Int. Cl. D24-04
[52] U.S. Cl. D24/64
[58] Field of Search D24/64; 128/87 R, 89 R,
128/88, 93

[56] References Cited
U.S. PATENT DOCUMENTS

D. 234,271	2/1975	Moore		D24/64
D. 235,927	7/1975	Moore		D24/64
2,486,687	11/1949	Svaetichin		128/88
2,667,868	2/1954	Smyth		128/87 R
2,984,239	5/1961	Taylor		128/87 R X
3,232,289	2/1966	Zimmerman		128/87 R
3,496,934	2/1970	Anderson		128/88
3,624,745	11/1971	Bowers		128/93
3,695,258	10/1972	Castle		128/87 R
3,850,167	8/1973	Seeley		128/87 R
3,896,799	7/1975	Seeley		128/87 R

3,923,048	12/1975	Schaar		128/87 R
4,043,330	8/1977	Bansal		128/87 R
4,143,653	3/1979	Wichman		128/89 R

Primary Examiner—Bernard Ansher
Attorney, Agent, or Firm—Richard C. Woodbridge

[57] CLAIM

The ornamental design for a disposable splint, as shown and described.

DESCRIPTION

FIG. 1 is a front elevation of a disposable splint showing my new design;
FIG. 2 is a rear elevational thereof;
FIG. 3 is a bottom plan view thereof;
FIG. 4 is a right side elevation thereof;
FIG. 5 is a front perspective view thereof, in an alternate condition;
FIG. 6 is a elevation as seen from the left of FIG. 5;
FIG. 7 is a front elevation of a modified embodiment of the form illustrated in FIG. 1;
FIG. 8 is a rear elevation thereof;
FIG. 9 is a bottom plan view thereof;
FIG. 10 is a front perspective view thereof; in an alternate condition;
FIG. 11 is a right side elevation thereof; and
FIG. 12 is an elevation as seen from the left of FIG. 10.




FIG. 1.




FIG. 2.




FIG. 3.



FIG. 4.



FIG. 5.




FIG. 6.




FIG. 7.




FIG. 8.




FIG. 9.



FIG. 10.




FIG. 11.



FIG. 12.

