

[54] COMBINED CHECK RAIL LOCK AND KEEPER

[75] Inventor: Donald L. Anderson, Owatonna, Minn.

[73] Assignee: Truth Incorporated, Owatonna, Minn.

[] Term:** 14 Years

[21] Appl. No.: 220,297

[22] Filed: Dec. 29, 1981

[51] Int. Cl. D8-07

[52] U.S. Cl. D8/337

[58] Field of Search 292/241, 194, 206; D8/330, 331, 337, 341, 344, 343

[56] References Cited

U.S. PATENT DOCUMENTS

| | | | |
|------------|---------|-------------------|--------|
| D. 5,696 | 3/1872 | Fogelstrand | D8/337 |
| D. 14,972 | 4/1884 | Sparks | D8/337 |
| D. 15,755 | 1/1885 | Sparks | D8/337 |
| D. 66,181 | 12/1924 | Edelson | D8/341 |
| D. 69,503 | 2/1926 | Edelson . | |
| D. 137,539 | 3/1944 | Ledin | D8/341 |
| D. 141,887 | 7/1945 | Wilder | D8/341 |
| 156,860 | 11/1874 | Ruscoe et al. . | |
| D. 179,048 | 10/1956 | Ahlgren | D8/337 |
| D. 185,254 | 5/1959 | Ahlgren | D8/337 |
| D. 196,713 | 10/1963 | Ahlgren | D8/341 |
| D. 211,452 | 6/1968 | Petrell | D8/341 |
| D. 237,041 | 10/1975 | Ruderfer | D8/337 |
| D. 242,840 | 12/1976 | Schmidt | D8/338 |
| D. 249,017 | 8/1978 | Costello | D8/337 |
| 404,916 | 6/1889 | Koenen . | |
| 471,363 | 3/1892 | Sloan, Jr. . | |

| | | | |
|-----------|---------|-------------------|----------|
| 587,424 | 8/1897 | Bonine . | |
| 979,581 | 12/1910 | Smith . | |
| 2,135,105 | 11/1938 | Knauff | 292/206 |
| 2,997,323 | 8/1961 | Riser | D8/331 X |
| 3,811,718 | 5/1974 | Bates | 292/241 |
| 4,095,829 | 6/1978 | Klompenburg | 292/241 |

Primary Examiner—A. Hugo Word
Attorney, Agent, or Firm—Wegner, McCord, Wood & Dalton

[57] CLAIM

The ornamental design for a combined check rail lock and keeper, substantially as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of the combined check rail lock and keeper showing my new design; FIG. 2 is a front elevational view of the combined check rail lock looking toward the right side of FIG. 1; FIG. 3 is a rear elevational view of the combined check rail lock; FIG. 4 is a side elevational view of the combined check rail lock; FIG. 5 is a side elevational view of the combined check rail lock from the side opposite that shown in FIG. 4; FIG. 6 is a rear elevational view of the keeper looking toward the left side of FIG. 1; FIG. 7 is a front elevational view of the keeper; and FIG. 8 is a side elevational view of the keeper. The side of the keeper opposite that shown in FIG. 8 is a mirror image thereof and thus is not shown in the drawings. The bottom sides of both the check rail lock and the keeper are essentially planar, and similarly are not shown in detail in the drawings.




FIG. 1.




FIG. 2.




FIG. 3.




FIG. 4.




FIG. 5.




FIG. 6.




FIG. 7.





FIG. 8.



UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : Des. 268,643
DATED : Apr. 19, 1983
INVENTOR(S) : Donald L. Anderson

It is certified that error appears in the above-identified patent and that said Letters Patent are hereby corrected as shown below:

[22] Filed: Dec. 29, 1980

[SEAL]

Signed and Sealed this
Twenty-eighth Day of June 1983

Attest:

Attesting Officer

GERALD J. MOSSINGHOFF
Commissioner of Patents and Trademarks