

[54] BORE DEPTH AND FACE SQUARENESS GAGE

3,073,033 1/1963 Dega 33/174 Q
3,534,480 10/1970 Webb 33/174 Q

[75] Inventor: Robert H. Gordon, Cincinnati, Ohio

Primary Examiner—Nelson C. Holtje
Attorney, Agent, or Firm—Thomas M. Farrell

[73] Assignee: Cincinnati Milacron Inc., Cincinnati, Ohio

[57] CLAIM

[**] Term: 14 Years

The ornamental design for a bore depth and face squareness gage, as shown and described.

[21] Appl. No.: 262,345

DESCRIPTION

[22] Filed: May 11, 1981

[51] Int. Cl. D10-04

FIG. 1 is a left side elevational view of a bore depth and face squareness gage showing my new design, the right side being a mirror image thereto;

[52] U.S. Cl. D10/73

[58] Field of Search D10/73, 64, 70;
33/174 Q, 178 R, 172 R, 181 AT

FIG. 2 is a front elevational view, the rear being substantially similar but without the dial indicator and a curved mounting face, as taken from arrow 2 of FIG. 1;

FIG. 3 is a top plan view as taken from arrow 3 of FIG. 1;

FIG. 4 is a bottom plan view as taken from arrow 4 of FIG. 1.

[56] References Cited

U.S. PATENT DOCUMENTS

1,996,092 4/1935 Albertson 33/172 R
2,362,808 11/1944 Durgin D10/64 X
2,542,470 2/1951 Booth 33/174 Q
2,744,333 5/1956 Eisele 33/178 R
2,765,539 10/1956 Sear 33/181 AT

The left side elevation is plain and unornamental, depicting the vertical coaxial cylindrical and tapered surfaces of FIG. 1.



