

[54] ARMCHAIR

[76] Inventor: David L. Rowland, 8 E. 62nd St., New York, N.Y. 10021

[*] Notice: The portion of the term of this patent subsequent to May 3, 1997, has been disclaimed.

[**] Term: 14 Years

[21] Appl. No.: 157,960

[22] Filed: Jun. 9, 1980

[51] Int. Cl. D6-01
[52] U.S. Cl. D6/72
[58] Field of Search D6/47-78,
D6/32-36; 297/239, 445, 450

[56] References Cited
U.S. PATENT DOCUMENTS

D. 109,423	4/1938	Salomon	D6/78
D. 248,432	7/1978	Petersen	D6/72
3,767,261	10/1973	Rowland	D6/76 X
3,845,986	11/1974	Rowland	D6/76 X

OTHER PUBLICATIONS

Interiors, 1-1973, p. 117, Chair top center.

Primary Examiner—Bruce W. Dunkins
Attorney, Agent, or Firm—Owen, Wickersham & Erickson

[57] CLAIM

The ornamental design for an armchair, substantially as shown.

DESCRIPTION

FIG. 1 is a perspective view, looking from the front and side at about a 45° angle, of an armchair embodying my new design.

FIG. 2 is a perspective view thereof, looking from one side.

FIG. 3 is a perspective view thereof, looking down from above and from the rear at about 45°.

FIG. 4 is a perspective view thereof, looking from the rear and slightly above.

FIG. 5 is a bottom view thereof.

FIG. 6 is a perspective view, looking down from above and from one side and the front of a modified form of armchair also embodying my new design.


FIG. 7 is a perspective view of the armchair of FIG. 6, looking from the rear and one side and from above.


FIG. 8 is a perspective view, looking down from the front and one side of another modified form of armchair also embodying my new design.

FIG. 9 is a perspective view of the armchair of FIG. 8, looking down from the rear and one side.

FIG. 10 is a bottom view of the armchair of FIGS. 8 and 9.

The design is characterized by the combination of the specific curvature of the short tubular arm rest members in combination with the front legs which are spaced inwardly of the rear legs, said front legs being formed of a singular tubular member which is continuous with the side and rear rails of the seat, all as best illustrated in FIGS. 2 and 4.








FIG. 3




FIG. 4




FIG. 5

FIG.6




FIG.7




FIG.8





FIG.9






FIG. 10