

[54] COMBINED CONDUCTIVITY MONITOR AND CONTROLLER

[75] Inventor: William J. Berry, Jr., Durham, N.C.

[73] Assignee: Darco Water Systems, Inc., Durham, N.C.

[**] Term: 14 Years

[21] Appl. No.: 128,634

[22] Filed: Mar. 10, 1980

[51] Int. Cl. D13-03

[52] U.S. Cl. D13/11; D13/29

[58] Field of Search D13/11, 12, 40, 29, D13/30, 41, 24; 361/52, 56, 57, 118; 337/197, 198; D10/49, 75; 324/439, 444

[56] References Cited

U.S. PATENT DOCUMENTS

- 3,371,302 2/1968 Mas D13/11 X
- 3,452,252 6/1969 Mapham D13/11 X

- 3,535,667 10/1970 Harnish, Jr. et al. 337/197
- 3,634,804 1/1972 Mineo 337/197 X
- 4,075,676 2/1978 Phillips, Jr. 361/56

OTHER PUBLICATIONS

Industrial Instruments Inc. Electrolytic Conductivity Equipment Cat. #27, 1963, p. 17, RGC-11-Conductivity Controller.


Primary Examiner—Susan J. Lucas

[57] CLAIM

The ornamental design for a combined conductivity monitor and controller, as shown.

DESCRIPTION

FIG. 1 is a perspective view of a combined conductivity monitor and controller embodying my design;
 FIG. 2 is a front view thereof;
 FIG. 3 is a side view thereof;
 FIG. 4 is a rear view thereof;
 FIG. 5 is a top view thereof; and
 FIG. 6 is a bottom view thereof.






FIG. 1




FIG. 5




FIG. 2




FIG. 3




FIG. 4




FIG. 6