

[54] COMBINED SPACER AND FOLDABLE LOCK FOR WIRES OR THE LIKE

[75] Inventor: Rudolph E. Muench, Shelby, N.C.

[73] Assignee: Fasco Controls Corporation, Shelby, N.C.

[**] Term: 14 Years

[21] Appl. No.: 305,273

[22] Filed: Sep. 24, 1981

[51] Int. Cl. D8-08

[52] U.S. Cl. D8/356; D8/382; D8/396

[58] Field of Search D8/354, 356, 396, 382; 248/68 R, 71, 73, 74 R, 74.1

[56] References Cited

U.S. PATENT DOCUMENTS

2,650,948	9/1953	Findlay	248/68 R
3,430,904	3/1969	Soltysik	248/73
4,244,544	1/1981	Kornat	248/68 R
4,264,047	4/1981	Nelson	248/74.1
4,295,618	10/1981	Morota et al.	248/73

FOREIGN PATENT DOCUMENTS

1077284	3/1960	Fed. Rep. of Germany	248/71
373083	12/1963	Switzerland	24/339
950228	2/1964	United Kingdom	24/339

Primary Examiner—B. J. Bullock
Attorney, Agent, or Firm—Shlesinger, Fitzsimmons & Shlesinger

[57] CLAIM

The ornamental design for a combined spacer and foldable lock for wires or the like, as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of a combined spacer and foldable lock for wires or the like showing my new design;
FIG. 2 is a front elevational view thereof;
FIG. 3 is a bottom plan view thereof;
FIG. 4 is a rear elevational view thereof;
FIG. 5 is a side elevational view taken from the left of FIG. 1;
FIG. 6 is a front elevational view of a second embodiment of the design of FIG. 1, the only difference being the omission of the groove in the downwardly projecting lug.




FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5




FIG. 6