

[54] ANTI-SEASICKNESS BELT DEVICE

[76] Inventors: Leo J. Burby, 2851 E. Overlook Rd., Cleveland, Ohio 44118; Henry P. Evans, 17618 Walnut Trail, Chagrin Falls, Ohio 44022

[**] Term: 14 Years

[21] Appl. No.: 321,637

[22] Filed: Nov. 16, 1981

[52] U.S. Cl. D24/99; D2/380

[58] Field of Search 128/384, DIG. 15, 385, 128/381; D2/1, 380, 381; D24/34, 99, 36

[56] References Cited

U.S. PATENT DOCUMENTS

D. 263,869	4/1982	Sumiyasu	D24/99
D. 265,422	7/1982	Howe	D24/99 X
2,479,803	8/1949	Zetterlund	128/384 X
3,075,517	1/1963	Morehead	128/384 X
3,247,842	4/1966	Spasi/	128/384 X
3,407,818	10/1968	Costanzo	128/384
3,797,483	3/1974	Feldman	128/DIG. 15 X

FOREIGN PATENT DOCUMENTS

2834 of 1885 United Kingdom 128/384

Primary Examiner—Bernard Ansher
Attorney, Agent, or Firm—Baldwin, Egan, Walling & Fetzer

[57] CLAIM

The ornamental design for an anti-seasickness belt device, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of an anti-seasickness belt device showing our new design; FIG. 2 is an enlarged, front elevation thereof, with the strap members broken away to indicate indeterminate length; FIG. 3 is a top plan view thereof; FIG. 4 is an end elevation thereof; FIG. 5 is a rear elevation thereof; and FIG. 6 is a front elevation thereof with the straps omitted for clarity of illustration. The broken lines are shown for illustrative purposes only.





