United States Patent [19]

McCain

[11] **Patent Number: Des. 274,521**

[45] **Date of Patent: ** Jul. 3, 1984**

[54] **CATHODE RAY TUBE DISPLAY HOUSING FOR ELECTRONIC INSTRUMENTS**

[75] Inventor: **George L. McCain,** Seattle, Wash.

[73] Assignee: **John Fluke Mfg. Co., Inc.,** Everett, Wash.

[**] Term: **14 Years**

[21] Appl. No.: **373,008**

[22] Filed: **Apr. 29, 1982**

[52] **U.S. Cl.** **D14/113**

[58] **Field of Search** ..... D13/12, 13, 35, 38, D13/40, 41; 361/331, 332, 334, 335, 336, 337, 338, 374, 380.4, 389, 390.4, 399; 74/50 R, 51, 52 R; D14/113

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 212,950	12/1968	GruyéD13	40/
D. 266,762	11/1982	Gibson	D14/113
4,120,545	10/1978	Happak et al.	174/50

OTHER PUBLICATIONS

Thermotron–Automatic Control Systems 3038 Microcomputer Programmer–Controller, 2–14–80, Housings Box II.

Primary Examiner—Wallace R. Burke
Assistant Examiner—Lynn Wilder
Attorney, Agent, or Firm—Orland M. Christensen; Mikio Ishimaru

[57] **CLAIM**

The ornamental design for cathode ray tube display housing for electronic instruments, as shown and described.

DESCRIPTION

FIG. **1** is a front perspective view of a cathode ray tube display housing for electronic instruments showing my new design;
FIG. **2** is a front elevational view thereof;
FIG. **3** is a left side elevational view thereof, the right side being a mirror image;
FIG. **4** is a bottom plan view thereof; and
FIG. **5** is a rear elevational view thereof.
The broken line disclosure shown in FIG. **5** is for illustrative purposes only and forms no part of the claimed design.



Fig. 1.



Fig. 2.





Fig. 3.



Fig. 4.



Fig. 5.