

[54] DEVICE FOR SECURING LOAD TIE DOWN ROPES

[76] Inventor: James F. Kimball, 83617 Rattlesnake Rd., Dexter, Oreg. 97431

[**] Term: 14 Years

[21] Appl. No.: 395,148

[22] Filed: Jul. 6, 1982

[52] U.S. Cl. D8/356

[58] Field of Search D8/356, 44; 24/131, 24/128, 129 B; 248/499

[56] References Cited

U.S. PATENT DOCUMENTS

D. 180,332	5/1957	Jackson	D8/358
D. 197,065	12/1963	Nilsson	D8/356
D. 221,511	8/1971	Dufault	D8/358
278,097	5/1883	Collins	24/129 B
656,431	8/1900	Stewart	24/129 B
1,383,665	7/1921	Rohan	24/129 B
1,852,887	4/1930	Lossius	24/129 B
2,229,935	1/1941	Powers	D8/44

2,418,885	4/1947	Houston	24/129 B
2,466,083	4/1949	Crosby	24/129 B
4,092,075	5/1978	Kimball	24/129 B

FOREIGN PATENT DOCUMENTS

36527	11/1885	Fed. Rep. of Germany	24/129 B
375245	6/1973	U.S.S.R.	24/129 B


Primary Examiner—Wallace R. Burke
Assistant Examiner—Horace B. Fay
Attorney, Agent, or Firm—James D. Givnan, Jr.

[57] CLAIM

The ornamental design for a device for securing load tie down ropes, as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of the device for securing load tie down ropes showing my new design; FIG. 2 is a front elevational view of FIG. 1; and FIG. 3 is an end elevational view taken from the right side of FIG. 2. A bottom plan view of the device would be a mirror image of FIG. 1. An end elevational view taken from the left side of FIG. 2 would be identical to FIG. 3.






Fig 1



Fig 2




Fig 3