

[54] COMBINED TOTE BAG AND BACK REST

[76] Inventor: Kathleen Y. Spiegelman, 3627 Serra Rd., Malibu, Calif. 90265

[**] Term: 14 Years

[21] Appl. No.: 347,019

[22] Filed: Feb. 8, 1982

[52] U.S. Cl. D3/43; D3/48; D3/77

[58] Field of Search D3/30.1, 43, 44, 48, D3/76, 77; 190/8, 2; 297/377, 118; 5/431

[56] References Cited

U.S. PATENT DOCUMENTS

D. 226,637	4/1973	Rauch	D3/48
D. 254,157	2/1980	Delavin	D3/77
3,822,424	7/1974	Messer	297/377
4,154,323	5/1979	Sneider	190/2
4,194,601	3/1980	Yellin	D3/43
4,273,221	6/1981	Doag	190/8

Primary Examiner—George P. Word
Attorney, Agent, or Firm—Robert B. Block


[57] CLAIM

The ornamental designs for a combined tote bag and back rest, as shown as described.

DESCRIPTION

FIG. 1 is a front elevational view of a combined tote bag and back rest showing my new design;
FIG. 2 is a right side elevational view thereof;
FIG. 3 is a left side elevational view thereof;
FIG. 4 is a top plan view thereof;
FIG. 5 is a rear elevational view thereof;
FIG. 6 is a bottom plan view thereof;

FIG. 7 is a top plan view thereof in the opened condition;
FIG. 8 is a front perspective view of FIG. 1 with the bottom panel unrolled and in the back rest configuration, an intermediate portion of the panel being broken away and omitted for convenience of illustration;
FIG. 9 is a front elevational view of a second embodiment of the combined tote bag and back rest;
FIG. 10 is a right side elevational view thereof;
FIG. 11 is a left side elevational view thereof;
FIG. 12 is a top plan view thereof;
FIG. 13 is a rear elevational view thereof;
FIG. 14 is a bottom plan view thereof;
FIG. 15 is a top plan view thereof in the opened condition;
FIG. 16 is a front perspective view of FIG. 9 with the bottom panel unrolled and in the back rest configuration, an intermediate portion of the panel being broken away and omitted for convenience of illustration;
FIG. 17 is a rear elevational view of a third embodiment of the combined tote bag and back rest;
FIG. 18 is a side elevational view thereof, the opposite side being a mirror image;
FIG. 19 is a front perspective view thereof in the closed condition with the bottom panel unrolled and in the back rest configuration, a portion of the panel being broken away and omitted for convenience of illustration;
FIG. 20 is a side elevational view of FIG. 16 in the open condition;
FIG. 21 is an enlarged scale fragmentary cross-sectional view of the handle fastening of the embodiment of FIGS. 1 through 8;
FIG. 22 is an enlarged scale fragmentary cross-sectional view of the handle fastening of the embodiment of FIGS. 9 through 16 and 20; and
FIG. 23 is an enlarged scale fragmentary cross-sectional view of the handle fastening of the embodiment of FIGS. 17 through 19.






Fig. 1




Fig. 2



Fig. 3




Fig. 6

Fig. 5





Fig. 8

Fig. 4





Fig. 7






FIG. 9

FIG. 10




FIG. 11




FIG. 13




FIG. 14




FIG. 12




FIG. 16





FIG. 15






Fig. 17




Fig. 18




Fig. 20




Fig. 19




Fig. 21




Fig. 22




Fig. 23