United States Patent [19]

Mori

[11] Patent Number: Des. 276,479
[45] Date of Patent: ** Nov. 27, 1984

	[54]	COMBINE	ED KEY HOLDER AND WRITING ENT
	[76]	Inventor:	Gian L. Mori, Via Andorno 5, Torino, Italy
	[**]	Term:	14 Years
	[21]	Appl. No.:	398,786
	[22]	Filed:	Jul. 16, 1982
	[30] Foreign Application Priority Data		
	Jan [52] [58]	U.S. Cl Field of Sea	T] Italy
	[56] References Cited		
U.S. PATENT DOCUMENTS			
	D D	. 139,904 1/3 . 207,563 5/3 . 247,395 2/3	1934 Harris

Hong Kong Enterprise 3/81, p. 347, "key ring" bottom left.

Eberhard Faber Cat. 1907, p. 31, Item No. 1544.

Primary Examiner—George P. Word Attorney, Agent, or Firm—Young & Thompson

[57] CLAIM

The ornamental design for a combined key holder and writing instrument, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a combined key holder and writing instrument, showing my new design;

FIG. 2 is a plan view thereof;

FIG. 3 is a side elevational view thereof;

FIG. 4 is a plan view thereof from the side opposite that shown in FIG. 2;

FIG. 5 is a side elevational view thereof from the side opposite that shown in FIG. 3;

FIG. 6 is a left end elevational view of FIG. 3;

FIG. 7 is a right end elevational view of FIG. 3;

FIG. 8 is an exploded perspective view thereof with the key holder separated from the writing instrument;

FIG. 9 is a side elevational view of the writing instrument;

FIG. 10 is a plan view of the writing instrument from the side opposite that shown in FIG. 8;


FIG. 11 is a side elevational view of the writing instrument from the side opposite that shown in FIG. 9;


FIG. 12 is a left end elevational view of FIG. 11;


FIG. 13 is a right end elevational view of FIG. 11;

FIG. 14 is an exploded perspective view similar to FIG. 8 but with the writing instrument turned in the opposite direction; and

FIG. 15 is a view similar to FIG. 1 but with the writing instrument inserted into the key holder in the writing position, that is, turned 180° from the position it occupies in FIG. 1.







U.S. Patent Nov. 27, 1984 Sheet 2 of 3 Des. 276,479

