

[54] COMBINED BATTERY CHARGER, POWER SUPPLY AND BATTERY TESTER

[75] Inventor: Joseph W. K. Ip, Kowloon, Hong Kong

[73] Assignee: Vanson Electronics Limited, Kowloon, Hong Kong

[**] Term: 14 Years

[21] Appl. No.: 413,438

[22] Filed: Aug. 31, 1982

[30] Foreign Application Priority Data

Jun. 3, 1982 [GB] United Kingdom 1007086

[52] U.S. Cl. D13/5; D10/77

[58] Field of Search D13/5, 8; D10/77; 320/2-5

[56] References Cited

U.S. PATENT DOCUMENTS

D. 97,286 10/1935 Heyer D13/5

D. 179,032 10/1956 Peth D10/77
D. 180,475 6/1957 Dickinson D10/77
D. 207,010 2/1967 Raymond D13/5
D. 273,580 4/1984 Riumbau D13/5


Primary Examiner—A. Hugo Word
Assistant Examiner—Lynn Wilder
Attorney, Agent, or Firm—Wenderoth, Lind & Ponack

[57] CLAIM

The ornamental design for combined battery charger, power supply and battery tester, substantially as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of the combined battery charger, power supply and battery tester from above showing my new design;
FIG. 2 is a rear perspective view thereof from below;
FIG. 3 is a top plan view thereof with the lid removed;
FIG. 4 is a cross-sectional view thereof taken on the line 4—4 in FIG. 3, and
FIG. 5 is a cross-sectional view thereof taken on the line 5—5 of FIG. 3.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5