United States Patent [19]

Mathiasen

[11] Patent Number: Des. 278,625

[45] Date of Patent: ** Apr. 30, 1985

[54] MICROPHONE

[75] Inventor: Hilmer Mathiasen, Holte, Denmark

[73] Assignee: Bruel & Kjaer A/S, Naerum,

Denmark

[**] Term: 14 Years

[21] Appl. No.: 456,435

[22] Filed: Jan. 7, 1983

[30] Foreign Application Priority Data

| Jul | . 12, 1982 [DK] | Denmark 667 |
|------|-----------------|------------------------|
| Jul | 12, 1982 [DK] | Denmark 668 |
| [52] | U.S. Cl | |
| | | D14/12; 179/121 D, 179 |

[56] References Cited

U.S. PATENT DOCUMENTS

| D. 173,367 | 11/1954 | McVay | D14/12 |
|------------|---------|------------|-----------|
| | | | D14/12 |
| 3.201.530 | 8/1965 | Levv et al | 179/121 D |

OTHER PUBLICATIONS

Nakamichi Peripheral Equipment Cat. #0-804200A & OD0366OA, p. 4, CM-700 Microphone. Radio Shack '82 Cat. #341, p. 50, Omni Mike, #33-1050.

Primary Examiner—Jane E. Corrigan
Attorney, Agent, or Firm—Cushman, Darby & Cushman

[57] CLAIM

The ornamental design for a microphone, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a microphone showing my new design;

FIG. 2 is a side elevational view thereof;

FIG. 3 is a front elevational view thereof;

FIG. 4 is a rear elevational view thereof;

FIG. 5 is a view like FIG. 1 of a second embodiment of the microphone, wherein a distinct ring at the rear of the cylindrical housing is included;

FIG. 6 is a side elevational view thereof;

FIG. 7 is a view like FIG. 3 thereof;

FIG. 8 is a rear elevational view thereof;

FIG. 9 is a view like FIG. 1 of a third embodiment of the microphone, wherein the front center small circular opening is omitted;

FIG. 10 is a side elevational view thereof;

FIG. 11 is a front elevational view thereof;

FIG. 12 is a view like FIG. 4 thereof;

FIG. 13 is a view like FIG. 1 of a fourth embodiment of the microphone, wherein a distinct ring at the rear of the cylindrical housing is included and the front center small circular opening is omitted;

FIG. 14 is a side elevational view thereof;

FIG. 15 is a view like FIG. 11 thereof;

FIG. 16 is a view like FIG. 8 thereof;

FIG. 17 is a view like FIG. 1 of a fifth embodiment of the microphone, wherein the front is of lesser diameter and the tapered portion is accordingly more pronounced;

FIG. 18 is a side elevational view thereof;

FIG. 19 is a front elevational view thereof;


FIG. 20 is a view like FIG. 4 thereof;


FIG. 21 is a view like FIG. 1 of a sixth embodiment of the microphone, wherein a distinct ring has been added at the rear of the fifth embodiment housing;


FIG. 22 is a side elevational view thereof;


FIG. 23 is a view like FIG. 19 thereof; and

FIG. 24 is a view like FIG. 8 thereof.











U.S. Patent Apr. 30, 1985 Sheet 4 of 6 Des. 278,625





U.S. Patent Apr. 30, 1985 Sheet 6 of 6 Des. 278,625

