

[54] **PULSE TRANSMITTER**
 [75] **Inventor: Seppo J. Saynajakangas, Kempele, Finland**
 [73] **Assignee: Polar Electro Ky, Oulu, Finland**
 [**] **Term: 14 Years**
 [21] **Appl. No.: 444,533**
 [22] **Filed: Nov. 26, 1982**
 [30] **Foreign Application Priority Data**
 Sep. 10, 1982 [FI] Finland 805/82
 [52] **U.S. Cl. D24/17; D10/31; D24/21**
 [58] **Field of Search D24/17; D10/31, 32, D10/38, 39; 368/276, 281, 309, 69, 70, 224, 110, 111, 113; 128/690, 687, 689, 691**

[56] **References Cited**
U.S. PATENT DOCUMENTS
 D. 237,748 11/1975 Sarnoff et al. D24/17
 D. 269,546 6/1983 Rogers et al. D24/17
 1,431,802 10/1922 Horvath 368/276
 3,572,316 3/1971 Vogelmann et al. 128/690

3,968,640 7/1976 Clemmer et al. 368/69
 4,409,983 10/1983 Albert 128/689
 4,450,843 5/1984 Barney et al. 128/690

FOREIGN PATENT DOCUMENTS

2910302 9/1980 Fed. Rep. of Germany 128/690
 2928154 1/1981 Fed. Rep. of Germany 128/690
 1370661 7/1964 France 128/690
 2298820 9/1976 France 368/70


Primary Examiner—A. Hugo Word
Assistant Examiner—R. C. Anderson
Attorney, Agent, or Firm—Martin Smolowitz

[57] **CLAIM**

The ornamental design for a pulse transmitter, as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of a pulse transmitter showing my new design;
 FIG. 2 is a side elevational view thereof;
 FIG. 3 is a bottom view thereof;
 FIG. 4 is a side elevational view showing the side opposite that shown in FIG. 2;
 FIG. 5 is a right end view thereof; and
 FIG. 6 is a left end view thereof.






Fig. 1

Fig. 2





Fig. 3




Fig. 4

Fig. 5




Fig. 6

