

[54] THROTTLE POSITION SENSOR

4,503,417 3/1985 Bleeke et al. 338/184

[75] Inventors: Donald A. Overcash, San Juan Capistrano; Lloyd E. Hall, Fullerton; Guenter W. Mueller, Santa Ana, all of Calif.

[73] Assignee: Duncan Electronics, Costa Mesa, Calif.

[**] Term: 14 Years

[21] Appl. No.: 491,074

[22] Filed: May 3, 1983

[52] U.S. Cl. D15/5

[58] Field of Search D15/5; 73/118; 338/128, 338/162, 174.6, 184

[56] References Cited

U.S. PATENT DOCUMENTS

2,809,516	10/1957	Brush	73/118
2,839,642	6/1958	Dickinson et al.	338/184
3,111,640	11/1963	Dial	338/160
3,518,604	6/1970	Beaver et al.	338/184
3,640,128	2/1972	Cunning et al.	73/118
3,905,097	9/1975	Beetle	338/128
3,909,769	9/1975	Rozema et al.	338/48
4,355,293	10/1982	Driscoll	538/184
4,411,154	10/1983	Kitamura et al.	73/118
4,429,297	1/1984	Nakatso	338/184

OTHER PUBLICATIONS

Halley Throttle Position Sensor Brochure-copyright '82.

Primary Examiner—Wallace R. Burke

Assistant Examiner—Lynn Wilder

Attorney, Agent, or Firm—Knobbe, Martens, Olson & Bear

[57] CLAIM

The ornamental design for a throttle position sensor, substantially as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a first embodiment of a throttle position sensor showing my new design; FIG. 2 is a reduced side elevation view thereof; FIG. 3 is a reduced front elevation view thereof; FIG. 4 is a reduced rear elevational view thereof; FIG. 5 is a top plan view thereof; FIG. 6 is a rear perspective view thereof; FIG. 7 is a rear perspective view of a second embodiment of a throttle position sensor showing my design; FIG. 8 is a side elevational view thereof; FIG. 9 is a front perspective view of a third embodiment of a throttle position sensor showing my new design; and FIG. 10 is a reduced side elevational view thereof.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 10



UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : Des. 281,323
DATED : November 12, 1985
INVENTOR(S) : Overcash, et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the front page of the Patent, Column 1, line 22, after Driscoll, delete "538/184" and insert --338/184-- in its place. In Column 2, line 3, delete "Halley" and insert --Holley-- in its place.

Signed and Sealed this
Nineteenth Day of August 1986

[SEAL]

Attest:

Attesting Officer

DONALD J. QUIGG

Commissioner of Patents and Trademarks