

[54] **RESILIENT RING FOR FLUID COUPLING**

[75] **Inventor: Robert W. Gilbert, Adelaide, Australia**  
 [73] **Assignee: Mining Supplies (Minsup) Pty. Ltd., Edwardstown, Australia**  
 [\*\*] **Term: 14 Years**  
 [21] **Appl. No.: 334,730**  
 [22] **Filed: Dec. 28, 1981**

[30] **Foreign Application Priority Data**

Aug. 7, 1981 [AU] Australia ..... 84842  
 [52] **U.S. Cl. .... D23/47**  
 [58] **Field of Search ..... D23/47; 277/92, 167.5, 277/188 A, 188 R, 212 C, 212 R**

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

D. 44,533 5/1977 Eidelberg et al. .... D23/47  
 2,330,197 9/1943 Allen et al. .... 277/188 A X  
 3,392,984 7/1968 Reinsma et al. .... 277/92 X

3,446,507 5/1969 Ulies ..... 277/92  
 3,595,572 7/1970 Granda ..... 277/92  
 3,719,366 3/1973 Pippert ..... 277/188 A X  
 3,970,321 7/1976 Dechavanno ..... 277/188 A  
 4,143,586 3/1979 Zitting ..... 277/188 A



*Primary Examiner*—James R. Largen  
*Attorney, Agent, or Firm*—Robert E. Burns; Emmanuel J. Lobato; Bruce L. Adams


[57] **CLAIM**

The ornamental design for a resilient ring for fluid coupling, substantially as shown and described.


**DESCRIPTION**

FIG. 1 is a side elevational view of a resilient ring for fluid coupling showing my new design;  
 FIG. 2 is a cross-sectional view thereof taken on line 2—2 of FIG. 3;  
 FIG. 3 is a top plan view thereof; and  
 FIG. 4 is a bottom plan view thereof.  
 The design is characterized by two concentric tapered portions having different degrees of taper and which are axially separated by a concentric cylindrical portion.







*FIG. 1*



*FIG. 2*



*FIG. 3*



*FIG. 4*