

[54] DEVICE FOR MAINTAINING A GASOLINE
PUMP NOZZLE IN THE OPEN POSITION

[76] Inventor: Milton Scanlon, 5058 Lexington
Blvd., Fort Meyers, Fla. 33907

[**] Term: 14 Years

[21] Appl. No.: 559,021

[22] Filed: Dec. 7, 1983

[52] U.S. Cl. D8/349; D8/354

[58] Field of Search D8/349, 354; 74/526;
141/392; 251/90; D3/62

[56] References Cited

U.S. PATENT DOCUMENTS

D. 254,050	1/1980	Fitzgerald		D8/349
D. 255,321	6/1980	Stelman		D8/354
D. 258,114	2/1981	Maynor, Jr.		D8/354
4,175,595	11/1979	Noe		D8/354
4,200,128	4/1980	Pokrzywa		251/90
4,201,253	5/1980	Maloney		141/392

4,216,807 8/1980 Diamond 74/526

Primary Examiner—B. J. Bullock
Attorney, Agent, or Firm—Lockwood, Alex, Fitzgibbon
& Cummings

[57] CLAIM

The ornamental design for a device for maintaining a gasoline pump nozzle in the open position, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a device for maintaining a gasoline pump nozzle in the open position showing my new design;
FIG. 2 is a right side elevational view thereof;
FIG. 3 is a left side elevational view thereof;
FIG. 4 is a bottom plan view thereof;
FIG. 5 is a top plan view thereof;
FIG. 6 is a front elevational view thereof;
FIG. 7 is a rear elevational view thereof.
The chain which is shown in FIG. 1 has been omitted from FIGS. 2-7 for ease of illustration.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

