

[54] **COMBINED RECONFIGURABLE TOY
VEHICULAR AND SIMULATIVE MOTOR
UNITS**

[75] Inventor: Hiroyuki Obara, Tokyo, Japan

[73] Assignee: Takara Co., Ltd., Tokyo, Japan

[**] Term: 14 Years

[21] Appl. No.: 616,421

[22] Filed: May 30, 1984

[30] **Foreign Application Priority Data**

Mar. 21, 1984 [JP] Japan 59-10888

[52] U.S. Cl. D21/136; D21/128;
D21/150; D21/166

[58] Field of Search D21/128-140,
D21/166, 177; 446/71, 72, 73, 74, 75, 77, 78;
D12/90

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 246,126 10/1977 Ogawa D21/150
D. 274,165 6/1984 Duennes D21/134
D. 275,122 8/1984 Murakami D21/150
D. 279,017 5/1985 Boudreaux D21/128
D. 279,307 6/1985 Murakami D21/136
D. 279,916 7/1985 Obara D21/136
D. 281,087 10/1985 Ohno D21/136

Primary Examiner—Charles A. Rademaker

Attorney, Agent, or Firm—Price, Gess & Ubell

[57] **CLAIM**

The ornamental design for a combined reconfigurable toy vehicular and simulative motor units, substantially as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a reconfigurable

toy vehicular and simulative motor units showing my new design in a vehicular condition;

FIG. 2 is a rear elevational view thereof;

FIG. 3 is a top plan view thereof;

FIG. 4 is a top plan view thereof;

FIG. 5 is a bottom plan view thereof;

FIG. 6 is a front elevational view thereof reconfigured with the motor units;

FIG. 7 is a rear elevational view thereof;

FIG. 8 is a side elevational view thereof;

FIG. 9 is a top plan view thereof;

FIG. 10 is a bottom plan view thereof;

FIG. 11 is a front elevational view of the design shown in FIGS. 1 through 5 reconfigured in a humanoid condition;

FIG. 12 is a rear elevational view thereof;

FIG. 13 is a right side elevational view thereof;

FIG. 14 is a left side elevational view thereof;

FIG. 15 is a top plan view thereof;

FIG. 16 is a bottom plan view thereof;

FIG. 17 is a side perspective view thereof showing the design in a transitory condition;

FIG. 18 is another side perspective view thereof showing the design in a transitory condition;

FIG. 19 is another side perspective view thereof showing the design in a transitory condition;

FIG. 20 is another side perspective view thereof showing the design in a transitory condition;

FIG. 21 is a perspective view of the design shown in FIGS. 1 through 5 in a vehicular condition;

FIG. 22 is another perspective view thereof reconfigured with the motor units;

FIG. 23 is a front perspective view of the design shown in FIGS. 1 through 5 in a humanoid configuration; and,

FIG. 24 is another front perspective view thereof with the motor units.




FIG.1




FIG.2




FIG.3




FIG.5




FIG.4




FIG.6




FIG.7





FIG.8






FIG.9




FIG.10

FIG.11





FIG.12






FIG.13




FIG.14

FIG.15




FIG.16




FIG.17




FIG.18




FIG.19




FIG.20




FIG. 21




FIG. 22




FIG. 23




FIG. 24

