

[54] COMBINATION PULLEY AND WEIGHT ANCHOR DEVICE

[76] Inventors: Richard F. Hahn, 1428 Gentian Dr., S.E., Kentwood, Mich. 49508; John P. Soby, 7730 Leonard, N.E., Ada, Mich. 49301

[**] Term: 14 Years

[21] Appl. No.: 684,255

[22] Filed: Dec. 20, 1984

[52] U.S. Cl. D8/360; 114/294; D12/215; D8/356

[58] Field of Search D8/360; 114/294, 293, 114/300, 29, 206; D12/215; 89/30; 16/1 R; 280/187; 24/136 R; 43/44.91

[56] References Cited

U.S. PATENT DOCUMENTS

1,418	11/1839	Evarts	89/30
D. 136,547	10/1943	Cohen	D8/360
D. 191,726	11/1961	Divietro	D12/215
203,569	5/1878	Van Kannel	16/1 R
D. 260,963	9/1981	Merry	D8/360
D. 280,316	8/1985	Gooden	D12/215
704,730	7/1902	Zierleyn	280/187
1,321,356	11/1919	Bateman	114/356
1,493,489	5/1924	Holzappel	D12/215
1,771,406	7/1930	Fountain	114/29
2,023,526	12/1935	Hoberg	114/300
2,315,513	4/1943	Fitzgerald	114/294
3,055,332	9/1962	Linsdeau	114/206
3,187,705	6/1965	Costello et al.	114/294
3,431,879	3/1969	Westling	114/294
3,754,524	8/1973	Locks	114/294
4,090,463	5/1978	Söderberg	114/294

OTHER PUBLICATIONS

"The Technique of Anchoring" by Alex W. Moffat, Yachting Magazine, August, 1962, pp. 42, 43 and 88.
"A Sentinel Keeps Watch" by Lee Tolman from Cruising World Magazine, Sept., 1983.



Primary Examiner—Wallace R. Burke
Assistant Examiner—Horace B. Fay
Attorney, Agent, or Firm—Price, Heneveld, Huizenga & Cooper

[57] CLAIM

The ornamental design for combination pulley and weight anchor device, substantially as shown and described.

DESCRIPTION

FIG. 1 is a front, partial top and a side perspective view of a combination pulley and weight anchor device showing our new invention;
FIG. 2 is a side elevation thereof;
FIG. 3 is a front elevation thereof;
FIG. 4 is a rear elevation thereof;
FIG. 5 is a top plan view thereof;
FIG. 6 is a sectional view thereof taken along plane VI—VI of FIG. 2;
FIG. 7 is a front, partial top and a side perspective view of a second embodiment thereof;
FIG. 8 is a side elevation thereof;
FIG. 9 is a front elevation thereof, the rear elevation being substantially identical to that of FIG. 4;
FIG. 10 is a top plan view thereof;
FIG. 11 is a sectional view thereof taken along plane XI—XI of FIG. 9;
FIG. 12 is a sectional view thereof taken along plane XII—XII of FIG. 9;
FIG. 13 is a front, partial top and a side perspective view of a third embodiment thereof;
FIG. 14 is a side elevation thereof;
FIG. 15 is a fragmentary, front perspective view of the lower half thereof;
FIG. 16 is a rear elevation thereof;
FIG. 17 is a front, partial top and a side perspective view of a fourth embodiment thereof;
FIG. 18 is a side elevation thereof; and
FIG. 19 is a fragmentary, front elevation thereof, the rear elevation being substantially identical to that of FIG. 16.






Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.




Fig. 7.




Fig. 8.




Fig. 11.




Fig. 12.




Fig. 13.




Fig. 9.




Fig. 10.




Fig. 14.




Fig. 16.




Fig. 17.




Fig. 18.




Fig. 15.




Fig. 19.